



Date: October 10, 2023

Quotation for City of Oregon City

Quote No: 8082074-00

Prepared For: Dan Hepler

Quote No: 8082074-00

City of Oregon City
PO Box 3040
122 South Center
Oregon City, OR 97045

iQuote No: 143498

Sales Person: Aaron Semm
aaron.semm@turfstar.com
(971) 291-9959

This quote is priced on Sourcewell using Toro contract number 031121-TTC

Summary

| Configuration Name | Qty | Unit Price | Sub Total | Sales Tax | Total |
|--------------------------------------|-----|-------------|--------------------|---------------|--------------------|
| #881 010-Groundsmaster 3200 24HP AWD | 1 | \$28,451.24 | \$28,451.24 | \$0.00 | \$28,451.24 |
| #787 020-Groundsmaster 3200 24HP AWD | 1 | \$28,451.24 | \$28,451.24 | \$0.00 | \$28,451.24 |
| #788 030-Groundsmaster 3200 24HP AWD | 1 | \$27,072.24 | \$27,072.24 | \$0.00 | \$27,072.24 |
| Totals: | | | \$83,974.72 | \$0.00 | \$83,974.72 |



Date: October 10, 2023

Quotation for City of Oregon City

Quote No:8082074-00

Configuration Product Details 010-Groundsmaster 3200 24HP AWD

| Model | Product Description | Qty | Unit Price | Extended | Sales Tax | Total |
|----------------|--------------------------------------|-----|-------------|--------------|-----------|--------------------|
| 31901 | Groundsmaster 3200 24HP AWD | 1 | \$22,232.34 | \$22,232.34 | \$0.00 | \$22,232.34 |
| 31971 | 60in Rear Discharge Deck GM3200/33xx | 1 | \$4,308.72 | \$4,308.72 | \$0.00 | \$4,308.72 |
| 110-4703-03 | BLADE-ROTARY, ATOMIC (20 .5) | 3 | \$30.90 | \$92.70 | \$0.00 | \$92.70 |
| 31982 | Seat Asm Air Ride Susp | 1 | \$1,230.84 | \$1,230.84 | \$0.00 | \$1,230.84 |
| 30671 | Universal Sunshade Red | 1 | \$805.74 | \$805.74 | \$0.00 | \$805.74 |
| 117-0095 | SEAT COVER W/ARM REST - Z MASTERS | 1 | \$47.57 | \$47.57 | \$0.00 | \$47.57 |
| 114-4096 | WEIGHT | 1 | \$125.33 | \$125.33 | \$0.00 | \$125.33 |
| FSD1 | Setup | 1 | \$554.00 | \$554.00 | \$0.00 | \$554.00 |
| FSD2 | Delivery | 1 | \$554.00 | \$554.00 | \$0.00 | \$554.00 |
| TRADE-IN | Trade-In Allowance | -1 | \$1,500.00 | (\$1,500.00) | \$0.00 | (\$1,500.00) |
| Totals: | | | | | | \$28,451.24 |



Date: October 10, 2023

Quotation for City of Oregon City

Quote No:8082074-00

Configuration Product Details 020-Groundsmaster 3200 24HP AWD

| Model | Product Description | Qty | Unit Price | Extended | Sales Tax | Total |
|----------------|--------------------------------------|-----|-------------|--------------|-----------|--------------------|
| 31901 | Groundsmaster 3200 24HP AWD | 1 | \$22,232.34 | \$22,232.34 | \$0.00 | \$22,232.34 |
| 31971 | 60in Rear Discharge Deck GM3200/33xx | 1 | \$4,308.72 | \$4,308.72 | \$0.00 | \$4,308.72 |
| 110-4703-03 | BLADE-ROTARY, ATOMIC (20 .5) | 3 | \$30.90 | \$92.70 | \$0.00 | \$92.70 |
| 31982 | Seat Asm Air Ride Susp | 1 | \$1,230.84 | \$1,230.84 | \$0.00 | \$1,230.84 |
| 30671 | Universal Sunshade Red | 1 | \$805.74 | \$805.74 | \$0.00 | \$805.74 |
| 117-0095 | SEAT COVER W/ARM REST - Z MASTERS | 1 | \$47.57 | \$47.57 | \$0.00 | \$47.57 |
| 114-4096 | WEIGHT | 1 | \$125.33 | \$125.33 | \$0.00 | \$125.33 |
| FSD1 | Setup | 1 | \$554.00 | \$554.00 | \$0.00 | \$554.00 |
| FSD2 | Delivery | 1 | \$554.00 | \$554.00 | \$0.00 | \$554.00 |
| TRADE-IN | Trade-In Allowance | -1 | \$1,500.00 | (\$1,500.00) | \$0.00 | (\$1,500.00) |
| Totals: | | | | | | \$28,451.24 |



Date: October 10, 2023

Quotation for City of Oregon City

Quote No:8082074-00

Configuration Product Details 030-Groundsmaster 3200 24HP AWD

| Model | Product Description | Qty | Unit Price | Extended | Sales Tax | Total |
|----------------|------------------------------------|-----|-------------|--------------|-----------|--------------------|
| 31901 | Groundsmaster 3200 24HP AWD | 1 | \$22,232.34 | \$22,232.34 | \$0.00 | \$22,232.34 |
| 31973 | 72in Rear Discharge Deck GM32/33xx | 1 | \$4,425.72 | \$4,425.72 | \$0.00 | \$4,425.72 |
| 110-0624-03 | BLADE-ROTARY, ATOMIC .5) | 3 | \$30.90 | \$92.70 | \$0.00 | \$92.70 |
| 31982 | Seat Asm Air Ride Susp | 1 | \$1,230.84 | \$1,230.84 | \$0.00 | \$1,230.84 |
| 30671 | Universal Sunshade Red | 1 | \$805.74 | \$805.74 | \$0.00 | \$805.74 |
| 117-0095 | SEAT COVER W/ARM REST - Z MASTERS | 1 | \$47.57 | \$47.57 | \$0.00 | \$47.57 |
| 114-4096 | WEIGHT | 1 | \$125.33 | \$125.33 | \$0.00 | \$125.33 |
| FSD1 | Setup | 1 | \$556.00 | \$556.00 | \$0.00 | \$556.00 |
| FSD2 | Delivery | 1 | \$556.00 | \$556.00 | \$0.00 | \$556.00 |
| TRADE-IN | Trade-In Allowance | -1 | \$2,500.00 | (\$2,500.00) | \$0.00 | (\$2,500.00) |
| TRADE-IN | Trade-In Allowance | -1 | \$500.00 | (\$500.00) | \$0.00 | (\$500.00) |
| Totals: | | | | | | \$27,072.24 |



Date: October 10, 2023

Quotation for City of Oregon City

Quote No:8082074-00

Standard Terms and Conditions

Prices including all finance options are subject to change based on Turf Star Western's receipt of product and estimated shipments. Currently, product availability is a minimum of 6-18 months. Your Final Price will be determined at time of shipment. Delivery is FOB point of origin unless otherwise stated.

Office Locations

Northern California:

3928 N.Blaetela Lane
Fresno, CA 93727
Fax: (559) 277-7123

2438 Radley Court
Hayward, CA 94545
Fax: (510) 785-3576

11373 Sunrise Gold Circle
Rancho Cordova, CA 95742
Fax: (800) 241-1997

Southern California:

79-253 Country Club Drive
Bermuda Dunes, CA 92203
Fax: (760) 345-4297

955 Beacon Street
Brea, CA 92821
Fax: (800) 775-8873

2110 La Mirada Ste 100
Vista, CA 92083
Fax: (760) 734-4285

Pacific Northwest:

1750 Industrial Dr.NE
Salem, OR 97301
Ph: (503) 691-0250

5869 South 194th
Kent, WA 98032
Fax: (253) 872-6942

2824 East Garland
Spokane, WA 99207
Fax: (509) 483-7563



WARNING:

Cancer and Reproductive Harm-<http://www.P65Warnings.ca.gov>
For more information, please visit <http://www.ticoCAProp65.com>

CALIFORNIA SPARK ARRESTER WARNING

Operation of this equipment in the State of California may create sparks that can start fires around dry vegetation. A spark arrestor may be required. The operator should contact local fire agencies for laws or regulations relating to fire prevention requirements.

TORO

Groundsmaster® 3200/3300

OUT-FRONT ROTARY MOWERS

FEATURES

Power & Durability

- Powerful 24.7 HP (18.4 kW) or 37.4 HP (27.9 kW) Yanmar® EPA Tier 4/Stage V diesel engines
- Rugged 7-gauge high-strength steel rotary decks Available 60" (152 cm) or 72" (183 cm) width of cut. Side and rear discharge options.

Performance

- CrossTrax® all-wheel drive provides superior traction
- 7.8" (19.8 cm) ground clearance for exceptional maneuverability

Productivity

- Innovative tilt-up deck for easy cleaning and maintenance
- Up to 15 mph (24 km/h) ground speed
- 1"-6" (25-152 mm) height of cut with a simple pin adjustment
- Comfortable operator platform
- Easy to access maintenance points

Versatility

- Rotary and Fine Cut Flail mowing decks available
- Year-round versatility with a variety of multi-season attachments
- Cab option helps keep operators comfortable and productive all season long



A Revolution in Out-Front Rotaries.

Toro has been creating world-class out front rotary mowers for over 45 years.

We are continuing this legacy with the new Groundsmaster 3200/3300.

The Groundsmaster 3200/3300 delivers unparalleled productivity. Featuring a powerful 37.4 HP (27.9 kW) or 24.7 HP (18.4 kW) engine, CrossTrax® all-wheel drive and legendary Groundsmaster decks, the Groundsmaster 3200/3300 makes quick work in even the toughest terrain while delivering an exceptional quality of cut. From the fully-adjustable suspension seat and steering column, the fingertip engine controls and optional all-season cab, this new mower is designed for all-day comfort. Routine maintenance is also easy with the Groundsmaster 3200/3300. The innovative Tilt-Up Deck design making blade maintenance and deck cleaning simple. Additionally, all engine maintenance points are easily accessible to help ensure your Groundsmaster runs smoothly and reliably for years.

Productivity, comfort, reliability. That's the all-new Groundsmaster 3200/3300.

toro.com/outfront



©2020 The Toro Company. All rights reserved. Rev. 3/20

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. All trademarks are property of their respective owners.

Call your Toro distributor at 800-803-8676

Groundsmaster® 3200/3300 Specifications

| | GROUNDSMASTER 3200 2WD, MODEL 31900 | GROUNDSMASTER 3200 AWD, MODEL 31901 | GROUNDSMASTER 3300 AWD, MODEL 31902 | GROUNDSMASTER 3310 AWD CAB, MODEL 31903 |
|------------------|--|--|--|---|
| ENGINE | Yanmar® 3 Cylinder, liquid cooled diesel, Power: 24.7 HP (18.4kW) @ 3000 rpm, Torque peak: 50.9 ft-lbs. (69 Nm) @ 2100 rpm. Displacement 1267cc. High Idle: 3230 rpm (no load). Remote mounted Donaldson air cleaner. Fuel filter water separator. EPA Tier 4 / Stage V compliant | Yanmar, 3 Cylinder, liquid cooled diesel, Power: 37.4 HP (27.9kW) @ 3000 rpm, Torque peak: 80.4 ft-lbs. (109 Nm) @ 1950 rpm. Displacement 1642. High Idle: 3150 rpm (no load). Remote mounted Donaldson air cleaner. Fuel filter water separator. EPA Tier 4 / Stage V compliant | Yanmar, 3 Cylinder, liquid cooled diesel, Power: 37.4 HP (27.9kW) @ 3000 rpm, Torque peak: 80.4 ft-lbs. (109 Nm) @ 1950 rpm. Displacement 1642. High Idle: 3150 rpm (no load). Remote mounted Donaldson air cleaner. Fuel filter water separator. EPA Tier 4 / Stage V compliant | Yanmar, 3 Cylinder, liquid cooled diesel, Power: 37.4 HP (27.9kW) @ 3000 rpm, Torque peak: 80.4 ft-lbs. (109 Nm) @ 1950 rpm. Displacement 1642. High Idle: 3150 rpm (no load). Remote mounted Donaldson air cleaner. Fuel filter water separator. EPA Tier 4 / Stage V compliant |
| RADIATOR | Rear mount, cross flow, 8.5 fins per 1" (25 mm), 7 quart (6.6 liter) capacity | | Rear mount, cross flow, 8.5 fins per 1" (25 mm), 8 quart (7.6 liter) capacity | |
| FUEL CAPACITY | | 12 gallon (45 L) | | |
| TRACTION DRIVE | 2WD Parallel hydraulic traction system. Parallel hydraulic flow between the front wheel motors powered by hydrostatic pump | Patented CrossTrax® AWD. Series parallel hydraulic traction system w/full time, bi-directional 4-wheel drive. Parallel hydraulic flow between front and rear wheels. | | |
| GROUND SPEED | Up to 12.5 MPH (20 km/h) | | Up to 15 MPH (24 km/h) | |
| MAIN FRAME | | All welded tubular and formed steel | | |
| IMPLEMENT DRIVE | Engine mounted 350 ft. lb. (475 Nm) rated electro-magnetic PTO clutch drives 2" (5 cm) telescoping shaft. Rotary deck connection allows for tip-up service position without disconnection of PTO. | | | |
| IMPLEMENT LIFT | Twin 2.5" (6.4 cm) bore, 1.25" (3.2 cm) rod hydraulic cylinders operate lift arms. Hydraulic counterbalance for optimum traction and stability. | | | |
| TIRES | Front: 23 x 10.5 - 12 4-ply, Rear: 16 x 6.5 - 8, 4-ply | Front: 23 x 10.5 - 12 4-ply, Rear: 18 x 9.5 - 8, 4-ply | Front: 24 x 12 - 12, 4-ply, Rear: 18 x 9.5 - 8, 4-ply | |
| BRAKES | Dynamic braking through hydrostat and foot pedal. Parking Brake: Hand-actuated drum type on front left and right traction wheels | | | |
| SEAT | Deluxe Bolstered Seat (model 31980), Mechanical Suspension Seat (Model 31981), Air Ride Suspension Seat (Model 31982) | | | |
| STEERING | Hydraulic Power Steering. Tilt steering wheel released and locked by a foot actuated lever | | | |
| OPERATOR AREA | Operator step, beverage holder, control arm, retractable seat belt, standard | | | |
| INSTRUMENTATION | InfoCenter™: Onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics. Indicates coolant temps, oil pressure, alternator voltage, engine hours, (37.4 HP models, engine RPM). | | | |
| CONTROLS | Foot-operated pedal for forward and reverse. Manually adjustable forward speed limiter. Control arm includes hand-operated throttle, PTO switch, deck/implement lift lower switch, ignition switch, (24.7 HP models, glow plug switch) | | | |
| ELECTRICAL | 12V maintenance-free battery with 540 cold cranking amps at 0 degrees F (-18 degrees C). 80 minute reserve capacity at 80 degrees F (27 degrees C). 40-amp alternator on 24.7 HP models, 55-amp alternator on 37.4 HP models. Seal, PTO, lift/lower, traction and parking brake interlock switches. Easy access to fuse panel. | | | |
| GROUND CLEARANCE | 8.3" (21 cm) traction unit only | | | |
| LENGTH | | 107" (271.7 cm) | | |
| WIDTH | 52" (132 cm) | | 53.1" (134.8 cm) | |
| HEIGHT | 79" (200.6 cm) with ROPS up | | | 89" (226 cm) |
| WHEELBASE | | 51.5" (130.8 cm) | | |
| WEIGHT | 1,751 lbs. (794 kg) | 1,886 lbs. (855 kg) | 2,486 lbs. (1128 kg) | |
| SAFETY CAB | Optional ROPS certified cab with heat only. Tempered curved windshield, tinted side and rear glass (50% tint); front wiper/washer; interior mirror and exterior side mirrors; SMV sign; road light kit and work light kit sold separately. All glass windows meets ANSI Z-26.1999 and ECE R43 | | | Factory installed, ROPS certified cab with AC and heat. Tempered curved windshield, tinted side and rear glass (50% tint); front wiper/washer; interior mirror and exterior side mirrors; SMV sign; road light kit and work light kit sold separately. All glass windows meets ANSI Z-26.1999 and ECE R43 |
| WARRANTY | Two-year limited warranty. Refer to operators manual for further information. | | | |
| ACCESSORIES | LED work light kit, LED road light kit, beacon, recycler kits, slope sensor kit, optional cab (heat only) | | | |

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



| CUTTING DECKS (SOLD SEPARATELY) | | | | | |
|---|---|---|---|--|--|
| CUTTING DECK CONFIGURATIONS | 60" (152 CM) SIDE DISCHARGE DECK, MODEL 31970 | 72" (183 CM) SIDE DISCHARGE DECK, MODEL 31972 | 60" (152 CM) REAR DISCHARGE DECK, MODEL 31971 | | |
| CONSTRUCTION | 7-gauge (4.5 mm) high-strength steel, 5.5" (14 cm) deep; welded deck with grass discharged on the right side. A 5/16" (8 mm) thick rubber discharge chute covers the discharge opening to limit the throw distance of clippings. Adjustable baffle. | | | | |
| SERVICE POSITION | | | | | |
| HEIGHT OF CUT | Cutting deck can tip up to the service position from the transport position to conduct routine maintenance quickly. Driveshaft stays connected during tip up. | | | | |
| MOWING RATE** | 1"-6" (25 - 152 mm) adjustable in 0.25" (6 mm) increments. | | | | |
| SPINDLE ASSEMBLY | Up to 4.2 acres (1.7 hectares) per hour | Up to 5 acres (2.1 hectares) per hour | Up to 4.2 acres (1.7 hectares) per hour | | |
| CUTTER DRIVE | Up to 5 acres (2.1 hectares) per hour | | | | |
| BLADES | Ductile cast iron 9" (23 cm) diameter conical spindle housing; Dual greaseable tapered roller bearings; Spindle shaft is 1.25" (3.2 cm) diameter, solid cold finished steel, splined connection between spindle shaft and pulley; Welded blade retainer plus anti-scalp cups. | | | | |
| BLADE TIP SPEED (3000 RPM) | Solid mounted, splined PTO-driven gearbox transfers power to three separate spindles via one "B" section belt. | | | | |
| DECK SUSPENSION | Three 0.25" (6 mm) thick, 2.5" (63 mm) wide, heat-treated steel blades. | | | | |
| BELT IDLER | 17,500 | 16,000 | | | |
| DECK SKID | Independent, 2" (5 cm) square tubing, lift/push arms each attached to separate castor arms. | | | | |
| ANTI SCALP | Spring-loaded (torsion) idler | | | | |
| DECK COVERS | Replaceable, bolt-on, non-marking UHMW skid on both sides for rear discharge decks and on left side only for side discharge decks. Interchangeable left to right. | | | | |
| LIFT ARMS | Anti-scalp cup located on each blade spindle. Additional anti-scalp gauge wheels. | | | | |
| SHIPPING WEIGHT | 450 lbs. (204 kg) | 510 lbs. (231 kg) | 460 lbs. (208 kg) | | |
| OPTIONAL ACCESSORIES | 512 lbs. (232 kg) | | | | |
| Recycler kits, blade options (low sail, medium sail, high sail, atomic), blowout baffle, roller striper | | | | | |

| OPTIONAL ATTACHMENTS | |
|----------------------|---|
| CAB | Heated cab that fits ROPS models. |
| UNIVERSAL SUNSHADE | Universal sunshade, red or white |
| ROTARY BROOM | 60" (152 cm) clearing width, from M-B®. |
| SNOWTHROWER | 53" (134 cm) clearing width, from Erskine®. |
| SNOW BLADE | 60" (152 cm) straight blade, from BOSS®. |

| | |
|----------------------|---|
| FRAME CONSTRUCTION | 60" (152 CM) F60 FLAIL CUTTING DECK, MODEL 02835 |
| ROTOR CONSTRUCTION | Welded, high strength steel frame |
| HEIGHT OF CUT | 4" (100 mm) diameter, dynamically balanced flail rotor. |
| MOWING RATE** | Greaseable tapered roller bearings mounted in rigid mounted bearing housings. Rotor can be removed from frame without prior removal of bearings and bearing housings. |
| BLADES | Up to 4.2 acres (1.7 hectares) per hour |
| BELT IDLER | 32x TEMPEST™ paddle-style flail blades |
| DECK SKID | Mechanical adjustable idler. Locked with M20 bolt. |
| CASTOR WHEELS | Replaceable, bolt-on steel skid |
| LIFT ARMS | 8 x 3.5-4 4-Ply , pneumatic, sealed ball bearings. |
| SHIPPING WEIGHT | Independent lift arms and hydraulic weight transfer provide deck floatation. Supplied complete with the flail. |
| OPTIONAL ACCESSORIES | 564 lbs. (256 kg) |
| | Fine Cut Baffle Kit, Mulching Bar, Back to Back Flail Blades, Replacement Blade Kits, choice of 2x blades or 16x blades (2x per flail required) |



*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

**Assumes 7 mph (11.3 km/h) mow speed, no overlap and 100% efficiency.

