## 2022-2023 Outsourced Excavation Costs

	<u>NTrak</u>	Stenstrom
1.)	\$4,383.12	\$14,388.33
2.)	\$3,481.07	\$1,636.00
3.)	\$5,780.53	
4.)	\$11,375.00	
5.)	\$5,838.08	
Company Totals:	\$30,857.80	\$16,024.33
2022-2023 Total:	\$46,882.13	

Sourcewell 3 Utility Tractors & Mowers - 031121 CE and AG - 040319 Utility Vehicles 122220 Arkansas 4600041718 Delaware GSS-21673 Mississippi (CE Only) 8200056371 Mississippi 8200055841

KX057-5R3AP WEB QUOTE #2556219 Date: 1/13/2023 12:34:31 PM -- Customer Information --Howe, David Village of Poplar Grove dhowe@villageofpoplargrove.com 815-765-3201

Quote Provided By JOHNSON TRACTOR, INC. Dave King 20508 OAK GROVE RD. HARVARD, IL 60033 email: davek@johnsontractor.com phone: 8154031871

-- Custom Options --

-- Standard Features --

Kubota

\* \* \* EQUIPMENT IN STANDARD MACHINE \* \* \*

**FEATURES** 7" LCD Color Display Auto Idler Rubber Track Models A/C ROPS/OPG Cab Kubota 3 Hydraulic Pump Load OPERATIONAL Sensing System 1 Gear, 2 Variable Displacement Pumps All Controls Hydraulic Pilot Controls Two Operating Pattern Selection System Accumulator

Digital Control Panel Attachment Flow Presets, Service Alerts

Standard Front Dozer Blade w/ Float 360 Degree Full Rotation 70 Degree Left, 55 Degree

Right Boom Swing 19.8 gpm Adjustable Auxiliary Hydraulics Port 1 Auxiliary Hydraulics Diverter

Valve Thumb Bracket and Relief

Valves Five Second Quick Preheat

Key Switch Stop System

Half Pitch Rubber Tracks Self Bleed Fuel System Auto-Downshift Two Speed Travel System Swivel Negative Brake Travel Negative Brake

Third Line DIMENSIONS AND

**OPERATING WEIGHT** KX057-5R3AP, Rubber Tracks. ROPS/OPG (Top Guard, Level Angle Dozer Blade, Dipper Arm, Counterweight, SP2 Overall Length 18' 1.3" Overall Width 6' 5.2" Overall Height 8' 4.4" Operating Weight 13,051 lbs.\*

\*Includes operator's weight, 165 lbs.

Ground Clearance 12' 0.2"

**ENGINE** 

V2607 Kubota CR E5 Tier 4 Diesel Engine 4 Cylinder, 4 Cycle 46.4 Net HP @ 2200 rpm (SAE J1349)

**DIMENSIONS** 

Max Digging Depth 12' 9" Max Digging Radius @ Ground Level 20' 1' Max Vertical Digging Depth 5' 4" Max Dumping Height 13' 8.6"

DOZER BLADE **DIMENSIONS** Width 77.2" Height 16.1" Lift Above Ground 17,3" Drop Below Ground 15.9"

PERFORMANCE Digging Force @ Bucket 10,172 lbs. Digging Force @ Dipper Arm 5,463 lbs. Travel Speed (Low) 1.7 mph Travel Speed (High) 3.0 mph Climbing Ability 36% / 20° Lift Capacity 3,410 lbs.

Over Front Blade Grounded 4.0 Ft. Load Point Height 12.0 Ft. Load Radius

STANDARD WARRANTY Basic Warranty - 24 Months / 2000 Hours

Rubber Track Warranty - 12 Months / 1000 Hours

KX057-5R3AP Base Price: \$92,971.00 (1) 48" BOLT ON CUTTING EDGE \$306.00 878A-48" BOLT ON CUTTING EDGE (1) 48" QUICK ATTACH GRADING BUCKET \$2,400.00 K7924A-48" QUICK ATTACH GRADING BUCKET (1) 24"Q.A. TRENCHING BCKT/U55/KX057-4 \$1,866.00 K7919-24"Q.A. TRENCHING BCKT/U55/KX057-4 (1) HYDRUALIC THUMB \$3,294.00 K7937B-HYDRUALIC THUMB (1) BKT Q.A. COUPLER FOR U55/KX057-4 \$1,335.00 K7915-BKT Q.A. COUPLER FOR U55/KX057-4 (1) 36"Q.A. TRENCHING BCKT/U55/KX057-4 \$2,839.00 K7921-36"Q.A. TRENCHING BCKT/U55/KX057-4 Configured Price: \$105,011.00 Sourcewell Discount: (\$25,202.64)SUBTOTAL: \$79,808.36 Dealer Assembly: \$82.50

Freight Cost:

PDI:

Total Unit Price: \$81,253.36 Quantity Ordered: Final Sales Price: \$81,253,36

\$962.50

\$400.00

Purchase Order Must Reflect the Final Sales Price

To order, place your Purchase Order directly with the quoting

\*Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the ote. All equipment as quoted is subject to availability.

## **David Howe**

From:

Sent: To:

Friday, January 13, 2023 2:50 PM

David Howe

Subject:

Kubota excavator quotes

Attachments:

Village of Poplar Grove KX057 quote.pdf; Village of Poplar Grove KX080 quote.pdf

David,

Thank you for taking time and giving me the opportunity to quote the excavators!

I have included a quote for the KX080 and KX057. The KX057 does not offer a tilt grading bucket so I quoted a 48" Std grading bucket.

We will allow \$39,000 on your KX033 trade.

Please give me a call with any questions.

Thank You,



## KX057-5R3AP WEB QUOTE #2577334 Date: 2/9/2023 8:11:08 AM

-- Standard Features --

-- Custom Options --



K Series

KX057-5R3AP

\* \* \* EQUIPMENT IN STANDARD MACHINE \* \* \*

**FEATURES** 

7" LCD Color Display Auto Idler

Rubber Track Models

A/C ROPS/OPG Cab

Sensing System 1 Gear, 2 Variable

Displacement Pumps All Controls Hydraulic Pilot

Controls Two Operating Pattern Selection System

Accumulator Digital Control Panel Attachment Flow Presets,

Service Alerts Standard Front Dozer Blade w/

Float

360 Degree Full Rotation 70 Degree Left, 55 Degree Right Boom Swing

19.8 gpm Adjustable Auxiliary Hydraulics Port 1 Auxiliary Hydraulics Diverter

Valve

Thumb Bracket and Relief

Valves Five Second Quick Preheat

System Key Switch Stop System Half Pitch Rubber Tracks

Self Bleed Fuel System Auto-Downshift Two Speed Travel System Swivel Negative Brake

Travel Negative Brake Third Line

**DIMENSIONS AND OPERATING WEIGHT** KX057-5R3AP, Rubber Tracks, ROPS/OPG (Top Guard, Level

I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight, SP2

Overall Length 18' 1.3" Overall Width 6' 5.2" Overall Height 8' 4.4" Operating Weight 13,051 lbs.\*

Ground Clearance 12' 0.2"

\*Includes operator's weight, 165 lbs.

**ENGINE** 

V2607 Kubota CR E5 Tier 4 Diesel Engine

4 Cylinder, 4 Cycle

46.4 Net HP @ 2200 rpm (SAE J1349)

Kubota 3 Hydraulic Pump Load OPERATIONAL **DIMENSIONS** 

> Max Digging Depth 12' 9" Max Digging Radius @ Ground

Level 20' 1'

Max Vertical Digging Depth 5' 4" Max Dumping Height 13' 8.6"

DOZER BLADE **DIMENSIONS** 

Width 77.2" Height 16.1"

Lift Above Ground 17.3" Drop Below Ground 15.9"

**PERFORMANCE** 

Digging Force @ Bucket 10,172 lbs.

Digging Force @ Dipper Arm

5,463 lbs.

Travel Speed (Low) 1.7 mph

Travel Speed (High) 3.0 mph Climbing Ability 36% / 20° Lift Capacity 3,410 lbs.

Over Front Blade Grounded

4.0 Ft. Load Point Height 12.0 Ft. Load Radius

STANDARD WARRANTY

Basic Warranty - 24 Months / 2000

Hours Rubber Track Warranty - 12

Months / 1000 Hours

KX057-5R3AP Base Price: \$92,971.00

(1) 48" QUICK ATTACH GRADING BUCKET \$2,400.00

K7924A-48" QUICK ATTACH GRADING BUCKET

\$3,294.00

(1) HYDRUALIC THUMB K7937B-HYDRUALIC THUMB

(1) BKT Q.A. COUPLER FOR U55/KX057-4 K7915-BKT Q.A. COUPLER FOR U55/KX057-4

\$1,335.00

(1) 24" QA TRENCHING BUCKET WITHOUT

\$1,797.00

K7919AC-24" QA TRENCHING BUCKET WITHOUT TEETH

Suggested List Price w/ Options: \$101,797.00

Available Manufacturer Rebates:

Cash Customer Instant Rebate Up To: (\$2,700.00)

Municipal Price

\$70,872

Not Included: \*Taxes, shipping & handling, surcharges, assembly charges, destination, freight and/or delivery charges.

This MSRP configuration program is for informational purposes only. Price on this sales quote is an estimate and is subject to being increased. Final pricing and applicable programs will be established at delivery. In all instances, the user of this program must consult with an authorized Kubota Dealer for complete purchase, warranty and safety information. Special pricing and promotions may be available on certain models. See your Kubota Dealer for details and individual Dealer product pricing. All prices are shown in U.S. Dollars. Quotes are for products sold in the

© 2018 Kubota Tractor Corporation. All rights reserved.