light House Reach Dla	yaro	und	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			the first contraction could be first force in the contract of
Playground area is free of anthills/hazardous insects or toxic plants.	17/	Г	
Playground area is free of holes and other tripping hazards.	./	г	
Proper signage with rules, hours, and age- appropriate use is posted.	7	г	
Playground area is properly fenced.	г	Г	N/A
Self-latching gate works as designed.	Γ.	Γ	N/A
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Г	г	W/A
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	Γ	N/A
Surfacing material is free of glass, debris, or other foreign objects.	Г	ŗ-	weeds growing around playground
Surfacing material is not compacting or deteriorating.	٢	Γ	N/A
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Γ	г	N/A
Proper drainage prevents water from forming puddles.	Г	Г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	7	Г	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	r-	L-	N/A
Equipment is free of potential clothing entanglement hazards.	г	۲	
Equipment free of pinch and crush points or exposed moving parts.	Γ-	F /	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	Rust on the plue metal ladders
Equipment is free of entrapments.	F/	Γ	
Equipment is safely anchored.		Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	N/A
Swings are a safe distance from other playground equipment.	Г	Γ	N/A
Swings are 24 inches apart.	г	Γ	N/A
Edges of seats are smooth and free from obstructions.	Г	г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Г	N/A

light House Beach Playa	muno	and the design of the second	
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	Г	2 a 3 a 3 a 3 a 3 a 3 a 3 a 3 a 3 a 3 a
Equipped with platforms to facilitate access to the sitting position.	TE /	О	4
Platforms are equipped with guardrails or equivalent protective equipment.	1	П	
Average incline is less than 30 degrees.	TV/	, 0	
Exit regions are level.	T/	0	
Metal slides are shaded to prevent overheating.		- Acstic	Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	TT/		
Rope or chain ladders are anchored at both ends.	П	n N/A	
Foot holds/rungs are in good condition and adequately spaced.	7	п	
Seesaws	Pass	Fail	Problem / Solution
	Pass	Fail N/A	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion,		П //A	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г.	n N/A	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	П //A	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	n n	П //A	Problem / Solution

light House & Splash Pag	1	laya	round
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	/ 「	
Playground area is free of anthills/hazardous insects or toxic plants.	i.e.	Г	,
Playground area is free of holes and other tripping hazards.	г	۲./	Couple holes
Proper signage with rules, hours, and age- appropriate use is posted.	5	Г	
Playground area is properly fenced.	Г	Γ	N/A
Self-latching gate works as designed.	г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	г		Couple holes
Surfacing material under and around equipment is adequate depth (6-12 inches).	-/	Г	
Surfacing material is free of glass, debris, or other foreign objects.		Γ	
Surfacing material is not compacting or deteriorating.	17	٦	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	NIA
Proper drainage prevents water from forming puddles.	Г	г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	/ [
Equipment is free from sharp points, corners, or edges.	,/	Г	
Protective caps or plugs are not missing or damaged.		Г	NA
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	-/		
Equipment is free of rust, rot, cracks, and splinters.		√	meinor rust
Equipment is free of entrapments.	1	<u></u>	
Equipment is safely anchored.	La	Г	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	N/A
Swings are a safe distance from other playground equipment.	г	Г	N/A
Swings are 24 inches apart.	Г	Г	N/A
Edges of seats are smooth and free from obstructions.	Г	Г	NA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	N/A

light House solosh Oad old	Var	und	
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	[]	, 0	
Equipped with platforms to facilitate access to the sitting position.		П	
Platforms are equipped with guardrails or equivalent protective equipment.			
Average incline is less than 30 degrees.		В	N/A
Exit regions are level.	E	П	,-
Metal slides are shaded to prevent overheating.	Œ		Plastic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	P		
Rope or chain ladders are anchored at both ends.	П	П	N/A
Foot holds/rungs are in good condition and adequately spaced.	F-/	П	
Seesaws	Pass	Fail	Problem / Solution
			[1] 是一个大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大
Seesaws are free of cracks, corrosion, and other obvious structural defects.	п	П	N/A
	п	п	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			N/ À
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	п	П	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	С	п	N/A

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1 455	1 all	Trostem solution
Playground area is free of anthills/hazardous insects		,	
or toxic plants.		Γ	
Playground area is free of holes and other tripping hazards.	j	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	i-/	Г	
Playground area is properly fenced.	Г	Γ	N/A
Self-latching gate works as designed.	Г	٢	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	F	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		г	W/A
Surfacing material is free of glass, debris, or other foreign objects.	[]	L	
Surfacing material is not compacting or deteriorating.	17	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Γ	N/A
Proper drainage prevents water from forming puddles.	ŗ.	r	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	,	Г	
Equipment is free from sharp points, corners, or edges.	,	Γ	
Protective caps or plugs are not missing or damaged.	Г	Г	N/A
Equipment is free of potential clothing entanglement hazards.		<u></u>	
Equipment free of pinch and crush points or exposed moving parts.		r	
Equipment is free of rust, rot, cracks, and splinters.	-/	г	
Equipment is free of entrapments.		Г	
Equipment is safely anchored.	=	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	г	4/4
Swings are a safe distance from other playground equipment.	Г	г	ALW
Swings are 24 inches apart.	Г	Г	W/A
Edges of seats are smooth and free from obstructions.	Г	Г	N/A

light House 5Plash	Pad		ar gist	70
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	Г	Г	ALCA	
Equipped with platforms to facilitate access to the sitting position.	-	Г	A)/ A	
Platforms are equipped with guardrails or equivalent protective equipment.	Г	Г	NIA	
Average incline is less than 30 degrees.	Г	Г	NIA	v
Exit regions are level.	г	Г	1/A	
Metal slides are shaded to prevent overheating.	Г	г	N/A	
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	г	Г	A/K	
Rope or chain ladders are anchored at both ends.	г	Г	A)/A	
Foot holds/rungs are in good condition and adequately spaced.	г	г	Witt	
		A SECTION AND ADDRESS OF THE PARTY.		图像 的复数加速的 医多种性神经病 医多种性神经病 医多种性神经病 医多种性神经病 医多种性神经病 医多种性神经病
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	W/A	Problem / Solution
Seesaws are free of cracks, corrosion,				Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	Γ	N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	Г		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	г г	L L	A/A	Problem / Solution

light House Splash	Pad	,		
Slides	Pass	Fail	Problem / Solution	一直 军
Slides are free of obstructions and protrusions.	г	F	A)(A	
Equipped with platforms to facilitate access to the sitting position.	г	Γ.	A)/ A	
Platforms are equipped with guardrails or equivalent protective equipment.	г	г	NIA	
Average incline is less than 30 degrees.	Г	Г	NIA	
Exit regions are level.	г	Г	4)/A	
Metal slides are shaded to prevent overheating.	г	Γ	1)/2	
Climbing Equipment	Pass	Fail	Problem / Solution	
Hand grips are secured and do not rotate.		Г	۸۱۸	
Rope or chain ladders are anchored at both ends.	Г	Γ	N/A	****
Foot holds/rungs are in good condition and adequately spaced.	г	Г		
Seesaws	Pass	Fail	Problem / Solution	ALLEY A LOSS TO
	433		1 Tobletti / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	r ass	T		
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	antice Value of		ν/ /A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	Г	N/A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	г	г	ν/ /A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	-	N/A N/A	

light House pavillan playara General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1 455	Г	
Playground area is free of anthills/hazardous insects			
or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.	17/	Γ,	
Proper signage with rules, hours, and age- appropriate use is posted.	,70	Γ	
Playground area is properly fenced.	г	T	NA
Self-latching gate works as designed.	Г	Γ	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	ic	Г	
Surfacing material is free of glass, debris, or other foreign objects.			
Surfacing material is not compacting or deteriorating.	10	٦	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Г	N/A
Proper drainage prevents water from forming puddles.	г	L	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	1	Г	,
Protective caps or plugs are not missing or damaged.	Г,	Г	N/A
Equipment is free of potential clothing			1-7-
entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment free of pinch and crush points or exposed	7	<u> </u>	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters.	7	Г	
Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments.	7	г г	Problem / Solution
Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored.	7	 	Problem / Solution
Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. Swings	Pass	r Fail	N/A
Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. Swings Hardware and chains are in good condition. Swings are a safe distance from other playground	Pass	Fail	N/A
Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. Swings Hardware and chains are in good condition. Swings are a safe distance from other playground equipment.	Pass	Fail	N/A

light House Owillow Play	(h)()(m)			
Slides	Pass			Problem / Solution
Slides are free of obstructions and protrusions.	1	Г		Toblem, Colucion
Equipped with platforms to facilitate access to the sitting position.	-	Г		
Platforms are equipped with guardrails or equivalent protective equipment.	,/			
Average incline is less than 30 degrees.		Г		
Exit regions are level.		г		
Metal slides are shaded to prevent overheating.	Г	г	N/A	
Climbing Equipment	Pass	Fail	THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TRANSPORT OF THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW	roblem / Solution
Hand grips are secured and do not rotate.	1			
Rope or chain ladders are anchored at both ends.	1			
Foot holds/rungs are in good condition and adequately spaced.	10	Г		
"我们就是一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个一个	and the second second	Section Section		CONTROL OF THE PROPERTY OF THE
Seesaws	Pass	Fail		roblem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	A) / A	roblem / Solution
Seesaws are free of cracks, corrosion,			A)/A A)/A	roblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	Г	N/A	roblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	L .	Г	N/A	roblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r .	r -	N/A	roblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r .	r -	N/A N/A N/A	Jan 13, 2025

Butter tly Dayarnunch			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	N		
Playground area is free of anthills/hazardous insects or toxic plants.	/	Г	
Playground area is free of holes and other tripping hazards.	. ୮	5	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Г	. 「	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	г		Rubber Peeling off
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	A/U.
Surfacing material is free of glass, debris, or other foreign objects.	/	г	
Surfacing material is not compacting or deteriorating.	Г	Г	Detertorting
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Γ	A/W
Proper drainage prevents water from forming puddles.	٦	Г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	~	Г	
Equipment is free from sharp points, corners, or edges.	Γ.	J	Rust points
Protective caps or plugs are not missing or damaged.	г	Г	NA
Equipment is free of potential clothing entanglement hazards.	Г	, _	Rust
Equipment free of pinch and crush points or exposed moving parts.	-	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	Г	Rust all over
Equipment is free of entrapments.	Г	Г	
Equipment is safely anchored.	Г	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.		-	;
Swings are 24 inches apart.		_	
Edges of seats are smooth and free from obstructions.	7	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		Г	

Buttertly playground		1 20.00		
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	1			
Equipped with platforms to facilitate access to the sitting position.		Г		
Platforms are equipped with guardrails or equivalent protective equipment.				
Average incline is less than 30 degrees.	-	Г		
Exit regions are level.	1	г		
Metal slides are shaded to prevent overheating.	Г	г	Plastic	Slides
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	~	г		
Rope or chain ladders are anchored at both ends.	Г	Г	N/A	
Foot holds/rungs are in good condition and adequately spaced.		г	7.1.	
Seesaws	Pass	Fail		Problem / Solution
	I ass	I all		1 Tobleili / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	r ass	I all	۸۷/Å	i robiem / Solution
Seesaws are free of cracks, corrosion,			N/A	Troblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	г	L	N/A N/A	r roblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	г	r	,	r roblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г	r	,	Troblem / Solution

13autrant Olavaround	(a F	Belle
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	Control of the second s
Playground area is free of anthills/hazardous insects or toxic plants.		\ r	
Playground area is free of holes and other tripping hazards.		Г	·
Proper signage with rules, hours, and age- appropriate use is posted.		г	
Playground area is properly fenced.	Γ-	Γ.	N/A
Self-latching gate works as designed.	Γ.	f"	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	I ⁻	Г	N/A
Surfacing material is free of glass, debris, or other foreign objects.		r	•
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	ī	г	W/A
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Γ	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	r	,	NIA
Equipment is free of potential clothing entanglement hazards.		, r	71.
Equipment free of pinch and crush points or exposed moving parts.		Γ	
Equipment is free of rust, rot, cracks, and splinters.	Г	г	minor Rust on Nuts
Equipment is free of entrapments.	۲	Г	
Equipment is safely anchored.	r	Γ.	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	г	Γ	N/A
Swings are a safe distance from other playground equipment.	r	Γ.	N/A
Swings are 24 inches apart.	Γ-	Г	N/A
Edges of seats are smooth and free from obstructions.	Г	Г	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Γ.	Г	N/A

(To be completed monthly.)

Claret Crossing Dark

LIMPY CHOSSIMI ISMA			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			
Playground area is free of anthills/hazardous insects or toxic plants.	10		
Playground area is free of holes and other tripping hazards.			
Proper signage with rules, hours, and age- appropriate use is posted.			
Playground area is properly fenced.			A)/A
Self-latching gate works as designed.			ALA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).			
Surfacing material under and around equipment is adequate depth (6-12 inches).	IU		
Surfacing material is free of glass, debris, or other foreign objects.			
Surfacing material is not compacting or deteriorating.		П	Concrete Cracking
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		П	NIA
Proper drainage prevents water from forming puddles.		П	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.			
Equipment is free from sharp points, corners, or edges.		/	
Protective caps or plugs are not missing or damaged.	r/	/ 0	
Equipment is free of potential clothing entanglement hazards.		, [
Equipment free of pinch and crush points or exposed moving parts.		П	
Equipment is free of rust, rot, cracks, and splinters.			
Equipment is free of entrapments.	1/		
Equipment is safely anchored.		٦	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	/-	
Swings are a safe distance from other playground equipment.		/ n	
Swings are 24 inches apart.		<u></u>	
Edges of seats are smooth and free from obstructions.	r-/	/ n	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		П	

Claret Crossing Park			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		, r	
Equipped with platforms to facilitate access to the sitting position.			
Platforms are equipped with guardrails or equivalent protective equipment.			
Average incline is less than 30 degrees.	1	/ [
Exit regions are level.	7	/г	
Metal slides are shaded to prevent overheating.	F	Г	Dastic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	Г	
Rope or chain ladders are anchored at both ends.	r/	<u>г</u>	
Foot holds/rungs are in good condition and adequately spaced.	F	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		Г	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		Г	
Fulcrums/pivot points are free of pinch or crush hazards.		Γ	
Handholds are provided at each seating position.	1	Г	
Inspector name, signature, and completion date			
Name: Dauglas Corpio			Date: Jan 13, 7025

13autrant Olavaround	((a F	Belle
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	F	1	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.	[2	Γ	
Playground area is properly fenced.	Г	Г	A)/A
Self-latching gate works as designed.	F.	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1-	Г	W/A
Surfacing material is free of glass, debris, or other foreign objects.		г	
Surfacing material is not compacting or deteriorating.	1	F	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	г	N/A
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	۲-	,	A9/A
Equipment is free of potential clothing entanglement hazards.		Г	191R
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	г	Г	minor Rust on Nuts
Equipment is free of entrapments.	Γ-	Г	TO HITTO THOSE OF THE PARTY OF
Equipment is safely anchored.	г	٣	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	N/A
Swings are a safe distance from other playground equipment.	L-	Γ.	N/A
Swings are 24 inches apart.	г	Г	N/A
Edges of seats are smooth and free from obstructions.	г	Γ	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	I ^{re.}	Г	N/A

Bayfront Dayground la	Bel	De		
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	ī/	-		
Equipped with platforms to facilitate access to the sitting position.	-/	٦		
Platforms are equipped with guardrails or equivalent protective equipment.	100	Г		
Average incline is less than 30 degrees.	Г	Г	J/A	
Exit regions are level.		г	MA	
Metal slides are shaded to prevent overheating.	Г	г	N/A	Plastic Sticles
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	7	Г		
Rope or chain ladders are anchored at both ends.	г	Г	NA	
Foot holds/rungs are in good condition and adequately spaced.	/	٦	<i>7011</i> .	
	COMPLETE OF STREET	The State of the Labor of the	Corporative Contractive Contra	
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail r	N/A	Problem / Solution
Seesaws are free of cracks, corrosion,	Service Control		N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Service Control		N/Å	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Service Control	Г	N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Service Control	Г	N/A	Problem / Solution

(To be completed monthly.)

City Park

City Park	15000000000	CHARLES ON THE	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	, г	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.		Г (
Proper signage with rules, hours, and age- appropriate use is posted.	17	Γ	
Playground area is properly fenced.	г	Г	N/A
Self-latching gate works as designed.	Г	Γ	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	۲	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	Г	Г	۵/۵
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	r,	Г	N/A
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		/ r	
Equipment is free from sharp points, corners, or edges.		г	•
Protective caps or plugs are not missing or damaged.		Г	N/A
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	/	Г	
Equipment is free of rust, rot, cracks, and splinters.	1/	T	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	1		
Swings are 24 inches apart.	1	Г	
Edges of seats are smooth and free from obstructions.		Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		Г	

City Durk		No.	
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		Г	
Equipped with platforms to facilitate access to the sitting position.	P	Г	
Platforms are equipped with guardrails or equivalent protective equipment.		г	
Average incline is less than 30 degrees.	r	Г	N/A
Exit regions are level.	7	Г	
Metal slides are shaded to prevent overheating.	г	г	Plastic slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	. г	
Rope or chain ladders are anchored at both ends.	1		
Foot holds/rungs are in good condition and adequately spaced.		٢	
Seesaws	Pass	Fail	Problem / Solution
	THE RESERVE OF THE PARTY OF THE		
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Г	N/A
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	г	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			A/U A)U
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch		Г	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	-	Γ	

CHU Park Ry Ashley for	eld.	5	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	[-/	D	and the company of th
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.		г	
Playground area is properly fenced.	Γ-	Г	N/A
Self-latching gate works as designed.	Γ.	۲	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	г	г	N)A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Γ	
Equipment is free from sharp points, corners, or edges.	/	Г	
Protective caps or plugs are not missing or damaged.	r-	L-	N/A
Equipment is free of potential clothing entanglement hazards.	7	٢	
Equipment free of pinch and crush points or exposed moving parts.		r	
Equipment is free of rust, rot, cracks, and splinters.	г	Г	minor rust
Equipment is free of entrapments.	Γ-	Γ	7.11.01 1.02
Equipment is safely anchored.	Г	Γ.	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Γ	NIA
Swings are a safe distance from other playground equipment.	ľ.	Г	N/A
Swings are 24 inches apart.	Γ-	г	۸/ A
Edges of seats are smooth and free from obstructions.	Г	r	N// 1
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Γ	N/A

City Dork By Ashley Ciela	15		and the first	
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	5	L.		
Equipped with platforms to facilitate access to the sitting position.	1	٦		
Platforms are equipped with guardrails or equivalent protective equipment.	1	г		
Average incline is less than 30 degrees.	-	Г		
Exit regions are level.		Г		
Metal slides are shaded to prevent overheating.	г	Г	Plastic	Slidys
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	-	Г		
Rope or chain ladders are anchored at both ends.	1	Г		
Foot holds/rungs are in good condition and adequately spaced.	~	Г		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	г	Г	NA	
Equipment is provided with spring centering devices		_	7011	
or cushioning material to prevent abrupt contact with the ground.	Г	,	NA	
or cushioning material to prevent abrupt contact		Г.	N/A	
or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch			N/A N/A	
or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	г	Г	N/A N/A	

(To be completed monthly.)

Wilson Park

Wilson Park		HOUSE MICHIGAN	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		, ' _	
Playground area is free of anthills/hazardous insects or toxic plants.	-	Г	
Playground area is free of holes and other tripping hazards.	F.		
Proper signage with rules, hours, and age- appropriate use is posted.		٢	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Г	Г	A)/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	17	Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	-	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Г	N/A
Proper drainage prevents water from forming puddles.	г	г	WA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		г	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	10/	Г	·
Equipment is free of potential clothing entanglement hazards.	,/	Г	
Equipment free of pinch and crush points or exposed moving parts.	F-/	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г		minor rust
Equipment is free of entrapments.	17	-	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	/ 「	
Swings are a safe distance from other playground equipment.	-/	-	
Swings are 24 inches apart.		\ F	
Edges of seats are smooth and free from obstructions.	F/	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	Г	

Wilson Park			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		Г	ez.e Colución
Equipped with platforms to facilitate access to the sitting position.	/	Г	
Platforms are equipped with guardrails or equivalent protective equipment.		Г	
Average incline is less than 30 degrees.	Γ"	(F 1)//L	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.	Г	- Dlastic	-111-C
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		[·	i robiem / Solution
Rope or chain ladders are anchored at both ends.		Г	
Foot holds/rungs are in good condition and adequately spaced.	5/	г	
adequately spaced.			
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion.		Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	T N/A	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	- N/A - N/A - N/A	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	- N/A - N/A - N/A	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	- N/A - N/A - N/A	

Czeorce Adams Park	0.000		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	-/	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	٦ /	
Playground area is free of holes and other tripping hazards.	F/		
Proper signage with rules, hours, and age- appropriate use is posted.	-/	Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Г	Г	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	r	Г	Needs more much
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	5/	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Г	N/A
Proper drainage prevents water from forming puddles.	Г	Г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	17	Г	
Equipment is free from sharp points, corners, or edges.	, , ,	Г	•
Protective caps or plugs are not missing or damaged.	~	Г	
Equipment is free of potential clothing entanglement hazards.	,/	Г	
Equipment free of pinch and crush points or exposed moving parts.	-	٢	
Equipment is free of rust, rot, cracks, and splinters.	٢		minor rust
Equipment is free of entrapments.	-	/ -	
Equipment is safely anchored.	F/	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	-/	\ r	
Swings are a safe distance from other playground equipment.	/	Г	:
Swings are 24 inches apart.		Г	
Edges of seats are smooth and free from obstructions.	_/		
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	F-/]	

Corge Adams Park		Av de la comp		
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	F/	Г		
Equipped with platforms to facilitate access to the sitting position.	-	Г		
Platforms are equipped with guardrails or equivalent protective equipment.	/	г		
Average incline is less than 30 degrees.	Г		NA	
Exit regions are level.	~	Г		
Metal slides are shaded to prevent overheating.	г	Γ	NA	
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	7	, г		
Rope or chain ladders are anchored at both ends.	-	Γ		
Foot holds/rungs are in good condition and adequately spaced.	-/	г		
Seesaws	Pass	Fail		Problem / Solution
Seesaws	L 422	I all		
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	7	Г		
Seesaws are free of cracks, corrosion,	dss	S.C. Wallet		
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		Г		
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch		Г		
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.		Г		