| General Inspection  | 0    | G 11 | D. N. 18 L.        |
|---|------|------|--------------------|
| Playground area is free of litter and debris.   | Pass | Fail | Problem / Solution |
| Playground area is free of anthills/hazardous insects   |      |      |                    |
| or toxic plants.  | 13   | Г    |                    |
| Playground area is free of holes and other tripping hazards.  |      |      |                    |
| Proper signage with rules, hours, and age- appropriate use is posted.   | Г    | г    | Signs being male   |
| Playground area is properly fenced.   | Г    | П    |                    |
| Self-latching gate works as designed.   | r    | r    |                    |
| Surfacing   | Pass | Fail | Problem / Solution |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | 7    | ŗ-   |                    |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | /    | г    |                    |
| Surfacing material is free of glass, debris, or other foreign objects.  |      | 1    |                    |
| Surfacing material is not compacting or deteriorating.  | 2    | Г    |                    |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  | r    | 1-   | N/A                |
| Proper drainage prevents water from forming puddles.  | 7    | г    |                    |
| Equipment Hazards   | Pass | Fail | Problem / Solution |
| Equipment is not damaged or vandalized.   | U    | г    |                    |
| Equipment is free from sharp points, corners, or edges.   | 1    | Г    |                    |
| Protective caps or plugs are not missing or damaged.  | +    | г    |                    |
| Equipment is free of potential clothing entanglement hazards.   | g*** | г    |                    |
| Equipment free of pinch and crush points or exposed moving parts.   | Г    | Г    |                    |
| Equipment is free of rust, rot, cracks, and splinters.  | 1    | Г    |                    |
| Equipment is free of entrapments.   | Γ''  | Г    |                    |
| Equipment is safely anchored.   |      | Γ    |                    |
| Swings Swings   | Pass | Fail | Problem / Solution |
| Hardware and chains are in good condition.  | Г    | Г    |                    |
| Swings are a safe distance from other playground equipment.   | Γ    | r    | . // 1/2           |
| Swings are 24 inches apart.   | Γ-   | Г    | 1411               |
| Edges of seats are smooth and free from obstructions.   | Г    | Г    |                    |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | г    | г    |                    |

|   |             | W-2      |                    |
|---|-------------|----------|--------------------|
| Slides  | Pass        | Fail     | Problem / Solution |
| Slides are free of obstructions and protrusions.  |             | П        |                    |
| Equipped with platforms to facilitate access to the sitting position.   |             | Γ        |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 1           |          |                    |
| Average incline is less than 30 degrees.  | Г           | Г        |                    |
| Exit regions are level.   |             | Г        |                    |
| Metal slides are shaded to prevent overheating.   | Γ           | П        |                    |
| Climbing Equipment  | Pass        | Fail     | Problem / Solution |
| Hand grips are secured and do not rotate.   | 1           | П        |                    |
| Rope or chain ladders are anchored at both ends.  |             | Г        |                    |
| Foot holds/rungs are in good condition and adequately spaced.   |             | ٣        |                    |
| Seesaws Seesaws   | Pass        | Fail     | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | Г           | American |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | С           | П        | MA                 |
| Fulcrums/pivot points are free of pinch or crush hazards.   | grande<br>d | 4        |                    |
| Handholds are provided at each seating position.  | г           | Γ        |                    |
| Inspector name, signature, and completion date  |             |          |                    |
| Name: Joe Radigeel Signature: Que Roby  |             |          | Date: 1-12-23      |
| BAYFRONT  |             |          |                    |

| General Inspection   | Pass | Fail |       |              | Problem / S | Solution |                           |
|--|------|------|-------|--------------|-------------|----------|---------------------------|
| Playground area is free of litter and debris.  | 1    |      |       | n de mezon   |             |          | Albert Mark States of the |
| Playground area is free of anthills/hazardous insects or toxic plants.   | P    | lan- |       |              |             |          |                           |
| Playground area is free of holes and other tripping hazards.   | 1    | Г    |       |              |             |          |                           |
| Proper signage with rules, hours, and age- appropriate use is posted.  | Г    | г    | Signs | Arc be       | ing mal     | و        |                           |
| Playground area is properly fenced.  | Г    | Г    | 4     |              | 27          |          | 1                         |
| Self-latching gate works as designed.  | г    | ٢    |       |              |             |          |                           |
| Surfacing  | Pass | Fail |       |              | Problem / S | olution  |                           |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).  | 1/   | Γ    |       |              |             |          |                           |
| Surfacing material under and around equipment is adequate depth (6-12 inches).   |      | г    |       |              |             |          |                           |
| Surfacing material is free of glass, debris, or other foreign objects.   | 1    | Г    |       |              |             |          |                           |
| Surfacing material is not compacting or deteriorating.   |      | Г    |       |              |             |          |                           |
| Rubber wear mats are used under high-traffic-use areas and are in good condition   | r    | г    | N/A   |              |             | ž.       |                           |
| Proper drainage prevents water from forming puddles.   | 1/   | Г    |       |              |             |          |                           |
| Equipment Hazards  | Pass | Fail |       |              | Problem / S | olution  |                           |
| Equipment is not damaged or vandalized.  |      | Г    |       |              |             |          |                           |
| Equipment is free from sharp points, corners, or edges.  |      | Г    |       |              |             |          |                           |
| Protective caps or plugs are not missing or damaged.   |      | Г    |       |              |             |          |                           |
| Equipment is free of potential clothing entanglement hazards.  | ſ    | ٢    |       |              |             |          |                           |
| Equipment free of pinch and crush points or exposed moving parts.  | Г    | Г    |       |              |             |          |                           |
| Equipment is free of rust, rot, cracks, and splinters.   |      | Г    |       |              |             |          |                           |
| Equipment is free of entrapments.  | ٢    | Г    |       |              |             |          |                           |
| Equipment is safely anchored.  | 1    | Γ    |       |              |             |          |                           |
| Swings Charles Control of the Contro | Pass | Fail |       | <b>MANUT</b> | Problem / S | olution  |                           |
| Hardware and chains are in good condition.   | Г    | Γ    |       |              |             |          |                           |
| Swings are a safe distance from other playground equipment.  | Г    | г    |       | MA           |             |          |                           |
| Swings are 24 inches apart.  | г    | Γ    |       | '/'          | 4           |          |                           |
| Edges of seats are smooth and free from obstructions.  | -    | Г    |       |              |             |          |                           |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.  | г    | г    |       |              |             |          |                           |

| Slides  | Pass   | Fail     | Problem / Solution |
|---|--------|----------|--------------------|
| Slides are free of obstructions and protrusions.  | 1      | П        |                    |
| Equipped with platforms to facilitate access to the sitting position.   | 17     | <b>C</b> |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | /      | П        |                    |
| Average incline is less than 30 degrees.  | yane.  | Г        |                    |
| Exit regions are level.   | /      | Г        |                    |
| Metal slides are shaded to prevent overheating.   | r      | r        |                    |
| Climbing Equipment  | Pass   | Fail     | Problem / Solution |
| Hand grips are secured and do not rotate.   | 17     | Г        |                    |
| Rope or chain ladders are anchored at both ends.  | 1      | Г        |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | land   | г        |                    |
| Seesaws Seesaws   | Pass   | Fail     | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | г      | Г        |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | -      | П        | 1.1/0              |
| Fulcrums/pivot points are free of pinch or crush hazards.   | r      | Г        |                    |
| Handholds are provided at each seating position.  | г      | Γ        |                    |
| Inspector name, signature, and completion date  |        |          |                    |
| Name: Joe Rodrigue? Signature: Jac Russia   |        |          | Date: 1~12-23      |
| LIGHT BEACH NEXT TO F   | Avilio | N        |                    |

| General Inspection  | Pass | Fail | Problem / Solution   |
|---|------|------|----------------------|
| Playground area is free of litter and debris.   |      | П    |                      |
| Playground area is free of anthills/hazardous insects or toxic plants.  |      | Г    |                      |
| Playground area is free of holes and other tripping hazards.  | /    | Г    |                      |
| Proper signage with rules, hours, and age- appropriate use is posted.   | г    | r    | Sings are being made |
| Playground area is properly fenced.   | Г    | Г    |                      |
| Self-latching gate works as designed.   | Γ    | П    |                      |
| Surfacing   | Pass | Fail | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). |      | I    |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  |      | r    |                      |
| Surfacing material is free of glass, debris, or other foreign objects.  | 1    | Г    |                      |
| Surfacing material is not compacting or deteriorating.  | 12   | Γ-   |                      |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  | 1    | 1    | NA                   |
| Proper drainage prevents water from forming puddles.  |      | r    |                      |
| Equipment Hazards   | Pass | Fail | Problem / Solution   |
| Equipment is not damaged or vandalized.   | 7    | Γ-   |                      |
| Equipment is free from sharp points, corners, or edges.   | 1    | Г    |                      |
| Protective caps or plugs are not missing or damaged.  | 1    | Γ    |                      |
| Equipment is free of potential clothing entanglement hazards.   | De   | Г    |                      |
| Equipment free of pinch and crush points or exposed moving parts.   | г    | Г    |                      |
| Equipment is free of rust, rot, cracks, and splinters.  |      | Г    |                      |
| Equipment is free of entrapments.   | г    | Г    |                      |
| Equipment is safely anchored.   | 1    | г    |                      |
| Swings - Swings   | Pass | Fail | Problem / Solution   |
| Hardware and chains are in good condition.  | Γ    | Γ    |                      |
| Swings are a safe distance from other playground equipment.   | г    | г    | A // A               |
| Swings are 24 inches apart.   | Г    | Г    | 10/1                 |
| Edges of seats are smooth and free from obstructions.   | Г    | г    |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | Γ    | Г    |                      |

(To be completed monthly.)

| Slides  | Pass | Fail | Problem / Solution |
|---|------|------|--------------------|
| Slides are free of obstructions and protrusions.  |      | П    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | 17   | Г    |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | /    | П    |                    |
| Average incline is less than 30 degrees.  | Г    | Γ    |                    |
| Exit regions are level.   |      | Г    |                    |
| Metal slides are shaded to prevent overheating.   | г    | П    |                    |
| Climbing Equipment  | Pass | Fail | Problem / Solution |
| Hand grips are secured and do not rotate.   |      | П    |                    |
| Rope or chain ladders are anchored at both ends.  |      | Г    |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | /    | С    |                    |
| Seesaws Seesaws   | Pass | Fail | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | Г    | Г    |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | ļ    | Ţ.   | N/A                |
| Fulcrums/pivot points are free of pinch or crush hazards.   | Г    | Γ    |                    |
| Handholds are provided at each seating position.  | r    | r    |                    |
| Inspector name, signature, and completion date  |      |      |                    |
| Name: Joe Ropinguez  Signature: Jan Roja  |      |      | Date: 1-12-23      |
|   |      | 0.1  |                    |

LIGHT house BEACH NEXT TO SPIASH PAN

| General Inspection  | Pass | Fail                  | Problem / Solution   |
|---|------|-----------------------|----------------------|
| Playground area is free of litter and debris.   |      |                       |                      |
| Playground area is free of anthills/hazardous insects or toxic plants.  |      | Γ                     |                      |
| Playground area is free of holes and other tripping hazards.  |      | Γ                     |                      |
| Proper signage with rules, hours, and age- appropriate use is posted.   | Γ    | г                     | SIGNS HAT being made |
| Playground area is properly fenced.   | Г    | Г                     |                      |
| Self-latching gate works as designed.   | г    | П                     |                      |
| Surfacing   | Pass | Fail                  | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | F/   | 1                     |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  |      | Т                     |                      |
| Surfacing material is free of glass, debris, or other foreign objects.  | /    | Г                     |                      |
| Surfacing material is not compacting or deteriorating.  | /    | m                     |                      |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  | r    | -                     | N/A                  |
| Proper drainage prevents water from forming puddles.  | 1    | Г                     |                      |
| Equipment Hazards   | Pass | Fail                  | Problem / Solution   |
| Equipment is not damaged or vandalized.   | 1    | Г                     |                      |
| Equipment is free from sharp points, corners, or edges.   | 1    | Г                     |                      |
| Protective caps or plugs are not missing or damaged.  | 1    | F                     |                      |
| Equipment is free of potential clothing entanglement hazards.   | Г    | Г                     |                      |
| Equipment free of pinch and crush points or exposed moving parts.   | Г    | ٢                     |                      |
| Equipment is free of rust, rot, cracks, and splinters.  | Г    | Г                     |                      |
| Equipment is free of entrapments.   | r    | Γ                     |                      |
| Equipment is safely anchored.   |      | -                     |                      |
| Swings  | Pass | Fail                  | Problem / Solution   |
| Hardware and chains are in good condition.  | Г    | Γ                     |                      |
| Swings are a safe distance from other playground equipment.   | Г    | Г                     | 1 (/P                |
| Swings are 24 inches apart.   | J-   | Terror and the second | 7011                 |
| Edges of seats are smooth and free from obstructions.   | Г    | r                     |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | Γ    | Г                     |                      |

| Slides Slides  | Pass | Fail    | Problem / Solution   |
|--|------|---------|----------------------|
| Slides are free of obstructions and protrusions.   |      | п       |                      |
| Equipped with platforms to facilitate access to the sitting position.  |      | r       |                      |
| Platforms are equipped with guardrails or equivalent protective equipment.   |      | П       |                      |
| Average incline is less than 30 degrees.   | T    | 1       |                      |
| Exit regions are level.  |      | Г       |                      |
| Metal slides are shaded to prevent overheating.  | Г    | П       |                      |
| Climbing Equipment   | Pass | Fail    | Problem / Solution   |
| Hand grips are secured and do not rotate.  |      | п       |                      |
| Rope or chain ladders are anchored at both ends.   |      | r       |                      |
| Foot holds/rungs are in good condition and adequately spaced.  |      | grant g |                      |
| Seesaws "Salt And Control of the Con | Pass | Fail    | Problem / Solution   |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.   | Г    | Г       |                      |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  | r    | П       | N/A                  |
| Fulcrums/pivot points are free of pinch or crush hazards.  | r-   | Г       |                      |
| Handholds are provided at each seating position.   | Γ.   | С       |                      |
| Inspector name, signature, and completion date   |      |         |                      |
| Name: JoE Rodryvel Signature: Qa Rodz  |      |         | Date: <u>/-/2-23</u> |
| LIGHT LAKE BEACH ON BAC  | BeAC | h       |                      |

|  | P. C.  |                  |                      |
|--|--------|------------------|----------------------|
| General Inspection  Playground area is free of litter and debris.  | Pass   | Fail             | Problem / Solution   |
| Playground area is free of anthills/hazardous insects  | 1/     | ()               |                      |
| or toxic plants.   |        | П                |                      |
| Playground area is free of holes and other tripping hazards.   |        | Г                |                      |
| Proper signage with rules, hours, and age- appropriate use is posted.  | Africa | Г                | Signs Are being Made |
| Playground area is properly fenced.  | Г      | П                | -                    |
| Self-latching gate works as designed.  | r      | Г                |                      |
| Surfacing Surfac | Pass   | Fail             | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).  |        | r                |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).   |        | Name of the last |                      |
| Surfacing material is free of glass, debris, or other foreign objects.   | 7      | Г                |                      |
| Surfacing material is not compacting or deteriorating.   | 7      | Г                |                      |
| Rubber wear mats are used under high-traffic-use areas and are in good condition   | r      | in the second    |                      |
| Proper drainage prevents water from forming puddles.   | 1      | г                |                      |
| Equipment Hazards  | Pass   | Fail             | Problem / Solution   |
| Equipment is not damaged or vandalized.  |        | П                |                      |
| Equipment is free from sharp points, corners, or edges.  |        | Г                |                      |
| Protective caps or plugs are not missing or damaged.   | 1      | Г                |                      |
| Equipment is free of potential clothing entanglement hazards.  | Г      |                  |                      |
| Equipment free of pinch and crush points or exposed moving parts.  | r-     | Г                |                      |
| Equipment is free of rust, rot, cracks, and splinters.   | 1      | Г                |                      |
| Equipment is free of entrapments.  | Г      | Γ                |                      |
| Equipment is safely anchored.  | 7      | Г                |                      |
| Swings A Swings  | Pass   | Fail             | Problem / Solution   |
| Hardware and chains are in good condition.   | 1      | Γ                |                      |
| Swings are a safe distance from other playground equipment.  | *      | Г                |                      |
| Swings are 24 inches apart.  | 1      | Γ                |                      |
| Edges of seats are smooth and free from obstructions.  | 1      | Г                |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.  | 1      | г                |                      |

| Slides  | Pass  | Fail  | Problem / Solution |
|---|-------|-------|--------------------|
| Slides are free of obstructions and protrusions.  | I dob | T all | Problem / Solution |
| Equipped with platforms to facilitate access  |       |       |                    |
| to the sitting position.  |       |       |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 1     | П     |                    |
| Average incline is less than 30 degrees.  | Γ     | Г     |                    |
| Exit regions are level.   | /     | Г     |                    |
| Metal slides are shaded to prevent overheating.   | Г     |       |                    |
| Climbing Equipment  | Pass  | Fail  | Problem / Solution |
| Hand grips are secured and do not rotate.   | 5     | П     |                    |
| Rope or chain ladders are anchored at both ends.  | 1     | П     |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | /     | П     |                    |
| Seesaws Seesaws   | Pass  | Fail  | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | ~     | n     |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | 6     | г     |                    |
| Fulcrums/pivot points are free of pinch or crush hazards.   | ~     | П     |                    |
| Handholds are provided at each seating position.  | +     | П     |                    |
| Inspector name, signature, and completion date  |       |       |                    |
| Name: Joe Rodriguez Signature: Rodge  |       |       | Date: 1-13-23      |
| George Adam's Park  |       |       |                    |

| Slides Slides   | Pass  | Fail | Problem / Solution |
|---|-------|------|--------------------|
| Slides are free of obstructions and protrusions.  | 1     | П    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | /     | п    |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 1/    | 0    |                    |
| Average incline is less than 30 degrees.  | Г     | П    |                    |
| Exit regions are level.   | 1     |      |                    |
| Metal slides are shaded to prevent overheating.   | Γ     | n    |                    |
| Climbing Equipment  | Pass  | Fail | Problem / Solution |
| Hand grips are secured and do not rotate.   |       | П    |                    |
| Rope or chain ladders are anchored at both ends.  |       | *    |                    |
| Foot holds/rungs are in good condition and adequately spaced.   |       | Г    |                    |
| Seesaws Seesaws   | Pass  | Fail | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | г     | г    |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | П     | П    | N/A                |
| Fulcrums/pivot points are free of pinch or crush hazards.   | г     | П    |                    |
| Handholds are provided at each seating position.  | Г     | f    |                    |
| Inspector name, signature, and completion date  |       |      |                    |
| Name: Joe Robingurz Signature: Jan Robinson   |       |      | Date: 13-23        |
| FHLOY CITY PARK NEXT ASh  | Ley + | reld |                    |

| General Inspection  | Pass | Fail    | Problem / Solution   |
|---|------|---------|----------------------|
| Playground area is free of litter and debris.   |      |         | 1 - OBJETH 1 BOILDON |
| Playground area is free of anthills/hazardous insects or toxic plants.  |      | Г       |                      |
| Playground area is free of holes and other tripping hazards.  | /    | Г       |                      |
| Proper signage with rules, hours, and age- appropriate use is posted.   | 17   | П       |                      |
| Playground area is properly fenced.   | Г    | Г       |                      |
| Self-latching gate works as designed.   | г    | П       |                      |
| Surfacing   | Pass | Fail    | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). |      | [-·     |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | /    | <u></u> |                      |
| Surfacing material is free of glass, debris, or other foreign objects.  | 1    | Г       |                      |
| Surfacing material is not compacting or deteriorating.  |      | Г       |                      |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  |      | Г       |                      |
| Proper drainage prevents water from forming puddles.  | 1    | г       |                      |
| Equipment Hazards   | Pass | Fail    | Problem / Solution   |
| Equipment is not damaged or vandalized.   | 1    | Г       |                      |
| Equipment is free from sharp points, corners, or edges.   | /    | Г       |                      |
| Protective caps or plugs are not missing or damaged.  |      | Г       |                      |
| Equipment is free of potential clothing entanglement hazards.   | E    | Г       |                      |
| Equipment free of pinch and crush points or exposed moving parts.   | r    | Г       |                      |
| Equipment is free of rust, rot, cracks, and splinters.  |      | Г       |                      |
| Equipment is free of entrapments.   |      | Г       |                      |
| Equipment is safely anchored.   | 17   |         |                      |
| Swings  | Pass | Fail    | Problem / Solution   |
| Hardware and chains are in good condition.  | Г    | г       |                      |
| Swings are a safe distance from other playground equipment.   | Γ    | П       | 1//4                 |
| Swings are 24 inches apart.   | Г    | Γ       | / 1                  |
| Edges of seats are smooth and free from obstructions.   | Г    | Г       |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | r    | г       |                      |

| Slides  | Pass   | Fail    | Problem / Solution |  |  |
|---|--------|---------|--------------------|--|--|
| Slides are free of obstructions and protrusions.  | 1      | 0       |                    |  |  |
| Equipped with platforms to facilitate access to the sitting position.   |        | П       |                    |  |  |
| Platforms are equipped with guardrails or equivalent protective equipment.  | /      |         |                    |  |  |
| Average incline is less than 30 degrees.  | П      | r       |                    |  |  |
| Exit regions are level.   |        | П       |                    |  |  |
| Metal slides are shaded to prevent overheating.   | Г      |         |                    |  |  |
| Climbing Equipment  | Pass   | Fail    | Problem / Solution |  |  |
| Hand grips are secured and do not rotate.   |        | П       |                    |  |  |
| Rope or chain ladders are anchored at both ends.  |        | 177     |                    |  |  |
| Foot holds/rungs are in good condition and adequately spaced.   | /      | П       |                    |  |  |
| Seesaws   | Pass   | Fail    | Problem / Solution |  |  |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | m      | n       |                    |  |  |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | Γ      | <u></u> | Λ //               |  |  |
| Fulcrums/pivot points are free of pinch or crush hazards.   |        | П       | 19/A               |  |  |
| Handholds are provided at each seating position.  |        | П       |                    |  |  |
| Inspector name, signature, and completion date  | ***    |         |                    |  |  |
| Name: <u>Joe Raprigar 2</u> Signature: Robert   |        |         | Date: 1-13-23      |  |  |
| Need to Build A Barrier Around the Swing Set's Neet to Tilley Rd  |        |         |                    |  |  |
| Tilley PANK NEXT TO HAIF LE   | g Leag | ue R    | d<br>              |  |  |

|   |      | Street of the |                      |
|---|------|---------------|----------------------|
| General Inspection  | Pass | Fail          | Problem / Solution   |
| Playground area is free of litter and debris.   |      |               |                      |
| Playground area is free of anthills/hazardous insects or toxic plants.  |      | П             |                      |
| Playground area is free of holes and other tripping hazards.  |      |               |                      |
| Proper signage with rules, hours, and age- appropriate use is posted.   | Г    | П             | Signs are being made |
| Playground area is properly fenced.   |      |               |                      |
| Self-latching gate works as designed.   |      |               |                      |
| Surfacing   | Pass | Fail          | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). |      | m             |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  |      | П             |                      |
| Surfacing material is free of glass, debris, or other foreign objects.  | 1    |               |                      |
| Surfacing material is not compacting or deteriorating.  |      | П             | -                    |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  |      | -             |                      |
| Proper drainage prevents water from forming puddles.  | P/   | n             |                      |
| Equipment Hazards   | Pass | Fail          | Problem / Solution   |
| Equipment is not damaged or vandalized.   |      | П             |                      |
| Equipment is free from sharp points, corners, or edges.   |      | Г             |                      |
| Protective caps or plugs are not missing or damaged.  | 1    | Г             |                      |
| Equipment is free of potential clothing entanglement hazards.   | Г    | Г             |                      |
| Equipment free of pinch and crush points or exposed moving parts.   | Г.   | Г             |                      |
| Equipment is free of rust, rot, cracks, and splinters.  |      |               |                      |
| Equipment is free of entrapments.   | г    | Г             |                      |
| Equipment is safely anchored.   |      | П             |                      |
| Swings Swings   | Pass | Fail          | Problem / Solution   |
| Hardware and chains are in good condition.  | 1    | Γ             |                      |
| Swings are a safe distance from other playground equipment.   | 1    | П             |                      |
| Swings are 24 inches apart.   | 9    | r             |                      |
| Edges of seats are smooth and free from obstructions.   | 1    | Г             |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | 1    | Г             |                      |

|   | The Control of the Co |      |                    |
|---|--|------|--------------------|
| Slides  | Pass   | Fail | Problem / Solution |
| Slides are free of obstructions and protrusions.  | V  | П    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | 1  | Г    |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | /  | С    |                    |
| Average incline is less than 30 degrees.  | F  | Г    |                    |
| Exit regions are level.   |  |      |                    |
| Metal slides are shaded to prevent overheating.   | С  |      |                    |
| Climbing Equipment  | Pass   | Fail | Problem / Solution |
| Hand grips are secured and do not rotate.   | 1  | П    |                    |
| Rope or chain ladders are anchored at both ends.  | 1  | П    |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | 1  | П    |                    |
| Seesaws Seesaws   | Pass   | Fail | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | 1""  | п    |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | Г  | П    | 1 // 0             |
| Fulcrums/pivot points are free of pinch or crush hazards.   | г  | П    | /V/P               |
| Handholds are provided at each seating position.  | Г  | Г    |                    |
| Inspector name, signature, and completion date  |  |      |                    |
| Name: Joe Rodrigues Signature: Jan Rub  |  |      | Date: 1-13-23      |
| WILSON PARK   |  |      |                    |

| General Inspection  | Pass | Fail | Problem / Solution                          |
|---|------|------|---|
| Playground area is free of litter and debris.   |      |      | 11 Objetti 1 Solution                       |
| Playground area is free of anthills/hazardous insects or toxic plants.  | /    | r    |   |
| Playground area is free of holes and other tripping hazards.  | /    | П    |   |
| Proper signage with rules, hours, and age- appropriate use is posted.   | Г    | r"   | Signs All being MALE                        |
| Playground area is properly fenced.   | Г    | 4    |   |
| Self-latching gate works as designed.   | Г    | П    |   |
| Surfacing   | Pass | Fail | Problem / Solution                          |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). |      | Г    |   |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | 12/  | 2000 |   |
| Surfacing material is free of glass, debris, or other foreign objects.  | /    | Г    |   |
| Surfacing material is not compacting or deteriorating.  | /    | Г    |   |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  | pri- | г    |   |
| Proper drainage prevents water from forming puddles.  | г    | Г    |   |
| Equipment Hazards   | Pass | Fail | Problem / Solution                          |
| Equipment is not damaged or vandalized.   |      | Г    |   |
| Equipment is free from sharp points, corners, or edges.   | 1    | Г    |   |
| Protective caps or plugs are not missing or damaged.  | 7    | ٢    |   |
| Equipment is free of potential clothing entanglement hazards.   | ٢    | Г    |   |
| Equipment free of pinch and crush points or exposed moving parts.   | Г    | Г    |   |
| Equipment is free of rust, rot, cracks, and splinters.  | -    | F    |   |
| Equipment is free of entrapments.   | ٢    | Г    |   |
| Equipment is safely anchored.   | 17   | Г    |   |
| Swings Swings   | Pass | Fail | Problem / Solution                          |
| Hardware and chains are in good condition.  | 1/   | г    |   |
| Swings are a safe distance from other playground equipment.   | 1/   | г    |   |
| Swings are 24 inches apart.   | 12   | -    |   |
| Edges of seats are smooth and free from obstructions.   |      | Г    |   |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | P"   | T 1  | leed to build Barrier Around The Swing ScTs |

| Slides  | Pass | Fail    | Problem / Solution |
|---|------|---------|--------------------|
| Slides are free of obstructions and protrusions.  |      |         |                    |
| Equipped with platforms to facilitate access to the sitting position.   |      | m       |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  |      | Г       |                    |
| Average incline is less than 30 degrees.  | Г    | Г       |                    |
| Exit regions are level.   |      |         |                    |
| Metal slides are shaded to prevent overheating.   |      | П       |                    |
| Climbing Equipment  | Pass | Fail    | Problem / Solution |
| Hand grips are secured and do not rotate.   | 6    | П       |                    |
| Rope or chain ladders are anchored at both ends.  |      | П       |                    |
| Foot holds/rungs are in good condition and adequately spaced.   |      | г       |                    |
| Seesaws Seesaws   | Pass | Fail    | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  |      | г       |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. |      | -       |                    |
| Fulcrums/pivot points are free of pinch or crush hazards.   |      | guette. |                    |
| Handholds are provided at each seating position.  | -    | П       |                    |
| Inspector name, signature, and completion date  |      |         |                    |
| Name: Joe Rodriguez Signature: Ja Rodyn   |      |         | Date: 1-12-23      |
| CLARET Crossins PANK  |      |         |                    |

| General Inspection  | Pass | Fail | Problem / Solution   |
|---|------|------|----------------------|
| Playground area is free of litter and debris.   | 1    |      |                      |
| Playground area is free of anthills/hazardous insects or toxic plants.  | 7    | П    |                      |
| Playground area is free of holes and other tripping hazards.  | 1    | Г    | Sings are being made |
| Proper signage with rules, hours, and age- appropriate use is posted.   | r    | Г    | Sign Are being made  |
| Playground area is properly fenced.   | Е    | -    |                      |
| Self-latching gate works as designed.   | г    | Γ    |                      |
| Surfacing   | Pass | Fail | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). |      | Γ    |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | 1    | Г    |                      |
| Surfacing material is free of glass, debris, or other foreign objects.  | 1    | Г    |                      |
| Surfacing material is not compacting or deteriorating.  |      | Г    |                      |
| Rubber wear mats are used under high-traffic-use areas and are in good condition  | /    | г    |                      |
| Proper drainage prevents water from forming puddles.  | 1    | r    |                      |
| Equipment Hazards   | Pass | Fail | Problem / Solution   |
| Equipment is not damaged or vandalized.   | 1    | Г    |                      |
| Equipment is free from sharp points, corners, or edges.   |      | Г    |                      |
| Protective caps or plugs are not missing or damaged.  |      | -    |                      |
| Equipment is free of potential clothing entanglement hazards.   | ۲    | Г    |                      |
| Equipment free of pinch and crush points or exposed moving parts.   | Γ-   | ·    |                      |
| Equipment is free of rust, rot, cracks, and splinters.  |      | Г    |                      |
| Equipment is free of entrapments.   | г    | Г    |                      |
| Equipment is safely anchored.   | 1    | П    |                      |
| Swings Swings   | Pass | Fail | Problem / Solution   |
| Hardware and chains are in good condition.  |      | Г    |                      |
| Swings are a safe distance from other playground equipment.   | 1    | -    |                      |
| Swings are 24 inches apart.   | T.   | Г    |                      |
| Edges of seats are smooth and free from obstructions.   | 1    | -    |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               |      | Γ    |                      |

| General Inspection   | Pass | Fail |        | Problem / Solution |  |
|--|------|------|--------|--------------------|--|
| Playground area is free of litter and debris.  | /    |      |        |                    | and the second second second   |
| Playground area is free of anthills/hazardous insects or toxic plants.   | 1    | Г    |        |                    |  |
| Playground area is free of holes and other tripping hazards.   | [    | D    |        |                    |  |
| Proper signage with rules, hours, and age- appropriate use is posted.  | г    | г    | SIGNUS | Are being made     |  |
| Playground area is properly fenced.  | Г    | 1    |        |                    | Marie Salvado, and |
| Self-latching gate works as designed.  | г    | T    |        |                    |  |
| Surfacing  | Pass | Fail |        | Problem / Solution |  |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).  |      | g.   |        |                    |  |
| Surfacing material under and around equipment is adequate depth (6-12 inches).   |      | Г    |        |                    |  |
| Surfacing material is free of glass, debris, or other foreign objects.   |      | Г    |        |                    |  |
| Surfacing material is not compacting or deteriorating.   |      |      |        |                    |  |
| Rubber wear mats are used under high-traffic-use areas and are in good condition   | 1    | Γ-   |        |                    |  |
| Proper drainage prevents water from forming puddles.   | 1    | П    |        |                    |  |
| Equipment Hazards  | Pass | Fail |        | Problem / Solution |  |
| Equipment is not damaged or vandalized.  |      | П    |        |                    |  |
| Equipment is free from sharp points, corners, or edges.  | 1    | No.  |        |                    |  |
| Protective caps or plugs are not missing or damaged.   |      | Γ    |        |                    |  |
| Equipment is free of potential clothing entanglement hazards.  | Г    | g*** |        |                    |  |
| Equipment free of pinch and crush points or exposed moving parts.  | Г    | Г    |        |                    |  |
| Equipment is free of rust, rot, cracks, and splinters.   | 1    | Г    |        |                    |  |
| Equipment is free of entrapments.  | m    | r    |        |                    |  |
| Equipment is safely anchored.  | 1    |      |        |                    |  |
| Swings Company of the | Pass | Fail |        | Problem / Solution |  |
| Hardware and chains are in good condition.   | 1    | Г    |        |                    |  |
| Swings are a safe distance from other playground equipment.  | 17   | Г    |        |                    | Ÿ  |
| Swings are 24 inches apart.  | 1    | Γ    |        |                    |  |
| Edges of seats are smooth and free from obstructions.  | 1    | r    |        |                    |  |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.  | +    | _    |        |                    |  |

| Slides Slides   | Pass | Fail | Problem / Solution |
|---|------|------|--------------------|
| Slides are free of obstructions and protrusions.  | 7    | П    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | 1    | п    |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  |      | Б    |                    |
| Average incline is less than 30 degrees.  |      | П    |                    |
| Exit regions are level.   | 1/   | П    |                    |
| Metal slides are shaded to prevent overheating.   | ľ    | П    |                    |
| Climbing Equipment  | Pass | Fail | Problem / Solution |
| Hand grips are secured and do not rotate.   |      | П    |                    |
| Rope or chain ladders are anchored at both ends.  |      | П    |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | /    | п    |                    |
| Seesaws Seesaws   | Pass | Fail | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | Г    | П    |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | Γ    |      | N/A                |
| Fulcrums/pivot points are free of pinch or crush hazards.   | ~    | О    |                    |
| Handholds are provided at each seating position.  | П    | п    |                    |
| Inspector name, signature, and completion date  |      |      |                    |
| Name: Joe Rodrigues Signature: Ja Rod.  |      |      | Date: 1-12-23      |
| BUTTERFLY PARK  |      |      |                    |