	Ouc	1	and the desired		1	February)	
General Inspection	Pa	ess	Fail			Problem / Solution	
Playground area is free of litter and debris.	,		1-				
Playground area is free of anthills/hazardous insect or toxic plants.	:S		Г				
Playground area is free of holes and other tripping hazards.	Ŀ		P				
Proper signage with rules, hours, and age- appropriate use is posted.	P		٢		-		
Playground area is properly fenced.	Г		Γ'	N/A			
Self-latching gate works as designed.	i-		F	W/A			
Surfacing	Pa	SS	Fail	W/ 14		Problem / Solution	
Approved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	,		F			, repletif Solution	
Surfacing material under and around equipment is adequate depth (6-12 inches).			Γ	NIA			
Surfacing material is free of glass, debris, or other foreign objects.	0		г	70/14			
Surfacing material is not compacting or deteriorating.	>						
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F			1\4			-
Proper drainage prevents water from forming puddles.	5	1	-	<i>N</i> /4			18
Equipment Hazards	Pass	F	ail			Problem / Solution	
Equipment is not damaged or vandalized.	F	-	DER ST			Linguism (Solution	
Equipment is free from sharp points, corners, or edges.	0	 -					
rotective caps or plugs are not missing or damaged.	· F	, ,	·	U/A			
Equipment is free of potential clothing entanglement hazards.	-	Г		U/K			
quipment free of pinch and crush points or exposed moving parts.	-	Г					
Equipment is free of rust, rot, cracks, and splinters.	7	, __	+				
Equipment is free of entrapments.	1	/ [\dashv				
Equipment is safely anchored.	F-	Г	+				
Swings	Pass	Fai				roblem / Solution	
Hardware and chains are in good condition.	Г	Г)/A			
Swings are a safe distance from other playground equipment.	Г	Γ) //			
Swings are 24 inches apart.	Г	Г	1	1//			
Edges of seats are smooth and free from obstructions.	F	Г		1/1			
lequate depths of surfacing material extend out a inimum distance of twice the height of the swing.	-	Γ	N	/ <u>A</u> /A			
			1				1

light House solash Do	acl		
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	Γ	T 19/4	
Equipped with platforms to facilitate access to the sitting position.	r-		
Platforms are equipped with guardrails or equivalent protective equipment.	1	- 11/h	
Average incline is less than 30 degrees.	Г		
Exit regions are level.	ľ		
Metal slides are shaded to prevent overheating.		N/4	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		E 1771	Froblem / Solution
Rope or chain ladders are anchored at both ends.	г		
Foot holds/rungs are in good condition and adequately spaced.	Γ-	N/A	
	A STATE OF THE PARTY OF THE PAR	10///	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail Al/A	Problem / Solution
Seesaws are free of cracks, corrosion		Fail F N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	-	Fail N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	r	Fail N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	Fail N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	Fail N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position. Inspector name, signature, and completion date	r	Fail N/A N/A N/A	Problem / Solution Date: 2/18/25

light House Dovillo	M	40.00	· Yaraund	
General Inspection	AL ASS	ss F	ail T	Problem / Solution
Playground area is free of litter and debris.	P	1	-	1 STATE OF STATE OF
Playground area is free of anthills/hazardous insects or toxic plants.	S P	Г	-	
Playground area is free of holes and other tripping hazards.	P			
Proper signage with rules, hours, and age- appropriate use is posted.	0	-		
Playground area is properly fenced.	Г	T	N/A	
Self-latching gate works as designed.	i-	Г		
Surfacing	Pas	s Fa	THE PERSON OF TH	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	100			. Toblem / Solution
Surfacing material under and around equipment is adequate depth (6-12 inches).	100	Г		
Surfacing material is free of glass, debris, or other foreign objects.	-/	Г		
Surfacing material is not compacting or deteriorating.	1	F		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	. 1/4	
Proper drainage prevents water from forming puddles.	-	Г	N/A	
Equipment Hazards	Pass	Fail	THE RESIDENCE OF THE PARTY OF T	Problem / Solution
Equipment is not damaged or vandalized.		/ [
Equipment is free from sharp points, corners, or edges.	/	Г		
Protective caps or plugs are not missing or damaged.	-,-	r	JA	
Equipment is free of potential clothing entanglement hazards.		Г	N/A	
quipment free of pinch and crush points or exposed moving parts.		/ F		
Equipment is free of rust, rot, cracks, and splinters.	14	<u></u>		
Equipment is free of entrapments.	1	Г		
Equipment is safely anchored.	F	Г		
Swings	Pass	Fail		Problem / Solution
Hardware and chains are in good condition.	Г	Г	AJ/A	Li anemi / Solution
Swings are a safe distance from other playground equipment.	г	Г	AI/A	
Swings are 24 inches apart.	г	Г	. + / /	
Edges of seats are smooth and free from obstructions.	-	г	N//t	
dequate depths of surfacing material extend out a inimum distance of twice the height of the swing.	F	Г	1//	

light House Pavillon 1	Dlaya	Youn	d	
Slides	Pass			Problem / Solution
Slides are free of obstructions and protrusions.	-			
Equipped with platforms to facilitate access to the sitting position.	/	Г		
Platforms are equipped with guardrails or equivalent protective equipment.		Г		
Average incline is less than 30 degrees.		Г		
Exit regions are level.	1	Г		
Metal slides are shaded to prevent overheating.	Г	Г	NIA	
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	12	Г		
Rope or chain ladders are anchored at both ends.	F-	/ 「		
Foot holds/rungs are in good condition and adequately spaced.	13	г		
	OF THE PARTY OF THE			
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail r	AJA	Problem / Solution
Seesaws are free of cracks, corrosion,			N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	Г	N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	Г	N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	г г	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	г г	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	г г	N/A N/A N/A	Problem / Solution Date:

General Inspection	CUY	200		
		Pas	s Fa	Pushbar (C. L.)
Playground area is free of litter and debris.		5/	, ,-	Il Problem / Solution
Playground area is free of anthills/hazardous insec or toxic plants.	its	7	Г	
Playground area is free of holes and other tripping hazards.		Г	ID/	
Proper signage with rules, hours, and age- appropriate use is posted.			Г	
Playground area is properly fenced.	-	г	+-	N/A
Self-latching gate works as designed.		F ^r	+-	
Surfacing	i:	ass	Fail	A)/ A Problem / Solution
Approved surfacing material is used (i.e. solid rubbe artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	r,	r	Z	Rubber Deeling off
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	Г	WIA
Surfacing material is free of glass, debris, or other foreign objects.		1	г	
Surfacing material is not compacting or deteriorating		Γ	Г	Dalaniandia
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		r	Г	NA
Proper drainage prevents water from forming puddles.	,	-	Г	N/A
Equipment Hazards	Pa	LSS.	Fail	Problem / Solution
Equipment is not damaged or vandalized.	P		F	. I Oblem / Solution
Equipment is free from sharp points, corners, or edges.	ı	-	Γ	Rust paints
Protective caps or plugs are not missing or damaged.	F	-	r-	N/A
Equipment is free of potential clothing entanglement hazards.	1		г	Rust
Equipment free of pinch and crush points or exposed moving parts.	F		г	Nug!
Equipment is free of rust, rot, cracks, and splinters.	-		_	Rust all was
Equipment is free of entrapments.	Г		Г	Rust all over
Equipment is safely anchored.	1	\dashv	Г	
Swings	Pas	S	Fail	Problem / Solution
Hardware and chains are in good condition.	[2		, _	Troblem / Solution
Swings are a safe distance from other playground equipment.			/ Γ	
Swings are 24 inches apart.	I-		Г	
Edges of seats are smooth and free from obstructions.	1		-	
dequate depths of surfacing material extend out a ninimum distance of twice the height of the swing.	1	1	г	

Butterfly playground	y		
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.			
Equipped with platforms to facilitate access to the sitting position.	15/		
Platforms are equipped with guardrails or equivalent protective equipment.	[/		
Average incline is less than 30 degrees.	F.	П	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.	С	· Plustic	Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	P	П	
Rope or chain ladders are anchored at both ends.	п	~ N/A	
Foot holds/rungs are in good condition and adequately spaced.	F		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			
and other obvious structural defects.	Г	N/A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	// N/A	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		n	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	п	n	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	г	n	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	г	n	

Claret Crossing Dork			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	10	Г	
Equipped with platforms to facilitate access to the sitting position.	-	Г	
Platforms are equipped with guardrails or equivalent protective equipment.		Г	
Average incline is less than 30 degrees.	F	Г	
Exit regions are level.			
Metal slides are shaded to prevent overheating.	-	Е	Questic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	10	/ _	
Rope or chain ladders are anchored at both ends.		, r	
Foot holds/rungs are in good condition and adequately spaced.	7	Г	
Seesaws	Pass	Fail	Problem / Solution
	A		
Seesaws are free of cracks, corrosion, and other obvious structural defects.	le le	Г	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		г Г	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		г / /	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch		Г / / г	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.		Г /Г	

Baytront Playarous	rd	la	3	peller
General Inspection		ASSESSED FOR STREET	ail	Problem / Solution
Playground area is free of litter and debris.	1 ,	/	r-	
Playground area is free of anthills/hazardous insect or toxic plants.	S		Γ	
Playground area is free of holes and other tripping hazards.	F		г	
Proper signage with rules, hours, and age- appropriate use is posted.	F			
Playground area is properly fenced.	Г	. ,	-	AVA
Self-latching gate works as designed.	i-		-	NIA
Surfacing	Pa	ss F	ail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	9	-	-	· TOBLETT SOINTION
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г		
Surfacing material is free of glass, debris, or other foreign objects.	P	Г	7	
Surfacing material is not compacting or deteriorating.	1	F	\dashv	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-/	-		
Proper drainage prevents water from forming puddles.	-	1 -		N/A
Equipment Hazards	Pas	Fai		Problem / Solution
Equipment is not damaged or vandalized.	1	-		1. Toblem / Solution
Equipment is free from sharp points, corners, or edges.	P	Г		
Protective caps or plugs are not missing or damaged.	r-	r		N/A
Equipment is free of potential clothing entanglement hazards.	1	Г	1	
quipment free of pinch and crush points or exposed moving parts.	+	Г	1	
Equipment is free of rust, rot, cracks, and splinters.	Г	\ r	V	minor rust
Equipment is free of entrapments.	1			10101 115
Equipment is safely anchored.	F	Г	+	
Swings	Pass	Fail	700	Problem / Solution
Hardware and chains are in good condition.	_	Г		A A A A A A A A A A A A A A A A A A A
Swings are a safe distance from other playground equipment.	Г	Г) / A
Swings are 24 inches apart.	Г	Г	1	1/4
Edges of seats are smooth and free from obstructions.	Г	Г	1	1)/A
dequate depths of surfacing material extend out a inimum distance of twice the height of the swing.	Г	Γ	1	D/A
The state of the s				1

Port Lavaca Playground Safety Checklist (To be completed monthly.)

Baytrant Olayaroun	d	la	Belle
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	17	Г	
Equipped with platforms to facilitate access to the sitting position.	-	г	
Platforms are equipped with guardrails or equivalent protective equipment.	T	Г	
Average incline is less than 30 degrees.	Г	, г	N/A
Exit regions are level.		Е	
Metal slides are shaded to prevent overheating.	Ė	Г	Dlastic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	P	Г	
Rope or chain ladders are anchored at both ends.	Г	Г	1)/A
Foot holds/rungs are in good condition and adequately spaced.		Г	
	A STATE OF THE PARTY OF THE PAR	THE STATE OF	
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail r	Problem / Solution
Seesaws are free of cracks, corrosion.			
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	Г	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	r	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г	г г	

(To be completed monthly:

City Park

CHY Park					-
General Inspection	Pa	ss Fa	il	Problem / Solution	
Playground area is free of litter and debris.	7		0.	2.3.t., Solution	
Playground area is free of anthills/hazardous insects or toxic plants.	17	Г			
Playground area is free of holes and other tripping hazards.	-	7			
Proper signage with rules, hours, and age- appropriate use is posted.	[2	г			
Playground area is properly fenced.	Г	F		NA	
Self-latching gate works as designed.	Г	Г		N/A	
Surfacing	Pas	s Fai		Problem / Solution	
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	Г		· · · · · · · · · · · · · · · · · · ·	
Surfacing material under and around equipment is adequate depth (6-12 inches).	-/	Г			
Surfacing material is free of glass, debris, or other foreign objects.	/	Г			
Surfacing material is not compacting or deteriorating.	Г	Г	1,	U/A	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г			N/A	
Proper drainage prevents water from forming puddles.	,_/	Г		N/A	
Equipment Hazards	Pass	Fail		Problem / Solution	
Equipment is not damaged or vandalized.	1	:		. i edicini dolation	2 1916
Equipment is free from sharp points, corners, or edges.	+	Г			
Protective caps or plugs are not missing or damaged.	Γ-	г	1 A b	I/A	
Equipment is free of potential clothing entanglement hazards.	-	г	70/		
quipment free of pinch and crush points or exposed moving parts.		, [
Equipment is free of rust, rot, cracks, and splinters.	F-	/			
Equipment is free of entrapments.	[/	Г			
Equipment is safely anchored.	1	Г	· ·		
Swings	Pass	Fail		Problem / Solution	
Hardware and chains are in good condition.	1	Г		1. GBIGHT GOIGHOIT	
Swings are a safe distance from other playground equipment.	-/	Г			\dashv
Swings are 24 inches apart.	17	Г			
Edges of seats are smooth and free from obstructions.	-	г			
dequate depths of surfacing material extend out a ninimum distance of twice the height of the swing.		_			
					1

(To be completed monthly.)

City Dark

Slides	Pass Fail Problem / Solution
Slides are free of obstructions and protrusions.	T TODIETT / Solution
Equipped with platforms to facilitate access to the sitting position.	
Platforms are equipped with guardrails or equivalent protective equipment.	r r
Average incline is less than 30 degrees.	5/ 5 N/A
Exit regions are level.	1, 5
Metal slides are shaded to prevent overheating.	- Plastic Slides
Climbing Equipment	
Hand grips are secured and do not rotate.	Pass Fail Problem / Solution
Rope or chain ladders are anchored at both ends.	1/5
Foot holds/rungs are in good condition and adequately spaced.	7 -
Seesaws	Pass Fail Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Froblem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	
Fulcrums/pivot points are free of pinch or crush hazards.	- M/K
Handholds are provided at each seating position.	T N/A
Inspector name, signature, and completion date	70/7
Name: Douglas Compio	Date: _Z()8(75

C'ASA O N. E				d monthly.)
City Park By Ash				es
General Inspection	Pa	iss F	ail	Problem / Solution
Playground area is free of litter and debris. Playground area is free of anthills/hazardous insects		//	<u> </u>	
or toxic plants.	S r		Γ	
Playground area is free of holes and other tripping hazards.	Г		4	
Proper signage with rules, hours, and age- appropriate use is posted.	I.		-	
Playground area is properly fenced.	Г		-	47//
Self-latching gate works as designed.	r	-	-	11/15
Surfacing	Pa	ss Fa	H:	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	P			. Tobletti / Solution
Surfacing material under and around equipment is adequate depth (6-12 inches).	10	1		
Surfacing material is free of glass, debris, or other foreign objects.	la de	Г		
Surfacing material is not compacting or deteriorating.	1	7	\top	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F/	-		
Proper drainage prevents water from forming puddles.	-	Г		NA
Equipment Hazards	Pass	Fail	STREET, SQUARE	Problem / Solution
Equipment is not damaged or vandalized.	-	 		1 Constant Solution
Equipment is free from sharp points, corners, or edges.	7	Г	\dagger	
Protective caps or plugs are not missing or damaged.	r	/_	1.	1/ /
Equipment is free of potential clothing entanglement hazards.	/	/-	1	V/A
equipment free of pinch and crush points or exposed moving parts.	5	Г	T	
Equipment is free of rust, rot, cracks, and splinters.	٢	-	1.0	2000
Equipment is free of entrapments.	Г	Г	T V	ninor rust
Equipment is safely anchored.	Г	Г	-	
Swings	Pass	Fail		Purchland (Cataly)
Hardware and chains are in good condition.	Г	Г	1	Problem / Solution
Swings are a safe distance from other playground equipment.	_	Г	1	1/ //
Swings are 24 inches apart.	Г	Г	^\	1/1
Edges of seats are smooth and free from obstructions.	г	г	,	1/A
dequate depths of surfacing material extend out a ninimum distance of twice the height of the swing.	F	г	A 1	1/4
			10	

CITY PATR DY ASHIEV	tields	
Slides	Pass Fail	Problem / Solution
Slides are free of obstructions and protrusions.	F	Trobletti/ Solution
Equipped with platforms to facilitate access to the sitting position.	7	
Platforms are equipped with guardrails or equivalent protective equipment.	1,5	
Average incline is less than 30 degrees.	7/1	
Exit regions are level.	r/ r	
Metal slides are shaded to prevent overheating.	- Dastic	Slides
Climbing Equipment	Pass Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	1 Tobletti / Solution
Rope or chain ladders are anchored at both ends.	1/5	
Foot holds/rungs are in good condition and adequately spaced.	· -	
Seesaws	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	r r	. r oblem / Solderon
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г г Д/Д	
Fulcrums/pivot points are free of pinch or crush hazards.	- N/A	
Handholds are provided at each seating position.	Γ Γ Δ)/Δ	
Inspector name, signature, and completion date	70 / A	-
Name: Douglas Carpio		Date: 218(25

Wilson Park			
General Inspection	Pa	ss Fail	Problem / Solution
Playground area is free of litter and debris.	120		Froblem / Solution
Playground area is free of anthills/hazardous insect or toxic plants.	S i	1	
Playground area is free of holes and other tripping hazards.	/	1	
Proper signage with rules, hours, and age- appropriate use is posted.	1	Г	
Playground area is properly fenced.	Г	Г	W/A
Self-latching gate works as designed.	I-	F	N/A
Surfacing	Pas	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	,	Г	. Toblem / Solution
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	NA
Proper drainage prevents water from forming puddles.	-	Г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	F	Obtem / Solution
Equipment is free from sharp points, corners, or edges.	1	Г.	
Protective caps or plugs are not missing or damaged.	1	r	
Equipment is free of potential clothing entanglement hazards.	7	/ [
Equipment free of pinch and crush points or exposed moving parts.	1	г	
Equipment is free of rust, rot, cracks, and splinters.	Г	7-	Minor rust
Equipment is free of entrapments.	14	Γ	Maldandaush
Equipment is safely anchored.	F-/	Г	AAT BOOK STATES
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	[-//	Г	1 1 aprietti 1, 201fifioti
Swings are a safe distance from other playground equipment.	F	F	
Swings are 24 inches apart.	i-	Г	
Edges of seats are smooth and free from obstructions.	1	-	
dequate depths of surfacing material extend out a ninimum distance of twice the height of the swing.	7	г	

(To be completed monthly.)

Wilson Park

Slides	Pass	Fai	il Problem / Solution
Slides are free of obstructions and protrusions.	5	/ [i resienti solution
Equipped with platforms to facilitate access to the sitting position.	Г	1	
Platforms are equipped with guardrails or equivalent protective equipment.		г	
Average incline is less than 30 degrees.	Г/	· r	NIA
Exit regions are level.	1	r r	
Metal slides are shaded to prevent overheating.	۲	r	Plastic Sticles
Climbing Equipment	Pass	Fail	
Hand grips are secured and do not rotate.	P/	Г	i i obiem / Solution
Rope or chain ladders are anchored at both ends.	Tr.	7 -	
Foot holds/rungs are in good condition and adequately spaced.	1	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	r	Γ	W/A
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Γ	Г	A)/A
Fulcrums/pivot points are free of pinch or crush hazards.	Г	F	11/4
Handholds are provided at each seating position.	<u></u>	T	A) [B
Inspector name, signature, and completion date			-N(A
Name: Doinglas Carpio			Date: 2/18/25

				Language and the second se
George Adams	Par	K		
General Inspection	P	ass F	ail	Problem / Solution
Playground area is free of litter and debris.		//	1	
Playground area is free of anthills/hazardous insec or toxic plants.	its		Г	
Playground area is free of holes and other tripping hazards.	F		г	
Proper signage with rules, hours, and age- appropriate use is posted.	l _e	/	-	
Playground area is properly fenced.	Г	- 1	WIA	
Self-latching gate works as designed.	i	- -	1-11	
Surfacing	Pa	ss Fa	CONTROL OF THE OWNER,	Problem / Solution
Approved surfacing material is used (i.e. solid rubbe artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	r, ₽	1		
Surfacing material under and around equipment is adequate depth (6-12 inches).			MANCO	much beeds to be adde
Surfacing material is free of glass, debris, or other foreign objects.	lan	Г		Which needs to be adde
Surfacing material is not compacting or deteriorating.	. 7	F		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-	ı	11/0	
Proper drainage prevents water from forming puddles.	-	T -	NA	
Equipment Hazards	Pass	s Fai	AND DESCRIPTION OF ADMINISTRATION	Problem / Solution
Equipment is not damaged or vandalized.	-	/ -		Fromew / Solution
Equipment is free from sharp points, corners, or edges.	1	\ \r		
Protective caps or plugs are not missing or damaged.		7 -		
Equipment is free of potential clothing entanglement hazards.	1	\r		
iquipment free of pinch and crush points or exposed moving parts.		Г		
Equipment is free of rust, rot, cracks, and splinters.	[]	\ -	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
Equipment is free of entrapments.	1	 	Minor	TUST
Equipment is safely anchored.	1	 		
Swings	Pass	Fail		
Hardware and chains are in good condition.	T GES	٦		Problem / Solution
Swings are a safe distance from other playground equipment.	Г	, 	,	
Swings are 24 inches apart.	F	Г		
Edges of seats are smooth and free from obstructions.	г	Γ	}	

Gorge Holams		
Slides	Pass Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7	1 Tobletti / Solution
Equipped with platforms to facilitate access to the sitting position.	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	r	
Average incline is less than 30 degrees.	r / r N/A	
Exit regions are level.	7 011	
Metal slides are shaded to prevent overheating.	r robella	Slides
Climbing Equipment	Pass Fail	Problem / Solution
Hand grips are secured and do not rotate.	d/ r	1 Lopietti / Solutioti
Rope or chain ladders are anchored at both ends.	7/1	
Foot holds/rungs are in good condition and adequately spaced.	r/ r	
Seesaws	CONTRACTOR OF THE PERSON OF TH	
	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	Pass Fail	Date: 2(18) 25

			· ·
light House Splash p		0	wyground
General Inspection	Pa	ss Fa	ail Problem / Solution
Playground area is free of litter and debris.	P	/ 1	
Playground area is free of anthills/hazardous insects or toxic plants.	5 13	Г	
Playground area is free of holes and other tripping hazards.	Г	Г	notes around the playground
Proper signage with rules, hours, and age- appropriate use is posted.	r~	Г	
Playground area is properly fenced.	Г	T-	NIA
Self-latching gate works as designed.	IT.	Г	A)/A
Surfacing	Pas	s Fai	Serve Control of the
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		·	1. CONCENT SOLUTION
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	notes around the playaround
Surfacing material is free of glass, debris, or other foreign objects.	-	Г	The around the playground
Surfacing material is not compacting or deteriorating.	-	F	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	X	Г	N/A
Proper drainage prevents water from forming puddles.	Г	 	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Г	Troblem/ Solution
Equipment is free from sharp points, corners, or edges.	12	Г	
Protective caps or plugs are not missing or damaged.	Γ	r	11/ /
Equipment is free of potential clothing entanglement hazards.	/	<u>_</u> г	N/A
quipment free of pinch and crush points or exposed moving parts.	[-/	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	1 1	
Equipment is free of entrapments.	1	/_	TUST-
Equipment is safely anchored.	P		
Swings	Pass	Fail	Problem / S. L.
Hardware and chains are in good condition.	Г	Г	Problem / Solution
Swings are a safe distance from other playground equipment.	-	г	N/A
Swings are 24 inches apart.	Г	\vdash	
Edges of seats are smooth and free from obstructions.	_	г	.1/4
dequate depths of surfacing material extend out a inimum distance of twice the height of the swing.	<u> </u>	г	N/A
		1	

hant House Solash !	and playaround	
Slides	Pass Fail Problem / Solution	2000
Slides are free of obstructions and protrusions.	Troblem Solution	
Equipped with platforms to facilitate access to the sitting position.		
Platforms are equipped with guardrails or equivalent protective equipment.	nt	
Average incline is less than 30 degrees.	T N/A	
Exit regions are level.	N/R	
Metal slides are shaded to prevent overheating.	- Plastic Slides	
Climbing Equipment	Pass Fail Problem / Solution	A STATE OF THE STA
Hand grips are secured and do not rotate.	Froblem / Solution	
Rope or chain ladders are anchored at both ends.	Γ .Γ	
Foot holds/rungs are in good condition and adequately spaced.		
Seesaws	Pass Fail Problem / Solvetion	NASCONO.
	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass Fail Problem / Solution	
Seesaws are free of cracks, corrosion	N/A	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	N/A	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	T DIA T T N/A T T N/A	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	T DIEM SOLUTION T T N/A T T N/A T T N/A	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	T DIEM SOLUTION T T N/A T T N/A T T N/A	

listal Mayor Dr. do Olay	41200		
light House Beach Plux General Inspection	Pass	of the state of the state of the	Problem / Solution
Playground area is free of litter and debris.	1 GSS	r-	Frobletti Goldtion
Playground area is free of anthills/hazardous insects or toxic plants.	T/	Г	
Playground area is free of holes and other tripping hazards.	TV.	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	TV.	Г	
Playground area is properly fenced.	Г	Г	A)/A
Self-latching gate works as designed.	г	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Г	Г	N/A
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	г	N/A
Surfacing material is free of glass, debris, or other foreign objects.	Г	г	Weeds growing around
Surfacing material is not compacting or deteriorating.	r	г	NIA
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	N/A
Proper drainage prevents water from forming puddles.	г	г	A) / A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	~	Г	
Equipment is free from sharp points, corners, or edges.	<i>\$</i>	Г	
Protective caps or plugs are not missing or damaged.	Г	Γ	N/A
Equipment is free of potential clothing entanglement hazards.	г	Γ	
Equipment free of pinch and crush points or exposed moving parts.	Г	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г/	10/	Rust on the vive ladder
Equipment is free of entrapments.	N	Γ	
Equipment is safely anchored.		Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	٢	۲	N/A
Swings are a safe distance from other playground equipment.		г	N/A
Swings are 24 inches apart.	Г	Г	N/A
Edges of seats are smooth and free from obstructions.	г	г	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	WIA

light house Beach Playard	and	
Slides	Pass Fail	Problem / Solution
Slides are free of obstructions and protrusions.	0/ 1	
Equipped with platforms to facilitate access to the sitting position.	/	
Platforms are equipped with guardrails or equivalent protective equipment.	г	
Average incline is less than 30 degrees.	r/r	
Exit regions are level.	7/-	
Metal slides are shaded to prevent overheating.	Г	
Climbing Equipment	Pass Fail	Problem / Solution
Hand grips are secured and do not rotate.	r -	
Rope or chain ladders are anchored at both ends.	r ru/A	
Foot holds/rungs are in good condition and adequately spaced.	F -	
adequately spaced.		
Seesaws	Pass Fail	Problem / Solution
	Pass Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion,		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	r N/A	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Γ Γ <i>N/</i> A	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Γ Γ <i>N/A</i> Γ Γ <i>N/A</i>	Problem / Solution

() ()			ted mortani.)
Claret crossing	DOW	15	
General Inspection	Pa	ss Fa	il Problem / Solution
Playground area is free of litter and debris.	17	Г	
Playground area is free of anthills/hazardous insect or toxic plants.	:S		
Playground area is free of holes and other tripping hazards.	P		
Proper signage with rules, hours, and age- appropriate use is posted.	9	Г	
Playground area is properly fenced.	г	Г	11/1
Self-latching gate works as designed.	r	Г	121/2
Surfacing	Pas	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	,	Г	, robletti / Solution
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	г	
Surfacing material is not compacting or deteriorating.	F	1 -	Concrete cracking
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-	г	N/A
Proper drainage prevents water from forming puddles.	-	 -	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	. Postern adultion
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	/ -	
Equipment is free of potential clothing entanglement hazards.	/	Г	
Equipment free of pinch and crush points or exposed moving parts.		/ F	
Equipment is free of rust, rot, cracks, and splinters.	7	г	
Equipment is free of entrapments.	1	/	
Equipment is safely anchored.			
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	13		T TODIEM / SOUDON
Swings are a safe distance from other playground equipment.	5/	-	
Swings are 24 inches apart.	1	F	
Edges of seats are smooth and free from obstructions.		F	
dequate depths of surfacing material extend out a ninimum distance of twice the height of the swing.		Г	
		1	1