

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

City Park (Ashley)

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	None
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Some rust on bolt bases
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input type="checkbox"/>	<input type="checkbox"/>	↑
Swings are 24 inches apart.	<input type="checkbox"/>	<input type="checkbox"/>	No Swings
Edges of seats are smooth and free from obstructions.	<input type="checkbox"/>	<input type="checkbox"/>	↓
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

City Park (Ashley)

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	None
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: Blain Carter

Signature: B Carter

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

City Park

Pavilion

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	No
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Edges of seats are smooth and free from obstructions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

City Park (Pavillion)

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	↑ None
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	↓
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: Blair Carter

Signature: *B Carter*

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Wilson Park

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	/	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	/	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	/	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	/	
Playground area is properly fenced.	<input type="checkbox"/>	/	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	/	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	/	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	/	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	/	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	<input type="checkbox"/>	
Proper drainage prevents water from forming puddles.	/	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	/	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	/	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	/	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	/	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	/	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input type="checkbox"/>	/	Minor Rust, bolts & Anchors
Equipment is free of entrapments.	/	<input type="checkbox"/>	
Equipment is safely anchored.	/	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	/	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	/	<input type="checkbox"/>	
Swings are 24 inches apart.	/	<input type="checkbox"/>	
Edges of seats are smooth and free from obstructions.	/	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	/	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Wilson Park

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	↑ None
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	↓
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: Blair Carter

Signature: *B Carter*

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

George Adams (Both Playgrounds)

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Mulch Base
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	①
Swings are a safe distance from other playground equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	② New Swingset Ordered
Swings are 24 inches apart.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Edges of seats are smooth and free from obstructions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

George Adams

(Both Playgrounds)


Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Fulcrums/pivot points are free of pinch or crush hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Handholds are provided at each seating position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: Blair Carter

Signature: 

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Baymont

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input type="checkbox"/>	<input type="checkbox"/>	No Swings
Edges of seats are smooth and free from obstructions.	<input type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Bay front

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	None
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: Blain Carter

Signature: 

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Claret Crossing

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	<i>N/A</i>
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	<i>N/A</i>
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Edges of seats are smooth and free from obstructions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Claret Crossing

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30-degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	<i>None</i>
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: *Blair Carter*

Signature: *[Signature]*

Date: *7-17-23*

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Lighthouse (Splash Playground)

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	<i>N/A</i>
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	<i>N/A</i>
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input type="checkbox"/>	<input type="checkbox"/>	<i>No Swings</i>
Edges of seats are smooth and free from obstructions.	<input type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Lighthouse (Splashpad) Playground

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	<i>None</i>
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: *Blair Carter*

Signature: *B Carter*

Date: *7-17-23*

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Lighthouse - (Beach Playground)

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is properly fenced.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Sand
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input type="checkbox"/>	<input type="checkbox"/>	None
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Rust has been painted
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input type="checkbox"/>	<input type="checkbox"/>	No / Swings
Edges of seats are smooth and free from obstructions.	<input type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing:	<input type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	None
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	

Inspector name, signature, and completion date

Name: Blair Carter

Signature: [Signature]

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

LA Beach

Pavillion

Playground

Pg 1

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	/	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	/	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	/	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	/	
Playground area is properly fenced.	<input type="checkbox"/>	/	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	/	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	/	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	/	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	/	<input type="checkbox"/>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input type="checkbox"/>	/	
Proper drainage prevents water from forming puddles.	/	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	/	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	/	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	/	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	/	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	/	<input type="checkbox"/>	
Equipment is free of rust, rot, cracks, and splinters.	/	<input type="checkbox"/>	
Equipment is free of entrapments.	/	<input type="checkbox"/>	
Equipment is safely anchored.	/	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	/	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input type="checkbox"/>	<input type="checkbox"/>	No Swings
Edges of seats are smooth and free from obstructions.	<input type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

LH Beach Pavilion Playground

Page 2

Slides	Pass	Fail	Problem / Solution
--------	------	------	--------------------

Slides are free of obstructions and protrusions.

☒

☐

Equipped with platforms to facilitate access to the sitting position.

☒

☐

Platforms are equipped with guardrails or equivalent protective equipment.

☒

☐

Average incline is less than 30 degrees.

☐

☐

Exit regions are level.

☒

☐

Metal slides are shaded to prevent overheating.

☐

☐

Climbing Equipment	Pass	Fail	Problem / Solution
--------------------	------	------	--------------------

Hand grips are secured and do not rotate.

☒

☐

Rope or chain ladders are anchored at both ends.

☒

☐

Foot holds/rungs are in good condition and adequately spaced.

☒

☐

Seesaws	Pass	Fail	Problem / Solution
---------	------	------	--------------------

Seesaws are free of cracks, corrosion, and other obvious structural defects.

☐

☐

Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.

☐

☐

Fulcrums/pivot points are free of pinch or crush hazards.

☐

☐

Handholds are provided at each seating position.

☐

☐

Inspector name, signature, and completion date

Name: Blain Carter

Signature: 

Date: 7-17-23

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Butterfly Park

pg 1

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of anthills/hazardous insects or toxic plants.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Playground area is free of holes and other tripping hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Proper signage with rules, hours, and age-appropriate use is posted.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Playground area is properly fenced.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	N/A
Self-latching gate works as designed.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is free of glass, debris, or other foreign objects.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Surfacing material is not compacting or deteriorating.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Consider future replacement
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Proper drainage prevents water from forming puddles.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free from sharp points, corners, or edges.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Protective caps or plugs are not missing or damaged.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is free of potential clothing entanglement hazards.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment free of pinch and crush points or exposed moving parts.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	surface
Equipment is free of rust, rot, cracks, and splinters.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	light rust around screwheads
Equipment is free of entrapments.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipment is safely anchored.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are a safe distance from other playground equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Swings are 24 inches apart.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Edges of seats are smooth and free from obstructions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Port Lavaca Playground Safety Checklist

(To be completed monthly.)

Butterfly Park

pg 2


Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Equipped with platforms to facilitate access to the sitting position.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Platforms are equipped with guardrails or equivalent protective equipment.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Average incline is less than 30 degrees.	<input type="checkbox"/>	<input type="checkbox"/>	
Exit regions are level.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Metal slides are shaded to prevent overheating.	<input type="checkbox"/>	<input type="checkbox"/>	

Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Rope or chain ladders are anchored at both ends.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Foot holds/rungs are in good condition and adequately spaced.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<input type="checkbox"/>	<input type="checkbox"/>	N/A
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<input type="checkbox"/>	<input type="checkbox"/>	ll
Fulcrums/pivot points are free of pinch or crush hazards.	<input type="checkbox"/>	<input type="checkbox"/>	ll
Handholds are provided at each seating position.	<input type="checkbox"/>	<input type="checkbox"/>	ll

Inspector name, signature, and completion date

Name: Blair Carter

Signature: 

Date: 7-17-23