(To be completed monthly.)

Claret Crossing

Llane Chossing			Description of the second seco
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	F	г	
Proper signage with rules, hours, and age- appropriate use is posted.	F	1	
Playground area is properly fenced.	No.	1	
Self-latching gate works as designed.	Γ.	1	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1		
Surfacing material under and around equipment is adequate depth (6-12 inches).	A	ļ.	
Surfacing material is free of glass, debris, or other foreign objects.	1	-	
Surfacing material is not compacting or deteriorating.	1		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	-	
Proper drainage prevents water from forming puddles.	K	g-	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.		г	
Equipment is free of potential clothing entanglement hazards.	7	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	1	г	
Equipment is safely anchored.	1	-	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	K	-	1
Swings are 24 inches apart.	1	r	1. %
Edges of seats are smooth and free from obstructions.	7	г	

(To be completed monthly.)

•		j. ,	,	·			
. 6	, ,		_ L	 7	,		_
•			PT	1 A.	1 C	51.7	
- 5	<b>-</b>	·U	<b>\</b>	 CA	$\mathcal{I}$	" ( )	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	F.	ָ ה	
Equipped with platforms to facilitate access to the sitting position.	<b>y</b> :	D	
Platforms are equipped with guardrails or equivalent protective equipment.	1	n	
Average incline is less than 30 degrees.	Г. /	/ П	
Exit regions are level.	7/	r,	
Metal slides are shaded to prevent overheating.	Γ	· n	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	f.	Ü	
Rope or chain ladders are anchored at both ends.	FY.	r)	
Foot holds/rungs are in good condition and adequately spaced.	7	Π 	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	7	ū	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	1	r	
Fulcrums/pivot points are free of pinch or crush hazards.	4	<u>.</u>	·
Handholds are provided at each seating position.	7	Γ,	· · · · · · · · · · · · · · · · · · ·
Inspector name, signature, and completion date			
Name: Blair Carter, Signature:			Date: 6 ~ 19 - 23
	- · · · ·		

- Some back fill areas around new sidewalls.

(To be completed monthly.)

George Adoms

George Hdoms	The Carlo	ar er i	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	П	
Playground area is free of anthills/hazardous insects or toxic plants.	1	r	
Playground area is free of holes and other tripping hazards.	1	P	
Proper signage with rules, hours, and age- appropriate use is posted.	F	1	
Playground area is properly fenced.	Г	1	
Self-latching gate works as designed.	Γ.	1	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	-	
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	la des	
Surfacing material is free of glass, debris, or other foreign objects.	1	and the second s	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		1	
Proper drainage prevents water from forming puddles.	7	g manu	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Г	
Equipment is free from sharp points, corners, or edges.	t	Г	
Protective caps or plugs are not missing or damaged.	<i>f</i> -	de la	
Equipment is free of potential clothing entanglement hazards.	F	es y	
Equipment free of pinch and crush points or exposed moving parts.	1	r	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	Some surface point needs
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	1	г	One new swingset an order
Swings are 24 inches apart.	1	-	VIII V
Edges of seats are smooth and free from obstructions.	1	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	ga man. Par	

George Adoms	. <u>.</u> .	-	,	i en
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	1	r,		
Equipped with platforms to facilitate access to the sitting position.	A	Ç		
Platforms are equipped with guardrails or equivalent protective equipment.	Ý	r,		
Average incline is less than 30 degrees.	Γ	Π		
Exit regions are level.	<b>S</b>	П		
Metal slides are shaded to prevent overheating.	<u> </u>	П		
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	<i>F</i> .	r,		
Rope or chain ladders are anchored at both ends.	1	Ū		
Foot holds/rungs are in good condition and adequately spaced.	F.	Γ:		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	1	D		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	fo.	Г		
Fulcrums/pivot points are free of pinch or crush hazards.	H.	C:		
Handholds are provided at each seating position.	15	r.		
Inspector name, signature, and completion date			· · · · · ·	
Name: Blair Conter		·		
Name: Blair Conter				Date:6 - 19 - 23

(To be completed monthly.)

Butterfly Parts.

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	,
Playground area is free of holes and other tripping hazards.	1	grant our	
Proper signage with rules, hours, and age- appropriate use is posted.	F	1	
Playground area is properly fenced.	-	1	
Self-latching gate works as designed.	F	1	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	f		
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	F	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	**	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	garan.	
Proper drainage prevents water from forming puddles.	*		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	7	1	
Protective caps or plugs are not missing or damaged.	1	f-	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Γ	f.D.
Equipment is free of rust, rot, cracks, and splinters.	Г	1	Very few rustmarks andecon
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	/	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	1	-	1 /
Swings are 24 inches apart.	1	-	-
Edges of seats are smooth and free from obstructions.	7	Г	

(To be completed monthly.)

Butterfly Park,

Duller (Lg)	:.		
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7	П	
Equipped with platforms to facilitate access to the sitting position.	T/	ū	
Platforms are equipped with guardrails or equivalent protective equipment.	S.	0	
Average incline is less than 30 degrees.	Π,	Ľ	
Exit regions are level.	1	n	
Metal slides are shaded to prevent overheating.	П	П	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	p)	П	
Rope or chain ladders are anchored at both ends.	1	- []	
Foot holds/rungs are in good condition and adequately spaced.	V	C	·.
<b>S</b> eesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П	п	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Π	Γ	N/A
Fulcrums/pivot points are free of pinch or crush hazards.	r,	ū	
Handholds are provided at each seating position.	E,	Ü	
Inspector name, signature, and completion date		·	
Name: Bloir Corter.			
Name: Bloir Corter. Signature: 2 8 Cat			Date: 6-19.23

Fit ness area, still to be done!

Lighouse Beach		Bea	ch Playground)
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	1	ŗ	
Proper signage with rules, hours, and age- appropriate use is posted.	F-	1	
Playground area is properly fenced.	anov.	1	
Self-latching gate works as designed.	game.	1	
Surfacing (	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	The second secon	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1		
Surfacing material is free of glass, debris, or other foreign objects.	1	beste	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	ļ-	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	-	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	E	Г	
Equipment is free of potential clothing entanglement hazards.	1	Γ	
Equipment free of pinch and crush points or exposed moving parts.	1	-	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	Recent repairs made
Equipment is free of entrapments.	1		
Equipment is safely anchored.	1		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	X	Г	
Swings are a safe distance from other playground equipment.		Г	1
Swings are 24 inches apart.	Г	1	No Swings
Edges of seats are smooth and free from obstructions.	r	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г		

Lighthouse: Beach Pla	401	0000	1	34			
Slides	Pass	Fail		Pr	oblem / Soluti	ion	
Slides are free of obstructions and protrusions.	1		7 •				
Equipped with platforms to facilitate access to the sitting position.	1	ņ		· · · · · · · · · · · · · · · · · · ·			
Platforms are equipped with guardrails or equivalent protective equipment.	¥	D.					
Average incline is less than 30 degrees.	o.	ū					
Exit regions are level.	1	מ				,	
Metal slides are shaded to prevent overheating.		П	:		<del>,</del>		
Climbing Equipment	Pass	Fail		Pr	oblem / Solut	on	
Hand grips are secured and do not rotate.	7	D.	:- :		,	- :	
Rope or chain ladders are anchored at both ends.	7/	П					
Foot holds/rungs are in good condition and adequately spaced.	1	ū					
Seesaws	Pass	Fail		Pr	oblem / Solut	on	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	0	G					-
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ū	<u>.</u>		N/F	7		
Fulcrums/pivot points are free of pinch or crush hazards.	<b>G</b> .	Π.					
Handholds are provided at each seating position.	ū	n				,,	
Inspector name, signature, and completion date							
Name: Blain Corter		· · ·		· 	1 10	0 -	
Name: Blain Coctor Signature: DB ett		÷ .		Date:	6-19.	23	
2							
Splashpad.	Α	/ ^	. /			Pale	
Recontrepairs; clean	ied.	/Pa	Hs 1	l con Rust	ope	1016	

Lighthouse ( Day Ro.	om	)	MI (tord young
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	5	r	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	F	
Playground area is properly fenced.	Avois	1	
Self-latching gate works as designed.	Γ.	*	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	. /		
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	e e	
Surfacing material is free of glass, debris, or other foreign objects.	1	-	
Surfacing material is not compacting or deteriorating.	1	F	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	ş	
Proper drainage prevents water from forming puddles.	1	r	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	i	
Protective caps or plugs are not missing or damaged.	1	ļ	
Equipment is free of potential clothing entanglement hazards.	1		
Equipment free of pinch and crush points or exposed moving parts.	1	<u></u>	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	a	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	ī	-	
Swings are 24 inches apart.	-	r	A1/A
Edges of seats are smooth and free from obstructions.	Г	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	F	Г	

(To be completed monthly.)

Lighthouse Day Room **Slides** Pass Fail **Problem / Solution** Slides are free of obstructions and protrusions. П Equipped with platforms to facilitate access  $\Gamma_{i}$ to the sitting position. Platforms are equipped with quardrails or equivalent 1 D protective equipment. Average incline is less than 30 degrees.  $\Gamma$  $\Box$ Exit regions are level.  $\Gamma_{i}$ Metal slides are shaded to prevent overheating. D **Climbing Equipment Pass** Fail **Problem / Solution** 1 Hand grips are secured and do not rotate. Γ. Rope or chain ladders are anchored at both ends. Ţί Foot holds/rungs are in good condition and 7 E. adequately spaced. **Seesaws Pass** Fail **Problem / Solution** Seesaws are free of cracks, corrosion.  $\Box$  $\Box$ and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch  $\Gamma$ or crush hazards. Handholds are provided at each seating position.  $\Gamma$ Inspector name, signature, and completion date Date: 6-19-23

(To be completed monthly.)

Bay front Pork

Bay front Port			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	F	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	1	f	
Playground area is properly fenced.	F	by an	N/A
Self-latching gate works as designed.	Γ.	r	NIA
Surfacing Surfac	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	M	Contract Con	
Surfacing material under and around equipment is adequate depth (6-12 inches).	+	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Γ	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	42	-	N/A
Proper drainage prevents water from forming puddles.	1	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	-	
Equipment is free from sharp points, corners, or edges.	1	Γ	
Protective caps or plugs are not missing or damaged.	1	r	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	5	
Equipment is free of rust, rot, cracks, and splinters.	1	r	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	г	Г	
Swings are a safe distance from other playground equipment.	-	г	
Swings are 24 inches apart.	г	T	NA
Edges of seats are smooth and free from obstructions.	г	Γ-	(: <sup>1</sup>
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	and the second	in a	

(To be completed monthly.)

Bay front Part.			*		_
Slides	Pass	Fail		<b>Problem / Solution</b>	
Slides are free of obstructions and protrusions.	K	Б			
Equipped with platforms to facilitate access to the sitting position.	V	D			
Platforms are equipped with guardrails or equivalent protective equipment.	Ŋ	0			
Average incline is less than 30 degrees.	Γ.	Ti			
Exit regions are level.		Ð			
Metal slides are shaded to prevent overheating.	<u></u>				
Climbing Equipment	Pass	Fail		Problem / Solution	
Hand grips are secured and do not rotate.	1	ה			
Rope or chain ladders are anchored at both ends.	1	n			
Foot holds/rungs are in good condition and adequately spaced.	K	<b>G</b>			
Seesaws	Pass	Fail		Problem / Solution	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail		Problem / Solution	
Seesaws are free of cracks, corrosion,				Problem / Solution  NA	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		r.		Problem / Solution  NA	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	E	E .		Problem / Solution  NA	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	Б Б	П		Problem / Solution  N/A	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.  Handholds are provided at each seating position.	Б Б	П		Problem / Solution  N/A  Date: 6 - (9, 23	

Splash Pad. Replaced drainage grills

(To be completed monthly.)

Wilson

$U_1 500$			W. Communication of the Commun
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		n	
Playground area is free of anthills/hazardous insects or toxic plants.	7	ם	
Playground area is free of holes and other tripping hazards.	1	L	
Proper signage with rules, hours, and age- appropriate use is posted.	T.	7	
Playground area is properly fenced.	£	7	
Self-latching gate works as designed.		1	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<b>-</b>	l ī	
Surfacing material under and around equipment is adequate depth (6-12 inches).	Z.	[].	
Surfacing material is free of glass, debris, or other foreign objects.	V	F	
Surfacing material is not compacting or deteriorating.	7	r.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	4	L	
Proper drainage prevents water from forming puddles.	V	r	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	7	п	
Equipment is free from sharp points, corners, or edges.	7	Г	
Protective caps or plugs are not missing or damaged.	7	i	
Equipment is free of potential clothing entanglement hazards.	7	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	۲	Surface rust on bottome
Equipment is free of rust, rot, cracks, and splinters.	ţ-	W/	Surface rust on bottorea
Equipment is free of entrapments.	y	г	
Equipment is safely anchored.	1	П	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	E.		
Swings are a safe distance from other playground equipment.	7	Г	
Swings are 24 inches apart.	7	٢	
Edges of seats are smooth and free from obstructions.	7	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	Г	

(To be completed monthly.)

. . .

Wilson

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	K	E _	
Equipped with platforms to facilitate access to the sitting position.	7		
Platforms are equipped with guardrails or equivalent protective equipment.		D	
Average incline is less than 30 degrees.	П	n	
Exit regions are level.	7	ה	
Metal slides are shaded to prevent overheating.	ū	·Π	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7		
Rope or chain ladders are anchored at both ends.	1	П	
Foot holds/rungs are in good condition and adequately spaced.	K	L:	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<u> </u>		NA
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	A.	Π	
Fulcrums/pivot points are free of pinch or crush hazards.	1	П	
Handholds are provided at each seating position.	K	Г	
Inspector name, signature, and completion date			
Name: Blair Corter			
Name: Blass Cortes Signature: 93 H			Date: 6 - 19 · 23

(To be completed monthly.)

Eithy Ashley

Eithy Ashley		198 <u>2</u> 3.08	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	F	
Playground area is free of holes and other tripping hazards.	1	ļ.	
Proper signage with rules, hours, and age- appropriate use is posted.	F	1	
Playground area is properly fenced.	8	1	
Self-latching gate works as designed.	F	1	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Γ	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	14.0	
Surfacing material is free of glass, debris, or other foreign objects.	V	Г	
Surfacing material is not compacting or deteriorating.	+		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	1	
Proper drainage prevents water from forming puddles.	7	loos.	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	*	Γ	
Equipment is free from sharp points, corners, or edges.	1	Γ	
Protective caps or plugs are not missing or damaged.	1	Γ	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Γ	
Equipment is free of rust, rot, cracks, and splinters.	Γ-	1	light nust around stop rails
Equipment is free of entrapments.	Г	Г	
Equipment is safely anchored.	~	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	0	Г	
Swings are a safe distance from other playground equipment.		F	No Swings.
Swings are 24 inches apart.	Г	г	
Edges of seats are smooth and free from obstructions.	г	г	2 .
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	

LHA H Shley		***	
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	R		
Equipped with platforms to facilitate access to the sitting position.	F	Ü	
Platforms are equipped with guardrails or equivalent protective equipment.	F	a	
Average incline is less than 30 degrees.	Г.	r,	
Exit regions are level.	P	C	
Metal slides are shaded to prevent overheating.	Ð	П	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	D	
Rope or chain ladders are anchored at both ends.	1		
Foot holds/rungs are in good condition and adequately spaced.	7	E.	
adequately spaced.			
Seesaws	Pass	Fail	Problem / Solution
	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion,			Problem/Solution  None Home
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	С	<u>D</u>	
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	Б Б	e r	
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	Б Б	n n	
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.  Handholds are provided at each seating position.	Б Б	n n	

(To be completed monthly.)

City Pavillion

COS Pavillion		1	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	a	
Playground area is free of anthills/hazardous insects or toxic plants.	1	D.	
Playground area is free of holes and other tripping hazards.	1/2:	ß	
Proper signage with rules, hours, and age- appropriate use is posted.	G	A	
Playground area is properly fenced.	r:	<b>Z</b> .	
Self-latching gate works as designed.	Г.	5/-	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	p.	Б	
Surfacing material is free of glass, debris, or other foreign objects.	6	Ü	
Surfacing material is not compacting or deteriorating.	P	r.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	נז	
Proper drainage prevents water from forming puddles.	D:	п	. *
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	П	
Equipment is free from sharp points, corners, or edges.	6	Г	
Protective caps or plugs are not missing or damaged.	1	Ľ	
Equipment is free of potential clothing entanglement hazards.	1	Г.	
Equipment free of pinch and crush points or exposed moving parts.	P.	Г.	
Equipment is free of rust, rot, cracks, and splinters.	Ľ.	5	Around a low bott heads
Equipment is free of entrapments.	7	L:	
Equipment is safely anchored.	7:	Ŀ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	n	
Swings are a safe distance from other playground equipment.		п	:
Swings are 24 inches apart.	1	۲.	
Edges of seats are smooth and free from obstructions.	7	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	Г	

(To be completed monthly.)

Cito Pavillion

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		ū	
Equipped with platforms to facilitate access to the sitting position.	¥.	G	
Platforms are equipped with guardrails or equivalent protective equipment.	Þ	G	
Average incline is less than 30 degrees.	<b>E</b>		
Exit regions are level.	1	D	
Metal slides are shaded to prevent overheating.	П	Ö	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7		
Rope or chain ladders are anchored at both ends.	1	<u>ה</u>	
Foot holds/rungs are in good condition and adequately spaced.	1	ū	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	г ,	D	· · · · · · · · · · · · · · · · · · ·
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		Ē	None
Fulcrums/pivot points are free of pinch or crush hazards.	0	5	
Handholds are provided at each seating position.	П		
Inspector name, signature, and completion date			
Name: Blair Corter Signature: B Cutt			Date: 619-23