

(To be completed monthly.)

george Adoms fank

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	5	E)	
Playground area is free of anthills/hazardous insects or toxic plants.	2	ם	
Playground area is free of holes and other tripping hazards.	2	G	
Proper signage with rules, hours, and age- appropriate use is posted.	12	С	
Playground area is properly fenced.	1		
Self-latching gate works as designed.		ם	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	₹/	ū	
Surfacing material under and around equipment is adequate depth (6-12 inches).		[] 	
Surfacing material is free of glass, debris, or other foreign objects.	4	מ	
Surfacing material is not compacting or deteriorating.	1	מ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.			
Proper drainage prevents water from forming puddles.	2		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	₽.	/ti	-
Equipment is free from sharp points, corners, or edges.	۲.	n	
Protective caps or plugs are not missing or damaged.	r./	C	
Equipment is free of potential clothing entanglement hazards.	F./	⊢ □	
Equipment free of pinch and crush points or exposed moving parts.	٠,	ה	
Equipment is free of rust, rot, cracks, and splinters.	n /	П	
Equipment is free of entrapments.	1.	Ļ	
Equipment is safely anchored.		ū	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	4	ם	
Swings are a safe distance from other playground equipment.	٠,	П	
Swings are 24 inches apart.	C	D	
Edges of seats are smooth and free from obstructions.	n	n	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Ľ	G	

(To be completed monthly.)

george Adams Park **Slides** Pass Fail **Problem / Solution** d Slides are free of obstructions and protrusions. Ð Equipped with platforms to facilitate access **~** to the sitting position. Platforms are equipped with guardrails or equivalent \Box protective equipment. Average incline is less than 30 degrees. П Б Exit regions are level. Metal slides are shaded to prevent overheating. Climbing Equipment **Pass** Fail **Problem / Solution** Hand grips are secured and do not rotate. \Box Rope or chain ladders are anchored at both ends. Foot holds/rungs are in good condition and adequately spaced. **Seesaws Pass** Fail **Problem / Solution** Seesaws are free of cracks, corrosion. Ū and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact Ð with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position. Inspector name, signature, and completion date Name: <u>Douglos</u> Corpio Date: 3/10/23

(To be completed monthly.)

UNISON Park

Wilder Ason d	,		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	D.	0	
Playground area is free of anthills/hazardous insects or toxic plants.	5		
Playground area is free of holes and other tripping hazards.	E.	ם	
Proper signage with rules, hours, and age- appropriate use is posted.	G	0	Signs are being made
Playground area is properly fenced.	ם	נו	SMA
Self-latching gate works as designed.		ū	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-	c c	
Surfacing material under and around equipment is adequate depth (6-12 inches).	$\left \int_{A}$	ם	
Surfacing material is free of glass, debris, or other foreign objects.	5	ם	
Surfacing material is not compacting or deteriorating.		נו	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	J.		
Proper drainage prevents water from forming puddles.	P.	<u></u>	
Equipment Hazards	Pass	Fäil	Problem / Solution
Equipment is not damaged or vandalized.	45	, 0	-
Equipment is free from sharp points, corners, or edges.	Į,	Ľ	
Protective caps or plugs are not missing or damaged.	₽		
-Equipment is free of potential clothing entanglement hazards.	<u></u>	ם	
Equipment free of pinch and crush points or exposed moving parts.	G	ם	
Equipment is free of rust, rot, cracks, and splinters.	Б	Ü	
Equipment is free of entrapments.		נז	Rost Sand down and putt
Equipment is safely anchored.	√	ū	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	C	נו	
Swings are a safe distance from other playground equipment.	D	ם	
Swings are 24 inches apart.	다	ם	
Edges of seats are smooth and free from obstructions.	[]	D	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	ם	ם	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	E/	Ľ	
Equipped with platforms to facilitate access to the sitting position.		, 0	
Platforms are equipped with guardrails or equivalent protective equipment.	2	ū	
Average incline is less than 30 degrees.	п	, D	
Exit regions are level.	12.1	0	
Metal slides are shaded to prevent overheating.		П	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		ū	
Rope or chain ladders are anchored at both ends.	[-/	D.	
Foot holds/rungs are in good condition and adequately spaced.			
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,	Li .	Б	
and other obvious structural defects.	[.]	,	
	<u> </u>	ם	NIA
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			NIA
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	<u> </u>	מ	NIA
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	- C	מ	NIA



(To be completed monthly.)

Bay front

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	Į,	, C	
Playground area is free of anthills/hazardous insects or toxic plants.	IZ.	ו	
Playground area is free of holes and other tripping hazards.	rv/	ם	
Proper signage with rules, hours, and age- appropriate use is posted.	ה	E .	Signs being mole
Playground area is properly fenced.	Ü		
Self-latching gate works as designed.	Ľ	G	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	ريا		
Surfacing material under and around equipment is adequate depth (6-12 inches).	7	ם	
Surfacing material is free of glass, debris, or other foreign objects.	IT.	ני	
Surfacing material is not compacting or deteriorating.	F.	ū	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	C.		A) /A
Proper drainage prevents water from forming puddles.	F.	[]	
Equipment Hazards	Pass	Fail	Problem /'Solution
Equipment is not damaged or vandalized.	L.		_
Equipment is free from sharp points, corners, or edges.	~	<u>ا</u>	
Protective caps or plugs are not missing or damaged.	II.	₽	
Equipment is free of potential clothing entanglement hazards.	Ŀ	נז	
Equipment free of pinch and crush points or exposed moving parts.	Б	Г	
Equipment is free of rust, rot, cracks, and splinters.	150	Ei .	
Equipment is free of entrapments.		П	
Equipment is safely anchored.	F .	נז	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		П	
Swings are a safe distance from other playground equipment.	Γ	L	NIA
Swings are 24 inches apart.	r.,	Γ;	·
Edges of seats are smooth and free from obstructions.	F:	Ľ	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	£.	ה	

(To be completed monthly.)

Bayfront

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	12.	, D	
Equipped with platforms to facilitate access to the sitting position.	E		
Platforms are equipped with guardrails or equivalent protective equipment.			
Average incline is less than 30 degrees.	ı.	. 0	
Exit regions are level.	~		
Metal slides are shaded to prevent overheating.	ם	П	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		ū	
Rope or chain ladders are anchored at both ends.	₹		
Foot holds/rungs are in good condition and adequately spaced.	5	<u> </u>	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	D	[i	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	D.		N/A
Fulcrums/pivot points are free of pinch or crush hazards.	D	ם	
Handholds are provided at each seating position.	ם	ם	

UI CIUSII IIdzaius.	1	ļ	
Handholds are provided at each seating position.	ה	ם	
Inspector name, signature, and completion date			
Name: <u>Douglas Capio</u> Signature: <u>Day Jas</u> Capio			Date: 3/10/23



(To be completed monthly.)

City Park

a y your			<u> </u>
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	r.		
Playground area is free of anthills/hazardous insects or toxic plants.	t.V	מ	
Playground area is free of holes and other tripping hazards.	17		
Proper signage with rules, hours, and age- appropriate use is posted.	N	ם	
Playground area is properly fenced.	ᄃ		
Self-latching gate works as designed.	П	Ü	
Surfacing	Pass	Fail	Problem:/ Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	5/	ព	
Surfacing material under and around equipment is adequate depth (6-12 inches).	√	יט	
Surfacing material is free of glass, debris, or other foreign objects.	5	U	
Surfacing material is not compacting or deteriorating.	~	г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	√	E	
Proper drainage prevents water from forming puddles.	là.	Ľ.	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	E.	П	
Equipment is free from sharp points, corners, or edges.	7	r.	
Protective caps or plugs are not missing or damaged.	F	D ,	
Equipment is free of potential clothing entanglement hazards.	130	D.	
Equipment free of pinch and crush points or exposed moving parts.	14	_ C	
Equipment is free of rust, rot, cracks, and splinters.	P.	Г	
Equipment is free of entrapments.	r.	П	
Equipment is safely anchored.	₹⁄	Ľ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	D	כו	
Swings are a safe distance from other playground equipment.	Б.	Ð	
Swings are 24 inches apart.	E	П	
Edges of seats are smooth and free from obstructions.	ŗ	П	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	E	С	

(To be completed monthly.)

ď

Problem / Solution

Thit city Park Next to Asnly feiters

Slides Pass Fail

Slides are free of obstructions and protrusions.

shaes are tree or obstructions and produsions.	· ·	'-	
Equipped with platforms to facilitate access to the sitting position.		ü	
Platforms are equipped with guardrails or equivalent protective equipment.	F	o o	
Average incline is less than 30 degrees.			
Exit regions are level.	DZ.	ם	
Metal slides are shaded to prevent overheating.		Π	-
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	E /	ū	
Rope or chain ladders are anchored at both ends.	0.	D	
Foot holds/rungs are in good condition and adequately spaced.	1	Ö	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		ם	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	נו	o	N/A
Fulcrums/pivot points are free of pinch or crush hazards.	ה	G.	
Handholds are provided at each seating position.	n		
Inspector name, signature, and completion date			
Name: Douglas Capio			Date: 3/10/73



(To be completed monthly.)

Cleart crossing park

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	· ·	/ n	-
Playground area is free of anthills/hazardous insects or toxic plants.	r/	/ ¹⁰	
Playground area is free of holes and other tripping hazards.	Li	<u> </u>	
Proper signage with rules, hours, and age- appropriate use is posted.	۲	G	
Playground area is properly fenced.	Ü		
Self-latching gate works as designed.	п	D	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	✓	Π	
Surfacing material under and around equipment is adequate depth (6-12 inches).	17	П	
Surfacing material is free of glass, debris, or other foreign objects.	rV	ت ر	
Surfacing material is not compacting or deteriorating.	7	<u> </u>	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<i>-</i> √	П	
Proper drainage prevents water from forming puddles.	r.	D	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	.	\ ₀	
Equipment is free from sharp points, corners, or edges.	<u> </u>	<u> </u>	
Protective caps or plugs are not missing or damaged.	ī	ū	
Equipment is free of potential clothing entanglement hazards.	G	F	
Equipment free of pinch and crush points or exposed moving parts.	۲,	G	
Equipment is free of rust, rot, cracks, and splinters.	/ب	Ŀ	
Equipment is free of entrapments.	п	/ r <u>.</u>	
Equipment is safely anchored.	الأيا	Ľ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	F.		
Swings are a safe distance from other playground equipment.	-	Б	
Swings are 24 inches apart.	√	Ū	
Edges of seats are smooth and free from obstructions.	<i>J.</i>	Ť:	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	/		

Claret crossing	, P	~//< S	
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	C.	o o	
Equipped with platforms to facilitate access to the sitting position.		ı ı	
Platforms are equipped with guardrails or equivalent protective equipment.	Ţ.	<u>.</u>	
Average incline is less than 30 degrees.	5	n	
Exit regions are level.	12		
Metal slides are shaded to prevent overheating.	Ľ	13	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			•
Rope or chain ladders are anchored at both ends.	F.	п	
Foot holds/rungs are in good condition and adequately spaced.	-	Б	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	/	ם	•
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		ם	
Fulcrums/pivot points are free of pinch or crush hazards.	52		
Handholds are provided at each seating position.	l ¹	o.	
Inspector name, signature, and completion date			
Name: Doug low Cupio			Date: 3/10/23



(To be completed monthly.)

ButerCly Darks

Dutertly Darks			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	r.	, n	
Playground area is free of anthills/hazardous insects or toxic plants.	[~	/ "	
Playground area is free of holes and other tripping hazards.	~		
Proper signage with rules, hours, and age- appropriate use is posted.	г	ra .	
Playground area is properly fenced.	_ г	Г	
Self-latching gate works as designed.	Γ.	<u></u>	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		כז	
Surfacing material under and around equipment is adequate depth (6-12 inches).	~	, 5	
Surfacing material is free of glass, debris, or other foreign objects.	F	Ľ	
Surfacing material is not compacting or deteriorating.	[]	Г.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	ם	ם	N/A
Proper drainage prevents water from forming puddles.	15.	נז	
Equipment Hazards	Pass-	Fail	Problem / Solution
Equipment is not damaged or vandalized.	۲,	נו	
Equipment is free from sharp points, corners, or edges.	r.	С	
Protective caps or plugs are not missing or damaged.	\[\bar{\bar{\bar{\bar{\bar{\bar{\bar{	n	·
Equipment is free of potential clothing entanglement hazards.	Б	ח	
Equipment free of pinch and crush points or exposed moving parts.	Г	G	
Equipment is free of rust, rot, cracks, and splinters.	<u>ر</u> ې	г	
Equipment is free of entrapments.	Г.	<u>Γ</u>	
Equipment is safely anchored.	F/		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	П		·
Swings are a safe distance from other playground equipment.		Γi	NA
Swings are 24 inches apart.	С	E.	
Edges of seats are smooth and free from obstructions.	Г	L.	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	- ID	

(To be completed monthly.)

Butterfb Park

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	E	ם	
Equipped with platforms to facilitate access to the sitting position.		, []	
Platforms are equipped with guardrails or equivalent protective equipment.		ם	
Average incline is less than 30 degrees.	/		
Exit regions are level.	تآ	ם	
Metal slides are shaded to prevent overheating.		ū	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7		
Rope or chain ladders are anchored at both ends.	ī.		
Foot holds/rungs are in good condition and adequately spaced.	FZ		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	נו	ני	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	П	ū	
Fulcrums/pivot points are free of pinch or crush hazards.	ם		
Handholds are provided at each seating position.	n	מ	

oi ciusii nazaius.				
Handholds are provided at each seating position.	n			-
Inspector name, signature, and completion date				
Name: Douglas Crpio Signature: Douglas Curpio			Date: 3/10/2	3

(Lo be completed monthly.)

March HOUSE Light **General Inspection** Pass Fail Problem / Solution ď Playground area is free of litter and debris. Playground area is free of anthills/hazardous insects . [] or toxic plants. Playground area is free of holes and other tripping hazards. Proper signage with rules, hours, and Ö age- appropriate use is posted. Sigh being water Playground area is properly fenced. \Box Self-latching gate works as designed. П Surfacing Pass Fail **Problem / Solution** Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, П wood chips, rubber mulch). Surfacing material under and around equipment is adequate depth (6-12 inches). Surfacing material is free of glass, debris, F_U or other foreign objects. Surfacing material is not compacting or deteriorating. \Box Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material. Proper drainage prevents water from П forming puddles. Equipment Hazards Pass, Fail Problem / Solution Equipment is not damaged or vandalized. C Equipment is free from sharp points, corners, Ċ. or edges. Protective caps or plugs are not missing or damaged. П П Equipment is free of potential clothing C. entanglement hazards. Equipment free of pinch and crush points or exposed \Box moving parts. Equipment is free of rust, rot, cracks, and splinters. \Box Equipment is free of entrapments. П Equipment is safely anchored. \Box **Swings** Pass Fail **Problem / Solution** Hardware and chains are in good condition. [] Swings are a safe distance from other playground equipment. Swings are 24 inches apart. D Edges of seats are smooth and free from Π 5/ obstructions. Adequate depths of surfacing material extend out a \Box minimum distance of twice the height of the swing.

light House Bean	Nex	+ 10	Splash Pad
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	√.		
Equipped with platforms to facilitate access to the sitting position.	E.	ū	
Platforms are equipped with guardrails or equivalent protective equipment.	r./	o l	
Average incline is less than 30 degrees.	D /	D	
Exit regions are level.	₽	0	
Metal slides are shaded to prevent overheating.	C	ū	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			;
Rope or chain ladders are anchored at both ends.	√ ✓	0	
Foot holds/rungs are in good condition and adequately spaced.	N.	o.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	D C	ם	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	נו		NIA
Fulcrums/pivot points are free of pinch or crush hazards.	D	ū	
Handholds are provided at each seating position.		Ü	
Inspector name, signature, and completion date	•		-
mapoccor marro, agriacaro, and completion date			
Name: Dougland Curpio			Date: 3/10/23

1991 house Breach	ON	<u>13æ</u>	each Side
Slides	Pass		Problem / Solution
Slides are free of obstructions and protrusions.		ם	
Equipped with platforms to facilitate access to the sitting position.	Ę	a	
Platforms are equipped with guardrails or equivalent protective equipment.		0	
Average incline is less than 30 degrees.		ı ı	
Exit regions are level.	P.1	ם	
Metal slides are shaded to prevent overheating.	IJ		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	2	ū	
Rope or chain ladders are anchored at both ends.	✓	<u></u>	
Foot holds/rungs are in good condition and adequately spaced.		a	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		o o	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ם	ם	N/A
Fulcrums/pivot points are free of pinch or crush hazards.	Ü	D.	
Handholds are provided at each seating position.	בו	E	
Inspector name, signature, and completion date			
Name: Doylas Confus Signature: Doylas Cypra			Date: 3/20/23

(To be completed monthly.)

Beach Next to the Pavillon light House Slides Pass Fail Problem / Solution Slides are free of obstructions and protrusions. П Equipped with platforms to facilitate access \Box to the sitting position. Platforms are equipped with quardrails or equivalent protective equipment. Average incline is less than 30 degrees. \Box Exit regions are level. П Metal slides are shaded to prevent overheating. **Climbing Equipment** Pass Fail Problem / Solution Hand grips are secured and do not rotate. П Rope or chain ladders are anchored at both ends. Foot holds/rungs are in good condition and ATTA adequately spaced. **Seesaws Pass** Fail **Problem / Solution** Seesaws are free of cracks, corrosion. and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact \mathcal{N}/A with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position. Б Inspector name, signature, and completion date Douglas Cario Date: 3/10/23