(To be completed monthly.)

Clairet Chossing.

Carrer	- 11 0	<u> </u>	<u> </u>
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	7	ה	
Playground area is free of anthills/hazardous insects or toxic plants.	1	C	
Playground area is free of holes and other tripping hazards.	V		
Proper signage with rules, hours, and age- appropriate use is posted.	r.	7/	
Playground area is properly fenced.	Ľ	Ď.	
Self-latching gate works as designed.	Г	2	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	pr-	П	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	D.	
Surfacing material is free of glass, debris, or other foreign objects.	1	۲	
Surfacing material is not compacting or deteriorating.	1	Ľ.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	7/		
Proper drainage prevents water from forming puddles.	1	נז	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	25	r.	•
Equipment is free from sharp points, corners, or edges.	V	r	
Protective caps or plugs are not missing or damaged.	V	Ŀ	
Equipment is free of potential clothing entanglement hazards.	V	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	, L	
Equipment is free of rust, rot, cracks, and splinters.	a de la companya de l	Г	
Equipment is free of entrapments.	10	٢	
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	П	
Swings are a safe distance from other playground equipment.	10	۲	DA BC
Swings are 24 inches apart.	1	Ľ	}/
Edges of seats are smooth and free from obstructions.	Ī/	Г /	Vy
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	8	Ľ.	7,

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	4		
Equipped with platforms to facilitate access to the sitting position.	7	E	
Platforms are equipped with guardrails or equivalent protective equipment.		о \	
Average incline is less than 30 degrees.	8	ם	
Exit regions are level.	14.	C	
Metal slides are shaded to prevent overheating.	W		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<i>a</i>	ם	
Rope or chain ladders are anchored at both ends.	D.	۵	-
Foot holds/rungs are in good condition and adequately spaced.	iv.	С	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	ני		NIA
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ם	ני	11
Fulcrums/pivot points are free of pinch or crush hazards.	Г	Ω	/1
Handholds are provided at each seating position.	E	n	
			

or crush hazards.	Г		/1	
Handholds are provided at each seating position.	E	'n		
Inspector name, signature, and completion date				
Name: Blair Corter Signature: Blom Ut		_		Date: 4-14-23

Baxfront Penining ta			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	<i>F</i>	Ĺ	•
Playground area is free of anthills/hazardous insects or toxic plants.	f	5	
Playground area is free of holes and other tripping hazards.	1.	ů	
Proper signage with rules, hours, and age- appropriate use is posted.	Ľ	G	
Playground area is properly fenced.	Г.	Ľ.	
Self-latching gate works as designed.	r	Б	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	fn.	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	ľī	
Surfacing material is free of glass, debris, or other foreign objects.	1	r.	
Surfacing material is not compacting or deteriorating.	I □	L:	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	1	r.	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	Ľ	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	٢	
Equipment is free of rust, rot, cracks, and splinters.	*	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.		۲	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1.	Ľ	•
Swings are a safe distance from other playground equipment.	Г	٦	NIA
Swings are 24 inches apart.	Г.	Г	11
Edges of seats are smooth and free from obstructions.	٦	Г	\(\(\)
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	 	ſ.	U

(To be completed monthly.)

Fail

 \Box

Problem / Solution

Pass

Slides

Slides are free of obstructions and protrusions.

ondes are need or obstitute ons and productions.	<i>y</i> .	'-	
Equipped with platforms to facilitate access to the sitting position.	1	Ľ	
Platforms are equipped with guardrails or equivalent protective equipment.	7	ū	
Average incline is less than 30 degrees.	7	П	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.		ם	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<u> </u>		
Rope or chain ladders are anchored at both ends.	1	Ð	· · · · · · · · · · · · · · · · · · ·
Foot holds/rungs are in good condition and adequately spaced.	7	ה	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Ę	G	NA
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ŗ	П	
Fulcrums/pivot points are free of pinch or crush hazards.	Г	Ü	W.
Handholds are provided at each seating position.	10	נו	
Inspector name, signature, and completion date			
Name: Blain Contor Signature: Blow Ut			Date: 4,14.23

	300	ng	e Adoms
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	D.	. " "
Playground area is free of anthills/hazardous insects or toxic plants.	7	П	
Playground area is free of holes and other tripping hazards.	7	Ū	
Proper signage with rules, hours, and age- appropriate use is posted.	1	C	
Playground area is properly fenced.	Б	Г.	No Fencino
Self-latching gate works as designed.	m	п	u //
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	Ŀ	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	ם	
Surfacing material is free of glass, debris, or other foreign objects.		Ľ	
Surfacing material is not compacting or deteriorating.	1	Ŀ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	7	Ľ	
Proper drainage prevents water from forming puddles.	W	r,	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	<i>j</i>	Ü	
Equipment is free from sharp points, corners, or edges.	7	Г	
Protective caps or plugs are not missing or damaged.	7	Ŀ	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	۲	
Equipment is free of rust, rot, cracks, and splinters.	Г	No.	Some surface rust on Post
Equipment is free of entrapments.	-	Ŀ	Bises
Equipment is safely anchored.	1/	Γ.	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	/	Г	
Swings are a safe distance from other playground equipment.	N		One swingset is older due for replacement, other
Swings are 24 inches apart.	17	۲	11
Edges of seats are smooth and free from obstructions.	7	۲	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	Γ	

(To be completed monthly.)

Fail

Problem / Solution

Pass

Slides

Slides are free of obstructions and protrusions.	7		
Equipped with platforms to facilitate access to the sitting position.	1		·
Platforms are equipped with guardrails or equivalent protective equipment.	1	٥	
Average incline is less than 30 degrees.	1	. 0	
Exit regions are level.	1/		
Metal slides are shaded to prevent overheating.	1.	Ü	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	Ţ.	O	
Rope or chain ladders are anchored at both ends.	1.	ū	
Foot holds/rungs are in good condition and adequately spaced.	1/2	Ľ	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	g/s	C	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	1/2	G	
Fulcrums/pivot points are free of pinch or crush hazards.	1	D .	
Handholds are provided at each seating position.	1/5	D	
Inspector name, signature, and completion date			
Name: Blair Canter Signature: Blow delta			Date: 4-14-23

(To be completed monthly.)

Wilson Part

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Ľ	
Playground area is free of anthills/hazardous insects or toxic plants.	1	ם	
Playground area is free of holes and other tripping hazards.		מ	,
Proper signage with rules, hours, and age- appropriate use is posted.	Г,	1	Post signage No fince
Playground area is properly fenced.	r.	Œ	No fine
Self-latching gate works as designed.	Г	F	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		r	
Surfacing material under and around equipment is adequate depth (6-12 inches).	7	С	
Surfacing material is free of glass, debris, or other foreign objects.	F	Ŀ	
Surfacing material is not compacting or deteriorating.		Ŀ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	ר	
Proper drainage prevents water from forming puddles.	1/5	G	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	7	Ľ	
Equipment is free from sharp points, corners, or edges.	<i>y</i> /	Г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	Γ	
Equipment free of pinch and crush points or exposed moving parts.	K	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	۲	
Equipment is free of entrapments.	1	f.	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Γ.	
Swings are a safe distance from other playground equipment.	1	۲	•
Swings are 24 inches apart.	F	Г	
Edges of seats are smooth and free from obstructions.	1	Γ	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	K	٦	

(To be completed monthly.)

Problem / Solution

Pass Fail

Slides

Slides are free of obstructions and protrusions.	1	П	
Equipped with platforms to facilitate access to the sitting position.	7	ū	
Platforms are equipped with guardrails or equivalent protective equipment.	1	П	
Average incline is less than 30 degrees.	1	ū	
Exit regions are level.	1	П	
Metal slides are shaded to prevent overheating.	1	ū	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	C i	
Rope or chain ladders are anchored at both ends.	K	נז	
Foot holds/rungs are in good condition and adequately spaced.	1	ū	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	[;	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	7	Ĺ	
Fulcrums/pivot points are free of pinch or crush hazards.	1	5	
Handholds are provided at each seating position.	1	Г.	
Inspector name, signature, and completion date			
Name: Blair Carls Signature: Mr.	•		Date: 4-14-23

Port Lavaca Playground Safety Checklist (To be completed monthly.)

City Part 1	Pan	Mie	77
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Ľ	
Playground area is free of anthills/hazardous insects or toxic plants.	1	ם	
Playground area is free of holes and other tripping hazards.	1	Ĺĵ	
Proper signage with rules, hours, and age- appropriate use is posted.	m	7	Post Signage
Playground area is properly fenced.	Ľ	r:	· · · · · · · · · · · · · · · · · · ·
Self-latching gate works as designed.	П	n	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	y	G .	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	E.	
Surfacing material is free of glass, debris, or other foreign objects.		r.	
Surfacing material is not compacting or deteriorating.	7	г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	K	Ŀ	
Proper drainage prevents water from forming puddles.	W	Ľ.	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	L.	
Equipment is free of potential clothing entanglement hazards.	1	٦	
Equipment free of pinch and crush points or exposed moving parts.	f	Г	/
Equipment is free of rust, rot, cracks, and splinters.	Г	/	Some post bases/ touch up.
Equipment is free of entrapments.	۲	Ŀ	, , , , , , , , , , , , , , , , , , , ,
Equipment is safely anchored.	Г	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	г	-
Swings are a safe distance from other playground equipment.	1	Г	
Swings are 24 inches apart.	1	Г	
Edges of seats are smooth and free from obstructions.	1	۲	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	Г	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	A	, D	
Equipped with platforms to facilitate access to the sitting position.	1	D.	
Platforms are equipped with guardrails or equivalent protective equipment.	1		
Average incline is less than 30 degrees.	Ø	Ü	
Exit regions are level.	1	ם	
Metal slides are shaded to prevent overheating.	1		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	ם	-
Rope or chain ladders are anchored at both ends.	Ps.	Ü	
Foot holds/rungs are in good condition and adequately spaced.	4	D.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	₽.	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ני		NA
Fulcrums/pivot points are free of pinch or crush hazards.	G	D	
Handholds are provided at each seating position.	[.]	n	
Inspector name, signature, and completion date			
Name: Blair Carter Signature: Blair WA			Date: 4-14,23

(To be completed monthly.)							
City Park Hshley							
General Inspection	Pass	Fail	Problem / Solution				
Playground area is free of litter and debris.	1	C					
Playground area is free of anthills/hazardous insects or toxic plants.	A	ū					
Playground area is free of holes and other tripping hazards.	7	ū					
Proper signage with rules, hours, and age- appropriate use is posted.	L:	A	Post signage				
Playground area is properly fenced.	r.	2					
Self-latching gate works as designed.	r.	7.					
Surfacing	Pass	Fail	Problem / Solution				
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Ľ					
Surfacing material under and around equipment is adequate depth (6-12 inches).	K	E					
Surfacing material is free of glass, debris, or other foreign objects.	1	۲					
Surfacing material is not compacting or deteriorating.	*	۲					
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Ľ.					
Proper drainage prevents water from forming puddles.	J.	ני					
Equipment Hazards	Pass	Fail	Problem / Solution				
Equipment is not damaged or vandalized.	1	Ç					
Equipment is free from sharp points, corners, or edges.	1	Г					
Protective caps or plugs are not missing or damaged.		Ľ					
Equipment is free of potential clothing entanglement hazards.	1	L					
Equipment free of pinch and crush points or exposed moving parts.	1	Г	Pariat				
Equipment is free of rust, rot, cracks, and splinters.	Г	1	Rust around Hardroil base				
Equipment is free of entrapments.		Ľ					
Equipment is safely anchored.	4	F -					
Swings	Pass	Fail	Problem / Solution				
Hardware and chains are in good condition.		П					
Swings are a safe distance from other playground equipment.	٦	Г					
Swings are 24 inches apart.	E	Г					
Edges of seats are smooth and free from obstructions.	Г	٢					
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	۲					

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	11	D.	·
Equipped with platforms to facilitate access to the sitting position.	K		
Platforms are equipped with guardrails or equivalent protective equipment.	1		
Average incline is less than 30 degrees.	- Par	□. -	
Exit regions are level.	P	ū	
Metal slides are shaded to prevent overheating.	ם	ū	Plastic stides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	[]	
Rope or chain ladders are anchored at both ends.	ū	Ü	
Foot holds/rungs are in good condition and adequately spaced.	P	D	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	ה	G	N/A
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	D	ם	N/A
Fulcrums/pivot points are free of pinch or crush hazards.	n	c	N/A
Handholds are provided at each seating position.	N	ה	

Inspector name, signature, and completion date	
Name: Blain Carton Signature: Blain MT	Date: 4-14-23

(To be completed monthly.)

Butterfly Park

Buttertly Park			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	F	П	
Playground area is free of anthills/hazardous insects or toxic plants.	F.		
Playground area is free of holes and other tripping hazards.	NT.	ra.	
Proper signage with rules, hours, and age- appropriate use is posted.	ם	·	
Playground area is properly fenced.	נז	D	
Self-latching gate works as designed.	D ₂	n	
Surfacing,	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Ľ	
Surfacing material under and around equipment is adequate depth (6-12 inches).		ם	
Surfacing material is free of glass, debris, or other foreign objects.	5/	Г	
Surfacing material is not compacting or deteriorating.	F	D	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г.	С	
Proper drainage prevents water from forming puddles.	1	Ľ	
Equipment Häzards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	~	Ω	
Equipment is free from sharp points, corners, or edges.	٦	F.	
Protective caps or plugs are not missing or damaged.	r	r.	/
Equipment is free of potential clothing entanglement hazards.	[-	~	
Equipment free of pinch and crush points or exposed moving parts.	١.	٦	
Equipment is free of rust, rot, cracks, and splinters.	<u></u>		
Equipment is free of entrapments.	Г /	, L.	
Equipment is safely anchored.	2	<u>Г</u>	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	ري.	n	
Swings are a safe distance from other playground equipment.	~	Г	
Swings are 24 inches apart.	-~	٦	
Edges of seats are smooth and free from obstructions.	₹	/ ^r	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	7	Γ.	

(To be completed monthly.)

Butterfly Parks

Exercise equipment is rosted out

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	Ę	, []	
Equipped with platforms to facilitate access to the sitting position.	2	ū	
Platforms are equipped with guardrails or equivalent protective equipment.	R	0	
Average incline is less than 30 degrees.	[2]		
Exit regions are level.	2	D	
Metal slides are shaded to prevent overheating.	ם	G	N/A
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	/جِا	ū	
Rope or chain ladders are anchored at both ends.	r:/	□	
Foot holds/rungs are in good condition and adequately spaced.	r.	ū	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		Ö	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	G	'n	
Fulcrums/pivot points are free of pinch or crush hazards.	Ŀ	D '	
Handholds are provided at each seating position.	Ľ	מ	

Inspector name, signature, and completion date	
Name: Blair Corter Signature: Blair Otto	Date: 4-14-23
Alotica	

light House Beach Peru	Hlan	-	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	√	Γ;	
Playground area is free of anthills/hazardous insects or toxic plants.	V	<u>.</u>	
Playground area is free of holes and other tripping hazards.		Ē	
Proper signage with rules, hours, and age- appropriate use is posted.	Y,	Е	
Playground area is properly fenced.	г	Ľ.	NA
Self-latching gate works as designed.	Г	r,	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		n	
Surfacing material under and around equipment is adequate depth (6-12 inches).	~/	ני	
Surfacing material is free of glass, debris, or other foreign objects.	F	, r	
Surfacing material is not compacting or deteriorating.	F-/	L.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	ĒΧ	ר	~// Å
Proper drainage prevents water from forming puddles.	Г	Ľ	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	E	רי	
Equipment is free from sharp points, corners, or edges.	~/		
Protective caps or plugs are not missing or damaged.	F/	r.	
Equipment is free of potential clothing entanglement hazards.	r√	Г	
Equipment free of pinch and crush points or exposed moving parts.	~	Г	
Equipment is free of rust, rot, cracks, and splinters.	~	٦	
Equipment is free of entrapments.	r /	י ר	
Equipment is safely anchored.	r./	٦	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	L.	
Swings are a safe distance from other playground equipment.	Г	ŗ	
Swings are 24 inches apart.	Г.	Г	
Edges of seats are smooth and free from obstructions.	Г	r	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	

(To be completed monthly.)

light House Beach Pervillon

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	≅∕	<u> </u>	
Equipped with platforms to facilitate access to the sitting position.		D	
Platforms are equipped with guardrails or equivalent protective equipment.	Ē	Ci .	
Average incline is less than 30 degrees.	~	ם	
Exit regions are level.	₹		
Metal slides are shaded to prevent overheating.			MA
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F	D	
Rope or chain ladders are anchored at both ends.	Г		
Foot holds/rungs are in good condition and adequately spaced.	Ľ	ני	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	r;	C	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	٢	e.	
Fulcrums/pivot points are free of pinch or crush hazards.	Ľ	φ	
Handholds are provided at each seating position.	r:	П	

Inspector name, signature, and completion date	·
Name: Blair Carter Signature: Blair Out	Date: 4-14-23

Light House Reach O General Inspection	Pass	1	Problem / Solution
Playground area is free of litter and debris.		- E	Troblem Jointon
Playground area is free of anthills/hazardous insects			
or toxic plants.	c	5	weeds around the Play ground
Playground area is free of holes and other tripping hazards.	nt/	ro	
Proper signage with rules, hours, and age- appropriate use is posted.	TC/		
Playground area is properly fenced.	Γ.	D	N/A
Self-latching gate works as designed.	П	П	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	4	Ŀ	
Surfacing material under and around equipment is adequate depth (6-12 inches).	, ,	E	
Surfacing material is free of glass, debris, or other foreign objects.	√	۲	
Surfacing material is not compacting or deteriorating.	С	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Γ.	Г	
Proper drainage prevents water from forming puddles.	<u></u>	Ľ	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Г	
Equipment is free from sharp points, corners, or edges.	Ľ	r	
Protective caps or plugs are not missing or damaged.	Г	[
Equipment is free of potential clothing entanglement hazards.	۲,	Г	
Equipment free of pinch and crush points or exposed moving parts.	,	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	Г	
Equipment is free of entrapments.	Г	Г	
Equipment is safely anchored.	N.	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.	-	· F	
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from obstructions.	Г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Ľ	

light House Beach Playor	ound		
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	<u></u>		
Equipped with platforms to facilitate access to the sitting position.		ū	
Platforms are equipped with guardrails or equivalent protective equipment.	2	0	
Average incline is less than 30 degrees.	r <u>e</u> /		
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.		<u> </u>	N/A
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		ם	
Rope or chain ladders are anchored at both ends.	I.S.		
Foot holds/rungs are in good condition and adequately spaced.	b .	ם	
Seesaws	Pass	Fail	Problem / Solution
Jeesans	1 433	Lan	Froblem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	. ass		Problem / Solution
Seesaws are free of cracks, corrosion,			Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	۵		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	מ		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	ם	0 0	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	ם	0 0	Date: 4-14-23