

|   | <u>ar k</u> |      | Lift 5 tation                      |
|---|-------------|------|------------------------------------|
| General Inspection  | Pass        | Fail | Problem / Solution                 |
| Playground area is free of litter and debris.   | IT/         |      |                                    |
| Playground area is free of anthills/hazardous insects or toxic plants.  | 7           | C    |                                    |
| Playground area is free of holes and other tripping hazards.  | E           |      |                                    |
| Proper signage with rules, hours, and age- appropriate use is posted.   |             | ם    | New signs are Being made  N/A  N/A |
| Playground area is properly fenced.   | ם           | D    | N/h                                |
| Self-latching gate works as designed.   | ם           | ם    | N/A                                |
| Surfacing   | Pass        | Fail | Problem / Solution                 |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | 13/         | G    |                                    |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | E           | D O  |                                    |
| Surfacing material is free of glass, debris, or other foreign objects.  | <b></b>     | a    |                                    |
| Surfacing material is not compacting or deteriorating.  | FZ/         | a    |                                    |
| Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.                       | FZ -        |      |                                    |
| Proper drainage prevents water from forming puddles.  | 7           | п    |                                    |
| Equipment Hazards   | Pass,       | Fail | Problem / Solution                 |
| Equipment is not damaged or vandalized.   | 12          | מ    |                                    |
| Equipment is free from sharp points, corners, or edges.   | nt/         | ם    |                                    |
| Protective caps or plugs are not missing or damaged.  | F           |      |                                    |
| Equipment is free of potential clothing entanglement hazards.   | √2          | ם    |                                    |
| Equipment free of pinch and crush points or exposed moving parts.   | 10.         | ני   |                                    |
| Equipment is free of rust, rot, cracks, and splinters.  | 13/         | []   | some rust; sand and Paint spots    |
| Equipment is free of entrapments.   | [iz/        | [;   | <i>y</i>                           |
| Equipment is safely anchored.   | <b>1</b>    | E E  | -                                  |
| Swings  | Pass        | Fail | Problem / Solution                 |
| Hardware and chains are in good condition.  | TE/         | D.   | Hardware will Be Installed soon    |
| Swings are a safe distance from other playground equipment.   | E/          | ם    |                                    |
| Swings are 24 inches apart.   | F/          | ם    |                                    |
| Edges of seats are smooth and free from obstructions.   | TE/         | ti   |                                    |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | 11/         | ū    |                                    |

| 10 CITY Pav   | ` K  |          | LITT STATION       |
|---|------|----------|--------------------|
| Slides  | Pass | Fail     | Problem / Solution |
| Slides are free of obstructions and protrusions.  | 1    | п        |                    |
| Equipped with platforms to facilitate access to the sitting position.   | €    | ū        |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 5    | П        |                    |
| Average incline is less than 30 degrees.  | √.   | ជា       |                    |
| Exit regions are level.   | FE/  |          |                    |
| Metal slides are shaded to prevent overheating.   | 2    |          |                    |
| Climbing Equipment  | Pass | Fail     | Problem / Solution |
| Hand grips are secured and do not rotate.   | 12/  | 0        |                    |
| Rope or chain ladders are anchored at both ends.  | r./  | ū        |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | 6    | <u> </u> |                    |
| Seesaws   | Pass | Fail     | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | G.   | o o      |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | D    | ū        | NA                 |
| Fulcrums/pivot points are free of pinch or crush hazards.   | מ    | G        |                    |
| Handholds are provided at each seating position.  |      |          |                    |
| Inspector name, signature, and completion date  |      |          |                    |
| Name: Eddie Tyker Signature: Coldie Tyker City Park   |      |          | Date: 2-13-23      |
| City Park   |      |          |                    |

| 9 01  | 1+4        | Pa   | rk Ashey field        |
|---|------------|------|-----------------------|
| General Inspection  | Pass       | Fail | Problem / Solution    |
| Playground area is free of litter and debris.   | E/         | 13   |                       |
| Playground area is free of anthills/hazardous insects or toxic plants.  | [Z         |      |                       |
| Playground area is free of holes and other tripping hazards.  | <b>2</b>   | ם    |                       |
| Proper signage with rules, hours, and age- appropriate use is posted.   | <b>E</b> / | D    | SigNs are Being made  |
| Playground area is properly fenced.   | 0,         | Π    | N/A                   |
| Self-latching gate works as designed.   | IÇ.        | ū    | NIA                   |
| Surfacing   | Pass       | Fail | Problèm / Solution    |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | <b>□</b>   |      |                       |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | re/        |      |                       |
| Surfacing material is free of glass, debris, or other foreign objects.  | nt/        | D    |                       |
| Surfacing material is not compacting or deteriorating.  | Le/        | П    |                       |
| Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.                       | ly.        | C    |                       |
| Proper drainage prevents water from forming puddles.  | •          |      |                       |
| Equipment Hazards   | Pass       | Fail | Problem / Solution    |
| Equipment is not damaged or vandalized.   |            | . П  |                       |
| Equipment is free from sharp points, corners, or edges.   | <b>D</b> . | O    |                       |
| Protective caps or plugs are not missing or damaged.  | □ □        | 0    |                       |
| Equipment is free of potential clothing entanglement hazards.   | G          | П    |                       |
| Equipment free of pinch and crush points or exposed moving parts.   | D          | מ    |                       |
| Equipment is free of rust, rot, cracks, and splinters.  |            | П    | Rust / sand and Paint |
| Equipment is free of entrapments.   | □          |      |                       |
| Equipment is safely anchored.   | Ü          | ū    |                       |
| Swings  | Pass       | Fail | Problem / Solution    |
| Hardware and chains are in good condition.  | D          | מ    |                       |
| Swings are a safe distance from other playground equipment.   | D          | ū    | of la                 |
| Swings are 24 inches apart.   |            | П    | N/A                   |
| Edges of seats are smooth and free from obstructions.   | G          | П    |                       |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | а          | D    |                       |

|   |          | City  | Park   | A shey field       |
|---|----------|-------|--------|--------------------|
| Slides  | Pass     | Fail  |        | Problem / Solution |
| Slides are free of obstructions and protrusions.  | 15/      | ם     |        |                    |
| Equipped with platforms to facilitate access to the sitting position.   | <b>~</b> | ם     |        |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | []       |       |        |                    |
| Average incline is less than 30 degrees.  | 12/      | □     |        |                    |
| Exit regions are level.   | II/      | . D   |        |                    |
| Metal slides are shaded to prevent overheating.   | ū        | a     |        |                    |
| Climbing Equipment  | Pass     | Fail  |        | Problem / Solution |
| Hand grips are secured and do not rotate.   |          | 0     |        |                    |
| Rope or chain ladders are anchored at both ends.  | 5/       | O     |        |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | 72/      |       |        |                    |
| Seesaws   | Pass     | Fail  |        | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | c        |       |        |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | <b>5</b> |       |        | \/\/A              |
| Fulcrums/pivot points are free of pinch or crush hazards.   | ū        | D     |        |                    |
| Handholds are provided at each seating position.  |          | מ     |        |                    |
| Inspector name, signature, and completion date  |          | -     |        |                    |
|   |          |       |        |                    |
| Name: Eddie Tyler Signature: Coldie Offer  Play Ground Next +   |          |       |        | Date: 2-/3-23      |
| Signature: Ode Tyler  |          | Date: |        |                    |
| Play Ground Next +  | o A      | 3h le | y food |                    |
| /   | C        | ity/  | Part   |                    |

(To be completed monthly.)

#### WILSON

| General Inspection  | Pass | Fail     | Problem / Solution        |
|---|------|----------|---------------------------|
| Playground area is free of litter and debris.   | ī/   |          |                           |
| Playground area is free of anthills/hazardous insects or toxic plants.  | ,C   | D        |                           |
| Playground area is free of holes and other tripping hazards.  | [P   |          |                           |
| Proper signage with rules, hours, and age- appropriate use is posted.   | D    | IT       | 5'gN3 Being made          |
| Playground area is properly fenced.   | D    |          | J                         |
| Self-latching gate works as designed.   |      | <u> </u> |                           |
| Surfacing °   | Pass | Fail     | Problem / Solution        |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | r/   | Ü        |                           |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  |      | ם        |                           |
| Surfacing material is free of glass, debris, or other foreign objects.  | rc/  | 0        |                           |
| Surfacing material is not compacting or deteriorating.  | -    | <b>6</b> |                           |
| Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.                       | re/  | В        |                           |
| Proper drainage prevents water from forming puddles.  | ď    | ď        |                           |
| Equipment Hazards   | Pass | Fail     | Problem / Solution        |
| Equipment is not damaged or vandalized.   | 10/  | ·D       |                           |
| Equipment is free from sharp points, corners, or edges.   | r./  | ū        |                           |
| Protective caps or plugs are not missing or damaged.  | 12   | a        |                           |
| Equipment is free of potential clothing entanglement hazards.   |      |          |                           |
| Equipment free of pinch and crush points or exposed moving parts.   | 0    | О        |                           |
| Equipment is free of rust, rot, cracks, and splinters.  | Ti-  | П        | some (V3+ / sandand Paint |
| Equipment is free of entrapments.   | ני   | ū        |                           |
| Equipment is safely anchored.   | F./  |          |                           |
| Swings  | Pass | Fail     | Problem / Solution        |
| Hardware and chains are in good condition.  | 17/  |          |                           |
| Swings are a safe distance from other playground  | /    |          |                           |
| equipment.  | F./  |          |                           |
| equipment. Swings are 24 inches apart.  |      | ם        |                           |
| Swings are 24 inches apart. Edges of seats are smooth and free from obstructions.   | · ·  | -        |                           |
| Swings are 24 inches apart.  Edges of seats are smooth and free from  | Fz/  | D.       |                           |

(To be completed monthly.)

WilsoN

| Slides  | Pass | Fail | Problem / Solution |
|---|------|------|--------------------|
| Slides are free of obstructions and protrusions.  | 77.  | 0    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | 7    | - D  |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 5    |      |                    |
| Average incline is less than 30 degrees.  | מ    |      |                    |
| Exit regions are level.   | rt/  | ם    |                    |
| Metal slides are shaded to prevent overheating.   | _ ·  | ū    |                    |
| Climbing Equipment  | Pass | Fail | Problem / Solution |
| Hand grips are secured and do not rotate.   | E/   | D    |                    |
| Rope or chain ladders are anchored at both ends.  | 12/  |      |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | 5    | 0    |                    |
| Seesaws   | Pass | Fail | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  |      | ם '  |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. |      |      | N/K                |
| Fulcrums/pivot points are free of pinch or crush hazards.   | 0    | ם    |                    |
| Handholds are provided at each seating position.  | C    |      |                    |
| Inspector name, signature, and completion date  | •    |      |                    |
| Name: Eddie Tyler Signature: Coldie Tyler Wilson Park   |      |      | Date: 2 - 13 - 23  |
| Wilson Park   |      |      |                    |

| 2   | _    | G    | eorge | Adams                  |
|---|------|------|-------|------------------------|
| General Inspection  | Pass | Fail | ,     | Problem / Solution     |
| Playground area is free of litter and debris.   | Ľ.   |      |       |                        |
| Playground area is free of anthills/hazardous insects or toxic plants.  | TE   |      |       |                        |
| Playground area is free of holes and other tripping hazards.  | 10/  | 0    |       |                        |
| Proper signage with rules, hours, and age- appropriate use is posted.   | Ü    |      |       |                        |
| Playground area is properly fenced.   |      |      |       |                        |
| Self-latching gate works as designed.   | C    | 0    |       |                        |
| Surfacing   | Pass | Fail |       | Problem / Solution     |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | □    | D    |       |                        |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | П    | ם    |       |                        |
| Surfacing material is free of glass, debris,<br>or other foreign objects.   | D    | ם    |       |                        |
| Surfacing material is not compacting or deteriorating.  | C    | П    |       |                        |
| Rubber wear mats are used under high-traffic-use<br>areas and covered by sufficient depth of<br>surfacing material.                 | П    | Б    |       |                        |
| Proper drainage prevents water from forming puddles.  |      | О    |       |                        |
| Equipment Hazards   | Pass | Fail |       | Problem / Solution     |
| Equipment is not damaged or vandalized.   |      | П    |       |                        |
| Equipment is free from sharp points, corners, or edges.   | D.   | נו   |       |                        |
| Protective caps or plugs are not missing or damaged.  | П    |      |       | •                      |
| Equipment is free of potential clothing entanglement hazards.   | ū    | נים  |       |                        |
| Equipment free of pinch and crush points or exposed moving parts.   | C    | Ľ.   |       |                        |
| Equipment is free of rust, rot, cracks, and splinters.  | Е    | П    |       |                        |
| Equipment is free of entrapments.   |      | O    | i.    |                        |
| Equipment is safely anchored.   | L)   | מ    | _     |                        |
| Swings  | Pašš | Fail |       | Problem / Solution     |
| Hardware and chains are in good condition.  |      |      | Hard  | ware will Be Replaced  |
| Swings are a safe distance from other playground equipment.   | 6    | ū    |       | ware will Be Replaced  |
| Swings are 24 inches apart.   | ū    | 5/   | will  | Need to Remove I swing |
| Edges of seats are smooth and free from obstructions.   | Ft.  | ם    | · ·   |                        |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | Iē,  |      |       |                        |

| 2   |          | Ge     | orge               | Adams              |
|---|----------|--------|--------------------|--------------------|
| Slides  | Pass     | Fail   |                    | Problem / Solution |
| Slides are free of obstructions and protrusions.  | 5        |        |                    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | no/      |        |                    |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | E E      |        |                    | ,                  |
| Average incline is less than 30 degrees.  |          |        |                    |                    |
| Exit regions are level.   | E        |        |                    |                    |
| Metal slides are shaded to prevent overheating.   | Z.       |        | - · · <del>-</del> |                    |
| Climbing Equipment  | Pass     | Fail   |                    | Problem / Solution |
| Hand grips are secured and do not rotate.   | G/       |        |                    |                    |
| Rope or chain ladders are anchored at both ends.  |          | D      |                    |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | [2       |        |                    |                    |
| Seesaws   | Pass     | Fail   |                    | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | E P      | ,<br>ם |                    |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. |          | . 🗆    |                    |                    |
| Fulcrums/pivot points are free of pinch or crush hazards.   |          | . 🗅    |                    | *                  |
| Handholds are provided at each seating position.  | 12/      |        |                    |                    |
| Inspector name, signature, and completion date  |          |        |                    |                    |
| Name: <u>Eddie Tyler</u> Signature: <u>Cddie Jyler</u> George Adams Pari  | <b>K</b> |        |                    | Date: 2 - 13 - 23  |

(To be completed monthly.)

Bay Front

| General Inspection  | Pass | Fail | Problem / Solution |
|---|------|------|--------------------|
| Playground area is free of litter and debris.   | TZ/  |      |                    |
| Playground area is free of anthills/hazardous insects or toxic plants.  | 2    | П    |                    |
| Playground area is free of holes and other tripping hazards.  | 6    |      |                    |
| Proper signage with rules, hours, and age- appropriate use is posted.   | V.   | C    |                    |
| Playground area is properly fenced.   | D    | Б    | 1/1                |
| Self-latching gate works as designed.   | 6    | 0    | 11/ 7              |
| Surfacing   | Pass | Fail | Problem / Solution |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | 1.   | D    |                    |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | ם    | Г    | NA                 |
| Surfacing material is free of glass, debris, or other foreign objects.  |      | Ü    |                    |
| Surfacing material is not compacting or deteriorating.  | 13/  | מ    |                    |
| Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.                       | C    | 0    | MA                 |
| Proper drainage prevents water from forming puddles.  | 7.   | c c  |                    |
| Equipment Hazards   | Pass | Fail | Problem / Solution |
| Equipment is not damaged or vandalized.   | 12   | П    |                    |
| Equipment is free from sharp points, corners, or edges.   | r/   | מ    |                    |
| Protective caps or plugs are not missing or damaged.  | 1    |      |                    |
| Equipment is free of potential clothing entanglement hazards.   | r.   | נו   |                    |
| Equipment free of pinch and crush points or exposed moving parts.   | re/  | []   |                    |
| Equipment is free of rust, rot, cracks, and splinters.  | r/   | п    |                    |
| Equipment is free of entrapments.   | I?   | ū    |                    |
| Equipment is safely anchored.   | 70   |      |                    |
| Swings  | Pass | Fail | Problem / Solution |
| Hardware and chains are in good condition.  |      | ח    |                    |
| Swings are a safe distance from other playground equipment.   | L.   | מ    |                    |
| Swings are 24 inches apart.   | C    | D    | \//A               |
| Edges of seats are smooth and free from obstructions.   | г.   | П    |                    |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | E    | C    |                    |

(To be completed monthly.)

Bay Front

|   |      | Bay      | Front                                 |
|---|------|----------|---------------------------------------|
| Slides  | Pass | Fail     | Problem / Solution                    |
| Slides are free of obstructions and protrusions.  | F    |          |                                       |
| Equipped with platforms to facilitate access to the sitting position.   | ري   | П        |                                       |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 6    | ם        |                                       |
| Average incline is less than 30 degrees.  | F6/  |          |                                       |
| Exit regions are level.   | ₽/   | ū        |                                       |
| Metal slides are shaded to prevent overheating.   | E    | ۵        |                                       |
| Climbing Equipment  | Pass | Fail     | Problem / Solution                    |
| Hand grips are secured and do not rotate.   | 5/   | o l      |                                       |
| Rope or chain ladders are anchored at both ends.  |      |          |                                       |
| Foot holds/rungs are in good condition and adequately spaced.   | E.   | П        |                                       |
| Seesaws   | Pass | Fail     | Problem / Solution                    |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | E/   | <u> </u> |                                       |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | 0    |          | MA                                    |
| Fulcrums/pivot points are free of pinch or crush hazards.   | 0/   | מ        |                                       |
| Handholds are provided at each seating position.  | H=   | ם        | · · · · · · · · · · · · · · · · · · · |
| nspector name, signature, and completion date   |      |          |                                       |
| Name: Eddie Tyler   |      |          |                                       |

| Inspector name, signature, and completion date                        |                            |
|---|----------------------------|
| Name: <u>Eddie Tyler</u> Signature: <u>Oddie Tyler</u> Bay Front Park | Date: <u>Z ^ / 3 ^ 2 3</u> |
| La Belle  |                            |

(To be completed monthly.)

BuHer fly Park General Inspection Pass Fail **Problem / Solution** Playground area is free of litter and debris. Playground area is free of anthills/hazardous insects or toxic plants. Playground area is free of holes and other tripping hazards. Proper signage with rules, hours, and Sign Being made age-appropriate use is posted. Playground area is properly fenced. Self-latching gate works as designed.  $\Box$ Problem / Solution Fail Surfacing Pass Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, Γ. wood chips, rubber mulch). Surfacing material under and around equipment is  $\Gamma /$ П adequate depth (6-12 inches). Surfacing material is free of glass, debris,  $\Box$ or other foreign objects. Surfacing material is not compacting or deteriorating. П Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material. Proper drainage prevents water from D forming puddles. **Equipment Hazards Problem / Solution Pass** Fail Equipment is not damaged or vandalized. **[/** Equipment is free from sharp points, corners. П or edges. Protective caps or plugs are not missing or damaged.  $\Box$ Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed П moving parts. rust / sand and Paint ræ/ Equipment is free of rust, rot, cracks, and splinters. П ۲/ Equipment is free of entrapments.  $\Box$ Equipment is safely anchored. D **Swings** 'Fail Problem / Solution Pass Hardware and chains are in good condition. √ П Swings are a safe distance from other playground √  $\Box$ equipment. Swings are 24 inches apart. П Edges of seats are smooth and free from Ü obstructions. Adequate depths of surfacing material extend out a  $\Box$ minimum distance of twice the height of the swing.

(To be completed monthly.)

| 8 Butt  | er f     | -7/y | Park               |
|---|----------|------|--------------------|
| Slides  | Pass     |      | Problem / Solution |
| Slides are free of obstructions and protrusions.  | 0/       | ם    |                    |
| Equipped with platforms to facilitate access to the sitting position.   | €/       | П    |                    |
| Platforms are equipped with guardrails or equivalent protective equipment.  | 0/       | ۵    |                    |
| Average incline is less than 30 degrees.  | 7        |      |                    |
| Exit regions are level.   | Te/      | а    |                    |
| Metal slides are shaded to prevent overheating.   | 152      |      |                    |
| Climbing Equipment  | Pass     | Fail | Problem / Solution |
| Hand grips are secured and do not rotate.   | 17       |      |                    |
| Rope or chain ladders are anchored at both ends.  | 12/      | D    |                    |
| Foot holds/rungs are in good condition and adequately spaced.   | TV.      | 0    |                    |
| Seesaws   | Pass     | Fail | Problem / Solution |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | ۵        | L)   |                    |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | ß        | п    | W/A                |
| Fulcrums/pivot points are free of pinch or crush hazards.   | <u> </u> | G    | 10-1-              |
| Handholds are provided at each seating position.  | i⊐       | П    |                    |

| Name: Eddie Tyler      |                          |
|------------------------|--------------------------|
| Signature: Eddie Tyler | Date: <u>2 - 13 - 23</u> |

Benchs meel Painted Body curl and sit up Beuch Need to Be romoved OR Replaced

| 7 6   | lar              | e+     | Park                 |
|---|------------------|--------|----------------------|
| General Inspection  | Pašs             | Fail   | Problem / Solution   |
| Playground area is free of litter and debris.   | ₽                |        |                      |
| Playground area is free of anthills/hazardous insects or toxic plants.  | 2                |        |                      |
| Playground area is free of holes and other tripping hazards.  | 7                |        |                      |
| Proper signage with rules, hours, and age- appropriate use is posted.   | ₽/               | 0      | Sign Being made      |
| Playground area is properly fenced.   | r <sub>s</sub> / | D      |                      |
| Self-latching gate works as designed.   | /                | l la   |                      |
| Surfacing   | Pass             | Fail   | Problem / Solution   |
| Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). | F./              | a      |                      |
| Surfacing material under and around equipment is adequate depth (6-12 inches).  | <b>~</b>         | מ      |                      |
| Surfacing material is free of glass, debris,<br>or other foreign objects.   | 5/               | ם      |                      |
| Surfacing material is not compacting or deteriorating.  | IE/              | П      |                      |
| Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.                       | 5/               | C      |                      |
| Proper drainage prevents water from forming puddles.  | E/               | D      |                      |
| Equipment Hazards   | Pass             | 'Fail  | Problem / Solution   |
| Equipment is not damaged or vandalized.   | 5/               | П      |                      |
| Equipment is free from sharp points, corners, or edges.   | 77/              |        |                      |
| Protective caps or plugs are not missing or damaged.  | 10               |        |                      |
| Equipment is free of potential clothing entanglement hazards.   | 73/              | П      |                      |
| Equipment free of pinch and crush points or exposed moving parts.   | 12/              |        |                      |
| Equipment is free of rust, rot, cracks, and splinters.  | r/               | ם<br>ا |                      |
| Equipment is free of entrapments.   | П                | G      |                      |
| Equipment is safely anchored.   | Ŀ                | G      |                      |
| Swings  | Pass             | Fail   | * Problem / Solution |
| Hardware and chains are in good condition.  | [3/              |        |                      |
| Swings are a safe distance from other playground equipment.   | 2                | ם      | :                    |
| Swings are 24 inches apart.   | TE/              |        |                      |
| Edges of seats are smooth and free from obstructions.   | Te/              | ß      |                      |
| Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.                               | 17               | ם      |                      |
| ·   |                  |        | ·                    |

| <u> </u>  |                |       | Claret Park         |
|---|----------------|-------|---------------------|
| Slides  | Pass           | Fail  | Problem / Solution  |
| Slides are free of obstructions and protrusions.  | 8/             | ם     |                     |
| Equipped with platforms to facilitate access to the sitting position.   | 5⁄             | П     |                     |
| Platforms are equipped with guardrails or equivalent protective equipment.  | П              |       |                     |
| Average incline is less than 30 degrees.  | F              |       |                     |
| Exit regions are level.   | T:             | _ n   |                     |
| Metal slides are shaded to prevent overheating.   | T <sub>p</sub> |       |                     |
| Climbing Equipment  | Pass           | Fail  | Problem / Solution  |
| Hand grips are secured and do not rotate.   | 17/            | п     |                     |
| Rope or chain ladders are anchored at both ends.  | -/             | מ     |                     |
| Foot holds/rungs are in good condition and adequately spaced.   | [·             | c     |                     |
| Seesaws   | Pass           | Fail  | Problem / Solution  |
| Seesaws are free of cracks, corrosion, and other obvious structural defects.  | <b>v</b> /     | ם     |                     |
| Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. | F.             |       |                     |
| Fulcrums/pivot points are free of pinch or crush hazards.   | Tt.            | 'n    |                     |
| Handholds are provided at each seating position.  |                |       |                     |
| Inspector name, signature, and completion date  |                |       |                     |
| Name: Eddic Trier Signature: Claset Crossing P  | <u>.</u>       |       | 1 2 / 3 2 3         |
| Signature: Cadie Toyler   |                |       | Date: 2 ~ / 3 ~ 2 3 |
| Claset Crossing P   | ar K           | ,<br> | <u> </u>            |

(To be completed monthly.)

Light House Beach Pass Fail **General Inspection Problem / Solution** Playground area is free of litter and debris. 5/ П Playground area is free of anthills/hazardous insects をノ  $\Box$ or toxic plants. Playground area is free of holes and  $\nabla$ other tripping hazards. Proper signage with rules, hours, and Ċī. Signs Being made age-appropriate use is posted. Playground area is properly fenced. **17**/ Self-latching gate works as designed.  $\Box$ Fail Surfacing Pass **Problem / Solution** Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch). Surfacing material under and around equipment is 5 П adequate depth (6-12 inches). Surfacing material is free of glass, debris, Ci E/ or other foreign objects. R/ Surfacing material is not compacting or deteriorating. Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of  $\Box$ П surfacing material. Proper drainage prevents water from D forming puddles. **Equipment Hazards** Fail **Problem / Solution** Pass Equipment is not damaged or vandalized.  $\Box$ Equipment is free from sharp points, corners, Ð or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing  $\Box$ entanglement hazards. Equipment free of pinch and crush points or exposed  $\Box$ moving parts. sand and Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. D **Swings Problem / Solution Pass** Fail Hardware and chains are in good condition. П Swings are a safe distance from other playground  $\Box$  $\Box$ equipment. Swings are 24 inches apart. Edges of seats are smooth and free from П  $\Box$ obstructions. Adequate depths of surfacing material extend out a П minimum distance of twice the height of the swing.

(To be completed monthly.)

Lighthouse Beach

| Pass   | Fail<br>D       | Problem / Solution              |
|--------|-----------------|---------------------------------|
| D 50   |                 |                                 |
| T.     |                 |                                 |
|        | D.              |                                 |
| √      |                 |                                 |
|        |                 |                                 |
| √2     |                 |                                 |
| G/     |                 |                                 |
| Pass   | Fail            | Problem / Solution              |
| €/     |                 |                                 |
| G/     | ۵               |                                 |
| ري     | а               |                                 |
| Pass   | Fail            | Problem / Solution              |
| G      |                 |                                 |
| D      | П               | N/A                             |
| כז     |                 |                                 |
| a      | п               |                                 |
|        |                 |                                 |
|        |                 |                                 |
|        |                 | Date: 2-13-23                   |
|        |                 |                                 |
| init i | lous e          | Beach                           |
|        | Pass Pass D D D | Pass Fail  Pass Fail  Pass Fail |

(To be completed monthly.)

Light novse Beach Pavillar General Inspection Pass Fail Problem / Solution Playground area is free of litter and debris. Playground area is free of anthills/hazardous insects or toxic plants. Playground area is free of holes and other tripping hazards. Proper signage with rules, hours, and SigNs Being made Ę, age-appropriate use is posted. Playground area is properly fenced.  $\Box$ Self-latching gate works as designed. [Z/ Surfacing Fail Pass. Problem / Solution Approved surfacing material is used (i.e. solid rubber. artificial grass or turf, play sand, pea gravel, П wood chips, rubber mulch). Surfacing material under and around equipment is П adequate depth (6-12 inches). Surfacing material is free of glass, debris, or other foreign objects. Surfacing material is not compacting or deteriorating. П Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material. Proper drainage prevents water from forming puddles. **Equipment Hazards Pass** Fail **Problem / Solution** Equipment is not damaged or vandalized. 7 Equipment is free from sharp points, corners, П or edges. Protective caps or plugs are not missing or damaged. П Equipment is free of potential clothing П entanglement hazards. Equipment free of pinch and crush points or exposed Γ. moving parts. Equipment is free of rust, rot, cracks, and splinters.  $\Box$ Equipment is free of entrapments  $\Box$ Equipment is safely anchored.  $\Box$ **Swings** Problem / Solution Pass Fail Hardware and chains are in good condition. Swings are a safe distance from other playground  $\Box$  $\Box$ equipment. Swings are 24 inches apart. G Edges of seats are smooth and free from D obstructions. Adequate depths of surfacing material extend out a Ę. П minimum distance of twice the height of the swing.

(To be completed monthly.)

PavilloN Light House Slides Pass Fail Problem / Solution Slides are free of obstructions and protrusions. П Equipped with platforms to facilitate access 1 П to the sitting position. Platforms are equipped with quardrails or equivalent IJ protective equipment. Average incline is less than 30 degrees. Exit regions are level. Metal slides are shaded to prevent overheating. П **Climbing Equipment Pass** Fail **Problem / Solution** Hand grips are secured and do not rotate. Rope or chain ladders are anchored at both ends.  $\Box$  $\Box$ Foot holds/rungs are in good condition and П adequately spaced. Seesaws Pass. Fail Problem / Solution Seesaws are free of cracks, corrosion,  $\Box$ and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact П with the ground. Fulcrums/pivot points are free of pinch Πì or crush hazards. Handholds are provided at each seating position. П Inspector name, signature, and completion date Name: Edice Tylet

Signature: Oddie Tylet

Lighthouse Beach

Next to PavilloN Date: 2-13-23