General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	Ø.	0	
Playground area is free of anthills/hazardous insects or toxic plants.	V		
Playground area is free of holes and other tripping hazards.	12/	а	
Proper signage with rules, hours, and age- appropriate use is posted.		NO SENC	Available Signs Are being MALE
Playground area is properly fenced.			
Self-latching gate works as designed.	0		
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		0	
Surfacing material under and around equipment is adequate depth (6-12 inches).	e	0	
Surfacing material is free of glass, debris, or other foreign objects.	Ø	۵	
Surfacing material is not compacting or deteriorating.	E	<u> </u>	
Rubber wear mats are used under high-traffic-use areas and are in good condition	øſ	0	
Proper drainage prevents water from forming puddles.	2	Ö	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		0	
Equipment is free from sharp points, corners, or edges.	N	0	
Protective caps or plugs are not missing or damaged.	d	0	
Equipment is free of potential clothing entanglement hazards.		G	
Equipment free of pinch and crush points or exposed moving parts.		G	
Equipment is free of rust, rot, cracks, and splinters.	2	o	
Equipment is free of entrapments.	П		
Equipment is safely anchored.	0/		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Ø	0 "	
Swings are a safe distance from other playground equipment.		G	
Swings are 24 inches apart.	8	0 15	
Edges of seats are smooth and free from obstructions.	7		
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		0	

ıtion
ıtion
·
ition
2 Z

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	E.		
Playground area is free of anthills/hazardous insects or toxic plants.	2		
Playground area is free of holes and other tripping hazards.	œ		
Proper signage with rules, hours, and age- appropriate use is posted.		Z NO	Signs Available, Signs are being Made
Playground area is properly fenced.			
Self-latching gate works as designed.		0	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	ď	0	But will need to be Replace in Couple Years
Surfacing material under and around equipment is adequate depth (6-12 inches).		0	,
Surfacing material is free of glass, debris, or other foreign objects.	a	О	
Surfacing material is not compacting or deteriorating.	Œ		
Rubber wear mats are used under high-traffic-use areas and are in good condition	6	а	
Proper drainage prevents water from forming puddles.	e/	0	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	•		
Equipment is free from sharp points, corners, or edges.	e e	0	
Protective caps or plugs are not missing or damaged.	R.		
Equipment is free of potential clothing entanglement hazards.	0		
Equipment free of pinch and crush points or exposed moving parts.		D	
Equipment is free of rust, rot, cracks, and splinters.		□ Ru	TSBT, SAUL DOWN AND PAINT RUT SPOT
Equipment is free of entrapments.	0		
Equipment is safely anchored.	C	D	2
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	9		
Swings are a safe distance from other playground equipment.			
Swings are 24 inches apart.	2		
Edges of seats are smooth and free from obstructions.	6		
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	8		

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	8		
Equipped with platforms to facilitate access to the sitting position.	₽	а	
Platforms are equipped with guardrails or equivalent protective equipment.	5		
Average incline is less than 30 degrees.	0		
Exit regions are level.	<u>-</u>		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	8	0	
Rope or chain ladders are anchored at both ends.	B	D.	
Foot holds/rungs are in good condition and adequately spaced.	D'	0	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	0	0	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		0	11/A
Fulcrums/pivot points are free of pinch or crush hazards.	0	0	
Handholds are provided at each seating position.		0	
Inspector name, signature, and completion date			
Name: Joe Rodrigue 1 Signature: Joe Rode & Butter Fly PACK			Date: 10-6-22

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			
Playground area is free of anthills/hazardous insects or toxic plants.			
Playground area is free of holes and other tripping hazards.	G/		
Proper signage with rules, hours, and age- appropriate use is posted.	D	Nos	igns AVAILABLE, Signs are being MALE
Playground area is properly fenced.	0	0	, , , , , , , , , , , , , , , , , , , ,
Self-latching gate works as designed.	.0	0	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	8	0	
Surfacing material under and around equipment is adequate depth (6-12 inches).		0	
Surfacing material is free of glass, debris, or other foreign objects.	0	0	
Surfacing material is not compacting or deteriorating.	□		
Rubber wear mats are used under high-traffic-use areas and are in good condition	ď	С	
Proper drainage prevents water from forming puddles.	Z.	О	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	D/	۵	
Equipment is free from sharp points, corners, or edges.		a	
Protective caps or plugs are not missing or damaged.	G/		
Equipment is free of potential clothing entanglement hazards.	Б	а	
Equipment free of pinch and crush points or exposed moving parts.	D	а	
Equipment is free of rust, rot, cracks, and splinters.		Rust	SPOT, SAND DOWN PRINT RUST SPOT
Equipment is free of entrapments.			,
Equipment is safely anchored.	0	0	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
Swings are a safe distance from other playground equipment.	es .	0	
Swings are 24 inches apart.	3		
Edges of seats are smooth and free from obstructions.	d		
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	E/	0	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	8		
Equipped with platforms to facilitate access to the sitting position.	9	a	
Platforms are equipped with guardrails or equivalent protective equipment.	6		
Average incline is less than 30 degrees.		0	
Exit regions are level.	2	0	
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			
Rope or chain ladders are anchored at both ends.		0	
Foot holds/rungs are in good condition and adequately spaced.	a	0	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		0	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	0	О	N//a
Fulcrums/pivot points are free of pinch or crush hazards.		0	
Handholds are provided at each seating position.		0	
Inspector name, signature, and completion date			
Name: Joe Rodriguer Signature: Ja. Role Play Ground Next to Hair Longue	Rd,	Cry Park	Date: 10 - 6 - 2 Z

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	8	0	
Playground area is free of anthills/hazardous insects or toxic plants.	9		
Playground area is free of holes and other tripping hazards.		0	
Proper signage with rules, hours, and age- appropriate use is posted.		€ No	SIGN AVAILABLE, SIGNS ARE being MADE
Playground area is properly fenced.	D		
Self-latching gate works as designed.		a	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		0	
Surfacing material under and around equipment is adequate depth (6-12 inches).			
Surfacing material is free of glass, debris, or other foreign objects.		0	
Surfacing material is not compacting or deteriorating.	8		
Rubber wear mats are used under high-traffic-use areas and are in good condition		0	
Proper drainage prevents water from forming puddles.	2	0	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	ø		
Equipment is free from sharp points, corners, or edges.	6	0	
Protective caps or plugs are not missing or damaged.			
Equipment is free of potential clothing entanglement hazards.			
Equipment free of pinch and crush points or exposed moving parts.		Ö	
Equipment is free of rust, rot, cracks, and splinters.		2	Sakust, SANDLY DOW AND PAINTING
Equipment is free of entrapments.			
Equipment is safely anchored.	2	0	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
Swings are a safe distance from other playground equipment.	6	D.	
Swings are 24 inches apart.	2		
Edges of seats are smooth and free from obstructions.	8	0	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	8		

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	P.		
Equipped with platforms to facilitate access to the sitting position.	6	0	
Platforms are equipped with guardrails or equivalent protective equipment.	d	0	
Average incline is less than 30 degrees.			
Exit regions are level.	•	o	
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			
Rope or chain ladders are anchored at both ends.	12	0	
Foot holds/rungs are in good condition and adequately spaced.			
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П	D	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	П	О	N/A
Fulcrums/pivot points are free of pinch or crush hazards.		0	
Handholds are provided at each seating position.		0	
Inspector name, signature, and completion date			
Name: Joe Robrigue 7 Signature: Rod Robrigue 7	P	16	Date:

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	8		
Playground area is free of anthills/hazardous insects or toxic plants.	ø	0	
Playground area is free of holes and other tripping hazards.	3	0	
Proper signage with rules, hours, and age- appropriate use is posted.		No Signs	AVAILABLE SONS Are being made
Playground area is properly fenced.			
Self-latching gate works as designed.		۵	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	œ⁄	а	
Surfacing material under and around equipment is adequate depth (6-12 inches).	d		
Surfacing material is free of glass, debris, or other foreign objects.	ø		
Surfacing material is not compacting or deteriorating.	e	0	
Rubber wear mats are used under high-traffic-use areas and are in good condition	Ø	0	
Proper drainage prevents water from forming puddles.	6	0	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		0	
Equipment is free from sharp points, corners, or edges.	el el	0	
Protective caps or plugs are not missing or damaged.	8	0	
Equipment is free of potential clothing entanglement hazards.		0	
Equipment free of pinch and crush points or exposed moving parts.		0	
Equipment is free of rust, rot, cracks, and splinters.	CE	E Rust S	BT, SANdING DRUN AND PRINT
Equipment is free of entrapments.		0	, 2
Equipment is safely anchored.	er	0	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
Swings are a safe distance from other playground equipment.	П	0	1//1
Swings are 24 inches apart.		0	
Edges of seats are smooth and free from obstructions.		D	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	0		
Equipped with platforms to facilitate access to the sitting position.	0		
Platforms are equipped with guardrails or equivalent protective equipment.		o	
Average incline is less than 30 degrees.		o .	
Exit regions are level.	0	0	70.50
Metal slides are shaded to prevent overheating.		0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	D'		
Rope or chain ladders are anchored at both ends.	6		
Foot holds/rungs are in good condition and adequately spaced.	6	0	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	0	0	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	0	П	M/p
Fulcrums/pivot points are free of pinch or crush hazards.	П		/ // /
Handholds are provided at each seating position.			
Inspector name, signature, and completion date			
Name: Joe Rodrigue - Signature: Que Rodes Play Ground Next to Ashley Field			Date: 10-6-22
MAU Ground Next TO AShley Fiel	d		

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			
Playground area is free of anthills/hazardous insects or toxic plants.	2	۵	
Playground area is free of holes and other tripping hazards.		0	
Proper signage with rules, hours, and age- appropriate use is posted.	0	a No	Signs Available, Signs are being made
Playground area is properly fenced.	0	0	
Self-latching gate works as designed.	0		
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		٥	
Surfacing material under and around equipment is adequate depth (6-12 inches).		0	
Surfacing material is free of glass, debris, or other foreign objects.		0	
Surfacing material is not compacting or deteriorating.		۵	
Rubber wear mats are used under high-traffic-use areas and are in good condition			
Proper drainage prevents water from forming puddles.			
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	E		
Equipment is free from sharp points, corners, or edges.		0	
Protective caps or plugs are not missing or damaged.	12		
Equipment is free of potential clothing entanglement hazards.		Ö	
Equipment free of pinch and crush points or exposed moving parts:			
Equipment is free of rust, rot, cracks, and splinters.	đ	Ru	ST SAT, SANDLY, AND PRINT
Equipment is free of entrapments.	0/		
Equipment is safely anchored.	e		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
Swings are a safe distance from other playground equipment.	D		
Swings are 24 inches apart.		0	NA
Edges of seats are smooth and free from obstructions.		0	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	П	0	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.			
Equipped with platforms to facilitate access to the sitting position.	4		
Platforms are equipped with guardrails or equivalent protective equipment.	e e	0	
Average incline is less than 30 degrees:		a	
Exit regions are level.		D	
Metal slides are shaded to prevent overheating.		Q	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	2		
Rope or chain ladders are anchored at both ends.	0	0	
Foot holds/rungs are in good condition and adequately spaced.		Ö	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	0	D	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	О	0	NA
Fulcrums/pivot points are free of pinch or crush hazards.	۵		771
Handholds are provided at each seating position.	0		
Inspector name, signature, and completion date			
Name: Je Rodriguez Signature: Ja Rolg Plan Ground on Beach Lichthaue B	2.401		Date: 10-5-22

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			
Playground area is free of anthills/hazardous insects or toxic plants.	3		
Playground area is free of holes and other tripping hazards.		۵	
Proper signage with rules, hours, and age- appropriate use is posted.	P. S.	E)	VOSIGNS AVAILANC, SIGNS ALL being MAde
Playground area is properly fenced.		а	
Self-latching gate works as designed.		0	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		а	
Surfacing material under and around equipment is adequate depth (6-12 inches).	G.		
Surfacing material is free of glass, debris, or other foreign objects.			
Surfacing material is not compacting or deteriorating.			
Rubber wear mats are used under high-traffic-use areas and are in good condition	6		
Proper drainage prevents water from forming puddles.		Ġ	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	Ø		
Equipment is free from sharp points, corners, or edges.	1		
Protective caps or plugs are not missing or damaged.	b		
Equipment is free of potential clothing entanglement hazards:	D		
Equipment free of pinch and crush points or exposed moving parts.	0	0	
Equipment is free of rust, rot, cracks, and splinters.	6	3	RUST SPOT, SANJING DOWN AND PRINT SPOT
Equipment is free of entrapments.	0/		
Equipment is safely anchored.	6		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			2
Swings are a safe distance from other playground equipment.	Ö		
Swings are 24 inches apart.	Ð		/V/A
Edges of seats are smooth and free from obstructions.	۵	©.	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	D	D	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	4		
Equipped with platforms to facilitate access to the sitting position.	6	0	
Platforms are equipped with guardrails or equivalent protective equipment.	6	О	
Average incline is less than 30 degrees.		0	
Exit regions are level.	6		
Metal slides are shaded to prevent overheating.	D		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	60	0	
Rope or chain ladders are anchored at both ends.	c		
Foot holds/rungs are in good condition and adequately spaced.	6		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		0	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	О		NA
Fulcrums/pivot points are free of pinch or crush hazards.		0	
Handholds are provided at each seating position.			
Inspector name, signature, and completion date			
Name: Joe Rouriguez Signature: Que Rodge			Date: /0-5-22
Signature: Que Roder PlayGraves Next To Splash Pad			
THE TOTAL THE			The state of the s

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	ZZ		
Playground area is free of anthills/hazardous insects or toxic plants.	ď	0	
Playground area is free of holes and other tripping hazards.	d		
Proper signage with rules, hours, and age- appropriate use is posted.		S N	OSIGNS AVAILABLE, SIGNS Are Deing Made
Playground area is properly fenced.			· · · · · · · · · · · · · · · · · · ·
Self-latching gate works as designed.	0	0	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	d	D	
Surfacing material under and around equipment is adequate depth (6-12 inches).	Ø	0	
Surfacing material is free of glass, debris, or other foreign objects.	6	D	
Surfacing material is not compacting or deteriorating.	7		
Rubber wear mats are used under high-traffic-use areas and are in good condition	6	0	
Proper drainage prevents water from forming puddles.	6	D	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	Ø		
Equipment is free from sharp points, corners, or edges.	d	0	
Protective caps or plugs are not missing or damaged.	d		
Equipment is free of potential clothing entanglement hazards.		0	
Equipment free of pinch and crush points or exposed moving parts.	n (
Equipment is free of rust, rot, cracks, and splinters.	d		
Equipment is free of entrapments:	0/		
Equipment is safely anchored.	6	D	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	0		
Swings are a safe distance from other playground equipment.	0	D.	
Swings are 24 inches apart.			N/A
Edges of seats are smooth and free from obstructions.	0	0	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	О	0	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	6		
Equipped with platforms to facilitate access to the sitting position.	6	a	
Platforms are equipped with guardrails or equivalent protective equipment.	d	0	
Average incline is less than 30 degrees.			
Exit regions are level.	d	0	
Metal slides are shaded to prevent overheating.		0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	ø		
Rope or chain ladders are anchored at both ends.	ď		
Foot holds/rungs are in good condition and adequately spaced.	6	0	,
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	0	0	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	0		NA
Fulcrums/pivot points are free of pinch or crush hazards.	а	0	
Handholds are provided at each seating position.	0		
Inspector name, signature, and completion date			
Name: JOE RODrigue Z Signature: Jan Rodging Lighthouse Beach Play GROUND NEX			Date: 10-5-27
LIGHTHOUSE BEACH PLAY GROUND NEX	T To	3 the	e YAVILION

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	10	а	
Playground area is free of anthills/hazardous insects or toxic plants.	6		
Playground area is free of holes and other tripping hazards.	6		
Proper signage with rules, hours, and age- appropriate use is posted.			UU SIGNS AVAILANCE, Signs are heine made
Playground area is properly fenced.			, , ,
Self-latching gate works as designed.			
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	6	0	
Surfacing material under and around equipment is adequate depth (6-12 inches).	6	0	
Surfacing material is free of glass, debris, or other foreign objects.	6	п	
Surfacing material is not compacting or deteriorating.	d		
Rubber wear mats are used under high-traffic-use areas and are in good condition	d	0	
Proper drainage prevents water from forming puddles.	4	0	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	Ø		
Equipment is free from sharp points, corners, or edges.	ઇ	0	
Protective caps or plugs are not missing or damaged.	e	0	
Equipment is free of potential clothing entanglement hazards.		Φ	
Equipment free of pinch and crush points or exposed moving parts.	D	٥	
Equipment is free of rust, rot, cracks, and splinters.	-6		
Equipment is free of entrapments.	0		
Equipment is safely anchored.	6		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		đ	BAD HARdWARE, REPLACE HARdWARE
Swings are a safe distance from other playground equipment.	d	a	·
Swings are 24 inches apart.	П	BA	10T 24 INCh APART, REMOVE I SWING TO MAKE IT
Edges of seats are smooth and free from obstructions.	6	o	10T 24 Inch APART, Remove & Swing To MAKE it
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	9		

Slides	Pass	Fail	Problem / Solution	
Slides are free of obstructions and protrusions.				
Equipped with platforms to facilitate access to the sitting position.	8	0		
Platforms are equipped with guardrails or equivalent protective equipment.	8	0		
Average incline is less than 30 degrees.				
Exit regions are level.	9	O		
Metal slides are shaded to prevent overheating.	0	0		
Climbing Equipment	Pass	Fail	Problem / Solution	
Hand grips are secured and do not rotate.	12		Œ.	
Rope or chain ladders are anchored at both ends.	8			
Foot holds/rungs are in good condition and adequately spaced.	12	0		
Seesaws	Pass	Fail	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	•	0		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	9			
Fulcrums/pivot points are free of pinch or crush hazards.	9			
Handholds are provided at each seating position.	9	D		
Inspector name, signature, and completion date				
Name: Joe Robriguez Signature: Joe Roby Canno Adamis Pook			Date: 10-6-27	_