City Park			Ashler Field 10-6.23
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	T	г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	y	$\mathcal{N}$
Playground area is properly fenced.	г	г	NA
Self-latching gate works as designed.	1	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	~	۲	
Surfacing material under and around equipment is adequate depth (6-12 inches).	7		
Surfacing material is free of glass, debris, or other foreign objects.	¥	Г	
Surfacing material is not compacting or deteriorating.	7	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Γ	·	
Proper drainage prevents water from forming puddles.	g-	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	M	Γ	
Equipment is free from sharp points, corners, or edges.	Y	Γ	*
Protective caps or plugs are not missing or damaged.	1-	f	
Equipment is free of potential clothing entanglement hazards.	Ā	٢	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	around a from screws
Equipment is free of entrapments.	-15	Г	
Equipment is safely anchored.	Ø	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	. г	г	No Swings
Swings are 24 inches apart.	г	г	
Edges of seats are smooth and free from obstructions.	г	г	
Adaquato danthe of curfacing material avtand out a			

City Part	a Maria	Ashley	Field
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	W.		
Equipped with platforms to facilitate access to the sitting position.	1	С	
Platforms are equipped with guardrails or equivalent protective equipment.	1	О	
Average incline is less than 30 degrees.	П	П	
Exit regions are level.	F.	О	
Metal slides are shaded to prevent overheating.	П		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<b>7</b> /1		
Rope or chain ladders are anchored at both ends.	1	Б	
Foot holds/rungs are in good condition and adequately spaced.	7		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	n /	None
Fulcrums/pivot points are free of pinch or crush hazards.	г	a	
Handholds are provided at each seating position.	Г		
Inspector name, signature, and completion date			
Name: James Canter Signature: Mass Conter			Date: 16-6-23

City Part	2 × 2 11 × 2 × 3 × 3		(Pavillion) 10-6.23
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	п	
Playground area is free of anthills/hazardous insects or toxic plants.	7	Г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	P	N
Playground area is properly fenced.	г	Г	N/A
Self-latching gate works as designed.	Γ.	Г	NA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	4	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	r-	,
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	7	г	
Proper drainage prevents water from forming puddles.	F	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	٢	
Equipment is free from sharp points, corners, or edges.	1	۲	
Protective caps or plugs are not missing or damaged.	1	l.	
Equipment is free of potential clothing entanglement hazards.	r	Г	
Equipment free of pinch and crush points or exposed moving parts.	<b>9</b> 7	Г	
Equipment is free of rust, rot, cracks, and splinters.	7	Г	
Equipment is free of entrapments.	4	Г	
Equipment is safely anchored.	1	Γ	
Swings 5	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	r	Г	
Swings are a safe distance from other playground equipment.	k	Г	
Swings are 24 inches apart.	1	Г	
Edges of seats are smooth and free from obstructions.	1	г	
Adaquate denths of surfacing material extend out a			

Cito Part		The second second second	Pavillion
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7		and the state of t
Equipped with platforms to facilitate access to the sitting position.	D		
Platforms are equipped with guardrails or equivalent protective equipment.	T/	О	
Average incline is less than 30 degrees.	С		
Exit regions are level.	F		
Metal slides are shaded to prevent overheating.	С	О	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	1	Г	
Foot holds/rungs are in good condition and adequately spaced.	K	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			
and other obvious structural defects.	П		
	П	п	None
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			None
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	Г	п	None
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	C	n	None

Wilson Part		August Salata	10-6-23
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	17.	a de la companya de l
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	V	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	1	
Playground area is properly fenced.	Г	1	N/A
Self-latching gate works as designed.	T,	1	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		٢	
Surfacing material is free of glass, debris, or other foreign objects.	1	r	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	7	Г	
Proper drainage prevents water from forming puddles.	1	г	·
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Γ	
Equipment is free from sharp points, corners, or edges.	IJ	Γ	
Protective caps or plugs are not missing or damaged.	1	L-	
Equipment is free of potential clothing entanglement hazards.	R	г	
Equipment free of pinch and crush points or exposed moving parts.	1	Γ	
Equipment is free of rust, rot, cracks, and splinters.	Г	7	around some screws
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	r	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	+	Г	
Swings are a safe distance from other playground equipment.	7	г	, i
Swings are 24 inches apart.	7	Г	
our go are a remarkable aparts			

Wilson Part	a desired		10-6.23
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	П	And the second s
Equipped with platforms to facilitate access to the sitting position.	4	П	
Platforms are equipped with guardrails or equivalent protective equipment.	p	О	
Average incline is less than 30 degrees.			
Exit regions are level.	m		
Metal slides are shaded to prevent overheating.	О		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	R		
Rope or chain ladders are anchored at both ends.	7		
Foot holds/rungs are in good condition and adequately spaced.	W	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			Problem / Solution  None
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	п	П	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	Г	n	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	. n	n n	

George Adoms	American process		10-6-23
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	THE	Γ	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	A	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	*	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	r	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	P	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	Г	
Surfacing material is free of glass, debris, or other foreign objects.	- قل	г	
Surfacing material is not compacting or deteriorating.	F	Γ'	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	7	
Proper drainage prevents water from forming puddles.	1	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	г	
Equipment is free from sharp points, corners, or edges.	I	г	
Protective caps or plugs are not missing or damaged.	1	f***	
Equipment is free of potential clothing entanglement hazards.	Ī	г	
Equipment free of pinch and crush points or exposed moving parts.	0	Г	4
Equipment is free of rust, rot, cracks, and splinters.		Ī	Around screw/bolthoads
Equipment is free of entrapments.	M	Г	
Equipment is safely anchored.	M	۳	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	г	One New Swingset
Swings are a safe distance from other playground equipment.	i f	Г	one New Swingset in Process of install.
Swings are 24 inches apart.	7	г	
Edges of seats are smooth and free from obstructions.	7	г	
Adamse dantha of antestica metastal subsect of the		1	

George Hoons				10-6-23
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	V		NO SECULIARION POR	Manufacture of Manufa
Equipped with platforms to facilitate access to the sitting position.	7			
Platforms are equipped with guardrails or equivalent protective equipment.	a			
Average incline is less than 30 degrees.		П		
Exit regions are level.	7			
Metal slides are shaded to prevent overheating.	С	П		
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	1	П		
Rope or chain ladders are anchored at both ends.	V	Π		
Foot holds/rungs are in good condition and adequately spaced.	Ø	П		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	7	П		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	1	Г		
Fulcrums/pivot points are free of pinch or crush hazards.	1	О		
Handholds are provided at each seating position.	7	п		
Inspector name, signature, and completion date				
Name: James Conten Signature: Dos Otto				Date: 10-6-23

Bunfront	F	lay	ground	10-6-23
General Inspection	Pass			Problem / Solution
Playground area is free of litter and debris.	1	П		
Playground area is free of anthills/hazardous insects or toxic plants.	1	- r		
Playground area is free of holes and other tripping hazards.	1	Г		
Proper signage with rules, hours, and age- appropriate use is posted.	г	7		
Playground area is properly fenced.	г	г	NA	
Self-latching gate works as designed.	r.	Γ	N/A	
Surfacing Surfac	Pass	Fail		Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г		
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	Г		
Surfacing material is free of glass, debris, or other foreign objects.	1	r		
Surfacing material is not compacting or deteriorating.	1	г		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	г		
Proper drainage prevents water from forming puddles.	7	Г		
Equipment Hazards	Pass	Fail		Problem / Solution
Equipment is not damaged or vandalized.	7	Г		
Equipment is free from sharp points, corners, or edges.	1	Г		
Protective caps or plugs are not missing or damaged.	1	L-		
Equipment is free of potential clothing entanglement hazards.	A	Г		
Equipment free of pinch and crush points or exposed moving parts.	1.	г		
Equipment is free of rust, rot, cracks, and splinters.	V	Г		
Equipment is free of entrapments.	P	Г		
Equipment is safely anchored.	Ø.	г		
Swings	Pass	Fail		Problem / Solution
Hardware and chains are in good condition.	Ę	Г		
Swings are a safe distance from other playground equipment.	· r	г	No	Swings
=-1				
Swings are 24 inches apart.	Г			

Bantront		P	ayground
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	D		and the second difference of the second
Equipped with platforms to facilitate access to the sitting position.	7	0	
Platforms are equipped with guardrails or equivalent protective equipment.	y.	О	
Average incline is less than 30 degrees.	П		
Exit regions are level.	P		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	7	n	
Foot holds/rungs are in good condition and adequately spaced.	1	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	п	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г	Г	None
Fulcrums/pivot points are free of pinch or crush hazards.	Г	r.	
Handholds are provided at each seating position.	Γ	П	
Inspector name, signature, and completion date			
Name: Jamas Carter Signature: Ones Contar		-	Date: 10-6-23

(To be completed monthly.)

Clorat Crossing

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	D	
Playground area is free of anthills/hazardous insects or toxic plants.	1		
Playground area is free of holes and other tripping hazards.	Г	1	LARGE CRACKS In Bose and peremeter (Shifting
Proper signage with rules, hours, and age- appropriate use is posted.	г	1	
Playground area is properly fenced.	Г	г	NA
Self-latching gate works as designed.	F°.	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	7	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	F	ţ-	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	г	
Proper drainage prevents water from forming puddles.	1	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	8	Γ	
Equipment is free from sharp points, corners, or edges.	F	Г	
Protective caps or plugs are not missing or damaged.	1	l	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	7	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	f	Г	
Swings are a safe distance from other playground equipment.	7	Г	
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from obstructions.	1	Γ"	
Adaquata danthe of curfacing material outand out a		T	

(To be completed monthly.)

Clanet Crossing

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	П	
Equipped with platforms to facilitate access to the sitting position.	1	П	
Platforms are equipped with guardrails or equivalent protective equipment.	V		
Average incline is less than 30 degrees.	П	П	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	p	П	
Rope or chain ladders are anchored at both ends.	7	Б	
Foot holds/rungs are in good condition and adequately spaced.	¥		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	, r°	П	None
Fulcrums/pivot points are free of pinch or crush hazards.	С	а	
Handholds are provided at each seating position.	Г	П	
Inspector name, signature, and completion date			
Name: James Carter Signature: James Carter			Date: (6-6-23

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	7	Б	
Playground area is free of anthills/hazardous insects or toxic plants.	1		,
Playground area is free of holes and other tripping hazards.	Г	1	Irregularities in surface
Proper signage with rules, hours, and age- appropriate use is posted.	۳	1	
Playground area is properly fenced.	Г	г	N/A
Self-latching gate works as designed.	Γ.	٣	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Г	V	Heavy ware in creus.
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	ŗ-	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	7	г	
Proper drainage prevents water from forming puddles.	7	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	8	Γ	
Equipment is free from sharp points, corners, or edges.	*	г	
Protective caps or plugs are not missing or damaged.	1	L-	
Equipment is free of potential clothing entanglement hazards.	7	۲	
Equipment free of pinch and crush points or exposed moving parts.	(JP)	Г	
Equipment is free of rust, rot, cracks, and splinters.	г	7	Around screws
Equipment is free of entrapments.	7	Г	
Equipment is safely anchored.	V	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	W	Γ	
Swings are a safe distance from other playground equipment.	7	Г	
Swings are 24 inches apart.	N	г	
Edges of seats are smooth and free from obstructions.	7	г	

Butterfly Part			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	1		
Platforms are equipped with guardrails or equivalent protective equipment.	1	О	
Average incline is less than 30 degrees.	Г	П	
Exit regions are level.	V		
Metal slides are shaded to prevent overheating.	П		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F		
Rope or chain ladders are anchored at both ends.	7	П	
Foot holds/rungs are in good condition and adequately spaced.	M)	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П	С	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Γ	е	None
Fulcrums/pivot points are free of pinch or crush hazards.	Г	О	
Handholds are provided at each seating position.	Г	П	
Inspector name, signature, and completion date			
Name: Janes Carter Signature:			

General Inspection	Pass		Plana round Problem / Solution
Playground area is free of litter and debris.	1	г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	1	Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	l r	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	N.	г	Sand base
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Γ	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	7	
Proper drainage prevents water from forming puddles.	7	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	7	Г	
Protective caps or plugs are not missing or damaged.	1	l	· ·
Equipment is free of potential clothing entanglement hazards.	8	٢	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	Γ	N	Some rust around screw head
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	F	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.		Г	
Swings are 24 inches apart.	г	г	No Swings
Edges of seats are smooth and free from			•

LH Beach (	Beac	14	Planground)
Slides	Pass		Problem / Solution
Slides are free of obstructions and protrusions.	7		
Equipped with platforms to facilitate access to the sitting position.	F		
Platforms are equipped with guardrails or equivalent protective equipment.	11		
Average incline is less than 30 degrees.		D	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.		П	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	1	П	
Foot holds/rungs are in good condition and adequately spaced.	1	п	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	п	п	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	П	٣	None
Fulcrums/pivot points are free of pinch or crush hazards.	П	п	
Handholds are provided at each seating position.	Г	П	
Inspector name, signature, and completion date			
Name: James Canter Signature: Jam Cat			Date: 10-6-23

Lighthouse Beach		ur i de le ur i hedge	Splashpad Plunground 10-5
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	8		
Playground area is free of anthills/hazardous insects or toxic plants.	7	г	
Playground area is free of holes and other tripping hazards.	Г	K	hole beneathy hanging
Proper signage with rules, hours, and age- appropriate use is posted.	7	г	rings
Playground area is properly fenced.	г	Г	NIA
Self-latching gate works as designed.	r,	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	6	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	r	
Surfacing material is not compacting or deteriorating.	W	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	1	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Г	
Equipment is free from sharp points, corners, or edges.	7	Γ	
Protective caps or plugs are not missing or damaged.	9	-	
Equipment is free of potential clothing entanglement hazards.	P	Γ	
Equipment free of pinch and crush points or exposed moving parts.	1	۲	
Equipment is free of rust, rot, cracks, and splinters.	Ī	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.	·	Г	No Swings
Swings are 24 inches apart.	г	Г	
Edges of seats are smooth and free from obstructions.	Г	г	
Al all de et all all a			

Lighthouse	1	Paville	17 Plat CHAPUNA)
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	п (	Splashpad)
Equipped with platforms to facilitate access to the sitting position.	7		
Platforms are equipped with guardrails or equivalent protective equipment.	Ø	D	
Average incline is less than 30 degrees.	Г	П	
Exit regions are level.	W	D	
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	7	П	
Foot holds/rungs are in good condition and adequately spaced.	Ħ	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,	Г	Г	
and other obvious structural defects.			
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г	n	None
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			None
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	Г	п	None
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	Г	n	None

Lighthouse (1	ov i	1110	10/6/23
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	9	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	r	
Playground area is free of holes and other tripping hazards.	1	г	
Proper signage with rules, hours, and age- appropriate use is posted.	7	г	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г	Г	n //
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	P	٦	
Surfacing material under and around equipment is adequate depth (6-12 inches).	7	Г	
Surfacing material is free of glass, debris, or other foreign objects.	The	t_	
Surfacing material is not compacting or deteriorating.	7	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	г	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	7	Г	
Protective caps or plugs are not missing or damaged.	1	г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.		г	
Swings are 24 inches apart.	Г	Г	No Swass
Edges of seats are smooth and free from obstructions.	Γ	r	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Γ-	ŗ	