George Adams / San At	1ton	0 5%	<i>+</i>
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	/	Γ.	2
Playground area is free of anthills/hazardous insects or toxic plants.	~	Г	
Playground area is free of holes and other tripping hazards.		F	·
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Г	Г	NH.
Self-latching gate works as designed.	Γ.	-	NA
Surfacing (1) 2 30 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	г	1	missing material funds new surfa
Surfacing material under and around equipment is adequate depth (6-12 inches).	/	Г	
Surfacing material is free of glass, debris, or other foreign objects.	г		weeds Inceds mousing
Surfacing material is not compacting or deteriorating.	г		material missing Incel new sorta
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	-	NA
Proper drainage prevents water from forming puddles.	~	i_	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-	Г	
Equipment is free from sharp points, corners, or edges.	/	F	
Protective caps or plugs are not missing or damaged.	r-	i_	nla
Equipment is free of potential clothing entanglement hazards.		r	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	F/	Just I need to be resurfaced
Equipment is free of entrapments.		Г	
Equipment is safely anchored.	5/	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	-	Г	
Swings are a safe distance from other playground equipment.		Г	i i
Swings are 24 inches apart.		Г	
Edges of seats are smooth and free from obstructions.	/	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	/	٢	

Slides	Pass		
Slides are free of obstructions and protrusions.	L 5722.	Fail	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	<u> </u>	r w/A	-
Platforms are equipped with guardrails or equivalent protective equipment.	1.	r 1/A	· · · · · · · · · · · · · · · · · · ·
Average incline is less than 30 degrees.	f"	- N/A	
Exit regions are level.	ĵ	1/1	
Metal slides are shaded to prevent overheating.	- r	5 114	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			Fromein/Solution
Rope or chain ladders are anchored at both ends.	1		
Foot holds/rungs are in good condition and adequately spaced.	1	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	r n/a	Problem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ī ·	- 1/A	·
Fulcrums/pivot points are free of pinch or crush hazards.	r	- 1/h	
Handholds are provided at each seating position.	٦	E N/A	
Inspector name, signature, and completion date	·		
Name: Jose Villalar			
Signature: Jaller			Date: 4/15-/25
			_

George Adams / ML	Kir	51	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	F=	Г	2
Playground area įs free of anthills/hazardous insects or toxic plants.	F-/	۲	
Playground area is free of holes and other tripping hazards.	F	Г	•
Proper signage with rules, hours, and age- appropriate use is posted.	5/	Г	
Playground area is properly fenced.	Γ'	Г	NA
Self-latching gate works as designed.	Γ.	r	NA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	P/	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	/	Г	
Surfacing material is free of glass, debris, or other foreign objects.	/	г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	Г	
Proper drainage prevents water from forming puddles.	~	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-/	Г	
Equipment is free from sharp points, corners, or edges.	٢	-	Sharp adgrs / Lephon handles
Protective caps or plugs are not missing or damaged.	12	Г	The state of the s
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	-	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	Г	rest / Leplace
Equipment is free of entrapments.		Γ	, , , , , , , , , , , , , , , , , , , ,
Equipment is safely anchored.	F	۲	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	-	Г	
Swings are a safe distance from other playground equipment.		۲	
Swings are 24 inches apart.	1	F	
Edges of seats are smooth and free from obstructions.	P/	r	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		٢	

Slides	Pass	Fail	- 10
Slides are free of obstructions and protrusions.	- 3.5	Г an	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	/	r	
Platforms are equipped with guardrails or equivalent protective equipment.	j /	r	
Average incline is less than 30 degrees.	Γ	E N/A	
Exit regions are level.	/		
Metal slides are shaded to prevent overheating.	r	MA	
Climbing Equipment	Pass	Fail	Problem #5-122
Hand grips are secured and do not rotate.	-		Problem / Solution
Rope or chain ladders are anchored at both ends.		r	
Foot holds/rungs are in good condition and adequately spaced.	4	r.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	*		Paint (Vacking Preservashed and Repainted
Fulcrums/pivot points are free of pinch or crush hazards.	,-/	<i>r</i> -	
Handholds are provided at each seating position.		ſ	
Inspector name, signature, and completion date			
Name: Jose Villa/an			
Signature: Land Will			Date: 41/15 /25
			

(To be completed monthly.)

Wilson field

wilson fixed		100 00 00	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	=	Γ.	2
Playground area is free of anthills/hazardous insects or toxic plants.	-	r y	
Playground area is free of holes and other tripping hazards.	Г	F-/	Hole in floor / repair floor
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	L	Г	NA
Self-latching gate works as designed.	Γ.	Γ	NIA
Surfacing 1990	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Г		Hote in guperfloor/ repair floor
Surfacing material under and around equipment is adequate depth (6-12 inches).	*	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	+	г	
Surfacing material is not compacting or deteriorating.	-	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	p/	г	4
Proper drainage prevents water from forming puddles.	/	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-	Γ	
Equipment is free from sharp points, corners, or edges.	Г	-	Shamp edges-rust/resurbae-replace
Protective caps or plugs are not missing or damaged.	=	Г	, , ,
Equipment is free of potential clothing entanglement hazards.		۲-	
Equipment free of pinch and crush points or exposed moving parts.		Γ	
Equipment is free of rust, rot, cracks, and splinters.	Г		10st /reserver - reperint - toplace
Equipment is free of entrapments.	-	Г	
Equipment is safely anchored.	+	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	/	г	i a
Swings are 24 inches apart.	/	Г	
Edges of seats are smooth and free from obstructions.		r	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	j/	Г	

Slides	Pass	Fail	
Slides are free of obstructions and protrusions.		, a	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.		·	F
Platforms are equipped with guardrails or equivalent protective equipment.			
Average incline is less than 30 degrees.	r-	Г /	1/4
Exit regions are level.	·/		
Metal slides are shaded to prevent overheating.	r	F //	1/4
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			1 topicint adiabou
Rope or chain ladders are anchored at both ends.	7	· <u>-</u>	
Foot holds/rungs are in good condition and adequately spaced.	Г	I A	et/end 100 t
Seesaws	Pass	Fail	Problem/Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	r	Γ	1/A
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Γ	<u>-</u> Л	/n
Fulcrums/pivot points are free of pinch or crush hazards.	Г	- //	<u> </u>
Handholds are provided at each seating position.	Г	I NI	4
Inspector name, signature, and completion date		//	·
Name: Jose VIllalan			Date: 4/15/25
Signature: Jos Vallantes	_		Date: 4/15/25

(To be completed monthly.)

Tilly Park / By Ashley Rield

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	F/	Γ.	,
Playground area įs free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	/	Г	
Playground area is properly fenced.	г	Г	n/A
Self-latching gate works as designed.	Γ.	۲	NA
Surfacing Surfac	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		Г	n H
Proper drainage prevents water from forming puddles.	-	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-	Γ	
Equipment is free from sharp points, corners, or edges.	Г	~	Short edges-10st/resurface - It has
	F	Г	Sharf edges-Just/vesurface - lefter
or edges.			Sharp edges-10st/resurban -17/hac
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing	190	Г	Sharp edges-Just / Nesurlan - 1 of how
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed	190	Г	
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts.		Г Г	Sharf edges-Just/resurface - 1 of here
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters.			
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments.			
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored.			Nust / Resurface - Yepkine
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. Swings	Pass	r r r	Nust / Resurface - Yepkace
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. Swings Hardware and chains are in good condition. Swings are a safe distance from other playground	Pass	Fail F	Nust / Resurface - Yepkace
or edges. Protective caps or plugs are not missing or damaged. Equipment is free of potential clothing entanglement hazards. Equipment free of pinch and crush points or exposed moving parts. Equipment is free of rust, rot, cracks, and splinters. Equipment is free of entrapments. Equipment is safely anchored. Swings Hardware and chains are in good condition. Swings are a safe distance from other playground equipment.	Pass	Fail F	Nust / Resurface - Yepkure

; i'o be completed monthly.)

Slides	Pass	Fail	Problem / Salar
Slides are free of obstructions and protrusions.	1	r	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	1	L.	
Platforms are equipped with guardrails or equivalent protective equipment.	1	(T	
Average incline is less than 30 degrees.	Γ-	T 1/1	
Exit regions are level.	· ·		
Metal slides are shaded to prevent overheating.	r-	- ala.	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		F	Froblem/Solution
Rope or chain ladders are anchored at both ends.		r	
Foot holds/rungs are in good condition and adequately spaced.	Γ-	Vilber	i's coached / replace
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		- 114	1 roblem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г		
Fulcrums/pivot points are free of pinch or crush hazards.	Г	5 n/A	
Handholds are provided at each seating position.	Ċ	cnla	
Inspector name, signature, and completion date			
Name: Jose Villalen			
Signature Juille			Date: 4/15/25

Tilly look / By Store			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		r.	3
Playground area is free of anthills/hazardous insects or toxic plants.	7	Г	
Playground area is free of holes and other tripping hazards.	/	г	
Proper signage with rules, hours, and age- appropriate use is posted.	5 /	г	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	Γ-	г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).			
Surfacing material is free of glass, debris, or other foreign objects.	r	-	words freeds werd killer
Surfacing material is not compacting or deteriorating.	-	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	~	F	
Proper drainage prevents water from forming puddles.	-	;-	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	14		Lacosti Konna e with and theme
Equipment is free from sharp points, corners, or edges.	Γ,		Vist/restance repaint
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	4	Г	
Equipment free of pinch and crush points or exposed moving parts.	F-	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	~	rust / resurface - replace
Equipment is free of entrapments.		Г	/
Equipment is safely anchored.	F	Г	
Swings Office States	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	1	Г	· ·
Swings are 24 inches apart.	5	٢	
Edges of seats are smooth and free from obstructions.	1	Γ-	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	٢	

fito be completed monthly)

Slides	Páss	Fail:	District 120 Page 150
Slides are free of obstructions and protrusions.	7	F .	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	/	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	1	Γ	
Average incline is less than 30 degrees.	ſ-	r n/A	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.		- 114	
Climbing Equipment	Pass	'Fail'	Problem #Solution
Hand grips are secured and do not rotate.	,,	X 100 100 100 100 100 100 100 100 100 10	Lopieu Poinnoù
Rope or chain ladders are anchored at both ends.			
Foot holds/rungs are in good condition and adequately spaced.	<i>5</i> ′	<u> </u>	
Seesaws	Pass	Fail	Dasking
Seesaws are free of cracks, corrosion, and other obvious structural defects.	L.	T 1/4	Problem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Γ	- 11/11	
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	- NA	
Handholds are provided at each seating position.	r	" N/A	
Inspector name, signature, and completion date	······································		;
Name: Jose Villalan			
Signature: Jon Visit on			Date: 4/15 /25
	. —		

(To be completed monthly.)

Bayfront

Daytont			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Г	3
Playground area is free of anthills/hazardous insects or toxic plants.	-	Г	
Playground area is free of holes and other tripping hazards.	₽	Г	· ·
Proper signage with rules, hours, and age- appropriate use is posted.	F	Г	
Playground area is properly fenced.	Г	Г	n/A
Self-latching gate works as designed.	r.	Γ	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	~	Г	
Surfacing material is free of glass, debris, or other foreign objects.	/	г	
Surfacing material is not compacting or deteriorating.	/	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.			
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	P	Г	
Equipment is free from sharp points, corners, or edges.	~	г	
Protective caps or plugs are not missing or damaged.	+	L	
Equipment is free of potential clothing entanglement hazards.		٢	
Equipment free of pinch and crush points or exposed moving parts.	/	г	
Equipment is free of rust, rot, cracks, and splinters.		Г	
Equipment is free of entrapments.	19/	Г	
Equipment is safely anchored.	F	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	1/4
Swings are a safe distance from other playground equipment.	F	۲	nlA
Swings are 24 inches apart.	ī	Г	nla
Edges of seats are smooth and free from obstructions.	Г	I	n/4
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	r	Г	n/A

Slides	Pass	Fai!	Problem (C.)
Slides are free of obstructions and protrusions.	-	r an	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	1	Γ	
Platforms are equipped with guardrails or equivalent protective equipment.	»	Γ	
Average incline is less than 30 degrees.	r-	- u /A	
Exit regions are level.		7	
Metal slides are shaded to prevent overheating.	ſ-	F 11A	
Climbing Equipment	Pass	Fail	Brokley /S L /
Hand grips are secured and do not rotate.	Jis/	F*	Problem / Solution
Rope or chain ladders are anchored at both ends.			
Foot holds/rungs are in good condition and adequately spaced.	/	f	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<u> </u>	r 1/4	Problem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		r n/A	
Fulcrums/pivot points are free of pinch or crush hazards.	r	- n/p	
Handholds are provided at each seating position.	٢	5 m/m	
Inspector name, signature, and completion date	·		
Name: Jore Villalan Signature: Julille			Date: 4/15/25
	-		•

Splanh pad Bastront	er order a service		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	f*	Г	3
Playground area is free of anthills/hazardous insects or toxic plants.	-	г	
Playground area is free of holes and other tripping hazards.		r	
Proper signage with rules, hours, and age- appropriate use is posted.	#	Γ	
Playground area is properly fenced.	г	Г	nla
Self-latching gate works as designed.	r	Г	NIA
Surfacing to the same of the s	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		r	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	г	N/A
Proper drainage prevents water from forming puddles.		г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-	Г	
Equipment is free from sharp points, corners, or edges.	V	Г	
Protective caps or plugs are not missing or damaged.	~	Г	
Equipment is free of potential clothing entanglement hazards.	-	Γ	
Equipment free of pinch and crush points or exposed moving parts.	-	Г	N/A
Equipment is free of rust, rot, cracks, and splinters.	13	Г	
Equipment is free of entrapments.		Г	
Equipment is safely anchored.	1	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	nla
Swings are a safe distance from other playground equipment.	. г	Г	nla
Swings are 24 inches apart.	-	Г	nla
Edges of seats are smooth and free from obstructions.	г	r	nlA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	J	Г	NIA

Slides	Pass	Fail	
Slides are free of obstructions and protrusions.		[10 / A	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	r-	· 11/14	
Platforms are equipped with guardrails or equivalent protective equipment.	j.	- n/A	
Average incline is less than 30 degrees.	Ī-		
Exit regions are level.	î"	10/11	
Metal slides are shaded to prevent overheating.	r	T WA	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	٢	5 m/A	1 Tobletti #Solution
Rope or chain ladders are anchored at both ends.	г		
Foot holds/rungs are in good condition and adequately spaced.	r	" n/A	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	5 n/A	Trobletti/ Soldtion
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	5 11/4	
Fulcrums/pivot points are free of pinch or crush hazards.	г	5 n/A	
Handholds are provided at each seating position.	r	TULA	
Inspector name, signature, and completion date		——————————————————————————————————————	
Name: Jose Villalan			
Signature: Jan Villa			Date: 4/15/23
			<u>.</u>

Claret CROSSing			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	-	IT.	3
Playground area is free of anthills/hazardous insects or toxic plants.	FF	Г	
Playground area is free of holes and other tripping hazards.	1	Г	·
Proper signage with rules, hours, and age- appropriate use is posted.	-	г	
Playground area is properly fenced.	Γ	Г	N/A
Self-latching gate works as designed.	Γ,	Г	NA
Surfacing Walter Control of the Cont	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	F/	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	5/	r-	
Surfacing material is not compacting or deteriorating.	2	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	4	Г	e e
Proper drainage prevents water from forming puddles.	1	ı	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	2	Г	
Equipment is free from sharp points, corners, or edges.	1	. Г	
Protective caps or plugs are not missing or damaged.	#	г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	0	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	0	Г	
Swings are a safe distance from other playground equipment.	1	г	i a
Swings are 24 inches apart.	4	Г	
Edges of seats are smooth and free from obstructions.	K	l	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	r	

(I's be completed monthly)

Slides	Pass	Fail	Buckey
Slides are free of obstructions and protrusions.	4	<u> </u>	Problem / Soluțion
Equipped with platforms to facilitate access to the sitting position.	P	۲	· · · · · · · · · · · · · · · · · · ·
Platforms are equipped with guardrails or equivalent protective equipment.	<i>کن</i>	Г	
Average incline is less than 30 degrees.	ſ-	- N/A	
Exit regions are level.	7		
Metal slides are shaded to prevent overheating.	Г	- 1/1	
Climbing Equipment	Pass ,	Fail	
Hand grips are secured and do not rotate.			Problem / Solution
Rope or chain ladders are anchored at both ends.			
Foot holds/rungs are in good condition and adequately spaced.		· ·	
Seesaws	Pass.	Eail	70.
Seesaws are free of cracks, corrosion, and other obvious structural defects.		i i	Problem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground	-	r	
Fulcrums/pivot points are free of pinch or crush hazards.		۴	
Handholds are provided at each seating position.	9	i ·	
Inspector name, signature, and completion date			
Name: Jose Utlanam		14	
Signature: In VIII			Date: 4/15/25
			•

(To be completed monthly.)

Butterfly Park

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Γ.	3
Playground area is free of anthills/hazardous insects or toxic plants.	~	r	
Playground area is free of holes and other tripping hazards.	F/	г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Γ"	Г	n/A
Self-latching gate works as designed.	Γ-	Γ	NA
Surfacing to the state of the s	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	12/	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		-	
Surfacing material is free of glass, debris, or other foreign objects.	(V	weeds pred great killer
Surfacing material is not compacting or deteriorating.	1		deteriorating floor / replace floor
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	n/A
Proper drainage prevents water from forming puddles.	Part -	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	File	Γ	
Equipment is free from sharp points, corners, or edges.	Г	-	Just / replace play ground
Protective caps or plugs are not missing or damaged.	1=	Γ	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	L-	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г		rigt, cracks / replie phygrand
Equipment is free of entrapments.	-	Г	
Equipment is safely anchored.	-	Γ	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	ン	Г	i g
Swings are 24 inches apart.	-	Г	
Edges of seats are smooth and free from obstructions.		r	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	-	г	

Slides	Pass	Fail	Purchass / Color
Slides are free of obstructions and protrusions.	7		Problem / Solution
Equipped with platforms to facilitate access to the sitting position.		г	
Platforms are equipped with guardrails or equivalent protective equipment.	1	r-	
Average incline is less than 30 degrees.	r	5 m /4	
Exit regions are level.	/	- <i>N/N</i> -	
Metal slides are shaded to prevent overheating.		- n/A	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	5/	F	Problem / Solution
Rope or chain ladders are anchored at both ends.			
Foot holds/rungs are in good condition and adequately spaced.	المحرا	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	5 0/0	Troplem / Sojution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	r		
Fulcrums/pivot points are free of pinch or crush hazards.	F	- n/1A	
Handholds are provided at each seating position.	۲	5 n/s	,
Inspector name, signature, and completion date			
Name: Jose Villapon			
Signature: La Villa			Date: 4/15/25
		,	

Light House Beach Behind P.	001		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	2	Γ.	2
Playground area is free of anthills/hazardous insects or toxic plants.	5	Г	
Playground area is free of holes and other tripping hazards.	4	г	
Proper signage with rules, hours, and age- appropriate use is posted.	F/	г	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	Γ.	Г	nIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	-	г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	-	F	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	n/A
Proper drainage prevents water from forming puddles.	in	F	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	-	Г	
Protective caps or plugs are not missing or damaged.	4	1-	
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	-	[
Equipment is free of rust, rot, cracks, and splinters.	Г		Vost / resusface and paint
Equipment is free of entrapments.	P	Г	, , , , , ,
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	г	Г	NA
Swings are a safe distance from other playground equipment.	· r	г	n/a
Swings are 24 inches apart.	Г	Г	NA
Edges of seats are smooth and free from obstructions.	г	ſ	1/4
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	F	NA

Slides	, Pass	Fail	3 a Es a 4	District the second sec
Slides are free of obstructions and protrusions.	- F	F	E ti	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.		<u>'</u> -		· · · · · · · · · · · · · · · · · · ·
Platforms are equipped with guardrails or equivalent protective equipment.	~	r	<u> </u>	
Average incline is less than 30 degrees.	Г	F	NIA	
Exit regions are level.	-	<u> </u>		
Metal slides are shaded to prevent overheating.	ŗ		114	
Climbing Equipment	Pass	Fail		District the second
Hand grips are secured and do not rotate.		- F	on al	Problem #Solution
Rope or chain ladders are anchored at both ends.				
Foot holds/rungs are in good condition and adequately spaced.		L.		
Seesaws	Pass	Fail	и <u>и</u>	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	F .	1/2	LLopiem / Zointion
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		r	n/A	
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	Г	u/A	
Handholds are provided at each seating position.	<u> </u>		NA	
Inspector name, signature, and completion date				
Name: Jose Villalon				
Signature: Jalla				Date: 4/15/25
				•

Splash Pad Light house Bear	ch		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	-	17	
Playground area įs free of anthills/hazardous insects or toxic plants.	P	г	
Playground area is free of holes and other tripping hazards.	-	Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Γ.	Г	n/A
Self-latching gate works as designed.	IT.	Г	nIA
Surfacing to the second	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.	-	г	
Surfacing material is not compacting or deteriorating.	10	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		F	NIA
Proper drainage prevents water from forming puddles.	Fire	F	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.		. г	
Protective caps or plugs are not missing or damaged.	17	Г	
Equipment is free of potential clothing entanglement hazards.	-	Г	
Equipment free of pinch and crush points or exposed moving parts.	F-/	г	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	surface must / resurface and paint
Equipment is free of entrapments.	-	Г	
Equipment is safely anchored.	10	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	٢	Г	NA
Swings are a safe distance from other playground equipment.		F-	n/A
Swings are 24 inches apart.	F	Г	NA
Edges of seats are smooth and free from obstructions.	Г	r-	NA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	5	۲	NA

Slides	Pass.	Fail	***	and the second s
Slides are free of obstructions and protrusions.	, 435 F	r (en	1/4	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	F	r	N/A N/A	
Platforms are equipped with guardrails or equivalent protective equipment.	1.	<i>_</i>	n/A	
Average incline is less than 30 degrees.	r	ī	n/n	
Exit regions are level.	i"	7~	1/1	
Metal slides are shaded to prevent overheating.	٢		11/1	
Climbing Equipment	Pāss	Fajl '	V 17 17	Parkley Bred 24
Hand grips are secured and do not rotate.		Г	E B A A A	Problem://Solution:
Rope or chain ladders are anchored at both ends.			·	
Foot holds/rungs are in good condition and adequately spaced.		l		
Seesaws	Pass	Fail	'N	Problem / Solution.
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Γ	1/1	Propiem / Zoingou"
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	۲	14	
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	Г	n/ 14 / 14	
Handholds are provided at each seating position.	r	f"	n 1.A	
Inspector name, signature, and completion date				
Name: Some Villalan				
Signature Jan Villa				Date: 4/15/25

Light house back / By Sile	THE RESERVE AND ADDRESS OF	Deid	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	-	Γ.	
Playground area is free of anthills/hazardous insects or toxic plants.	-	Г	
Playground area is free of holes and other tripping hazards.	F	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	F-	Г	
Playground area is properly fenced.	F	Г	
Self-latching gate works as designed.	-	Г	
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	~		
Surfacing material is free of glass, debris, or other foreign objects.	=	r	
Surfacing material is not compacting or deteriorating.	г	1	Hole in rubber / hepair Rubber
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		1	, , , , , , , , , , , , , , , , , , ,
Proper drainage prevents water from forming puddles.	P	ï	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-	Г	
Equipment is free from sharp points, corners, or edges.	L.	/	sharp edges / Providence
Protective caps or plugs are not missing or damaged.		Г	The second secon
Equipment is free of potential clothing entanglement hazards.	V	Г	
Equipment free of pinch and crush points or exposed moving parts.	-	г	
Equipment is free of rust, rot, cracks, and splinters.	Г		rost / resurface and paint
Equipment is free of entrapments.	/	Г	The period and frage
Equipment is safely anchored.	je/	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	٣	Г	n la
Swings are a safe distance from other playground equipment.	· r-	Г	n/A
Swings are 24 inches apart.	Г	Г	n/A
Edges of seats are smooth and free from obstructions.	г	l	n/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	L-	F**	n/4

Slides	Pass	Fail	
Slides are free of obstructions and protrusions.	5/	F 401	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	<i>v</i>	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	/	Г	
Average incline is less than 30 degrees.	Ĩ.	r u/A	
Exit regions are level.	+	r	
Metal slides are shaded to prevent overheating.	Γ	- n/n	· · · · · · · · · · · · · · · · · · ·
Climbing Equipment	Pass	Fail •	Problem / Solution
Hand grips are secured and do not rotate.	- Farm	-	TAODIGILI I Solution
Rope or chain ladders are anchored at both ends.		F	
Foot holds/rungs are in good condition and adequately spaced.		Γ.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	- 1/A	1 Toblem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г	- 11/17-	
Fulcrums/pivot points are free of pinch or crush hazards.		5 W/A	
Handholds are provided at each seating position.	ſ	5 MA	
Inspector name, signature, and completion date			
Name: Jose Villalon			
Signature: La Villa			Date: 4/15/25
			-

Light house beach 1 At Bail	1		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	-	Г	2
Playground area is free of anthills/hazardous insects or toxic plants.	#	г	
Playground area is free of holes and other tripping hazards.	-	г	
Proper signage with rules, hours, and age- appropriate use is posted.	p.	Г	
Playground area is properly fenced.	E	Г	NH
Self-latching gate works as designed.	Γ	Г	nIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	+	Г	
Surfacing material is free of glass, debris, or other foreign objects.	r	p=/	words por de wood filler
Surfacing material is not compacting or deteriorating.		Γ	,
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Γ	N/A
Proper drainage prevents water from forming puddles.	7	F	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-	Г	
Equipment is free from sharp points, corners, or edges.	Г	2	shown whis / resertace and don't
Protective caps or plugs are not missing or damaged.	Li	r	
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	F-/	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г		rust/resurrans or heplace
Equipment is free of entrapments.	-	Г	
Equipment is safely anchored.	Tipo -	Г	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Γ	n/A
Swings are a safe distance from other playground equipment.		Γ	n/A
Swings are 24 inches apart.	Г	Г	nlA
Edges of seats are smooth and free from obstructions.	Г	r	nlA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	1	nla



Slides	Pass	Fail	Problem (C.L.)
Slides are free of obstructions and protrusions.	,	["	'Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	/	r	·
Platforms are equipped with guardrails or equivalent protective equipment.	/	r	
Average incline is less than 30 degrees.	٦	i n/n	
Exit regions are level.	17		
Metal slides are shaded to prevent overheating.		- 1/2	
Climbing Equipment	Páss	Fail	Problem / C. L. &
Hand grips are secured and do not rotate.	7	, <u> </u>	Problem / Solution
Rope or chain ladders are anchored at both ends.			
Foot holds/rungs are in good condition and adequately spaced.	-	ŗ.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	- 1/4	1 roblem / Soldalon
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	ī	- n/a	
Fulcrums/pivot points are free of pinch or crush hazards.		5 n/n	
Handholds are provided at each seating position.	۲	1 1/4	
Inspector name, signature, and completion date	·		
Name: Jose Villalar Signature: Julian			Date: 4/15/25