

Playground Safety Checklist

Inspection ID

Name of Park Lighthouse Beach Park Playground 3 (beach area)

Inspection Date 09-17-2025 09:15 AM

General Inspection

	In Good Condition	Needs Improvement	Notes
Playground are is free of litter and debris	X	-	-
Playground area is free of anthills/hazardous insects or toxic plants.	X	-	-
Playground area is free of holes and other tripping hazards.	Х	-	-
Proper signage with rules, hours, and age-appropriate use is posted.	Х	-	-
Playground area is properly fenced	-	-	N/A
Self latching gate works as designed	-	-	N/A

Surfacing

	In Good Condition	Needs Improvement	Notes
Approved surfacing material is used (i.e. solid rubber, artificial graass or turf, play sand, pea gravel, wood chips, rubber mulch)	X	-	-
Surfacing material under and around equipment is adequate depth (6-12 inches)	X	-	-
Surfacing material is free of glass, debris, or other foreign objects.	-	X	Weeds/ needs weedeating
Surfacing material is not compacting or deteriorating.	X	-	-
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-	-	N/A
Proper drainage prevents water from forming puddles.	X	-	-

Equipment Hazards

	In Good Condition	Needs Improvement	Notes
Equipment is not damaged or vandalized.	X	-	-
Equipment is free from sharp points, corners, or edges.	-	X	Sharp edges/ resurface, repaint
Protective caps or plugs are not missing or damaged.	X	-	-
Equipment is free of potential clothing entanglement hazards.	X	-	-
Equipment is free of pinch and crush points or exposed moving parts.	X	-	-
Equipment is free of rust, rot, cracks, and splinters.	-	X	Rust, rot/ resurface, repaint
Equipment is free of entrapments.	X	-	-
Equipment is safely anchored.	X	-	-

Swings

	In Good Condition	Needs Improvement	Notes
Hardware and chains are in good condition.	-	-	N/A
Swings are a safe distance from other playground equipment.	-	-	N/A
Swings are 24 inches apart.	-	-	N/A
Edges of seats are smooth and free from obstructions.	-	-	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	-	-	N/A

Slides

	In Good Condition	Needs Improvement	Notes
Slides are free of obstructions and protrusions.	X	-	-
Equipped with platforms to facilitate access to the sitting position.	Х	-	-
Platforms are equipped with guardrails or equivilent protective equipment.	X	-	-

Climbing Equipr	ment					
		In Good Condition	Needs Improven		otes	
	Hand grips are secured and do not rotate.	X	-		-	
	Rope or chain ladders are anchored at both ends.	X	-		-	
	Foot holds/ rungs are in good condition and adequately spaced.	X	-		-	
				In Good Condition	Needs Improvement	Notes
Seesaws are free of cr	acks, corrosion, and other obvious structural defects.					Notes N/A
	acks, corrosion, and other obvious structural defects.	upt contact with t	the ground.	Condition		
Equipment is provided	· · · · · ·	upt contact with t	the ground.	Condition -		N/A
Equipment is provided Fulcrums/ pivot points	with spring centering devices or cushioning material to prevent abru	upt contact with t	the ground.	Condition - -	Improvement	N/A N/A
Equipment is provided Fulcrums/ pivot points	with spring centering devices or cushioning material to prevent abruare free of pinch or crush hazards.	upt contact with t	the ground.	Condition	Improvement	N/A N/A N/A
Equipment is provided Fulcrums/ pivot points Handholds are provided	with spring centering devices or cushioning material to prevent abruare free of pinch or crush hazards. In dat each sitting position.	upt contact with t	the ground.	Condition	Improvement	N/A N/A N/A