

Playground Safety Checklist

Inspection ID 0052

Name of Park George Adams JKF Jr. Dr. Inspection Date 09-17-2025 02:18 PM

General Inspection

	In Good Condition	Needs Improvement	Notes
Playground are is free of litter and debris	X	-	-
Playground area is free of anthills/hazardous insects or toxic plants.	X	-	-
Playground area is free of holes and other tripping hazards.	X	-	-
Proper signage with rules, hours, and age-appropriate use is posted.	X	-	-
Playground area is properly fenced	-	-	N/A
Self latching gate works as designed	-	-	N/A

Surfacing

	In Good Condition	Needs Improvement	Notes
Approved surfacing material is used (i.e. solid rubber, artificial graass or turf, play sand, pea gravel, wood chips, rubber mulch)	X	-	-
Surfacing material under and around equipment is adequate depth (6-12 inches)	X	-	-
Surfacing material is free of glass, debris, or other foreign objects.	X	-	-
Surfacing material is not compacting or deteriorating.	X	-	-
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	X	-	-
Proper drainage prevents water from forming puddles.	X	-	-

Equipment Hazards

	In Good Condition	Needs Improvement	Notes
Equipment is not damaged or vandalized.	X	-	-
Equipment is free from sharp points, corners, or edges.	-	X	Sharp edges/ resurface, replace
Protective caps or plugs are not missing or damaged.	X	-	-
Equipment is free of potential clothing entanglement hazards.	X	-	-
Equipment is free of pinch and crush points or exposed moving parts.	X	-	-
Equipment is free of rust, rot, cracks, and splinters.	-	X	Rust,rot/ replace
Equipment is free of entrapments.	X	-	-
Equipment is safely anchored.	X	-	-

Swings

	In Good Condition	Needs Improvement	Notes
Hardware and chains are in good condition.	X	-	-
Swings are a safe distance from other playground equipment.	X	-	-
Swings are 24 inches apart.	X	-	-
Edges of seats are smooth and free from obstructions.	X	-	-
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	X	-	-

Slides

	In Good Condition	Needs Improvement	Notes
Slides are free of obstructions and protrusions.	-	X	Hole in slide/ replace slide
Equipped with platforms to facilitate access to the sitting position.	X	-	-

Platforms are equipped with guardrails or equivilent protective equipment.	X	-	-	
Exit regions are level.	X	-	-	

Climbing Equipment

	In Good Condition	Needs Improvement	Notes
Hand grips are secured and do not rotate.	X	-	-
Rope or chain ladders are anchored at both ends.	X	-	-
Foot holds/ rungs are in good condition and adequately spaced.	X	-	-

Seesaws

	In Good Condition	Needs Improvement	Notes
Seesaws are free of cracks, corrosion, and other obvious structural defects.	-	×	Bad paint/ repaint
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	X	-	-
Fulcrums/ pivot points are free of pinch or crush hazards.	X	-	-
Handholds are provided at each sitting position.	X	-	-

Inspector Name Jose Villalon
Signature

You can $\underline{\text{edit this submission}}$ and $\underline{\text{view all your submissions}}$ easily.