

From: [Jotform](#)
To: [Joe Villalon](#); [Lorena Perez-Diaz](#); [Wayne Shaffer](#); [Edward Tyler](#)
Subject: Re: Playground Safety Checklist - Joe Villalon
Date: Tuesday, August 18, 2026 12:29:36 PM



Playground Safety Checklist

Inspection ID 0192

Name of Park George Adams JKF Jr. Dr.

Inspection Date 08-18-2026 09:25 AM

General Inspection		In Good Condition	Needs Improvement	Notes
	Playground are is free of litter and debris	☐		
	Playground area is free of anthills/hazardous insects or toxic plants.	☐		
	Playground area is free of holes and other tripping hazards.	☐		
	Proper signage with rules, hours, and age-appropriate use is posted.	☐		
	Playground area is properly fenced			N/A
	Self latching gate works as designed			N/A

	In Good Condition	Needs Improvement	Notes

Surfacing	Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch)	☐		
	Surfacing material under and around equipment is adequate depth (6-12 inches)	☐		
	Surfacing material is free of glass, debris, or other foreign objects.		☐	Weeds
	Surfacing material is not compacting or deteriorating.	☐		
	Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	☐		
	Proper drainage prevents water from forming puddles.	☐		
		In Good Condition	Needs Improvement	Notes

Equipment Hazards	Equipment is not damaged or vandalized.	☐		
	Equipment is free from sharp points, corners, or edges.		☐	Sharp edges
	Protective caps or plugs are not missing or damaged.	☐		
	Equipment is free of potential clothing entanglement hazards.	☐		
	Equipment is free of pinch and crush points or exposed moving parts.	☐		
	Equipment is free of rust, rot, cracks, and splinters.		☐	Rust,rot
	Equipment is free of entrapments.	☐		
	Equipment is safely anchored.	☐		

	In Good Condition	Needs Improvement	Notes
Hardware and chains are in good condition.	☐		
Swings are a safe distance from other playground	☐		

Swings	equipment.			
	Swings are 24 inches apart.	☐		
	Edges of seats are smooth and free from obstructions.	☐		
	Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	☐		
Slides		In Good Condition	Needs Improvement	Notes
	Slides are free of obstructions and protrusions.		☐	Holes on slide
	Equipped with platforms to facilitate access to the sitting position.	☐		
	Platforms are equipped with guardrails or equivalent protective equipment.	☐		
	Exit regions are level.	☐		
		In Good Condition	Needs Improvement	Notes
	Hand grips			

Climbing Equipment	are secured and do not rotate.	☐		
	Rope or chain ladders are anchored at both ends.		☐	Broken anchor
	Foot holds/ rungs are in good condition and adequately spaced.	☐		
Seesaws		In Good Condition	Needs Improvement	Notes
	Seesaws are free of cracks, corrosion, and other obvious structural defects.		☐	Concrete base is moving needs to be repaired
	Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	☐		
	Fulcrums/ pivot points are free of pinch or crush hazards.	☐		
	Handholds			

are
provided
at each
sitting
position.



Inspector Name

Joe Villalon

You can [edit this submission](#) and [view all your submissions](#) easily.