George Adams Dark		*	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	100	1-	
Playground area is free of anthills/hazardous insects or toxic plants.	it/	\rangle \(\tau \)	
Playground area is free of holes and other tripping hazards.	10/	г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	~
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	۲	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	√	-	۰
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	√	
Surfacing material is free of glass, debris, or other foreign objects.		г	Mulch needs to be adorated
Surfacing material is not compacting or deteriorating.	-	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Γ	NYA
Proper drainage prevents water from forming puddles.	Г	г	NIA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	5	, Г	
Protective caps or plugs are not missing or damaged.		ļ.	
Equipment is free of potential clothing entanglement hazards.	ī	, г	
Equipment free of pinch and crush points or exposed moving parts.	r./	٢	
Equipment is free of rust, rot, cracks, and splinters.	г	×	Has rust
Equipment is free of entrapments.	IE/	/ 「	
Equipment is safely anchored.	~	Г	
S wings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	[~	, 「	
Swings are a safe distance from other playground equipment.	ī	, г	
Swings are 24 inches apart.	F/	. г	
Edges of seats are smooth and free from obstructions.	75	, F	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	it	r	

Grorge Adams Dark		
Slides	Pass Fail	Problem / Solution
Slides are free of obstructions and protrusions.	N _ F	
Equipped with platforms to facilitate access to the sitting position.	r/r	
Platforms are equipped with guardrails or equivalent protective equipment.	r r	
Average incline is less than 30 degrees.	- NIA	
Exit regions are level.	г⁄ г	
Metal slides are shaded to prevent overheating.	F F N/A	
Climbing Equipment	Pass Fail	Problem / Solution
Hand grips are secured and do not rotate.	N _ F	
Rope or chain ladders are anchored at both ends.	r/ r	
Foot holds/rungs are in good condition and adequately spaced.		*
Seesaws	Pass Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion,	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	Pass Fail	Problem / Solution Date: 10/14/24

Wilson Parls			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	rV	Γ	
Equipped with platforms to facilitate access to the sitting position.		Τ	
Platforms are equipped with guardrails or equivalent protective equipment.		Γ	
Average incline is less than 30 degrees.	r /	" N/A	
Exit regions are level.	1	г (
Metal slides are shaded to prevent overheating.	Г.	- NIA	Plustic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		Γ	
Rope or chain ladders are anchored at both ends.		Γ	
Foot holds/rungs are in good condition and adequately spaced.		Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r		Date:

		100	
WILSON PONC			B. H. JC L.C.
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	ID. A. S.	Γ	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age-appropriate use is posted.		٢	
Playground area is properly fenced.	Г	г	NIA
Self-latching gate works as designed.	г	г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	□ ✓	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	it	Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	ī	Г	,
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	r	NIA
Proper drainage prevents water from forming puddles.	F	ı	NIA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.		/ F	
Protective caps or plugs are not missing or damaged.		/ 「	
Equipment is free of potential clothing entanglement hazards.	·/		
Equipment free of pinch and crush points or exposed moving parts.	r.	Г	
Equipment is free of rust, rot, cracks, and splinters.	Γ	-/	
Equipment is free of entrapments.	Г	<u> Г</u>	Surface rust
Equipment is safely anchored.	ī√	г	JOI MEE 1951
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		, 「	
Swings are a safe distance from other playground equipment.		, г	
Swings are 24 inches apart.	√	, 「	
Edges of seats are smooth and free from obstructions.	7/	<u>,</u> г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	√	г	

City Park by Ashley +	1010	.1	
Slides	Pass		Problem / Solution
Slides are free of obstructions and protrusions.	1	Г	- Constant
Equipped with platforms to facilitate access to the sitting position.	-/	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	V	Г	
Average incline is less than 30 degrees.	N	Г	
Exit regions are level.	IN	, г	
Metal slides are shaded to prevent overheating.	17	Г	Plastic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	Г	
Rope or chain ladders are anchored at both ends.	1	Г	
Foot holds/rungs are in good condition and adequately spaced.	7	Г	
Seesaws	Pass	Fail	Problem / Solution
			Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Г	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.			N/A A//A
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Γ-	Г	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	r	Г	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	Г	

City Park by Ashle	1 t	ield	
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	1	T	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	~	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	iv	Г	
Playground area is properly fenced.	Г	Г	M/A
Self-latching gate works as designed.	г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-/	_	
Surfacing material under and around equipment is adequate depth (6-12 inches).	\ \rac{1}{\sqrt{1}}	Г	
Surfacing material is free of glass, debris, or other foreign objects.	12	г	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	10/	٢	
Proper drainage prevents water from forming puddles.	_	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	~	/ -	
Equipment is free from sharp points, corners, or edges.	rc	Γ	
Protective caps or plugs are not missing or damaged.	<u></u>	Г	N/À
Equipment is free of potential clothing entanglement hazards.	~	г	
Equipment free of pinch and crush points or exposed moving parts.	5	Г	
Equipment is free of rust, rot, cracks, and splinters.	г	100	Surface rust
Equipment is free of entrapments.	Г	Г	Surface
Equipment is safely anchored.	г	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	īt	/ [
Swings are a safe distance from other playground equipment.	·-/	/ _	**
Swings are 24 inches apart.	17	Г	
Edges of seats are smooth and free from obstructions.	17	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	V	г	

City Dark in front	0+5	<	200	
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	TV	Γ		
Equipped with platforms to facilitate access to the sitting position.	1	Г 		
Platforms are equipped with guardrails or equivalent protective equipment.		г 		
Average incline is less than 30 degrees.	iV			
Exit regions are level.	W			
Metal slides are shaded to prevent overheating.	5/	Г	Plastic	Slides
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.				
Rope or chain ladders are anchored at both ends.	<i></i>	г		
Foot holds/rungs are in good condition and adequately spaced.		Г		
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	N/A	Problem / Solution
Seesaws are free of cracks, corrosion,			N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	۲	N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	r	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г	r -	N/A N/A N/A	Problem / Solution

= City point in front	_0+	- 51	cire
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	ŗ-	
Playground area is free of anthills/hazardous insects or toxic plants.	15/	Г	
Playground area is free of holes and other tripping hazards.	nv/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	17	г	**.
Playground area is properly fenced.	Г	۲.	N/A
Self-latching gate works as designed.	Γ.	Γ	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	-/	, 	
Surfacing material under and around equipment is adequate depth (6-12 inches).	-/	Г	
Surfacing material is free of glass, debris, or other foreign objects.	rs/	r	
urfacing material is not compacting or deteriorating.	i.e.	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	√	, 	·
Proper drainage prevents water from forming puddles.	г	r	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	iV	, г	
Equipment is free from sharp points, corners, or edges.	~	Γ	
Protective caps or plugs are not missing or damaged.	r-	r-	NIA
Equipment is free of potential clothing entanglement hazards.	~	٢	
Equipment free of pinch and crush points or exposed moving parts.	N	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	г	Surface rust
Equipment is free of entrapments.	г	Γ	
Equipment is safely anchored.	г	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
Swings are a safe distance from other playground equipment.	17/	, r	
Swings are 24 inches apart.	~/	Γ	
Edges of seats are smooth and free from obstructions.	-/	, Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		Г	

Bayfront Solash Pag	1		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	r	·
Playground area is free of anthills/hazardous insects or toxic plants.	17	Г	
Playground area is free of holes and other tripping hazards.	~	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	5/	Г	~
Playground area is properly fenced.	Г		NIA
Self-latching gate works as designed.	r	г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	₹		Concrete Sorface
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	Г	Concrete Sorface
Surfacing material is free of glass, debris, or other foreign objects.	5	Г	
Surfacing material is not compacting or deteriorating.	ī	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	N/A
Proper drainage prevents water from forming puddles.	7	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	ī	Г	
Equipment is free from sharp points, corners, or edges.	1	Γ	
Protective caps or plugs are not missing or damaged.	rī/	, r	
Equipment is free of potential clothing entanglement hazards.	,/	۲	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	N	٢	
Equipment is free of entrapments.	TT/	/ F	
Equipment is safely anchored.	IT	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	۲	NIH
Swings are a safe distance from other playground equipment.	Г	Γ	NIA
Swings are 24 inches apart.	Γ	Г	NII À
Edges of seats are smooth and free from obstructions.	г	г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Г	NIA

Buttont Mayaroun	$c\lambda$ ϵ	-c	Belle	•		
Slides	Pass	Fail			/ Solution	
Slides are free of obstructions and protrusions.	=/	Γ				
Equipped with platforms to facilitate access to the sitting position.	1	Γ.			CONTRACTOR OF THE STATE OF THE	
Platforms are equipped with guardrails or equivalent protective equipment.		г				
Average incline is less than 30 degrees:	Г/	٢	N/A			
Exit regions are level.	1	Γ.				
Metal slides are shaded to prevent overheating:	-/	Γ	Plastic	Slides		
Climbing Equipment	Pass	Fail		Problem	/ Solution	
Hand grips are secured and do not rotate.		Γ				
Rope or chain ladders are anchored at both ends.	Г	Γ-	NIA			
Foot holds/rungs are in good condition and adequately spaced.		Г	,,,,			
Seesaws	Pass	Fail		Problem	/ Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Г	N/A			
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Γ	г	9			
Fulcrums/pivot points are free of pinch or crush hazards.	Г	г				
Fulcrums/pivot points are free of pinch	Г	Г				
Fulcrums/pivot points are free of pinch or crush hazards.						,

Bry Grant Day ground	(al	Belle
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	~	t-	
Playground area is free of anthills/hazardous insects or toxic plants.	17	Γ	
Playground area is free of holes and other tripping hazards.	75/	г	
Proper signage with rules, hours, and age- appropriate use is posted.	r\	Г	-
Playground area is properly fenced.	г	г	NIA
Self-latching gate works as designed.	r	Γ	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	~	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	NIA
Surfacing material is free of glass, debris, or other foreign objects.	r\	, r	
urfacing material is not compacting or deteriorating.	1	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		г	N/A
Proper drainage prevents water from forming puddles.	٦	г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		F	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	r	٢	N/A
Equipment is free of potential clothing entanglement hazards.	5	, r	
Equipment free of pinch and crush points or exposed moving parts.	r.	Γ	
Equipment is free of rust, rot, cracks, and splinters.	г		Sixtace rust
Equipment is free of entrapments.	Г	Г	
Equipment is safely anchored.	Г	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	NIA
Swings are a safe distance from other playground equipment.	г	Γ	NIA
Swings are 24 inches apart.	Г	Γ	NIA
Edges of seats are smooth and free from obstructions.	г	г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Γ	N/A

Clarete Crossing Park					
Slides	Pass	Fail		Problem / Solution	
Slides are free of obstructions and protrusions.	V	Γ			
Equipped with platforms to facilitate access to the sitting position.	;./	٢			
Platforms are equipped with guardrails or equivalent protective equipment.		ľ			
Average incline is less than 30 degrees.	r /	Γ			
Exit regions are level.	F	r			
Metal slides are shaded to prevent overheating.	·/	Γ-	Plastic	Slides	
Climbing Equipment	Pass	Fail		Problem / Solution	
Hand grips are secured and do not rotate.	TV	Г			
Rope or chain ladders are anchored at both ends.	Γ	-	NIA		
Foot holds/rungs are in good condition and adequately spaced.	N	Γ			
Seesaws	Pass	Fail		Problem / Solution	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	NIA	Problem / Solution	
Seesaws are free of cracks, corrosion,			NIA	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	7	1		Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	F	1		Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г	1		Problem / Solution	

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	1 an	Frontem / Solution
Playground area is free of anthills/hazardous insects or toxic plants.	1	 r	
Playground area is free of holes and other tripping hazards.	5/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	√	Г	-
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	r	Г	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	V	_	
Surfacing material under and around equipment is adequate depth (6-12 inches).		г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	-	Г	Concrete is chacking rubber is dam
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	г	N/A
Proper drainage prevents water from forming puddles.	_	r	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	ī	г	
Equipment is free from sharp points, corners, or edges.	7	Г	
Protective caps or plugs are not missing or damaged.	,V	r	
Equipment is free of potential clothing entanglement hazards.	.√	г	
quipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	it l		
Equipment is free of entrapments.	r.	Г	
Equipment is safely anchored.	r-/	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	-	
Swings are a safe distance from other playground equipment.	7	г	
Swings are 24 inches apart.	F	Г	
Edges of seats are smooth and free from obstructions.	,√	г	
dequate depths of surfacing material extend out a ninimum distance of twice the height of the swing.	1	г	

Buttelly Park Playaroun	d			
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	5	Γ		
Equipped with platforms to facilitate access to the sitting position.	√	۲		
Platforms are equipped with guardrails or equivalent protective equipment.	√	Г		
Average incline is less than 30 degrees.	TV/	Г		
Exit regions are level.	N	Г		
Metal slides are shaded to prevent overheating.	īV.	Г	@ Diasti	C Slides
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.		Г		
Rope or chain ladders are anchored at both ends.	Г	, г	N/A	
Foot holds/rungs are in good condition and adequately spaced.	r\	г	V	
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail -	N/A	Problem / Solution
Seesaws are free of cracks, corrosion,		Fail	N/A N//A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	F	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	F	N/A N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	F	N/A N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	F	N/A N/A N/A N/A	Problem / Solution Date: 10/14/24

Butter Elx powla Playe	arou	nd	
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.		i_	
Playground area is free of anthills/hazardous insects or toxic plants.	-/	Г	
Playground area is free of holes and other tripping hazards.	Г	1	rubber is domage
Proper signage with rules, hours, and age- appropriate use is posted.	nt/	Г	-
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	-	
Surfacing material under and around equipment is adequate depth (6-12 inches).	r		NIA
Surfacing material is free of glass, debris, or other foreign objects.		г	
Surfacing material is not compacting or deteriorating.	г	Г	Pour Condition in all piaces
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F	г	N/A
Proper drainage prevents water from forming puddles.	-	г	NIA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	FZ/	Г	
Protective caps or plugs are not missing or damaged.	Γ-	г	NA
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	~	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г,	T	rusting in all placess
Equipment is free of entrapments.	N	Г	is it will places
Equipment is safely anchored.	1	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	~	Г	
Swings are a safe distance from other playground equipment.	ī	г	- 1
Swings are 24 inches apart.	N	г	
Edges of seats are smooth and free from obstructions.	.√	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		г	

LIHIB Pavillion Pla	y ar	SULV	d		
Slides	Pass	Fail		Problem / Solution	12.0
Slides are free of obstructions and protrusions.		F			
Equipped with platforms to facilitate access to the sitting position.	N	Г			
Platforms are equipped with guardrails or equivalent protective equipment.		Г			
Average incline is less than 30 degrees.		Γ			
Exit regions are level.	10	ī			
Metal slides are shaded to prevent overheating.	٦	٢	NI	2	
Climbing Equipment	Pass	Fail	PROPERTY AND ADDRESS OF THE PARTY.	Problem / Solution	A TO
Hand grips are secured and do not rotate.	7	Г			
Rope or chain ladders are anchored at both ends.		Γ-			
Foot holds/rungs are in good condition and adequately spaced.		Γ			
			THE PARTY OF THE P		
Seesaws	Pass	Fail		Problem / Solution	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	N/A	Problem / Solution	
Seesaws are free of cracks, corrosion.			N/A N/A	Problem / Solution	-
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г		N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	r	г г	N/A N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r		N/A N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r		N/A N/A N/A	Problem / Solution Date: 10/14/24	

LIHIB Parties Pavillion	L DI	ally	iround
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	~	1-	
Playground area is free of anthills/hazardous insects or toxic plants.	it	Г	
Playground area is free of holes and other tripping hazards.	IV/	г	
Proper signage with rules, hours, and age-appropriate use is posted.	15/	Г	-
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г.	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	~		
Surfacing material under and around equipment is adequate depth (6-12 inches).	\ <u>\</u>	Г	
Surfacing material is free of glass, debris, or other foreign objects.	iv	r -	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Γ	NIA
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	iv/	Г	
Equipment is free from sharp points, corners, or edges.	~	Γ	
Protective caps or plugs are not missing or damaged.	Γ-	٣	NIA
Equipment is free of potential clothing entanglement hazards.		г	
Equipment free of pinch and crush points or exposed moving parts.	R./	Г	
Equipment is free of rust, rot, cracks, and splinters.	8	г	Small rust
Equipment is free of entrapments.	N	\ 	
Equipment is safely anchored.	N	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	г	۲	NIA
Swings are a safe distance from other playground equipment.	Г	Г	NIA
Swings are 24 inches apart.	г	Г	NIA
Edges of seats are smooth and free from obstructions.	г	г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	NIA

L, H, 13 50	lash fad				
Slide	es	Pass	Fail	Problem / Solution	
Slides are free of obstruc	tions and protrusions.	Γ	NIA		
Equipped with platform to the sittin		Γ	NIA		
Platforms are equipped with protective e		Γ	\[\mu/A\]		
Average incline is less	s than 30 degrees.	Γ	- NIL		
Exit regions	are level.	г	NIA		
Metal slides are shaded to	prevent overheating.	г	T N/A		
Climbing Ed	quipment	Pass	Fail	Problem / Solution	
Hand grips are secured	and do not rotate.	Γ-	- NIA		
Rope or chain ladders are	anchored at both ends.	Г	- NIA		
Foot holds/rungs are in adequately		Г	Г		
Seesa	ws	Pass	Fail	Problem / Solution	
Seesaws are free of c and other obvious st	racks, corrosion,	Pass	Fail	Problem / Solution	
Seesaws are free of c	racks, corrosion, tructural defects. spring centering devices prevent abrupt contact		Fail N/A N/A	Problem / Solution	
Seesaws are free of c and other obvious st Equipment is provided with or cushioning material to	racks, corrosion, tructural defects. spring centering devices prevent abrupt contact round. s are free of pinch	Г	Fail N/A N/A N/A	Problem / Solution	
Seesaws are free of c and other obvious st Equipment is provided with or cushioning material to with the g Fulcrums/pivot points	racks, corrosion, tructural defects. spring centering devices prevent abrupt contact round. s are free of pinch nazards.	Г	Fail N/A N/A N/A N/A	Problem / Solution	
Seesaws are free of c and other obvious st Equipment is provided with or cushioning material to with the g Fulcrums/pivot points or crush h	racks, corrosion, tructural defects. spring centering devices prevent abrupt contact round. s are free of pinch nazards. c each seating position.	r	Fail N/A N/A N/A N/A	Problem / Solution	
Seesaws are free of c and other obvious st Equipment is provided with or cushioning material to with the g Fulcrums/pivot points or crush h Handholds are provided at	racks, corrosion, tructural defects. spring centering devices prevent abrupt contact round. s are free of pinch nazards. c each seating position.	r	Fail N/A N/A N/A N/A	Problem / Solution Date: 10/14/24	

(To be completed monthly.

Litib Splasn Dad

LIHIB SPLASIN Dad	History of Styles		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	V	Γ	
Playground area is free of anthills/hazardous insects or toxic plants.	√	г	
Playground area is free of holes and other tripping hazards.	~	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	V	Г	
Playground area is properly fenced.	г	Г	N/A
Self-latching gate works as designed.	Е	П	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	Concrete pad
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	Г	Concrete pad
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	~/	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	, r	NIA
Proper drainage prevents water from forming puddles.		Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	V	Γ	
Equipment is free from sharp points, corners, or edges.	1	г	
Protective caps or plugs are not missing or damaged.	г	Г	NIA
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.		Г	
Equipment is free of entrapments.	5/	Γ	
Equipment is safely anchored.	~	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г.	Г	NIA
Swings are a safe distance from other playground equipment.	Г	Г	NIH
Swings are 24 inches apart.	Г	Γ	NIA
Edges of seats are smooth and free from obstructions.	г	Г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Γ	MA

LIHOIS Playaround Nex	+ 40	25	Plash	Dad
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	TV.	ŗ		
Equipped with platforms to facilitate access to the sitting position.		Г		
Platforms are equipped with guardrails or equivalent protective equipment.		۲.		
Average incline is less than 30 degrees.	Γ	Γ	NIA	
Exit regions are level.		۲		
Metal slides are shaded to prevent overheating.	1	Г	Plastic	- 51id +5
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.		Γ		
Rope or chain ladders are anchored at both ends.	Γ	Γ-	NIAI	
Foot holds/rungs are in good condition and adequately spaced.		Г		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	г	Γ	NIL	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	г 	NA	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			N/A N/A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г		N/A N/A N/A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г		N/A N/A N/A	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	Г		N/A N/A N/A	Date: 10/14/24

L.H.B Diak wround wext &	_A> <	5 Plas	sh pad
General Inspection	Pas	BOY STREET	
Playground area is free of litter and debris.	V	1-	·
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	Г	X	robber is dange
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	г	Г	NIA
Surfacing	Pass	s Fail	
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Г	5/	The rubber padding is damage, Trying to fix it
Surfacing material under and around equipment is adequate depth (6-12 inches).	V	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	15/	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	NIA
Proper drainage prevents water from forming puddles.	_	г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	~/	Г	
Protective caps or plugs are not missing or damaged.	L-	r	N/A
Equipment is free of potential clothing entanglement hazards.	~/	Г	70/18
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	г	P	rusting on some parts
Equipment is free of entrapments.	~	Г	30000
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	1/1/1
Swings are a safe distance from other playground equipment.	Г	Γ	NIA
Swings are 24 inches apart.	Г	Γ	NIA
Edges of seats are smooth and free from obstructions.	г	г	NA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	NIA

L, H, 13	Brach	Dlayaro,	ind				
	Slides		Pass	Fail		Problem / Solut	ion
Slides are free of o	bstructions and p	protrusions.	ne /	Г			
	latforms to facilita e sitting position		N	۲			
Platforms are equipper prote	ed with guardrail: ctive equipment		V	г			
Average incline	e is less than 30 d	egrees.	V	Г			
Exit r	egions are level.		n/	Г			
Metal slides are sh	aded to prevent o	verheating.	۲	Γ	Plastic	Slicies	
Climb	oing Equipment		Pass	Fail		Problem / Soluti	ion
Hand grips are s	secured and do no	ot rotate.	r		smissing	Handlesgri	OC
Rope or chain ladde	ers are anchored a	at both ends.	Г	/ 1	VIA	- Carista Squ	r3
	s are in good conc quately spaced.	lition and		Г			
	Seesaws		Pass	Fail		Problem / Soluti	on
Seesaws are fr and other obv	Seesaws ree of cracks, corr rious structural de	rosion, efects.	Pass	Fail	NA	Problem / Soluti	on .
Equipment is provide or cushioning mater	ree of cracks, corr vious structural de d with spring cen	efects. tering devices			N/A N/A	Problem / Soluti	ion
and other obvertigation in a cushioning mater with	ree of cracks, corr vious structural de d with spring cen rial to prevent ab	efects. tering devices prupt contact	Г	Г	N/A N/A	Problem / Soluti	on .
and other obvertigation in a cushioning mater with	ree of cracks, corr vious structural de d with spring cen rial to prevent ab n the ground. t points are free o crush hazards.	efects. tering devices orupt contact f pinch	Г	г	N/A N/A N/A	Problem / Soluti	on
and other obv Equipment is provide or cushioning mate with Fulcrums/pivot or c	ree of cracks, corr vious structural de d with spring cen rial to prevent ab n the ground. t points are free o crush hazards. ided at each seati	efects. tering devices brupt contact f pinch ng position.	r r	г г	N/A N/A N/A	Problem / Soluti	ion .
and other obv Equipment is provide or cushioning mater with Fulcrums/pivot or co Handholds are provi	ree of cracks, corr vious structural de d with spring cen rial to prevent ab n the ground. t points are free o crush hazards. ided at each seati	efects. tering devices brupt contact f pinch ng position.	r r	г г	N/A N/A N/A	Problem / Soluti	ion .

Litib Beach playground			
General Inspection	Pas	Fail	Problem / Solution
Playground area is free of litter and debris.	2	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	5/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	Г	
Playground area is properly fenced.	T -	Г	NIA
Self-latching gate works as designed.	Г	Г	NIA
Surfacing	Pass	Fail	
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	_	Г	NA
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	NIA
Surfacing material is free of glass, debris, or other foreign objects.	Г	7	weeds growing around play ostound
Surfacing material is not compacting or deteriorating.	Г	Г	NA
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-	г	NA
Proper drainage prevents water from forming puddles.	_	г	NIA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	r/	·~/	missing Hondle on Climbing
Equipment is free from sharp points, corners, or edges.	1	г	We Crive of the
Protective caps or plugs are not missing or damaged.	Γ-	г	N/A
Equipment is free of potential clothing entanglement hazards.	. 2	Г	
Equipment free of pinch and crush points or exposed moving parts.		_E X	rusting the tedder
Equipment is free of rust, rot, cracks, and splinters.	NX.	- *	rusting Blue lader
Equipment is free of entrapments.		Г	, so c (more)
Equipment is safely anchored.	4	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	AJ/A
Swings are a safe distance from other playground equipment.	- Г	Г	N/A
Swings are 24 inches apart.	Г	Г	NIA
Edges of seats are smooth and free from obstructions.	F	г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	г	NA