LH Beach (Pov	Illio	70 1	Planaround)
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	1	п	
Playground area is free of anthills/hazardous insects or toxic plants.	1	r	
Playground area is free of holes and other tripping hazards.	7	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	٣	1	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	r.	r.	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	۲	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	A	Г	
Surfacing material is not compacting or deteriorating.	4	г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	1	
Proper drainage prevents water from forming puddles.	j.	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	F	г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Γ	
Equipment is free of rust, rot, cracks, and splinters.	JE.	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	F	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	of	Г	
Swings are a safe distance from other playground equipment.	· -	'r	4 /
Swings are 24 inches apart.	Г	Г	NO Swings
Edges of seats are smooth and free from obstructions.	г	r <b>'</b>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	

Lt Beach (Pavi	110	n Pl	ay ground)
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	A		
Platforms are equipped with guardrails or equivalent protective equipment.		D	
Average incline is less than 30 degrees.		П	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	N	n	
Rope or chain ladders are anchored at both ends.	7	П	
Foot holds/rungs are in good condition and adequately spaced.	P		
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			,
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	С	Problem / Solution  None
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	п	п	,
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	n n	0	,
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.  Handholds are provided at each seating position.	n n	0	,

Lighthouse (	Bea	ch	Planground)
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	1	г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	1:	
Playground area is properly fenced.	Г	г	N(A)
Self-latching gate works as designed.	Γ.	Ē	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Г	L	Sandbase
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	į (
Surfacing material is free of glass, debris, or other foreign objects.	Γ	Г	ι (
Surfacing material is not compacting or deteriorating.	Г	Г	į (
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	r	ιι
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	A	Γ,	
Protective caps or plugs are not missing or damaged.	7	l	
Equipment is free of potential clothing entanglement hazards.	P	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	г	
Equipment is free of rust, rot, cracks, and splinters.	yk.	г	•
Equipment is free of entrapments.	F	Г	
Equipment is safely anchored.	1	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.	г	'г	
Swings are 24 inches apart.	Г	г	NO Swings
Edges of seats are smooth and free from obstructions.	г	۲,	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	

Littouse (Beach P	109	Grou	ind )
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	7	П	
Platforms are equipped with guardrails or equivalent protective equipment.	B	0	
Average incline is less than 30 degrees.		П	
Exit regions are level.	P		Sand
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	ji .	П	
Foot holds/rungs are in good condition and adequately spaced.	N		
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			Problem / Solution  No See Saw 5
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	П	П	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	0	0	
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	n n	о О	

	A SECTION OF THE RESERVE OF THE RESE	St. Co. and the Co. and the Co. and the Co.	pad play ground
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	F	г	
Playground area is free of holes and other tripping hazards.	A	г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	1	F
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	F	r	
Surfacing material under and around equipment is adequate depth (6-12 inches).	A	г	
Surfacing material is free of glass, debris, or other foreign objects.	1	г	
urfacing material is not compacting or deteriorating.	A	г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	7	٢	
Proper drainage prevents water from forming puddles.	-	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	г	
rotective caps or plugs are not missing or damaged.	1	L.	
Equipment is free of potential clothing entanglement hazards.	<i>it</i> -	г	
quipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	8	Г	
Equipment is free of entrapments.	*	Г	
Equipment is safely anchored.	1	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.	: !	·r	1
Swings are 24 inches apart.	Г	Г	NO Suings
Edges of seats are smooth and free from obstructions.	г	r'	i v v v v v v v v v v v v v v v v v v v
ate depths of surfacing material extend out a m distance of twice the height of the swing.	r	r	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	A		
Equipped with platforms to facilitate access to the sitting position.	M	П	
Platforms are equipped with guardrails or equivalent protective equipment.	1		
Average incline is less than 30 degrees.			
Exit regions are level.	1	D	
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	P	П	
Foot holds/rungs are in good condition and adequately spaced.	V	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	Ō	None
Fulcrums/pivot points are free of pinch or crush hazards.	П		
Handholds are provided at each seating position.	Г	П	
Inspector name, signature, and completion date			
Name: Blair Carter Signature:			Date:
Signature.			

E STATE OF THE STA	71	of the second		
1911	Hen	MIA/	Pan	4
PIL	1	TIV	1 011	

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	1	۳	
Playground area is free of holes and other tripping hazards.	7h	г	
Proper signage with rules, hours, and age- appropriate use is posted.	X	1	
Playground area is properly fenced.	Г	Γ	W/A
Self-latching gate works as designed.	Г.	r.	N/A
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	P	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	M	Γ	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	٢	1	
Proper drainage prevents water from forming puddles.	Ø.	г	
Equipment Hazards	Pass	Fail	Problem / Solution
<b>Equipment Hazards</b> Equipment is not damaged or vandalized.	Pass	Fail	Problem / Solution
			Problem / Solution
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners,	1	Γ	Problem / Solution
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.	f. 1	Г	Problem / Solution
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing	F. 1	Г	a Cew
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed	F. 1	г г	a Cew
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.	F. 1 W W W W W W W W W W W W W W W W W W	L L L	
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.	* / / / / / / / / / / / / / / / / / / /	r r	a Cew
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.	# # # #		a Cew
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.	# / / / / / / / / / / / / / / / / / / /		a few Need touch ups around botts
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.  Swings	/ / / / / / / / / / / / / / / / / / /	r r r r	a few Need touch ups around botts
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.  Swings  Hardware and chains are in good condition.  Swings are a safe distance from other playground	/ / / / / / / / / / / / / / / / / / /	r r r r Fail	a few Need touch ups around botts
Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.  Swings  Hardware and chains are in good condition.  Swings are a safe distance from other playground equipment.	/ / / / / / / / / / / / / / / / / / /	Fail r	a few Need touch ups around botts

(To be completed monthly.)

Buttenflu Pant

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	P	П	
Equipped with platforms to facilitate access to the sitting position.	0	П	
Platforms are equipped with guardrails or equivalent protective equipment.	7		
Average incline is less than 30 degrees.		П	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	p		
Foot holds/rungs are in good condition and adequately spaced.	p	n	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Е	П	None
Fulcrums/pivot points are free of pinch or crush hazards.	п	П	
Handholds are provided at each seating position.	г	П	
Inspector name, signature, and completion date			
Name: B(gia Content			Date:

Note; I know that its known, but exercise area needs attention.

(To be completed monthly.)

#### Claret Crossing

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	P	П	
Playground area is free of anthills/hazardous insects or toxic plants.	ti	г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Γ	P	
Playground area is properly fenced.	Г	Г	WA
Self-latching gate works as designed.	Γ.	Г	WIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	x	٦	
Surfacing material under and around equipment is adequate depth (6-12 inches).	+	Г	
Surfacing material is free of glass, debris, or other foreign objects.	7	Г	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	at .	Г	
Proper drainage prevents water from forming puddles.	Jan .	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Г	
Equipment is free from sharp points, corners, or edges.	6	Г	
Protective caps or plugs are not missing or damaged.	0	r	
Equipment is free of potential clothing entanglement hazards.	1	Г	,
Equipment free of pinch and crush points or exposed moving parts.	A.	٢	
Equipment is free of rust, rot, cracks, and splinters.	A	Г	
Equipment is free of entrapments.	ø	Г	
Equipment is safely anchored.	2	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	25	Г	
Swings are a safe distance from other playground equipment.	A	'г	
Swings are 24 inches apart.	Ī	Г	
Edges of seats are smooth and free from obstructions.	P	r <b>'</b>	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	0	r	

Claret Crossing			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	F	П	
Equipped with platforms to facilitate access to the sitting position.	7		
Platforms are equipped with guardrails or equivalent protective equipment.	t	Ō	
Average incline is less than 30 degrees.		П	
Exit regions are level.	Sp.		
Metal slides are shaded to prevent overheating.	С		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	a	П	
Rope or chain ladders are anchored at both ends.	1	П	
Foot holds/rungs are in good condition and adequately spaced.	п	CI.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П	Г	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	П	П	Wone
Fulcrums/pivot points are free of pinch or crush hazards.	С	C	
Handholds are provided at each seating position.	Г	П	
Inspector name, signature, and completion date			
Name: Blain Carter			
Bot			Date: 8.2-23

Bonfront (Plang	nov	ind	
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	P	Γ.	
Playground area is free of anthills/hazardous insects or toxic plants.	n	r	
Playground area is free of holes and other tripping hazards.	7	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	×	N	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Γ	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	a	Γ	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Ā	r	
Proper drainage prevents water from forming puddles.	a	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	4	Г	
Equipment is free from sharp points, corners, or edges.	A-	Г	
Protective caps or plugs are not missing or damaged.	A	L.	
Equipment is free of potential clothing entanglement hazards.	A	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Γ	
Equipment is free of entrapments.	ins	Г	
Equipment is safely anchored.	R	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	г	Г	
Swings are a safe distance from other playground equipment.	Г	r'	
Swings are 24 inches apart.	г	Г	NOND
Edges of seats are smooth and free from obstructions.	г	۲,	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	. F	

(To be completed monthly.)

Banfront ( Planground Slides **Pass** Fail **Problem / Solution** Slides are free of obstructions and protrusions. Equipped with platforms to facilitate access 1 to the sitting position. Platforms are equipped with guardrails or equivalent protective equipment. Average incline is less than 30 degrees. Exit regions are level. 1 Metal slides are shaded to prevent overheating. **Climbing Equipment** Fail Problem / Solution Pass Hand grips are secured and do not rotate. Rope or chain ladders are anchored at both ends. Foot holds/rungs are in good condition and adequately spaced. Problem / Solution Fail Seesaws Pass Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact WONE with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position. -Inspector name, signature, and completion date Date: 8 - 2 - 23

(To be completed monthly.)

Gearge Adams

Gearge Hdoms	Stein 20 in		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	16	f"	
Playground area is free of holes and other tripping hazards.	M	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	ľ.	F	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Γ.	Г.	NA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	٦	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	г	
Surfacing material is not compacting or deteriorating.	Г	1	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<b>X</b>	г	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	7	Г	
Equipment is free of potential clothing entanglement hazards.	de	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	г	1	Rust around some botts
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	+	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	Г	1 swingset on order
Swings are a safe distance from other playground equipment.	7	· r	30 (11) 30 (10) 100
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from obstructions.	1	Γ'	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	г	

(To be completed monthly.)

George Adams

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	F		10.000
Equipped with platforms to facilitate access to the sitting position.	To the state of th		
Platforms are equipped with guardrails or equivalent protective equipment.	V		
Average incline is less than 30 degrees.			
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	V	П	
Rope or chain ladders are anchored at both ends.	P		
Foot holds/rungs are in good condition and adequately spaced.	7	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	1		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	1	П	
Fulcrums/pivot points are free of pinch or crush hazards.	1		
Handholds are provided at each seating position.	1	П	
Inspector name, signature, and completion date			
Name: Blair Carler Signature: Batt			Date:

(To be completed monthly.)

WWI SON FORT

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	P	Γ.	
Playground area is free of anthills/hazardous insects or toxic plants.	M	l.	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	P	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Γ.	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Ø	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	J	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	8	Γ	
Surfacing material is not compacting or deteriorating.	N	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	er .	٦	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	4	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	L.	
Equipment is free of potential clothing entanglement hazards.	5	г	
Equipment free of pinch and crush points or exposed moving parts.	de	٢	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	A few bolt surrounds
Equipment is free of entrapments.	ir	Г	
Equipment is safely anchored.	A	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	A	г	
Swings are a safe distance from other playground equipment.	No. of the last of	′ г	a
Swings are 24 inches apart.	15	Г	
Edges of seats are smooth and free from obstructions.	5	r'	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	15	г	

Pass	Fail	Problem / Solution
6		The state of the s
j.		
A	D	
N		
Pass	Fail	Problem / Solution
1	П	
1	D	
A	п	
Pass	Fail	Problem / Solution
П	П	
<u>п</u>	п	No Seesaws
		No Seesaws
п	П	No Seesaws
С	n	No Seesaws
	Pass	Pass Fail

Gitz Park (P	avi	llio	n) Playgnound
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Б	
Playground area is free of anthills/hazardous insects or toxic plants.	1	r	
Playground area is free of holes and other tripping hazards.	1	г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	1	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	Γ.	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	9	L	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	٢	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	7	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	*	r	
Proper drainage prevents water from forming puddles.	*	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	a	Г	
Equipment is free from sharp points, corners, or edges.	X	г	
Protective caps or plugs are not missing or damaged.	7	L.	
Equipment is free of potential clothing entanglement hazards.	F	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	г	Ø.	Lightrust around bolts
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	7	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	8	ŕ	t u.
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from obstructions.	7	Γ'	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	×	г	

CIYO Park Pavi	110	9	Planground
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	8		
Platforms are equipped with guardrails or equivalent protective equipment.	7	П	
Average incline is less than 30 degrees.			
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	П	
Rope or chain ladders are anchored at both ends.	V	Ü	
Foot holds/rungs are in good condition and adequately spaced.	7		
the state of the s		National Contract of the Contr	
Seesaws	Pass	Fail	Problem / Solution
	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion,			Problem / Solution  None
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	С	П	
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	С	п	
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	0	0	
Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.  Handholds are provided at each seating position.	0	0	

CitaPart (As	hle	7 F	relds Blangrounds
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	7	r	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	1	
Playground area is properly fenced.	Г	F	NIA
Self-latching gate works as designed.	Γ.	r	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	L	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	7	
Proper drainage prevents water from forming puddles.	1	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	K	Г	
Equipment is free from sharp points, corners, or edges.	6	Г	
Protective caps or plugs are not missing or damaged.	7	Г	
Equipment is free of potential clothing entanglement hazards.	7	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	7	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	г	Г	
Swings are a safe distance from other playground equipment.	-	'r	
Swings are 24 inches apart.	Г	г	NO Duings
Edges of seats are smooth and free from obstructions.	г	r'	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	г	

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	#		
Equipped with platforms to facilitate access to the sitting position.	1		
Platforms are equipped with guardrails or equivalent protective equipment.	7	D	
Average incline is less than 30 degrees.			
Exit regions are level.	11	П	
Metal slides are shaded to prevent overheating.			
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	П	
Rope or chain ladders are anchored at both ends.	D	D	
Foot holds/rungs are in good condition and adequately spaced.	1		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	П	П	No Secsaws
Fulcrums/pivot points are free of pinch or crush hazards.		П	
Handholds are provided at each seating position.	П	П	
Inspector name, signature, and completion date			
Name: Bluir Carter			
Signature: B CA			Date: 8.2-23