
Light House Reach P	laygr	rounc	Dec 13, 7024
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	п	Franciscondistricture of the constitution of t
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.	V	Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	П	Г	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	г	Г	N/A
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	Г	N/A
Surfacing material is free of glass, debris, or other foreign objects.	, _	Г	weeds growing around playgrow
Surfacing material is not compacting or deteriorating.	Г	Г	A)/A
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Г	N/A
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	Г	V	missing 9 bolts
Equipment is free from sharp points, corners, or edges.		Г	vitissing twis
Protective caps or plugs are not missing or damaged.	r	r-	N/A
Equipment is free of potential clothing entanglement hazards.	г	Г	
Equipment free of pinch and crush points or exposed moving parts.	г	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г		Rust on bive metal lackders
Equipment is free of entrapments.		٢	J. J
Equipment is safely anchored.	V	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	NA
Swings are a safe distance from other playground equipment.		г	N/A
Swings are 24 inches apart.	Г	Г	1// /4
Edges of seats are smooth and free from obstructions.	Г	г	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Γ.	Г	NA



TIGHT HOUSE KEEC	.V\	W.L.U.	YGYOUN	<u> </u>	
Slides	Pass	Fail		Problem / Solution	
Slides are free of obstructions and protrusions.	Ľ	Ü	<u> </u>		
Equipped with platforms to facilitate access to the sitting position.	Ľ	D			
Platforms are equipped with guardrails or equivalent protective equipment.	F./	П			
Average incline is less than 30 degrees.	[2]	<u>_</u> "			
Exit regions are level.	[S	מ	te		
Metal slides are shaded to prevent overheating.		0	N/A	Plustic Slides	
Climbing Equipment	Pass	Fail		Problem / Solution	
Hand grips are secured and do not rotate.	n	D	order	R New handgrips	•
Rope or chain ladders are anchored at both ends.	ח	_ <u>_</u>	N/A	100000000000000000000000000000000000000	
Foot holds/rungs are in good condition and adequately spaced.	[ı.	7-771		<u> </u>
Seesaws	Pass	Fail		Problem / Solution	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass r	Fail n	N/A	Problem / Solution	
Seesaws are free of cracks, corrosion,			N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	٦	n_	N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	r 	n n	N/A N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r r	u u	N/A N/A N/A N/A	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r r	u u	N/A N/A N/A	Problem / Solution	

light House Splash	Que	1	Playaround
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	/	10	
Playground area is free of anthills/hazardous insects or toxic plants.	~	Г	
Playground area is free of holes and other tripping hazards.	Г		Couple notes
Proper signage with rules, hours, and age- appropriate use is posted.		ſ	
Playground area is properly fenced.	Г	-	NIA
Self-latching gate works as designed.	Г	-	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		/ -	
Surfacing material is not compacting or deteriorating.		E.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	N/A
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	/	Г	
Protective caps or plugs are not missing or damaged.	r-	f	NIA
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	Г,	T.	minor rust
Equipment is free of entrapments.	1	· r	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	N/N
Swings are a safe distance from other playground equipment.		Г	N/A
Swings are 24 inches apart.	г		NIA
Edges of seats are smooth and free from obstructions.	г	۳	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	NIA

light House splas	AND RESIDENCE OF STREET	A STATE OF THE PARTY OF THE PAR	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		17	
Playground area is free of anthills/hazardous insects or toxic plants.	~	Г	
Playground area is free of holes and other tripping hazards.	/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	~	Г	9
Playground area is properly fenced.	Г	F	NIA
Self-latching gate works as designed.	Ι τ.	-	NIA
Surfacing The Control of the Control	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	٢	
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	Г	N/A
Surfacing material is free of glass, debris, or other foreign objects.		r	
Surfacing material is not compacting or deteriorating.	1	г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	NIA
Proper drainage prevents water from forming puddles.		-	,,,,,,
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	/	Г	
Protective caps or plugs are not missing or damaged.	l	F	N/A
Equipment is free of potential clothing entanglement hazards.	F-	Г	
Equipment free of pinch and crush points or exposed moving parts.		, Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.		/г	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	11/19
Swings are a safe distance from other playground equipment.	Г	г	NA
Swings are 24 inches apart.	F	Г	1/A
Edges of seats are smooth and free from obstructions.	Г	Г	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	J	r	N/A

light House Splash +	od!		ž stala	and the second of the second o
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.			N/A	attati oo ta'a ahaa aasaa ka ahaa waa aa
Equipped with platforms to facilitate access to the sitting position.	Ľ		J/A	
Platforms are equipped with guardrails or equivalent protective equipment.	ני	D	u/ /\	,
Average incline is less than 30 degrees.	С		J/À	
Exit regions are level.	n	□ V	J/A	
Metal slides are shaded to prevent overheating.	_ r:	J	/A	
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	0	n	W/A	·
Rope or chain ladders are anchored at both ends.	Ľ	П	W/ A	
Foot holds/rungs are in good condition and adequately spaced.	п	n.	<i>,</i>	
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Ľ1	L,	AJ/A	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	, n	ß	N/A	
Fulcrums/pivot points are free of pinch or crush hazards.	Ŀ	Γ.	N/A	
Handholds are provided at each seating position.	г	n	W/A	
Inspector name, signature, and completion date				
Name: Douglus Capio Signature: Suglus Capso			· .	Date: <u>Dec 13, とめこ4</u>
v				

<u>1511 - </u>	VJa	a ylaya	around	<i>a,</i>
Pass	Fail		Problem / Solution	
5	ដា ំ	4 gr vit		
	Ū			
	מ			
[/	D	W/A		
15.	ם	. ,		•
<u>.</u>	G.	Plastic	Slides	
Pass	Fail		Problem / Solution	
Į.	□			
п	r)	N/A		
ē	u.	· · · · · · · · · · · · · · · · · · ·		
Pass	Fail		Problem / Solution	
٢	r:	N/A		
Г	П	A1/A		-
Г	ជ	N/A		
n	r:	N/A		
				
			Date: Dec 13, 2024	
	Pass Pass Pass r	Pass Fail Pass Fail Pass Fail Pass Fail Pass Fail Pass Fail Pass Fail	Pass Fail Pass Fail	Pass Fail Problem/Solution D D D D D D D D D D D D D

light House Davillon	6	laya	round
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	100	/-	
Playground area is free of anthills/hazardous insects or toxic plants.			
Playground area is free of holes and other tripping hazards.		1	
Proper signage with rules, hours, and age- appropriate use is posted.	/	Г	N. Control of the Con
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	Γ.	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	N-
Surfacing material is free of glass, debris, or other foreign objects.		/ [
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	NIA
Proper drainage prevents water from forming puddles.		- an	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	r-	L	N/A
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	1	1	
Equipment is free of entrapments.	1		
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	AJ/A
Swings are a safe distance from other playground equipment.		r	Al/A
Swings are 24 inches apart.	Г	Г	NA
Edges of seats are smooth and free from obstructions.	Г	Г	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	r	Г	N/A

hant House Pavillon	<u> 10 0</u>	Yarr	ound	and the second of the second o
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.				
Equipped with platforms to facilitate access to the sitting position.	F			
Platforms are equipped with guardrails or equivalent protective equipment.	i			
Average incline is less than 30 degrees.		<u>_</u>		
Exit regions are level.	E	D		
Metal slides are shaded to prevent overheating.			U/A.	
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.		/ n "		· · · · · · · · · · · · · · · · · · ·
Rope or chain ladders are anchored at both ends.	, ,	П		
Foot holds/rungs are in good condition and adequately spaced.		Π		
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail □	N/A	Problem / Solution
Seesaws are free of cracks, corrosion,	_	-	N/A N//	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	L.	N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	r	מ	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r r	n n	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r r	n n	N/A N/A N/A	Date: Dec 13, 2024

Buttertly Duyarou	ncl		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	/	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	~	Г	
Playground area is free of holes and other tripping hazards.	/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	8
Playground area is properly fenced.	Г	ľ.	NIA
Self-latching gate works as designed.	Г.	г	NIA
Surfacing 1997 And Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	N/A
Surfacing material is free of glass, debris, or other foreign objects.	F	r	
Surfacing material is not compacting or deteriorating.	Г	Г	Deteriorationa
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<u></u>	Г	N/A
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	-		
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	r-	, I	N/A
Equipment is free of potential clothing entanglement hazards.	/	Г	
Equipment free of pinch and crush points or exposed moving parts.	7	Г	•
Equipment is free of rust, rot, cracks, and splinters.	г	~	rust all over
Equipment is free of entrapments.		-	
Equipment is safely anchored.		Г	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	1	
Swings are a safe distance from other playground equipment.		/ 「	+ i
Swings are 24 inches apart.	1	1	
Edges of seats are smooth and free from obstructions.		/ -	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	5	Г	

Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	F	, in	. 9*	to the second
Equipped with platforms to facilitate access to the sitting position.	13			
Platforms are equipped with guardrails or equivalent protective equipment.	<u></u>	מ	•	
Average incline is less than 30 degrees.		ָם		
Exit regions are level.		ū		
Metal slides are shaded to prevent overheating.			Plustic	Slides
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	E,	П		
Rope or chain ladders are anchored at both ends.	<u>.</u>	<u></u>	N/A	
Foot holds/rungs are in good condition and adequately spaced.	8			
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Ľ.	Ľ	N/A	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	L,	n	N/A	
Fulcrums/pivot points are free of pinch or crush hazards.	Γ;	r;	N/A	
Handholds are provided at each seating position.	г	Г	N/A	
nspector name, signature, and completion date				
ignature: Doy 18 Cape				Date: 5 2024

Claret crossing			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Г	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	,
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	× ×
Playground area is properly fenced.	Г	Va.	W/A
Self-latching gate works as designed.	r.	T	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).			
Surfacing material is free of glass, debris, or other foreign objects.	-	F	
Surfacing material is not compacting or deteriorating.	f-	Г	Concrete cracking
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Towns	N/A
Proper drainage prevents water from forming puddles.	г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.		, Г	
Protective caps or plugs are not missing or damaged.	1	r	
Equipment is free of potential clothing entanglement hazards.		, г	
Equipment free of pinch and crush points or exposed moving parts.		, 「	
Equipment is free of rust, rot, cracks, and splinters.	1		
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	/	Г	
Swings are a safe distance from other playground equipment.		Г	a t
Swings are 24 inches apart.	1	F	
Edges of seats are smooth and free from obstructions.	1	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	r	

Clarete Crossing		
Slides	Pass Fail	Problem / Solution
Slides are free of obstructions and protrusions.	₽ _□	* * * * * * * * * * * * * * * * * * * *
Equipped with platforms to facilitate access to the sitting position.		
Platforms are equipped with guardrails or equivalent protective equipment.	5 / D	
Average incline is less than 30 degrees.	F	
Exit regions are level.	L C	
Metal slides are shaded to prevent overheating.		A Plustic Sticles
Climbing Equipment	Pass Fail	Problem / Solution
Hand grips are secured and do not rotate.	E / D	
Rope or chain ladders are anchored at both ends.	r/ /ri	
Foot holds/rungs are in good condition and adequately spaced.	, n	
Seesaws	Pass Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	г,	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	
Fulcrums/pivot points are free of pinch or crush hazards.	5/5	
Handholds are provided at each seating position.	Г	
Inspector name, signature, and completion date		
Name: Dauglas Corpia		

Rayfront Splush	Par	d	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Γ	
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	8.
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	r	Г	NIA
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	Г	Concrete
Surfacing material under and around equipment is adequate depth (6-12 inches).	1-	Г	Concrete N/A
Surfacing material is free of glass, debris, or other foreign objects.	1	г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	г	1)/A
Proper drainage prevents water from forming puddles.		г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.		1	
Equipment is free of potential clothing entanglement hazards.		, г	
Equipment free of pinch and crush points or exposed moving parts.		<i>/</i>	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	F	Г	
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Γ	Г	N/A
Swings are a safe distance from other playground equipment.	· _	Г	NIA
Swings are 24 inches apart.	-	Г	NIA
Edges of seats are smooth and free from obstructions.	Г	Г	NIA
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	J	r	NIA

DIVERNAT DIGINGING	unc		La Belle
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	Per	Г	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	si di
Playground area is properly fenced.	F	Г	NIA
Self-latching gate works as designed.	Γ.	Γ	NIA
Surfacing *** *** Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	N/A
Surfacing material is free of glass, debris, or other foreign objects.		, г	
Surfacing material is not compacting or deteriorating.	-/	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	NJ/Å
Proper drainage prevents water from forming puddles.	Т	г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		, г	
Equipment is free from sharp points, corners, or edges.	/	Γ	
Protective caps or plugs are not missing or damaged.	r	, _	N/A
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	Г		minor Rust on Nuts and Bol
Equipment is free of entrapments.	Г	Г	
Equipment is safely anchored.	Г	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	NIA
Swings are a safe distance from other playground equipment.	Г	Г	N/A
Swings are 24 inches apart.	F	Г	NIA
Edges of seats are smooth and free from obstructions.	г	Г	NIK
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	r	NIK

			•		
					•
		× .			
	•				
•					
	21.5				

<u> IVICL</u>	L	a b	elle:		A Section of the sect	
Pass	Fail		Pr	oblem / Solu	ution	
	П		· •			
	Ci					
	מ					
n /	/ 0	NIA	t			
	Ü					
Ľ	. D	N/A	Plastic	Slicke	9	•
Pass	Fail				ution	
[-/	ה	-				
Б /	, G	NIA				-
,,	n 					
Pass	Fail		Pr	oblem / Sol	ution	
۲ ,	п	N/A				
Ē.	D	•				
L.	Б		-		•	
Ĺ	ß					
			 D a te:	Dec 13	3, (di	74
	Pass Pass Pass F	Pass Fail D D D D D D D D D D D D D D D D D D	Pass Fail Pass Fail Pass Fail Pass Fail Pass Fail Pass Fail	Pass Fail Property of the control o	Pass Fail Problem/Solution DA DA DAS Fail Problem/Solution Pass Fail Problem/Solution Pass Fail Problem/Solution DA D	Pass Fail D D D D D D D D D D D D D




(To be completed monthly.)

City Dark


LITY PARK			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	F		-
Playground area is free of anthills/hazardous insects , or toxic plants.	F-/	٦	
Playground area is free of holes and other tripping hazards.		٦	
Proper signage with rules, hours, and age- appropriate use is posted.	-		
Playground area is properly fenced.	Г	-	NIA
Self-latching gate works as designed.	F.	ŗ	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		r	
Surfacing material under and around equipment is adequate depth (6-12 inches).	is	F	
Surfacing material is free of glass, debris, or other foreign objects.		-	
Surfacing material is not compacting or deteriorating.	r/	Ĺ.	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	г	
Proper drainage prevents water from forming puddles.	Г	-	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		/ F	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	r	Γ"	ル/A
Equipment is free of potential clothing entanglement hazards.	1	١,	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.		f*	minor rust
Equipment is free of entrapments.	r	Г	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		∕ 「	
Swings are a safe distance from other playground equipment.		<u></u>	
Swings are 24 inches apart.		/ [
Edges of seats are smooth and free from obstructions.			
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		٦	

City Pork	7 m, 7			
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	, G	ū	NIA	- · · · · · · · · · · · · · · · · · · ·
Equipped with platforms to facilitate access to the sitting position.	ם	П	1)/A	
Platforms are equipped with guardrails or equivalent protective equipment.	ü	<u>.</u>	J/A	
Average incline is less than 30 degrees.	С	0	N/A	
Exit regions are level.	ח	D	N/A	
Metal slides are shaded to prevent overheating.	L.;	П		
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	√	Б		
Rope or chain ladders are anchored at both ends.	Γ.	[a	ALLA	
Foot holds/rungs are in good condition and adequately spaced.	7			
_				
Seesaws	Pass	Fail		Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail r.	V/A	Problem / Solution
Seesaws are free of cracks, corrosion,	Pass		W/A W/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	F	Г.	N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch		г. -	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г	г. п	N/A N/A N/A	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	Г	г. п	N/A N/A N/A	Problem / Solution Date: Dec 13, 2024



City Park By Ash	ley	fie	elds
General Inspection	Pass		Problem / Solution
Playground area is free of litter and debris.	1	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	/	Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	Г	г	, .
Surfacing Company of the Company of	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	/	Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.		厂	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	Г	
Proper drainage prevents water from forming puddles.	Г	F	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Γ	
Equipment is free from sharp points, corners, or edges.		/ [「] /	
Protective caps or plugs are not missing or damaged.	麦	*	
Equipment is free of potential clothing entanglement hazards.			
Equipment free of pinch and crush points or exposed moving parts.	F-/	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	Г	minor rust
Equipment is free of entrapments.	Г	Г	-
Equipment is safely anchored.	г	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	NIA
Swings are a safe distance from other playground equipment.	Г	Г	N/A
Swings are 24 inches apart.	-	T	N/A
Edges of seats are smooth and free from obstructions.	Г	Г	N/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	100	NA
			/

City parts by Ashley +	-1910	The second second second	and the second of the second o
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	П	and the second control of the boundary of the second control of the second of the seco
Equipped with platforms to facilitate access to the sitting position.	E/		
Platforms are equipped with guardrails or equivalent protective equipment.		П	
Average incline is less than 30 degrees.		. 0	
Exit regions are level.	/		
Metal slides are shaded to prevent overheating.		- Dlush	C Stides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.			
Rope or chain ladders are anchored at both ends.		_ [9
Foot holds/rungs are in good condition and adequately spaced.		П	
_			
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail NIA	Problem / Solution
Seesaws are free of cracks, corrosion,	and the same		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	DIA	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	Г	DIA	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	Г	DIA	Problem / Solution



(To be completed monthly.)

Wilson Porks

MISONI POVICS	M STREET, STRE	Name of Street Control	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Г	Appropriation of the second se
Playground area is free of anthills/hazardous insects or toxic plants.		-	
Playground area is free of holes and other tripping hazards.	1	, 「	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	No.
Playground area is properly fenced.	Г	Γ	NIA
Self-latching gate works as designed.	Г	Γ	NIA
Surfacing ************************************	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.	[2]	/ F	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	and the second	Г	N/A
Proper drainage prevents water from forming puddles.	9	г	W/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Γ	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	1	/ F	
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	X	-	minor rust
Equipment is free of entrapments.		/, [
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.		Г	
Swings are 24 inches apart.	1	· 「	
Edges of seats are smooth and free from obstructions.	1	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	+	Г	

WILSON DONG	v. 4			
Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.			17A - P	
Equipped with platforms to facilitate access to the sitting position.			,	
Platforms are equipped with guardrails or equivalent protective equipment.	-/	П		
Average incline is less than 30 degrees.	D ,	/ D	N/A	
Exit regions are level.	Ę,	D		
Metal slides are shaded to prevent overheating.			N/A ()	ostic Slides
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	Ľ	п		
Rope or chain ladders are anchored at both ends.	N.	_ G	<u>. </u>	
Foot holds/rungs are in good condition and adequately spaced.	[·	П		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	. <u> </u>	Ľ	N/A	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	r	r ₂	N/A	
Fulcrums/pivot points are free of pinch or crush hazards.	Г	Γ	N/A	
Handholds are provided at each seating position.	r	Γ:	N/A	
nspector name, signature, and completion date				<u> </u>
Name: Douglas Carpio				Date: Dec 13, 2024
Signature: 1 cm Jus Corplis				

George Adams Park			Section of the sectio
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Г	
Playground area is free of anthills/hazardous insects or toxic plants.	-/	Г	
Playground area is free of holes and other tripping hazards.	/	Г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	8
Playground area is properly fenced.	1	F	NIA
Self-latching gate works as designed.	_ n	Г	NIA
Surfacing Water State Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	-	-/	littlemore mulch needed
Surfacing material is free of glass, debris, or other foreign objects.			
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	T	N/A
Proper drainage prevents water from forming puddles.	г	9	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		/ 「	
Equipment is free from sharp points, corners, or edges.	1	, г	
Protective caps or plugs are not missing or damaged.	P	/ 「	
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	1	ſ	
Equipment is free of rust, rot, cracks, and splinters.		- 「	minor rust
Equipment is free of entrapments.		/ 「	•
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	/ 「	
Swings are a safe distance from other playground equipment.		/ 「	e i
Swings are 24 inches apart.		/ 「	
Edges of seats are smooth and free from obstructions.	-	/ -	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		-	

Teorge Adams			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	٦	<u> </u>	- · · · · · · · · · · · · · · · · · · ·
Equipped with platforms to facilitate access to the sitting position.	F		
Platforms are equipped with guardrails or equivalent protective equipment.	7	D	
Average incline is less than 30 degrees.	G	· D W/A	
Exit regions are level.	ſ.	ū	
Metal slides are shaded to prevent overheating.	C	5 N/A	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F.	П	
Rope or chain ladders are anchored at both ends.	<u></u>	<u>ر</u> م	
Foot holds/rungs are in good condition and adequately spaced.	F/	r	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	/م	ļ.,	
		r r	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		,	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch		Г:	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.		г / п	
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.		г / п	