in the state of th	o depley	(1) (1) (8)	Povillion
City Port	Pas	s Fail	
General Inspection		E TETT	· ·
Playground area is free of litter and debris.	9		
Playground area is free of anthills/hazardous insects or toxic plants.	7	, r	
Playground area is free of holes and other tripping hazards.	1		
Proper signage with rules, hours, and age- appropriate use is posted.	1	. Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Γ.	Г	NIA
Surfacing	Pas	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	Ó	r	
urfacing material is not compacting or deteriorating.	1	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	1		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1		
rotective caps or plugs are not missing or damaged.	8	r	
Equipment is free of potential clothing entanglement hazards.	-	٦	
Juipment free of pinch and crush points or exposed moving parts.	Ø	Г	
quipment is free of rust, rot, cracks, and splinters.	8	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	OF	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
wings are a safe distance from other playground equipment.	F	Г	
Swings are 24 inches apart.	1	Г	
El C			

City Part			Pavillion
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		г	
Equipped with platforms to facilitate access to the sitting position.	1	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	1	Γ.	
Average incline is less than 30 degrees.	Γ	<i>;</i> -	
Exit regions are level.		٢	
Metal slides are shaded to prevent overheating.	Г	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F	г.	
Rope or chain ladders are anchored at both ends.		Γ	
Foot holds/rungs are in good condition and adequately spaced.	Ē	Г	
表面的 2 分配的 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		Fail	Problem / Solution
Seesaws	Pass	Fall	T TO DIGHT, C.
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	L.	
Seesaws are free of cracks, corrosion,		NEW TOTAL	Nonc
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		Г	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	F	г	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	r -	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	r -	

in the state of th	u Yerlai		Ashley Field
City Pant	Pas	s Faii	Problem / Solution
General Inspection Playground area is free of litter and debris.	#	2 81.611	
Playground area is free of anthills/hazardous insects	+		
or toxic plants.	#	, ,	
Playground area is free of holes and other tripping hazards.	1	· r	
Proper signage with rules, hours, and age- appropriate use is posted.	Γ.	tw	
Playground area is properly fenced.	Г	Г	W/A
Self-latching gate works as designed.	Γ.	Г	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	#	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	15	г	
urfacing material is not compacting or deteriorating.	~	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F	Г	
Proper drainage prevents water from forming puddles.	4-	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	*	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
otective caps or plugs are not missing or damaged.	4	r	
Equipment is free of potential clothing entanglement hazards.	<i>F</i>	Г	
Juipment free of pinch and crush points or exposed moving parts.	Ø	г	
quipment is free of rust, rot, cracks, and splinters.	1	г	
Equipment is free of entrapments.	P)	Г	
Equipment is safely anchored.			
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
wings are a safe distance from other playground equipment.		Г	" Ware
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from	г	Г	

city Pant	y ens en en en en		Ashler rield
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7	r:	
Equipped with platforms to facilitate access to the sitting position.	F	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	St.	Γ.	
Average incline is less than 30 degrees.	Γ	F	
Exit regions are level.	1	٢	
Metal slides are shaded to prevent overheating.	Г	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	6	Г.	
Rope or chain ladders are anchored at both ends.			
Foot holds/rungs are in good condition and adequately spaced.	A	ſ.	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	۲	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	£	٢	Wore
Fulcrums/pivot points are free of pinch or crush hazards.	Г	Γ,	
Handholds are provided at each seating position.	Г	r	
nspector name, signature, and completion date			
lame: Janos Bicart	cr		Date:
<i>y</i>			

	0.75	D	on T
General Inspection	Pas	A THE PARTY	Problem / Solution
Playground area is free of litter and debris.	1	Г.	
Playground area is free of anthills/hazardous insects or toxic plants.	7	Г	
Playground area is free of holes and other tripping hazards.	4	<u>;</u> г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	Ţ	
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	Γ.	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	17	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	4	ŗ	
urfacing material is not compacting or deteriorating.	f	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	1		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	D'	Л	
rotective caps or plugs are not missing or damaged.	7	r	
Equipment is free of potential clothing entanglement hazards.	*	Г	
Juipment free of pinch and crush points or exposed moving parts.	\$	Г	
quipment is free of rust, rot, cracks, and splinters.	7		
Equipment is free of entrapments.	7	Г	
Equipment is safely anchored.	7	L L	
	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
wings are a safe distance from other playground equipment.	Г		Word
Swings are 24 inches apart.			
Edges of seats are smooth and free from	г	г	

Boyfront			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	П	
Equipped with platforms to facilitate access to the sitting position.	<i>F</i>	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	<i>I</i>	Γ.	
Average incline is less than 30 degrees.	X		
Exit regions are level.	1	Γ	
Metal slides are shaded to prevent overheating.	٠٢	F	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F	Г.	
Rope or chain ladders are anchored at both ends.	7	F	
Foot holds/rungs are in good condition and adequately spaced.	n	Γ	
	Pass	Fail	Problem / Solution
Seesaws	Газз	Leil	
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г а 55	["	
Seesaws are free of cracks, corrosion,			None
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	r"	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	F	r r	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r	r r	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	r r	Nane
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	r	r r	

George Adams	16 Jun 132		
General Inspection	Pas	s Fail	Problem / Solution
Playground area is free of litter and debris.	1	Г.	
Playground area is free of anthills/hazardous insects or toxic plants.	5	, ,	
Playground area is free of holes and other tripping hazards.	M	· r	•
Proper signage with rules, hours, and age- appropriate use is posted.	Г	. U	
Playground area is properly fenced.	Г	Г	N/IH
Self-latching gate works as designed.	r	Г	N/A
Surfacing	Pas	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	г	<i>F</i>	Thinning in spots
Surfacing material is free of glass, debris, or other foreign objects.	18:	Г	
urfacing material is not compacting or deteriorating.	г	at .	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	N.	
Proper drainage prevents water from forming puddles.	+		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	+	Г	
rotective caps or plugs are not missing or damaged.	B	r	
Equipment is free of potential clothing entanglement hazards.	A	Г	
Juipment free of pinch and crush points or exposed moving parts.	p-	Г	
quipment is free of rust, rot, cracks, and splinters.	Ar.	Г	
Equipment is free of entrapments.	7	Г	
Equipment is safely anchored.	0	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1		
wings are a safe distance from other playground equipment.	7	Г	. 1
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from	P	г	

George Adoms			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7	П	
Equipped with platforms to facilitate access to the sitting position.	ø	Γ	
Platforms are equipped with guardrails or equivalent protective equipment.	1	Γ·	
Average incline is less than 30 degrees.	ī	<u></u>	
Exit regions are level.	9 F	<u>г</u>	
Metal slides are shaded to prevent overheating.	Г	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	H	Γ.	
Rope or chain ladders are anchored at both ends.	*	F	
Foot holds/rungs are in good condition and adequately spaced.	<i>†</i>	Γ	
			Problem / Solution
Seesaws	Pass	Fail	(Toblein / Solder
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass /F	Fail	Troblem Coldino.
Seesaws are free of cracks, corrosion,			1 Toblem Column
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	/ -	Г	Troblem Cource.
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	<i>f</i> -	Г	Troblem Cource.
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	<i>f</i> -	Γ .	Troblem Council
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	<i>f</i> -	Γ .	Date:

1 .1 1	-	
VIII	e e	-M
VAL.		1111

General Inspection	Pass	Fail	l Problem / Solution
Playground area is free of litter and debris.	8	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	at .	г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	7	
Playground area is properly fenced.	Γ	Γ	
Self-latching gate works as designed.	Г	Г	
Surfacing	Pass	Fail	l Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	g.	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	/	Γ	
Surfacing material is not compacting or deteriorating.	F	Γ	
Rubber wear mats are used under high-traffic-use areas and are in good condition	Ro-	Г	
Proper drainage prevents water from forming puddles.	(st	г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	A-	Г	
Equipment is free from sharp points, corners, or edges.	1	Γ	•
Protective caps or plugs are not missing or damaged.	No.	Г	
Equipment is free of potential clothing entanglement hazards.	Г	Г	
Equipment free of pinch and crush points or exposed moving parts.	г	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	V	Some around Schools Minor
Equipment is free of entrapments.	Γ-	Γ	·
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	协	Г	
Swings are a safe distance from other playground equipment.	F	Γ	
Swings are 24 inches apart.	F	Ĺ.	
Edges of seats are smooth and free from obstructions.	¥	Γ	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	T	Г	

(To be completed monthly.)

Wilson

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	Γ	
Equipped with platforms to facilitate access to the sitting position.	9	Γ	
Platforms are equipped with guardrails or equivalent protective equipment.	,	-	
Average incline is less than 30 degrees.	г	r	
Exit regions are level.	1	٢٠	
Metal slides are shaded to prevent overheating.	r	٢	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	-	
Rope or chain ladders are anchored at both ends.	1	! "	
Foot holds/rungs are in good condition and adequately spaced.	1	Γ	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.		٢	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<u> </u>	Γ	WA
Fulcrums/pivot points are free of pinch or crush hazards.		۲	
Handholds are provided at each seating position.	r	٢	
Inspector name, signature, and completion date			
Name: Jamos B Corto	man.		Date:
Signature:			

	a Version		Cal and Oracl
Lighthouse	Pass	(Fali	Splash Pae
General Inspection	Pass	The second second	I FORCH A SOLUTION
Playground area is free of litter and debris.		Г.	
Playground area is free of anthills/hazardous insects or toxic plants.		A	1 tear in surface
Playground area is free of holes and other tripping hazards.	Г	7	11
Proper signage with rules, hours, and age- appropriate use is posted.	Γ.	7	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Γ,	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	Tean at bose of Climbing Riggs
Surfacing material under and around equipment is adequate depth (6-12 inches).	-	Г	
Surfacing material is free of glass, debris, or other foreign objects.	0	г	
urfacing material is not compacting or deteriorating.	J	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	at-	г	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	P	.г	
otective caps or plugs are not missing or damaged.	M	I-	
Equipment is free of potential clothing entanglement hazards.		٠. ٢	
Juipment free of pinch and crush points or exposed moving parts.	R	Г	
quipment is free of rust, rot, cracks, and splinters.	05	Γ.	
Equipment is free of entrapments.	0	Г	
Equipment is safely anchored.	F	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
wings are a safe distance from other playground equipment.	Г	Г	NAME
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from	г	г	

bighthouse	(· 5	plash pad
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	H	r	
Equipped with platforms to facilitate access to the sitting position.	<i>F</i>	Г:	
Platforms are equipped with guardrails or equivalent protective equipment.	K	Γ.	
Average incline is less than 30 degrees.	Γ	F	
Exit regions are level.	17	<u></u>	
Metal slides are shaded to prevent overheating.	Г	F	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	K	Г	
Rope or chain ladders are anchored at both ends.	D	F	
Foot holds/rungs are in good condition and adequately spaced.	Ø	Γ	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<u> </u>	Γ	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	_	٢	None
Fulcrums/pivot points are free of pinch or crush hazards.	۲	٢.	
Handholds are provided at each seating position.	Γ	Ĩ.	
nspector name, signature, and completion date			
lame: Jamas Cortor			Date:
ignature:			

LAI	•.		Boach Playground
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	#	· L	
Playground area is free of anthills/hazardous insects or toxic plants.	<i>t</i>	· F	
Playground area is free of holes and other tripping hazards.	P	. г	·
Proper signage with rules, hours, and age- appropriate use is posted.	Γ.	R	
Playground area is properly fenced.	Г		W/H
Self-latching gate works as designed.	J.r.	Г	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	+	Г	Sand base
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	·
urfacing material is not compacting or deteriorating.	y .	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	0	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	15	Г	
Equipment is free from sharp points, corners, or edges.	Ī	Г	
otective caps or plugs are not missing or damaged.	1	г	
Equipment is free of potential clothing entanglement hazards.	1	. г	
luipment free of pinch and crush points or exposed moving parts.	<i>8</i> -	Г	
quipment is free of rust, rot, cracks, and splinters.	1	г	
Equipment is free of entrapments.	Ø-	Г	
Equipment is safely anchored.	0-	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
wings are a safe distance from other playground equipment.	Г	Г	None
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from	г	г	

		Beach Playground)
Pass	Fail	Problem / Solution
7	r	
N.	Γ.	
P	Γ	
R		
J)	Г 	
旅	۲	
Pass	Fail	Problem / Solution
9	Г.	
*	r	
d	Γ	
Pass	Fail	Problem / Solution
Pass	Fail	Problem / Solution
	and the second of	Problem / Solution Wone
	Γ	
Г	r	
r	· · ·	
	Pass	Pass Fail Pass Fail Pass Fail

A STATE OF THE STA			om Playgreand
Lighthouse	Pass	A RESOURCE OF	Problem / Solution
General Inspection	THE SE	T CILL	1100.000, 550.000
Playground area is free of litter and debris. Playground area is free of anthills/hazardous insects		1	
or toxic plants.	7		
Playground area is free of holes and other tripping hazards.	4	r	
Proper signage with rules, hours, and age- appropriate use is posted.	got.	Г	
Playground area is properly fenced.	г	Г	W/A
Self-latching gate works as designed.	Γ.	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	P	Г	
Surfacing material is free of glass, debris, or other foreign objects.	Ŋ	r	
Surfacing material is not compacting or deteriorating.	7	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F	₩.	Mulch base
Proper drainage prevents water from forming puddles.	μĺ	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	4	л	
Protective caps or plugs are not missing or damaged.	#	۳	
Equipment is free of potential clothing entanglement hazards.	F	- r	
Equipment free of pinch and crush points or exposed moving parts.	A	г	
Equipment is free of rust, rot, cracks, and splinters.	1	_	
Equipment is free of entrapments.	7	г	
Equipment is safely anchored.	M	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	*	Г	ĮΙ
Swings are a safe distance from other playground equipment.	· -	٢	No Swings
Swings are 24 inches apart.	Г	Г	, 1
Edges of seats are smooth and free from	г	г	

Lighthouse		Pun	noom P	longround.
Slides	Pass	Fail	Proble	em / Solution
Slides are free of obstructions and protrusions.	#	г		
Equipped with platforms to facilitate access to the sitting position.	T/	n		
Platforms are equipped with guardrails or equivalent protective equipment.	dt	Г		
Average incline is less than 30 degrees.				
Exit regions are level.		<u>Г</u>		
Metal slides are shaded to prevent overheating.	Г	Γ		
Climbing Equipment	Pass	Fail	Proble	em / Solution
Hand grips are secured and do not rotate.	<i>f</i>	Γ.		
Rope or chain ladders are anchored at both ends.	Ť	Γ		
Foot holds/rungs are in good condition and adequately spaced.	A	Γ.		
	Pass	Fail	Proble	em / Solution
Seesaws	1 455			
Seesaws Seesaws Seesaws and other obvious structural defects.	Г азз	۳		
Seesaws are free of cracks, corrosion,			None	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact		Γ		
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	F	r r		
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	r r	r r		

Buttertly	(9-2)-1-3	(1) (h)	regione plane (15) in the construction of the property of the construction of the cons
General Inspection	Pas	s Fail	Problem / Solution
Playground area is free of litter and debris.	7	I.	Minor surface flows
Playground area is free of anthills/hazardous insects or toxic plants.	M	, 'Г	
Playground area is free of holes and other tripping hazards.	•	-	
Proper signage with rules, hours, and age- appropriate use is posted.	Г	K	
Playground area is properly fenced.	Г	Г	W/A
Self-latching gate works as designed.	r.	Г	N/A
Surfacing	Pas	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	P	Г	No holes, but surface is deleminating (spots)
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	,
urfacing material is not compacting or deteriorating.	pf	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	1	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	7	, г	
Equipment is free from sharp points, corners, or edges.	P	.5	
otective caps or plugs are not missing or damaged.	50	Г	
Equipment is free of potential clothing entanglement hazards.	•	· [
Juipment free of pinch and crush points or exposed moving parts.	F	Г	
quipment is free of rust, rot, cracks, and splinters.	1	г	
Equipment is free of entrapments.	pf.	Г	
Equipment is safely anchored.	þ	Г	The state of the s
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	₽ ^A	Г	
wings are a safe distance from other playground equipment.	7	Г	.1
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from	#	Г	

Butlently	M		
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	F	r:	
Equipped with platforms to facilitate access to the sitting position.	7	Γ:	
Platforms are equipped with guardrails or equivalent protective equipment.	7	Γ.	
Average incline is less than 30 degrees.	Γ		
Exit regions are level.	1	<u>آ</u>	
Metal slides are shaded to prevent overheating.	Г	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<i>F</i>	Γ.	
Rope or chain ladders are anchored at both ends.	<i>f</i>	[
Foot holds/rungs are in good condition and adequately spaced.		Γ	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	Γ	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	r	Nona
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			Nonz
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	F"	٦	Nona
and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	г	г г.	Nona

Ellanet Cro.	55 I I	167	
General Inspection		ss Fail	Problem / Solution
Playground area is free of litter and debris.	*	Г.	·
Playground area is free of anthills/hazardous insects or toxic plants.	S	1	Some soil crosion cracks in surface
Playground area is free of holes and other tripping hazards.	Г	1	cracks in surface
Proper signage with rules, hours, and age- appropriate use is posted.	5	. Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Γ.	Г	N/A
Surfacing	Pas	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	*	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	7	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	г	
urfacing material is not compacting or deteriorating.	P	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	A	Г	
Proper drainage prevents water from forming puddles.	id	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	K	Г	
Equipment is free from sharp points, corners, or edges.	1	.୮	
otective caps or plugs are not missing or damaged.	*	۳	
Equipment is free of potential clothing entanglement hazards.	+	Г	er .
juipment free of pinch and crush points or exposed moving parts.	1	Г	
quipment is free of rust, rot, cracks, and splinters.	1	г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	F	r	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	踊		
wings are a safe distance from other playground equipment.	4	Г	• 1
Swings are 24 inches apart.	7	F	
Edges of seats are smooth and free from	<i>f</i>	r	

Claret Crossina			and the second s
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	Г	
Equipped with platforms to facilitate access to the sitting position.	Ī	r.	
Platforms are equipped with guardrails or equivalent protective equipment.	D	Γ	
Average incline is less than 30 degrees.	Г	<i>T</i>	
Exit regions are level.	7	r	
Metal slides are shaded to prevent overheating.	۲	F	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	Đ	Γ.	
Rope or chain ladders are anchored at both ends.	A	F	
Foot holds/rungs are in good condition and adequately spaced.	if	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,	4005		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	4005	۲	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	4005	r	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position. Inspector name, signature, and completion date	t t	r -	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	t t	r -	Problem / Solution Date: 1- 16-24