## Port Lavaca Playground Safety Checklist (To be completed monthly.)

Eight house		10 6 10	Dann	00m	Plane	510und
General Inspection	Pa	ss Fail		Proble	in I Solution	
Playground area is free of litter and debris.	1	Г.	1 ( Mi	lford	White	2
Playground area is free of anthills/hazardous insects or toxic plants.	5. 7			•		
Playground area is free of holes and other tripping hazards.	N	Г				3
Proper signage with rules, hours, and age- appropriate use is posted.	1	. Г		((0	9	
Playground area is properly fenced.	Г	Г	N.	Z.H		
Self-latching gate works as designed.	Г	Г	N/		( ) to large with	
Surfacing	Pag	s Rail	y kina	Proble	m/Solution	<b>学可能等性过</b>
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	r	<			
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г				
Surfacing material is free of glass, debris, or other foreign objects.	3ª	Г	4			
rfacing material is not compacting or deteriorating.	1	Г				
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	7				
Proper drainage prevents water from forming puddles.	Ī,	Γ		· · · · · · · · · · · · · · · · · · ·		7
Eguipment Hazards	Pass	Fall	a projection designation	Problem	n/Solution	A DE LEGIT OF
Equipment is not damaged or vandalized.	DA	Г				<del></del>
Equipment is free from sharp points, corners, or edges.	F	<u>_</u>				
tective caps or plugs are not missing or damaged.	· f	Г				
Equipment is free of potential clothing entanglement hazards.	, A	· [	4			
ipment free of pinch and crush points or exposed moving parts.	¥	·r				
upment is free of rust, rot, cracks, and splinters.	参	Г		a		
Equipment is free of entrapments.	Ato	Г				
Equipment is safely anchored.	1	r l				
	Pass	Fail	egyant garage and a second	Problem.	/Solution	. Listanton de la lista
Hardware and chains are in good condition.	Г	Г				
ngs are a safe distance from other playground equipment.		. Г	W/	A		
Swings are 24 inches apart.	Г	Г				
Edges of seats are smooth and free from	г [	r		*		

A Comment of the Comm	THE RESERVE	MIRE	ubite.
Lighthonse Beach	Pass	Fail	Problem / Solution
Slides	و دون	П	
Slides are free of obstructions and protrusions.		•	
Equipped with platforms to facilitate access to the sitting position.	37	Г:	
Platforms are equipped with guardrails or equivalent protective equipment.	P	F·	
Average incline is less than 30 degrees.	Г	-	
Exit regions are level.	P	۲ 	
Metal slides are shaded to prevent overheating.	Г	F	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	6	Г.	
Rope or chain ladders are anchored at both ends.	8	Γ.	
Foot holds/rungs are in good condition and adequately spaced.	Ep.	۲ :	
The state of the s	<b>美工作系统</b>		Problem / Solution
Seesaws	Pass	Fáil	English Soldwor
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fall	ratublem control.
Seesaws are free of cracks, corrosion,	S (1) September 1		W/A
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	S (1) September 1	Γ	W/A
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	F	Γ	W/A
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	r r	Γ Γ	A/A

LH Beach			Beach Playmound
General Inspection	Pic	s Fai	Problem !/Solution
Playground area is free of litter and debris.	T	Г.	
Playground area is free of anthills/hazardous insects or toxic plants.	The state of the s	,	
Playground area is free of holes and other tripping hazards.	K	; · r	
Proper signage with rules, hours, and age- appropriate use is posted.	8'	Г	
Playground area is properly fenced.	Г	Г	W/H
Self-latching gate works as designed.	Γ.	Г	M/A
Surfacing .	Pas	s Fall	Problem // Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	8	Г	Sandbase
Surfacing material under and around equipment is adequate depth (6-12 inches).	柯	Г	
Surfacing material is free of glass, debris, or other foreign objects.	f	Г	(1)
rfacing material is not compacting or deteriorating.	17	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	
Proper drainage prevents water from forming puddles.	Г	Г	
Equipment Hazards	Pass	Fail	Problem//Solution
Equipment is not damaged or vandalized.	A.	Г	
Equipment is free from sharp points, corners, or edges.	<i>F</i>	Г	
ntective caps or plugs are not missing or damaged.	65	Γ.	
Equipment is free of potential clothing entanglement hazards.	, <b>/</b> -	·ŗ	
ipment free of pinch and crush points or exposed moving parts.	6	Γ	
uipment is free of rust, rot, cracks, and splinters.	16	Г	
Equipment is free of entrapments.	En .	Г	
Equipment is safely anchored.	6	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
ings are a safe distance from other playground equipment.		Г	· N/A
Swings are 24 inches apart.	Г	Γ	
Edges of seats are smooth and free from	г	r	

Lighthouse Reach			Beach Plancround
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		ŗ.	
Equipped with platforms to facilitate access to the sitting position.	T	Г	Sand buse
Platforms are equipped with guardrails or equivalent protective equipment.	N	L.	<b>\</b> (.
Average incline is less than 30 degrees.	Γ		l (
Exit regions are level.	John Committee of the C	Г —-	
Metal slides are shaded to prevent overheating.	Γ	A PARTY OF THE PARTY.	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	V	Г.	
Rope or chain ladders are anchored at both ends.	7	Γ	
Foot holds/rungs are in good condition and adequately spaced.	agr.	Γ	
Seesaws	Pass	Fail	Problem / Solution
SIGHTIME.	Carlow du		the state of the s
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Γ	
Seesaws are free of cracks, corrosion,	Carton da	i de la company	None
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	ŗ	Γ	None
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	F	Г	None
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	r	Г	None
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.  Handholds are provided at each seating position.	r	Г	None  Date: 2-12-24

# Poft Lavaca: Playground Safety Checklist (To be completed monthly.)

LH Beuch		(	Splash Pad Play
General Inspection	Par	s Fai	Problem / Solution
Playground area is free of litter and debris.	1	Г.	
Playground area is free of anthills/hazardous insects or toxic plants.	F	• г	
Playground area is free of holes and other tripping hazards.	Г	1	. One hole by climbing equip
Proper signage with rules, hours, and age- appropriate use is posted.	¥	. Г	
Playground area is properly fenced.			N/Fl
Self-latching gate works as designed.	Г	F T T T T T T T T T T T T T T T T T T T	
Surfacing :	Pas	s Fall	Problem/Solition
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	r	
Surfacing material under and around equipment is adequate depth (6-12 inches).	If	Г	
Surfacing material is free of glass, debris, or other foreign objects.	A.	Г	·
rfacing material is not compacting or deteriorating.	F	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	<b>F</b> .	Г	
Proper drainage prevents water from forming puddles.	J	F	
Equipment Hazards	Pass	Fall	Problem//Solution
Equipment is not damaged or vandalized.	V	Г	
Equipment is free from sharp points, corners, or edges.	1/2	Г	
ntective caps or plugs are not missing or damaged.	7	r	
Equipment is free of potential clothing entanglement hazards.	F	·	
ipment free of pinch and crush points or exposed moving parts.	Ø.	Г	
uipment is free of rust, rot, cracks, and splinters.	项		
Equipment is free of entrapments.	\$\$	Г	
Equipment is safely anchored.	\$#	r l	5 (Flew (Schiller)
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
rings are a safe distance from other playground equipment.	· _	Г	W/A
Swings are 24 inches apart.	Г	Γ	
Edges of seats are smooth and free from	r	г	

		4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Splash pad)
Lighthouse Beac	1	900 To 100 To 10	ACTUAL SECTION	Problem / Solution
Slides	Pass	Fail		- Rodanii sulaaan
Slides are free of obstructions and protrusions.	J.	Ľ.		
Equipped with platforms to facilitate access to the sitting position.	fr.	Γ:		
Platforms are equipped with guardrails or equivalent protective equipment.	F	r.		
Average incline is less than 30 degrees.	Γ	<i></i>		
Exit regions are level.	NT-	٢		
Metal slides are shaded to prevent overheating.	Γ	F CANADA TO SE	na saya a wasa	Tech-Hos
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	#	Γ.		
Rope or chain ladders are anchored at both ends.	Ø.	Γ.		
Foot holds/rungs are in good condition and adequately spaced.	A.	Г		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	٢		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	Γ		WA
Fulcrums/pivot points are free of pinch or crush hazards.	Г	٢.		
Handholds are provided at each seating position.	Γ	<u> </u>		
spector name, signature, and completion date				
me: Janes B Cartac				Date: 2-12-24
•				

Butterfly Part	•		
General lispection	Pas	s Fai	Problem / Solution
Playground area is free of litter and debris.	1	F.	1 1 1 1 1 1 1 1 1
Playground area is free of anthills/hazardous insects or toxic plants.	<b>V</b>	1	Treated all anthills
Playground area is free of holes and other tripping hazards.	7	· r	
Proper signage with rules, hours, and age- appropriate use is posted.	ľ	. Г	
Playground area is properly fenced.	Г	Г	10/4
Self-latching gate works as designed.	Γ.	Г	
Surfacing	25,000	s Fall	Problem/Solution:
artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<i>p</i> *	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	Г	
Surfacing material is free of glass, debris, or other foreign objects.	F	Г	
rfacing material is not compacting or deteriorating.	1	[	·
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F	Г	
Proper drainage prevents water from forming puddles.	1		
Eguipment Hazards	Pass	Fail	Problem/Solution
Equipment is not damaged or vandalized.	V	Γ	
Equipment is free from sharp points, corners, or edges.	*	,,	·
tective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	. /-	. [	•
ipment free of pinch and crush points or exposed moving parts.	f	Г	Same around helts (Sufface)
uipment is free of rust, rot, cracks, and splinters.	Γ	A	Some around botts (Sulface)
Equipment is free of entrapments.	F	Г	·
Equipment is safely anchored.	A	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Ø	Г	
ings are a safe distance from other playground equipment.	V	Г	. 1
Swings are 24 inches apart.	<i>J</i>	F	
Edges of seats are smooth and free from	a l	r-	

Bufferfly			Plajground
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	Γ.	
Equipped with platforms to facilitate access to the sitting position.	Tr.	Γ:	
Platforms are equipped with guardrails or equivalent protective equipment.	F	۲۰	
Average incline is less than 30 degrees.	Γ	<i></i>	
Exit regions are level.	F	Γ	
Metal slides are shaded to prevent overheating.	Γ	Γ	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	<i>t</i> -	<u>۲</u> .	
Rope or chain ladders are anchored at both ends.	F	ř	
Foot holds/rungs are in good condition and adequately spaced.	7		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	٢	
quipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	٢	Г	Wore
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	Γ.	
Handholds are provided at each seating position.	Γ	Γ	
pector name, signature, and completion date			
ne: Janes B Carter  nature: AB M			Date: 2 - R2 - 2 +

Claret Cross	100	, )	
General Inspection	Pas	1300	Problem / Solution
Playground area is free of litter and debris.	1	F.	$\mathcal{L}(\mathcal{L})$
Playground area is free of anthills/hazardous insects or toxic plants.	Т	<i>f</i>	Treaded HU Return
Playground area is free of holes and other tripping hazards.	1	: r	
Proper signage with rules, hours, and age- appropriate use is posted.	I.	.   г	1/11
Playground area is properly fenced.			N/+
Self-latching gate works as designed.	L.	Г (1102-22	// //
Surfacing	Pas		Paroptauly Sometime
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	Á	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	Γ	
Surfacing material is free of glass, debris, or other foreign objects.	8-	Г	
ırfacing material is not compacting or deteriorating.	1	r	·
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	15	Г	
Proper drainage prevents water from forming puddles.	<i>f</i>	T	Techtical (Control of the Control of
Equipment Hazards	Pass	Fail	Problem#Solution
Equipment is not damaged or vandalized.	34	Г	
Equipment is free from sharp points, corners, or edges.	办	,г	
otective caps or plugs are not missing or damaged.	75	F	
Equipment is free of potential clothing entanglement hazards.	*	· [	
uipment free of pinch and crush points or exposed moving parts.	ST .	Г	
juipment is free of rust, rot, cracks, and splinters.	50h	г	
Equipment is free of entrapments.	A.	Г	
Equipment is safely anchored.	4	C C	During Shiften
Swings	Pass	Fail	Problem/Solution
Hardware and chains are in good condition.	1		
rings are a safe distance from other playground equipment.	F	г	. 1
Swings are 24 inches apart.	10	Γ	
Edges of seats are smooth and free from	¥	-	

## Port Lavaca Playground Safety Checklist (Lo be completed monthly.)

The state of the s	INDICATE SILVERS	and the state of t	
Claret Crossing	Pass	Fail	Problem / Solution
Slides	ress g	r-all	
Slides are free of obstructions and protrusions.		1.	
Equipped with platforms to facilitate access to the sitting position.	1	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	1	r· ·	
Average incline is less than 30 degrees.	7		
Exit regions are level.	F	Г ————————	
Metal slides are shaded to prevent overheating.	A		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	J.	Г.	
Rope or chain ladders are anchored at both ends.	F	F	
Foot holds/rungs are in good condition and adequately spaced.	F	۲ ·	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	7	Г	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	٢	
Fulcrums/pivot points are free of pinch or crush hazards.	7	ſ.	
Handholds are provided at each seating position.	F	Γ	
spector name, signature, and completion date			
me: Jance B Cartor nature: 1 B Et			Date: 212-24

Baytront	AND ENTRY OF THE		Plun ground
General Inspection	Ph	Es Fe	Problem / Solution
Playground area is free of litter and debris.	J.	Г.	(Interest of the second of the
Playground area is free of anthills/hazardous insect			
or toxic plants.  Playground area is free of holes and other tripping hazards.	ji	-   -	
Proper signage with rules, hours, and age- appropriate use is posted.	5	. г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Г	. Г	NH
Surfacing	Pag	s Fa	Problem / Solution
rpproved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	, <i>f</i>	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	F	г	·
rfacing material is not compacting or deteriorating.	Ā	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	I	-	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	V	Γ	
Equipment is free from sharp points, corners, or edges.	T	,Γ	
tective caps or plugs are not missing or damaged.	8	г	
Equipment is free of potential clothing entanglement hazards.	. 1	· ŗ	
ipment free of pinch and crush points or exposed moving parts.	ST	Г	
aipment is free of rust, rot, cracks, and splinters.	D	г	
Equipment is free of entrapments.	Ā	ŗ	
Equipment is safely anchored.	A .	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
ngs are a safe distance from other playground equipment.		Г	· N/A
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from	Г		

Buntagnt		A STATE OF THE STA	Plancing
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	Ţ.	r:	
Equipped with platforms to facilitate access to the sitting position.	T/A	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	7	Γ·	
Average incline is less than 30 degrees.	Γ		
Exit regions are level.	P	Γ	
Metal slides are shaded to prevent overheating.	To the second second	F	C-L-Han
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	4	Γ.	
Rope or chain ladders are anchored at both ends.	Æ.	F	
Foot holds/rungs are in good condition and adequately spaced.	P	F	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	٢	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	Г	W/A
Fulcrums/pivot points are free of pinch or crush hazards.	Г	Γ.	
Handholds are provided at each seating position.		ī	
spector name, signature, and completion date			
me: Jams B Carter  nature: 93 th			

George Hdams	119-1-1		
General Inspection 4	W Pa	ss Fa	I ANDIEND POPERATE
Playground area is free of litter and debris.	*	ī.	
Playground area is free of anthills/hazardous insects or toxic plants.	7	, · r	
Playground area is free of holes and other tripping hazards.	F4	, : r	
Proper signage with rules, hours, and age- appropriate use is posted.	P	. г	4//4
Playground area is properly fenced.	Г	Г	NIA
Self-latching gate works as designed.	r	г_	NIA
Surfacing	Pag	s Fai	Problem / Solution
rpproved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	F	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	6	Г	·
rfacing material is not compacting or deteriorating.	o	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	1	
Proper drainage prevents water from forming puddles.	g.		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	7	Г	
Equipment is free from sharp points, corners, or edges.	1	,Г	
tective caps or plugs are not missing or damaged.	A	Г	
Equipment is free of potential clothing entanglement hazards.	á <del>t</del>	· . [	
ipment free of pinch and crush points or exposed moving parts.	矿	Г	(4)
ipment is free of rust, rot, cracks, and splinters.	Г	x	Rust around bolt bases (6)
Equipment is free of entrapments.	中	Г	
Equipment is safely anchored.	*	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	F	Г	New Swag set
ngs are a.safe distance from other playground equipment.	7	г	is complete
Swings are 24 inches apart.	Ī	Г	V-g 1
Edges of seats are smooth and free from	<b>F</b>	· _	

George Adoms			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7	Γ:	
Equipped with platforms to facilitate access to the sitting position.	7	Γ:	
Platforms are equipped with guardrails or equivalent protective equipment.	Di	ŗ.	
Average incline is less than 30 degrees.	Γ		
Exit regions are level.	gar.	Γ	
Metal slides are shaded to prevent overheating.	Γ	F	What the first the second seco
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F	Γ.	
Rope or chain ladders are anchored at both ends.	1	:	
Foot holds/rungs are in good condition and adequately spaced.	A-	Γ	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<i>F</i>	Г	
quipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<i>t</i>	Г	
Fulcrums/pivot points are free of pinch or crush hazards.	f	Γ.	
Handholds are provided at each seating position.	M	٢	
pector name, signature, and completion date			
me: James B Carte	2 (		Date: 2-12-24

Wilson Field	3 - 10 - 10 - 10 - 10 - 10 - 10 - 10 - 1		
General Inspection	Pa	is Fe	in Problem / Solution
Playground area is free of litter and debris.	1	Г.	
Playground area is free of anthills/hazardous insect or toxic plants.	S. J	, · r	
Playground area is free of holes and other tripping hazards.	Ŋ	/ · · · ·	
Proper signage with rules, hours, and age- appropriate use is posted.	13	ý. r	
Playground area is properly fenced.	Г		N/A
Self-latching gate works as designed.	г		N/A
Surfacing	Pa	ss Fa	Problem/Solution
Approved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	· AF	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	c.jpo	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
rfacing material is not compacting or deteriorating.	ē.	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	q <del>4</del>	Г	
Proper drainage prevents water from forming puddles.	Á		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	y	.Г	
tective caps or plugs are not missing or damaged.	B	Г	
Equipment is free of potential clothing entanglement hazards.	7	ŀ ŗ	
ipment free of pinch and crush points or exposed moving parts.	M	Г	
lipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	8	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	St.	Г	
ngs are a safe distance from other playground equipment.	*	Г	V-1
Swings are 24 inches apart.	F	Г	
Edges of seats are smooth and free from	1	-	

Wilson Field			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	Ti.	
Equipped with platforms to facilitate access to the sitting position.	J.	Γ:	
latforms are equipped with guardrails or equivalent protective equipment.	7	Г.	
Average incline is less than 30 degrees.	Г		
Exit regions are level.	1	<u> </u>	
Metal slides are shaded to prevent overheating.	r mauring	Γ	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	r.	
Rope or chain ladders are anchored at both ends.	17	Γ	
Foot holds/rungs are in good condition and adequately spaced.	J	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ		
quipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	г	MA
Fulcrums/pivot points are free of pinch or crush hazards.	Г	۳.	
Handholds are provided at each seating position.	Г	Γ	
pector name, signature, and completion date			
me: James B Carter  nature: 18 CA	-		Date: 2 42 - 24
<i>y</i>			

## Port Lavaca Playground Safety Checklist (To be completed monthly.)

	14.2		Paullion
City Pont			Problem / Solution
General linspection   1	Life	LES   11/10	
Playground area is free of litter and debris.	1	т.	
Playground area is free of anthills/hazardous insect or toxic plants.		- 1	
Playground area is free of holes and other tripping hazards.	1	² : r	
Proper signage with rules, hours, and age- appropriate use is posted.	15	ř. [	- / 4
Playground area is properly fenced.	Г	- г	- N/A
Self-latching gate works as designed.	Г	Г	N/A
Surfacing	Pa	ss   Fa	H Problem/Solution
pproved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	, A	Г	-
Surfacing material under and around equipment is adequate depth (6-12 inches).	F	Г	
Surfacing material is free of glass, debris, or other foreign objects.	Ū	Г	·
facing material is not compacting or deteriorating.	J	Γ	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	A	Г	
Proper drainage prevents water from forming puddles.	5		
Equipment Hazards	Pas	s Fall	Rroblem//Solution
Equipment is not damaged or vandalized.	A	Г	
Equipment is free from sharp points, corners, or edges.	F	,Г	
tective caps or plugs are not missing or damaged.	7	Γ_	
Equipment is free of potential clothing entanglement hazards.	. *		
ipment free of pinch and crush points or exposed moving parts.	¥	Г	
ipment is free of rust, rot, cracks, and splinters.	*	Г	
Equipment is free of entrapments.	F	Г	
Equipment is safely anchored.	逻	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	Г	
ngs are a safe distance from other playground equipment.	*	Г	. 1
Swings are 24 inches apart.	F	Г	
Edges of seats are smooth and free from	gi-	-	

		or other as and	Pavillion
Cito Park		Fail	Problem / Solution
Sildes	Pass		ji i casicini)
Slides are free of obstructions and protrusions.	J.	П	
Equipped with platforms to facilitate access to the sitting position.	7	Г.	
Platforms are equipped with guardrails or equivalent protective equipment.	7	Г-	
Average incline is less than 30 degrees.	1	<u> </u>	
Exit regions are level.	7	ŗ.	
Metal slides are shaded to prevent overheating.	Г	Γ	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	色	Γ.	
Rope or chain ladders are anchored at both ends.	8	Γ	
Foot holds/rungs are in good condition and adequately spaced.	AT	Γ	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	٣	
quipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	۲	Γ	N/X
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	۲.	
Handholds are provided at each seating position.	Г	ī .	
pector name, signature, and completion date			
me: James B Carte, nature:			Date: 2-12-24
V			

Cido Part			Ashles Field
General Inspection	Pa	ss Fai	Problem / Solution
Playground area is free of litter and debris.	7	7 F.	
Playground area is free of anthills/hazardous insect or toxic plants.	S. 7		
Playground area is free of holes and other tripping hazards.	Į	: r	
Proper signage with rules, hours, and age- appropriate use is posted.	1	. Г	
Playground area is properly fenced.	1	Г	
Self-latching gate works as designed.	T	. Г	
Surfacing	Pa	s Fall	Problem / Solution
Approved surfacing material is used (i.e. solid rubber artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	, 	Г	·
Surfacing material under and around equipment is adequate depth (6-12 inches).	f	Г	
Surfacing material is free of glass, debris, or other foreign objects.	7	Г	
rfacing material is not compacting or deteriorating.	荻	Г	·
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	F	Г	
Proper drainage prevents water from forming puddles.	1		
<b>E</b> quipment Hazards	Pass	Fall	Problem / Solution
Equipment is not damaged or vandalized.	7	Γ	·
Equipment is free from sharp points, corners, or edges.	V	Г.	
tective caps or plugs are not missing or damaged.	FF.		
Equipment is free of potential clothing entanglement hazards.	. F	· [	
ipment free of pinch and crush points or exposed moving parts.	F	Г	
ripment is free of rust, rot, cracks, and splinters.	1		
Equipment is free of entrapments.	f	Г	
Equipment is safely anchored.	1	r l	Send of the send o
Swings	Pass	1	Problem / Solution
Hardware and chains are in good condition.	Г		
ngs are a safe distance from other playground equipment.	· _	Г	" None
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from	-	- J	

- City Part	laste camara	on the state of	Ashlen	Field
Sildes	Pass	Fail		/ Solution
Slides are free of obstructions and protrusions.	J.	Ţ:	Cod ( a cody pa V r Epipera Code)	
Equipped with platforms to facilitate access to the sitting position.	f	П		
Platforms are equipped with guardrails or equivalent protective equipment.	7	Г.		
Average incline is less than 30 degrees.	Γ	F		
Exit regions are level.	<u> </u>	<u>г</u>		
Metal slides are shaded to prevent overheating.	Γ	Γ		
Climbing Equipment	Pass	Fail	Problem	Solution
Hand grips are secured and do not rotate.	7	<u>r.</u>		
Rope or chain ladders are anchored at both ends.	*	<u> </u>		
Foot holds/rungs are in good condition and adequately spaced.	F	Г		
Seesiws	Pass	Fail	Problem /	Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	Γ		
quipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	<u></u>	г	WA	
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	Γ.		
Handholds are provided at each seating position.	Г	Ĭ"		
pector name, signature, and completion date				
me: James B. Cartæ nature: JB DA				2-24
/				