General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Г	
Playground area is free of anthills/hazardous insects or toxic plants.	-	F	
Playground area is free of holes and other tripping hazards.	7/	г	
Proper signage with rules, hours, and age- appropriate use is posted.	/	Г	
Playground area is properly fenced.	Г	Г	1/A
Self-latching gate works as designed.	Г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	13/		
Surfacing material under and around equipment is adequate depth (6-12 inches).	/	Г	
Surfacing material is free of glass, debris, or other foreign objects.		-	
Surfacing material is not compacting or deteriorating.	/		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	г	1/4
Proper drainage prevents water from forming puddles.		г	* 50
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	/	Γ	
Equipment is free from sharp points, corners, or edges.	Г	/	just spots sharp points/resustase out pa
Protective caps or plugs are not missing or damaged.	/	1	To the same of the
Equipment is free of potential clothing entanglement hazards.	~	Γ	
Equipment free of pinch and crush points or exposed moving parts.		г	
Equipment is free of rust, rot, cracks, and splinters.	r	/	rust / Kesurface and paint
Equipment is free of entrapments.		Г	The property of the property o
Equipment is safely anchored.		Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	~	Γ	
Swings are a safe distance from other playground equipment.	г	.r	AlA
Swings are 24 inches apart.	Г	г	NA
Edges of seats are smooth and free from obstructions.	Г	г	n lA
Adequate depths of surfacing material extend out a			



flo be completed monthly.)

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	-	r	
Equipped with platforms to facilitate access to the sitting position.	r-/	۲	
Platforms are equipped with guardrails or equivalent protective equipment.	5/	L_	
Average incline is less than 30 degrees.	<b>S</b>	٢	
Exit regions are level.	6	٦	
Metal slides are shaded to prevent overheating:	٦	۲	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		F	
Rope or chain ladders are anchored at both ends.		r	
Foot holds/rungs are in good condition and adequately spaced.	F-/	r" .	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	٢	- NA	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F-	\ \/A	
Fulcrums/pivot points are free of pinch or crush hazards.	Γ	5 NH	
Handholds are provided at each seating position.	Г	" N/A	
Inspector name, signature, and completion date			
Name: Jose Villalone			
Signature: La Zalana			Date: 3/26/25

Light have Isobish and	··		
General Inspection	Pass	Fai	Durithma (Call 2)
Playground area is free of litter and debris.	, dss	. Lan	Problem / Solution
Playground area is free of anthills/hazardous insects or toxic plants.		· ·	
Playground area is free of holes and other tripping hazards.	+-	F-	Hole in phorefloor freplan
Proper signage with rules, hours, and age- appropriate use is posted.		ī	The togstr floor freshon
Playground area is properly fenced.	F"	Г	114
Self-latching gate works as designed.		Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	F	<i>=</i> _	Wher flow has a hole / topher
Surfacing material under and around equipment is adequate depth (6-12 inches).	150	Г	105th floor has a ville / 14 min
Surfacing material is free of glass, debris, or other foreign objects.	-	Г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	5	r	
Proper drainage prevents water from forming puddles.	-	F	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Γ	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	7	Г	
Equipment is free of potential clothing entanglement hazards.	F/	r	.a
Equipment free of pinch and crush points or exposed moving parts.	:_/	Г	
Equipment is free of rust, rot, cracks, and splinters.	г	-	fiften 1 Goods / 125 uster and Paint
Equipment is free of entrapments.	5	٢	10): 400 / 100 100 - 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 /
Equipment is safely anchored.	5	ŕ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	r-	٦	n/A
Swings are a safe distance from other playground equipment.	۲	r	NIA
Swings are 24 inches apart.	Г	F	nla
Edges of seats are smooth and free from obstructions.	Г	۲	n/A
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	r	ŗ	NA

Slides	Pass	Fail		Problem / Solution
Slides are free of obstructions and protrusions.	=	۲		
Equipped with platforms to facilitate access to the sitting position.	F	r		
Platforms are equipped with guardrails or equivalent protective equipment.	-	r		
Average incline is less than 30 degrees.	Г	Г	NA	
Exit regions are level.	=======================================	٢	<del>*                                    </del>	
Metal slides are shaded to prevent overheating.	г	r"	NA	
Climbing Equipment	Pass	Fail		Problem / Solution
Hand grips are secured and do not rotate.	<b>5</b> /	٣		
Rope or chain ladders are anchored at both ends.		г		
Foot holds/rungs are in good condition and adequately spaced.	<i></i>	Г		
Seesaws	Pass	Fail		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	٦	ſ-	n/A	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	r-	n la	
Fulcrums/pivot points are free of pinch or crush hazards.	r		NIA	
Handholds are provided at each seating position.	۲		1/1	
Inspector name, signature, and completion date			7	
Name: La Vollan				,
Signature: Jose VIllalan				Date: 3/26/25

Light house beach / beach side		_,	
General Inspection	Pass	Fai	Problem / Solution
Playground area is free of litter and debris.	9-	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	F3-/	Г	
Playground area is free of holes and other tripping hazards.		۲	
Proper signage with rules, hours, and age- appropriate use is posted.	-		
Playground area is properly fenced.	T -	Г	1/4
Self-latching gate works as designed.	Г	Г	114
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	P-	۲	
Surfacing material under and around equipment is adequate depth (6-12 inches).		٦	
Surfacing material is free of glass, debris, or other foreign objects.	F	Ĺ.	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	n la
Proper drainage prevents water from forming puddles.	-	  -	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	- F	-	
Equipment is free from sharp points, corners, or edges.	L	5	stop point-rust /residen and point
Protective caps or plugs are not missing or damaged.	F		July 1011-105 / External ferial
Equipment is free of potential clothing entanglement hazards.	-	Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	F	Post presentace & print
Equipment is free of entrapments.	<u></u>	Г	The priace o pains
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	r	Г	1.10
Swings are a safe distance from other playground equipment.	Г	Г	n la
Swings are 24 inches apart.	Г	r	in let
Edges of seats are smooth and free from obstructions.		Г	n/a
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	r-	Γ	nlA

Slides	Pass	Fail		Problem / Solution	
Slides are free of obstructions and protrusions.		D		and and the contract of the co	
Equipped with platforms to facilitate access to the sitting position.					
Platforms are equipped with guardrails or equivalent protective equipment.		0			
Average incline is less than 30 degrees.		D	N/A		
Exit regions are level.			,		
Metal slides are shaded to prevent overheating.		D	NA		5.15
Climbing Equipment	Pass	Fail		Problem / Solution	
Hand grips are secured and do not rotate.		П		and the second s	
Rope or chain ladders are anchored at both ends.	~	П			
Foot holds/rungs are in good condition and adequately spaced.	/	П			
Seesaws	Pass	Fail		Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Γ	П	1/4		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	Г	n/m		
Fulcrums/pivot points are free of pinch or crush hazards.	Г	О	nla		
Handholds are provided at each seating position.	Г		MA		
Inspector name, signature, and completion date					
Name: Jose Villalan Signature: La Villa				Date: 3/26/25	1

Butter All General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1 435	r all	Trobletti Solution
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.	~	Г	
Proper signage with rules, hours, and age- appropriate use is posted.			
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	г	Γ	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	г		MIRIO WASTER / replace Floor
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-	Г	
Proper drainage prevents water from forming puddles.		Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	Г		Slove points + rest /tephon
Protective caps or plugs are not missing or damaged.	Per	Γ	7-17
Equipment is free of potential clothing entanglement hazards.	Г	F#	entanglement / revolue
Equipment free of pinch and crush points or exposed moving parts.	<b>5</b>	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г		lust everywhere / replace
Equipment is free of entrapments.	-	Γ	7. /
Equipment is safely anchored.	-	Γ	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	-	Г	
Swings are a safe distance from other playground equipment.		Г	· 9
Swings are 24 inches apart.		Г	
Edges of seats are smooth and free from obstructions.	-	Γ.	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		Г	

National Action in the Control of th									
Slides Slides	Pass	Fail		Pr	oblem /	Solutio			
Slides are free of obstructions and protrusions.	1	F			obleiil /	Solutio			
Equipped with platforms to facilitate access to the sitting position.	1	Г						***************************************	
Platforms are equipped with guardrails or equivalent protective equipment.	/	Г						***************************************	
Average incline is less than 30 degrees.	Ē-	Γ							
Exit regions are level.	1	£~							
Metal slides are shaded to prevent overheating.	r	Г		***************************************					
Climbing Equipment	Pass	Fail		Pr.	oblom /	Solution			
Hand grips are secured and do not rotate.	1	r			JuleIII I	Solution			
Rope or chain ladders are anchored at both ends.	/	Г							
Foot holds/rungs are in good condition and adequately spaced.	۲-		hst /	W -		, ,	' /-		
Seesaws - Property - Commencer	Pass	Fail	Name of the last	Pro	phlem /	Solution	142	he di nega	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Г.,			DICITI'	Solution			
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г								
Fulcrums/pivot points are free of pinch or crush hazards.	į –	- 19	14						
Handholds are provided at each seating position.	۲	" n/	1	ddon yw yn i'r rhydd					-
Inspector name, signature, and completion date					-				
Name: Jose Villalan				Date:	3/2/	1/2	~		
Signature:					-	1			
		7							

Claret Crossing			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	/	Г	Control to the second s
Playground area is free of anthills/hazardous insects or toxic plants.	1	Г	
Playground area is free of holes and other tripping hazards.	/	г	
Proper signage with rules, hours, and age- appropriate use is posted.		Г	
Playground area is properly fenced.	Г	Г	n p4
Self-latching gate works as designed.	Γ	Г	n/A
Surfacing Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.	/	Г	
Surfacing material is not compacting or deteriorating.	~	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	Г	
Proper drainage prevents water from forming puddles.	-	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Γ	
Equipment is free from sharp points, corners, or edges.	г	-	shap paints - rust / resurface of paint
Protective caps or plugs are not missing or damaged.		r	, , , ,
Equipment is free of potential clothing entanglement hazards.	~	Г	
Equipment free of pinch and crush points or exposed moving parts.	-	Е	
Equipment is free of rust, rot, cracks, and splinters.	г		Just / he surface + paint
Equipment is free of entrapments.	-	Г	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	V	Γ	4 ×
Swings are 24 inches apart.	1	Г	
Edges of seats are smooth and free from obstructions.	1	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	/	Γ	

Labe completed monthly

Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		F 260	
Equipped with platforms to facilitate access to the sitting position.	4	r	
Platforms are equipped with guardrails or equivalent protective equipment.	/	۲	
Average incline is less than 30 degrees.	r	5 n/A	
Exit regions are level.	·/		
Metal slides are shaded to prevent overheating.	Г	T N/A	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F	Γ,	. Tobiciny Solution
Rope or chain ladders are anchored at both ends.	-	r	
Foot holds/rungs are in good condition and adequately spaced.	<b>√</b>	r-	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	F-/	<b>!</b>	, codem soluțion
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	/	٦	
Fulcrums/pivot points are free of pinch or crush hazards.		r	
Handholds are provided at each seating position.		r	
Inspector name, signature, and completion date			
Name: Jose Wille for Signature: Style 1	-		Date: 3/26/25

City Pork	(		ed Horiting.)
General Inspection	Pas	s, Fai	Position / C. J. C.
Playground area is free of litter and debris.		, r	Problem / Solution
Playground area is free of anthills/hazardous insects or toxic plants.	5 1	-	Just weeds around playaro
Playground area is free of holes and other tripping hazards.		Г	JUST WEEDS around playgro
Proper signage with rules, hours, and age- appropriate use is posted.	/	-	
Playground area is properly fenced.	7	Ε	N/A
Self-latching gate works as designed.	F	F	W/A
Surfacing	P'as:	s Fail	
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	-	, Solderon
Surfacing material under and around equipment is adequate depth (6-12 inches).	1		
Surfacing material is free of glass, debris, or other foreign objects.	-	F	
Surfacing material is not compacting or deteriorating.	-	i.	N/A
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	٦	F	A)/A
Proper drainage prevents water from forming puddles.	-/	Г	All A
Equipment Hazards	Pass	<sup>*</sup> Fāil	Problem / Solution
Equipment is not damaged or vandalized.	7	ī	and the second s
Equipment is free from sharp points, corners, or edges.		r	
rotective caps or plugs are not missing or damaged.	Γ"	Ŀ	N/A
Equipment is free of potential clothing entanglement hazards.	7	۲	N/A
quipment free of pinch and crush points or exposed moving parts.	7	Г	
Equipment is free of rust, rot, cracks, and splinters.			Surface grust
Equipment is free of entrapments.	7	7.	Direct Frast
Equipment is safely anchored.	п		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	ŗŽ	Г	. Tobletti Joiddol
Swings are a safe distance from other playground equipment.	-	Г	
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from obstructions.	1	г	
lequate depths of surfacing material extend out a inimum distance of twice the height of the swing.	7	г	

. To be completed monthly,

City Dark	<del>.</del> -	र्टी देश को जुक्ता अंध्येकी कारी	and the state of t
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	I.	<b>∠</b> □	r roblem / Solution
Equipped with platforms to facilitate access to the sitting position.			
Platforms are equipped with guardrails or equivalent protective equipment.		ř	*
Average incline is less than 30 degrees.	Г	[ N/A	
Exit regions are level.	-	70/14	
Metal slides are shaded to prevent overheating.	٦	- Plastic	Clidag
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	-	/ [	1 Tobletti / Soluciosi
Rope or chain ladders are anchored at both ends.	X	ILA	
Foot holds/rungs are in good condition and adequately spaced.		<i></i>	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	F		
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		r NIA	
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact			
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch			
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.			
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.  Handholds are provided at each seating position.			Date: 3/26/25

Pass	Fa		Problem / Solution
	L L		Problem / Solution
Г	-		
Г			
Г	Γ		
Г	<del> </del> -		
Г	ī	<del> </del>	~
		A VA	
	-	<del>                                      </del>	
ass	Fail		Problem / Solution
,	-		, Toblem / Solution
	r	A1/A	
		/V/ <i>[</i> 5	
7	F.		
r		ν/Δ	
-	Г		
ass.	'Fail	10/ (1	Problem / Solution
			1 / Objects / Solution
	Γ		
		NI/A	
1	, r	N/A	
1	r		
-+		2001.00	10.01
. +		1 4 11 4 11 11 11	1024
_	-		
ss			District Color
		11/3	Problem / Solution
+	-		
-	Г		
+	-	N/4	
+	-	N/ A N/ A	
	T SSS	Fail F F F F F F F F F F F F F F F F F F F	F Fail F N/A

Slides Pass Fail Problem / Solution  Slides are free of obstructions and protrusions.  Equipped with platforms to facilitate access to the sitting position.  Platforms are equipped with guardrails or equivalent protective equipment.  Average incline is less than 30 degrees:  Exit regions are level.  Metal slides are shaded to prevent overheating.  Climbing Equipment  Pass Fail Problem / Solution  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail Problem / Solution  Problem / Solution  Pass Fail Problem / Solution
Slides are free of obstructions and protrusions.  Equipped with platforms to facilitate access to the sitting position.  Platforms are equipped with guardrails or equivalent protective equipment.  Average incline is less than 30 degrees.  Exit regions are level.  Metal slides are shaded to prevent overheating.  Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
The sitting position.  Platforms are equipped with guardrails or equivalent protective equipment.  Average incline is less than 30 degrees.  Exit regions are level.  Metal slides are shaded to prevent overheating.  Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Average incline is less than 30 degrees:  Exit regions are level.  Metal slides are shaded to prevent overheating:  Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Seesaws are free of cracks, corrosion, and other obvious structural defects.  Pass Fail  Problem / Solution  Problem / Solution
Exit regions are level.  Metal slides are shaded to prevent overheating.  Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Seesaws  Pass Fail  Problem / Solution  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Metal slides are shaded to prevent overheating.  Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Climbing Equipment  Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Problem / Solution  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Hand grips are secured and do not rotate.  Rope or chain ladders are anchored at both ends.  Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Foot holds/rungs are in good condition and adequately spaced.  Seesaws  Pass Fail  Problem / Solution  Seesaws are free of cracks, corrosion, and other obvious structural defects.
Seesaws are free of cracks, corrosion, and other obvious structural defects.
Seesaws are free of cracks, corrosion, and other obvious structural defects.
Fauinment is provided with a six
equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.
Fulcrums/pivot points are free of pinch or crush hazards.
Handholds are provided at each seating position.
Inspector name, signature, and completion date
Inspector name, signature, and completion date  Name: Day (a Cox pro  Date: 3/26/25

City Dark By Anshy file	eds		
General Inspection	Pas	s. Fa	il Problem / Solution
Playground area is free of litter and debris.		Г	
Playground area is free of anthilis/hazardous insects or toxic plants.	-	-	
Playground area is free of holes and other tripping hazards.		-	
Proper signage with rules, hours, and age- appropriate use is posted.	1		_
Playground area is properly fenced.		-	NA
Self-latching gate works as designed.	r	F	1)/A
Surfacing	Pas	s Fa	
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<sub>1</sub> ⁄	F	. Toblein 2 Solderon
Surfacing material under and around equipment is adequate depth (6-12 inches).	-/		
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	1		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	/	-	
Proper drainage prevents water from forming puddles.		F	254
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	7		Coult as to -
Equipment is free from sharp points, corners, or edges.	,	٦	Small paint Job
rotective caps or plugs are not missing or damaged.	-,X	Γ.	N/A
Equipment is free of potential clothing entanglement hazards.	,/		NAA
quipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.			Minor rust
Equipment is free of entrapments.			1,4,01,103
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	_	٦	N/A
Swings are a safe distance from other playground equipment.	Г	F	NIA
Swings are 24 inches apart	F	F	NIA
Edges of seats are smooth and free from obstructions.	-	- -	A)/A
lequate depths of surfacing material extend out a inimum distance of twice the height of the swing.	F	г	NIA

CITY DOWN BY ACHEY +	alile	7		
Slides	Pass	Fail	Problem (Calari	20
Slides are free of obstructions and protrusions.			Problem / Solution	
Equipped with platforms to facilitate access to the sitting position.	/			_
Platforms are equipped with guardrails or equivalent protective equipment.		Г		
Average incline is less than 30 degrees.		( T 1) / A		
Exit regions are level.	1			
Metal slides are shaded to prevent overheating.		- Dlustic	Slides	
Climbing Equipment	Pass	Fail	Problem / Solution	
Hand grips are secured and do not rotate.	1	· r	1 Objetti / Solution	148
Rope or chain ladders are anchored at both ends.		Γ		_
Foot holds/rungs are in good condition and adequately spaced.		Γ		
Seesaws	Pass	Fail	Problem / Solution	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	N/A	Troblem, Soldton	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	- 1)/A		_
Fulcrums/pivot points are free of pinch or crush hazards.	Г	~/A		
Handholds are provided at each seating position.	5	17/4		_
Inspector name, signature, and completion date		N/A		
Name: Douglas Carpo			Date: 3/7/0/25	
Signature: ) and the ( while)			9 4/	_

- WILLSOVIEWONIK	3 /		
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			and the state of t
Playground area is free of anthills/hazardous insects , or toxic plants.	[-/	5	
Playground area is free of holes and other tripping hazards.	100	F	
Proper signage with rules, hours, and age- appropriate use is posted.		Ţ.	
Playground area is properly fenced.		۲	NA
Self-latching gate works as designed.	r,	į.	W/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	,/	, r	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.		г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	r	1)/4
Proper drainage prevents water from forming puddles.	Г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	15	Г	
Equipment is free from sharp points, corners, or edges.		- r	
Protective caps or plugs are not missing or damaged.	5/	\ r	
Equipment is free of potential clothing entanglement hazards.		Γ	
Equipment free of pinch and crush points or exposed moving parts.		F	
Equipment is free of rust, rot, cracks, and splinters.			minor rust on cornors
Equipment is free of entrapments.	-	۲	
Equipment is safely anchored.		۲	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	-	, L	
Swings are a safe distance from other playground equipment.		<u>_</u> r	
	- F	F	
equipment.			

Wilson Paris			Control of the second of the second
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		L CONTRACTOR OF THE PARTY OF TH	1 Toblem 3 Solution
Equipped with platforms to facilitate access to the sitting position.	1	Г	
Platforms are equipped with guardrails or equivalent protective equipment.		Г	
Average incline is less than 30 degrees.	٢	- N/A	
Exit regions are level.	1	70/14	
Metal slides are shaded to prevent overheating.	٢	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		T	Froblem / Solution
Rope or chain ladders are anchored at both ends.	1		
Foot holds/rungs are in good condition and adequately spaced.			
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	T 19/1	1 Toblem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г	N/A	
Fulcrums/pivot points are free of pinch or crush hazards.		N/A	
Handholds are provided at each seating position.	Г	(A)/A	
Inspector name, signature, and completion date		NIF	
Name: Douglas Carpio			
			Date: 3/26/25

Gorge Adams Dork		)E)	
General Inspection	Pas	s. Fail	Problem / Solution
Playground area is free of litter and debris.	7	1:	F F F F F F F F F F F F F F F F F F F
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.	/	F	· · · · · · · · · · · · · · · · · · ·
Proper signage with rules, hours, and age- appropriate use is posted.	7	F	-
Playground area is properly fenced.	Г	-	LVA
Self-latching gate works as designed.	Г	-	1/1
Surfacing	Pass	s Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	,/	-	
Surfacing material under and around equipment is adequate depth (6-12 inches).	Γ-		mulch is beeched
Surfacing material is free of glass, debris, or other foreign objects.		-	LOCCIC IS DEFOIL
Surfacing material is not compacting or deteriorating.	1	Į,	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	-	Ī.	N/A
Proper drainage prevents water from forming puddles.	<del>  -</del>	۱	N/A
Equipment Hazards	Pass	"Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	, ī	Solderon
Equipment is free from sharp points, corners, or edges.		F	
rotective caps or plugs are not missing or damaged.	-	, [	,
Equipment is free of potential clothing entanglement hazards.		, F	
quipment free of pinch and crush points or exposed moving parts.	5	Г	
equipment is free of rust, rot, cracks, and splinters.	г	/ -	rust
Equipment is free of entrapments.	-	<b>/</b>	1001
Equipment is safely anchored.		r	
Swings	Pass.	Fail	Problem / Solution
Hardware and chains are in good condition.	Į,	/ F	Transferring Solution
iwings are a safe distance from other playground equipment.		,	,
Swings are 24 inches apart.	ī	Г	
Edges of seats are smooth and free from obstructions.		r	
lequate depths of surfacing material extend out a inimum distance of twice the height of the swing.		F	

Garge Adams Dar			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		<u>Г</u>	1 Tobletti / Solution
Equipped with platforms to facilitate access to the sitting position.	/	Г	
Platforms are equipped with guardrails or equivalent protective equipment.		7	
Average incline is less than 30 degrees.	1	7	
Exit regions are level.	-	T +++	
Metal slides are shaded to prevent overheating.		44	
Climbing Equipment	Pass	A)/A	
Hand grips are secured and do not rotate.		- T 411	Problem / Solution
Rope or chain ladders are anchored at both ends.	-	7	
Foot holds/rungs are in good condition and adequately spaced.	/		
Seesaws	Pass	Fail	
Seesaws are free of cracks, corrosion, and other obvious structural defects.		T dil	Problem / Solution
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	/	r	
Fulcrums/pivot points are free of pinch or crush hazards.	1		
Handholds are provided at each seating position.	1	r	
Inspector name, signature, and completion date			
Name: DOUGLOS Corpio			Date: 3/24/25