Lorena Perez-Diaz

From: Jose Villalon <noreply@jotform.com>
Sent: Thursday, June 19, 2025 8:41 AM

To: Lorena Perez-Diaz; Wayne Shaffer; Joe Villalon; sara@portlavacaevents.com; Edward

Tyler

Subject: Re: Playground Safety Checklist - Jose Villalon



Playground Safety Checklist

Inspection ID 0011

Name of Park Claret Crossing Park

Inspection Date 06-19-2025 07:50 AM

General Inspection

	In Good Condition	Needs Improvement	Notes
Playground are is free of litter and debris		-	-
Playground area is free of anthills/hazardous insects or toxic plants.		-	-
Playground area is free of holes and other tripping hazards.		-	-
Proper signage with rules, hours, and age-appropriate use is posted.		-	-
Playground area is properly fenced	-	-	N/A
Self latching gate works as designed	-	-	N/A

Surfacing

	In Good Condition	Needs Improvement	Notes
Approved surfacing material is used (i.e. solid rubber, artificial graass or turf, play sand, pea gravel, wood chips, rubber mulch)	¥	-	-
Surfacing material under and around equipment is adequate depth (6-12 inches)	×	-	-
Surfacing material is free of glass, debris, or other foreign objects.	¥	-	-
Surfacing material is not compacting or deteriorating.	×	-	-
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	¥	-	-
Proper drainage prevents water from forming puddles.	¥	-	-

Equipment Hazards

	In Good Condition	Needs Improvement	Notes
Equipment is not damaged or vandalized.		-	-
Equipment is free from sharp points, corners, or edges.		-	-
Protective caps or plugs are not missing or damaged.		-	-
Equipment is free of potential clothing entanglement hazards.		-	-
Equipment is free of pinch and crush points or exposed moving parts.		-	-
Equipment is free of rust, rot, cracks, and splinters.		-	-
Equipment is free of entrapments.		-	-
Equipment is safely anchored.		-	-

Swings

	In Good Condition	Needs Improvement	Notes
Hardware and chains are in good condition.	×	-	-
Swings are a safe distance from other playground equipment.	×	-	-
Swings are 24 inches apart.	<u> </u>	-	-
Edges of seats are smooth and free from obstructions.	-	-	-
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		-	-

Slides

	In Good Condition	Needs Improvement	Notes
Slides are free of obstructions and protrusions.		-	-
Equipped with platforms to facilitate access to the sitting position.	l v	-	-
Platforms are equipped with guardrails or equivilent protective equipment.		-	-
Exit regions are level.		-	-

Climbing Equipment

	In Good Condition	Needs Improvement	Notes
Hand grips are secured and do not rotate.		-	-
Rope or chain ladders are anchored at both ends.		-	-
Foot holds/ rungs are in good condition and adequately spaced.		-	-

Seesaws

	In Good Condition	Needs Improvement	Notes
Seesaws are free of cracks, corrosion, and other obvious structural defects.	¥	-	-
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	×	-	-
Fulcrums/ pivot points are free of pinch or crush hazards.	V	-	-

