General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	D	
Playground area is free of anthills/hazardous insects or toxic plants.	1	0	
Playground area is free of holes and other tripping hazards.	r	0	
Proper signage with rules, hours, and age-appropriate use is posted.		7	
Playground area is properly fenced.	p	1	
Self-latching gate works as designed.	D	6	Mary of the sea of the
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	<i>F</i>	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	r	
Surfacing material is not compacting or deteriorating.	Г	1	Some
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	N	П	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	Applications of the section of the s
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	W	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	Surface/ around bolts
Equipment is free of entrapments.	N	Г	
Equipment is safely anchored.	1	Е	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	And the second s
Swings are a safe distance from other playground equipment.	V	Г).
Swings are 24 inches apart.	1	٢	
Edges of seats are smooth and free from obstructions.	1	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	*	Г	

City Part Pavillion	* (*)		rage 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	D	
Equipped with platforms to facilitate access to the sitting position.	1		
Platforms are equipped with guardrails or equivalent protective equipment.	1	D	
Average incline is less than 30 degrees.	1		
Exit regions are level.	1	п	
Metal slides are shaded to prevent overheating.	6	D	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1		
Rope or chain ladders are anchored at both ends.	1	D	
Foot holds/rungs are in good condition and adequately spaced.	7	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	С	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	п	О	None
Fulcrums/pivot points are free of pinch or crush hazards.	п	n	
Handholds are provided at each seating position.		n	
Inspector name, signature, and completion date			
Name: Blair Corfer Signature: Blir M			Date:

Cita Part - Ashle			
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	П	
Playground area is free of anthills/hazardous insects or toxic plants.	1	П	
Playground area is free of holes and other tripping hazards.	1	О	
Proper signage with rules, hours, and age-appropriate use is posted.	ם	1	
Playground area is properly fenced.		1	N/A
Self-latching gate works as designed.	0	W.	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	С	
Surfacing material under and around equipment is adequate depth (6-12 inches).	f	С	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	C	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	п	Γ	None
Proper drainage prevents water from forming puddles.	1	п	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	the same through sections is a considered to a construction of the
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	r	
Equipment free of pinch and crush points or exposed moving parts.	V	F	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	some rust around bott hands
Equipment is free of entrapments.	W	Г.	•
Equipment is safely anchored.	N	П	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	*	г	
Swings are a safe distance from other playground equipment.	Г	Г	
Swings are 24 inches apart.	Г	Г	No Swings
Edges of seats are smooth and free from obstructions.	г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	

Coty Port Hohley	4		Page 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	K	0	the state of the second
Equipped with platforms to facilitate access to the sitting position.	1	D	
Platforms are equipped with guardrails or equivalent protective equipment.	V	п	
Average incline is less than 30 degrees.	1	Ð	
Exit regions are level.	7	D	
Metal slides are shaded to prevent overheating.	1	D	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1	D	The commence of the control of the c
Rope or chain ladders are anchored at both ends.	1	D	
Foot holds/rungs are in good condition and adequately spaced.	1	ם	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		П	None
Fulcrums/pivot points are free of pinch or crush hazards.	п	n	
Handholds are provided at each seating position.	П	n	
Inspector name, signature, and completion date			
Name: Blair Carter Signature: Bla. Utr			Date:

Lighthouse > (Beac	4)	P	lay Page
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	6	D	The state of the s
Playground area is free of anthills/hazardous insects or toxic plants.	1		
Playground area is free of holes and other tripping hazards.			
Proper signage with rules, hours, and age-appropriate use is posted.	П	10	
Playground area is properly fenced.		/	
Self-latching gate works as designed.		1	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	D	
Surfacing material is free of glass, debris, or other foreign objects.	F	Г	
Surfacing material is not compacting or deteriorating.	1	С	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	п	1	Sand base
Proper drainage prevents water from forming puddles.	П	7	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1		
Equipment is free from sharp points, corners, or edges.	Г	1	Climb lodder edge rust
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	Ţ-	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	4	Г	
Equipment is free of entrapments.	w	Г	
Equipment is safely anchored.	N	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.	Г	Г	
Swings are 24 inches apart.	Г	Г	NO SWINGS
Edges of seats are smooth and free from obstructions.	Г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	

Lighthouse, Beach Play	1.		P9 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	V		
Platforms are equipped with guardrails or equivalent protective equipment.	0	D	
Average incline is less than 30 degrees.	0	D	
Exit regions are level.	~		
Metal slides are shaded to prevent overheating.	0		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	0		The state of the s
Rope or chain ladders are anchored at both ends.	0		
Foot holds/rungs are in good condition and adequately spaced.	6	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Б	ם	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	С	П	None
Fulcrums/pivot points are free of pinch or crush hazards.	п	П	,
Handholds are provided at each seating position.	D	П	
Inspector name, signature, and completion date			
Name: Blain Catro			Date:

Lighthouse Splashpai	d		Pg 1
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	E	Control of the second of the second s
Playground area is free of anthills/hazardous insects or toxic plants.	1	D	
Playground area is free of holes and other tripping hazards.	V	0	
Proper signage with rules, hours, and age- appropriate use is posted.	1	*	
Playground area is properly fenced.		1	NA
Self-latching gate works as designed.	0	10	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	С	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	K	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	The state of the s
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	Ę	~ : A
Equipment is free of potential clothing entanglement hazards.	1	г	Y /
Equipment free of pinch and crush points or exposed moving parts.	/	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	V	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	П	
Swings are a safe distance from other playground equipment.	Г	Г	No Swings
Swings are 24 inches apart.	Г		u /
Edges of seats are smooth and free from obstructions.	Г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	г	

Lighthouse Splosh pud			Pg 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	7		
Platforms are equipped with guardrails or equivalent protective equipment.	V	П.	
Average incline is less than 30 degrees.	1		
Exit regions are level.	V	D	
Metal slides are shaded to prevent overheating.	V	0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	V		
Rope or chain ladders are anchored at both ends.	0	D	
Foot holds/rungs are in good condition and adequately spaced.		П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,		-	Problem / Solution None
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	П	П	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	0	п	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	0 0	n n	

Lighthouse Pavillion)	1954	Pg 1
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1		The state of the s
Playground area is free of anthills/hazardous insects or toxic plants.	1	П	
Playground area is free of holes and other tripping hazards.	8		
Proper signage with rules, hours, and age- appropriate use is posted.	П	1	
Playground area is properly fenced.		K	
Self-latching gate works as designed.		P	
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	/	П	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	С	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	V	~
Proper drainage prevents water from forming puddles.	1	С	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	
Equipment is free from sharp points, corners, or edges.	V	г	
Protective caps or plugs are not missing or damaged.	V	Г	
Equipment is free of potential clothing entanglement hazards.	V	Г	
Equipment free of pinch and crush points or exposed moving parts.		Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	V		
Equipment is safely anchored.	V	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	7	г/	
Swings are a safe distance from other playground equipment.		/-	1
Swings are 24 inches apart.	- /		
Edges of seats are smooth and free from obstructions.	_/	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.		[

Lighthouse Povillion			Fg 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	V		The control of the second state and the second state and the second seco
Equipped with platforms to facilitate access to the sitting position.	V		
Platforms are equipped with guardrails or equivalent protective equipment.	V	ם	
Average incline is less than 30 degrees.	0	n	
Exit regions are level.	0	D	
Metal slides are shaded to prevent overheating.	0	0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	V		
Rope or chain ladders are anchored at both ends.	0	D	
Foot holds/rungs are in good condition and adequately spaced.	6	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	П	N/A none
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	п	none
Fulcrums/pivot points are free of pinch or crush hazards.	П	Г	none
Handholds are provided at each seating position.		П	
Inspector name, signature, and completion date			
Name: Blin Carter Signature: Blin Carter			Date: \$ -(5-23
Signature: VXIII CILLUT			

George Adems Buthroom	THE RESERVE TO SHARE		Pg (
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1		
Playground area is free of anthills/hazardous insects or toxic plants.		D	
Playground area is free of holes and other tripping hazards.	1	Ö	
Proper signage with rules, hours, and age- appropriate use is posted.	п	1	No Signage
Playground area is properly fenced.	П	K	NA
Self-latching gate works as designed.	D	T.	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	7	П	Neods Freshening.
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	С	11
Surfacing material is free of glass, debris, or other foreign objects.	1	Ė	
Surfacing material is not compacting or deteriorating.	Г	С	tt //
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Б	Ē.	No Mats yet.
Proper drainage prevents water from forming puddles.	п	7	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	Г	
Equipment is free from sharp points, corners, or edges.	1	г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	7	Г	
Equipment is safely anchored.	1	Б	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	Г	
Swings are a safe distance from other playground equipment.	7	Г	,
Swings are 24 inches apart.	1	Г	
Edges of seats are smooth and free from obstructions.	1	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	Freshiering needed.

George Adoms Buthroo.	m		Pg2		
Slides	Pass	Fail	Problem / Solution		
Slides are free of obstructions and protrusions.			the first problem and the second the second		
Equipped with platforms to facilitate access to the sitting position.	П				
Platforms are equipped with guardrails or equivalent protective equipment.	п				
Average incline is less than 30 degrees.	D				
Exit regions are level.		D			
Metal slides are shaded to prevent overheating.					
Climbing Equipment	Pass	Fail	Problem / Solution		
Hand grips are secured and do not rotate.	F				
Rope or chain ladders are anchored at both ends.	П		NA		
Foot holds/rungs are in good condition and adequately spaced.	П	Г			
Seesaws	Pass	Fail	Problem / Solution		
Seesaws are free of cracks, corrosion, and other obvious structural defects.	П		N/A		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	п	П			
Fulcrums/pivot points are free of pinch or crush hazards.	П	D			
Handholds are provided at each seating position.	П		,		
Inspector name, signature, and completion date					
Name: Blain Carten Signature: Blein Cett			Date: 5 - (5 - 23		

scorge Adams/ Pavil	llio.	2	Pg
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	П	
Playground area is free of anthills/hazardous insects or toxic plants.	1		
Playground area is free of holes and other tripping hazards.	1		
Proper signage with rules, hours, and age-appropriate use is posted.	П	1	
Playground area is properly fenced.		Г	N/A
Self-latching gate works as designed.	С	D	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	r	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	Г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	П	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	П	6	Swingsel is ordered. Mats will be installed then
Proper drainage prevents water from forming puddles.		1	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	M	П	Old domage cloosed.
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	K	Г	
Equipment is free of potential clothing entanglement hazards.	V	Г	
Equipment free of pinch and crush points or exposed moving parts.	~	Г	
Equipment is free of rust, rot, cracks, and splinters.	Г	1	Minor pust around screws
Equipment is free of entrapments.	г	Г	
Equipment is safely anchored.	N	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	K	Г	
Swings are a safe distance from other playground equipment.	/	Г	
Swings are 24 inches apart.	п	1	New goded.
Edges of seats are smooth and free from obstructions.	Г	П	11

George Itdoms ruville	00		Pg 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1	D	Control of the Contro
Equipped with platforms to facilitate access to the sitting position.	1		
Platforms are equipped with guardrails or equivalent protective equipment.	*	П	
Average incline is less than 30 degrees.	K	0	
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.	1	D	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	1		
Rope or chain ladders are anchored at both ends.	1		
Foot holds/rungs are in good condition and adequately spaced.	1		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Y		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	1	0	
Fulcrums/pivot points are free of pinch or crush hazards.	V		
Handholds are provided at each seating position.	1	П	
Inspector name, signature, and completion date			
Name: Black Corfer Signature: Black			Date:

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	P	П	
Playground area is free of anthills/hazardous insects or toxic plants.	1		
Playground area is free of holes and other tripping hazards.	10	0	
Proper signage with rules, hours, and age- appropriate use is posted.	П	A	NB
Playground area is properly fenced.		С	N/A
Self-latching gate works as designed.	0	D	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1		
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1		7
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Г	
Proper drainage prevents water from forming puddles.	N	П	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	
Equipment is free from sharp points, corners, or edges.	*	Г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	0	г	
Equipment is free of rust, rot, cracks, and splinters.	Г	Г	
Equipment is free of entrapments.	7	Г	9
Equipment is safely anchored.	1	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1		
Swings are a safe distance from other playground equipment.	1	Г	
Swings are 24 inches apart.	1	Г	
Edges of seats are smooth and free from obstructions.	1	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	1	Г	

Wilson Part			Page 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		
Equipped with platforms to facilitate access to the sitting position.	1	D	
Platforms are equipped with guardrails or equivalent protective equipment.	K	Б	
Average incline is less than 30 degrees.	K	0	
Exit regions are level.	1	D	
Metal slides are shaded to prevent overheating.	1	0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	F		
Rope or chain ladders are anchored at both ends.	r		
Foot holds/rungs are in good condition and adequately spaced.	A	П	
	Control of the last of the las	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,			Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	P P	П	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	T R	0	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	P P	n n	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards. Handholds are provided at each seating position.	P P	n n	Date:

	(To be con	npleted month	nly.)
Baytront			
General Inspection	Pass	Fail	Problem
Discoursed area in free of litter and debuis	-		A STATE OF THE PARTY OF THE PAR

General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1		
Playground area is free of anthills/hazardous insects or toxic plants.	1	П	-
Playground area is free of holes and other tripping hazards.	1	D	
Proper signage with rules, hours, and age- appropriate use is posted.	.0	1	
Playground area is properly fenced.			NA
Self-latching gate works as designed.	D	Ð	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	K		
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	1	0	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1		
Proper drainage prevents water from forming puddles.	1		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1		min de action de la company de
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	г	
Equipment is free of rust, rot, cracks, and splinters.	1	- [Minimal rust around screwhood
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	1	0	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	4		
Swings are a safe distance from other playground equipment.	Г	*	No Swinss
Swings are 24 inches apart.	Г	Г	(1)
Edges of seats are smooth and free from obstructions.	Г	,Г	\\ 1/
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	\\ //
		The second second	

Bayfront			Parge 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	7		And the state of the second state of the secon
Equipped with platforms to facilitate access to the sitting position.	1		
Platforms are equipped with guardrails or equivalent protective equipment.	1		
Average incline is less than 30 degrees.	1		
Exit regions are level.	1	0	
Metal slides are shaded to prevent overheating.	1	0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7		the first control of the control of
Rope or chain ladders are anchored at both ends.	1	D	
Foot holds/rungs are in good condition and adequately spaced.	K	О	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	П	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	С	п	NIA
Fulcrums/pivot points are free of pinch or crush hazards.	п	0	
Handholds are provided at each seating position.	П	Г	
Inspector name, signature, and completion date			
Name: Blair Carter			Date:
1511 DIL			Date.

Clarette Crossing			Pg 1
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1		ministeriole financia de la financia de la companya
Playground area is free of anthills/hazardous insects or toxic plants.	7	D	
Playground area is free of holes and other tripping hazards.	1	0	
Proper signage with rules, hours, and age-appropriate use is posted.	D	1	
Playground area is properly fenced.		D	NIA
Self-latching gate works as designed.		0	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	С	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	С	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.	A	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	1	Е	
Proper drainage prevents water from forming puddles.	1	Б	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1		
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	Г	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.	6	Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	П	
Swings are a safe distance from other playground equipment.	1	Г	1
Swings are 24 inches apart.	1	г	. per .
Edges of seats are smooth and free from obstructions.	*	Г	

Cloricy Chossing

19-

Port Lavaca Playground Safety Checklist

Claret Crossing			Py2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	1		the state of the s
Equipped with platforms to facilitate access to the sitting position.	7		
Platforms are equipped with guardrails or equivalent protective equipment.	1		
Average incline is less than 30 degrees.	1		
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.	1	. 0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	4		and the financial control of the con
Rope or chain ladders are anchored at both ends.	1		
Foot holds/rungs are in good condition and adequately spaced.	7	П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	F		
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	1	П	
Fulcrums/pivot points are free of pinch or crush hazards.	P	0	
Handholds are provided at each seating position.	11	П	
Inspector name, signature, and completion date			
Name: Blair Cartac Signature: Blin At			Date: 5-15-23

Buttertly May 1.	S THE RESERVE OF	202	
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	1	D	
Playground area is free of anthills/hazardous insects or toxic plants.	1		
Playground area is free of holes and other tripping hazards.	1	D	
Proper signage with rules, hours, and age- appropriate use is posted.		1	
Playground area is properly fenced.		.0	N/A
Self-latching gate works as designed.		D	N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	1	С	
Surfacing material is free of glass, debris, or other foreign objects.	1	D	
Surfacing material is not compacting or deteriorating.	Г	1	At Jumpott points studes
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	п	1	1 Stides
Proper drainage prevents water from forming puddles.	6	О	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	П	
Equipment is free from sharp points, corners, or edges.	1	Г	\$ 1
Protective caps or plugs are not missing or damaged.	1	Г	
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	1	г	
Equipment is free of rust, rot, cracks, and splinters.	г	1	Minimal nust on steppole
Equipment is free of entrapments.	Г	Г	unden Pe
Equipment is safely anchored.	n	П	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	1	П	
Swings are a safe distance from other playground equipment.	1	Г	i.
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from obstructions.	7	П	
Adequate depths of surfacing material extend out a	1	Г	

Butterfly	Section 1	-	Pg 2
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	6		Septimental september and september 25 September 25 September 2011 September 2011
Equipped with platforms to facilitate access to the sitting position.	1		
Platforms are equipped with guardrails or equivalent protective equipment.	7		
Average incline is less than 30 degrees.	1		
Exit regions are level.	1		
Metal slides are shaded to prevent overheating.	1	0	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	0	State of the state
Rope or chain ladders are anchored at both ends.	*		
Foot holds/rungs are in good condition and adequately spaced.	¥		
(2011년) 1월 1일			[10] [15] [15] [15] [15] [15] [15] [15] [15
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	N/A
Seesaws are free of cracks, corrosion,			
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	П	П	
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch	0	0	N/A N/A
Seesaws are free of cracks, corrosion, and other obvious structural defects. Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground. Fulcrums/pivot points are free of pinch or crush hazards.	0	n n	N/A N/A