Bayfront (La Belle)	July	112/	2024
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	d	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	ī	Г	
Playground area is free of holes and other tripping hazards.	1	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	\ \  \  \	Г	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	J	Γ	
Surfacing material under and around equipment is adequate depth (6-12 inches).		Г	
Surfacing material is free of glass, debris, or other foreign objects.		Г	
Surfacing material is not compacting or deteriorating.	5	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Γ	NA
Proper drainage prevents water from forming puddles.	г	Г	MA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	1	г	
Equipment is free from sharp points, corners, or edges.	<i>y</i>	Г	
Protective caps or plugs are not missing or damaged.	Γ,	Г	NA
Equipment is free of potential clothing entanglement hazards.	1	Г	
Equipment free of pinch and crush points or exposed moving parts.	\ \[ \sqrt{\sq}\sqrt{\sq}}}}}}}}}}\signtifien\signtifta\sintitex{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sq}}}}}}}\sqrt{\sqrt{\sqrt{\sqrt{\sq}}}}}}}\sqrt{\sqrt{\sqrt{\sintitita}}}}\signtifien\signtifta\signtifta\sint{\sint{\sint{\sinititit{\sint{\sint{\sint{\sint{\sinititi}}}}}}}}\signtifien\sint		
Equipment is free of rust, rot, cracks, and splinters.	r/		little rust on bolts & nuts
Equipment is free of entrapments.	1	Г	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		г	/
Swings are a safe distance from other playground equipment.	r	г	A / //
Swings are 24 inches apart.	Г	Г	
Edges of seats are smooth and free from obstructions.	Г	г	11/1
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	г	

(To be completed monthly.

la Belle

la belle			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		г	
Equipped with platforms to facilitate access to the sitting position.		Г	
Platforms are equipped with guardrails or equivalent protective equipment.		Г	
Average incline is less than 30 degrees.	1	Г	
Exit regions are level.	1	Г	
Metal slides are shaded to prevent overheating.	Г	Г	N/A Plastic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	Г	
Rope or chain ladders are anchored at both ends.	r/	Γ	NA
Foot holds/rungs are in good condition and adequately spaced.		Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	١	Г	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Γ	Γ	1//1
Fulcrums/pivot points are free of pinch or crush hazards.	г	Г	
Handholds are provided at each seating position.	г	Г	
Inspector name, signature, and completion date			

inspector name, signature, and completion date	
Name: Roge/io Barraza III Signature: Kaylio Sanga III.	Date: 7/12/2024

Bay front solash pad	Ju	Jy 17	1,2024
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	4	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	ī	г	
Playground area is free of holes and other tripping hazards.	F	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	<b>V</b>	г	
Playground area is properly fenced.	Г	Г	MA
Self-latching gate works as designed.		Г	NH
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	FS	٢	surface is concrete
Surfacing material under and around equipment is adequate depth (6-12 inches).	- /	Г	
Surfacing material is free of glass, debris, or other foreign objects.		Γ	
Surfacing material is not compacting or deteriorating.	<b>V</b>	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		Γ	NA
Proper drainage prevents water from forming puddles.	T		
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	F	Г	
Equipment is free from sharp points, corners, or edges.	1	Г	
Protective caps or plugs are not missing or damaged.	F	Г	
Equipment is free of potential clothing entanglement hazards.		٢	
Equipment free of pinch and crush points or exposed moving parts.	T/	Г	
Equipment is free of rust, rot, cracks, and splinters.	7	Г	
Equipment is free of entrapments.	10/	Г	
Equipment is safely anchored.	īt	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	1 / / /
Swings are a safe distance from other playground equipment.	Г	۲	
Swings are 24 inches apart.	г	Г	
Edges of seats are smooth and free from obstructions.	г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	

7	1	- 01	- 1	2 7
DOS	front	5/10	29N	you

( test) Witely ( the		ETTER TOTAL	
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	Г	г	, , , ,
Equipped with platforms to facilitate access to the sitting position.	Г	г	1///
Platforms are equipped with guardrails or equivalent protective equipment.	г	Г	
Average incline is less than 30 degrees.	Г	Г	
Exit regions are level.	Г	Γ	
Metal slides are shaded to prevent overheating.	Г	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	Г	Г	1 [ ]
Rope or chain ladders are anchored at both ends.	г	Γ	// / / /
Foot holds/rungs are in good condition and adequately spaced.	Г	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	г	Г	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	г	
Fulcrums/pivot points are free of pinch or crush hazards.	г	Г	11/1/
Handholds are provided at each seating position.	r	г	

Inspector name, signature, and completion date	
Name: Rogelio Barraza III  Signature: Maglio Barraza III	te: 7/12/24

L. H.B. Splash pad	Ju	y 12	-/2024
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	الحا	Г	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.		Г	
Proper signage with rules, hours, and age- appropriate use is posted.	V	Г	
Playground area is properly fenced.	Г	Г	N/A
Self-latching gate works as designed.	Г	Г	NIA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	Г	surface 16 concréte
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	
Surfacing material is free of glass, debris, or other foreign objects.		г	
Surfacing material is not compacting or deteriorating.		г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	NA
Proper drainage prevents water from forming puddles.	₹	Г	
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.		г	
Protective caps or plugs are not missing or damaged.	r /	Г	NA
Equipment is free of potential clothing entanglement hazards.		٢	
Equipment free of pinch and crush points or exposed moving parts.	ē/	Г	
Equipment is free of rust, rot, cracks, and splinters.	1/	F	
Equipment is free of entrapments.	12/	Г	
Equipment is safely anchored.	iV	г	
Swings Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	Ė	г	
Swings are 24 inches apart.	г		
Edges of seats are smooth and free from obstructions.	г	г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	г	

Slides	Pass	Fail	P. L. John
Slides are free of obstructions and protrusions.			Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	Г	Г	. ( / /
Platforms are equipped with guardrails or equivalent protective equipment.	Г	Г	
Average incline is less than 30 degrees.	Г	Г	
Exit regions are level.	Г	Г	
Metal slides are shaded to prevent overheating.	Г	г	
Climbing Equipment	Pass	Fail	/ Problem / Solution
Hand grips are secured and do not rotate.	Г	Г	. spicini, solution
Rope or chain ladders are anchored at both ends.	г	r	
Foot holds/rungs are in good condition and adequately spaced.	Г	г	
Seesaws	Pass	Fail	Problem / Solution
		No. of Concession, Name of Street, or other Designation, Name of Street, Name	
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Г	Г	1 Toblem Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.		enided (Sect	1 TOBIETT / Solution
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	٦	Г	1 TOBIETT / Solution
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	Г	Г	1 TODIETTI SOLUCION
and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	r	r	Troblem? Solution

L.H.B. Green + Blue Dlay ground	-	YWZ	12,2029
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.		Г	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.	Г/	N	Play ground rubber surface has Three minor Holes near mankey bars
Proper signage with rules, hours, and age- appropriate use is posted.		г	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	1	г	
Surfacing material under and around equipment is adequate depth (6-12 inches).	ito	г	
Surfacing material is free of glass, debris, or other foreign objects.	1	Г	
Surfacing material is not compacting or deteriorating.		Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	г	Γ	N/A
Proper drainage prevents water from forming puddles.	г	г	N/A
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		Г	
Equipment is free from sharp points, corners, or edges.	Te <sup>2</sup>	Г	
Protective caps or plugs are not missing or damaged.	Г	Г	NA
Equipment is free of potential clothing entanglement hazards.	Ti.	Г	
Equipment free of pinch and crush points or exposed moving parts.	5	۲,	
Equipment is free of rust, rot, cracks, and splinters.	г/		little rust on bolts & nuts
Equipment is free of entrapments.	5	Г	7777 07 00113 () 17003
Equipment is safely anchored.	-15/	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	Г	Г	
Swings are a safe distance from other playground equipment.	r		
Swings are 24 inches apart.	г	Г	
Edges of seats are smooth and free from obstructions.	Г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Г	

LHB Green & Blue play ground	7.	14	12,2024
Slides	Pass		Problem / Solution
Slides are free of obstructions and protrusions.	IN.	Г	Troblem/ Solution
Equipped with platforms to facilitate access to the sitting position.		Г	
Platforms are equipped with guardrails or equivalent protective equipment.	1	F.	
Average incline is less than 30 degrees.	1	Г	
Exit regions are level.	1	Г	
Metal slides are shaded to prevent overheating.	t	Г	slides are plastic
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		Г	
Rope or chain ladders are anchored at both ends.	г	Г	1//4
Foot holds/rungs are in good condition and adequately spaced.		Г	
	MARKET LANGE STATE		
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail r	Problem / Solution
Seesaws are free of cracks, corrosion.			Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	٦	Г	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	r	Г	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	r -	г г	Problem / Solution

L HB Naval Pirate ship	JWY	12	12029
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	J	Г	
Playground area is free of anthills/hazardous insects or toxic plants.		Г	
Playground area is free of holes and other tripping hazards.	10	С	
Proper signage with rules, hours, and age- appropriate use is posted.		٢	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	٢	l ave	NA
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	Г	N/A
Surfacing material is free of glass, debris, or other foreign objects.	г		swfacing is sand has grass growth.
Surfacing material is not compacting or deteriorating.	Г	Г	N/A
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Г	1//4
Proper drainage prevents water from forming puddles.	Г	Г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.		TV	Bolts missing, 2 Hond supports missing
Equipment is free from sharp points, corners, or edges.	Г		Two hand supports, has broken screws sticking out.
Protective caps or plugs are not missing or damaged.	Γ,	86	NA
Equipment is free of potential clothing entanglement hazards.	5	Г	
Equipment free of pinch and crush points or exposed moving parts.	E.	Г	
Equipment is free of rust, rot, cracks, and splinters.	Γ,	√	has rust on blue side ladder
Equipment is free of entrapments.	7	Г	
Equipment is safely anchored.	憋	TV.	one tunne above surface has three missing
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	i i	٦	
Swings are 24 inches apart.	г	Г	
Edges of seats are smooth and free from obstructions.	Г	Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	Г	Г	

LHB Nava Pirate ship Th	14 1.	2,2	224
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	H,	Г	
Equipped with platforms to facilitate access to the sitting position.	7	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	1	Г	
Average incline is less than 30 degrees.	1	Г	
Exit regions are level.	0	Г	
Metal slides are shaded to prevent overheating.	г	Г	Plastic slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	г	Г	AUA
Rope or chain ladders are anchored at both ends.	г	Γ	NA
Foot holds/rungs are in good condition and adequately spaced.		Г	
Seesaws	No. of Lot		
	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion.		Sales and Sales and Advantage of the Control of the	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	Г	Г	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch	Г	Г	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.	r	Г	Problem / Solution

2HB Pavillion Planground	July	121	2014
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	Inc.	г	
Playground area is free of anthills/hazardous insects or toxic plants.	ng/	Г	
Playground area is free of holes and other tripping hazards.	7	Г	
Proper signage with rules, hours, and age- appropriate use is posted.	√	Г	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		-	
Surfacing material under and around equipment is adequate depth (6-12 inches).	\ \frac{1}{2}	Г	
Surfacing material is free of glass, debris, or other foreign objects.		Γ	
Surfacing material is not compacting or deteriorating.	la la	Г	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	٢	NA
Proper drainage prevents water from forming puddles.	г	la de	MA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	0/	Г	
Equipment is free from sharp points, corners, or edges.	P	Γ	
Protective caps or plugs are not missing or damaged.	r /	Г	NA
Equipment is free of potential clothing entanglement hazards.		Г	
Equipment free of pinch and crush points or exposed moving parts.	7	٢	
Equipment is free of rust, rot, cracks, and splinters.	1	Г	
Equipment is free of entrapments.		Г	
Equipment is safely anchored.		Г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		Г	
Swings are a safe distance from other playground equipment.	г	г	1//
Swings are 24 inches apart.	г	Г	
Edges of seats are smooth and free from obstructions.	Г	Γ	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	г	Γ	

LHB Pavillion Playground	Ju	M 12	- hort
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.		Г	
Equipped with platforms to facilitate access to the sitting position.		п	
Platforms are equipped with guardrails or equivalent protective equipment.	П	Г	
Average incline is less than 30 degrees.	17/	Г	
Exit regions are level.	1	Г	
Metal slides are shaded to prevent overheating.	TS/	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.		Г	
Rope or chain ladders are anchored at both ends.	īv	Г	
Foot holds/rungs are in good condition and adequately spaced.	rJ	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	۲	Г	A \
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	г	г	
Fulcrums/pivot points are free of pinch or crush hazards.	Г	Г	1111
Handholds are provided at each seating position.	Г	г	
Inspector name, signature, and completion date			
Name: Rogelio Borros o III Signature:			Date: 7/12/24

Butterfly playaround & Fittness area	MY	12/2	-024
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	in lar	Г	
Playground area is free of anthills/hazardous insects or toxic plants.	5	Г	
Playground area is free of holes and other tripping hazards.	1	г	
Proper signage with rules, hours, and age- appropriate use is posted.	г	no	
Playground area is properly fenced.	Г	Г	NA
Self-latching gate works as designed.	Г	Г	NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).		Γ	
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г/	Г	NA
Surfacing material is free of glass, debris, or other foreign objects.	FIF /	Γ,	
Surfacing material is not compacting or deteriorating.	Г	<b>-</b>	rubber surfacing is cracked; packing is exposed"
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Г	Γ	NA
Proper drainage prevents water from forming puddles.	г	Г	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	0	Г	
Equipment is free from sharp points, corners, or edges.		Г	
Protective caps or plugs are not missing or damaged.	Γ,	Г	NA
Equipment is free of potential clothing entanglement hazards.	[ ]	۲	
Equipment free of pinch and crush points or exposed moving parts.			
Equipment is free of rust, rot, cracks, and splinters.	Γ,	1	rust build up on all surfaces
Equipment is free of entrapments.	~	Г	
Equipment is safely anchored.	<b>「</b>	г	
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.	15/	Г	
Swings are a safe distance from other playground equipment.	17	г	
Swings are 24 inches apart.	7	Г	
Edges of seats are smooth and free from obstructions.		Г	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	F.	Г	

Butter fly playground & Fittness area			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	J	г	
Equipped with platforms to facilitate access to the sitting position.	F	г	
Platforms are equipped with guardrails or equivalent protective equipment.		г	
Average incline is less than 30 degrees.		Г	
Exit regions are level.	1	Г	
Metal slides are shaded to prevent overheating.	Г	Г	Plastic Slides
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	,d	Г	
Rope or chain ladders are anchored at both ends.	г	Г	NA
Foot holds/rungs are in good condition and adequately spaced.	J	Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	٦	Г	0 / / /
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	F	г	
Fulcrums/pivot points are free of pinch or crush hazards.	г	г	
Handholds are provided at each seating position.	Г	г	·

Name: Rogelio Barraza II  Signature: Date: 7/12/14

Clare Lrossing	VMA	14,	12019
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	4		
Playground area is free of anthills/hazardous insects or toxic plants.	1	П	
Playground area is free of holes and other tripping hazards.			
Proper signage with rules, hours, and age- appropriate use is posted.	N		
Playground area is properly fenced.			1/4.
Self-latching gate works as designed.			NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<b>/</b>		
Surfacing material under and around equipment is adequate depth (6-12 inches).		П	
Surfacing material is free of glass, debris, or other foreign objects.			
Surfacing material is not compacting or deteriorating.	₩.	П	
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.			NA
Proper drainage prevents water from forming puddles.			NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	Par I		
Equipment is free from sharp points, corners, or edges.	ال		
Protective caps or plugs are not missing or damaged.	rJ ,		
Equipment is free of potential clothing entanglement hazards.		П	
Equipment free of pinch and crush points or exposed moving parts.	r//	П	
Equipment is free of rust, rot, cracks, and splinters.	10/	П	
	7/	G	
Equipment is free of entrapments.	7/		
Equipment is free of entrapments.  Equipment is safely anchored.	9		
	/	Fail	Problem / Solution
Equipment is safely anchored.	V	16/07/17/20	Problem / Solution
Equipment is safely anchored.  Swings	Pass	Fail	Problem / Solution
Equipment is safely anchored.  Swings  Hardware and chains are in good condition.  Swings are a safe distance from other playground	Pass	Fail	Problem / Solution
Equipment is safely anchored.  Swings  Hardware and chains are in good condition.  Swings are a safe distance from other playground equipment.	Pass	Fail	Problem / Solution

Claret Crossing Ju	Pass	THE RESERVE AND DESCRIPTION OF THE PERSON.	202
Slides are free of obstructions and protrusions.	rass	Fall	Problem / Solution
Equipped with platforms to facilitate access to the sitting position.	h/		
Platforms are equipped with guardrails or equivalent protective equipment.	7	Г	
Average incline is less than 30 degrees.	FV	Г	
Exit regions are level.	15/	Г	
Metal slides are shaded to prevent overheating.	To To	г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	N	Г	
Rope or chain ladders are anchored at both ends.	1	г	
Foot holds/rungs are in good condition and adequately spaced.	7	г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	<b>√</b>	Г	
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	4	Γ	
Fulcrums/pivot points are free of pinch or crush hazards.	0/	г	
Handholds are provided at each seating position.	V	г	
nspector name, signature, and completion date			
lame: Rogelio Barraza III	-		Date: 1/12/2014

City Pork/Ashley Field Ju	al y	12/2	014
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	Tel .		
Playground area is free of anthills/hazardous insects or toxic plants.		П	
Playground area is free of holes and other tripping hazards.			
Proper signage with rules, hours, and age- appropriate use is posted.			
Playground area is properly fenced.			NA
Self-latching gate works as designed.			NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).			
Surfacing material under and around equipment is adequate depth (6-12 inches).	Г	П	
Surfacing material is free of glass, debris, or other foreign objects.	/	TZ/	has minor grass growth
Surfacing material is not compacting or deteriorating.	Les /		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.		П	
5			_
Proper drainage prevents water from forming puddles.			NA
	Pass	Fail	NA Problem / Solution
forming puddles.		of the same	
forming puddles.  Equipment Hazards	Pass	Fail	
forming puddles.  Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners,	Pass	Fail	
forming puddles.  Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.	Pass	Fail	
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing	Pass	Fail	
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed	Pass	Fail	
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.	Pass	Fail	Problem / Solution  NA
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.	Pass	Fail	Problem / Solution  NA
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.	Pass		Problem / Solution  NA
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.	Pass	Fail	Problem / Solution  NA  Minor Yust
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.  Swings	Pass  Pass  Pass	Fail  Fail	Problem / Solution  NA  Minor Yust
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.  Swings  Hardware and chains are in good condition.  Swings are a safe distance from other playground	Pass Pass	Fail  Fail	Problem / Solution  NA  Minor Yust
Equipment Hazards  Equipment is not damaged or vandalized.  Equipment is free from sharp points, corners, or edges.  Protective caps or plugs are not missing or damaged.  Equipment is free of potential clothing entanglement hazards.  Equipment free of pinch and crush points or exposed moving parts.  Equipment is free of rust, rot, cracks, and splinters.  Equipment is free of entrapments.  Equipment is safely anchored.  Swings  Hardware and chains are in good condition.  Swings are a safe distance from other playground equipment.	Pass  Pass  Pass	Fail  Fail	Problem / Solution  NA  Minor Yust

(To be completed monthly.)

City Park /Ashter Field			
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	FJ	Γ	
Equipped with platforms to facilitate access to the sitting position.	\	Г	
Platforms are equipped with guardrails or equivalent protective equipment.	₩	г	
Average incline is less than 30 degrees.	l l	Г	
Exit regions are level.	N.	Г	
Metal slides are shaded to prevent overheating.	rt	Г	
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	7	Г	4
Rope or chain ladders are anchored at both ends.		Г	
Foot holds/rungs are in good condition and adequately spaced.		Г	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.	٦	г	1 /
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	Г	Г	
Fulcrums/pivot points are free of pinch or crush hazards.	Г	г	
Handholds are provided at each seating position.	Г		

Inspector name, signature, and completion date

Name: Rogelio Borrozer III

Signature:

Date: 7/12/2014

Wilson Park Ju	14 1	2/2	2014
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.	N/		
Playground area is free of anthills/hazardous insects or toxic plants.	4	П	
Playground area is free of holes and other tripping hazards.			
Proper signage with rules, hours, and age- appropriate use is posted.	П		
Playground area is properly fenced.			NA
Self-latching gate works as designed.			N/A
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	E.		
Surfacing material under and around equipment is adequate depth (6-12 inches).		П	
Surfacing material is free of glass, debris, or other foreign objects.			
Surfacing material is not compacting or deteriorating.	7		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	П		NA
Proper drainage prevents water from forming puddles.			NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	ď		
Equipment is free from sharp points, corners, or edges.	P.		
Protective caps or plugs are not missing or damaged.	1		
Equipment is free of potential clothing entanglement hazards.	1	П	
Equipment free of pinch and crush points or exposed moving parts.			
Equipment is free of rust, rot, cracks, and splinters.			Has minor rust
Equipment is free of entrapments.	\ \/	П	
Equipment is safely anchored.	1		
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.			
Swings are a safe distance from other playground equipment.	- []	П	
Swings are 24 inches apart.	1		
Edges of seats are smooth and free from obstructions.		П	
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.	$\forall$	П	

(To be completed monthly.)

Wilson Park

Slides	Pass	Fail	Problem / Solution
	rass	rall	Problem / Solution
Slides are free of obstructions and protrusions.	P		
Equipped with platforms to facilitate access to the sitting position.	r.		
Platforms are equipped with guardrails or equivalent protective equipment.	17		
Average incline is less than 30 degrees.			
Exit regions are level.			
Metal slides are shaded to prevent overheating.	TV.		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	4		
Rope or chain ladders are anchored at both ends.	L.		
Foot holds/rungs are in good condition and adequately spaced.		П	
Seesaws	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.			N / /
Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.	П	п	
Fulcrums/pivot points are free of pinch or crush hazards.			
Handholds are provided at each seating position.			<i>V</i> /

Inspector name, signature, and completion date

Name: Roge of Porrara #	Date: 7/12/24

George Adolms Si	Ny	12/	1074
General Inspection	Pass	Fail	Problem / Solution
Playground area is free of litter and debris.			
Playground area is free of anthills/hazardous insects or toxic plants.			
Playground area is free of holes and other tripping hazards.	i.J		
Proper signage with rules, hours, and age- appropriate use is posted.			
Playground area is properly fenced.			NA
Self-latching gate works as designed.			NA
Surfacing	Pass	Fail	Problem / Solution
Approved surfacing material is used (i.e. solid rubber, artificial grass or turf, play sand, pea gravel, wood chips, rubber mulch).	<b>1</b>		
Surfacing material under and around equipment is adequate depth (6-12 inches).			NA
Surfacing material is free of glass, debris, or other foreign objects.		2	mossive infestation of weeds
Surfacing material is not compacting or deteriorating.	N		
Rubber wear mats are used under high-traffic-use areas and covered by sufficient depth of surfacing material.	Б		NA
Proper drainage prevents water from forming puddles.		П	NA
Equipment Hazards	Pass	Fail	Problem / Solution
Equipment is not damaged or vandalized.	la,		
Equipment is free from sharp points, corners, or edges.	1	П	
Protective caps or plugs are not missing or damaged.	r/		
Equipment is free of potential clothing entanglement hazards.	1		
Equipment free of pinch and crush points or exposed moving parts.	٦/	О	
Equipment is free of rust, rot, cracks, and splinters.	数	П	Has rust spots
Equipment is free of entrapments.	7	П	
Equipment is safely anchored.			
Swings	Pass	Fail	Problem / Solution
Hardware and chains are in good condition.		П	
Swings are a safe distance from other playground equipment.		П	8
Swings are 24 inches apart.	<b>1</b>		
Edges of seats are smooth and free from obstructions.	$\checkmark$		
Adequate depths of surfacing material extend out a minimum distance of twice the height of the swing.			

George Adams J.	y K	2,2	024
Slides	Pass	Fail	Problem / Solution
Slides are free of obstructions and protrusions.	l d		
Equipped with platforms to facilitate access to the sitting position.	4		
Platforms are equipped with guardrails or equivalent protective equipment.	I.		
Average incline is less than 30 degrees.	II.		
Exit regions are level.	E,		
Metal slides are shaded to prevent overheating.	4		
Climbing Equipment	Pass	Fail	Problem / Solution
Hand grips are secured and do not rotate.	D/		
Rope or chain ladders are anchored at both ends.		П	
Foot holds/rungs are in good condition and adequately spaced.	4		
	COLUMB TO STATE		D. I.L. J.C. L.C.
Seesaws	Pass	Fail	Problem / Solution
Seesaws Seesaws are free of cracks, corrosion, and other obvious structural defects.	Pass	Fail	Problem / Solution
Seesaws are free of cracks, corrosion,	Pass		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact	<u>-</u>		Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch			Problem / Solution
Seesaws are free of cracks, corrosion, and other obvious structural defects.  Equipment is provided with spring centering devices or cushioning material to prevent abrupt contact with the ground.  Fulcrums/pivot points are free of pinch or crush hazards.		0	Problem / Solution