


Drawn: 6/2/2021 08:51:152 380-Teel Due Diligence\CAD\Site Plan.dwg Saved By: Abcador Save Time: 6/2/2022 2:54:39 PM Plotted By: Abcador Plot Date: 6/2/2022 2:55:01 PM




Note:
All proposed driveways, deceleration lanes and median openings along 380 are subject to TxDOT approval.


LEGEND

- Firelane
- Match Line

BERT FIELDS, JR.
Vol. 523, Pg. 687
(Part 1 of 1)



1 inch = 80 ft.



Vicinity Map
NTS

Town of Prosper Site Plan Notes:

- Dumpsters and trash compactors shall be screened per the Zoning Ordinance.
- Open storage, where permitted, shall be screened per the Zoning Ordinance.
- Outdoor lighting shall comply with the lighting and glare standards contained within the Zoning Ordinance and Subdivision Ordinance.
- Landscape shall conform to landscape plans approved by the Town.
- All elevations shall comply with the standards contained within the Zoning Ordinance.
- Buildings of 5,000 square feet or greater shall be 100% fire sprinkled. Alternative fire protection measures may be approved by the Fire Department.
- Occupant notification per this section and 907.5 shall be required for all new construction, or existing construction complying with the International Building Code, for renovations to existing buildings, tenant spaces, changes in occupancy, replacement or modification of the existing fire alarm system, or as required by the Fire Code Official, for all buildings or spaces provided with an approved automatic sprinkler system.
- Fire lanes shall be designed and constructed per Town Standards or as directed by the Fire Department.
- Two points of access shall be maintained for the property at all times.
- Speed bumps/humps are not permitted within a fire lane.
- Fire lanes shall be provided within 150 feet of all exterior walls of any building for hose lay requirements. Amendment 503.1.1
- The fire lane shall be a minimum of 24 feet wide. Amendment 503.2.1
- Buildings more than 30 feet in height are required to have a minimum of a 26-foot wide fire lane in the immediate vicinity for firefighting operations of the building. One of the 26-foot wide fire lanes shall be located a minimum of 15 feet from the building and no more than 30 feet. Appendix D105
- The inside turning radius of the 24-foot fire lane shall be a minimum of 30 feet. Amendment 503.2.4
- The inside turning radius of the 26-foot fire lane shall be a minimum of 30 feet. Amendment 503.2.4
- Dead-end fire lanes are only permitted with approved hammerheads.
- Fire hydrants shall be provided at the entrances and intersections. Amendment 507.5.1
- As properties develop, fire hydrants shall be located at all intersecting streets and the maximum spacing shall be every 300 feet (300') for all developments, and facilities other than R3, R-3 developments shall be every 500 feet (500'). Distances between hydrants shall be measured along the route that fire hose is laid by a fire apparatus from hydrant-to-hydrant, not as the "crow flies" Amendment 507.5.1
- Fire department connection (FDC) for the fire sprinkler system shall be located within 50 feet of a fire hydrant and 50 feet of a fire lane. 5" Storz, 30-degree downward turn with locking cap. Amendment 507.5.1
- Fire hydrants shall be located 2 foot (2') to 6 foot (6') back from the curb or fire lane and shall not be located in the bulb of a cul-de-sac. Amendment 507.5.1
- There shall be a minimum of two (2) fire hydrants serving each property within the prescribed distances listed above. A minimum of one fire hydrant shall be located on each lot. Amendment 507.5.1
- A minimum 10-foot unobstructed width shall be provided around a building for adequate Fire Department access. A continuous row of parking and landscaping shall be considered a barrier. Amendment 503.1.1
- The maximum dead-end cul-de-sac length shall not exceed six hundred feet (600') as measured from the centerline of the intersection street to the center point of the radius. Amendment 503.1.5
- One- and two-family dwellings shall be every 500 feet (500'). Automatic fire protection systems per NFPA 130 or NFPA 13R shall be provided in all one- and two-family dwellings with a conditioned floor area of 5,500 square feet (511 m²) or greater, dwellings three (3) stories or greater, or dwellings with roof heights exceeding thirty-five feet (35') from grade. IRC-2015 Amendment R313.2
- Handicapped parking areas and building accessibility shall conform to the Americans with Disabilities Act (ADA) and with the requirements of the current, adopted Building Code.
- All signage is subject to Building Official approval.
- All fences and retaining walls shall be shown on the Site Plan and are subject to Building Official approval.
- All exterior building materials are subject to Building Official approval and shall conform to the approved facade plan.
- Sidewalks of not less than six (6) feet in width along thoroughfares and collectors and five (5) feet in width along residential streets and barrier-free ramps at all curb crossings shall be provided per Town Standards.
- All new electrical lines shall be installed and/or relocated underground.
- All mechanical equipment shall be screened from public view per the Zoning Ordinance.
- All landscape easements must be exclusive of any other type of easement.
- Impact fees will be assessed per the land use classification(s) identified on the Site Data Summary Table; however, changes to the proposed land use at the time of CO and/or finish-out permit may result in additional impact fees and/or parking requirements.
- The approval of a Preliminary Site Plan shall be effective for two (2) years from the date that the Preliminary Site Plan is approved by the Planning & Zoning Commission, at the end of which time the applicant must have submitted and received the approval of a Site Plan by the Planning & Zoning Commission. If a site plan is not approved within such two (2) year period, the Preliminary Site Plan approval is null and void. If Site Plan approval is only for a portion of the property, the approval of the Preliminary Site Plan for the remaining property shall be null and void.

SITE DATA SUMMARY TABLE

LOT	ZONING	PROPOSED USE	LOT AREA		FIRST FLOOR BUILDING AREA (SF)	TOTAL BUILDING AREA (SF)	UNIT COUNT	BUILDING HEIGHT (story)	COVERAGE (%)	FLOOR AREA RATIO	REQ. PARKING RATIO	PARKING REQUIRED	PARKING PROVIDED	REQUIRED HANDICAP PARKING	PROVIDED HANDICAP PARKING	INTERIOR LANDSCAPE REQUIRED (SF)	INTERIOR LANDSCAPE PROVIDED (SF)	IMPERVIOUS AREA (SF)	OPEN SPACE REQUIRED (SF)	OPEN SPACE PROVIDED (SF)
			SF	AC																
1	PD	CONVENIENCE STORE	122,582	2.81	5,674	5,674	N/A	1	4.6%	0.0463:1	1:250	23	56	3	4	840	2,106	32,956	8,581	9,953
2	PD	RETAIL & RESTAURANT	78,436	1.80	9,100	9,100	N/A	1	11.6%	0.116:1	1:100; 1:250	65	85	4	4	1,275	5,490	27,702	5,490	4,616
3	PD	RETAIL & RESTAURANT	75,554	1.73	8,671	10,660	N/A	1	11.5%	0.1411:1	1:100; 1:250	76	77	4	6	1,155	972	24,769	5,289	2,103
4	PD	RETAIL & RESTAURANT	57,130	1.31	5,200	5,200	N/A	1	9.1%	0.091:1	1:100; 1:250	37	49	2	2	735	1,296	53,972	3,999	4,144
5	PD	RETAIL & RESTAURANT	60,413	1.39	5,200	5,200	N/A	1	8.6%	0.0861:1	1:100; 1:250	37	49	2	2	735	1,296	31,555	4,229	3,867
6	PD	RETAIL & RESTAURANT	126,635	2.91	19,000	19,000	N/A	1	15.0%	0.15:1	1:100; 1:250	133	138	5	8	2,070	2,106	48,228	8,864	4,000
7	PD	RETAIL & RESTAURANT	120,589	2.77	20,000	20,000	N/A	1	16.6%	0.1659:1	1:100; 1:250	140	142	5	4	2,130	1,944	45,213	8,484	8,484
8	PD	MEDICAL OFFICE	124,273	2.85	19,800	19,800	N/A	1	15.9%	0.1593:1	1:250	80	135	5	6	2,025	2,916	47,054	8,699	18,681
9	PD	MEDICAL OFFICE	48,212	1.11	7,500	15,000	N/A	2	15.6%	0.3111:1	1:250	60	69	3	2	1,035	1,620	30,091	3,375	3,024
10	PD	MEDICAL OFFICE	40,230	0.92	7,500	14,250	N/A	2	18.6%	0.3542:1	1:250	57	57	3	2	855	1,944	16,285	2,816	4,050
11	PD	MEDICAL OFFICE	44,786	1.03	8,400	15,750	N/A	2	18.8%	0.3517:1	1:250	63	63	3	2	945	1,944	26,002	3,135	4,100
12	PD	MEDICAL OFFICE	57,028	1.31	8,400	16,800	N/A	2	14.7%	0.2946:1	1:250	68	80	4	2	1,200	10,692	229,398	3,992	7,760
Total			955,868	21.944	124,445	156,434						839	1,000	43	44	15,000	29,646	613,225	66,911	74,782


CASE No. - D 22-0021
PRELIMINARY SITE PLAN
US 380 & TEEL PARKWAY
IN THE TOWN OF PROSPER, DENTON COUNTY, TEXAS
C. SMITH SURVEY ABSTRACT NO. 1681
955,868 Sq. Ft./21.944 Acres

ENGINEER / SURVEYOR / APPLICANT
Spiars Engineering, Inc.
765 Custer Road, Suite 100
Plano, TX 75075
Telephone: (972) 422-0077
TBPE No. F-2121
Contact: David Bond

OWNER/DEVELOPER
Teel 380, LP
8668 John Hickman Parkway
Frisco, TX 75034
Telephone: (972) 679-1918
Contact: Shiva Kondru

Drawn: C:\2021\DRS\21-152-380-Teel Due Diligence\CAD\Site Plan.dwg Saved By: Abroador Date: 5/2/2022 2:55:59 PM
Plotted By: Abroador Plot Date: 5/2/2022 2:55:59 PM

NATHAN J. &
NATHAN P. BONITKE
Doc. 2007-144901
DROCT



Town of Prosper Site Plan Notes:












- 1) Dumpsters and trash compactors shall be screened per the Zoning Ordinance.
- 2) Open storage, where permitted, shall be screened per the Zoning Ordinance.
- 3) Outdoor lighting shall comply with the lighting and glare standards contained within the Zoning Ordinance and Subdivision Ordinance.
- 4) Landscaping shall conform to landscape plans approved by the Town of Prosper.
- 5) All elevations shall comply with the standards contained within the Zoning Ordinance.
- 6) Buildings of 5,000 square feet or greater shall be 100% fire sprinkled. Alternative fire protection measures may be approved by the Fire Department.
- 7) Occupant notification per this section and 907.5 shall be required for all new construction, or existing construction complying with the International Building Code, for renovations to existing buildings, tenant spaces, changes in occupancy, replacement or modification of the existing fire alarm system, or as required by the Fire Code Official, for all buildings or spaces provided with an approved automatic sprinkler system.
- 8) Fire lanes shall be designed and constructed per Town Standards or as directed by the Fire Department.
- 9) Two points of access shall be maintained for the property at all times.
- 10) Speed bumps/humps are not permitted within a fire lane.
- 11) Fire lanes shall be provided within 150 feet of all exterior walls of any building for hose lay requirements. Amendment 503.1.1
- 12) The fire lane shall be a minimum of 24 feet wide. Amendment 503.2.1
- 13) Buildings more than 30 feet in height are required to have a minimum of a 26-foot wide fire lane in the immediate vicinity for firefighting operations of the building. One of the 26-foot wide fire lanes shall be located a minimum of 15 feet from the building and no more than 30 feet. Appendix D105
- 14) The inside turning radius of the 24-foot fire lane shall be a minimum of 30 feet. Amendment 503.2.4
- 15) The inside turning radius of the 26-foot fire lane shall be a minimum of 30 feet. Amendment 503.2.4
- 16) Dead-end fire lanes are only permitted with approved hammerheads.
- 17) Fire hydrants shall be provided at the entrances and intersections. Amendment 507.5.1
- 18) As properties develop, fire hydrants shall be located at all intersecting streets and the maximum spacing shall be every 300 feet (300') for all developments, and facilities other than R3. R-3 developments shall be every 500 feet (500'). Distances between hydrants shall be measured along the route that fire hose is laid by a fire apparatus from hydrant-to-hydrant, not as the "crow flies" Amendment 507.5.1
- 19) Fire department connection (FDC) for the fire sprinkler system shall be located within 50 feet of a fire hydrant and 50 feet of a fire lane. 5" Starz, 30-degree downward turn with locking cap. Amendment 507.5.1
- 20) Fire hydrants shall be located 2 foot (2') to 6 foot (6') back from the curb or fire lane and shall not be located in the bulb of a cul-de-sac. Amendment 507.5.1
- 21) There shall be a minimum of two (2) fire hydrants serving each property within the prescribed distances listed above. A minimum of one fire hydrant shall be located on each lot. Amendment 507.5.1
- 22) A minimum 10-foot unobstructed width shall be provided around a building for adequate Fire Department access. A continuous row of parking and landscaping shall be considered a barrier. Amendment 503.1.1
- 23) The maximum dead-end cul-de-sac length shall not exceed six hundred feet (600') as measured from the centerline of the intersection street to the center point of the radius. Amendment 503.1.5
- 24) One- and two-family dwellings automatic fire systems. Automatic fire protection systems per NFPA 13D or NFPA 13R shall be provided in all one- and two-family dwellings with a conditioned floor area of 5,500 square feet (511 m2) or greater, dwellings three (3) stories or greater, or dwellings with roof heights exceeding thirty-five feet (35') from grade. IRC-2015 Amendment R313.2
- 25) Handicapped parking areas and building accessibility shall conform to the Americans with Disabilities Act (ADA) and with the requirements of the current, adopted Building Code.
- 26) All signage is subject to Building Official approval.
- 27) All fences and retaining walls shall be shown on the Site Plan and are subject to Building Official approval.
- 28) All exterior building materials are subject to Building Official approval and shall conform to the approved facade plan.
- 29) Sidewalks of not less than six (6) feet in width along thoroughfares and collectors and five (5) feet in width along residential streets and barrier-free ramps at all curb crossings shall be provided per Town Standards.
- 30) All new electrical lines shall be installed and/or relocated underground.
- 31) All mechanical equipment shall be screened from public view per the Zoning Ordinance.
- 32) All landscape easements must be exclusive of any other type of easement.
- 33) Impact fees will be assessed per the land use classification(s) identified on the Site Data Summary Table; however, changes to the proposed land use at the time of CO and/or finish-out permit may result in additional impact fees and/or parking requirements.
- 34) The approval of a Preliminary Site Plan shall be effective for two (2) years from the date that the Preliminary Site Plan is approved by the Planning & Zoning Commission, at the end of which time the applicant must have submitted and received the approval of a Site Plan by the Planning & Zoning Commission. If a site plan is not approved within such two (2) year period, the Preliminary Site Plan approval is null and void. If Site Plan approval is only for a portion of the property, the approval of the Preliminary Site Plan for the remaining property shall be null and void.

All dimensions are to face of curb or edge of building unless otherwise noted.

All curb radii are 2' unless otherwise noted.


Notes:

1. The thoroughfare alignments shown on this exhibit are for illustration purposes and does not set the alignment. The alignment is determined at time of final plat.
2. Headlight screening will be provided in accordance with Town Standards.

LEGEND	
	FIRELANE, ACCESS, DRAINAGE & UTILITY EASEMENT
	1/2" IRON ROD W/ PLASTIC CAP STAMPED "SPIRSEN" SET, UNLESS OTHERWISE NOTED.
	POWER POLE
	LIGHT POLE/STANDARD
	GUY WIRE ANCHOR
	BOLLARD
	SIGNPOST
	OVERHEAD POWER LINE
	CONTROL MONUMENT
	PROPOSED FIRE HYDRANT
	EXISTING FIRE HYDRANT

CASE No. - D 22-0021
PRELIMINARY SITE PLAN
US 380 & TEEL PARKWAY
IN THE TOWN OF PROSPER, DENTON COUNTY, TEXAS
C. SMITH SURVEY ABSTRACT NO. 1681
955,868 Sq. Ft./21.944 Acres

ENGINEER / SURVEYOR / APPLICANT Spiors Engineering, Inc. 765 Custer Road, Suite 100 Plano, TX 75075 Telephone: (972) 422-0077 TBPE No. F-2121 Contact: David Bond	OWNER/DEVELOPER Teel 380, LP 8668 John Hickman Parkway Frisco, TX 75034 Telephone: (972) 679-1918 Contact: Shiva Kondru
---	--



Town of Prosper Site Plan Notes:

- Dumpsters and trash compactors shall be screened per the Zoning Ordinance.
- Open storage, where permitted, shall be screened per the Zoning Ordinance.
- Outdoor lighting shall comply with the lighting and glare standards contained within the Zoning Ordinance and Subdivision Ordinance.
- Landscaping shall conform to landscape plans approved by the Town.
- All elevations shall comply with the standards contained within the Zoning Ordinance.
- Buildings of 5,000 square feet or greater shall be 100% fire sprinkled. Alternative fire protection measures may be approved by the Fire Department.
- Occupant notification per this section and 907.5 shall be required for all new construction, or existing construction complying with the International Building Code, for renovations to existing buildings, tenant spaces, changes in occupancy, replacement or modification of the existing fire alarm system, or as required by the Fire Code Official, for all buildings or spaces provided with an approved automatic sprinkler system.
- Fire lanes shall be designed and constructed per Town Standards or as directed by the Fire Department.
- Two points of access shall be maintained for the property at all times.
- Speed bumps/humps are not permitted within a fire lane.
- Fire lanes shall be provided within 150 feet of all exterior walls of any building for hose lay requirements. Amendment 503.1.1
- The fire lane shall be a minimum of 24 feet wide. Amendment 503.2.1
- Buildings more than 30 feet in height are required to have a minimum of a 26-foot wide fire lane in the immediate vicinity for firefighting operations of the building. One of the 26-foot wide fire lanes shall be located a minimum of 15 feet from the building and no more than 30 feet. Appendix D105
- The inside turning radius of the 24-foot fire lane shall be a minimum of 30 feet. Amendment 503.2.4
- The inside turning radius of the 26-foot fire lane shall be a minimum of 30 feet. Amendment 503.2.4
- Dead-end fire lanes are only permitted with approved hammerheads.
- Fire hydrants shall be provided at the entrances and intersections. Amendment 507.5.1
- As properties develop, fire hydrants shall be located at all intersecting streets and the maximum spacing shall be every 300 feet (300') for all developments, and facilities other than R3. R-3 developments shall be every 500 feet (500'). Distances between hydrants shall be measured along the route that fire hose is laid by a fire apparatus from hydrant-to-hydrant, not as the "crow flies" Amendment 507.5.1
- Fire department connection (FDC) for the fire sprinkler system shall be located within 50 feet of a fire hydrant and 50 feet of a fire lane. 5" Storz, 30-degree downward turn with locking cap. Amendment 507.5.1
- Fire hydrants shall be located 2 foot (2') to 6 foot (6') back from the curb or fire lane and shall not be located in the bulb of a cul-de-sac. Amendment 507.5.1
- There shall be a minimum of two (2) fire hydrants serving each property within the prescribed distances listed above. A minimum of one fire hydrant shall be located on each lot. Amendment 507.5.1
- A minimum 10-foot unobstructed width shall be provided around a building for adequate Fire Department access. A continuous row of parking and landscaping shall be considered a barrier. Amendment 503.1.1
- The maximum dead-end cul-de-sac length shall not exceed six hundred feet (600') as measured from the centerline of the intersection street to the center point of the radius. Amendment 503.1.5
- One-and-two-family dwellings automatic fire systems. Automatic fire protection systems per NFPA 13D or NFPA 13R shall be provided in all one-and-two-family dwellings with a conditioned floor area of 5,500 square feet (511 m2) or greater, dwellings three (3) stories or greater, or dwellings with roof heights exceeding thirty-five feet (35') from grade. IRC-2015 Amendment R313.2
- Handicapped parking areas and building accessibility shall conform to the Americans with Disabilities Act (ADA) and with the requirements of the current, adopted Building Code.
- All signage is subject to Building Official approval.
- All fences and retaining walls shall be shown on the Site Plan and are subject to Building Official approval.
- All exterior building materials are subject to Building Official approval and shall conform to the approved facade plan.
- Sidewalks of not less than six (6) feet in width along thoroughfares and collectors and five (5) feet in width along residential streets and barrier-free ramps at all curb crossings shall be provided per Town Standards.
- All new electrical lines shall be installed and/or relocated underground.
- All mechanical equipment shall be screened from public view per the Zoning Ordinance.
- All landscape easements must be exclusive of any other type of easement.
- Impact fees will be assessed per the land use classification(s) identified on the Site Data Summary Table; however, changes to the proposed land use at the time of CO and/or finish-out permit may result in additional impact fees and/or parking requirements.
- The approval of a Preliminary Site Plan shall be effective for two (2) years from the date that the Preliminary Site Plan is approved by the Planning & Zoning Commission, at the end of which time the applicant must have submitted and received the approval of a Site Plan by the Planning & Zoning Commission. If a site plan is not approved within such two (2) year period, the Preliminary Site Plan approval is null and void. If Site Plan approval is only for a portion of the property, the approval of the Preliminary Site Plan for the remaining property shall be null and void.

All dimensions are to face of curb or edge of building unless otherwise noted.

All curb radii are 2' unless otherwise noted.

Notes:

- The thoroughfare alignments shown on this exhibit are for illustration purposes and does not set the alignment. The alignment is determined at time of final plat.
- Headlight screening will be provided in accordance with Town Standards.

LEGEND

- FIRELANE, ACCESS, DRAINAGE & UTILITY EASEMENT
- 1/2" IRON ROD W/ PLASTIC CAP STAMPED "SPIRSENG" SET, UNLESS OTHERWISE NOTED.
- POWER POLE
- LIGHT POLE/STANDARD
- GUY WIRE ANCHOR
- BOLLARD
- SIGNPOST
- OVERHEAD POWER LINE
- CONTROL MONUMENT
- PROPOSED FIRE HYDRANT
- EXISTING FIRE HYDRANT

CASE No. - D 22-0021
PRELIMINARY SITE PLAN
US 380 & TEEL PARKWAY
IN THE TOWN OF PROSPER, DENTON COUNTY, TEXAS
C. SMITH SURVEY ABSTRACT NO. 1681
955,868 Sq. Ft./21.944 Acres

ENGINEER / SURVEYOR / APPLICANT
Spiors Engineering, Inc.
765 Custer Road, Suite 100
Plano, TX 75075
Telephone: (972) 422-0077
TBPE No. F-2121
Contact: David Bond

OWNER/DEVELOPER
Teel 380, LP
8668 John Hickman Parkway
Frisco, TX 75034
Telephone: (972) 679-1918
Contact: Shiva Kondru