



### **Addendum to September 15, 2022 Sales Agreement**

Addendum for the contract between Brindlee Mountain Fire Apparatus (Seller) and City of Republic Fire Department, MO (Buyer). This addendum names the specific items to be completed on the Apparatus (Stock #16114) by the Seller.

1. Full chassis service of all fluids and filters.
2. Current pump service test, including pump transfer case.
3. Install pump test tag to indicate the correct pump testing pressure and GPM. This tag should indicate the pump GPM as well. Currently missing and required per ISO.
4. Test all valves and drains for functionality and leaks and repair as needed.
5. Provide test results of motor oil sample.
6. Repaint apparatus per department specifications. Paint to city colors along the same paint break as now painted. Red PPG 70852, White PPG 2185 paint codes.
7. Remove all stripping on red painted surfaces
8. Repair the front fender cracks in the fiberglass when in the body shop.
9. Do not paint wheels owner will supply wheel simulators for the dealer to install.
10. Remove all striping on stainless surfaces and aluminum surfaces. Buff to match existing stainless steel and aluminum under striping and decals. Do not remove the white reflective striping under the fold-a- tank mounting bracket.
11. Spot treat rust on undercarriage with POR15. Noted at point where compartments are mounted to subframe.
12. Repair engine front main seal leak. Check for other leaks.
13. Repair rear axle (driver's side) seal leak.
14. Replace end of exhaust due to rust.
15. Recharge air conditioning system
16. Driver's seat losing air. Repair as needed.
17. Verify all DOT, emergency, compartment and ground lighting is in proper working condition. Multiple emergency lights have LEDs that are inoperable, lenses faded, cracked, or containing moisture.
18. Buff all plastic lenses with a headlight restoration product to remove haze. Headlights, park lights, turn signals, and taillights, and the light bar.
19. Install battery indicator to the right side of the battery compartment - facing the pump panel.
20. Install plate to cover hole in battery compartment
21. Chevron rear bumper
22. Repair rear dump leak
23. Replace rear brakes
24. Replace front tires.
25. Verify pressure governor is in proper working condition.
26. Verify a full complement of hard suction and caps for intakes and discharges are included. Remove piston intake valve.

27. Officer's side door rattles. Adjust as necessary.
28. Replace any missing pump panel tags.
29. Remove Kenwood radio equipment. And fill holed with plugs or low profile bolts. Do not leave holes open.
30. Remove GPS tracking antenna and seal the hole with a metal plate. Note it is very likely the RFD will mount an antenna into this replacement plate for our radios.
31. Remove radios antenna mounts on door mirrors and all coaxial cables. These are not needed.