



--- PCMS-548

TRAILER-MOUNTED MESSAGE SIGN

Ver-Mac's PCMS-548 PRO Series is a mini full-matrix trailer-mounted portable changeable message sign. The default display is 3 lines and 9 characters (8.75 in.) per line, with the ability of displaying multiple fonts, lines of text and graphics. It features Stealth Technology, NTCIPcompliant V-Touch controller, V-Sync Wi-Fi communication and JamLogic® Fleet Management Software. This unit combines cutting-edge technology, energy-efficient design and high-quality construction to provide the most reliable, cost-effective and safe to operate message sign on the market. The PCMS-548 PRO Series is perfect for lower speed roadways and urban areas.



PRO SERIES FEATURES

STEALTH TECHNOLOGY

Sealed Maintenance-Free Batteries Anti-Theft Hidden Battery Compartment

V-SYNC WI-FI TECHNOLOGY

Change Messages Via Wi-Fi Using Your Smartphone Safely Change Messages Out of Traffic.

ROBUST TRAILER DESIGN

Tongue Wheel Jack for safe and easy set up Controller located away from the road Rugged Indexed Rod Mast Brake

FULLY-INTEGRATED CELLULAR 4G LTE MODEM

No 3G Upgrade Needed 10-Year Fleet Cell Service SWZ upgrade (optional)

JAMLOGIC® SOFTWARE

Hourly Automated Refresh and Battery/GPS Alerts & Reports

Interactive Map & List View of All Equipment Project Folders to Group Equipment Historical Log of all Locally & Remotely Activated Messages with Date/Time

4 WAYS TO CHANGE A MESSAGE



AT THE SIGN

Using our V-Touch Controller



NEAR THE SIGN

Using our V-SYNC Wi-Fi



REMOTELY

Using JamLogic on your PC or Laptop



REMOTELY

Using JamLogic Web on your Smartphone or Tablet



POWER SUPPLY CONFIGURATION

SOLAR PANELS

Provide maximum solar recharging during all four seasons.

- Designed to run 12 months in most regions without manual charging
- Various configurations of solar panels and batteries are available to meet your needs.

HIGH-QUALITY CONSTRUCTION

POWDER COATING SUPERIOR FINISH

Impact, humidity, salt spray and rust resistant

4 ADJUSTABLE STABILIZER LEGS

For trailer stabilization and easy transportation

TONGUE WHEEL JACK

To move the trailer around easily

MANUAL LIFT MECHANISM

For a quick deployment

U-SHAPED CRADLE FOR THE SIGN

For better support during transportation

RUGGED INDEXED ROD MAST BRAKE

The sign can be positioned on 209 degrees (17 deg. increments)

HEAVY-DUTY PLASTIC FENDERS

For durability and easy replacement

LOCKABLE PLASTIC BOX

For controller, modem, pump, and other components protection

2-IN. (51 MM) COUPLER OR 3-IN. (76 MM) PINTLE EYE

For easy towing

APPLICATIONS

- City and county (urban areas)
- School zones
- Special events

V-TOUCH CONTROLLER

NTCIP COMPLIANT

EASY-TO-READ

7-inch (178 mm) color LCD touchscreen display screen

USER-FRIENDLY

One-click icon-based menu items

TIME-SAVING

Create your own library of messages

SIMPLE TO OPERATE

The intuitive point-n-go icons ensure quick and easy commands to display or edit messages

ADDITIONAL FUNCTIONALITIES

Scheduling, sign diagnostics, pin-protected security, and much more



DISPLAY

- Display panel: 45 x 80 in. (1142 x 2026 mm)
- Full matrix of 30 x 56 pixels
- 2 LEDs per pixel
- 5 x 7 pixels (8.75 in.) characters (default)
- 3 lines of 9 characters per line (5 x 7 default font)
- Up to 3 lines of 12 characters per line (3 x 7 font)
- Display sign can rotate on 360 degrees for perfect setting
- Plug-and-play display modules for simplified maintenance

DIMENSIONS AND WEIGHTS

- Overall length: 133 in. (3367 mm)
- Overall width: 70 in. (1788 mm)
- Travelling height: 91 in. (2308 mm)
- Operating height: 133 in. (3387 mm)
- Weight (approx.): 521 kg (1150 lb)
- Axle/suspension: 909 kg (2000 lb)

OPTIONS

- Battery charger
- Radar
- Data logger (requires radar)
- Tilt-and-Rotate Solar Panels

Other options are available to meet your needs.

WARRANTY

- 1 year on complete trailer
- 2 years on electronic components manufactured by Ver-Mac





