



ADDITIONAL TERMS AND CONDITIONS

1. AS USED IN THIS ORDER THE TERMS (A) "DEALER" SHALL MEAN THE AUTHORIZED DEALER TO WHOM THIS ORDER IS ADDRESSED AND WHO SHALL BECOME A PARTY HERETO BY ITS ACCEPTANCE HEREOF, (B) "PURCHASER" SHALL MEAN THE PARTY EXECUTING THIS ORDER SUCH ON THE FACE HEREOF, AND (C) "MANUFACTURER" SHALL MEAN THE CORPORATION THAT MANUFACTURED THE VEHICLE OR CHASSIS, IT BEING UNDERSTOOD BY PURCHASER AND DEALER THAT DEALER IS IN NO RESPECT THE AGENT OF MANUFACTURER, THAT DEALER AND PURCHASER ARE THE SOLE PARTIES TO THIS ORDER AND THAT REFERENCE TO MANUFACTURER HEREIN IS FOR THE PURPOSE OF EXPLAINING GENERALLY CERTAIN CONTRACTUAL RELATIONSHIPS EXISTING BETWEEN DEALER AND MANUFACTURER WITH RESPECT TO NEW MOTOR VEHICLES.
2. PURCHASE AGREES TO DELIVER TO DEALER SATISFACTORY EVIDENCE OF TITLE TO ANY USED MOTOR VEHICLE TRADED IN AS A PART OF THE CONSIDERATION FOR THE MOTOR VEHICLE ORDERED HEREUNDER OF THE TIME OF DELIVERY OF SUCH USED MOTOR VEHICLE TO DEALER. PURCHASER WARRANTS ANY SUCH USED MOTOR VEHICLE TO BE HIS PROPERTY FREE AND CLEAR OF ALL LIENS AND ENCUMBRANCES EXCEPT AS OTHERWISE NOTED HEREIN.
3. MANUFACTURER HAS RESERVED THE RIGHT TO CHANGE THE DESIGN OF ANY NEW MOTOR VEHICLE, CHASSIS, ACCESSORIES OR PARTS THEREOF AT ANY TIME WITHOUT NOTICE AND WITHOUT OBLIGATION TO MAKE THE SAME OR ANY SIMILAR CHANGE UPON ANY MOTOR VEHICLE, CHASSIS, ACCESSORIES OR PARTS THERE OF PREVIOUSLY PURCHASED BY OR SHIPPED TO DEALER OR BEING MANUFACTURED OR SOLD IN ACCORDANCE WITH DEALER'S ORDERS CORRESPONDINGLY, THE EVENT OF ANY SUCH CHANGE BY MANUFACTURER, DEALER SHALL HAVE NO OBLIGATION TO PURCHASER TO TAKE THE SAME OR ANY SIMILAR CHANGE IN ANY MOTOR VEHICLE, CHASSIS, ACCESSORIES OR PARTS THEREOF COVERED BY THIS ORDER EITHER BEFORE OR SUBSEQUENT TO DELIVERY THEREOF TO PURCHASER.
4. DEALER SHALL NOT BE LIABLE FOR FAILURE TO DELIVER OR DELAY IN DELIVERING THE MOTOR VEHICLE COVERED BY THIS ORDER WHERE SUCH FAILURE OR DELAY IS DUE, IN WHOLE OR IN PART, TO ANY CAUSE BEYOND THE CONTROL OF WITHOUT THE FAULT OF NEGLIGENCE OF DEALER.
5. THE PRICE FOR THE MOTOR VEHICLE SPECIFIED ON THE FACE OF THIS ORDER INCLUDES REIMBURSEMENT FOR FEDERAL EXCISE TAXES, BUT DOES NOT INCLUDE SALES TAXES, USE TAXES OR OCCUPATIONAL TAXES BASED ON SALES VOLUME, (FEDERAL, STATE, OR LOCAL) UNLESS EXPRESSLY SO STATED. PURCHASER ASSUMES AND AGREES TO PAY, UNLESS PROHIBITED BY LAW, ANY SUCH SALES, USE OR OCCUPATIONAL TAXES IMPOSED ON OR APPLICABLE TO THE TRANSACTION COVERED BY THIS ORDER, REGARDLESS OF WHICH PARTY MAY HAVE PRIMARY TAX LIABILITY THEREFORE.
6. FACTORY WARRANTY: ANY WARRANTY ON ANY NEW VEHICLE OR USED VEHICLE STILL SUBJECT TO A MANUFACTURER'S WARRANTY IS THAT MADE BY THE MANUFACTURER ONLY. THE SELLER HEREBY DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

USED VEHICLE WHETHER OR NOT SUBJECT TO MANUFACTURER'S WARRANTY: UNLESS A SEPARATE WRITTEN INSTRUMENT SHOWING THE TERMS OF ANY DEALER WARRANTY OR SERVICE CONTRACT IF FURNISHED BY DEALER TO BUYER. THIS VEHICLE IS SOLD "AS IS - NOT EXPRESSLY WARRANTED OR GUARANTEED" **AND** THE SELLER HEREBY DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
7. PURCHASER SHALL NOT BE ENTITLED TO RECOVER FROM DEALER ANY CONSEQUENTIAL DAMAGES, DAMAGES TO PROPERTY, DAMAGES FOR LOSS OF USE, LOSS OF TIME, LOSS OF PROFITS, OR INCOME, OR ANY OTHER INCIDENTAL DAMAGES.
8. THE PURCHASER, BEFORE OR AT THE TIME OF DELIVERY OF THE MOTOR VEHICLE COVERED BY THIS ORDER WILL EXECUTE SUCH FORMS OF AGREEMENT OR DOCUMENTS AS MAY BE REQUIRED BY THE TERMS AND CONDITIONS OF PAYMENT INDICATED ON THE FRONT OF THIS ORDER.



CIT TRUCKS - ROCKFORD (C260)
4301 N. BELL SCHOOL ROAD
LOVES PARK, Illinois 61111

Stock

Jeff Heiser
Cell Phone:
Office Phone: 815-639-2000
Email: jheiser@citrucks.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	T480 Series Conventional	Fr Axle Load (lbs):	20000
Type:	FULL TRUCK	Rr Axle Load (lbs):	23000
Description 1:	SINGLE AXLE T480 PLOW	G.C.W. (lbs):	43000
Description 2:	T480 CITY OF ROCHELLE		
Application		Road Conditions:	
Intended Serv.:	Snowplow: Vehicles which are configured	Class A (Highway)	90
Commodity:	Rock.	Class B (Hwy/Mtn)	10
		Class C (Off-Hwy)	0
Body		Class D (Off-Road)	0
Type:	Flatbed.	Maximum Grade:	6
Length (ft):	10	Wheelbase (in):	164
Height (ft):	13	Overhang (in):	65
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	69.5
		Cab to Axle (in):	94.5
Trailer		Cab to EOF (in):	159.5
No. of Trailer Axles:	0	Overall Comb. Length (in):	293
Type:			
Length (ft):	0	Special Req.	
Height (ft):	0	U.S. Domestic registry, 50-state.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Model				
0000480	S	T480 Series Conventional	108,636	10,386
0071001	O	T480 Vocational Hood	0	0
0080075	O	Dealer/Customer declines engine w/CARB Idle Emissions Reduction Feature.	0	0
0090161	O	T480 Single Rear	0	0
0098413	O	State of Registry: Illinois	0	0
Engine & Equipment				
0130207	O	PX-9 360 360@1650 1150@1200, 2021 With Turbo Exhaust Brake (VGT Brake). N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (N202 N09360 C400 252...Reserve Speed Function Reset N09200 C399 120...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (N20 N09220 C402 0.....Expiration Distance (N207) N09540 C395 0.....Expiration Distance (N209) N09260 C121 68....Max Vehicle Speed in Top Gea N09440 C234 YES...Engine Protection Shtdwn N09460 C231 NO....Gear Down Protection N09580 C133 5.....Idle Shtdwn Time N09680 C233 NO....Idle Shtdwn Override N09480 C132 1400..Max PTO Speed N09300 C128 64....Max Cruise Control Speed N09500 C239 NO....Cruise Control Auto Resume N09520 C238 NO....Auto Engine Brake in Cruise N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold N09560 C225 YES...Enable Idle Shutdown Park Br	4,179	0
1000046	O	EPA Compliant Engine	0	0
1000151	S	PremierSpec	0	0
1000243	O	Gearing Analysis: Performance power before economy results.	0	0
1000254	O	Customer's Typical Operating Spd: 65 mph.	0	0
1000684		Effective VSL Setting NA	0	0

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
1000858	O	Engine Idle Shutdown Timer Disabled	0	0
1000859	O	Enable EIST Ambient Temp Override	0	0
1000891		Eff EIST NA Expiration Miles	0	0
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0	0
1041399	S	Air Cleaner: MD Composite Engine Mounted	0	0
1093120	O	Inside/Outside Air Intake for Engine Mounted Air Cleaner	877	16
1105232	O	Fan Hub: Horton Variable Speed For use with PX engines, L9N or B6.7N natural gas engines on 2.1M only.	350	0
1121234	O	Cooling Module: 2.1M MD Vocational Hood, Clog Resistant, 1000 Square Inches	538	10
1160205	O	Bugscreen Front of grille on 2.1M MD, C500, T800, T880, and W900. Behind grille on T680 and 1.9M MD.	147	2
1247234	O	EXH: 2021 RH Under DPF/SCR with RH SOC Vertical tailpipe. Not 2.1m high roof sleepers	365	0
1290136	O	Tailpipe: 5 in. single 36 in. 45 degree curved.	195	15
1321102	S	Fuel Filter: PACCAR 2.1M MD for PX-7 or PX-9 Fuel/water separator for 2021 and later engines.	0	0
1321205	O	Run Aid:Fuel Heat *For Fuel Filter	45	0
1321305	O	Start Aid:12V Heat *For Fuel Filter	22	1
1500029	O	Kenworth Fuel Cooler Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.	168	0
1504006	O	Block heater: PACCAR 750 watt 120V for PX-7 1000 watt for PX-9 and ISL9 engines.	22	2
1816200	O	Alternator: SEG 200 amp, brush type Formerly Bosch.	-103	0
1821210	O	Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose.	153	62
1836106	S	Mitsubishi 105P55 12V Starter with Cummins and PX PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. Only for Cummins or PX engines.	0	0
1840066	O	Cab Power Cutoff SW on Cab Floor NFPA Compliant - Engine Shut off	314	2

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
1900996	O	Jump start terminals under hood.	72	0
1901020	O	Remote PTO/Throttle, 12-Pin, 500K, Back of Cab OR Back of Sleeper, J1939, Remote Control Provision	108	0
1901084	O	Body Builder Battery Power Prewire	39	0

Transmission & Clutch

2011205	O	Transmission: Allison 3000RDS 6-speed w/PTO drive gear. 5th Gen controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions. Requires a push button shift control code. Oil temperature gauge is standard on class 8 models.	5,835	399
2406453	O	Driveline: 2 Dana SPL250XL 1 centerbearing requires 3500057 interaxle driveline. Low maintenance offering from Spicer. On-highway 350K mi first service interval, 100K mi subsequent service interval on U-joint, splines lubed for life, quick disconnect end caps.	366	54
2410018	O	Torque converter included w/Allison Transmission.	0	0
2410153	O	Push Button Shifter Controls, Center Console Mounted for Allison Transmission. 2.1m Medium Duty only.	0	0
2410204	O	Allison Fuel Sense: Delete	0	0
2410244	O	J1939 Park Brake Auto Neutral	0	0
2410311	U	Decline Allison Neutral at Stop Stand-Alone	0	0
2429358	O	Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	68	0
2429378	O	Customer installed transmission PTO in the LH Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	0	0
2460069	O	Transmission Cooler: Automatic Transmission For use with 2.1M MD with Vocational Hood. Includes cooler protector.	895	38

Front Axle & Equipment

2506181	O	Dana Spicer D2000 Front Axle rated 20K standard track.	1,723	120
2641137	O	Front Brakes: 20K Meritor Q-Plus 16.5x6 in.	606	0
2690035	O	Front Brake Drum: 22,000 lbs. 16-1/2x6 in. Cast.	-227	104
2702022	O	Front Hubs Iron hub pilot 22,000 lbs. 10 Bolt 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle. Consider Wheelguards (5850002) with aluminum wheels.	329	80
2741970	S	ConMet PreSet Plus Hub package; front axle.	0	0

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
2750001	S	Hubcap: front vented.	0	0
2765001	S	Front Auto Slack Adjuster.	0	0
2865025	O	Front Springs: Taperleaf 20K w/shock absorbers w/ maintenance-free elastomer spring pin bushings.	146	76
2895305	O	Dual power steering gears: 18/20K	977	75
2899336	O	Power Steering Cooler:Radiator Mounted Air-to-Oil	324	11
2900055	O	5 mm front suspension spacer block.	0	0
2900612	O	Threaded front spring bushings in place of elastomeric.	59	0
Rear Axle & Equipment				
3061190	O	Single Dana Spicer S26-190 rear axle; 26K capacity rated at 26K. Single rear axle.	823	208
3200557	O	Rear Axle Ratio - 5.57.	0	0
3330004	S	Single Rear Brakes 16-1/2x7 in. Bendix ES-extended service S-cam.	0	0
3392001	O	Single Rear Brake heavy duty Brake Drums: cast. Use HD Gunite Drum when single axle with GAWR over 23,000 lbs is selected.	64	0
3403220	S	Single Rear Hubs: Iron hub pilot 11-1/4 in. bolt circle.	0	0
3441971	S	ConMet PreSet Plus Hub package; single rear axle.	0	0
3465001	S	Single Rear axle automatic slack adjusters.	0	0
3485007	S	Spring Brake: 3030 long stroke single 3 in. travel. Helps keep brakes in adjustment longer.	0	0
3495228	O	Bendix 4S/4M anti-lock brake system w/ air traction control (ATC).	510	2
3531001	O	Wheel Differential Lock for Dana Spicer Axles S21-170/172, S21-190, S23-170/172, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.	1,081	28
3632277	O	Rear suspension: single Hendrickson HAS230L 23K. Welded steel crossmember & gussets w/shocks at 8.3 in. laden height, 8.5 in. unladen height. Medium-duty. Includes air suspension dump valve. Not rear air disc brake compatible.	643	-59
3832313	O	Bolted rear suspension crossmembers for HAS 210/210L or 230/230L. Replaces medium duty standard.	0	0
Tires & Wheels				
4038678	O	Front tires: Goodyear G289 WHA 315/80R22.5 20PR. All position. 43.1 in. diameter. 20 in. SLR.	834	78
4277495	O	Rear tires: Bridgestone M770 11R22.5 16PR.	1,208	68

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
		42.2 in. diameter, drive. 19.6 in. SLR. Code is priced per pair of tires.		
4900004	O	Rear Tire Quantity: 4	0	0
5045280	O	Front Wheel: Alcoa 89U64 22.5X9 AL Ultra One High Polish Wheel.	486	0
5243363	O	Rear Wheel: Alcoa 88267 22.5x8.25 aluminum with Level One [TM] finish, hub-pilot mount. 7400 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels.	782	-92
5859010	O	Single Front Axle: 2 wheels Dura-Bright Mirror Polish Dura-Bright outboard surface of aluminum wheels.	236	0
5859011	O	Single Rear Axle Wheels: 2 wheels Dura-Bright Mirror Polish. Dura-Bright outboard surface of outer dual or single aluminum wheels.	355	0
5900004	O	Rear Wheel/Rim Quantity: 4	0	0
Frame & Equipment				
6056200	O	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel to 284 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	214	153
6309910	O	Delete bumper: Requires a bumper setting code.	-184	-27
6319064	O	64 in. Bumper setting. Requires a bumper code.	0	0
6321010	S	Front tow loops: Two	0	0
6390034	O	24 in. frame rail extensions. Vocational hoods only.	101	36
6391201	O	Custom Frame Layout: one chassis CFL F/T: customer wants	1,380	0
6400645	O	Battery box cantilever aluminum BOC with full polish.	457	19
6409210	O	Rubber battery pad in bottom of battery box. For cantilever-style or between the rails battery boxes.	7	0
6409902	S	Battery box location: RH Side.	89	15
6451126	O	DPF/SCR box polished end plates and polished cover.	194	0
6490139	S	Heavy-duty one-pc aluminum intermediate/fill-in crossmember.	0	0
6490433	S	Heavy-duty 5-piece rear cab support, hucked assembly. Huck fastened to frame.	0	0
6721102	S	Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	0	0

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
6722000	S	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0	0
6742009	S	Square end-of-frame w/o crossmember; non-towing.	0	0
Fuel Tanks & Equip				
7140080	O	80 US gallon D-Shape rectangular aluminum under fuel tank, replace. With non-slip step.	241	52
7722173	O	Large DEF tank, 15 gallons.	117	26
7840015	O	Polish only one aluminum tank.	141	0
7840038	O	Polished cover for 1 DEF tank any size.	229	3
7889061	O	Polished stainless steel tank straps for 1 tank.	71	0
7889203	O	DEF to fuel fill ratio 2:1 or greater.	0	0
7889368	O	Fuel tank drain plug.	3	0
7889614	O	DEF tank location is LH BOC. For 2.1M medium duty	0	0
7920080	O	Location: 80 gal fuel tank LH under cab	0	0
Cab & Equipment				
8024311	S	Cab: Stamped aluminum with curved windshield LED markers. Requires separate roof code.	0	0
8090153	O	Hood: Sloped Vocational w/ Stationary Grille w/ Chrome Crown	1,308	-24
8108002	O	Fine particulate filter for cabin air HVAC system. To provide extra filtration in high dust applications. Cabin airflow is reduced with this additional filter. *Cannot be used with code 8108003.	35	0
8108011	S	Cab HVAC - Day Cab and 40in Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0	0
8201013	S	Steering wheel: 18 in. 4-spoke.	0	0
8201200	S	Adjustable telescoping tilt steering column.	0	0
8203060	O	5 sets of keys. Replaces standard 2 sets of keys.	38	0
8205177	O	Dash Switch: 1st Allison-mntd PTO. Electric switch and wiring are factory-installed to control the 1st Allison Trans mounted PTO.	166	0



Sales Code	Std/Opt	Description	\$ List	Weight
8208495	O	Two spare switches: Wired to power.	51	0
8222400	O	Gauge: DD Virtual Gauge - Air Suspension Pressure 1	61	0
8222405	O	Gauge: DD Virtual Gauge - Fuel Filter Restriction	79	0
8222409	O	Gauge: DD Virtual Gauge - Air Filter Restriction	59	0
8222413	O	Gauge: DD Virtual Gauge - Manifold Pressure Boost	0	0
8222414	O	Gauge: DD Virtual Gauge - Engine Percent Torque	0	0
8222419	O	Gauge: DD Virtual Gauge - Volts Instrument Cluster	0	0
8282024	S	Main Instrument Package: 7" Digital Display Cluster. Includes Physical (Analog): Speedometer, Tachometer, Oil Pressure, and Coolant Temp; and Digital: Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure, and Air Application for air brake trucks.	0	0
8330591	S	Interior Trim Package: 2.1M MD Gray Foam Backing/Cloth Headliner W/Gray Sunvisor & Seat Color Three Underdash Center Console Cupholders (Two If Allison Transmission Is Selected).	0	0
8410217	O	Driver Seat: KW Premium Air Seat HB Tough Cloth w/ Dual Armrests/Susp Cover/Isolator Lever/Seat Heater	527	0
8480207	O	Rider Seat: KW Toolbox Seat HB Tough Cloth w/o Armrests	8	0
8601432	O	Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth	384	0
8698965	O	Speaker Package For Cab: (2) Speakers B-Pillar	50	0
8699933	O	CB Installation Kit: C/I Center Mtd of Header w/ Dual Antenna on LH/RH mirrors. One Jumper Harness.	178	2
8700091	O	Ashtray insert: W/cigar lighter located in center console. Deletes 1 12V outlet & 1 cupholder.	32	0
8700196	S	Turn Signal: Self-Cancelling	0	0
8700283	S	LH and RH Trip Ledge Rain Deflectors	0	0
8700663	O	Kenworth TruckTech+ The Kenworth Remote Diagnostics system provides the Worlds Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault	1,246	0

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
		severity and recommended actions. This option is Standard on all Heavy Duty Kenworths with a PACCAR MX engine, Cummins X15 engine, PX engine or Natural Gas engine. Optional on Medium Duty Kenworths.		
8800260	O	Long grabhandle RH side mounted to side-of-cab exhaust.	23	2
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0	0
8832113	S	Kenworth Daylite Door with standard LH/RH electric door locks and LH/RH electric window controls.	0	0
8841642	O	Air Horn: Dual Round 26" LH/RH Roof Incl Air Horn Cover	157	0
8850139	S	Look-Down, Pass. Door, Black 11x6	0	0
8850831	O	Mirror: RH Hood Mounted, Dual View, Round CX Chrome	99	4
8850841	O	Mirror Shell: Dual Aero Chrome	150	0
8860852	O	Mirror: Dual KW Aero Rear View Motor, heated with Integral CX	67	0
8871446	S	Rear cab stationary window 19in x 36in	0	0
8879917	O	Two additional outboard windows 19in x 12in	107	10
8890101	S	One-piece bonded-in windshield with curved glass. Standard.	0	0
8890135	O	Exterior stainless steel sunvisor.	700	11
8890356	O	4 1/4" Molded Wheelwell Fender Extension.	196	0
8890874	O	Kenworth Cab Air Suspension.	103	0
8891009	O	Thermal/Sound Insulation Package	244	0
8891011	O	Roof: Raised Profile, Stamped Aluminum w/ Additional Head Room & Interior Overhead Storage	43	0
Lights & Instruments				
9010813	O	Headlamps: Single Halogen Complex Reflector w/ Turn Indicator, Reflector and w/o DRL. Fender Mtd.	-8	0
9010951	O	Daytime Running Lights Located in Bumper. Driven by Chassis Height.	288	0
9022137	S	Marker Lights: Five, rectangular, LED	0	0
9030052	S	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.	0	0
9080135	O	Stainless Steel Brackets, Switch & Wiring: Customer-installed dual beacon lights mounted over door of cab.	217	4

Price Level: April 1, 2021

100% Complete

Date: December 15, 2021

Deal: SINGLE AXLE T480 PLOW

Quote Number: QUO-809821-W3L2S0

Printed On: 12/15/2021 3:31:25 PM

Sales Code	Std/ Opt	Description	\$ List	Weight
9090007	O	Override Switch: For daytime running lamps.	39	0
9090058	O	Switch & Wiring: For customer-installed plow light. Includes circuit breaker.	175	0
9090142	O	Wiring Only: For customer-installed backup alarm.	46	0
9090151	O	Wiring:Cust. Install Trlr Elec. Brake Controller. Class 8/T4 Content Includes Dash Signals: Ignition Power (20A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To EOF Junction Box. These Signals Are Located Near The NavPlus HD Area. No Need To Code For An Additional End of Frame Junction Box. EOF Junction Box Signals Are: Ground, Tail Lamp, Marker Lamp, Left Turn, Right Turn, Stop Lamp and Electric Trailer Brake Controller Wired To Dash. Medium Duty (not T4) Content Includes A MP 280 Series Connector In Dash Near Driver Door Connections With Signals: Battery Power (40A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To Chassis Connector. Medium Duty (not T4) 2 Way Deutsch Chassis Connector Located Near Back of Cab, With Signals: Ground and Electric Trailer Brake Controller Wired To Dash Connector.	153	4
9090302	O	Junction Box: Mounted Behind Cab or Sleeper Not Mounted at End of Frame.	127	1
9090312	O	Body Builder Lighting Harness Coiled End Of Frame For Additional Customer Installed Exterior Lighting. Harness Includes Circuits for Additional Customer Installed Tail Lamps, Turn Lamps, Stop Lamps, and Marker Lamps.	133	0
9090849	O	Polyswitches replacing fuses. Switch will automatically reset after removal of excess load.	44	0
Air Equipment				
9101219	O	Air Dryer: Bendix AD-HF Extended Purge Heated With Puraguard	24	0
9108001	S	Moisture ejection valve w/ pull cable drain.	0	0
9140020	S	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0	0
9140252	O	Locate air dryer inside LH rail BOC. This code requires the use of a custom frame layout code.	0	0
9150170	O	Air tanks: aluminum replacing steel all tanks. *Not air tanks on lift axles.	370	-44
Extended Warranty				
9200002	O	Base Warranty - Severe Service 12 months / 50,000 miles / 80,000 km.	0	0
9200008	S	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0	0
9212621	O	24 Month TruckTech+ Subscription for PACCAR PX Engines	0	0
9220001	O	Base Warranty: Emissions 5YR/100K MI - EPA Engine (Does not include CARB Clean Idle sticker)	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
Miscellaneous				
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0	0
9490003	O	Additional lead time required for off highway & /or specialty component truck.	0	0
9490206	O	Warning triangle reflector kit: Shipped loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	41	4
9490404	O	One 5 lb. dry chemical type fire extinguisher mounted outboard of driver seat. Class ABC.	117	11
9490645	O	Zinc Phosphate frame rail paint processing. Requires frame rail code. Code is for 1 pair of rails.	304	0
9491659	S	VMUX Architecture	0	0

Promotions

Paint

9700000	O	Paint color number(s).	0	0
		N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK		
9943050	S	Day Cab Standard Paint	0	0
9944820	S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0	0

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)	\$145,491
Marketing and Service Support Fee	\$815
Prepaid Freight	\$2,625
Total Surcharge/Options Not Subject To Discount	\$0
Total Weight	11,948

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

Price Level: April 1, 2021 100% Complete Date: December 15, 2021
Deal: SINGLE AXLE T480 PLOW Quote Number: QUO-809821-W3L2S0
Printed On: 12/15/2021 3:31:25 PM

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Shipping Destinations**Intermediate Destination:**

Final Destinations	Quantity
--------------------	----------



1385 Franklin Grove Rd
Dixon, IL 61021
815-284-3819 * 815-284-8815 Fax
800-851-9664
www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
Order Date: 11/29/2021



**Delivery Ticket only do not
remit from the Sales Order.
Invoice will arrive in the mail.**

Bill To: 0009562
CIT TRUCKS, LLC
4301 N BELL SCHOOL RD
LOVES PARK, IL 61111

Ship To: 4155
CITY OF ROCHELLE
420 N 6TH ST
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@citrucks.com
Confirm To: OZZY Comment:

Phone:
Fax:

Customer P.O.	Ship VIA	F.O.B.	Terms
---------------	----------	--------	-------

Net 10 Days

Ordered	Unit	Item Number	D/S	Each Price	Extended Price
1.00	EACH	TRUCK PACKAGE		103,781.00	103,781.00

APPLICATION: ONE NEW KENWORTH T370 SINGLE AXLE CLASS 7 SNOW AND ICE TRUCK WITH A 102" CAB TO AXLE MEASUREMENT. AUTOMATIC TRANSMISSION WITH LIVE PTO PROVISIONS, FACTORY SNOW PLOW PREP PACKAGE, FACTORY GROUND SPEED CONNECTION POINT. FACTORY FRAME EXTENSIONS ARE REQUIRED.

INCLUDES INSTALLATION OF THE FOLLOWING EQUIPMENT:

- DUMP BODY
- CAB SHIELD INSTALLED ON BODY
- HYDRAULIC SYSTEM
- ELECTRICAL & LIGHTING
- CONSOLE AND CONTROLS
- REAR TOWING HITCH
- PLOW HITCH
- SNOW PLOW
- WING, (MID-MOUNTED JUNIOR)
- UNDER TAILGATE SPREADER
- PREWET SYSTEM, (MOUNTED BEHIND CAB)

THE FOLLOWING ADDITIONAL ITEMS ARE INCLUDED:

- VIBRATOR INSTALLED (NEW VIBRATOR)
- FRAME COATING, (NOX-RUST 1523 UNDERCOATING)
- GREASE BANK AT REAR OF BODY OR FRAME TO GREASE ALL HINGE POINTS OF BODY

INSTALLED EQUIPMENT DETAILS ARE LISTED BELOW:

1.00	EACH	/PRODUCTS SURCHARGE		131.96	131.96
------	------	---------------------	--	--------	--------

BASE TRUCK PACKAGE SURCHARGE

1.00	EACH	DUMP BODY			
------	------	-----------	--	--	--

- DURAClass 10'-0" 201-2B STAINLESS DUMP BODY
- CROSSMEMBERLESS
- DOUBLE ACTING UNDER BODY HOIST
- 10" I-BEAM LONGSILLS OF CARBON STEEL
- 1/4" AR450 ABRASION RESISTANT FLOOR
- 28" 10 GA 201-2B STAINLESS SIDES-(ONE HORIZONTAL BRACE)
- 38" 10 GA 201-2B STAINLESS FRONT



1385 Franklin Grove Rd
Dixon, IL 61021
815-284-3819 * 815-284-8815 Fax
800-851-9664
www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
Order Date: 11/29/2021



**Delivery Ticket only do not
remit from the Sales Order.
Invoice will arrive in the mail.**

Bill To: 0009562
CIT TRUCKS, LLC
4301 N BELL SCHOOL RD
LOVES PARK, IL 61111

Ship To: 4155
CITY OF ROCHELLE
420 N 6TH ST
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
Confirm To: OZZY **Comment:**

Phone:
Fax:

Customer P.O.	Ship VIA	F.O.B.	Terms		
			Net 10 Days		
Ordered	Unit	Item Number	D/S	Each Price	Extended Price
		- 38" 10 GA 201-2B STAINLESS VERTICAL TAILGATE-(6 PANEL DESIGN)			
		- 201-2B STAINLESS CORNER POST			
		- ELECTRIC OVER AIR T-GATE LATCH			
		- UN-PAINTED STAINLESS TO BE CLEANED AND PASSIVATED			
		- GREASABLE TAILGATE LINKAGE INCLUDING UPPER HINGE			
		- TAILGATE LATCH MANUAL OVERRIDE INSTALLED			
		- STAINLESS STEEL TAILGATE LATCH LINKAGE			
		- LABOR TO INSTALL CUSTOM CAB SHIELD			
		- 3 RUNG FOLDING LADDER INSTALLED			
		- RIGID REAR RUBBER MUD FLAPS INSTALLED			
		- RUBBER FRONT MUD FLAPS INSTALLED			
		- STAINLESS CHAIN HOOKS ON LOWER CENTER OF T-GATE			
		- (2) OBLONG LIGHT HOLE CUTOUTS IN EACH CORNER POST			
		- MOUNTING HOLES FOR (1) FEDERAL MICROPULSE FLASHER IN EACH CORNER POST			
		- CONDUIT FOR WIRING CAB SHIELD LIGHTS			
		- 1/4X2 FLAT BAR SIDE RAIL INSTALLED			
		- PREPPED FOR NEW TAILGATE SPREADER			
		- 12" WIDE STAINLESS SPILL PAN INSTALLED			
		- VIBRATOR INSTALLED			
		- 2X10 OAK SIDE BOARDS (RAW OAK) INSTALLED			
1.00	EACH	/PRODUCTS SURCHARGE		549.76	549.76
		DUMP BODY SURCHARGE			
1.00	EACH	CAB SHIELD			
		CAB SHIELD - CUSTOM FABRICATED FOR SPECIFIED TRUCK AND BODY. CONFIGURED AS FOLLOWS:			
		*MATERIAL IS TO BE 201 STAINLESS STEEL.			
		*PAN WIDTH- 18".			
		*WIDTH- DETERMINED.			
		*HEIGHT TO BE DETERMINED TO BOTTOM OF PAN.			
		*4 FRONT FACING EVENLY SPACED OBLONG LIGHT HOLES.			
		*4 REAR FACING OBLONG LIGHT HOLES.			
		*1 SIDE FACING OBLONG LIGHT HOLE IN EACH SIDE FACING OUT.			
		*UNPAINTED.			
		*STAINLESS STEEL TO BE ELECTROCHEMICALLY CLEANED AND PASSIVATED.			
		**LIGHTING CODE: 44112			
1.00	EACH	/PRODUCTS SURCHARGE		64.98	64.98

CAB SHIELD SURCHARGE



1385 Franklin Grove Rd
Dixon, IL 61021
815-284-3819 * 815-284-8815 Fax
800-851-9664
www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
Order Date: 11/29/2021



**Delivery Ticket only do not
remit from the Sales Order.
Invoice will arrive in the mail.**

Bill To: 0009562
CIT TRUCKS, LLC
4301 N BELL SCHOOL RD
LOVES PARK, IL 61111

Ship To: 4155
CITY OF ROCHELLE
420 N 6TH ST
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
Confirm To: OZZY Comment:

Phone:
Fax:

Customer P.O.	Ship VIA	F.O.B.	Terms
---------------	----------	--------	-------

Net 10 Days

Ordered	Unit	Item Number	D/S	Each Price	Extended Price
---------	------	-------------	-----	------------	----------------

1.00	EACH	HYDRAULIC SYSTEM			
------	------	-------------------------	--	--	--

- PTO: OMFB 278 SERIES
- PUMP: TXV92
- ADD-A-STACK HYDRAULIC VALVE TO OPERATE:
HOIST, PLOW, WING, PREWET, AUGER, SPINNER
- APSCO AIR CONTROLS
- "FORCE" 5100EX ELECTRONIC SPREADER CONTROLLER
- "FORCE" VT35 STAINLESS STEEL TANK AND LID
- LOW OIL/HIGH TEMP AUTO SHUTDOWN SYSTEM
- EATON HP171 SERIES HIGH PRESSURE FILTER
- CLOSED LOOP PREWET CABLE
- CLOSED LOOP GRANULAR SENSOR

- BONNELL CONSOLE TO INCLUDE LEVERS:
- HOIST -- SINGLE AXIS LEVER W INTERLOCK
- PLOW LIFT -- SINGLE AXIS LEVER
- PLOW ANGLE -- SINGLE AXIS LEVER
- WING TOE -- SINGLE AXIS LEVER
- WING HEEL -- SINGLE AXIS LEVER

1.00	EACH	/PRODUCTS SURCHARGE		485.08	485.08
------	------	----------------------------	--	--------	--------

HYDRAULICS SURCHARGE

1.00	EACH	ELECTRICAL			
------	------	-------------------	--	--	--

- ALL LED LIGHTING UNLESS OTHERWISE NOTED
- BONNELL IGNITION ACTIVATED BATTERY RELAY DISCONNECT SYSTEM
- InPOWER STANDARD 8 SWITCH PANEL WITH 4 WARNING LAMPS AND 16
OUTPUTS
- DATA SHEET REQUIRED
- BODY UP SWITCH WITH INDICATOR LAMP
- BONNELL WIRE HARNESSSES
- ELECTRIC BRAKE CONTROLLER INSTALLED
- CAB ROOF LIGHTING AND ACCESSORIES
- FACTORY SUPPLIED ROOF BRACKET
- CAB MOUNTED PLOW LIGHTS AND WORK LIGHTS - WORK LIGHT TO COME ON
WITH HIGH BEAM ONLY
- HEATED WIPERS INSTALLED
- PLOW LIGHTING



1385 Franklin Grove Rd
Dixon, IL 61021
815-284-3819 * 815-284-8815 Fax
800-851-9664
www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
Order Date: 11/29/2021



**Delivery Ticket only do not
remit from the Sales Order.
Invoice will arrive in the mail.**

Bill To: 0009562
CIT TRUCKS, LLC
4301 N BELL SCHOOL RD
LOVES PARK, IL 61111

Ship To: 4155
CITY OF ROCHELLE
420 N 6TH ST
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
Confirm To: OZZY Comment:

Phone:
Fax:

Customer P.O.	Ship VIA	F.O.B.	Terms
			Net 10 Days

Ordered	Unit	Item Number	D/S	Each Price	Extended Price
		- ABL-3830-0080 LED PLOW LIGHTS ON BODY LIGHTING - FOUR FRONT FACING OBLONG AMBER FLASHERS ON CABSHIELD, EVENLY SPACED - ONE PAIR REAR FACING OBLONG STT ON CABSHIELD - ONE PAIR REAR FACING OBLONG AMBER/WHITE FLASHERS ON CABSHIELD - ONE AMBER/WHITE FLASHER ON EACH END OF CABSHIELD - ONE PAIR OBROUND STT IN REAR POSTS - ONE PAIR OBLONG AMBER/WHITE FLASHERS IN REAR POSTS - MARKER LIGHTS PER FMVSS STANDARDS REAR HITCH AND CHASSIS LIGHTING - ONE PAIR 4" ROUND STT LIGHTS ON REAR HITCH - ONE CENTER OBROUND BACKUP LIGHT ON REAR HITCH - PM-290C LICENSE PLATE LIGHT ON REAR HITCH - ICC THREE LIGHT CLUSTER ON REAR HINGE OF BODY - VEL-697112 BACK UP ALARM ON REAR HITCH OR FRAME EQUIPMENT WORK LIGHTS AND FLASHERS - ABL WORK LIGHT MOUNTED UNDER CORNER POST ON DRIVERS SIDE AIMED AT SPINNER - ABL WING WORK LIGHT MOUNTED ON STEP - ABL WING WORK LIGHT MOUNTED ON PREWET TANK BRACKET			
1.00	EACH	/PRODUCTS SURCHARGE		162.54	162.54
		ELECTRICAL SURCHARGE			
1.00	EACH	REAR HITCH			
		- REAR HITCH TYPE: CUSTOM REAR HITCH PER BELOW - 3/4" CARBON STEEL PLATE - 40K PH20 PINTLE HITCH-DIRECT MOUNTED - STD PINTLE MTG HEIGHT - TRAILER PLUG: 7 FLAT PIN RV STYLE - CUTOUTS FOR (2) 4" ROUND STT & (1) BACKUP - 2-BOLT TOW HOOKS INSTALLED - 5/8" CARBON STEEL D-RINGS - SEE CUSTOM DRAWING FOR HITCH MEASUREMENTS TO CLEAR PAVER			
1.00	EACH	/PRODUCTS SURCHARGE		30.83	30.83



1385 Franklin Grove Rd
Dixon, IL 61021
815-284-3819 * 815-284-8815 Fax
800-851-9664
www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
Order Date: 11/29/2021



**Delivery Ticket only do not
remit from the Sales Order.
Invoice will arrive in the mail.**

Bill To: 0009562
CIT TRUCKS, LLC
4301 N BELL SCHOOL RD
LOVES PARK, IL 61111

Ship To: 4155
CITY OF ROCHELLE
420 N 6TH ST
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
Confirm To: OZZY Comment:

Phone:
Fax:

Customer P.O.	Ship VIA	F.O.B.	Terms
			Net 10 Days

Ordered	Unit	Item Number	D/S	Each Price	Extended Price
REAR HITCH SURCHARGE					
1.00	EACH	PLOW HITCH HITCH FOR SNOW PLOW PLOW HITCH FOR A KENWORTH T370 WITH FRAME EXT. INSTALLED ON NEW TRUCK PACKAGE			
1.00	EACH	HFF-QX Heavy Front Frame Side Plate Hitch with QX Front Frame and Offset Lift Arm. (QAC Drop Pin Receiver with built in Two Pin Hookup.)			
1.00	EACH	H10170 4in X 10in Double Acting Cylinder W/Nitrided Rod			
1.00	EACH	H10310 Stainless Hood Mounted Light Brackets. (Side of Hood)			
1.00	EACH	H10400 1/2in Side Plates. (Included in Standard Price of Side Plate Hitch)			
1.00	EACH	H10420 Cross Over Relief Valve Kit (Installed or Not Installed)			
1.00	EACH	H10435 Steel Channel Bumpers			
1.00	EACH	/PRODUCTS SURCHARGE		262.60	262.60
PLOW HITCH SURCHARGE					
1.00	EACH	PLOW CONFIGURED AS FOLLOWS: YES PAINTED: ORANGE POLYURETHANE ENAMEL NO EXTRA RIBS EXTRA RIBS			
1.00	EACH	11ST49TT7 Base Model 11ST49TT7			

Continued



1385 Franklin Grove Rd
 Dixon, IL 61021
 815-284-3819 * 815-284-8815 Fax
 800-851-9664
 www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
 Order Date: 11/29/2021



**Delivery Ticket only do not
 remit from the Sales Order.
 Invoice will arrive in the mail.**

Bill To: 0009562
 CIT TRUCKS, LLC
 4301 N BELL SCHOOL RD
 LOVES PARK, IL 61111

Ship To: 4155
 CITY OF ROCHELLE
 420 N 6TH ST
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
 Confirm To: OZZY Comment:

Phone:
 Fax:

Customer P.O.		Ship VIA	F.O.B.	Terms	
				Net 10 Days	
Ordered	Unit	Item Number	D/S	Each Price	Extended Price
		Straight Steel Snow Plow 11'-0" Cutting Edge X 49" Straight Height Torsion Trip Cutting Edge (4) 7/8" Round Wire Trip Springs Metropolitan Table/A-Frame Assembly (2) 3X10 Reversing Cylinders (5) Table To Moldboard Hookup Points			
1.00	EACH	P10130			
		Level Raise Lift System with Lift Chains for High Country Plows (MX1 & MC1)			
1.00	EACH	P10210			
		Quick attach loop (plow section installed)			
1.00	EACH	P10400			
		3/4" Bottom Angle (ILO Standard)-Moldboard Weldment Angle			
1.00	EACH	P10401			
		3/4" Bottom Angle (ILO Standard) Trip Edge Angle (for trip edge plows)			
1.00	EACH	P10425			
		3/8" x 12" Rubber flap kit installed			
1.00	EACH	P10465			
		Plow stand - installed (to hold hook up point @ desired height when detached)			
1.00	EACH	P10470			
		36" Blaze orange markers			
1.00	EACH	P10527			
		PolarFLEX Carbide Cutting Edge System, Front Mount. (Installed on plow)			
1.00	EACH	P10555			
		1/2" Quick Couplers installed (one set/per plow) pioneer PHD-4000-4			
1.00	EACH	/PRODUCTS SURCHARGE		908.02	908.02

Continued



1385 Franklin Grove Rd
 Dixon, IL 61021
 815-284-3819 * 815-284-8815 Fax
 800-851-9664
 www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
 Order Date: 11/29/2021



**Delivery Ticket only do not
 remit from the Sales Order.
 Invoice will arrive in the mail.**

Bill To: 0009562
 CIT TRUCKS, LLC
 4301 N BELL SCHOOL RD
 LOVES PARK, IL 61111

Ship To: 4155
 CITY OF ROCHELLE
 420 N 6TH ST
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
Confirm To: OZZY Comment:

Phone:
 Fax:

Customer P.O.	Ship VIA	F.O.B.	Terms
			Net 10 Days

Ordered	Unit	Item Number	D/S	Each Price	Extended Price
---------	------	-------------	-----	------------	----------------

PLOW SURCHARGE

1.00	EACH	WING BONNELL WING PLOW - WING PLOW PAINTED ORANGE, CONFIGURED AS FOLLOWS:			
1.00	EACH	8NTWMMJ Mid Mounted Junior Wing 8'-0" Long At The Cutting Edge Non-Trip Moldboard Leading Edge Height 26" Discharge End Height 26" Painted as Specified			
1.00	EACH	W10115 12in Stroke on Front post cylinder (Toe) (8in benching height) (Patrol wing only)			
1.00	EACH	W10160 Wing lock valve - installed to cylinder			
1.00	EACH	W10190 24in Jumbo blade guide on discharge end with bolt on bracket			
8.00	EACH	W10500 Standard 3/4in x 6in C1084 Steel Cutting Edge			
1.00	EACH	W10532 3/4" x 6" Tapered Wing curb shoe (Installed on Leading end of Plow) (Standard on all wings)			
1.00	EACH	/PRODUCTS SURCHARGE		469.54	469.54

WING SURCHARGE

1.00	EACH	UT SPREADER - UNDER TAILGATE SPREADER CONFIGURED AS FOLLOWS:			
1.00	EACH	U696-DD-S2			

Continued



1385 Franklin Grove Rd
Dixon, IL 61021
815-284-3819 * 815-284-8815 Fax
800-851-9664
www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
Order Date: 11/29/2021



**Delivery Ticket only do not
remit from the Sales Order.
Invoice will arrive in the mail.**

Bill To: 0009562
CIT TRUCKS, LLC
4301 N BELL SCHOOL RD
LOVES PARK, IL 61111

Ship To: 4155
CITY OF ROCHELLE
420 N 6TH ST
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
Confirm To: OZZY Comment:

Phone:
Fax:

Customer P.O.		Ship VIA	F.O.B.	Terms	
				Net 10 Days	
Ordered	Unit	Item Number	D/S	Each Price	Extended Price
		Under Tailgate Spreader 6" Auger X 4" Pitch X 96" Overall length Direct Drive Motor with 22.6 CI displacement 201 Stainless Steel Includes Mounting Kit and Tailgate Shields Unpainted unless Otherwise Specified			
1.00	EACH	U10100 Single Drop Port 24in From Left End Of The Spreader. Standard On A 6in Spreader. Reverse Flighted Auger			
1.00	EACH	U10200 Single Spinner Assembly Mounted At Standard Drop Port. (Standard On All Spreaders). 18" Poly Spinner with 2.8 Cubic Inch Spinner Motor			
1.00	EACH	U10390 72" Spray Bar Installed In Spreader Body			
1.00	EACH	/PRODUCTS SURCHARGE		206.78	206.78
		UNDER TAILGATE SPREADER SURCHARGE			
1.00	EACH	PREWET SYSTEM BONNELL CONFIGURED PREWET SYSTEM - PREWET SYSTEM CONFIGURED AS FOLLOWS:			
1.00	EACH	BC-120P-1-150 Behind the Cab Prewet System with one 120 Gallon Poly Tank, Stainless Steel Tank Brackets, and 1-1/2in Plumbing.			
1.00	EACH	L10120 Hydraulic Prewet Pump in a Stainless Enclosure to Operate a Closed Loop System. Includes an IP68 Wire Connection for Feedback Signal.			
1.00	EACH	L10315 2in Male Quick Fill Kit Installed.			
1.00	EACH	L10355 Flush Kit. (Includes small poly flush tank) Installed.			
1.00	EACH	/PRODUCTS SURCHARGE		298.78	298.78



1385 Franklin Grove Rd
 Dixon, IL 61021
 815-284-3819 * 815-284-8815 Fax
 800-851-9664
 www.bonnell.com * info@bonnell.com

Quote

Order Number: 0153947
 Order Date: 11/29/2021



**Delivery Ticket only do not
 remit from the Sales Order.
 Invoice will arrive in the mail.**

Bill To: 0009562
 CIT TRUCKS, LLC
 4301 N BELL SCHOOL RD
 LOVES PARK, IL 61111

Ship To: 4155
 CITY OF ROCHELLE
 420 N 6TH ST
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com
 Confirm To: OZZY Comment:

Phone:
 Fax:

Customer P.O.		Ship VIA	F.O.B.	Terms	
				Net 10 Days	
Ordered	Unit	Item Number	D/S	Each Price	Extended Price

PREWET SYSTEM SURCHARGE

15% RESTOCKING FEE ON RETURNED ITEMS
NO RETURNS ON ELECTRICAL ITEMS

BS1

Net Order:	107,351.87
Less Discount:	0.00
Freight:	0.00
Sales Tax:	0.00
Order Total:	107,351.87
Less Deposit:	0.00
Order Balance:	107,351.87

Please Pay From Invoice
 1-1/2% Per Month (18% Annual Rate) Finance Charge Will Be Added to Past Due Accounts
 Salesperson: 0005 TOM MASSEY