

SANGER CIRCLE PH 7A

PD SUMMARY

Purpose Statement - To rezone approximately 1.283 acres from PD 07-01-24 along with approximately 0.628 acres from agriculture to a new PD for the property described by metes and bounds on Exhibit "A" (the "Property") of this PD Ordinance. Development and use of the Property shall comply with the Sanger Zoning Ordinance as it existed on the date of its adoption on August 3, 1987 and subsequent amended (the "The Zoning Ordinance") and this PD ordinance. In the event of a conflict between the Zoning Ordinance and this PD Ordinance, this PD ordinance shall control.

PROPOSED USES

Single Family (1.911 Acres)

1.911 acres are proposed as single family detached uses. The gross density is 5.2 units/acre.

COMMUNITY FEATURES

This PD will be a part of the mandatory homeowner's association for Sanger Circle Phase 7.

RESIDENTIAL LAND USES

I. Lot Sizes, Setbacks, etc. for Single Family Detached. Except as otherwise provided below, detached single family residences shall comply with Section 53, "R-1" RESIDENTIAL DISTRICT -1 of the Zoning Ordinance, subject to the following changes:

A. Minimum Lot Width, Depth, and Size.

The Manor Lots (50' X 120'):

The minimum lot width shall be 50 feet. The minimum lot depth shall be 120 feet. The minimum lot size shall be 6,000 square feet.

B. Minimum House Size.

The minimum air-conditioned area within each residence shall be 1,650 square feet. The Manor Lots shall place a limit of 20% of the total lot count to be below 2,000 square feet. No more than 10% shall be between 1,650 square feet to 1,800 square feet.

C. Maximum Height.

The maximum building height shall be 2 stories or 35 feet.

D. Front Yard Setback.

The minimum front yard building setback shall be twenty-five feet (25'). Front porches and architectural features such as stoops, overhangs, courtyard walls, masonry chimneys and bay windows may extend into the front yard a maximum of five feet (5').

E. Side Yard Setback.

The minimum side yard building setback shall be five feet (5') on each side. A side yard adjacent to a street on a corner lot shall always have a minimum ten-foot (10') side yard building setback.

F. Rear Yard Setback.

The minimum rear yard building setback shall be twenty feet (20') from the rear facade of the residence (excluding porches and projecting architectural features) to the rear lot line. Porches and architectural features such as stoops, overhangs, courtyard walls, masonry chimneys and bay windows may extend into the rear yard a maximum of five feet (5').

G. Maximum Lot Coverage.

The maximum lot coverage will be 65% for any residential lot.

H. Garages.

An enclosed parking area of at least four hundred square feet shall be provided for a garage (this does not count towards the minimum house size). The face of a garage door must be located at least 20 feet from the street right-of-way line that the garage door faces. The garage door does not have to be behind the street facing façade of the house. Split garage doors with a separate door for each vehicle bay are not required.

I. Design Elements

All residential dwellings will meet the City of Sanger Exterior Façade Design Criteria Manual as adopted on October 7, 2019, except as noted below:

1.3 Garages shall be a minimum of 400 square feet. Any garage facing a public street may not extend more than 15 feet beyond the house front or front porch, whichever is closer. On non-typical lots where site constraints are present, a variance to the maximum 15 feet garage extension beyond house front may be approved by the Director of Development Services or through an alternative façade permit application by the City Council.

1.4 All walls, except gabled roof areas, which are on the front façade and face a street other than an alley must contain at least 25% of the wall space in windows and doors. The garage door shall count as a “door” towards the 25% requirement.

In lieu of side yard walls on corner lots requiring windows and doors comprising of 25% of the wall space, a corner lot shall comply with the following:

1. A side yard wall on a corner lot facing a street shall consist of at least 2 windows or doors totaling 25 square feet in aggregate area.
2. On corner lots, side yard fencing facing residential streets and the adjacent gate return, shall be a stained 6-foot-tall cedar board-on-board fence with a decorative top cap and metal posts. Posts and hardware shall be on the internal side of the fence and not viewed from the public ROW.
3. On corner lots, fencing facing a collector or arterial street shall be a 6-foot masonry wall with columns.
4. On corner lots, front fencing or gates that face a primary street shall be set back from the front façade a minimum of 10 feet but no more than 15 feet.
5. If a window of any size is not installed on the side of a house on a corner lot between the front build line and side yard fence return, shrubs of a minimum of 3 gallons in size shall be planted between front build line and fence return at a spacing of 4 feet on center. In addition, one 3-inch caliper eastern red cedar (*Juniperus virginiana*), or other evergreen tree species approved by the Director of Development Services, shall be planted at the longitudinal midpoint between the front build line and fence return.

II. General Conditions.

- A. For the purposes of determining compliance with the lot width requirements, lot widths shall be measured at the rear of the required front yard setback as shown on the Final Plats.
- B. Sidewalks may be located outside of the public right-of-way if located within an adjacent open space lot with a pedestrian access easement to provide for meandering sidewalks and trails that may be located within adjacent common area lots or to preserve existing trees along perimeter roads.

III. Residential Single Family Detached Landscape Requirements. Except as otherwise provided below, landscape requirements shall comply with Section 48, Landscape Regulations of the Zoning Ordinance, subject to the following changes:

The following requirements apply to single family residential development:

- A. Each single-family residence shall have an irrigation system in the front yard and street corner side yard with a freeze sensor regulator shut off.
- B. Each Home lot shall have a minimum of two shade trees that are at least three inches in caliper planted. The trees shall be planted in the front and rear yard. If the lot fronts or sides onto a common area lot, the front yard requirement may be satisfied with the trees located in the adjacent greenspace. No other front yard or side yard tree planting requirement shall apply.
- C. All required trees shall be selected from a tree list approved during the Preliminary Plat stage.
- D. Each Home lot shall have a minimum of twelve (12) shrubs placed in the front yard. Individual shrubs shall be a minimum of three (3) gallons in size when planted.

IV. Open Space

- A. A Park Fee will be paid in lieu of park land dedication for the 10 lots proposed in this PD.
- B. All interior residential street rights-of-way shall be improved with sidewalks that are a minimum of four feet in width and (1) constructed by the homebuilders at the time of adjacent house construction; or (2) constructed by the developer for all non-buildable lots. All sidewalks along Collector and Arterial Road frontages are to be five feet in width.

V. Fencing Requirements

- A. Floodplain, parks, open spaces, right-of- way shall be exempt from the screening requirements in this Section; however, tubular steel fencing may be installed in these areas at the developer's option.
- B. Homebuilder side yard and back yard fencing on residential lots shall be a maximum of six feet in height and shall be setback a minimum of five feet from the front building line shown on the Concept Plan.
- C. Fencing on all residential lots abutting an open space lot or greenbelt shall be restricted to tubular steel painted black. No solid fencing other than a brick and/or stone masonry courtyard wall under 42 inches shall be permitted abutting an open space lot or greenbelt; however, landscape borders, included trimmed hedges, are permitted.
- D.

VI. Street Typology

- A. Standard curbs will be required adjacent to streets abutting all residential lot types unless otherwise approved by the City's engineering department.
- B. Streets fronting open space lots must have standard curbs adjacent to the common area lot. Streets adjacent to common area lots may provide for on-street parking. In addition, the street faces adjacent to open spaces near the flood plain will have a maintenance access location.
- C. Developer shall work with City to determine the location and number of stop signs within the subdivision and speed limits to facilitate traffic calming and maximum the benefit from the pedestrian system.

VII. Utilities and Equipment

- A. Electrical and gas utility meters and AC condensers should be unobtrusively located beyond the front or side street facade zone and screened from view from adjacent streets or common open spaces with landscaping or appropriate fencing.
- B. Transformers on individual lots should be screened to minimize visual impact.
- C. Satellite dishes and solar panels should be located in less conspicuous locations and out of view from adjacent streets or common open spaces when possible.
- D. Antennas should be located inside the building when possible.
- E. Solar panels, when visible from the front, should be flush with the roof.
- F. All public utility easements (PUE) shall be a minimum of 15 feet in width. All franchise utility easements (FUE) shall be a minimum of 10 feet in width.

VIII. Home Variety

- A. Detached home designs with the same or similar facade, materials, or colors should be separated by a minimum of three lots on the same side of the street and should not be located directly across or diagonally across the street from each other.
- B. If a detached home plan is repeated on an adjacent lot, it should be elevated with a different architectural style or two of the following three elevation changes - brick color, roof color, or flipped plan.