



Peterbilt of Utah, Inc. - 1910 S. 5500 W. - Salt Lake City, UT 84104 - PH: 801-486-8781

December 31, 2024

Prepared For: San Juan County

Prepared By: Doug Jarvis
Peterbilt of Utah

Jed,

Thank you for giving us this opportunity to provide a proposal for you truck needs. As you already know, Peterbilt assembles the highest quality trucks in the industry. Attention to quality also provides the lowest cost of ownership for our customers. Peterbilt of Utah is committed to providing the highest level of service to support your transportation needs.

2026 Peterbilt 567 Hook Chassis

\$ 149,969.00 Chassis Sale Price

State Contract # MA3321

Options:

We appreciate the opportunity to quote your company these units. Please indicate your acceptance of this proposal by signing below.

X _____ Accepted

Date: ____/____/____

X _____ Salesman



Peterbilt Of Utah (P250)
1910 S. 5500 West
Salt Lake City, Utah 84104

State Of Utah
4501 S 2700 W
Taylorsville, Utah 84119
United States of America

Doug Jarvis
Cell Phone:
Office Phone: 801-486-8781
Email: djarvis@jgpete.com

Vehicle Summary

Unit		Chassis	
Model:	Model 567	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	40000
Description 1:	San Juan County Hook	G.C.W. (lbs):	66000
Description 2:	12-12-24		
Application		Road Conditions:	
Intended Serv.:	Utility/Lube Service	Class A (Highway)	50
Commodity:	Other Commodity	Class B (Hwy/Mtn)	50
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Winch or Crane	Wheelbase (in):	261
Length (ft):	26	Overhang (in):	75
Height (ft):	12	Fr Axle to BOC (in):	74.1
Max Laden Weight (lbs):	1000		
Trailer		Cab to Axle (in):	186.9
No. of Trailer Axles:	0	Cab to EOF (in):	261.9
Type:		Overall Comb. Length (in):	383.23
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2025
Deal: San Juan County Hook
Printed On: 12/31/2024 12:56:31 PM

100% Complete

Date: December 31, 2024
Quote Number: QUO-1149571-Y7Q8V3



Sales Code	Std/Opt	Description	Weight
Base Model			
0005671	S	Model 567 The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	14,800
0091200	S	Other Commodity	0
0093140	O	Utility/Lube Service Truck used to service construction and mining equipment. Includes bodies such as, mechanics service bodies, tire hoists, fuel/lube, boom, etc.	0
0095050	O	Winch or Crane	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0
Configuration			
0200700	S	Not Applicable Secondary Manufacturer	0
Frame & Equipment			
0514020	O	10-3/4" Steel Rails 355-384" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	528
0601500	O	Full Steel Inner Liner	773
0611250	O	Heavy-Duty Iron Front Spring Brackets With Front Air Leaf the front spring bracket is iron but not the shackle bracket	35
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0
0644090	O	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	-64
0651090	O	Omit Rear Mudflaps and Hangers	-25
Front Axle & Equipment			
1011890	O	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding	137

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
		applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.	
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.	
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	119
1233110	O	Power Steering TRW THP60 Dual Gear For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	74
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	2
1354850	O	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	42
1354870	O	Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	97
1380070	O	Greasable Front Spring Pins	0
1380290	O	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0
1380490	O	PACCAR FX Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius.	15
1391480	O	Pad Dust Shields for Air Disc Brakes; Front Axle Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.	2
Rear Axle & Equipment			
1523310	O	Dana Spicer DSH40 40,000 lb, High Performance 40 Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear &	179

Price Level: January 1, 2025

Deal: San Juan County Hook

Printed On: 12/31/2024 12:56:31 PM

100% Complete

Date: December 31, 2024

Quote Number: QUO-1149571-Y7Q8V3



Sales Code	Std/ Opt	Description	Weight
		extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	
1616305	O	PHP10 Iron Preset + Hubs - Air Disc	0
1616310	O	Severe Service Disc Brake Rotor Severe Service Disc Brake Rotor for refuse applications.	14
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680565	O	Bendix ESP Electronic Stability Program With ATC Truck, Crane, Platform Devices. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0
1683245	S	Tire Pressure Monitoring System	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1687040	O	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	0
1687090	O	Diff Lock Tandem Axles With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	60
1703900	O	Ratio 3.90 Rear Axle	0
1821810	O	Peterbilt Air Trac 40,000 lbs, 54in Axle Spacing Light Weight	170
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	2
Engine & Equipment			
2075810	S	PACCAR MX-13 455@1600 GV@2200 1650@900 (2024 Emissions)	0

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
N20700	AA003	68....CC MAX TARGET SPEED	
N20800	AA004	10....CC MIN ENABLE SPEED	
N22000	AA005	OFF...DYNAMIC CC ENABLE	
N20830	AA006	MT....MULTI TORQUE IN CC	
N21930	AA009	0....DRIVER REWARD VEH SPD BONUS	
N21940	AA010	-5....DRIVER REWARD VEH SPD PNLTY	
N21920	AA013	BOTH..OFFSET MODE	
N21950	AA015	3.....MIN SPEED FOR DR SHIFT AID	
N21960	AA016	1.....DSA LOWEST ACTV GEAR	
N21970	AA017	10....DSA HIGHEST ACTV GEAR	
N21640	AA019	YES...EIST PARK BRAKE RESET ENABLE	
N21910	AA022	30....EIST LO CLNT TEMP OVRDRD	
N20870	AA023	80....EIST HI AMBAIR TEMP OVRDRD	
N20860	AA024	39....EIST LO AMBAIR TEMP OVRDRD	
N20900	AA025	5.....EIST PTO MAX IDLE TIME	
N20840	AA026	5.....EIST PARKED MAX IDLE TIME	
N20850	AA027	5.....EIST STANDSTILL IDLE TIME	
N20910	AA029	YES...EIST RESET FROM ENG LOAD	
N21170	AA030	NO....EIST OVERRIDE FROM ENG LOAD	
N21190	AA031	0.....EIST EXPIRATION DISTANCE	
N21230	AA032	YES...EIST ACCEL PEDAL RESET	
N21240	AA033	YES...EIST SERVICE BRK RESET	
N21250	AA034	YES...EIST CLUTCH PEDAL RESET	
N21260	AA035	YES...EIST PTO OVERRIDE	
N20770	AA037	4.....DSL SPD OFFSET	
N20760	AA038	2.....AUTO RTRDR VEH SPD OFFSET	
N20750	AA039	0.1...TIME DELAY FOR RTRDR ACT	
N20940	AA042	1900..FIC MAX ENG SPEED	
N22080	AA043	CNCL..CAB/REM: CUSTOM PRESET 1 FUN	
N22090	AA044	750...CAB/REM: CUSTOM PRESET 1	
N22100	AA045	CNCL..CAB/REM: CUSTOM PRESET 2 FUN	
N22110	AA046	850...CAB/REM: CUSTOM PRESET 2	
N22120	AA047	CNCL..CAB/REM: CUSTOM PRESET 3 FUN	
N22130	AA048	950...CAB/REM: CUSTOM PRESET 3	
N22010	AA049	CNCL..CAB: CUSTOM PRESET 1 FUNC	
N22020	AA050	0.....CAB: CUSTOM PRESET 1	
N22030	AA051	CNCL..CAB: CUSTOM PRESET 2 FUNC	
N22040	AA052	0.....CAB: CUSTOM PRESET 2	
N22050	AA053	CNCL..CAB: CUSTOM PRESET 3 FUNC	
N22060	AA054	0.....CAB: CUSTOM PRESET 3	
N20990	AA055	ON A..CAB: CLUTCH INTLK	
N21010	AA058	ON A..CAB: PARK BRK INTLK	
N21030	AA057	ON A..CAB: NEUTRAL INTLK	
N21150	AA059	ON A..SER BRK INTLK: NO PTO	
N21130	AA060	OFF...CAB: PRESET +/- SWITCH TYPE	
N21180	AA061	2000..CAB: MAX ENG SPD- ACCEL CTRL	
N21120	AA062	2000..CAB: MAX ENG SPD- SW CTRL	
N21020	AA063	6.....CAB:MAX VEH SPEED	
N21200	AA064	650...CAB: MIN ENG SPD	
N21220	AA065	800...CAB: DEDICATED PRESET (-)	
N21270	AA066	900...CAB: DEDICATED PRESET (+)	
N21900	AA067	TRQ...CAB: ACCEL PEDAL TYPE IN PTO	

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
		N21140 AA068 YES...CAB: ACCEL ACTV IN CAB PTO	
		N21990 AA069 YES...PTO REM PEDAL ENABLE	
		N21600 AA070 ON AD.REM: CLUTCH INTLK	
		N22140 AA071 OFF...REM: CUSTOM INTLK	
		N21700 AA072 ON AD.REM: NEUTRAL INTLK	
		N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO	
		N21980 AA074 2000..REM:MAX ENG SPD-ACCEL CTRL	
		N21110 AA075 2000..REM: MAX ENG SPD-SW/ TSC1 CT	
		N21320 AA076 650...REM: MIN ENG SPD	
		N21290 AA077 800...REM: DEDICATED PRESET (-)	
		N21490 AA078 900...REM: DEDICATED PRESET (+)	
		N21580 AA079 DEDIC.REM: PRESET +/- SWITCH TYPE	
		N20690 AA086 68....MAX ACCEL PEDAL VEH SPD	
		N21300 AA087 0.....VSL EXPIRATION DISTANCE	
		N21310 AA088 100...LRSL SPD LMT	
		N20740 AE001 NO....ENBL MX RETARDER IN NEUTRAL	
		N20710 AE002 650...IDLE TARGET	
		N20930 AE003 ON....FIC ENABLE/DISABLE	
		N22070 AA056 OFF...CAB: CUSTOM INTLK	
		N22170 AQ001 4.....PCC Max Negative Offset (AQ0	
		N22180 AQ002 4.....PCC Max Positive Offset (AQ0	
2091120	S	EMUX Electronics Architecture	0
2091305	S	Engine Idle Shutdown Timer Enabled	0
2091315	O	Enable EIST Ambient Temp Overrule	0
2091372		Eff EIST NA Expiration Miles	0
2091640		Effective VSL Setting NA	0
2092014	O	Typical Operating Speed 65 MPH	0
2092027	O	MX Retarder State Cruise Control On (Manual Mode Engine Parameter)	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2092065	O	PTO Mode Control - CAB Station	0
2092079	O	Decline Driver Performance Assistant	0
2092083	O	Engine Monitoring Protection - Shutdown (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and then engine shutdown to avoid damage to the engine.	0
2140410	S	Engine Brake Controls Located on RH Column	0

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	0
2140670	O	EPA Emission Warranty	0
2140700	S	EPA Engine Idling Compliance	0
2140940	O	Exterior Notification of Regen Required Includes Horn and Lights Flashing	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0
2522080	S	PACCAR Premium Starter - MX Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
2539720	S	Low Voltage Disconnect System	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
2738410	S	WABCO 25.9 CFM Air Compressor, MX only WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0
2811160	S	Compression Brake, MX The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0
2921180	S	PACCAR Fuel/Water Separator On Engine Extended life fuel filter, optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect	0

Price Level: January 1, 2025

Deal: San Juan County Hook

Printed On: 12/31/2024 12:56:31 PM

100% Complete

Date: December 31, 2024

Quote Number: QUO-1149571-Y7Q8V3



Sales Code	Std/ Opt	Description	Weight
		the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389 HH 1604 sq in, 567 1379 sq in.	
3281680	O	Dual Pre-Cleaners, Under Hood Mounted, Self Cleaning	0
3291680	S	(1) Air Cleaner Firewall Mounted Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
3367160	S	Exhaust Single RH Side of Cab DPF/SCR RH Under Cab, Single Module	0
3387890	O	36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	4

Transmission & Equipment

4022080	O	Eaton RTLO18913A 13-Speed Includes oil-to-water cooler, internal oil pump, rear transmission support, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: L-12.31, 1st-8.64, 2nd-6.11, 14th-1.00, 15th-0.86, 16th-0.73. Reverse ratios: LL-13.22, H-3.50	338
4210870	O	RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanently lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0
4211360	O	RPL25 SD Driveline, 1 Midship Bearing All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	120
4233930	O	(1) Dash Mounted Double Acting EOA PTO Control Electric-over-air (EOA), spec'ing PTO (power-take-off) control switch does not ensure the PTO will fit.	0
4256100	O	Manual Shifter, Black	0
4256250	O	Heavy Duty Input Bearing for PTO Operation For use with Fuller RTLO transmission 1100 through 2250 series. The roller style input shaft bearing has twice the dynamic radial load capability of the ball bearing style and is recommended for transmissions that will be equipped with a transmission mounted 6 or 8 bolt PTO.	0
4321000	O	Self-Adjust Clutch	0
4380220	O	Pre-Damped Clutch Pre-damped feature consists of a set of small springs around the hub, which dampen the engine torsional vibrations at idle speeds before they can reach the transmission and cause gear rattle. Option required on	0

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/Opt	Description	Weight
configurations specifying an ISX15 Family 1 engine and a manual transmission with torque ratings of 1650 lb-ft torque or higher.			
Air & Trailer Equipment			
4510350	O	Bendix AD-HFI EP Smart Air Dryer, Heater Coalescing filter, extended purge	15
4520420	O	Pull Cords All Air Tanks	1
4540420	S	Nylon Chassis Hose	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4611850	O	Omit Standard Trailer Connection Package Omits 12' AE lines, hose tenna, hand valve	-28
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	6
4615250	O	Fitting For F/O Air Port The furnished by owner fitting air port is mounted outboard of the driver's seat. This allows operators access to pressurize truck air, to maintain clean air in the cab.	0
Tires & Wheels			
5004040	O	FF: CN 20ply 315/80R22.5 HAU3 WT Efficiency Rating: Fair Waste transportation and other high scrub, urban applications.	98
5104230	O	RR: CN 14ply 11R22.5 HDR2+	176
5190008	S	Code-rear Tire Qty 08	0
5220520	O	FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	-36
5320770	O	RR: Alcoa ULA187 22.5X8.25 High Polish Alum Ultra One wheel with MagnaForce alloy.	-224
5390008	S	Code-rear Rim Qty 08	0
Fuel Tanks			
5534160	O	23" Aluminum 90 Gallon Fuel Tank LH U/C Includes non-slip fuel tank step left-hand under cab	13

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
5602090	O	Location LH U/C 90 Gallon	0
5652740	O	S Brace Fuel Tank Step Support	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0
5760010	O	RH Tank None Furnished	-86
Battery Box & Bumper			
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	-60
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0
6111010	S	Aluminum Bumper Swept Back Polished Without FEPTO SBFA, two tow pins and step plates on top of bumper	0
Cab & Equipment			
6515700	O	Vocational 121" BBC Alum Cab and Metton Hood SBFA Stainless crown and grille with tilt assist.	30
6540160	O	Thermal Insulation Package in Cab The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	2
6700000	S	No Sleeper Selected	0
6800510	O	Fender Lips 2.25" Wide	6
6911100	S	Peterbilt ST Driver Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal car/g/luggage. Standard vinyl finish - color coordinate with interior color.	0
6921740	S	Peterbilt ST Non-Adjustable Passenger Seat Standard vinyl, no suspension cover, no seat back recline.	0
6930500	O	Drivers Armrest - RH Only	2
6930800	O	Black Seat Color IPO Standard Color	0
6931120	O	Seat Belt Color Orange IPO Standard Black	0

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
6939400	S	Air Ride Driver	0
6939420	S	High Back Driver	0
6939470	S	Vinyl Driver	0
6939510	S	Non-Air Ride Passenger	0
6939520	S	High Back Passenger	0
6939570	S	Vinyl Passenger	0
6939660	S	Static Riser Under Passenger Seat Peterbilt passenger non-adjustable seat.	0
7000025	S	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0
7000045	O	High-Visibility Interior Grabhandles, Painted Bright yellow interior grabhandle for vocational vehicles.	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0
7001580	O	Vanity Mirror on Inside Sunvisors For use with ProBilt 1.9, Prestige (1.9 & 2.1) or Premier (2.1) interiors.	0
7037130	S	Prestige Interior - Sterling Gray Features single tone dash with tough, scratch resistant materials including soft touch points on top of dash. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical grained A,B, C & D instrument panels with contoured doorpads, padded fabric headliner and vinyl wall panels. Superior ergonomics are achieved while maximizing productivity featuring: multiple power ports, (2) coat hooks, header-mounted domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, rubber flooring, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in dash.	0
7110680	O	Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only.	6
7210420	O	Dark Window Tint IPO Standard Tint - Day Cab	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0
7210550	S	1-Piece Glass Rear Cab Window Fixed	0
7230060	S	1-Piece Curved Windshield	0

Price Level: January 1, 2025

Deal: San Juan County Hook

Printed On: 12/31/2024 12:56:31 PM

100% Complete

Date: December 31, 2024

Quote Number: QUO-1149571-Y7Q8V3



Sales Code	Std/ Opt	Description	Weight
7230360	S	Power Door Locks and Power Window Lifts Standard	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7330880	O	Additional Fine Particulate Filter For HVAC Syst 3 micron filtration. For use in extreme high dust applications. Not available with Ember filter 7330890.	1
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	8
7514010	O	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	3
7514020	O	Aero Rear View Mirror Housing - Body Color (Same Color as Vehicle Body)	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0
7610500	S	Air Horn Mounted Under Cab	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	4
7728040	O	Bluetooth Phone and Audio Requires USB Port	0
7728050	O	USB Port	0
7748145	O	CB Terminals/Wiring Mounted Under Header With mounting bracket	2
7748150	O	(1) Antenna for Factory Installed or F/O CB Mounted LH cowl, low mount only, with antenna cable. Provides clear top of cab.	1
7788335	S	Global Telematics Hardware	0
7850015	O	Rear Wall Deep Record/Map Pocket	2
7851040	O	Removable Bugscreen Behind Grille	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
7852020	O	Cab Air Suspension	15
7852050	O	Auto Reset Circuit Protection Daycab and Sleeper	0
7900090	O	Triangle Reflector Kit, Ship Loose	13

Price Level: January 1, 2025

Deal: San Juan County Hook

Printed On: 12/31/2024 12:56:31 PM

100% Complete

Date: December 31, 2024

Quote Number: QUO-1149571-Y7Q8V3



Sales Code	Std/ Opt	Description	Weight
		Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	
7900320	O	Fire Extinguisher, Mounted Inboard Driver Seat Hazmat approved UL listed/rated ABC	8
7900401	O	Cruise Control Inactive With Wipers On	0
7900403	O	Cruise Inactive At Wiper Speed 6 Only Only available with 7900401	0
7900560	O	Exterior Audible Alarm, Park Brake Not Set With door open; city horn.	0
7901130	O	Backup Alarm (107 DB)	3
8011470	O	Engine Oil Temperature Gauge 52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	0
8011850	O	Transmission Oil Temperature (Main) Located in Digital Cluster Display.	0
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0
8021830	O	Increased Air Filter Full Indication For air filter restriction gauge	0
8070000	O	Disable Brake Light With Engine Brake	0
8070010	O	Up To (4) Additional Electric Switches Up to (4) additional electric switches without wiring. Switch will short pin5 to pin 4 when off, and pin 5 to 6 when on. Backlighting provided by Lin jumper.	1
8070390	O	Engine Hourmeter Gauge Located in Digital Cluster Display	0
8070450	O	Engine PTO Hourmeter Gauge Located In Digital Cluster Display	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0
8070830	O	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0
8071900	O	Manifold Pressure Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	2
8073040	O	(1) Additional Electric Over Air Switch On/off only, switch has green indicator light, air connections on frame rail under cab. One accessory solenoid bank with plug on it.	0

Price Level: January 1, 2025

100% Complete

Date: December 31, 2024

Deal: San Juan County Hook

Quote Number: QUO-1149571-Y7Q8V3

Printed On: 12/31/2024 12:56:31 PM



Sales Code	Std/ Opt	Description	Weight
8110070	S	Headlights Projector Module Pod Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0
8133470	O	Switch & Wiring for F/O Beacon/Strobe Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill.	2
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0
8134160	O	Self-Canceling Turn Signal	2
8140080	O	LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame	20
8140850	O	Moveable EOF Crossmember For Mounting Tail Lights Square end of frame with or without end of frame crossmember	2
8151190	O	(2) Load Lights, LED, Flush Mounted Low Inboard Back of cab / back of sleeper	4
Paint			
8500710	S	Standard Paint Color Selection	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0
Shipping Destination			
Options Not Subject To Discount			
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0
9400092	S	PACCAR MX Standard Coverage 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0
9407147	O	Fuel Price Index Factor \$0 NET	0
9408656	O	SmartLINQ RD/OTA 5YR Sub PACCAR MX Engines	0
9408703	O	Base Warr: Emissions 5YR/100K MI-EPA Engine	0
9408937	O	PDI After Body Upfit	0
Miscellaneous			

Price Level: January 1, 2025
Deal: San Juan County Hook
Printed On: 12/31/2024 12:56:31 PM

100% Complete

Date: December 31, 2024
Quote Number: QUO-1149571-Y7Q8V3



Sales Code	Std/ Opt	Description	Weight
9409001	S	Day Cab / Prestige Interior (DM)	0
9409094	O	State Of Registry: Utah	0
9409645	O	Model Year 2025 Engine	0
9409749	O	2024 Series Emissions Engine	0

Promotions

Special Requirements

Special Requirement 1 0098170
Special Requirement 2
Special Requirement 3
Special Requirement 4

Order Comments



Total Weight (lbs)

17,448

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information