#### **VICINITY MAP** FOOTHILL VILLAGE SUBDIVISION PLAT 'T' SANTAQUIN CITY LOCATED IN THE SOUTHERN PORTION OF SECTION 11, TOWNSHIP 10 SOUTH RANGE 1 EAST, SALT LAKE BASE AND MERIDIAN PROJECT STATISTICS Santaquin, Utah County, Utah LOTS 16 LOTS TOTAL ACREAGE 7.23 ACRES TOTAL ACREAGE IN LOTS 14.43 ACRES TOTAL ACREAGE IN STREETS 1.49 ACRES TOTAL ACREAGE IN OPEN SPACE 0.41 ACRES DENSITY 2.21 UNITS PER ACRE ZONE R10 PUD PROJECT ENGINEER & SURVEYOR REGION ENGINEERING & SURVEYING ALL IMPROVEMENTS AND DETAILS PER 1776 NORTH STATE STREET #110 OREM, UTAH 84057 SANTAQUIN CITY CONSTRUCTION STANDARDS PLAT D PLAT J PH - 801.376.2245 MAILBOX (2 x CBU) LOCATION FOR PHASE T TO BE LOCATED AT THE INTERSECTION OF BLUFF STREET PROJECT DEVELOPER & FOOTHILL VILLAGE BLVD (PHASE D) 12351 So. Gateway Park Place PHASES P & O MUST BE COMPLETED PRIOR TO OR CONCURRENT TO PHASE T Draper UT 84020 Office: (801) 571-7101 CKLeavitt1@drhorton.com PLAT P NORTH (587) (24"x36") SCALE 1" = 100' (586) (584) (11"x17") INDEX OF PLAN SHEETS SCALE 1" = 200'COVER SHEET & NOTES (585) FINAL PLAT SITE & UTILITY PLAN SP-01 GR-01-02 GRADING PLAN (588) PLAN & PROFILE **NOTES:** (580) EROSION CONTROL PLAN (589) THE DEVELOPER AND THE GENERAL CONTRACTOR EROSION CONTROL DETAILS UNDERSTAND THAT IT IS HIS/HER RESPONSIBILITY TO ENSURE THAT ALL IMPROVEMENTS INSTALLED WITHIN THIS TYPICAL DETAILS DEVELOPMENT ARE CONSTRUCTED IN FULL COMPLIANCE WITH ALL STATE AND SANTAQUIN CITY CODES, ORDINANCES AND (590) STANDARDS. THESE PLANS ARE NOT ALL INCLUSIVE OF ALL MINIMUM CODES, ORDINANCES AND STANDARDS, THIS FACT DOES NOT RELIEVE THE DEVELOPER OR GENERAL CONTRACTOR FROM FULL COMPLIANCE WITH ALL MINIMUM STATE AND SANTAQUIN CITY CODES, ORDINANCES AND STANDARDS." (578) (591) 2. ALL SPEED & TRAFFIC REGULATION SIGNS TO BE DETERMINED AND INSTALLED BY SANTAQUIN CITY. DEVELOPER TO PAY SIGN EXPENSES WITH DEVELOPMENT 3. ALL SERVICE LATERALS SHALL BE INSTALLED PER SANTAQUIN STANDARDS AND DETAIL ON SHEET DT-01, UNLESS OTHERWISE NOTED. (592) 4. 18" MIN. VERTICAL SEPARATION BETWEEN CULINARY WATER AND PI, STORM DRAIN, OR SANITARY SEWER AT ALL CROSSINGS. CULINARY WATER TO HAVE 4' MIN. COVER AS PER CITY STANDARD. 5. SHALLOW SEWER MAY EXIST THROUGHOUT THIS PHASE. INJECTOR PUMPS MAY BE NEEDED IF BASEMENTS ARE 6. ALL RECOMMENDATIONS MADE IN A PERTINENT (593) GEOTECHNICAL REPORT/STUDY SHALL BE FOLLOWED EXPLICITLY DURING CONSTRUCTION OF BUILDING AND SITE 7. ALL CURB INLET BOX INVERTS MUST BE A MINIMUM OF 36" OR 2.5 TIMES THE PIPE DIAMETER ABOVE THE BOTTOM OF **ACCEPTANCE** SIGNATURE: BUILDING DEPARTMENT

SIGNATURE: POLICE DEPARTMENT

C:\USERS\SHERRING\DROPBOX\2\_REGION PROJECTS\1\_REGION ENGINEERING PROJECTS\0\_PROJECTS\0\_049\_FOOTHILL SANTAQUIN\2\_SHEET FILES\PHASE T\CS-01







F00

DATE:2.12.2021 PROJECT # **REVISIONS:** 

**COVER SHEET & NOTES** 

CS-01





C:\USERS\SHERRING\DROPBOX\2\_REGION PROJECTS\1\_REGION ENGINEERING PROJECTS\0\_PROJECTS\0\_049\_FOOTHILL SANTAQUIN\2\_SHEET FILES\PHASE T\SP-01

Engineering & Surveying State St. #110, UT 84057

1021011 1776 N. Sta Orem, U P: 801.3





SECTION

THILL VILLAGE SUBDIVISORED IN THE SOUTHERN PORTION OF STATE OF STA

00

DATE:2.12.2021
PROJECT #

REVISIONS:


1
2
3

SHEET NAME: SITE/UTILITY PLAN

SP-01

ALL CURB INLET BOX INVERTS MUST BE A MINIMUM OF 36" OR 2.5 TIMES THE

PIPE DIAMETER ABOVE THE BOTTOM OF THE BOX



C: \USERS\SHERRING\DROPBOX\2\_REGION PROJECTS\1\_REGION ENGINEERING PROJECTS\0\_PROJECTS\2016\2016\_049\_FOOTHILL SANTAQUIN\2\_SHEET FILES\PHASE T\GR-01









SUBDIVI:

FOOTHILL LOCATED

DATE:2.12.2021 PROJECT # **REVISIONS:** 

GRADING PLAN GR-01





INTERSECTION GRADING 'B'

FOOTHILL

VILL
PL
PL
THE SO
II, TOW
ST, SAI

**NOTES:** 


- 1. THE DEVELOPER AND THE GENERAL CONTRACTOR UNDERSTAND THAT IT IS HIS/HER RESPONSIBILITY TO ENSURE THAT ALL IMPROVEMENTS INSTALLED WITHIN THIS DEVELOPMENT ARE CONSTRUCTED IN FULL COMPLIANCE WITH ALL STATE AND SANTAQUIN CITY CODES, ORDINANCES AND STANDARDS. THESE PLANS ARE NOT ALL INCLUSIVE OF ALL MINIMUM CODES, ORDINANCES AND STANDARDS. THIS FACT DOES NOT RELIEVE THE DEVELOPER OR GENERAL CONTRACTOR FROM FULL COMPLIANCE WITH ALL MINIMUM STATE AND SANTAQUIN CITY CODES, ORDINANCES AND
- STANDARDS." 2. ALL SPEED & TRAFFIC REGULATION SIGNS TO BE DETERMINED AND INSTALLED BY SANTAQUIN CITY.
  DEVELOPER TO PAY SIGN EXPENSES WITH DEVELOPMENT
- 3. ALL SERVICE LATERALS SHALL BE INSTALLED PER SANTAQUIN STANDARDS AND DETAIL ON SHEET DT-01
- UNLESŠ OTHERWISE NOTED. 4. 18" MIN. VERTICAL SEPARATION BETWEEN CULINARY WATER AND PI, STORM DRAIN, OR SANITARY SEWER AT ALL CROSSINGS. CULINARY WATER TO HAVE 4' MIN. COVER AS PER CITY STANDARD.
- 5. ALL CURB INLET BOX INVERTS MUST BE A MINIMUM OF 36" OR 2.5 TIMES THE PIPE DIAMETER ABOVE THE BOTTOM OF THE BOX


NOTES TO CONTRACTOR: CONTRACTOR TO FIELD VERIFY ALL EXISTING CURB & GUTTER, STORM DRAIN, CHANNEL CROSSINGS, & SEWER ELEVATIONS OR INVERTS PRIOR TO CONSTRUCTION AND NOTIFY ENGINEER WHEN ELEVATIONS OR INVERTS DO NOT MATCH PLANS.


THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. HE AGREES TO BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY HIS FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES.

DATE:2.12.2021 PROJECT # **REVISIONS:** 

GRADING PLAN GR-02







gion 776 N C






SUBDIVISION T'

LAGE LAT VILL
PLL
TOWF FOOTHILL LOCATED

> DATE:2.12.2021 PROJECT # **REVISIONS:**

PLAN & PROFILE

PP-03



gion 776 N C


SUBDIVISION LAGE LAT FOOTHILL

OUTHERN PO WNSHIP 10 S VILL
PL
PL
TOWF LOCATED

> DATE:2.12.2021 PROJECT # **REVISIONS:**

PLAN & PROFILE

PP-04



C:\USERS\SHERRING\DROPBOX\2\_REGION PROJECTS\1\_REGION ENGINEERING PROJECTS\0\_PROJECTS\0\_049\_FOOTHILL SANTAQUIN\2\_SHEET FILES\PHASE T\PP-03

OUTHERN PO WNSHIP 10 3 LT LAKE BA

DATE:2.12.2021 PROJECT #

**REVISIONS:** 

PLAN & PROFILE

# LEGEND:

PROPOSED SILT FENCE (SEE SHEET EC-02)

FLOW ARROW



PROPOSED VEHICLE TRACKING CONTROL

(SEE SHEET EC-02)

PROPOSED CURB INLET PROTECTION

(SEE SHEET EC-02)

PORTABLE TOILETS

#### **NOTES:**

- 1. IN THE EVENT THAT ANY UNFORESEEN CONDITIONS NOT COVERED BY THESE NOTES ARE ENCOUNTERED DURING GRADING OPERATIONS, THE OWNER/ENGINEER IS TO BE IMMEDIATELY
- NOTIFIED FOR DIRECTION. 2. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PERFORM ALL NECESSARY CUTS AND FILLS WITHIN THE LIMITS OF THIS PROJECT AND THE RELATED OFF-SITE WORK, SO AS TO GENERATE THE DESIRED SUBGRADE, FINISH GRADES AND SLOPES SHOWN.
- 3. CONTRACTOR IS TO TAKE FULL RESPONSIBILITY FOR ALL EXCAVATION. ADEQUATE SHORING IS TO BE DESIGNED AND PROVIDED BY THE CONTRACTOR TO PREVENT UNDERMINING OF ANY ADJACENT FEATURES OR FACILITIES AND/OR CAVING OF THE
- 4. THE CONTRACTOR IS WARNED THAT AN EARTHWORK BALANCE WAS NOT NECESSARILY THE INTENT OF THIS PROJECT. ANY ADDITIONAL MATERIAL REQUIRED OR LEFTOVER MATERIAL FOLLOWING EARTHWORK OPERATIONS BECOMES THE RESPONSIBILITY OF THE CONTRACTOR.
- 5. THE GRADING CONTRACTOR IS RESPONSIBLE TO COORDINATE WITH THE OWNER TO PROVIDE FOR THE REQUIREMENTS OF THE PROJECT STORM WATER POLLUTION PREVENTION PLAN (SWPPP) AND ASSOCIATED PERMIT.
- 6. ALL CUT AND FILL SLOPES ARE TO BE PROTECTED UNTIL
- EFFECTIVE EROSION CONTROL HAS BEEN ESTABLISHED. 7. THE USE OF POTABLE WATER WITHOUT A SPECIAL PERMIT FOR
- BUILDING OR CONSTRUCTION PURPOSED INCLUDING CONSOLIDATION OF BACKFILL OR DUST CONTROL IS PROHIBITED. THE CONTRACTOR IS TO OBTAIN ALL NECESSARY PERMITS FOR CONSTRUCTION WATER. 8. THE CONTRACTOR IS TO MAINTAIN THE STREETS, SIDEWALKS, AND ALL OTHER PUBLIC RIGHT-OF-WAY IN A CLEAN, SAFE AND USABLE
- CONDITION. ALL SPILLS OF SOIL, ROCK OR CONSTRUCTION DEBRIS IS TO BE PROMPTLY REMOVED FROM THE PUBLICLY OWNED PROPERTY DURING CONSTRUCTION AND UPON COMPLETION OF THE PROJECT. ALL ADJACENT PROPERTY, PRIVATE OR PUBLIC IS TO BE MAINTAINED IN A CLEAN, SAFE AND USABLE CONDITION.
- 9. IN THE EVENT THAT ANY TEMPORARY CONSTRUCTION ITEM IS REQUIRED THAT IS NOT SHOWN ON THESE DRAWINGS, THE OWNER AGREES TO PROVIDE AND INSTALL SUCH ITEM AT HIS OWN EXPENSE AND AT THE DIRECTION OF THE ENGINEERING DEPARTMENT. TEMPORARY CONSTRUCTION INCLUDES DITCHES BERMS, ROAD SIGNS AND BARRICADES, ETC.

## PROJECT INFORMATION SIGN

ANY ACTIVITY THAT REQUIRES A GRADING PERMIT SHALL INSTALL AND MAINTAIN A PROJECT INFORMATION SIGN IN ACCORDANCE WITH THE FOLLOWING REQUIREMENTS:

- 1. THE SIGN SHALL BE INSTALLED PRIOR TO BEGINNING ACTUAL CONSTRUCTION ACTIVITIES OR INITIATING ANY TYPE OF EARTH-MOVING OPERATIONS.
- 2. THE SIGN SHALL BE INSTALLED AT A PROMINENT LOCATION ON THE PROPERTY NEAR THE MAIN ENTRANCE OF THE CONSTRUCTION SITE. TRAFFIC VISIBILITY SHALL BE MAINTAINED BY PLACING THE SIGN BACK FROM THE MAIN INGRESS/ EGRESS LOCATION AND AT ANY APPLICABLE INTERSECTION FOR PROPER SIGHT TRIANGLE CLEARANCES.
- THE SIGN MAY BE REMOVED ONCE FINAL STABILIZATION HAS BEEN ACHIEVED ON ALL PORTIONS OF THE SITE FOR WHICH THE PERSON IS RESPONSIBLE AND IS APPROVED BY THE CITY.
- 4. THE SIGN SHALL BE A MINIMUM OF 48" x 48" AND THE FOLLOWING INFORMATION SHALL BE DISPLAYED ON THE SIGN WITH THE DESIGNATED ALPHA AND NUMERIC DIMENSIONS. SIGN BOARDS WRITTEN IN LONGHAND ARE UNACCEPTABLE. DEVELOPERS NAME (4" Uppercase Bold Letters)


PROJECT NAME (4" Uppercase Bold Letters) PERMIT NUMBER

FOR PROJECT SITE CONCERNS CONTACT

Cell Phone Contact ###-###-####


IF NO RESPONSE PLEASE CONTACT CITY OFFICE AT (3" Uppercase Bold Letters and 3" Bold Numbers)

- 5. THE TEXT HEIGHT SHALL BE A MINIMUM AS SHOWN ON THE TEMPLATE ABOVE, AND MUST CONTRAST WITH LETTERING, TYPICALLY BLACK TEXT WITH WHITE BACKGROUND.
- THE LOWER EDGE OF THE SIGN BOARD MUST BE A MINIMUM OF THREE (3) FEET AND A MAXIMUM OF FIVE (5) FEET ABOVE GRADE. SIGN MAY BE POSTED ON A TRAILER OF IT MEETS THESE REQUIREMENTS..



## CONSTRUCTION PHASE STORM WATER POLLUTION PROTECTION PLAN BEST MANAGEMENT PRACTICES (BMP)

ВМР#	BMP SYMBOL	TITLE	LOCATION	DURATION
C101	101	PRESERVING NATURAL VEGETATION	PER CONTRACTOR	BEGINNING OF CONSTRUCTION THROUGH COMPLETION OF SITE IMPROVEMENTS
C105	105	STABILIZED CONSTRUCTION ENTRANCE	AS SHOWN	BEGINNING OF CONSTRUCTION THROUGH COMPLETION OF ASPHALT IMPROVEMENTS
C106	106	WHEEL WASH	AS SHOWN	AS NECESSARY
C151	151	CONCRETE WASTE MANAGEMENT	PER CONTRACTOR/ AS SHOWN	BEGINNING OF CONSTRUCTION THROUGH COMPLETION OF SITE IMPROVEMENTS
C190	190	PORTABLE TOILETS	PER CONTRACTOR/ AS SHOWN	BEGINNING OF CONSTRUCTION THROUGH COMPLETION OF SITE IMPROVEMENTS
C220	(550)	STORM DRAIN INLET PROTECTION	AS SHOWN	COMMENCEMENT OF GRADING THROUGH COMPLETION OF SITE IMPROVEMENTS
C233	233	SILT FENCE	AS SHOWN	COMMENCEMENT OF GRADING THROUGH COMPLETION OF SITE IMPROVEMENTS
C233	(240)	SEDIMENT TRAP	as shown	BEGINING OF CONSTRUCTION TO PLACEMENT OF ASPHALT



(24"x36") SCALE 1" = 60SCALE 1" = 120

C: \USERS\SHERRING\DROPBOX\2\_REGION PROJECTS\1\_REGION ENGINEERING PROJECTS\0\_PROJECTS\2016\2016\_049\_FOOTHILL SANTAQUIN\2\_SHEET FILES\PHASE T\EC-01







00

DATE:2.12.2021 PROJECT # **REVISIONS:** 

EROSION CONTROL PLA






DETAIL-C STRAW BALE DROP INLET PROTECTION DETAIL

## **EROSION CONTROL NOTES**

1. CONTROLLING SEDIMENT TRANSPORT AND PREVENTING AND/OR CORRECTING PROBLEMS ASSOCIATED WITH EROSION AND RUNOFF PROCESSES THAT COULD OCCUR BOTH DURING AND AFTER PROJECT CONSTRUCTION WILL BE CLOSELY MONITORED. PERIODIC MAINTENANCE AND INSPECTION OF SEDIMENT CONTROL DEVICES WILL BE SCHEDULED. PARTICULAR ATTENTION SHALL BE GIVEN TO EXISTING DRAINAGE PATTERNS THAT RUN THROUGH DISTURBED AREAS AND OVER EXTREME SLOPES. THESE PATTERNS WILL BE IDENTIFIED TO ISOLATE PROBLEM AREAS WHERE WATER WILL CONCENTRATE. PROVISIONS SHALL BE MADE TO CHANNEL RUNOFF AWAY FROM NEW OR EXISTING IMPROVEMENTS TO PREVENT UNDERMINING AND GENERAL SITE EROSION. THESE PROVISIONS SHALL BE STABILIZED AND SHALL REMAIN IN PLACE UNTIL THE PERMANENT STORM DRAINAGE FACILITIES ARE INSTALLED AND FUNCTIONAL.

- 2. EROSION CONTROL A STORMWATER POLLUTION PREVENTION PLAN (SWPPP) WILL BE PREPARED IN ACCORDANCE WITH THE UTAH POLLUTANT DISCHARGE ELIMINATION SYSTEM (UPDES) PERMIT FOR CONSTRUCTION, OUTLINING HOW EROSION AND SILTATION WILL BE CONTROLLED. A NOTICE OF INTENT (NOI) WILL BE SUBMITTED TO OBTAIN THE UPDES CONSTRUCTION PERMIT. A COPY OF THE PLAN MUST BE ON SITE AT ALL TIMES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR IMPLEMENTING THE PLAN AND INSTALLING AND MAINTAINING THE EROSION CONTROL FACILITIES WITH EACH PHASE OF WORK. SHOULD SILT LEAVE THE SITE OR EROSION OCCURS, IT WILL BE THE CONTRACTORS RESPONSIBILITY TO TAKE CORRECTIVE ACTION AND REPAIR ANY DAMAGE CAUSED BY THE SILT OR EROSION IMMEDIATELY. ALL COSTS ASSOCIATED WITH THE MODIFICATION AND APPROVAL OF THE PLAN WILL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 3. BEFORE CONSTRUCTION BEGINS, THE LIMITS OF DISTURBANCE (LOD) BOUNDARY SHALL BE STAKED ON SITE AND APPROVED BY THE OWNER'S REPRESENTATIVE AND THE
- 4. EXCAVATION AND EMBANKMENT OPERATIONS SHALL PROCEED IN SUCH A MANNER SO THAT FINISHING OF SLOPES, INCLUDING REVEGETATION SHALL BE ACCOMPLISHED AS SOON AS POSSIBLE AFTER ROUGH GRADING. ALL SLOPES 2:1 OR FLATTER SHALL BE SCARIFIED WITH HEAVY EQUIPMENT, LEAVING TRACKS PERPENDICULAR TO THE SLOPES. SLOPES OVER 1:1 SHALL UTILIZE EROSION CONTROL/REVEGETATION MATTING.
- 5. CUT AND FILL SLOPES SHALL BE CONDUCTED PER THE GEOTECHNICAL REPORT. THE TOPS OF ALL CUT SLOPES IN SOIL SHALL BE ROUNDED FOR A HORIZONTAL DISTANCE OF THREE (3) FEET BEYOND THE CATCH POINT. SLOPE ROUNDING SHALL OCCUR AS THE SLOPE IS BEING BROUGHT DOWN. THE OVERALL SHAPE, HEIGHT AND GRADE OF ANY CUT AND/OR FILL SLOPE SHALL BE DEVELOPED IN CONCERT WITH EXISTING NATURAL CONTOURS, SCALE AND VEGETATION OF NATURAL TERRAIN.
- 6. EXISTING VEGETATION SHOULD BE PRESERVED WHEREVER POSSIBLE AND DISTURBED PORTIONS OF THE SITE SHALL BE STABILIZED. STABILIZATION PRACTICES MAY INCLUDE, BUT NOT LIMITED TO, TEMPORARY SEEDING, PERMANENT SEEDING, MULCHING, GEOTEXTILES, SOD STABILIZATION, VEGETATION BUFFER STRIPS, PROTECTION OF TREES, PRESERVATION OF NATURAL VEGETATION AND OTHER APPROPRIATE MEASURES. USE OF IMPERVIOUS SURFACES FOR STABILIZATION SHALL BE AVOIDED. STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE PERMANENTLY CEASED. FOR MORE INFORMATION,
- SPECIFICALLY OUTLINED DISTURBED AREAS, BOTH ON AND OFF-SITE SHALL BE REVEGETATED. THESE AREAS SHALL BE INCLUDE, BUT NOT BE LIMITED TO, ALL UNSURFACED AREAS WITHIN THE STAKED LOD, STAGING AND STORAGE AREAS, MATERIAL WASTE AREAS, UNDERGROUND UTILITY CONSTRUCTION AREAS, BENCHED AREAS, INCLUDING RETAINING WALL BENCHES, AND TEMPORARY OR EXISTING ACCESS ROADS USED FOR CONSTRUCTION ACTIVITIES.
- 8. CONTROLLED OUTLETS SHALL DIRECT COLLECTED RUNOFF THROUGH SILT FENCES, STRAW BALES, OR WATTLE.
- TYPICAL FUGITIVE DUST SHALL BE CONTROLLED BY WATERING AND/OR CHEMICAL STABILIZATION, PROVIDING VEGETATIVE OR SYNTHETIC COVER AND WIND BREAKS CONSISTENT WITH UTAH STATE DIVISION OF AIR QUALITY STANDARDS.
- 10. ANY SEDIMENT TRACKED OFF-SITE SHALL BE REMOVED PRIOR TO THE END OF THE WORK SHIFT OR PRIOR TO SUNSET, WHICHEVER COMES FIRST.
- 11. CONTRACTOR MAY ADJUST THE LOCATIONS OF THE CONSTRUCTION FENCE, CONSTRUCTION TRAILERS, AND CONSTRUCTION MATERIALS RECEIVING AND STORAGE AREAS, AS NEEDED TO ACCOMPLISH THE CONSTRUCTION. ALL CHANGES SHALL BE NOTATED ON THE EROSION CONTROL PLAN.
- 12. THE CONTRACTOR SHALL CONDUCT PERIODIC INSPECTIONS OF THE EROSION CONTROL MEASURES, AS REQUIRED AND NOTATED IN THE SWPPP. THE CONTRACTOR WILL
- MAINTAIN A LOG ON-SITE OF ALL INSPECTIONS WITH THE SWPPP. 13. ALL DITCHES AND SWALES GREATER THAN 5% SHALL BE ARMORED WITH AN APPROPRIATE EROSION CONTROL/REVEGETATION STABILIZATION MAT TO PROMOTE

14. CONTRACTOR MAY ADJUST THE LOCATION OF CONCRETE WASHOUT AREAS AS NEEDED TO ACCOMPLISH THE CONSTRUCTION.



- 4. IN MEDIAN AREAS, CONSTRUCT SO THAT THE TOPS OF THE





SUBDIVISION


00


DATE:2.12.2021 PROJECT # **REVISIONS:** 


EROSION CONTROL DETAIL














# SUBDIVISION T' F SECTION MERIDIAN OF FOOTHILL

VILI PL THE SO 11, TOW AST, SAI LOCATED
RANGE

DATE:2.12.2021 PROJECT # **REVISIONS:** 

SHEET NAME: ΓΥΡΙCAL DETAILS