

# Standard Specifications and Drawings

Prepared by
Santaquin City Engineering and Public Works.
(Portions of text and Unaltered Drawings
Provided by J-U-B Engineers, Inc.)

Approval by the Santaquin City Council January XX, 2025

This Manual Updated Yearly



## Chapter 4

Standard Specifications



#### 2024 Standard and Specifications and Drawings Updates

#### Errata for

Changes made to the Santaquin City Standard Specification and Drawings

#### Division 1

Section 1.23 Subsection E: Compaction test of Soil, Untreated Base Course The proposed change is the update the testing requirements to include subgrade

Section 1.23 Subsection E Compaction Test of Soil, Untreated Base Course, and subgrade:

- Laboratory test to establish maximum laboratory density shall be determined in accordance with AASHTO T-180, Method D or ASTM D 1557.
- 2) Samples to determine laboratory density shall be taken from the stockpiled backfill or from the uncompacted imported subgrade or base course material in place.
- 3) The acceptance of soil, subgrade, and base course, with respect to compaction shall be based upon the average density of all density tests made in a lot.
  - a) Field density tests shall be taken as specified in AASHTO T-191 or by use of a portable nuclear density testing device. Field density tests shall be taken at a depth equal to ½ the maximum depth of the lift tested.
  - b) A lot shall equal the amount of soil or untreated base course compacted in each production day.
  - c) A test lot shall be divided into sub-lots and one density test shall be taken within each sub-lot.
  - d) The location of sampling sites within the sub-lot shall be chosen on a random basis by use of a suitable random number table or at the locations designated by the Public Works Representative/Engineer.
  - e) Each test lot shall have a minimum of two (2) sub-lots. A sub-lot shall be no larger than 1,000 cubic yards for embankment, no larger than 200 cubic yards for backfill over pipe or against structures and no larger than 500 tons for untreated road base.
- 4) The test results of all samples tested shall be reported to the City. A test lot shall be accepted when the average of the density determinations is not less than the density required for that improvement in these specifications and when no one density determination is less than 95% of the density required by these specifications.
- 5) Compaction test not meeting the required specifications may be rejected and re-compaction or related construction efforts to obtain compaction shall be at the Developer/Contractor's expense.
- 6) All compaction testing must be completed no less than 24 hours prior to the placement of any structural material, road base, asphalt or concrete within the roadway and sidewalk.

#### Division 3

- Section 3.04 Subsection G. Tracer Wire
The proposed change requires a continuity test for tracer wire on pressure irrigation pipe

All pipe shall include a 12 gauge solid THHN tracer wire installed according to NESC standards. The locator wire shall be installed in the pipeline trench approximately 6-inches above the top of pipe. The locator wire shall be extended 30" into all service boxes to permit a continuity connection when doing line location.

A continuity test shall be conducted to ensure there are no breaks in the tracer wire prior to the placement of material over said wire.

Section 3.05 Subsection F. Service Box and Meter Box
 The proposed change requires a purple lid for the irrigation service box

Service Box and Meter Box shall be DFW Plastics 1324C4-12-4T 63D with a purple lid or approved equivalent.

- Section 3.05 Subsection F. Service Box and Meter The proposed change requires PVC conduit be installed between the PI and Culinary meter boxes

Where PI and culinary meters are located together, A 1 1/4" PVC conduit shall be installed extending from the PI meter box to the Culinary Water Box, and stub at least 2" into each box.

#### Division 3A

- Section 3A.04 Subsection I. Tracer Wire
The proposed change requires a continuity test for tracer wire on culinary water pipe

A continuity test shall be conducted to ensure there are no breaks in the tracer wire prior to the placement of material over said wire.

#### Division 3A

- Section 3A.05 Subsection D. Meter, Meter Setter Assembly, Meter Box and Cover: The proposed change requires PVC conduit be installed between the PI and Culinary meter boxes

Where PI and Culinary meters are located together, A 1 1/4" PVC conduit shall be installed extending from the PI meter box to the Culinary Water Box, and stub at least 2" into each box.

#### Division 3A

- Section 3A.05 Subsection D. Meter, Meter Setter Assembly, Meter Box and Cover: The proposed change requires 4" meter vaults to have drain rock instead of a concrete floor

4" Meter Vaults shall have no concrete floor. Place 12" of drain rock along the bottom of vault.

#### Division 6

- Section 6.06 Fire Hydrants

The proposed change requires Fire Hydrants to be located outside of the clear view area as defined by city code 10.16.090

The proposed change requires a minimum of a 3 foot square concrete maintenance pad around the base of fire hydrants

Proposed change to require an "snake pit" access box for the locator wires at the fire hydrant

Fire Hydrants shall be located outside of the clear view area as defined in Santaguin City Code

All Fire Hydrants shall have a concrete maintenance pad surrounding the base of the fire hydrant. The fire hydrant shall be located in the center of the concrete pad. The maintenance pad shall be a minimum of 3 foot wide by the width of the planter strip or 3 foot square, whichever is greater.

A snake pit access box (PART #: CD14BTP BLUE LID) or approved equivalent shall be provided by and installed by the developer to house the locator wires at the hydrant. Box shall be located between the hydrant and the curb and gutter and within the concrete maintenance pad.

- Section 6.10 Pressure Irrigation 4-Inch Flushing, Air Inlet and Removal Facility Proposed change to require 4" vaults to have drain rock instead of a concrete floor

Each 4-inch flushing, air inlet and removal facility shall be constructed as detailed and placed at the locations shown on the drawings. The work is to include excavation, gravel foundation, backfill, piping, fittings, concrete thrust blocks and collars, valves, utility boxes, sod replacement, and appurtenances.

4" Vaults shall have no concrete floor. Place 12" of drain rock along the bottom of vault.

#### Division 10

Section 10.03 Removal of Pavement, Sidewalks, Curbs, Etc.
 Proposed change to require asphalt joints to run diagonally at a small angle

Asphalt joints shall run diagonally across the roadway at a 1 to 2 degree angle

#### Division 13

- Section 13.04 Manholes

Proposed change to require flowable fill where manholes and inlet boxes are located close together

Flowable fill shall be used between the manhole and an inlet box if they are located 32" or less from each other.

- Section 13.07 Subsection A. Concrete Inlet boxes:
- Proposed change to correct the part number of the storm drain grate required

The storm drain inlet grate and frame shall be a D & L Supply I-35178 single unit with curb box with type "V" grate or equal.. Grates and frames are to be dipped in cold tar epoxy following fabrication. Following construction of the curb and gutter improvements and before the final inspection each inlet box shall have a decal mounted on the curb face adjacent to the inlet box. The decal shall be purchased from the City by the Developer.

Section 13.07 Subsection A. Concrete Inlet Boxes:
 Proposed change to require a 10" opening at the curb box

The opening of the curb box must be at least 10" wide.

Proposed change to adds Section 13.09 requirements for Underground Stormwater Detention Systems
 Section 13.09 UNDERGROUND STORMWATER DETENTION SYSTEMS
 All underground stormwater detention systems are required to have a 10" diameter inspection port located at the end of the infiltration gallery furthest away from the inlet at the chambers.

The inspection port shall have a threaded cap and have a minimum 10 inch cast iron lid for access.

#### Division 16

- Section 16.05 Topsoil

Proposed change to require fractured rock surface in detention basins

Detention basins shall have a minimum of 6 inches of 2-3 inch Fractured rock along the entire surface of the basin, if not landscaped with grass.

#### Division 20:

Section 20.02 Topsoil Requirements and Placement
 Proposed change to specify a topsoil mix for landscaping

Topsoil shall be fertile, sandy loam topsoil, obtained from well-drained areas. It shall be without admixture of subsoil or slag and shall be free of stones, lumps, sticks, plants or their roots, toxic substances or other extraneous matter that may be harmful to plant growth and would interfere with future maintenance. Topsoil pH range shall be 5.3 to 6.0 shall meet the requirements listed in the tables below. Native topsoil at the site may be used as the final topsoil layer if it is of adequate quality. Where topsoil is required a 6" layer of topsoil shall be placed.

#### Physical Properties

Test	pН	EC	SAR	% Sand	% Silt	% Clay	% OM
Acceptable level(s)	5.5-8.0	<3.0	<6.0	15-60	10-60	5-30	>1.0

#### **Nutrients**

Test	No3-N	P ppm	K ppm	Fe
	ppm			ppm
Acceptable level(s)	>20	>11	>130	>10

#### Section 20.04 Subsection A. Basic Irrigation Requirements

- Proposed change to specify a minimum of 2" diameter for the irrigation connection to open space areas
- Proposed change to require unions at all valves filters and connection points

The Developer/Irrigation Contractor shall provide labor, materials, equipment and services necessary to complete the irrigation work as defined in these specifications and as indicated on the Improvement Drawings. The Contractor shall coordinate work of this section with work of all related trades and subcontractors to assure smooth progression of work. Work shall include, but is not limited to:

- 1. The minimum service connection to all open space areas either public dedication or privately maintained must be a minimum of 2" diameter.
- 2. Completing the irrigation system as shown on the Improvement Drawings and required by these specifications.
- 3. Verifying the underground utility locations.
- 4. Protecting and/or restoring all existing improvements.
- 5. Trenching and backfilling for all pipes, valves and drain pits specified.
- 6. Furnishing and installing all filter mains, laterals, risers and fitting, heads, quick-coupling valves, gate valves, control valves, controllers, electric wire, controls, etc., and all necessary specialties and accessories.
- 7. Furnishing and installing all sleeves beneath walkways, roads, and driveways where required.
- 8. Testing of irrigation system.
- 9. Regulating and adjusting all heads and programming controller.
- 10. Unions shall be installed at all valves, filters, and connection points, etc.

#### Section 20.04 Sub-section C. Fittings

Proposed change to require swing joints on fittings 1" or larger.

Swing joints are required on all fittings 1" and greater in diameter.

#### Section 20.04 Subsection D. Automatic Controller

Proposed change to the model of automatic controller required and to require a hydrometer and valve to accompany the controller

The developer will check with the Public Works Director prior to purchasing an automatic controller. Unless directed otherwise the automatic controller will be a Huner controller with stainless steel pedestal mount\_ICC, with TBOX batter operated module. The automatic controller shall be a WeatherTrak pro3 2 wire controller and ET Pro3 2-Wire housing box. The controller shall be housed in a NEMA Type 4, weatherproof, watertight enclosure with lockable access door. The enclosure shall be at grade or pedestal mounted as determined by the Public Works Director.

The developer shall provide an appropriately sized Netafim combined hydrometer and valve, with a digital register, after the point of connection, such as the meter. The equipment must be installed with the manufacturer's required materials.

Section 20.04 Subsection J. Valves and Couplers:
 Proposed change to require manual isolation valves on sprinklers

Manual Isolation valves shall be installed at each sprinkler valve.

Section 20.04

Proposed change to add a requirement for filters before the flow meter, and bypass systems on filters larger than 4"

Sub-section L. Filters

All filters must be installed before the flow meter. Filters must be an auto-flushing Amiad filter or approved equivalent.

All Filters 4" or larger shall utilize a bypass system with a manual flush drain valve before the filter.

- Section 20.07 Trees

Proposed change to require deep root tree irrigation systems on trees

A deep root tree irrigation system shall be installed on all trees.

- Proposed change to add section 20.08 Recreational Facility specifications for recreational facilities, including pour-in-place rubber play surfaces for playgrounds, and pavilion materials.

Section 20.08 Recreational Facilities

Playgrounds: Pour-in-place rubber surfaces shall be installed under all playground equipment. The manner and area of installation shall be done according to the approved plans and the manufacturer's recommendations for both the play structure and play surface. Colors must be neutral earthtone colors approved by Santaquin City.

Pavillions: Any pavilions installed shall be finished with an architectural powder coated metal or aluminum construction.

#### Standard Drawings:

- All Drawings: Update title block to show current address
- W3 Update the label on 4" Double check valve to state that it must be testable
- PI2 change label on conduit between meter boxes to match specification text
- W7: Remove label that says 2" PVC on the Eclipse Hydrant Blow-Off Assembly and replace with 2" ductile iron

#### **CHAPTER 4**

### STANDARD SPECIFICATIONS TABLE OF CONTENTS

DIVISION 1: GENERAL REQUIREMENTS	
Section 1.01 PURPOSE OF DOCUMENTS	pg. 1
Section 1.02 DEFINITIONS	
Section 1.03 EXCAVATION PERMIT, FEES, AND BONDIN	G REQUIREDpg. 1
Sub-Section A. Permit Application	
Sub-Section B. Fee Assessment	
Sub-Section C. Bonding	
Section 1.04 CONTRACTOR AND CONSTRUCTION PLAN	
Section 1.05 PRE-CONSTRUCTION CONFERENCE	
Section 1.06 TIMELY COMPLIANCE WITH THE ISSUED F	'ERMITpg. 3
Sub-section A. Inspections	
Sub-section B. Notification of Needed Inspections	
Sub-section C. Responsibility of the Developer	
Sub-section D. Conflict	_
Section 1.07 ELECTRONIC AND RECORD DRAWINGS	
Section 1.08 TEMPORARY SERVICES	
Section 1.09 CODES AND STANDARDS	
Section 1.10 STATE AND LOCAL LAWS	
Section 1.11 COMPLIANCE WITH GOVERNMENTAL REC	
Sub-section A. United States Occupational Safety and	
Health Administration Regulations	1.0
Sub-section B. Utah State Industrial Commission Reg	urations
Sub-section C. City Codes and Ordinances Sub-section D. UDOT Requirements	
Sub-section E. Permits	
Section 1.12 FEDERAL, STATE, AND LOCAL INSPECTING	ACENCIES ng 5
Section 1.13 PUBLIC SAFETY AND CONVENIENCE	
Sub-section A. Compliance with Rules and Regulation	10
Sub-section B. Road Closures and Obstructions	15
Sub-section C. Protection of the Traveling Public	
Sub-section D. Hazardous Conditions	
Sub-section E. Dust and Debris Control	
Section 1.14 CONFINEMENT OF WORK AND ACCESS TO	ı
RIGHT-OF-WAY AND EASEMENTS	
Section 1.15 NOTIFICATION OF RESIDENTS	
Section 1.16 WEATHER CONDITIONS	pg. 6
Section 1.17 LAND MONUMENTS	
Section 1.18 SOURCE OF MATERIALS	
Section 1.19 CONSTRUCTION WATER	pg. 7
Section 1.20 OPERATION AND MAINTENANCE MANUAL	_Spg. 7
Section 1.21 INTERFERING STRUCTURES, UTILITIES AN	ID FACILITIESpg. 7
Section 1.22 MATERIAL AND COMPACTION TESTING	
Section 1.23 TESTING AND PROCESS CONTROL	pg. 8
Sub-section A. Quality Assurance	

Sub-section B.	Submittals	
Sub-section C.	Sampling	
Sub-section D.	Soil Classification Test	
Sub-section E.	Compaction Test of Soil and Untreated Base Course	
Sub-section F.	Test Roll of Roadway Sub-grade	
Sub-section G.	Gradation Test of Untreated Base Course	
Sub-section H.	Extraction – Gradation Testing of Bituminous Surface Cou	rse
Sub-section I.	Compaction Testing of Bituminous Surface Course	
Sub-section J.	Compressive Strength Testing of Concrete Cylinders	
Sub-section K.	Additional Concrete Testing	
Sub-section L.		
	. Summary Table of Tests and Certifications	
	LLATION OF UTILITY CONDUITS	
Section 1.25 PHOTO	GRAPHS	pg. 14
	XCAVATION AND BACKFILL	
	AL	
	CADES	
	ING	
	ING, BRACING AND SHORING OF EXCAVATIONS	
Section 2.05 CONTR	OL OF GROUNDWATER	pg. 15
Section 2.06 TRENC	H EXCAVATION	pg. 16
Sub-section A.	Normal Excavation	
Sub-section B.	Authorized Over-Excavation	
Sub-section C.	Unauthorized Over-Excavation	
Sub-section D.	Trench Width	
Sub-section E.	Trenches in Embankments	
Sub-section F.	Placement of Excavated Material	
Sub-section G.	Fine Grading the Trench Bottom	
Section 2.07 TRENC	H BACKFILL	pg. 17
Sub-section A.	Imported Granular Material	
Sub-section B.	Foundation Placement	
Sub-section C.	Pipe Embedment	
Sub-section D.	Final Backfill	
Sub-section E.	Clay Dams	
Sub-section F.	Compaction	
Section 2.08 TRENC	H CROSSINGS AND EASEMENTS	pg. 19
Section 2.09 RESTO	RATION OF CONSTRUCTION SITE	pg. 20
Section 2.10 OPEN 7	TRENCHES IN PUBLIC THOROUGHFARES	pg. 20
	OPER/CONTRACTOR RESPONSIBILITY	
<b>DIVISION 3: PRESSURE</b>	PIPE - PRESSURE IRRIGATION	
	AL	pg. 21
	LE IRON PIPE	
Sub-section A.		18
Sub-section B.		
Sub-section C.	Coatings and Linings for Ductile Iron Pipe	
Sub-section D.		
Sub-section E.		
	PE	pg. 22
Sub-section A.		ro
Sub-section B.		
Sub-section C.		
	STALLATION	ng. 22
Sub-section A.		
	Dewatering of Trench	

Sub-section C.	Laying of Pipe	
Sub-section D.	Thrust Blocking & Megalug Joint Restraint	
Sub-section E.	Connections to Existing Water Lines	
Sub-section F.	Corrosion Protection and Soil Tests	
Sub-section G.	Tracer Wire	
Sub-section H.	Dead end Pressure Irrigation Lines.	
Section 3.05 PRESS	URE IRRIGATION SERVICE CONNECTION	pg. 24
Sub-section A.	Service Saddle Specifications	
Sub-section B.	Polyethylene Tubing	
Sub-section C.	Compression Connection	
Sub-section D.	Service Fittings	
Sub-section E.	Angle Ball Service Valve	
Sub-section F.	Service Box and Meter	
Sub-section G.	PVC Pipe	
Sub-section H.	Hose Bib	
Sub-section I.	Location of Stub Pipes	
Sub-section J.	Service Pipe Installation	
Section 3.06 TESTING	G AND FLUSHING	pg. 27
Sub-section A.	Pressure Test	
Sub-section B.	Leakage Test	
Sub-section C.	Flushing	
	-	
<b>DIVISION 3A: PRESSURE F</b>	PIPE - CULINARY WATER	
Section 3A.01 GENERA	L	pg. 30
	E IRON PIPE	
Sub-section A.	Materials	10
Sub-section B.	Joints	
Sub-section C.	Coatings and Linings for Ductile Iron Pipe	
Sub-section D.	Flanges	
Sub-section E.	Fittings	
	E	pg. 31
Sub-section A.	Materials	10
Sub-section B.	Joints	
Sub-section C.	Fittings	
Section 3A.04 PIPE INS	TALLATION	pg. 31
Sub-section A.	Cutting	10
Sub-section B.	Dewatering of Trench	
Sub-section C.	Laying of Pipe	
Sub-section D.	Separation	
Sub-section E.	Pipe Bedding	
Sub-section F.	Thrust Blocking & Megalug Joint Restraints	
Sub-section G.	Connections to Existing Water Lines	
Sub-section H.	Corrosion Protection and Soil Tests	
Sub-section I.	Tracer wire	
Sub-section J.	Damage and Repair of Water Mains and Appurtenances	
Sub-section K.	Dead end water lines	
Section 3A.05 WATER	SERVICE LATERALS	pg. 34
Sub-section A.	Extent of Laterals	10
Sub-section B.	Excavation and Backfill	
Sub-section C.	Connection to Main	
Sub-section D.	Meter, Meter Setter Assembly, Meter Box and Cover	
Sub-section E.	Special Joints and Fittings	
Sub-section F.	Separation	
Sub-section G.	Location of Stub Pipes	
Sub-section H.	Flushing, Testing, and Disinfecting	
	NG, DISINFECTING, AND TESTING	pg. 36

Sub-section A.	Flushing	
Sub-section B.	Disinfection	
Sub-section C.	Bacteriological Test	
Sub-section D.	Pressure Test	
Sub-section E.	Leakage Test	
Section 3A.07 SURFA	CE WATER CROSSING	pg. 40
Sub-Section A.	Crossing Type	10
	Water Crossings greater than 15 feet (15')	
DIVISION 4: CONCRETE	PIPE	
	AL	pg. 41
Sub-section A.	Reinforced Concrete Pipe	
	Non-Reinforced Concrete Pipe	
	Bell and Spigot Joints	
	Minimum size and Slope Requirements	
	.YING	pg. 42
	L FOUNDATION FOR PIPE	
	LATION REQUIREMENTS FOR LINE AND GRADE	
Section 4.06 PIPE BE	DDING	pg. 42
Section 4.07 TESTS		
	Displacement Test	10
	Infiltration Test	
Sub-section C		
Sub-section D.		
Sub-section E.	Televising	
Section 4.08 MANHO	DLE CONNECTIONS	pg. 44
	SERVICE LATERALS	
Sub-section A.		
Sub-section B.	Excavation and Backfill	
Sub-section C.	Pipe	
Sub-section D.	Connection to Main	
Sub-section E.	Cover Over Sewer Lateral Lines	
Sub-section F.	Sewer Clean Outs	
Sub-section G.	Location of Stub Pipes	
Sub-section H.		
Sub-section I.	Damage and Repair of Sewers and Appurtenances	
DIVISION 4A:PVC PLAST	IC PIPE	
Section 4A 01 GENER	AL	ng 47
Section 4A.02 PIPE		
	Minimum Size and Slope Requirements	pg. 47
	SS	ng 47
	YING	
	L FOUNDATION FOR PIPE	
Section 4A 07 DIDE DE	LATION REQUIREMENTS FOR LINE AND GRADE DDING	pg. 40
Section 4A.07 FIFE BE Section 4A.08 TESTS		
	Disalogoment Test	pg. 40
	Displacement Test	
	Infiltration Test Exfiltration Test	
Sub-section D.		
Sub-section E.		50
	DLE CONNECTIONS	
Section 4A.10 SEWER	LATERAL CONNECTIONS	pg. 50

Section 4A.11 SEWI	ER SERVICE LATERALS	pg. 50
Sub-section .	A. Extent of Laterals and Location of Laterals	
Sub-section 1	B. Excavation and Backfill	
Sub-section	C. Pipe	
Sub-section 1	D. Connection to Main	
Sub-section 1	E. Cover Over Sewer Lateral Lines	
Sub-section l	F. Sewer Clean Outs	
Sub-section	G. Location of Stub Pipes	
Sub-section 1	C	
Sub-section 1		
Section 4A.12 "GO/N	NO-GO" MANDREL PROOF TESTING	pg. 51
	IYLENE CORRUGATED PIPE	
	RAL	
Section 4B.02 PIPE		pg. 53
Section 4B.03 JOIN	TS	pg. 53
	ORATIONS	
Section 4B.05 PIPE	LAYING	pg. 54
Section 4B.06 GRAV	/EL FOUNDATION FOR PIPE	pg. 54
	ALLATION REQUIREMENTS FOR LINE AND GRADE	
Section 4B.08 PIPE	BEDDING	pg. 54
Section 4B.09 TEST	S	pg. 55
Sub-section .	A. Displacement Test	
	B. Televising	
Section 4B.10 MAN	HOLE CONNECTIONS	pg. 55
Section 4B.11 LATE	RAL CONNECTIONS	pg. 55
DIVISION 4C: POLYETH	IYLENE CORRUGATED PIPE WITH WATER TIG	HT JOINTS
	RAL	
	NGS	
	LAYING	
	/EL FOUNDATION FOR PIPE	
	ALLATION REQUIREMENTS FOR LINE AND GRADE	
	BEDDING	
Section 4C.08 TEST		
	A. Displacement Test	
	B. Infiltration Test	
Sub-section		
Sub-section 1		
Sub-section		
	HOLE CONNECTIONS	ng 59
	RAL CONNECTIONS	
	NO-GO" MANDREL PROOF TESTING	
DIVISION 5 MANHOL	ES	
	ERAL	ng 60
	CRETE BASE	
	KFILL REQUIREMENTS	
	L AND CONE SECTIONS	
Sub-section .		pg. 00
	MANHOLES	ng 61
Sub-section		ps. 01
Sub-section 1		
Sub-section	· · · · · · · · · · · · · · · · · · ·	
Sub-section 1		

Section 5.06	MANHOLE FRAMES AND COVERS	pg.	61
Sub-s	section A. Setting Manhole Frames and Covers		
Section 5.07	CONNECTIONS TO EXISTING SEWER	pg.	62
Section 5.08	INCOMING SEWER LINES		
Section 5.09	PREVENTING MATERIALS FROM ENTERING THE SEWER MAIN	pg.	63
Section 5.10	TESTING OF MANHOLES, GREASE INTERCEPTORS & SAND/OIL		
	INTERCEPTORS		
Section 5.11	Pipe Connections to Manholes	pg.	64
DIVISION 6: VAL	LVES, COUPLINGS, AND FIRE HYDRANTS		
Section 6.01	GENERAL	pg.	65
Section 6.02	RESILIENT SEATED GATE VALVE		
Section 6.03	BUTTERFLY VALVE		
Section 6.04	VALVE BOXES		
Section 6.05	COUPLINGS		
Section 6.06	FIRE HYDRANTS		
Section 6.07	BLOWOFF VALVE		
Section 6.08	PRESSURE IRRIGATION 2-INCH AIR INLET AND REMOVAL FACILITY		
Section 6.09	PRESSURE IRRIGATION DRAINS		
Section 6.10	PRESSURE IRRIGATION 4-INCH FLUSHING AIR INLET AND REMOVAL FACILITY .	pg.	68
DIVISION 7: EAR	RTHWORK		
Section 7.01	GENERAL	pg.	70
Section 7.02	EXCAVATION FOR STRUCTURES	pg.	70
Section 7.03	GRANULAR FOUNDATION BORROW	pg.	70
	BACKFILL AROUND STRUCTURES		
Section 7.05	CONSTRUCTION OF EMBANKMENTS AND FILLS	pg.	70
	section A. Foundation Preparation		
Sub-s	section B. Placement		
	section C. Borrow		
	COMPACTION OF MATERIALS	pg.	72
	section A. Under Roadways		
	section B. Under Sidewalk and Driveways		
Section 7.07	REMOVAL OF DEFECTIVE FILL AND PLACEMENT OF ACCEPTABLE FILL	pg.	73
DIVISION 8: POR	RTLAND CEMENT CONCRETE		
Section 8.01	GENERAL	pg.	74
Section 8.02	MATERIALS	pg.	74
	section A. Portland Cement		
	section B. Aggregate		
	section C. Water		
	section D. Air-Entraining Agent		
	section E. Steel Reinforcement		
	section F. Water-Reducing and Set-Retarding Admixtures		
Sub-s	section G. Curing Compound		
Section 8.03	CLASS OF CONCRETE		
Section 8.04	COMPOSITION OF CONCRETE	pg.	76
	section A. Aggregate		
	section B. Water		
	section C. Air-Content		
	section D. Admixtures		
Section 8.05	DESIGN OF THE CONCRETE MIX		
Section 8.06	OBSERVATION AND TESTING		
Section 8.07	HANDLING AND MEASUREMENT OF MATERIALS		
Section 8.08	MIXERS AND MIXING	pg.	77

Section 8.09	FORMS		
Section 8.10	PREPARATION OF FORMS AND SUBGRADE	pg.	. 78
Section 8.11	CONVEYING	pg.	78
Section 8.12	PLACING	pg.	78
Section 8.13	CONSTRUCTION JOINTS	pg.	79
Section 8.14	EXPANSION AND CONTRACTION JOINTS	pg.	79
Section 8.15	WATERSTOP		
Section 8.16	REMOVAL OF FORMS		
Section 8.17	FINISHING FORMED SURFACES	10	
Section 8.18	FINISHING UNFORMED SURFACES	10	
Section 8.19	CURING AND PROTECTION		
Section 8.20	REMOVAL OR REPAIR		
Section 8.21	CONCRETING IN COLD WEATHER	10	
Section 8.22	CONCRETING IN HOT WEATHER	pg	. 81
	NFORCING STEEL		
	GENERAL		
	FABRICATION AND PLACING REINFORCEMENT	pg	. 82
	section A. Fabrication		
	section B. Clearances		
	section C. Support		
	section D. Splicing		
Section 9.03	EPOXY COATING	pg	. 83
	section A. Prequalify all Coatings		
	section B. Coat Bars as Specified		
	section C. Handling		
Section 9.04	FIELD CUTTING EPOXY-COATED BARS	pg	. 84
	section A. Cutting		
Sub-s	section B. Repairing		
DIVIGION 10 DEG			
	TORATION OF SURFACE IMPROVEMENTS		o <b>-</b>
	GENERAL		
	FIELD VERIFICATION OF IMPROVEMENTS		
	REMOVAL OF PAVEMENT, SIDEWALKS, CURBS, ETC	10	
	MATERIALS	pg.	. 85
	section A. Untreated Base Course		
	section B. Bituminous Surface Course		
	section C. Concrete		
Section 10.05	RESTORING BITUMINOUS, CONCRETE, OR ASPHALT STREET		0.0
0.1	SURFACES	pg.	. 86
	section A. Before Excavation		
	section B. Temporary Graded Surface		
	section C. Preparation for Paving		
	section D. Bituminous Surface		0.0
	GRAVEL SURFACE	pg.	. 86
	section A. Layer Thickness		
	section B. Placement		
	section C. Gradation		0.7
	MISCELLANEOUS IMPROVEMENTS	10	
	RESTORATION OF SURFACES		
	CLEANUP		
Section 10.10	PAVEMENT MARKINGS	pg.	. 87
DIVIDION 44 PO	DWAY CONCEDUCETON		
	ADWAY CONSTRUCTION		0.0
	GENERALMINIMUM ROADWAY CROSS SECTION		
Section 11 07	MINIMUM RUADWAY UKUSS SECTION	ng	XX

Section	11.03 PULVERIZING	pg.	. 88
	11.04 EARTHWORK		
	11.05 ROADWAY EXCAVATION		
Section	11.06 SUBGRADE PREPARATION	pg.	. 88
Section	11.07 DRAIN ROCK	pg.	89
	11.08 GRANULAR BORROW		
	11.09 GRANULAR BACKFILL BORROW		
Section	11.10 FLOWABLE BACKFILL	pg.	89
	Sub-section A. Cement	10	
	Sub-section B. Fly Ash		
	Sub-section C. Fine Aggregate		
	Sub-section D. Mix Design		
Section	11.11 BASE COURSE	pg.	90
Section	11.12 TACK COAT	pg.	91
	11.13 BITUMINOUS ASPHALT CEMENT PAVEMENT		
	11.14 ADJUSTING MANHOLES AND VALVE BOXES TO FINAL GRADE		
	11.15 PAVEMENT CRACK SEAL		
	Sub-section A. Quality Assurance	10	
	Sub-section B. Filler and Sealer Materials		
	Sub-section C. Equipment		
	Sub-section D. Advanced Preparation		
	Sub-section E. Application		
	Sub-section F. Backer Rod		
Section	11.16 CHIP SEAL	pg.	. 95
	Sub-section A. Submittals		
	Sub-section B. Quality Assurance		
	Sub-section C. Paving Asphalt		
	Sub-section D. Cover Material		
	Sub-section E. Preparation		
	Sub-section F. Application		
	Sub-section G. Rolling		
	Sub-section H. Fog Seal		
	Sub-section I. Cleanup and Repair		
	Sub-section J. Acceptance		
Section	11.17 PAVEMENT MARKINGS	pg.	98
	Sub-section A. Materials		
	Sub-section B. Preparation		
	Sub-section C. Application		
	Sub-section D. Removing Pavement Markings		
	CONCRETE CURB, GUTTER AND SIDEWALK		
	12.01 GENERAL		
	12.02 CONCRETE		
	12.03 GRADE		
	12.04 FORMS		
	12.05 SUBGRADE PREPARATION		
	12.06 CONSTRUCTION OF CURB, GUTTER AND SIDEWALK		
	12.07 CONCRETE CURBWALL		
	12.08 6-INCH CONCRETE DRIVE APPROACH		
Section	12.09 ACCESSIBILITY STANDARDS IN PUBLIC RIGHTS-OF-WAY	. pg. 1	102
	Sub-section A. Sidewalks		
	Sub-section B. Curb Ramps		
	Sub-section C. Landings		
	Sub-section D. Side Flares		

Sub-s	section E.	Built up Curb Ramps	
Sub-s	section F.	Obstructions	
Sub-s	section G.	Location of Marked Crossings	
Sub-s	section H.	Diagonal Curb Ramps	
Sub-s	section I.	Curb Ramps Associated with Trails	
Sub-s	section J.	Detectable Warnings	
Sub-s	section K.	Islands	
		Pedestrian Crossings	
Section 12.10	LANDSO	CAPE RESTORATION	pg. 105
<b>DIVISION 13: STO</b>			
Section 13.01	GENERA	L	pg. 106
		TALLATION	
		LES	10
		TE	
		RCING STEEL	
		DRAIN AND INLET BOXES	pg. 106
		Concrete Inlet Boxes	
		PVC Inlets	
		NNECTING INLET BOXES TO EXISTING STORM DRAIN	
Section 13.09 (	JNDERGO	UNDSTORMWATER DETENTION SYSTEMS	PG.111
		RTMENT OF TRANSPORTATION RIGHTS-OF-W	
		L	
		LINE AGREEMENT	
Section 14.03	INSPECT	TION FEES	pg. 108
<b>DIVISION 15: CAS</b>			
		L	
		ALS	
		UCTION METHODS	
		D GRADE	
		R PIPE INSTALLATION THROUGH CASINGS	
		SPACERS	
Section 15.07	CASING	END SEALS	pg. 110
<b>DIVISION 16: DET</b>	ENTION	BASINS	
Section 16.01	GENERA	L	pg. 111
Section 16.02	EARTHW	VORK	pg. 111
Section 16.03	CONCRE	TE AND REINFORCING STEEL	pg. 111
Section 16.04			
Section 16.05	TOPSOIL		pg. 111
DIVISION 17: CON	DUIT		
Section 17.01	GENERA	L	pg. 112
		CONDUIT	
	section A.	Materials	- <del>-</del>
Sub-s	section B.	Location	
	section C.	Magnetic Locator Tape	
Section 17.03	INSTALI	_ATION	pg. 112
Sub-s	section A.	Cutting	
	section B.	Dewatering of Trench	
	section C.	Laying of Conduit	
Sub-s	section D	Redding	

<b>DIVISION 18: RESIDENTIA</b>	L & SMALL COMMERCIAL PUMP SYSTEMS
Section 18.01 GENERA	Lpg. 114
Sub-section A.	Installation
Sub-section B.	Inspection and Testing
Sub-section C.	Deviation from Requirements
DIVISION 19: STREET LIG	HTING
	Lpg. 117
	LIGHTS ALONG LOCAL AND COLLECTOR STREETSpg. 117
Sub-section A.	Placement
Sub-section B.	Luminaire
	Pole and Base
Sub-section D.	Lamp
	Installation
Section 19.03 STREET	LIGHTS ALONG MAIN STREETpg. 118
Sub-section A.	Placement
Sub-section B.	Luminaire
Sub-section C.	Pole and Base
Sub-section D.	Lamp
Sub-section E.	Installation
Section 19.04 STREET	LIGHTS ALONG ARTERIAL STREETSpg. 118
Sub-section A.	Placement
Sub-section B.	Luminaire
Sub-section C.	Pole and Base
Sub-section D.	Lamp
Sub-section E.	Foundation
DIVISION 20: LANDSCAPI	NG
	Lpg. 120
	REQUIREMENTS AND PLACEMENTpg. 120
	DRIVE APPROACHESpg. 120
	ION SYSTEM – MATERIALSpg. 120
	Basic Irrigation Requirements
Sub-section B.	Pipe
Sub-section C.	Fittings
Sub-section D.	Automatic Controller
Sub-section E.	Automatic Control Valve
Sub-section F.	Rotary Sprinkler
Sub-section G.	Plastic Nozzles
Sub-section H.	Valve Box
Sub-section I.	Control Wire, Wire Connectors and Sealing Cement
Sub-section J.	Valves and Couplers
Sub-section K.	Main Line Connections
Sub-Section L.	Filters
	ION SYSTEM – INSTALLATIONpg. 123
Sub-section A.	Trenching
Sub-section B.	Pipe Installation
	G OF TURFpg. 126
Sub-section A.	Seeding
Sub-section B.	Sodding
Sub-section C.	Maintenance
Section 20.07 TREES	pg. 128
Sub-section A.	Approved Tree Species List
Sub-section B.	Trees Prohibited in Park Strips

Sub-section C.	Tree Substitutions for Unique Environments	
Sub-section D.	Streetscape Substitutions	
Sub-section E.	Tree and Shrub Installation	
Section 20.08 Recreationa	al Facilities	pg 143
Section 20.09 Bonding		pg. 138
C		10