



CITY HALL REMODEL

115 2nd Street SE | Sidney, MT 59270









Google Earth

DWG SET #:


Preliminary Drawings -- Not For Construction DD Package


sdi architects + design architects + design


Revisions


Copyright © 2023 *DRAWN* BJ DATE 04.17.2023

Index, & Locations









59270 Sidney, Sidney of Stree

Revisions

Copyright © 2023

BY SDI ARCHITECTS + DESIGN

DATE 04.28.2023

Finish Floor

& Reflected


Ceiling Plan

JOB # 2022007

DRAWN JMJ

CHECK BJ

SQİ



| sdi architects + design | 909 main street | miles city, montana 5930



CITY HALL REMODEL

City of Sidney
115 2nd Street SE, Sidney, MT 59270

Revisions

Copyright © 2023
BY SDI ARCHITECTS + DESIGN

JOB # 2022007
DRAWN BJ
CHECK BJ
DATE 04.28.2023

Exterior Elevations

sdi architects + desigr 909 main stree miles city, montana 5930



CITY HALL REMODEL
City of Sidney
115 2nd Street SE, Sidney, MT 59270


Revisions


Copyright © 2023
BY SDI ARCHITECTS + DESIGN

JOB # 2022007
DRAWN MET
CHECK BJ
DATE 04.28.2023

Building Sections

Preliminary Drawings -- Not For Construction A3.0





59270 of Sidney 2nd Street SE, Sidney, MT City 115 Revisions

Copyright © 2023
BY SDI ARCHITECTS + DESIGN JOB# 2022007 DRAWN JMJ CHECK BJ DATE 04.17.2023

Interior Elevations

A6.1

\mathcal{O} **MECHANICAL SPECIFICATIONS:** 23 50 00 & 23 55 00 MECHANICAL & PLUMBING EQUIPMENT: SPLIT SYSTEM FURNACE & CONDENSING UNIT SCHEDULE PLUMBING FIXTURE AND EQUIPMENT SCHEDULE Sİ NEW EQUIPMENT IS DENOTED BY XX-# SEE SCHEDULES. & DETAILS. NEW EQUIPMENT MANUFACTURER & MODEL NUMBERS LISTED IN SCHEDULES & NOTES DEFINE . ALL WORK SHALL BE PERFORMED BY OR DIRECTLY SUPERVISED BY AN EXPERIENCED O AND SKILLED CRAFTSMAN IN THE TRADE. ALL WORK SHALL BE NEAT, CLEAN AND PROFESSIONAL LOOKING. UNSATISFACTORY INSTALLATION IDENTIFIED BY OWNER, GC PERFORMANCE, PHYSICAL AND QUALITY REQUIREMENTS. THE CONTRACTOR SHALL NOTES/REMARKS FIXTURE CW HW/TEPID WASTE VENT HEATING CAPACITY ELECTRICAL MANUFACTURER CONTROL VERIFY ANY CHANGES TO EQUIPMENT LISTED MEET OR EXCEED THOSE REQUIREMENTS \mathcal{O} LBWD00 P-TRAP ELKAY SHALL REPLACE AT THE CONTRACTOR'S EXPENSE WITHOUT IMPACT TO THE MODEL NO. CONTRACTOR IS RESPONSIBLE TO REPLACE EQUIPMENT AS HIS EXPENSE IF BOTTLE FILL STATION CONSTRUCTION SCHEDULE. ALTERNATE EQUIPMENT IS PURCHASED & INSTALLED WHICH FAILS TO MEET PROJECT STOPS OR EQUAL BY GUARDIAN, TRANE, AM ST RYANT CARRIER, ARCOAIRE, DAIKEN ELKAY P-TRAP INSTALL ALL EQUIPMENT PER THE MANUFACTURER'S RECOMMENDATIONS AND BUBBLER & BOTTLE EZSTL8WSLK COOLER - ADA S PROVIDE ADEQUATE CONCEALED BLOCKING AND ANCHORING FOR ALL CEILING AND FILL, ADA APRON STOPS NG | 58.0 | 55.7 | 8.3 | 120-1 | YORK TM9Y060B12 WALL MOUNTED EQUIPMENT, HARDWARE AND ACCESSORIES. WEST OFF | 191 | 0.50 | FLOOR DRAIN INSTALL EQUIPMENT TO ALLOW SERVICE CLEARANCES AS SUGGESTED BY THE JR SMITH 2005-NB ___ ___ ___ DEEP SEAL PROVIDE PROVEN 3. CEILING FANS SHALL HAVE REMOVABLE PERMANENTLY LUBRICATED, ENCLOSED TRAP GUARDS F-2 VERT EAST OFF | 1100 | 215 | 0.50 | NG | 61.8 | 59.3 | 8.3 | 120-1|YORK TM9Y060B12 Φ BRUSHLESS DC MOTORS W/ BUILT-IN SPEED SELECTOR & THERMAL CUTOFF FUSE. WORKMANSHIP SHALL COMPLY WITH THE CURRENT CODES AND ALL OTHER LOCAL HOUSING TO BE RUST PROOF. FANS SHALL BE LOW SONE. GARBAGE **EVOLUTION** IN-SINK-WALL SWITC 10.7 | 120-1 | YORK TM9Y100C20 F-3 VERT NG | 87.2 | 83.7 CHAMBERS CODES AND ORDINANCES. DISPOSER ERATOR EXCEL COORD W/ E PROVIDE FIXTURE FITTINGS NOT SANITARY TEES AT FIXTURE BRANCH 5. STORAGE OF MATERIAL: STORE ALL MATERIALS PROVIDE ON PROJECT PROTECTED WATER*TITE AB9700HA MOUNT 42"AFF FROM THE ENVIRONMENT. STORE MATERIALS OFF OF FINISHED GRADE OR FLOOR. CONNECTIONS TO MAINS PER CODE. ICE MAKER BOX LANCE SET HEATING CFM WITH FURNACE BLOWER AT SAME SPEED/SETTING AS COOLING CFM PROVIDE CRIBBING, SHELVING OR STORAGE CONTAINERS AS NECESSARY. PROVIDE WATER CLOSETS: PROVIDE STAINLESS STEEL (SS) CLOSET FLANGE W/ HEAVY PIPE AND DUCT CAPS FOR ALL STORED, STAGED AND HUNG MATERIALS. DUTY SS SCREWS, OATEY OR EQUAL. PROVIDE 1" GAP IN CAULK BETWEEN PROVIDE 7 DAY PROGRAMMABLE TOUCHSCREEN TSTAT. HONEYWELL VISIONPRO OR EQUAL. CONTROL OSA DAMPER - OPEN WHEN FURNACE IS ON, CLOSED WHEN FURNACE IS OFF. OAM STD 0355.012 6114.115.002 P-TRAP I POP-UP LAVATORY CLOSET & FLOOR AT BACK OF CLOSET FOR DETECTION OF SEAL FAILURE. PROVIDE 7 DAY PROGRAMMABLE TSTAT. HONEYWELL VISIONPRO TOUCH SCREEN OR EQUAL. PROVIDE THERMOSTAT WITH STAGING TO CONTROL OFFSETS, TRANSITIONS AND CHANGES IN DIRECTION IN PIPES AND DUCTS SHALL STOPS 0.5GPM AERATO MADE AS REQUIRED. MAINTAIN PROPER HEAD ROOM AND PITCH OF SLOPING PIPES NEYWELL JADE CONTROLLER ON ECON MIXING BOX O WHETHER OR NOT INDICATED ON THE DRAWINGS. FURNISH AND INSTALL ALL AM STD 0491.019 6114.115.002 P-TRAP POP-UP INSULATION SHALL BE FORMALDEHYDE FREE _AVATORY DUCTWORK FITTINGS, TRAPS, AIR VENTS, SANITARY VENTS, ETC., AS REQUIRED TO CLG COIL DATA ELECTRICAL IANUFACTURER & MODEL NO. S CT STOPS 0.5GPM AERATO AFFECT THESE OFFSETS, TRANSITIONS AND CHANGES IN DIRECTION. 2. INSULATION PRODUCTS SHALL BE UL 723/ASTM E84 LISTED. R EQUAL BY GUARDIAN, TRANE, AM ST SENS EAT °F MCA MOCF DBL COMP SIN CHECK THESE DRAWINGS ARE DIAGRAMMATIC AND SHALL NOT BE SCALED. ADDITIONAL DATA ELKAY DLR332210 -TRAP NOTE 4, ADA TRI TRAINFR PROVIDE PIPE INSULATION AS FOLLOW:. SHALL BE FROM THE DESIGN TEAM THROUGH WRITTEN CLARIFICATION ONLY. VERIFY LK800GN08T4 STOPS DEEP 1/2" FIBERGLASS INSULATION OR EQUIVALENT THERMAL RESISTANCE FOR ANOTHER ALL EXISTING CONDITIONS, ELEVATIONS, AND DIMENSIONS BEFORE PROCEEDING WITH CC-1 CU-1 17 | 25.7 | 25.7 | 63 | 208-1 | 21.4 YORK XAFB36 / YFK36B21A F-1 95 35 NSULATION TYPE ON COLD WATER PIPING, ADA SHOWER FREEDOM ANY PORTION OF ANY WORK. APF5430BF5 SEE NOTES -TRAP NOTE 6 1" INSULATION ON HW. SURROUND SHOWERS 17 | 28.0 | 28.0 | 95 | PROVIDE 20MIL PVC COVERS ON FITTINGS. WHITE UNLESS NOTED OTHERWISE. 63 | 208-1 | 21.4 | YORK XAFB36 / YFK36B21A CC-2 | CU-2 F-2 35 8. WHERE LACK OF INFORMATION, OR ANY DISCREPANCY SHOULD APPEAR IN THE WATER CLOSET ADA INSULATION ON LAV'S AND SINKS WITH EXPOSED PIPING, 211AA.104/5 5325.010 AM STD MAAP>800, 1.28 DRAWINGS OR SPECIFICATIONS, REQUEST WRITTEN INTERPRETATION FROM THE ENGINEER BEFORE PROCEEDING WITH THAT PORTION OF THE WORK. CC-3 CU-317 | 55.3 49.7 208-1 31.4 50 YORK XAFC60 / YFK60B21A FM, FT, ADA STOPS ACCESS SIDE 4. DUCTWORK WRAP OR LINER: ON SA, AND RA DUCTS SHALL HAVE A MIN THERMAL RESISTANCE R-8 WHERE GEND FM = FLOOR MOUNTED, WM = WALL MOUNTED, CT = COUNTERTOP, ADA = ADA APPROVED INSULATION ON HW, CW & SAN AS APPROPRIATE PERFORM WORK IN ACCORDANCE WITH GOOD COMMERCIAL PRACTICE. THE GOOD PROVIDE CASED COIL, THERMAL EXPANSION VALVE PER FACTORY SIZING, PROVIDE CONDENSATE DRAIN W/ 2" P-TRAP AND COLD WEATHER HARD START KIT. SEE CONDENSATE DRAIN DETAIL CONCEALED ABOVE CEILINGS AND IN WALLS. EXPOSED TO VIEW SHALL BE APPEARANCE OF THE FINISHED WORK SHALL BE OF EQUAL IMPORTANCE WITH ITS CP = CHROME PLATED, TP = TRAP PRIMER, PA = PRESSURE ASSIST, CM = CEILING MOUNTED, ADA = AMERICANS WITH DISABILITIES ACT OVIDE DUCT TRANSITIONS AS REQUIRED FROM FURNACE TO COIL, PROVIDE FACTORY LINESET OR ACR COPPER TUBING. MOUNT UNIT ON CONC PAD OR EQUIPMENT BASE 3" ABOVE GRADE. UNINSULATED MECHANICAL EFFICIENCY. DESIGN TEAM/OWNER MAY REJECT WORK IF WORKMANSHIP GENERAL ROOM EXHAUST AIR DUCTWORK SHALL HAVE A MIN THERMAI ROLLTE WIRING FROM FURNACE CONTROLLER / PROGRAMMARIE THERMOSTAT AND/OR APPEARANCE ARE NOT SATISFACTORY GENERAL NOTES RESISTANCE OF R-6 WHEN LOCATED ABOVE CEILINGS. SEE ARCHITECTURAL DWGS FOR MOUNTING HEIGHTS ON ALL WALL MOUNTED FIXTURES. 2. FIXTURES OR EQUAL BY AM STD, DELTA, KOHLER, CRANE, WATTS, ZURN, SYMMONS, PFISTER 4.3. WELDED GREASE DUCT WITH FIRE WRAP TO REQUIREMENTS OF THE IMC. 10. BE RESPONSIBLE FOR AND COORDINATE THE WORK OF ALL SUBCONTRACTORS OUTSIDE AIR JUSTIFICATION WORKING UNDER MECHANICAL CONTRACTOR. CONFER AND COOPERATE WITH OTHER 23 65 00 IDENTIFICATION: TRADES AND COORDINATE THE WORK IN PROPER RELATION WITH THEIRS. COMPLY WITH ASME A13.1 FOR IDENTIFICATION AND COLOR. 1 PAINTED ESCUTCHEONS ADA INSULATION ON SAN CW. & HW. COVERPLATE FOR FAUCET HOLES IN LAV. ASSE 1070 MIXING VALVE COORDINATE CEILING CAVITY SPACE CAREFULLY WITH OTHER TRADES. PROVIDE MARKERS, AND LABELS FOR PIPE, DUCTWORK AND EQUIPMENT LOCATED INDOORS, PROVIDE PAINTED STENCILS FOR PIPE, DUCTWORK AND EQUIPMENT LOCATED OUTDOORS OR WHERE SYSTEMS ARE EXPOSED TO WEATHER. PAINT SHALL BE SUITABLE FOR EXTERNAL 2. PAINTED ESCUTCHEONS, ADA INSULATION ON SAN, CW. & HW. COVERPLATE FOR FAUCET HOLES IN LAV INSTALL TRAP PRIMER TAIL PIECE SIOUX CHIEF 213-090. ROOM CHARACTERISTICS MECHANICAL VENTILATION (OSA) NATURAL VENTILATION 11. PROPERLY LOCATE ANCHORS, CHASES, RECESSES AND OPENINGS REQUIRED FOR THE 1/2 ROUTE CONTINUOUS SOFT COPPER TUBING OR PEX FROM TAIL PIECE DN IN WALL TO FD-1 PRIMER CONNECTION. TUBING SHALL HAVE NO JOINTS FROM TAIL PIECE TO FD-1. PROPER INSTALLATION OF THE WORK. ARRANGE WITH THE PROPER CONTRACTORS OPERABLE OPENINGS CFM REQ'D CFM FOR THE BUILDING OF ANCHORS, ETC. AND FOR LEAVING REQUIRED CHASES, PIPE IDENTIFICATION SHALL CONFORM TO DESCRIPTIONS IN LEGEND AND THE FOLLOWING: 3. MOUNT 84"AFF, 5000 PSI WORKING PRESSURE. PROVIDE HOTSY SPRAY GUN WITH PIPE HOLSTER PER OWNER'S PREFERENCES SOFT PROVIDED REQ'D PROVIDED MAX MIN RECESSES AND OPENINGS. REQUIRED ON ALL PIPING WHERE NON-POTABLE SYSTEMS ARE PRENSENT BY CODE. 4. PROVIDE ASSE 1070 MIX VALVE. SEE PLANS FOR WHICH SINKS HAVE GD AND ADJUST QTY OF STRAINER BASKET/ DRAINS a. PIPE SYSTEM AS DESIGNATED IN PLAN. 0.0 50 80 12. COORDINATE WORK WITH OTHER TRADES. COORDINATE ALL EQUIPMENT WITH CONTROL 54 2.2 ----70 __ 5. ASSE 1016 PRESSURE BALANCE MIXING VALVE W/INTEGRAL STOPS, SOAP DISH, CURTAIN, ROD, GRAB BAR, WALL/HAND SHOWER,FOLD UP SEAT, FLEXIBLE METAL HOSE, SLIDE BAR & DRAIN SYSTEM FOR A COMPLETE OPERABLE SYSTEM. . DIRECTIONAL FLOW ARROWS ORDER LH & RH MODELS TO WORK WITH LAYOUT, COLLAPSIBLE WATER RETAINER, WEIGHTED SHOWER CURTAIN AND ROD, 23 RR 2.2 0.0 50 54 70 80 d. TWENTY FIVE FEET (25'-0") MAXIMUM SPACING. ___ --___ 13. MECH CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS FOR THIS SCOPE e. AT ALL CHANGES IN DIRECTION. ON EACH SIDE OF STRUCTURAL PENETRATIONS (WALLS, FLOORS, CEILINGS, ETC.) AND COORDINATION W/ UTILITY CONNECTIONS AND SERVICES. 62 2.5 0.0 140 100 150 ___ ___ __ g. WHERE THE NEXT PIPE IDENTIFICATION CANNOT BE SEEN. h. LOCATIONS WHERE MAINTENANCE ACCESS WOULD OCCUR AND LABELS ARE NOT 14. WORK SHALL BE PERFORMED BY A LICENSED AND BONDED CONTRACTOR (IN CEILING EXHAUST FANS 20.0 509 324 360 30 CHAMBERS 1232 49.3 IMMEDIATELY VISIBLE. ___ __ --WYOMING) UTILIZING TRADESMEN SKILLED IN THE ART AND IN ACCORDANCE WITH PROVIDE EQUIPMENT IDENTIFICATION FOR ALL EQUIPMENT THAT HAS DESIGNATIONS IN ACCEPTABLE PRACTICES AND LICENSED WITH THE CITY OF RIVERTON. PLAN. IDENTIFY STARTERS, CONTROLS FOR EQUIPMENT AND EQUIPMENT ITSELF (UNLESS -3 SYSTEM PROVIDES 18% OSA VOZ= 324 360 =VOT EQUIPMENT DESIGNATION IS LOCATED PERMANENTLY ON NAMEPLATE). 15. PROVIDE AND INSTALL ALL INCIDENTAL ITEMS REQUIRED FOR A COMPLETE AND STATIC ELECTRICAL ACCESSORIES MANUFACTURER & MODE CONTRO BACKFLOW PREVENTERS: WHERE NON-POTABLE SYSTEMS OCCUR IN BUILDING (SITE FUNCTIONING SYSTEM. EQUIPMENT, MOTORS, ETC., TO BE LOCATED AND INSTALLED O1 ENTRY 139 20.0 5.6 39 OR EQUAL BY DELTA, BROAN, WESTWIND, L ___ ___ ___ PRESSURE IRRIGATION, ETC). PLACARD SHALL BE PROVIDE AT EVERY BACKFLOW PREVENTER TO SONES CC SENSOR AS SHOWN ON THE PLAN. DEVIATIONS SHALL BE APPROVED PRIOR TO INSTALLATION DAMPER PFRATIC IDENTIFY SERVICE OF PIPING DOWNSTREAM OF BACKFLOW PREVENTER Y/N MAIN OFF 582 23.3 21.0 50 89 90 ___ __ __ 16. CONTRACTOR SHALL INSTALL ANY BALANCING DEVICE NECESSARY TO ACHIEVE 23 90 00 TEMPERATURE CONTROLS: 0.38 PANASONIC FV-0511VK2 EF-1 80 0.3 120-1 Ν (50) 3 OFF 140 5.6 22.0 13 24 14 ___ __ ___ 1. SPACE TEMPERATURE SENSORS/STATS SHALL BE MOUNTED TO MEET ADA MOUNTING PROPER ADJUSTING AND BALANCING OF MECHANICAL SYSTEMS. EF-2 0.38 0.3 120-1 80 (50) N PANASONIC FV-0511VK2 17. SEE STRUCTURAL DRAWINGS FOR HANGING FROM ROOF TRUSSES OR FLOOR JOISTS 4 OFF 23.0 12 121 4.8 22 23 ___ ___ __ PROPERLY LOCATE ANCHORS, CHASES, RECESSES AND OPENINGS REQUIRED FOR THE PROPER WHERE THERMOSTATS OR TEMP SENSOR ARE LOCATED ON BUILDING STEEL OR ON EF-3 150 0.25 0.7 120 - 1PANASONIC FV-1115VK2 (50)N INSTALLATION OF THE WORK. ARRANGE WITH THE PROPER CONTRACTORS FOR THE BUILDING EXTERIOR WALLS, PROVIDE AN INSULATED SUBBASE FOR THE THERMOSTAT AND 5 OFF 167 6.7 24.0 15 27 33 ___ __ --OF ANCHORS. ETC. AND FOR LEAVING REQUIRED CHASES, RECESSES AND OPENINGS. SILICON CAULK HOLES THROUGH SUBBASE FOR WIRING TO MAKE BACKING AIRTIGHT. 0.38 EF-4 80 0.3 120 - 1PANASONIC FV-0511VK2 5.5 25.0 13 69 80 18. UNLESS OTHERWISE NOTED. ELECTRICAL CONDUITS, PLUMBING LINES, ETC., SHALL B 6 COPY 138 24 16 ___ RUN CONCEALED AND FRAMING SHALL BE ADEQUATE SIZE TO ACCOMPLISH RESULT ALL CONTROL WIRING SHALL BE ROUTED IN CONDUIT UNLESS CONCEALED IN WALLS EF-5 0.38 0.3 120-1 N PANASONIC FV-0511VK2 WITHOUT CAUSING ANY CHANGES IN THE WALL PLANE -2 SYSTEM PROVIDES 18% OSA VOZ= 194 215 =VOT 19. COORDINATE WITH ALL TRADES THE LOCATIONS OF SLEEVES OR OTHER PRESET EF-6 110 0.38 0.3 (50) 120-1 PANASONIC FV-0511VK2 COORDINATE W/ EC FOR POWERING 24V TRANSFORMERS AND LOCATIONS OF LINE 02 PLOT AREA 0.0 100 168 6.7 __ ACCESSORIES INVOLVING OTHER TRADES. VOLTAGE CONTROLS. PROVIDE UNIT W/ BACK DRAFT DAMPER & S&P HIGH ARC ROOF CAP RC-08 OR EQUAL - COLOR BY ARCH; ADJ MOTOR SETTINGS FOR AIRFLOW LISTED. 103 CONF 110 1.0 50 27 4.4 74 --20. IT IS THE INTENT OF THESE CONTRACT DOCUMENTS TO DEFINE A COMPLETE FINISHED __ LIGHT CONTROLS COORD W/FC TO SET OCC SENSOR DELAY TO 15 MINUTES MIN FACILITY. ANY MATERIAL, SYSTEM. EQUIPMENTS OR ASSEMBLY WHICH NORMALLY TEST ALL DOMESTIC & SANITARY PIPING TO THE REQUIREMENTS OF THE IPC. WOULD BE REQUIRED SHALL BE PROVIDED AS IF SPECIFICALLY NOTED. 104 OFF 97 3.9 2.0 13 22 19 ----__ 21. WHEN WORK IS NOT CALLED OUT BUT IS REQUIRED TO COMPLETE THE PROJECT, IT FLUSH AND SANITIZE DOMESTIC WATER SYSTEMS (CW, HW, HWC) PER THE 05 OFF 231 9.2 3.0 12 48 66 ___ __ SHALL BE PROVIDED BY THE CONTRACTOR AT NO ADDITIONAL EXPENSE TO THE REQUIREMENTS OF THE CITY OF RIVERTON, WYOMING DEQ & IPC. HAVE STERILIZATION WITNESS BY GC OR OWNER. FLUSHING SHALL MEET GUIDELINES SET IN AWWA OWNER AND BE OF THE BEST MATERIALS AND WORKMANSHIP. 106 STOR 3.4 4.0 15 86 10 14 ___ ___ ___ 23 30 00 DUCTWORK: 1. DUCT PRESSURE CLASSES: 108 STAIR 187 7.5 5.0 13 40 3. PROVIDE A FACTORY STARTUP OF THE FOLLOWING EQUIPMENT: PACKAGED ROOFTOP Ω ___ __ ___ SUPPLY DUCTWORK SHALL BE CONSTRUCTION TO +2"WC. PRESSURE CLASS UNITS (RTU-#), MAU-1, KF-1 AND KH-1. 1.2. RETURN & EXHAUST DUCTWORK SHALL BE CONSTRUCTED TO -1"WC 108 /110 RR 3.6 6.0 100 160 90 140 1.3. GENERAL EXHAUST DUCTWORK SHALL BE CONSTRUCTED TO +1.0"WC PER 23 93 00 TESTING. ADJUSTING BALANCING: SMACNA'S DEFINITIONS. -1 SYSTEM PROVIDES 20% OSA VOZ= 172 191 =VOT1. UPON COMPLETION OF WORK, AN INDEPENDENT TESTING AND BALANCING AGENCY 1.4. SEE DETAILS FOR GREASE DUCTWORK REQUIREMENTS. CERTIFIED BY THE NEBB/AABC/TABB SHALL BE ENGAGED TO TEST AND BALANCE THE HVAC SYSTEMS. SYSTEMS SHALL BE BALANCED TO PLUS/MINUS 10% OF DESIGN 2. ALL DUCTWORK, INCLUDING DAMPERS, SHALL BE SEALED TO SMACNA CLASS A (ALL REQUIREMENTS. THE CONTRACTOR SHALL PLACE ALL SYSTEMS AND EQUIPMENT INTO JOINTS & SEAMS SEALED/TAPED). AND ALL AUDIBLE LEAKS SHALL BE SEALED PRIOR FULL OPERATION FOR TESTING AND BALANCING. ONE COPY OF THE FINAL TEST AND TO COVERING WORK. BALANCE REPORT WITH THE NATIONAL PERFORMANCE GUARANTY SHALL BE SENT KITCHEN HOOD EXHAUST DIRECTLY TO THE ENGINEER OF RECORD. PROVIDE THREE (3) ADDITIONAL COPIES TO 3. ANY TAPE USED ON DUCTWORK SHALL HAVE UL181B-AP LISTING. THE CONTRACTOR. TAB SHALL PERFORM WORK TO THE CERTIFYING AGENCY'S REQUIREMENTS AND ASHRAE 111. 4. BRANCH DUCTS TO GRD'S SHALL BE SAME SIZE AS NECK OF GRD. MANUFACTURER & MODE R EQUAL BY ACME, GREENHECK, AEROVENT, 5. DUCTWORK SHALL BE G90 26GA GALV SHEET METAL MINIMUM OR HEAVIER PER 23 99 00 MECHANICAL CLOSEOUT: SONES STARTER ASHRAE/SMACNA REQUIREMENTS. PROVIDE (1) ELECTRONIC COPY IN PDF FORMAT AND (1) PHYSICAL COPY IN BINDER INCLUDING CUTSHEETS, SUBMITTAL DATA, & IOM DOCUMENTATION TO OWNER. SUBMIT 6. ROUND ELBOWS SHALL HAVE CLR = 1.5 SMOOTH OR 5 GORE ELBOWS. RESIDENTICAL AN ELECTRONIC COPY TO ENGINEER. BACK ' 150 **BROAN BKSA130WW** INTEGRA KH-1 YES 1.5 (168) 120-1 GENERAL MECHANICAL __ PIPE SYMBOLS RECTANGULAR DUCT TRANSITIONS SHALL BE CONSTRUCTED WITH ANGLE OF 0 EQUAL 2 PROVIDE A CLEAN SET OF DRAWINGS OF AS-BUILT CONDITIONS INCLUDE ALL MOUNT UNIT 24" ABOVE COOKING SURFACE. PROVIDE RECTANGULAR DISCHARGE BACKDRAFT DAMPER CHANGES AND DEVIATIONS MADE BY THE CONTRACTOR. SUBMIT AT SUBSTANTIAL CONTROLS (IN PLAN) TOP CONNECTION, 45° OR 90° 8. BALANCING DAMPERS: REINFORCED, 16 GAUGE MINIMUM SINGLE (DUCTS SMALLER SPLIT SYSTEM FURNACE & CONDENSING UNIT SCHEDULE THAN 8" IN HEIGHT) AND MULTIPLE OPPOSED BLADE (DUCTS OVER 8" IN HEIGHT) (T) ROOM TEMPERATURE SENSOR W/ USER BOTTOM CONNECTION, 45° OR 90° PROVIDE 4 HOURS OF SYSTEM, EQUIPMENT AND OPERATION TRAINING ON MECHANICAL RUSKIN MD25 & MD35, OR EQUAL, HEAVY DUTY 3/8" LOCKING REGULATOR, WITH & PLUMBING EQUIPMENT. TRAINING TO INCLUDE HOW TO OPERATE EQUIPMENT, WING NUT IN EXTENDED ARM OF REGULATOR. MAINTENANCE AND TROUBLESHOOTING PROCEDURES. SIDE CONNECTION HEATING CAPACITY **HVAC LEGEND** 9. DIMENSIONS SHOWN ON DRAWINGS FOR DUCTWORK ARE SHEET METAL DIMENSIONS. CFM FUEL INPUT OUT AMPS & MODEL NO. RISE OR DROP IN PIPE FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE. FIELD VERIFY ALL DIMENSIONS BEFORE FABRICATING DUCTWORK. OR EQUAL BY GUARDIAN, TRANE, AM STD CONTRACTOR FURTHER AGREES THAT HE WILL REPLACE OR REPAIR ALL DEFECTIVE MBH SUPPLY OR OSA DUCT (UP & DOWN) UNION EQUIPMENT AND INSTALLATION THAT BECOMES DEFECTIVE DURING THE TERM OF THE 10. CONTRACTOR SHALL INSTALL ANY BALANCING DEVICE NECESSARY TO ACHIEVE PIPE UP PROPER ADJUSTING AND BALANCING OF MECHANICAL SYSTEMS. RETURN DUCT (UP & DOWN) F-1 VERT WEST OFF 96 | 960 | 191 | 0.50 | NG | 58.0 | 55.7 | 8.3 |120-1|YORK TM9Y060B12 PIPE DOWN 23 99 90 OWNER'S INSTRUCTIONS/RESPONSIBILITIES: . PIPING SYSTEMS (NOT SLOPED PIPING I.E. -WASTE, DRAIN OR STORM) SHALL BE OWNER'S MAINTENANCE STAFF SHOULD REVIEW O&M MANUAL REVIEW AT BUILDING F-2 VERT 96 | 1100 | 215 | 0.50 | NG | 61.8 | 59.3 | 8.3 | 120-1 YORK TM9Y060B12 ROUND DUCT (UP & DOWN) EAST OFF **THERMOMETER** ROUTED TIGHT TO STRUCTURE ABOVE OR HIGH AS POSSIBLE IF NOT PHYSICALLY TURNOVER AND DEVELOP A PM SCHEDULE PER RECOMMENDATIONS LISTED IN THE CAPABLE OF BEING ROUTED TIGHT TO STRUCTURE UNLESS NOTED OTHERWISE. EQUIPMENT MANUALS. 96 | 1950 | 360 | 0.50 | NG | 87.2 | 83.7 | 10.7 | 120-1 YORK TM9Y100C20 CHAMBERS REVIEW BALANCE REPORT WITH TAB CONTRACTOR. **CEILING MOUNTED GRD:** PRESSURE GAGE 2. SEE PLUMBING FIXTURE SCHEDULE FOR SIZE BRANCH PIPING TO INDIVIDUAL PLUMBING PROVIDE PERIODIC MAINTENANCE OF ALL EQUIPMENT PER THE PM'S AND MANUALS SEE GAS EQUIPMENT CONNECTION & FURNACE RETURN AIR DETAIL. PROVIDE FILTERS FOR CONSTRUCTION PER DETAIL REQUIREMENTS, REPLACE AT OWNER OCCUPANCY. PIPE SYSTEM LEGEND ALL NATURAL GAS PIPE/FITTINGS SHALL SCHEDULE 40 STEEL AS LISTED IN IFGC W/ 4. REPLACE ALL AIR FILTERS: INITIALLY SCHEDULE FILTER REPLACEMENT EVERY 3 2 WAY THROW SUPPLY ALANCE SET HEATING CFM WITH FURNACE BLOWER AT SAME SPEED/SETTING AS COOLING CFM. MONTHS, ADJUST SCHEDULE ACCORDING TO LOADING (DIRT & MATERIAL) ON FILTERS. EXHAUST OR RELIEF DUCT (UP & DOWN) 4 WAY THROW SUPPLY PROVIDE 7 DAY PROGRAMMABLE TOUCHSCREEN TSTAT. HONEYWELL VISIONPRO OR EQUAL. CONTROL OSA DAMPER - OPEN WHEN FURNACE IS ON, CLOSED WHEN FURNACE IS OFF. DOMESTIC COLD WATER 5. PROVIDE REGULAR MAINTENANCE OF PACKAGE ROOFTOP UNITS, KITCHEN HOOD, 4. SANITARY WASTE (SAN), SANITARY VENT (V), DOMESTIC COLD WATER (CW), AND GREASE DUCTWORK, KITCHEN HOOD FAN PER IOM DOCUMENT IN BINDER. PROVIDE 7 DAY PROGRAMMABLE TSTAT. HONEYWELL VISIONPRO TOUCH SCREEN OR EQUAL. PROVIDE THERMOSTAT WITH STAGING TO CONTROL DOMESTIC HOT WATER DOMESTIC HOT WATER (HW) PIPE & FITTINGS SHALL BE OF ANY MATERIALS LISTED IN 6. BREAKDOWN / FAILURES: DOCUMENT ALL FAILURES AND EQUIPMENTS CHANGES. EXHAUST THE IPC W/ APPROVED LISTINGS SANITARY SEWER 4.1. PIPING SHALL BE INSTALLED IN SYSTEMS WITH PRESSURES AND TEMPERATURES INDOOR OUTDOOR CONDENSING UNIT CAPACITY | CLG COIL DATA ELECTRICAL MANUFACTURER & MODEL NO. RETURN OR TRANSFER GENERAL REQUIREMENTS: LESS THAN WORKING RATINGS OF PIPING BY MANUFACTURER. OR EQUAL BY GUARDIAN, TRANE, AM STI EAT *F STORM WATER MCA 4.2. PEX TUBING SHALL BE ONE SIZE GREATER THAN LISTED IN PLAN (COPPER TUBING STORM WATER DUCTWORK DIMENSIONAL DATA & TYPE: ##/##* AUTHORITY HAVING JURISDICTION: CITY OF SIDNEY MT 5. CONTRACTOR SHALL INSTALL ANY BALANCING DEVICE NECESSARY TO ACHIEVE CC-1 CU-1 17 | 25.7 | 25.7 | 95 | 79 63 | 208–1 | 21.4 | 35 | YORK XAFB36 / YFK36B21A SHEETMETAL DIMENSIONS WRAP PROPER ADJUSTING AND BALANCING OF MECHANICAL SYSTEMS. **ENFORCED CODES:** INSULATION AS APPLICABLE CC-2 | CU-2 17 | 28.0 | 28.0 | 95 | 79 63 | 208-1 | 21.4 | 35 | YORK XAFB36 / YFK36B21A | NATURAL GAS 2021 INTERNATIONAL FUEL GAS CODE RUN PIPING AS DIRECT AS POSSIBLE TO REQUIRED CONNECTIONS, AND SLOPE DRAIN VALVES AT LOW POINTS FOR COMPLETE SYSTEM DRAIN DOWN. LOCATE DRAIN ROUND DUCTWORK REVERSE OMOSIS TREATED WATER 2021 INTERNATIONAL MECHANICAL CODE 17 | 55.3 | 49.7 | 95 | 79 | CC-3 | CU-3 63 | 208-1 | 31.4 | 50 | YORK XAFC60 / YFK60B21A VALVES AT ACCESSIBLE POINTS WITHIN THE SYSTEM. 2021 UNIFORM PLUMBING CODE SANITARY VENT PROVIDE CASED COIL, THERMAL EXPANSION VALVE PER FACTORY SIZING, PROVIDE CONDENSATE DRAIN W/ 2" P-TRAP AND COLD WEATHER HARD START KIT. SEE CONDENSATE DRAIN DETAIL 2021 INTERNATIONAL FIRE CODE . ALL VALVES SHALL BE OF ONE MANUFACTURER AND SHALL BE LISTED WITH THE <u>VALVE SYMBOLS</u> MANUFACTURERS STANDARDIZATION SOCIETY OF THE VALVE AND FITTINGS INDUSTRY. 2021 INTERNAL ENERGY CONSERVATION CODE OVIDE DUCT TRANSITIONS AS REQUIRED FROM FURNACE TO COIL. PROVIDE FACTORY LINESET OR ACR COPPER TUBING. MOUNT UNIT ON CONC PAD OR EQUIPMENT BASE 3" ABOVE GRADE. BY edi architects + designers ROUTE WIRING FROM FURNACE CONTROLLER / PROGRAMMABLE THERMOSTAT CHECK VALVE 8. ALL FAUCETS/TRIM FOR PLUMBING FIXTURES SHALL BE FURNISHED BY ONE MANUFACTURER. PROJECT ALTITUDE: 3600' ALL EQUIPMENT MUST BE SELECTED WITH STATIONARY LOUVER SCHEDULE BALL VALVE 9. ALL VALVES SHALL HAVE WOG LISTING AND CWP OF 125PSIG. ALTITUDE CORRECTIONS AS NECESSARY 10. ALL VALVES, DEVICES, EQUIPMENT AND ASSEMBLIES CONNECTED TO THE DOMESTIC WINTER DESIGN CONDITION: WATER SYSTEM SHALL BE LEAD-FREE. PRESSURE RELIEF VALVE OUTDOOR -25°F / 80%RH OR EQUAL BY GREENHECK, NAILOR, AMERICAN WARMING DROP AREA 11. ALL PIPING SHALL BE RUN FULL SIZE AS INDICATED ON DRAWINGS. ANY REDUCTIONS **VELOCITY** HEIGHT 70°F & NO HUMIDITY CONTROL/REQUIREMENT MANUAL AIR VENT ROOM CESCO, DOWCO, LOUVERS & DAMPERS IN PIPING REQUIRED BY EQUIPMENT CONNECTIONS SHALL BE MADE AT THESE INWC TEST PLUG (PRESSURE/TEMPERATURE) SUMMER DESIGN CONDITION: F-1 OSA/ECON 1,950 | 0.07 2.05 SL-1 950 30 RUSKIN L375 24 12. INSTALL VALVES IN HORIZONTAL PIPING WITH STEM AT OR ABOVE CENTER OF OUTDOOR 98°F DB/ 62°F WB HORIZONTAL PIPE AND ALLOWS FULL STEM MOVEMENT. AUTOMATIC AIR VENT 76°F & NO HUMIDITY CONTROL/REQUIREMENT 4.07 CHAMBERS 975 525 30 RUSKIN L375 SL-213. UNIONS, FLANGES OR GROOVED PIPING ARE TO BE USED WHEREVER NECESSARY AND IN PIPING AT ALL EQUIPMENT SO THAT PIPING MAY BE CONVENIENTLY BROKEN AND SL-3**CHAMBERS** 975 5.07 525 1.86 RUSKIN L375 30 MECHANICAL ENGINEERING & DESIGN: PLUG VALVE MOVED TO FACILITATE EQUIPMENT MAINTENANCE. SIMPLICITY CONSULTING, ENGINEERING, & DESIGN PROVIDE W/172"X1/2"_BIRDSCREEN ON INSIDE_FACE, FEANGED FRAME, KYNAR FINISH COLOR BY ARCH, CAULK FLANGE TOFBUILDING. WYE STRAINER (WITH BALL VALVE & CORY HASIAK, PE 14. SUPPORT GAS PIPING PER SPACING REQUIREMENTS OF CHAPTER 3 OF 2012 HOSE CONNECTION) INTERNATIONAL FUEL GAS CODE, PLUMBING PIPING PER 2012 INTERNATIONAL 406.254.7157 PLUMBING CODE. chasiak@simplicityced.com

simplicity CONSULTING, ENGINEERING, & DESIGN PO BOX 8122 BILLINGS, MT 59108-1222 406.254.7157

0


2 0 \mathbf{C} idne S + 7 \sim


Revisions

Copyright © 2023

JOB# 2022007 **DRAWN** (CHECK CC **DATE** 04.17.2023

MECHANICAL **SCHEDULES**





CHECK CC / CH **DATE** 04.17.2023

MECHANICAL

DETAILS

2

0

2

Sidney

Street


ney

<u>0</u>

О

of 2n

City 115



NEW FURNACES ARE ASSUMED, HEATING CAPACITY OF FURNACES AND

EXISTING RETURN HAS BEEN MODIFIED AND RETURN FOR FURNACE IS PULLED FROM

BASEMENT VIA STAIRWELL

EXISTING WATER
HEATER TO REMAIN

- REPLACE FURNACES

Owners would like this replaced

FOR OFFICE AREA?

COOLING COILS

COULD BE REUSED, DUCTWORK REQUIRES MODIFICATION TO WORK EFFICIENTLY.

Sidney MT of Sidney 2nd Street Revisions

59270

chitects 4

Яľ


sdi

Copyright © 2023
BY ed erchitects + designers


JOB# 2022007 DRAWN CC / CH CHECK CC / CH **DATE** 04.17.2023

MECHANICAL DEMO PLAN


Progress Drawings -- Not For Construction




M2.0



M3.0



ED1.0



V//////// EXISTING TEL. BOARD E E REMOVE EXISTING FIXTURE & REPLACE WITH NEW

Lexisting furnace

1 - Basement Elec. Plan -

EXISTING_ WATER HTR

LETTER DESIG.	FIXTURE				LAMP		NOTE
	MANUFACTURER	CATALOG NO.	LOCATION	TYPE	TYPE	NO.	NOTE
А	LSI	LPASC24LED60LUNVDIM135	CEILING	RECESSED	48W LED	_	<u> </u>
В	LSI	SFP24LED50UEDIM35	CEILING	RECESSED	50W LED	_	
С	LSI	SFP24LED50UEDIM35 SFPSMK24	CEILING	SURFACE	50W LED	_	
D	LSI	LPEC24SMLEDHOWWUE	CEILING	SURFACE	47W LED	_	
E	LSI	SDL4LED40LFLUNV3580CRI	CEILING	SURFACE	30W LED	_	
F	NU-LITE	RP4B05UP06D0WNL35UNV DICSTDBKS RB486'	CEILING	_	67W LED	_	
G	LITFAD	221948776	WALL	SURFACE	20W LED	_	
Н	NORA	NLQS-R72L-35-WW	CEILING	SURFACE	14W LED	_	
1	NOT USED	_	_	_	_	_	
J	NORA	NLQS-R42L-35-WW	CEILING	SURFACE	11W LED	_	
K	MAXXIMA	MCL-3324900B	CEILING	SURFACE	52W LED	_	
L	MULE	SQC-LED-1-R-WW	WALL	SURFACE	LED	_	
М	MULE	SQ-LED-1-R-WW	WALL	SURFACE	LED	_	
N	MULE	MD B2R-WW	CEILING	SURFACE	LED	_	
0	MULE	MAKO-LED-ACEM-DB	WALL	SURFACE	LED	_	

Progress Drawings -- Not For Construction

of Sidney 2nd Street SE, Sidney MT

architects


Revisions

Copyright © 2023
BY ed architects + designers

JOB # 2022007
DRAWN CC / CH
CHECK CC / CH
DATE 04.17.2023

LIGHTING PLAN

E1.1



E2.0

POWER

PLAN