

Contact us today: 877.841.0848



(index.html)



POTHOLE PATCHING PRODUCTS

P2™ Two-Person Patcher with DuraPatcher™ Technology

Benefits:

- Lowest cost per patch with as little as 2-person crew and lower material costs
- Maximizes your budget by never having to patch the same pothole twice
- Faster and simpler patching process with our pothole patching machine that limits public disruption

Featuring:

- Virtually no moving parts in the delivery system which lowers maintenance costs
- Onboard heat allows patching in cold weather conditions
- Ergonomic, no-stress boom easily covers an 18-foot working radius
- Specially designed Vent-Flo™ nozzle that thoroughly coats the aggregate with emulsion, ensuring a permanent patch
- Powerful blower and DuraPatcher venturi system can reliably delivers aggregate up to 2.5" in diameter



(images/products/p2
750x421/P2™ Two-Person
Patcher with DuraPatcher™
Technology 1.jpg)



(images/products/p2
750x421/P2™ Two-Person
Patcher with DuraPatcher™
Technology 3.jpg)



(images/products/p2
750x421/P2™ Two-Person
Patcher with DuraPatcher™
Technology 4.jpg)



(images/products/p4
750x421/p4-3-750x421.jpg)



(images/products/p2
750x421/p2-3-750x421.jpg)



(images/products/p2
750x421/P2™ Two-Person
Patcher with DuraPatcher™
Technology Ergonomic no-stress
boom.jpg)



(images/products/p2
750x421/P2™ Two-Person
Patcher with DuraPatcher™
Technology Overnight heating
system.jpg)



(images/products/p2
750x421/Hitch adjusts for height
and distance.jpg)

REQUEST A QUOTE
(QUOTE.HTML)

DOWNLOAD LITERATURE
(HTTPS://DRIVE.GOOGLE.C
OM/FILE/D/1TNZTE2ZUY2
4VS2S2Y2QREJSILP7CUCXA
/VIEW?USP=DRIVE_LINK)

BID SPECIFICATION
(HTTPS://DRIVE.GOOGLE.C
OM/FILE/D/1KH31VEQHRF
RN7XACJYB7KLPFZFXOP1
O4/VIEW?
USP=DRIVE_LINK)

VIDEO - CLIMLINE P2
(HTTPS://YOUTU.BE/SBVQ
9TBXD3U)

MANUAL
(HTTPS://DRIVE.GOOGLE.C
OM/FILE/D/1Z4WZJOGJ-
M1LBFSYSO-0J8_IY4N-
SOFV/VIEW?
USP=DRIVE_LINK)

SPECIFICATIONS

Due to continuous improvement, specifications are subject to change without notice.

Emulsion Capacity: 250 Gallons

Engine: 74HP IT4 Diesel

Heating Method (Overnight): Electric Blanket

Heat Rating: 2 x 1500 Watts

Tank Insulation: R 15

Blower: 450 CFM at 1500 RPM, 10 PSI

GVWR (lbs): 10,400

GAWR (lbs): 2 x 6000

Axles/ Suspension: 2 (Leaf Spring)

Brake Type: Electric

Clean Out: 15 Gallons

Fuel Capacity: 18 Gallons

Trailer Construction: 2" x 6" x 1/4" Rectangular Tube

Drain Valve: 3"

Temperature Gauge: 5"

Dimensions (l x w x h) 194" x 96" x 91"

Shipping Weight : 5,560 lb.

Warranty: Two Year Limited

Pothole Patcher Machine



P3 Truck Mounted Patcher (p3.html)

LEARN MORE (P3.HTML)



P4 Roll-Off Patcher (p4.html)

[LEARN MORE \(P4.HTML\)](#)



P5 One-Person Patcher (p5.html)

LEARN MORE (P5.HTML)

PRODUCTS

P2 (p2.html)

P3 (p3.html)

P4 (p4.html)

P5 (p5.html)

M-Series (mseries.html)

MA4 (ma4.html)

K-Series (kseries.html)

T1 (T1.html)

T-Series (tseries.html)

R3 Router (r3.html)

NAVIGATE

Pothole Patching (potholepatching.html)

Crack Sealing (cracksealing.html)

Emulsion Storage (emulsionstorage.html)

Resources (index.html)

About (about.html)

NAVIGATE

Contact Us (contact.html)



International (international-contact.html)

Request a Quote (quote.html)

Tech Support (techsupport.html)

STAY CONNECTED



in (<https://www.linkedin.com/company/cimline-inc/about/>) 
(<https://www.instagram.com/cimlineinc/>) 
(<https://www.youtube.com/user/cimline1>)

Since 1970, Cimline™ has focused on bringing innovative solutions to the Pavement Maintenance Industry. With a drive for performance and innovation, Cimline continues to offer cutting edge technology through its worldwide network of distributors.

Copyright ©2022 Cimline Inc. All rights reserved.

[Privacy and Cookies Policy \(privacy.html\)](#) | [Terms and Conditions \(termofuse.html\)](#)

