

Your Configured Ricoh IM C4500



*Note: The image is a photo realistic illustration of your selected configuration.

WIDTH	DEPTH	HEIGHT
45.70in	27.00in	47.60in
(1,161mm)	(686mm)	(1,209mm)

Actual dimensions may vary. These are approximate only.

POWER CONSUMPTION (MAIN UNIT)

120V-127V, 60Hz

Additional power requirements may apply.

Please read each option's description copy to see if additional

power sources are needed.

Your Chosen Options

- IM C4500
- Paper Feed Unit PB3280
- Finisher SR3260
- Bridge Unit BU3090
- OCR Unit Type M13
- Fax Option Type M37
- ESP XG-PCS-15D
- Print Cartridge Black IM C6000
- Print Cartridge Yellow IM C6000
- Print Cartridge Magenta IM C6000
- Print Cartridge Cyan IM C6000
- Staple Refill Type T for SR3260/SR3280/SR3290/SR3250
- Waste Toner Bottle IM C6000

Ricoh Online System Configurator Tool

Choose a Model • Select Options • Save, Print or Email



Main Unit Main Unit Item/Description Item # Power Requirements IM C4500 418309 120V-127V, 60Hz Paper Tray & Optional Accessories Item/Description Item # **Power Requirements** Paper Feed Unit PB3280 418349 N/A **Output & Finishing Options** External Item/Description Item # Power Requirements Finisher SR3260 418337 N/A

Bridge Unit BU3090

Print/Scan Options

Printing/Scanning Features

Item/Description	ltem #	Power Requirements
OCR Unit Type M13	417428	N/A

N/A

418345

Fax Options		
Item/Description	ltem #	Power Requirements
Fax Option Type M37	418392	N/A

Security & Miscellaneous Accessories		
Item/Description	ltem #	Power Requirements
ESP XG-PCS-15D	006428MIU	N/A

Supplies		
Item/Description	ltem #	Power Requirements
Print Cartridge Black IM C6000	842279	N/A
Print Cartridge Yellow IM C6000	842280	N/A
Print Cartridge Magenta IM C6000	842281	N/A
Print Cartridge Cyan IM C6000	842282	N/A
Staple Refill Type T for SR3260/SR3280/SR3290/SR3250	415010	N/A
Waste Toner Bottle IM C6000	418425	N/A



Choose a Model • Select Options • Save, Print or Email



Main Unit

Main Unit

Item/Description	ltem #	Thumbnail
IM C4500	418309	
• Output Speed (Letter): 45-ppm		
Average Monthly Volume: 10,000 impressions/month		
Maximum Monthly Volume: 50,000 impressions/month		100 11
Power Requirements: 120V-127V, 60Hz		
• Weight: 223.5 lbs. (101.4 kg)		
• W × D × H (inches): 23.1 × 27 × 37.9		
• W × D × H (mm): 586.74 × 685.8 × 962.66		
Note: The DOSS does not overwrite the HDD for the Color Controller E-25C.		

Paper Tray & Optional Accessories		
Item/Description	ltem #	Thumbnail
Paper Feed Unit PB3280	418349	
Provides an additional 1,100 sheets.		
Paper sizes up to 12" x 18".		
Paper weights up to 80 lb. Bond/166 lb. Index (300 g/m ²).		
Weight: 50.7 lbs. (23 kg)		
W × D × H (inches): 23.1 × 27 × 9.7		
W × D × H (mm): 586.74 × 685.8 × 246.38		
Note: Paper Feed Unit PB3280 cannot be installed with Paper Feed Unit PB3270, Caster Table Type M3, Paper Feed LCIT PB3290, Cabinet Type F or any related options.		

Output & Finishing Options

External		
Item/Description	ltem #	Thumbnail
Finisher SR3260	418337	
1,000-sheet Finisher.		1
For offices that produce collated and stapled sets of documents, the SR3260 helps shorten production time. It offers 50-sheet, multi-position stapling, mixed sized stapling, optional hole punching, and shift-sort collating, as well as a staple-less binding capability of up to 5 sheets.		
Supports paper sizes up to 12" x 18".		
Weight: 75 lbs. (34 kg)		
W × D × H (inches): 22.6 × 24.4 × 37.8		
W × D × H (mm): 574.04 × 619.76 × 960.12		
Note: 1. Bridge Unit BU3090 or Internal Multi-Fold Unit FD3010 must be installed to add this option. 2. One of the following Paper Feed Units must be selected to add this finisher: Paper Feed Unit PB3280, Paper Feed LCIT PB3290 or Cabinet Type F. 3. Finisher SR3260 cannot be installed with Paper Feed Unit PB3270, Caster Table Type M3, Internal Shift Tray SH3080, Internal Finisher SR3250, Finisher SR3280, Booklet Finisher SR3270, Booklet Finisher SR3290 or any related options.		
Bridge Unit BU3090	418345	
A required accessory when the main unit is not configured with the Internal Multi-Fold Unit FD3010. The Bridge Unit transports pages from the standard exit area into a Finisher for online stapling or hole punching.		
Note: One of the following finishers must be selected to add this option: Finisher SR3260, Finisher SR3280, Booklet Finisher SR3270 or Booklet Finisher SR3290.		

Print/Scan Options

Printing/Scanning Features

Item/Description	ltem #	Thumbnail
OCR Unit Type M13 This function embeds invisible texts on scanned images of PDFs and enables users to search PDF files by arbitrary keywords. Searchable PDF files can be sent to email, folders, and external media (USB/SD). Supports blank page removal when scanning.	417428	1 5 70 7

Item/Description	ltem #	Thumbnail
Fax Option Type M37 Installation required to enable fax services: 33.6 kbps, approximately 2 second transmission speed, standard JBIG, and standard 320 Pages Memory. Includes standard Internet Fax (T.37), LAN Fax, IP-Fax (T.38), Fax Forwarding to Email & Paperless Fax function.	418392	Fax Destination Enter fax destination with the Numb ► Destination 912015551234_ Tone Pause

Security & Miscellaneous Accessories		
Item/Description	Item #	Thumbnail
ESP XG-PCS-15D	006428MIU	Ø
Designed to provide a higher level of noise filtering and surge protection for devices that employ more sensitive and complex electronic components.		G
Our Advanced Technical Support (ATS) recommends the use of power protection products to minimize potential electrical interference with products.		THE R. W.

Supplies		
Item/Description	Item #	Thumbnail
Print Cartridge Black IM C6000 Unit Packaging: 1 Bottle (544 g) Yield (CTN): 33,000 pages Based on printing on letter paper with 5% coverage.	842279	
Print Cartridge Yellow IM C6000 Unit Packaging: 1 Bottle (437 g) Yield (CTN): 22,500 pages Based on printing on letter paper with 5% coverage.	842280	

Print Cartridge Magenta IM C6000 Unit Packaging: 1 Bottle (455 g) Yield (CTN): 22,500 pages Based on printing on letter paper with 5% coverage.	842281	
Print Cartridge Cyan IM C6000 Unit Packaging: 1 Bottle (400 g) Yield (CTN): 22,500 pages Based on printing on letter paper with 5% coverage.	842282	
Staple Refill Type T for SR3260/SR3280/SR3290/SR3250 Unit Packaging: 5,000 per Crtg. (2 Crtg/Ctn) Yield (CTN): 10,000 Note: Internal Finisher SR3250, Finisher SR3260, Finisher SR3280 or Booklet Finisher SR3290 must be selected to add this supply.	415010	A CONTRACTOR
Waste Toner Bottle IM C6000 Unit Packaging: 1 - Each Yield (CTN): 100,000 pages	418425	

Ricoh is committed to creating value for our customers through the production of top quality products, services and solutions that directly meet the needs of today's communication intensive business environments. As a result, we offer a range of Multifunction products with advanced scanning and printing software options that help boost productivity and improve workflow by enhancing the user experience. Visit Ricoh-USA.com for more information.

We offer a variety of services and solutions to meet diverse and challenging business needs. To find out more information, visit solutions.ricoh-usa.com

The content on this site, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.

Ricoh USA, Inc., 70 Valley Stream Parkway, Malvern, PA 19355, 1-800-63-RICOH. ©2019 Ricoh USA, Inc. All rights reserved. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners.

