

January 16, 2026  
Our 97th Year

**Ship To:**  
ST JAMES PUBLIC UTILITY  
124 ARMSTRONG BLVD  
SAINT JAMES, MN 56081  
US

**Bill To:**  
ST JAMES PUBLIC UTILITY  
124 ARMSTRONG BLVD  
SAINT JAMES, MN 56081  
US

Attn:  
Phone: 507-375-3241  
Email:

**Altec Sales Order:** 8827070  
**Altec Quotation Number:** 1249134 - 7  
**Run Number:** 1485729  
**Account Manager:** Ryan Michael Scharnott  
**Technical Sales Rep:** Madalyn Ann Bienhoff  
**Reference WO:** Start From-953-57618195  
**Customer Inspection:** Pre-delivery/Customer  
Validation-Photos

**X7 Discrete Job:** 1049193083  
**X7 Configured Item:** 000037013-43947985  
**Quantity:** 1  
**X4 Discrete Job:**  
**X4 Configured Item:**  
**System Engineer:** Alex Aulabaugh  
**Structural Engineer:** Alex Aulabaugh

**Customer Truck Number:**

**Line Set Date:**

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Unit</u>	
1.	ALTEC Model DH50E Hydraulic Derrick, built in accordance with Altec standard specifications and to include the following features:	1
2.	Electric-Hydraulic Control System: Closed Center hydraulic system with maximum flow of 50 gpm for simultaneous operation of multiple functions	1
3.	Rear Mount Over Rear Axle for DH	1
4.	Three position throttle integrated into keypad at operator control station.	1
5.	No hard wired upper controls and NO TOOL CIRCUIT at boom tip	1
6.	Radio Remote Lower Controls (Traditional/Hetronic)	1
7.	Radio Remote Control Layout: COUNTER-CLOCKWISE, push lever to Right rotates boom Counter-Clockwise	1
8.	Neck Strap for Radio Remote Contols	1
9.	Audible HOP Indicator	1
10.	8 - Turntable Winch	1
11.	11 - Normal winch speed (15,000 lbs)	1
12.	94 - Digger, Two-Speed Mechanical Shift, 12,000 ft-lbs, includes all of the components necessary to operate digger, installed	1
13.	2.63 in Hex Output Shaft With 2.63 in Hex Extension Shaft	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
14.	88 - Digger - right-hand storage, viewing from boom tip - streetside for rear and corner mount, curbside for behind cab mount - normal. Includes Auger Overstow Protection System	1
15.	Dedicated digger shake command that provides rapid dig/clean reversing function for quick and convenient auger cleaning.	1
16.	175 - ANSI use criteria, Digger Derrick use only (no Personnel Handling)	1
17.	Pole Guides for 24.00 in Dia Pole Maximum	1
18.	No Derrick Tong Protectors	1
19.	No hard wired control station, only available with Radio Remote Lower Controls and includes emergency lowering handles at the main control valve	1
20.	Hydraulic Side Load Protection: relieves overload conditions by allowing rotation system to back drive.	1
21.	134 - Altec RotaFloat™ System. Activating this switch while digging frees the booms to rotate, thus eliminating one of the many functions needed to install screw anchors. Includes alarm and visual indicator	1
22.	Zone Rating System	1
23.	450 - Outriggers, A-frame, folding shoe, 153 maximum spread, for use as auxiliary outriggers on all units or primary outriggers on select units	1
24.	450 - Outriggers, A-frame, folding shoe, 153 maximum spread, for use as auxiliary outriggers on all units or primary outriggers on select units, includes:	1
25.	Powder coat unit Altec White.	1
<b><u>Unit and Hydraulic Acc.</u></b>		
26.	Bullet Teeth Auger 20 Inch DIA With 2-5/8 In ch Hex x 104 Inch L (Painted Black)	1
27.	Winch Rope For Turntable Winch 140 Ft Long x 1 Inch Dia	1
28.	Nylite Spool Shackle and Shield for Winch Rope - For 1.125 - 1.313 Inch Dia Rope	1
29.	Load Line Swivel Hook 8-1/2 In Ton	1
30.	DH Series Derrick Subbase (Rigid)	1
31.	Insert Subbase Stop At 10 Ft	1
32.	Insert Subbase Side Tube Storage Stop for Both Tubes At 10 Ft	1
33.	Subbase Storage with Drop Down Door (Paddle Latch) at Rear, 7 Inch High	1
34.	Subbase Storage Custom Option 1	1
<b><u>Sales Text: Stops installed at 120" in all sections</u></b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>		
35.	Hydraulic Reservoir, 30 Gallon, Rectangular, Boom Rest Mounted	1
36.	Hydraulic Oil, HVI-22 with Ultraviolet Dye (Standard)	38

<u>Item</u>	<u>Description</u>	<u>Qty</u>
37.	Pump - Right-Hand Rotation 95CC Pressure Compensated (Automatic Transmission)	1
38.	Muncie PTO	1
39.	Hot Shift PTO (for Automatic Transmission)	1
40.	Standard Altec PTO/Transmission Functionality with Park Brake Auto Neutral for Allison Automatic Transmissions: -Once the PTO switch is on, the Parking Brake is engaged, and the transmission is in a near stationary condition (i.e., below 5 mph) the transmission will be forced to neutral, and PTO will engage.	1
41.	Standard Parking Brake Machine Interlock: Parking (holding) brake must be set before machine is operable.	1
42.	Capstan Control on E-Series, Base Selection, Includes Keypad at Bumper with Front Bumper Winch Pay-In/Payout, Engine Start/Stop, Engine Throttle and Station-Select, Non-Meterable Controls	1
43.	Hydraulic Capstan, Braden PCD24B, 20 GPM, 3000 LBS	1
44.	Cathead General Purpose Capstan Head (Aluminum)	1
45.	Capstan Head Storage	1
<p><b><u>Sales Text:</u> Installed on front bumper with no headlight interference.</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>		
46.	Collapsible Reel (CR Reel) (Utility Tool And Body Co. #176-A-78)	1
47.	Altec recommends any connection made to the tool circuit be done with Non-Conductive hose. If ordering a Hose reel, Altec recommends ordering a hose reel with Non-Conductive hose. The lower tool circuit hoses may be, or become, conductive. Death or serious injury could occur if the unit becomes energized while lower tool circuit is in use.	1
48.	Install Tool Circuit For Hose Reel Below Rotation (Male Pressure, Female Return)	1
49.	50 Ft Non-Conductive Hose Kit, Orange, Includes Quick Disconnects And Dust Caps (Male Pressure, Female Return) (Industry Preferred)	1
50.	Set Of 8 Ft Non-Conductive Hoses And Couplings For Hydraulic Tools	1
51.	Hydraulic Pole Tamper, 5 Ft Handle, with Valve (Fairmont #H4802-5) (Requires 4-6 GPM, 1000-2000 PSI)	1
52.	Hydraulic Pole Puller, 5/8 Inch Chain, Puller Plate (Seabee #PD-2784)	1
53.	Storage Bracket for Hydraulic Pole Puller, Mounted on Outrigger	1
<p><b><u>Sales Text:</u> To extend with outrigger leg</b>  <b>-Reference run 1045500</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>		
54.	Hydraulic Hose Reel, Spring Loaded, ReelCraft HDTH88000 OMP 113, 50 Ft Hose Capacity, Vertical Mount, Top Payout (Altec Preferred)	1

**Sales Text: Install at curbside rear**

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<b>-Payout to rear</b> <b>Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:25</b>	
55.	Two-Part Load Line Kit, With Snatch Block And Clevis	1
56.	Locking Dog Storage Bracket	1
	<b><u>Sales Text:</u> Installed at streetside of ICC bumper extending to rear at 45 degree angle</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
57.	Unit Installation Components.	1
	<b><u>Body</u></b>	
58.	Altec Body	1
59.	Aluminum Body	1
60.	Platform/Flatbed	1
61.	Finish Paint Body Flatbed White	1
62.	Undercoat Body	1
63.	114" Estimated Aluminum Flatbed Length (Engineering To Determine Final Length)	1
64.	3/16" Aluminum Treadplate Floor	1
	<b><u>Sales Text:</u> Smooth floor in lieu of treadplate floor</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
65.	Custom Body Width	1
	<b><u>Sales Text:</u> 94 inch body width</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
66.	4 Inch High Flatbed (No Cross Storage Available)	1
67.	Custom Body Cargo Retaining Option	1
	<b><u>Sales Text:</u> 2" x 4" drop-in aluminum retaining board at top of side access and perimeter of flatbed</b> <b>- Retainer to sit flush on top of flatbed.</b> <b>-Spaced 1" from edge of flatbed</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
68.	Aluminum Rub Rails On Side Of Flatbed	1
69.	Additional Aluminum Access Step Option	1
	<b><u>Sales Text:</u> Recessed Aluminum Gripstrut Curbside Access Steps, One (1) U-Shaped Grab Handle</b> <b>(Second Handle Mounted On Rear Of T-Box/Saddlebox)</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
70.	Flatbed shipping channel	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
71.	Light Channels Installed At Rear Of Flatbed	1
72.	Outrigger Cutout Required	1
73.	Unit Cutout Required	1
74.	Altec Osceola T-Box/Saddle Box	1
75.	Fiberglass T-Box/Saddle Box	1
76.	Altec Standard Fiberglass T-Box/S-Box Specifications	1
	<ul style="list-style-type: none"> <li>A. Molded Fiberglass Side Compartments</li> <li>B. Reinforced, Double-Laminated Doors</li> <li>C. Heavy Duty Stainless Steel Hinges Installed On Doors</li> <li>D. Heavy Duty Strikers Installed On Body For Door Latches</li> <li>E. Automotive-Type Bulb Gasket Door Seal</li> <li>F. Corrosion Resistant Fasteners And Self-Locking Nuts Used Throughout</li> <li>G. Extruded Aluminum Drip Rail</li> <li>H. Fiberglass Bulkheads Installed Between Compartments</li> <li>I. Drains Installed In Each Compartment</li> <li>J. Body To Be Vented</li> </ul>	
77.	Custom T-Box/Saddle Box Option	1
	<p><b>Sales Text: S-34</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>	
78.	Gelcoat Finish Entire T-Box/Saddle Box Altec White	1
79.	Custom T-Box/Saddle Box Length	1
	<p><b>Sales Text: 34" long</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>	
80.	96" Body Width	1
81.	48" Body Compartment Height	1
82.	18" Body Compartment Depth	1
83.	Adhesive Strip Lighting (LED) Around Top And Sides Of Compartment Door Facings	2
84.	Stainless Steel Rotary Paddle Latches With Keyed Locks	6
85.	All Locks Keyed Alike Including Accessories (Preferred Option)	1
86.	No Master Body Locking System Required	1
87.	Gas Prop Rigid Door Holders On All Vertical Doors	1
88.	3/16 Smooth Aluminum Floor	1
89.	4" Aluminum Channel Body Frame	1
90.	1st Vertical (SS) - Adjustable Fiberglass Shelf With Removable Dividers On 4" Centers	3
91.	1st Vertical (SS) - Louvered Panel On Rear Wall To Ventilate Compartment	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
92.	1st Vertical (SS) - Inverter Storage Inside Of Body Compartment With Guard, Louvered Panel On Rear Wall To Ventilate Compartment, And Provisions For Remote GFCI Receptacle (Mounted On Top Shelf Unless Otherwise Specified)	1
	<b><u>Sales Text:</u> Installed in streetside 1st vertical at bottom</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
93.	1st Vertical (CS) - Locking Swivel Hooks On An Adjustable Aluminum Rail (Preferred Option) - Left Wall	2
94.	1st Vertical (CS) - Locking Swivel Hooks On An Adjustable Aluminum Rail (Preferred Option) - Rear Wall	3
95.	1st Vertical (CS) - Locking Swivel Hooks On An Adjustable Aluminum Rail (Preferred Option) - Right Wall	2
96.	Aluminum Rock Guards Installed Each Front Corner Of Body	1
97.	D-Ring Recessed In Body Floor 360 Degree Rotation	8
	<b><u>Sales Text:</u> Installed in the following locations, evenly spaced:</b> <b>- Three (3) each on curbside and streetside flatbed</b> <b>- Two (2) between curbside and streetside sidepacks</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
98.	Aluminum Sloped Grab Handle, Unpainted	1
	<b><u>Sales Text:</u> Installed on rear face of curbside 1st vertical for use with side access</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
99.	Open Top Storage Bin, Unpainted Aluminum, Punched Metal	1
	<b><u>Sales Text:</u> Sales Text: Installed transverse above hydraulic reservoir (on risers if necessary).</b> <b>- 94"L x 14"W x 10"H</b> <b>- Doors installed in floor for access to reservoir</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
100.	Aluminum E-Track (B-Track) Installed On Curbside Interior Cargo Wall, Custom Installation (Specify Installation Height), Unpainted	1
	<b><u>Sales Text:</u> As high as possible</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
101.	Aluminum E-Track (B-Track) Installed On Streetside Interior Cargo Wall, Custom Installation (Specify Installation Height), Unpainted	1
	<b><u>Sales Text:</u> As high as possible</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
102.	Custom Aluminum E-Track, Unpainted	1
	<b><u>Sales Text:</u> Installed across bulkhead to match height of e-track on sidepacks.</b> <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
103.	Additional Body Option	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<p><b><u>Sales Text:</u> Bulkhead installed between reservoir and pedestal</b>  <b>-Offset from front of S-Box</b>  <b>-Reference run 1045500</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>	
104.	Additional Body Option	1
	<p><b><u>Sales Text:</u> Adjustable rails installed as high as possible</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p> <p style="text-align: center;"><b><u>Body and Chassis Accessories</u></b></p>	
105.	Set of Safety Chain D-Rings	1
106.	Swivel Style Pintle Hitch (30,000 LB MGTW with 6,000 LB MVL), 11-Bolt T-Mount (T-125 Style)	1
	<p><b><u>Sales Text:</u> Installed at 24" from ground to center of throat.</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>	
107.	Underride Protection Bumper, Installed at Rear	1
108.	Eyebolt for Trailer Breakaway Cable, 3/8 Inch	1
109.	Rubber Belted Step, Steel, Mounted Beneath Side Access Steps (Installed to Extend Approx. 2 inches Outward)	1
110.	Secondary Boom Saddle for Offset Stowing of Derrick Due to Pole Rack	1
111.	Pole Rack, Two Pole Capacity with Hand Ratchet Tie Binders	1
112.	Mounting Brackets for Lights, Located on Lower Boom Rest	1
113.	Outrigger Pad Holder, 25 L x 25 W x 3 H Fits 24.5 x 24.5 x 2 and Smaller Pads Bolt-On Bottom, Washout Holes with 3/4 Inch Lip Retainer, Steel	2
114.	Pendulum Retainers for Outrigger Pad Holders	2
	<p><b><u>Sales Text:</u> Installed offset</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>	
115.	Wheel Chocks Rubber with Metal Hairpin Handle 9.75 L x 7.75 W x 5 H (Pair) (Industry Preferred)	1
116.	Wheel Chock Holders (Pair), For Installation Under Flatbed	1
117.	Mud Flaps with Altec Logo (Pair)	1
118.	Fold Over, Post Style Cone Holder (Holds up to four 15 x15 large cones), Outrigger Mount, Street Side	1
	<p><b><u>Sales Text:</u> Install on front outrigger</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>	
119.	Wire Reel Storage Bracket Option 1	1
	<p><b><u>Sales Text:</u> Wire Reel Holder, U-Shaped, 24" W, Holds 12" DIA Reels (Applicable For Copper Wire Reels And Spools)</b></p>	

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<ul style="list-style-type: none"> <li>- Hinged to rotate out over side of body</li> <li>- Reference run 1045500</li> <li>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</li> </ul>	
120.	PVC Canister Kit, 6 DIA Pipe 72 L with Aluminum Cap Door and Mounting U-Bolts	1
	<p><b>Sales Text:</b> Behind on the cab</p> <p>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</p>	
121.	Triangular Reflector Kit (Contains 3 Reflectors), Shipped Per DEPS 042	1
122.	Slope Indicator Assembly (Pair) for Machine with Outrigger	1
123.	D-Rings for mounting on Body or Pedestal, Weld On	2
	<p><b>Sales Text:</b> Installed on front of pedestal</p> <p>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</p>	
124.	Vinyl Manual Pouch for Storage of All Operator and Parts Manuals	1
125.	Additional Body/Chassis Accessory	5
	<p><b>Sales Text:</b> Shovel holder tubes installed between rear outrigger and pedestal</p> <ul style="list-style-type: none"> <li>- Installed as low as possible.</li> <li>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</li> </ul>	
126.	Additional Body/Chassis Accessory	1
	<p><b>Sales Text:</b> Speaker bracket installed between boom rest uprights</p> <ul style="list-style-type: none"> <li>- 6" x 6" plate</li> <li>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</li> </ul>	
127.	Additional Body/Chassis Accessory	1
	<p><b>Sales Text:</b> Sign base holder</p> <ul style="list-style-type: none"> <li>- 8 by 8</li> <li>- Deep as possible with chain retainer</li> <li>- Reference run 1045500</li> <li>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</li> </ul>	
<b><u>Electrical Accessories</u></b>		
128.	Compartment Lights Wired to Dash Mounted Master Switch in Chassis Cab	1
129.	Lights And Reflectors In Accordance With FMVSS 108 (Complete LED)	1
130.	Strobe Light Option	2
	<p><b>Sales Text:</b> Two (2) Whelen L32 beacon strobes installed on boom rest, one (1) each side.</p> <ul style="list-style-type: none"> <li>- Wired to separate switch from 4-corner strobes</li> <li>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</li> </ul>	
131.	4-Corner Strobes, Amber, LED, Two (2) Surface Mounted Lights In Grille, Two (2) Round Lights At Rear, Class II (Permit May Be Required)	1
132.	Flood Light, LED, With Aluminum Housing, 4.25 W x 4.25 H, No Switch on the Light	4

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	(Hella #H71030401) (Industry Preferred)	
	<b>Sales Text: Installed in the following locations:</b>	
	- Two (2) on boom rest, one each side, facing rear mounted on light arm.	
	- Two (2) at rear underneath light channels, one each side, wired to switch and reverse.	
	<b>Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:25</b>	
133.	Remote Spot Light, LED, Permanent Mount, With Wireless Dash Mounted Controls And Programmable Wireless Remote (Go-Light #20074GT)	1
	<b>Sales Text: Installed on curbside hood</b>	
	<b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
134.	Go-Light Hood Mounting Bracket	1
135.	Dual Tone Backup Alarm With Outrigger Motion Alarm	1
136.	Altec Standard Multi-Point Grounding System	11
137.	Grounding Reel, Automatic Retracting, Hannay #SGCR 10-17-19 - Holds #2 GA, #1/0 GA (Max 75 Ft) Or #2/0 GA Cable (Max 65 Ft)	1
	<b>Sales Text: Install on CS outrigger</b>	
	<b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
138.	Grounding Cable, #1/0 GA, Yellow Jacketed (Specify Length In Feet)	1
139.	Grounding Cable Option	1
	<b>Sales Text: 6' of grounding cable with grounding clamps installed at each end.</b>	
	<b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
140.	Grounding Lug, Copper, U-Shaped, Threaded	1
	<b>Sales Text: Installed on curbside of frame rail at rear</b>	
	<b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	
141.	Grounding Clamp, Aluminum C-Clamp Style With Serrated Jaws (Includes Ferrule And Heat Shrink Tubing), #1/0 GA Cable	1
142.	Altec Backup Camera System, 7 Inch Color LCD Monitor, Heated Infrared Camera With Day/Night Sensor And Audio	1
143.	Install backup camera monitor on the front windshield in lieu of the rearview mirror.	1
144.	PTO Hour Meter, Digital, With 10 000 Hour Display	1
145.	7-Way Trailer Receptacle (Blade Type) Installed At Rear	1
146.	Relocate Trailer Receptacle Supplied With Chassis	1
147.	Altec Standard Trailer Plug Wiring	1
148.	Electric Trailer Brake Controller (Curt #51126)	1
149.	Inverter Wired Ignition Hot (No Switch)	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
150.	Electrical Receptacle, 120 Volt, GFCI, Includes Weather-Resistant Enclosure  <b>Sales Text: One (1) installed on back wall of cab - One (1) installed at curbside of tailshelf Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:25</b>	1
151.	120 Volt Non-GFCI Receptacle Includes Weather-Resistant Enclosure Requires at least 1 GFCI Receptacle  <b>Sales Text: - One (1) installed at curbside of tailshelf Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:25</b>	1
152.	Hard Wire GFCI Receptacle To Protect Additional Non-GFCI Receptacles	1
153.	Pre-Wire Power Distribution Module (PDM-10), 10 Accessory Circuits, CAN Signals, Installed	1
154.	Controls Installed At Tailshelf, Outrigger Controls, Includes E-Stop, E-Series	1
155.	One Emergency Stop Located at Ground Level Installed at the Rear of the Vehicle	1
156.	Install Altec Telematics Control Unit (TCU) (Domestic and Carrier-Neutral), Includes In-Cab Antenna	1
157.	Additional Electrical Accessory  <b>Sales Text: On-demand throttle for outriggers Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>	1
158.	Additional Electrical Accessory  <b>Sales Text: Add protecting covering for the wiring in CS and SS compartment. Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:25</b>	1
<b><u>Finishing Details</u></b>		
159.	Front and Rear Frame Mounted and Under Body Mounted Components (With the Exception of Rust Resistant Components) Will Be Painted Black DEPS 005 DEPS 095 (Includes Non OEM Front Bumpers and Cabguards)	1
160.	Custom Undercoating  <b>Sales Text: Gatorhyde underside of flatbed. Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:25</b>	1
161.	Finish Paint Option 1  <b>Sales Text: Gatorhyde applied to ICC area and sides of flatbed Last Updated By: Alex Aulabaugh Hr on 26-SEP-2025 09:26</b>	1
162.	Powder Coat Unit Altec White	1
163.	Finish Paint Body Accessories Above Body Floor Altec White	1
164.	Apply Non-Skid Coating (Black) to All Walking Surfaces DEPS 057  <b>Sales Text: Applied to cargo floor</b>	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
<b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b>		
165.	Placard, Engine Block Heater	1
166.	Safety and Instructional Decals English	1
167.	Vehicle Height Placard Installed In Cab DEPS 002	1
168.	HVI-22 Hydraulic Oil Placard	1
169.	Dielectric Test Unit According to ANSI Requirements	1
170.	Stability Test Unit According to ANSI Requirements	1
171.	Focus Factory Build	1
172.	Delivery Of Completed Unit	1
173.	Inbound Freight	1
174.	As Built Electrical and Hydraulic Schematics to be Included In the Manual Pouch (Deps 024)	1
175.	Completed Test Forms To Be Included In The Manual Pouch: -Stability Test Form -Dielectric Test Form (For Insulated Units)	1
<b><u>Chassis</u></b>		
176.	Altec Supplied Chassis	1
177.	Chassis	1
178.	2027 Model Year	1
179.	International HV507	1
180.	Dual Rear Wheel	1
181.	Set Forward Axle	1
182.	4x4	1
183.	Chassis Cab	1
184.	Regular Cab	1
185.	Chassis Color - White NAV9036	1
186.	Front Frame Extensions	1
187.	Air Horn Under Cab	1
188.	Classic Hood	1
189.	AM/FM Radio	1
190.	Bluetooth	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
191.	Weather Band	1
192.	Block Heater	1
193.	Driver Controlled Locking Differential	1
194.	Fiberglass Tilting Hood	1
195.	Trailer Air Brake Package	1
196.	Cruise Control	1
197.	Air Conditioning	1
198.	Keyless Entry	1
199.	Power Door Locks	1
200.	Power Windows	1
201.	Tilt Steering Wheel	1
202.	120 Clear CA (Round To Next Whole Number)	1
203.	Chassis Wheelbase Length - 199 inch	1
204.	GVWR 39,000 LBS	1
205.	16,000 LBS Front GAWR	1
206.	23,000 LBS Rear GAWR	1
207.	120,000 Yield Strength (PSI)	1
208.	Spring Suspension	1
209.	Cummins L9	1
210.	Diesel	1
211.	330 HP Engine Rating	1
212.	Allison 3000 RDS Automatic Transmission (Left and Right Side PTO Openings Only)	1
213.	15SXJ - International 50 Gallon Fuel Tank Non-Polished (Under Cab Left Hand)	1
214.	15WCN - International 5 Gallon DEF Tank (Under Cab Left Hand)	1
215.	07BMA - International Exhaust (Right-Horizontal-Undercab-Vertical) (Cummins Engine Only) - All Wheel Drive Applications	1
216.	No CARB Clean Idle Certification Required	1
217.	EPA Clean Idle Certification	1
218.	EPA Emissions	1
219.	315/80R22.5 Front Tire	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
220.	11R22.5 Rear Tire	1
221.	Air Brakes	1
222.	Park Brake In Rear Wheels	1
223.	3 Chassis Batteries	1
224.	Other Battery Capacity (CCA)	1
<p><b>Sales Text: 1980 CCA</b>  <b>Last Updated By: Madalyn Bienhoff on 06-JUN-2025 16:51</b></p>		
225.	Battery Under Cab Left Hand	1
226.	12XBM - International PTO Throttle Wiring For Cummins B6.7 and L9	1
227.	16XJV - International Dash Cutout for Switch Panel	1
228.	International - 12THT Fan Drive - Horton Drivemaster Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed	1
229.	International - Disallow Regen while in PTO mode (13WEV)	1
230.	International - Electric Brake Controller Wiring With Combined Stop/Turn Signal Heavy Duty Tail Light Wiring At EOF (08HAH)	1
231.	International - Trailer Auxiliary Feed Circuit For Trailer ABS (08TKK)	1
232.	International Heavy Duty Tail Light Wiring (08HAB)	1
233.	International Transmission Dipstick Tube Enters Curbside of Transmission (13WGH)	1
234.	International Vertical Exhaust To Be Even With Top Of Cab (07WCM) and (07WAZ)	1
235.	International - Pre-Wire Chassis with Cab Pass-Thru (8HBE)	1
236.	Air Ride Drivers Seat	1
237.	Air Ride Passenger Seat	1
<p><b>Additional Pricing</b></p>		
238.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1
239.	Federal Excise Tax Item: If provided, Quote subtotal is an Estimate only. Final determined at invoicing.	1
<p><b>Miscellaneous</b></p>		
240.	Non-CARB Registered State	1
241.	Altec Insights for E-Series Derricks: 12-months of access, from date of in-service, to Altec Insights, which provides safety and performance insights for E-Series Derrick models. This content is managed and delivered through your Altec Connect account and includes configurable email and text message notifications. Access is for the first owner, non-transferrable, and non-refundable. Terms and exclusions apply (e.g., Terms and Conditions, and Warranty).	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
-------------	--------------------	------------

Altec Industries, Inc.

BY \_\_\_\_\_  
Madalyn Ann Bienhoff , Technical Sales Representative

**Unselected Items**

<u>Item Number</u>	<u>Description</u>
970660585-	Custom Body Frame Material/Size <b>4 Inch Steel Channel Body Frame (T-Box/Saddle Box)</b> - Stubbed crossmembers designed for body floor to sit directly on top of subbase <b>Unselected By:Madalyn Bienhoff on 03-DEC-2025 14:01</b>
970166016-	Custom Additional Flatbed Option <b>Stubbed steel crossmembers designed for aluminum body floor</b> - To sit directly on top of subbase <b>Unselected By:Madalyn Bienhoff on 03-DEC-2025 14:01</b>
970759010-	10 Gauge Smooth Steel Galvanneal Floor (T-Box/Saddle Box) <b>Unselected By:Madalyn Bienhoff on 03-DEC-2025 14:01</b>
970165819-	6 Inch High Flatbed <b>Unselected By:Madalyn Bienhoff on 06-JAN-2026 10:56</b>
970474490-	Aluminum PL Designator - 6 Inch Crossmember (120 Inch Or Less) <b>Unselected By:Madalyn Bienhoff on 06-JAN-2026 10:56</b>

**New Selected Items**

<u>Item Number</u>	<u>Description</u>
970759053-	3/16 Inch Smooth Aluminum Floor (T-Box/Saddle Box) (Preferred Option) <b>Created By:Madalyn Bienhoff on 03-DEC-2025 14:01</b>
970660582-	4 Inch Aluminum Channel Body Frame (T-Box/Saddle Box) <b>Created By:Madalyn Bienhoff on 03-DEC-2025 14:01</b>
970470881-	4 Inch High Flatbed (No Cross Storage Available) <b>Created By:Madalyn Bienhoff on 06-JAN-2026 10:55</b>