



NOTES:

- ① INTERMEDIATE BACKFILL (CLASS 3) MAY BE FROM NATIVE MATERIAL, NO ROCKS LARGER THAN 3 INCHES. (MAY BE EXTENDED TO SURFACE OUTSIDE ROADWAY STRUCTURAL SECTION).
- ② EXCAVATE 4" BELOW PIPE AND BACKFILL WITH SAND.
- ③ IN EXISTING ROADWAYS, TOP AND INTERMEDIATE BACKFILL SHALL BE 2 SACK CONCRETE SLURRY (CLASS 4) IF MIN. COVER IS LESS THAN 36". IF COVER EXCEEDS 36" REMAINDER OF BACKFILL ABOVE SAND SHALL BE AGGREGATE BASE (CLASS 2).
- ④ PROVIDE LOCATOR WIRE NO. 10 AWG COATED SOFT DRAWN COPPER WIRE. TAPE TO PIPE EVERY 10 FEET.
- ⑤ TRENCH DETAIL IN NEW STREET IS NOT SHOWN FOR CLARITY. FOR NEW STREETS, INTERMEDIATE BACKFILL SHALL BE (CLASS 3) AND COMPACTION SHALL BE IN ACCORDANCE WITH SECTION 19-5, "COMPACTION" OF THE STATE STANDARD SPECIFICATIONS.

CITY OF SUTTER CREEK
TRENCH DETAIL

1	08/22/2025	FWW	ST
			14
REV No.:	DATE:	BY:	