



HAYDEN PAVING, INC.

4710 Windsong Trail, Houston, TX 77084 O: 281-855-7710 F: 281-856-2506

Quotation

Quote Number: 35092

Quote Date: 8/30/2024

Quoted By: Michael Henry

Quoted to:

City of Tomball
501 James St.
Tomball, TX 77375

Job Name:

City of Tomball Matheson Park Trail
1240 Ulrich Road
Tomball TX 77375

Phone:

Contact	Good Through	Payment Terms	Job Location
Justin Pruitt	9/29/2024	Net 30 Days	

Item	Description	Amount
Supply material, labor and equipment to perform the following:		
BASE	TRAIL (BASE) 8 FOOT: Excavate the top 5-6" of the existing grass and dirt and haul off-site. Place and compact 4" of crushed concrete base material on sub-grade. Apply SS-1 primer coat @ 0.15 to 0.25 gal./sq.yd., place and compact 1.5" of type 'D' HMAC on the placed crushed concrete base material. Area totaling approximately 11,094 SF.	\$165,522.48
ALT #1	TRAIL (ALTERNATE #1) 8 FOOT: Excavate the top 5-6" of the existing grass and dirt and haul off-site. Place and compact 4" of crushed concrete base material on sub-grade. Apply SS-1 primer coat @ 0.15 to 0.25 gal./sq.yd., place and compact 1.5" of type 'D' HMAC on the placed crushed concrete base material. Area totaling approximately 5,916 SF.	\$88,266.72
ALT #2	TRAIL (ALTERNATE #2) 8 FOOT: Excavate the top 5-6" of the existing grass and dirt and haul off-site. Place and compact 4" of crushed concrete base material on sub-grade. Apply SS-1 primer coat @ 0.15 to 0.25 gal./sq.yd., place and compact 1.5" of type 'D' HMAC on the placed crushed concrete base material. Area totaling approximately 1,956 SF.	\$29,183.52
Seal	SEAL COAT: Sweep, clean and blow off parking lot of all debris and loose dirt and haul off. Treat any heavy oil spots with primer material to parking stall areas as needed. Apply 2 coats of sealant material each to contain 3 lbs. of silica sand per gallon of material with 3 per cent latex additive per 100 gallons of material applied at a total application rate of .20 gallons per square yard of area. Area totaling approximately 36,265 sq.ft.	\$12,754.00
STRI	STRIPING: Re-stripe per existing layout.	\$5,425.00
***	Buy Board Number: 700-23	

Base \$301,152

Bond Cost \$0

Subtotal \$301,152

Exempt - contingent upon receipt of Tax Certificate 8.25% \$0

Total \$301,152

Notes



HAYDEN PAVING, INC.

4710 Windsong Trail, Houston, TX 77084 O: 281-855-7710 F: 281-856-2506

- 1 This quote does not include the cost of permits, which may or may not be required, or the plan work necessary to obtain such permits.
- 2 Price is subject to change due to any freight increases, liquid asphalt increases, and fuel surcharges incurred.
- 3 Hayden Paving shall not warranty asphalt failures caused by sub-grade or base failures where asphalt is placed on existing sub-grade, base or asphalt surface which was not installed by Hayden Paving.
- 4 Asphalt paving industry recommended grade for proper drainage of asphalt surfaces is 2%. Designed grades of less than 1.5% will increase the chances of water ponding. Hayden Paving shall not guarantee zero ponding on surfaces designed with less than 1.5% grade.
- 5 Engineering layout, offset stakes and string line elevation control costs are not included in this quotation. This quote is based upon the assumption that elevations shall be controlled by existing curbs, gutters, base material, etc

"20 Years Experience"

Acceptance of proposal - The above prices, specifications and conditions are satisfactory and are hereby accepted. Hayden Paving, Inc is authorized to do the work as specified. Payment will be made as described by payment terms listed above. Hayden Paving, Inc. reserves the right to repossess any material that is not paid in full within 90 days of the job completion.

Signature _____

Date _____

Print Name _____