

December 26, 2024

#### **Project Narrative**

Project: Taco Bell

1803 Washington Street

Two Rivers, WI

Pacific Bells LLC is requesting site plan and conditional use review and approval for a new Taco Bell quick-serve restaurant with a drive-thru located at 1803 Washington Street in the City of Two Rivers. The property is zoned B-1 Business and the proposed use is permitted. The drive-thru use requires a conditional use permit. The 0.63 acre site currently contains a retail store that will be demolished for the proposed project.

The proposed Taco Bell will be single-story with a building footprint of 2,239 square feet with a single drive-thru lane around the north side of the building. A waste enclosure is proposed on the southeast corner of the site. Adequate parking will be provided with 16 spaces (including 1 handicap accessible stall). The existing access to the site from 18<sup>th</sup> Street will remain and the existing access from Washington St will be reconstructed in the same location.

Exterior materials are represented in the attached color elevations and waste enclosure detail. The building and site will blend in with and enhance the character of the area. The property will be transformed into a commercial development that is aesthetically pleasing with high-quality exterior materials on the building along with landscaping designed to ensure species resiliency and complimentary style. Site lighting will be provided in a fashion that provides appropriate foot candles for safety with cut-off fixtures for minimal light trespass and directed inward toward the development.



#### LAND DEVELOPMENT APPLICATION

APPLICANT_ Pacific Bells (Contact: Kari Keller)		TELEPHONE714-724-9415			
MAILING ADDRESS	111 W 39th Street	Vancouver		WA	98660
	(Street)	(City)	(	State)	(Zip)
PROPERTY OWNE	R CEHOG I, LLC	**	TELEF	HONE 847-904	-9201
MAILING ADDRESS		Brewntw		TN	37027
	(Street)	(City)	(	State)	(Zip)
REQUEST FOR:	Comprehensive	Plan Amendment	X Condition	al Han	
_	The state of the s				
_	X Site/Architectura Subdivision Plat			n Request	_
_	Zoning District C		Other	Board of Appeal	5
			Other		
STATUS OF APPLI	CANT: <u>x</u> O	wner Agent	Buyer _	x Other	
PROJECT LOCATION	ON 1803 Washington S	treetTYPI	E OF STRUCTURE	Proposed 2,23	39 sf building
PRESENT ZONING	B-1 Business	REG	QUESTED ZONING	B-1 Business	
PROPOSED LAND	USE Taco Bell restau	rant with drive-thru			
PARCEL # 053000			ACREAGE0.	63	<del></del>
		d Nine (9) of Block Fifty-one (51) of the			itowoc County, Wisconsin
		ne-page written description	<u> </u>		•
	NOTE. Attach a of	re-page written description	or your proposar	or request.	
this application. The	rtifies that he/she has fa	miliarized himself/herself with ereby certifies that the inform	ation contained in the	nis application is	edures pertaining to true and correct.
Signed (F	Property Owner)	7	Date1	2/24/2024	
				Market Control	
Fee Required			Schedule		
	sive Plan Amendment		Application Submittal	Date	
\$ t/b/d CSM Review	itectural Plan Approval (Listed in Sec 1-2-1) view (\$10 lot/\$30 min)		Date Fee(s) Paid	-	
\$ 350 Zoning Distr	Plat (fee to be determined) ict Change		Plan(s) Submittal Dat	e	
\$ 350 Conditional \$ t/b/d Annexation	Use Request (State Processing	Fees Apply)	Plan Comm Appearar		
	ard of Appeals	. 555 . ippiy)	Tian Commin Appearar		
\$TO	TAL FEE PAID	APPLICATION, PLANS & FEE	RECEIVED BY		
















## NEW BUILDING FOR:

# PACIFIC BELLS LLC

## TWO RIVERS, WI



PROPERTY LINES AND EASEMENTS SHOWN ON THIS SURVEY WERE DRAFTED FROM INFORMATION CONTAINED IN TITLE COMMITMENT NO. \_\_\_\_, BY \_\_\_\_ TITLE COMPANY, DATED \_\_\_, 20\_\_. AN UPDATED PLAT OF SURVEY, CERTIFIED SURVEY MAP OR ALTA SURVEY HAS NOT BEEN AUTHORIZED. SURFACE INDICATIONS OF UTILITIES ALONG WITH DIGGER'S HOTLINE MARKINGS PER TICKET NO. 20244618020 HAVE BEEN SHOWN. SIZES AND ELEVATION OF UNDERGROUND UTILITIES SHOWN HEREON ARE BASED ON FIELD MEASUREMENTS OF VISIBLE STRUCTURES IN COMBINATION WITH AVAILABLE DATA PROVIDED TO EXCEL ENGINEERING EXCEL ENGINEERING MAKES NO GUARANTEE THAT ALL THE EXISTING UTILITIES IN THE SURVEYED AREA HAVE BEEN SHOWN NOR THAT THEY ARE IN THE EXACT LOCATION INDICATED. CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE LOCATION OF ALL UTILITIES PRIOR TO CONSTRUCTION. THIS PLAN IS IN NO WAY A SUBSTITUTE FOR UTILITY LOCATING AT THE TIME OF EXCAVATION.



## **PROJECT CONTACTS**

OWNER INFORMATION: Anchor Point ManagEment Kari Keller 111W. 39TH Street Vancouver, WA 98660 Phone: (714) 724-9415 Email: KKeller@Anchorpointmg.com

CIVIL: Eric Drazkowski, P.E. Phone: (920)322-1678 E-mail: eric.drazkowski@excelengineer.com


CITY PLANNER Elizabeth Runge Phone: (920)793-5566 E-mail: erunge@two-rivers.org

CITY ENGINEER/DIRECTOR OF PUBLIC WORKS Matthew Heckenlaible Phone: (920)793-5566 E-mail: mathec@two-rivers.org

CITY FIRE CHIEF: Dave Murack Phone: (920)793-5521

CITY BUILDING INSPECTOR Jane Drager Phone: (920)793-5566 E-mail: jdrager@two-rivers.org

## **LOCATION MAP**



## PROJECT NOTES

#### **GENERAL PROJECT NOTES**

1. ALL DRIVEWAYS AND CURB CUTS TO BE CONSTRUCTED ACCORDING TO LOCAL ORDINANCES. CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS.

2. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL WORK IN ROW PERMITS.

#### CONSTRUCTION STAKING SERVICES

CONSTRUCTION STAKING SHALL BE COMPLETED BY EXCEL ENGINEERING AS REQUESTED BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE. CONTRACTOR TO CONTACT RYAN WILGREEN AT 920-926-9800 OR RYAN.W@EXCELENGINEER.COM TO GET STAKING PRICE TO INCLUDE IN BID TO OWNER. PAYMENT OF STAKING COSTS ABOVE AND BEYOND THE BASE PRICE DUE TO RESTAKING WILL BE THE RESPONSIBILITY OF THE CONTRACTOR, NOT THE OWNER. CAD DRAWING FILES AND SURVEY CONTROL WILL NOT BE PROVIDED FOR STAKING PURPOSES.

## **SHEET INDEX**

SHEETS BELOW INTENDED TO BE PRINTED IN: COLOR. REFER TO DIGITAL FORMAT DRAWINGS IF PRINTED GRAYSCALE TO ENSURE SCOPE CLARITY.

NUMBER	SHEET NAME / DESCRIPTION
C0.1	CIVIL COVER SHEET
C0.2	CIVIL SPECIFICATIONS
C1.0	EXISTING SITE AND DEMOLITION PLAN
C1.1	SITE PLAN
C1.2	GRADING AND EROSION CONTROL PLAN
C1.3	UTILITY PLAN
C1.4	LANDSCAPE AND RESTORATION PLAN
C2.0	DETAILS
C2.1	DETAILS
C3.1	SITE PHOTOMETRIC PLAN & DETAILS

## **LEGEND**

SYM. SPOT ELEVATION	BOLS SHOWN MAY NOT APPEAR ON DRAWINGS.  IDENTIFICATION  ONS	SYM.	IDENTIFICATION
000.00	PROPOSED SPOT ELEVATIONS (FLOW LINE OF CURB UNLESS OTHERWISE SPECIFIED)	000.00 TC	PROPOSED SPOT ELEVATIONS (TOP OF CURB, FLOWLINE
000.00 EG	EXISTING GRADE SPOT ELEVATIONS	000.00 FL	OF CURB)
000.00 BG 000.00 FG	PROPOSED SPOT ELEVATIONS (REFERENCE R-WALL DETAIL) BG-FINISHED SURFACE GRADE AT BACK OF WALL FG-FINISHED SURFACE GRADE AT FRONT OF WALL	000.00 TW 000.00 BW	PROPOSED SPOT ELEVATIONS (TOP OF WALK, BOTTOM OF WALK @ FLOWLINE)
EXISTING SITE	SYMBOLS		
-0-	EXISTING SIGN	Ø	EXISTING UTILITY POLE
Ŀ	EXISTING HANDICAP PARKING STALL	$\varnothing \longrightarrow$	EXISTING UTILITY POLE WITH GUY WIRE
8	EXISTING WATER VALVE IN BOX	0	EXISTING STREET LIGHT
<u></u> ⊗	EXISTING WATER VALVE IN MANHOLE	T	EXISTING TELEPHONE PEDESTAL
<b>X</b>	EXISTING WATER SERVICE VALVE	E	EXISTING ELECTRIC PEDESTAL
W -	EXISTING WELL		EXISTING ELECTRIC BOX
<b>:</b>	EXISTING STORM CATCH BASIN	•	EXISTING FLOOD LIGHT
<u> </u>	EXISTING STORM CURB INLET	T)	EXISTING TELEPHONE MANHOLE
	EXISTING SQUARE CATCH BASIN	©	EXISTING CABLE TV PEDESTAL
ф 	EXISTING LIGHT POLE	M	EXISTING GAS VALVE
	1-1/4" REBAR SET WEIGHING 4.30 LB/FT.	- 00	EXISTING HEDGE
<u> </u>	3/4" REBAR SET WEIGHING 1.50 LB/FT.		EXISTING WOODED AREA
	1-1/4" REBAR FOUND	<u>alli</u>	EXISTING MARSH AREA
0	3/4" REBAR FOUND	(•)	EXISTING DECIDUOUS TREE WITH TRUNK DIAMETER
<u> </u>	2" IRON PIPE FOUND	**	EXISTING CONIFEROUS TREE
	1" IRON PIPE FOUND		EXISTING SHRUB
DDODOSED SY	SECTION CORNER	A	EXISTING STUMP
PROPOSED SIT	TE SYMBOLS		
•	PROPOSED SIGN	<b>#</b>	PROPOSED STORM FIELD INLET - ST FI
<u></u> <u>E</u> ,	PROPOSED HANDICAP PARKING STALL	0-1	PROPOSED LIGHT POLE
⊗	PROPOSED WATER VALVE IN BOX	$\rightarrow$	PROPOSED DRAINAGE FLOW
<b>⊗</b>	PROPOSED WATER VALVE IN MANHOLE	<u> </u>	PROPOSED APRON END SECTION
×	PROPOSED WATER SERVICE VALVE		SOIL BORING
<b>W</b>	PROPOSED WELL	<u> </u>	CENTER LINE
<b>◎</b>	PROPOSED STORM CATCH BASIN - ST CB	co	PROPOSED CLEANOUT
='=	PROPOSED STORM CURB INLET - ST CI	DSG	PROPOSED DOWNSPOUT TO GRADE
		DSR	PROPOSED DOWNSPOUT TO RISER
EXISTING LINE	TYPES		
<u> </u>	— EXISTING CHAINLINK FENCE	POL	EXISTING POLISH SEWER AND MANHOLE
	—— EXISTING WOOD FENCE	P -	EXISTING PROCESS SEWER AND MANHOLE
×	— EXISTING BARBED WIRE FENCE	CLW	— EXISTING CLEAR WATER LINE
	EXISTING CURB AND GUTTER	— FO —	EXISTING UNDERGROUND FIBER OPTIC LINE
0 0 0	EXISTING GUARD RAIL	— E —	EXISTING UNDERGROUND ELECTRIC CABLE
_ 800	EXISTING GROUND CONTOUR	т	EXISTING UNDERGROUND TELEPHONE CABLE
ST(	⊕— EXISTING STORM SEWER AND MANHOLE	G	EXISTING UNDERGROUND GAS LINE
SA(	S—EXISTING SANITARY SEWER AND MANHOLE	OU	EXISTING OVERHEAD UTILITY LINE
— <b>%</b> —	EXISTING WATER LINE AND HYDRANT		RAILROAD TRACKS
	INTERIOR PROPERTY LINE		- RIGHT-OF-WAY LINE
ROPOSED LINE	<u>ETYPES</u>		
•	PROPOSED CHAINLINK FENCE	POL	PROPOSED POLISH SEWER AND MANHOLE
0 0	PROPOSED WOOD FENCE	— P — <del>□</del>	PROPOSED PROCESS SEWER AND MANHOLE
	-X- PROPOSED BARBED WIRE FENCE	CLW	PROPOSED CLEAR WATER LINE
	PROPOSED CURB AND GUTTER	—— FO ——	PROPOSED UNDERGROUND FIBER OPTIC LINE
• • •	PROPOSED GUARD RAIL	— Е —	PROPOSED UNDERGROUND ELECTRIC CABLE
<del>-</del> 800	PROPOSED GROUND CONTOUR	— т —	PROPOSED UNDERGROUND TELEPHONE CABLE
— st — (	PROPOSED STORM SEWER AND MANHOLE - ST MH	—— G ——	PROPOSED UNDERGROUND GAS LINE
SA(	PROPOSED SANITARY SEWER AND MANHOLE - SAN MH	OU	PROPOSED OVERHEAD UTILITY LINE
<b>_</b>	PROPOSED WATER LINE AND HYDRANT		-MATCHLINE
'	PROPOSED PROPERTY LINE		— GRADING/SEEDING LIMITS

CIVIL COVER SHEET



**PROJECT INFORMATION** 

Fond du Lac, WI 54935 920-926-9800 excelengineer.com

PROFESSIONAL SEAL

**PRELIMINARY DATES** DEC. 20, 2024

JOB NUMBER 240331100

**SHEET NUMBER** 

## **CIVIL SPECIFICATIONS**

#### **DIVISION 31 EARTH WORK**

#### 31 10 00 SITE CLEARING

- A. CONTRACTOR SHALL CALL DIGGER'S HOT LINE AND CONDUCT A PRIVATE UTILITY LOCATE AS REQUIRED TO ENSURE THAT ALL UTILITIES HAVE BEEN LOCATED BEFORE STARTING SITE DEMOLITION. DESIGN ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES BETWEEN PLAN AND FIELD CONDITIONS PRIOR TO CONSTRUCTION.
- B. CONTRACTOR TO FIELD TELEVISE ALL EXISTING SANITARY AND STORM LATERALS THAT ARE SCHEDULED TO BE RE-USED AND/OR CONNECTED TO ON SITE AT TIME OF DEMOLITION. THE TELEVISING SHALL BE COMPLETED TO ENSURE THE EXISTING LATERAL(S) ARE FREE OF OBSTRUCTIONS AND IN SOUND STRUCTURAL CONDITION. TELEVISING OF THESE LATERAL(S) SHOULD BE COMPLETED AT BEGINNING OF CONSTRUCTION AND DESIGN ENGINEER SHALL BE NOTIFIED OF ANY PIPE OBSTRUCTIONS AND/OR STRUCTURAL DEFICIENCIES IMMEDIATELY AFTER COMPLETION OF FIELD TELEVISING.
- C. DEMOLITION PLAN IS AN OVERVIEW OF DEMOLITION TO TAKE PLACE ON SITE. CONTRACTOR TO FIELD VERIFY EXISTING SITE CONDITIONS PRIOR TO BIDDING. CONTRACTOR SHALL REMOVE, REPLACE, OR DEMOLISH ALL ITEMS AS NEEDED DURING CONSTRUCTION.

  D. CONTRACTOR TO PROTECT EXISTING IMPROVEMENTS THAT ARE SCHEDULED TO REMAIN. ANY DAMAGE TO EXISTING FACILITIES SHALL BE
- CONTRACTOR TO PROTECT EXISTING IMPROVEMENTS THAT ARE SCHEDULED TO REMAIN. ANY DAMAGE TO EXISTING FACILITIES SHALL
  REPLACED AT CONTRACTORS EXPENSE.
- E. ALL CONCRETE NOTED TO BE REMOVED SHALL BE REMOVED TO THE NEAREST CONTROL JOINT.

#### 31 20 00 EARTH MOVING

- A. CONTRACTOR SHALL CALL DIGGER'S HOT LINE AND CONDUCT A PRIVATE UTILITY LOCATE AS REQUIRED TO ENSURE THAT ALL UTILITIES HAVE BEEN LOCATED BEFORE STARTING EXCAVATION. DESIGN ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES BETWEEN PLAN AND FIELD CONDITIONS PRIOR TO CONSTRUCTION.
- B. PROVIDE ALL LABOR, MATERIALS AND EQUIPMENT FOR ALL EXCAVATION, GRADING, FILL AND BACKFILL WORK AS REQUIRED TO COMPLETE THE GENERAL CONSTRUCTION WORK. ALL EXCAVATION AND BACKFILL FOR ELECTRICALS AND MECHANICALS ARE THE RESPONSIBILITY OF THE RESPECTIVE CONTRACTOR UNLESS OTHERWISE SPECIFIED IN THE BID DOCUMENTS.
- C. ALL ORGANIC TOPSOIL INSIDE THE BUILDING AREA, UNDER PAVED AREAS, AND AT SITE FILL AREAS SHALL BE REMOVED. PROOF ROLL SUBGRADES BEFORE PLACING FILL WITH HEAVY PNEUMATIC-TIRED EQUIPMENT, SUCH AS A FULLY-LOADED TANDEM AXLE DUMP TRUCK, TO IDENTIFY SOFT POCKETS AND AREAS OF EXCESS YIELDING. CONTRACTOR SHALL VERIFY TOPSOIL DEPTHS PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL REVIEW AND FOLLOW THE RECOMMENDATIONS OF THE GEOTECHNICAL REPORT AND ACCOUNT FOR EXISTING CONDITIONS PRIOR TO SUBMITTING BID FOR THE PROJECT. EXCESS MATERIALS SHALL BE REMOVED FROM THE SITE UNLESS OTHERWISE DIRECTED IN THE PLANS OR BY LOCAL ZONING REQUIREMENTS.
- D. PLACE AND COMPACT FILL MATERIAL IN LAYERS TO REQUIRED ELEVATIONS. UNIFORMLY MOISTEN OR AERATE SUBGRADE AND EACH SUBSEQUENT FILL OR BACKFILL LAYER BEFORE COMPACTION AS RECOMMENDED TO ACHIEVE SPECIFIED DRY DENSITY. REMOVE AND REPLACE, OR SCARIFY AND AIR DRY, OTHERWISE SATISFACTORY SOIL MATERIAL THAT IS TOO WET TO COMPACT TO SPECIFIED DRY DENSITY
- E. PLACE BACKFILL AND FILL MATERIALS IN LAYERS NOT MORE THAN 8" IN LOOSE DEPTH FOR MATERIAL COMPACTED BY HEAVY COMPACTION EQUIPMENT, AND NOT MORE THAN 4" IN LOOSE DEPTH FOR MATERIAL COMPACTED BY HAND-OPERATED TAMPERS.
- F. COMPACTION EQUIPMENT, AND NOT MORE THAN 4 IN LOOSE DEPTH FOR MATERIAL COMPACTED BY HAND-OPERATED TAMPERS.

  F. COMPACT THE SOIL TO NOT LESS THAN THE FOLLOWING PERCENTAGES OF MAXIMUM DRY DENSITY ACCORDING TO ASTM D 698, STANDARD PROCTOR TEST. FILL MAY NOT BE PLACED ON FROZEN GROUND AND NO FROZEN MATERIALS MAY BE USED FOR BACK FILL. APPLY THE MORE STRINGENT REQUIREMENTS WHEN COMPARING BETWEEN THE FOLLOWING AND THE GEOTECHNICAL REPORT.

  1. UNDER FOUNDATIONS SUBGRADE, AND EACH LAYER OF BACKFILL OR FILL MATERIAL, TO NOT LESS THAN 98 PERCENT.

  2. UNDER INTERIOR SLAB-ON-GRADE WHERE GROUNDWATER IS MORE THAN 3 FEET BELOW THE SLAB PLACE A DRAINAGE COURSE
- LAYER OF 3/4" CRUSHED STONE, WITH 5% TO 12% FINES, PER THICKNESS INDICATED ON FOUNDATION PLANS ON PREPARED SUBGRADE. COMPACT THE SUBGRADE AND DRAINAGE COURSE TO NOT LESS THAN 95 PERCENT.

  3. UNDER INTERIOR SLAB-ON-GRADE WHERE GROUNDWATER IS WITHIN 3 FEET OF THE SLAB SURFACE- PLACE A DRAINAGE COURSE LAYER OF CLEAN 3/4" CRUSHED STONE, WITH NO MORE THAN 5% FINES, PER THICKNESS INDICATED ON FOUNDATION PLANS ON PREPARED SUBGRADE. COMPACT THE SUBGRADE AND DRAINAGE COURSE TO NOT LESS THAN 95 PERCENT.
- 4. UNDER EXTERIOR CONCRETE AND ASPHALT PAVEMENTS COMPACT THE SUBGRADE AND EACH LAYER OF BACKFILL OR FILL MATERIAL TO NOT LESS THAN 95 PERCENT.
- 5. UNDER WALKWAYS COMPACT SUBGRADE AND EACH LAYER OF BACKFILL OR FILL MATERIAL TO NOT LESS THAN 95 PERCENT.
  6. UNDER LAWN OR UNPAVED AREAS COMPACT SUBGRADE AND EACH LAYER OF BACKFILL OR FILL MATERIAL, TO NOT LESS THAN 85 PERCENT
- G. CONTRACTOR SHALL ENGAGE A QUALIFIED INDEPENDENT TESTING AND INSPECTING AGENCY TO PERFORM FIELD TESTS AND INSPECTIONS. CONTRACTOR SHALL PROVIDE DOCUMENTATION OF PASSING DENSITY TESTING AND PROOF-ROLLING TO ENGINEER UPON COMPLETION. IT IS SUGGESTED THAT THE GEOTECHNICAL FIRM USED TO PERFORM THE SUBSURFACE SOIL INVESTIGATION BE ENGAGED FOR THE FIELD QUALITY CONTROL TESTS.
- H. ALLOW THE TESTING AGENCY TO TEST AND INSPECT SUBGRADES AND EACH FILL OR BACKFILL LAYER. PROCEED WITH SUBSEQUENT EARTHWORK ONLY AFTER TEST RESULTS FOR PREVIOUSLY COMPLETED WORK COMPLY WITH REQUIREMENTS. PROVIDE ONE TEST FOR EVERY 2000 SQUARE FEET OF PAVED AREA OR BUILDING SLAB, ONE TEST FOR EACH SPREAD FOOTING, AND ONE TEST FOR EVERY 50 LINEAR FEET OF WALL STRIP FOOTING.
- I. WHEN THE TESTING AGENCY REPORTS THAT SUBGRADES, FILLS, OR BACKFILLS HAVE NOT ACHIEVED DEGREE OF COMPACTION SPECIFIED, SCARIFY AND MOISTEN OR AERATE, OR REMOVE AND REPLACE SOIL TO DEPTH REQUIRED; RECOMPACT AND RETEST UNTIL SPECIFIED COMPACTION IS OBTAINED.
- J. THE BUILDING SITE SHALL BE GRADED TO PROVIDE DRAINAGE AWAY FROM THE BUILDING AS INDICATED ON THE PLANS. SITE EARTHWORK SHALL BE GRADED TO WITHIN 0.10' OF REQUIRED EARTHWORK ELEVATIONS ASSUMING POSITIVE DRAINAGE IS MAINTAINED IN ACCORDANCE WITH THE GRADING PLAN.

#### 31 30 00 EROSION CONTROL

- A. THE GRADING PLAN REFLECTS LESS THAN 1 ACRE OF DISTURBED AREA. THE SITE IS THEREFORE EXEMPT FROM WISCONSIN DEPARTMENT OF NATURAL RESOURCES NR 216 NOTICE OF INTENT REQUIREMENTS. THE DESIGN ENGINEER SHALL PREPARE AN EROSION CONTROL PLAN TO MEET NR 151.105 CONSTRUCTION SITE PERFORMANCE STANDARDS FOR NON-PERMITTED SITES.
- B. EROSION AND SEDIMENT CONTROL IMPLEMENTED DURING CONSTRUCTION SHALL STRICTLY COMPLY WITH THE GUIDELINES AND REQUIREMENTS SET FORTH IN WISCONSIN ADMINISTRATIVE CODE (W.A.C.) NR 151, THE STATE OF WISCONSIN DEPARTMENT OF NATURAL RESOURCES RUNOFF MANAGEMENT PERFORMANCE STANDARDS. TECHNICAL STANDARDS PUBLISHED BY THE WISCONSIN DNR SHALL ALSO BE UTILIZED TO IMPLEMENT THE REQUIRED PERFORMANCE STANDARDS. THE METHODS AND TYPES OF EROSION CONTROL WILL BE DEPENDENT ON THE LOCATION AND TYPE OF WORK INVOLVED. ALL SEDIMENT CONTROL MEASURES SHALL BE ADJUSTED TO MEET FIELD CONDITIONS AT THE TIME OF CONSTRUCTION, AND INSTALLED PRIOR TO ANY GRADING OR DISTURBANCE OF EXISTING SURFACE MATERIAL. BELOW IS A LIST OF EROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICES TO ACHIEVE THE PERFORMANCE STANDARDS REQUIRED.
- 1. SILT FENCE SHALL BE PLACED ON SITE AT LOCATIONS SHOWN ON THE EROSION CONTROL PLAN. SILT FENCE SHALL ALSO BE PROVIDED AROUND THE PERIMETER OF ALL SOIL STOCKPILES THAT WILL EXIST FOR MORE THAN 7 DAYS. FOLLOW PROCEDURES FOUND IN WISCONSIN DNR TECHNICAL STANDARD 1056 (CURRENT EDITION).
- 2. DITCH CHECKS SHALL BE PROVIDED TO REDUCE THE VELOCITY OF WATER FLOWING IN DITCH BOTTOMS. PLACE AT LOCATIONS SHOWN ON THE EROSION CONTROL PLAN. FOLLOW PROCEDURES FOUND IN WISCONSIN DNR TECHNICAL STANDARD 1062 (CURRENT EDITION)
- 3. STONE TRACKING PADS AND TRACKOUT CONTROL PRACTICES SHALL BE PLACED AT ALL CONSTRUCTION SITE ENTRANCES AND SHALL BE INSTALLED PRIOR TO ANY TRAFFIC LEAVING THE CONSTRUCTION SITE. SEE THE EROSION CONTROL PLAN FOR LOCATIONS. THE AGGREGATE USED FOR THE STONE TRACKING PAD SHALL BE 3/8" TO 3 INCH CLEAR OR WASHED STONE AND SHALL BE PLACED IN A LAYER AT LEAST 12 INCHES THICK. THE STONE SHALL BE UNDERLAIN WITH A WISDOT TYPE R GEOTEXTILE FABRIC AS NEEDED. THE TRACKING PAD SHALL BE THE FULL WIDTH OF THE EGRESS POINT (12' MIN WIDTH) AND SHALL BE A MINIMUM OF 50 FEET LONG. SURFACE WATER MUST BE PREVENTED FROM PASSING THROUGH THE TRACKING PAD. OTHER TRACKOUT CONTROL PRACTICES INCLUDING STABILIZED WORK SURFACES, MANUFACTURED TRACKOUT CONTROL DEVICES, TIRE WASHING, AND STREET/PAVEMENT CLEANING SHALL BE IMPLEMENTED AS NECESSARY TO MITIGATE THE TRACKOUT OF SEDIMENT OFFSITE. FOLLOW PROCEDURES FOUND IN WISCONSIN DNR TECHNICAL STANDARD 1057 (CURRENT EDITION).
- 4. STORM DRAIN INLET PROTECTION SHALL BE PROVIDED FOR ALL NEW AND DOWNSTREAM STORM CATCH BASINS AND CURB INLETS. TYPE B OR C PROTECTION SHOULD BE PROVIDED AND SHALL BE IN CONFORMANCE WITH WISCONSIN DNR TECHNICAL STANDARD 1060 (CURRENT EDITION).
- 5. DUST CONTROL MEASURES SHALL BE PROVIDED TO REDUCE OR PREVENT THE SURFACE AND AIR TRANSPORT OF DUST DURING CONSTRUCTION. CONTROL MEASURES INCLUDE APPLYING MULCH AND ESTABLISHING VEGETATION, WATER SPRAYING, SURFACE ROUGHENING, APPLYING POLYMERS, SPRAY-ON TACKIFIERS, CHLORIDES, AND BARRIERS. SOME SITES MAY REQUIRE AN APPROACH THAT UTILIZES A COMBINATION OF MEASURES FOR DUST CONTROL. FOLLOW PROCEDURES FOUND IN WISCONSIN DNR TECHNICAL STANDARD 1068 (CURRENT EDITION)
- THE USE, STORAGE, AND DISPOSAL OF CHEMICALS, CEMENT, AND OTHER COMPOUNDS AND MATERIALS USED ON SITE SHALL BE
  MANAGED DURING THE CONSTRUCTION PERIOD TO PREVENT THEIR TRANSPORT BY RUNOFF INTO WATERS OF THE STATE.
   CONTRACTOR SHALL PROVIDE AN OPEN AGGREGATE CONCRETE TRUCK WASHOUT AREA ON SITE. CONTRACTOR TO ENSURE THAT
  CONCRETE WASHOUT SHALL BE CONTAINED TO THIS DESIGNATED AREA AND NOT BE ALLOWED TO RUN INTO STORM INLETS OR INTO
  THE OVERLAND STORMWATER DRAINAGE SYSTEM. WASHOUT AREA SHALL BE REMOVED UPON COMPLETION OF CONSTRUCTION.
- 8. TEMPORARY SITE RESTORATION SHALL TAKE PLACE IN DISTURBED AREAS THAT WILL NOT BE BROUGHT TO FINAL GRADE OR ON WHICH LAND DISTURBING ACTIVITIES WILL NOT BE PERFORMED FOR A PERIOD GREATER THAN 14 DAYS AND REQUIRES VEGETATIVE COVER FOR LESS THAN ONE YEAR. THIS TEMPORARY SITE RESTORATION REQUIREMENT ALSO APPLIES TO SOIL STOCKPILES THAT EXIST FOR MORE THAN 7 DAYS. PERMANENT RESTORATION APPLIES TO AREAS WHERE PERENNIAL VEGETATIVE COVER IS NEEDED TO PERMANENTLY STABILIZE AREAS OF EXPOSED SOIL. PERMANENT STABILIZATION SHALL OCCUR WITHIN 3 WORKING DAYS OF FINAL GRADING. TOPSOIL, SEED, AND MULCH SHALL BE IN GENERAL CONFORMANCE WITH TECHNICAL STANDARDS 1058 AND 1059 AND SHALL MEET THE SPECIFICATIONS FOUND IN THE LANDSCAPING AND SITE STABILIZATION SECTION OF THIS CONSTRUCTION DOCUMENT. ANY SOIL EROSION THAT OCCURS AFTER FINAL GRADING AND/OR FINAL STABILIZATION MUST BE REPAIRED AND THE STABILIZATION WORK REDONE.
- IF SITE DEWATERING IS REQUIRED FOR PROPOSED CONSTRUCTION ACTIVITIES, ALL SEDIMENT LADEN WATER GENERATED DURING THE DEWATERING PROCESS SHALL BE TREATED TO REMOVE SEDIMENT PRIOR TO DISCHARGING OFF-SITE OR TO WATERS OF THE STATE. FOLLOW ALL PROCEDURES FOUND IN TECHNICAL STANDARD 1061.
- 10. ALL OFF-SITE SEDIMENT DEPOSITS OCCURRING AS A RESULT OF CONSTRUCTION WORK OR A STORM EVENT SHALL BE CLEANED UP BY THE END OF EACH WORKING DAY. DUST CONTROL REQUIREMENTS SHALL BE FOLLOWED PER WI DNR TECHNICAL STANDARD 1068 (CURRENT EDITION). FLUSHING SHALL NOT BE ALLOWED.
- C. ALL EROSION CONTROL DEVICES SHALL AT A MINIMUM BE INSPECTED EVERY 7 CALENDAR DAYS OR EVERY 14 DAYS AND WITHIN 24 HOURS OF THE END OF A RAIN EVENT OF 0.5" OR MORE. MAINTENANCE SHALL BE PERFORMED PER WISCONSIN ADMINISTRATIVE CODE (W.A.C.) NR 151 STORMWATER MANAGEMENT TECHNICAL STANDARD REQUIREMENTS.
- D. EROSION CONTROL MEASURES SHALL NOT BE REMOVED UNTIL THE AREA(S) SERVED HAVE ESTABLISHED VEGETATIVE COVER.
- E. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL LOCAL EROSION CONTROL PERMITS.

#### **DIVISION 32 EXTERIOR IMPROVEMENTS**

#### 32 10 00 AGGREGATE BASE & ASPHALT PAVEMENT

A. CONTRACTOR TO PROVIDE COMPACTED AGGREGATE BASE AND HOT MIX ASPHALT PAVEMENT WHERE INDICATED ON THE PLANS. ALL AGGREGATE PROVIDED MUST COMPLY WITH SECTION 305 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION. PROVIDE HOT MIX ASPHALT MIXTURE TYPES PER SECTION 460 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION. CONTRACTOR SHALL OBTAIN AND REVIEW SOILS REPORT FOR RECOMMENDATIONS FOR GEO-GRID / GEOTEXTILE BELOW CRUSHED AGGREGATE (IF APPLICABLE). CONTRACTOR TO PROVIDE AGGREGATE BASE AND HOT MIX ASPHALT PAVEMENT TYPES AND DEPTHS AS INDICATED BELOW:

STANDARD ASPHALT PAVING SECTION
1-1/2" SURFACE COURSE (5 LT 58-28S)

(WISDOT 455.2.5 TACK COAT (STAGED PAVING)
2" BINDER COURSE (4 LT 58-28S)

10" OF 1-1/4" CRUSHED AGGREGATE

HEAVY ASPHALT PAVING SECTION
1-1/2" SURFACE COURSE (5 LT 58-28S)

WISDOT 455.2.5 TACK COAT (STAGED PAVING)
2-1/2" BINDER COURSE (4 LT 58-28S)

12" OF 1-1/4" CRUSHED AGGREGATE

- B. CONTRACTOR TO COMPACT THE AGGREGATE BASE, ASPHALT BINDER COURSE, AND ASPHALT SURFACE COURSE TO AN AVERAGE DENSITY PER WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION. ALL ASPHALT PAVEMENT AREAS SHALL BE PAVED TO WITHIN 0.05' OF DESIGN SURFACE GRADES WITH POSITIVE DRAINAGE BEING MAINTAINED IN ACCORDANCE WITH DESIGN PLANS. A MINIMUM OF 1.1% SLOPE SHALL BE MAINTAINED IN ALL ASPHALT PAVEMENT AREA.
- C. HOT MIX ASPHALT CONSTRUCTION TO BE PROVIDED PER MORE STRINGENT REQUIREMENTS OF GEOTECHNICAL REPORT OR CONSTRUCTION DOCUMENTS.
- D. CONTRACTOR TO PROVIDE 4" WIDE YELLOW PAINTED STRIPING FOR PARKING STALLS, TRAFFIC LANES, AND NO PARKING AREAS. YELLOW PAINT MARKINGS SHALL ALSO BE PROVIDED FOR H.C. ACCESSIBLE SYMBOLS, TRAFFIC ARROWS, AND TRAFFIC MESSAGES.

#### 32 20 00 CONCRETE AND AGGREGATE BASE

- A. CONTRACTOR TO PROVIDE CRUSHED AGGREGATE BASE AND CONCRETE WHERE INDICATED ON THE PLANS.

  B. ALL AGGREGATE PROVIDED MUST COMPLY WITH SECTION 305 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION. ALL AGGREGATE PLACED MUST BE COMPACTED TO AN AVERAGE DENSITY PER WISCONSIN STANDARD
- SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION.

  C. DESIGN AND CONSTRUCTION OF ALL CAST-IN-PLACE EXTERIOR CONCRETE FLAT WORK SHALL CONFORM TO ACI 330R-08 & ACI 318-08.

  D. EXTERIOR CONCRETE FLAT WORK CONSTRUCTION TO BE PROVIDED PER MORE STRINGENT REQUIREMENTS OF THE GEOTECHNICAL
- REPORT OR THIS SPECIFICATION. CONCRETE FLAT WORK CONSTRUCTION IS AS FOLLOWS:

  1. SIDEWALK CONCRETE 4" OF CONCRETE OVER 4" OF 3/4" CRUSHED AGGREGATE BASE. CONTRACTION JOINTS SHALL CONSIST OF 1/8"
  WIDE BY 1" DEEP TOOLED JOINT WHERE INDICATED ON THE PLANS.
- 2. DUMPSTER PAD/APRON CONCRETE 8" OF CONCRETE OVER 6" OF AGGREGATE BASE.
- a. CONCRETE SHALL BE STEEL REINFORCED WITH THE FOLLOWING AND PLACED IN THE UPPER 1/3 TO ½ OF THE SLAB:
- 1) TIE BARS AT ALL CONTRACTION JOINTS OF THE CONCRETE. TIE BARS SHALL BE #4 REBAR 30" LONG PLACED AT 30" O.C.
- b. DUMPSTER PAD CONCRETE JOINTING SHALL BE AS FOLLOWS:
- CONTRACTION SAWCUT JOINT CONTRACTOR SHALL PROVIDE A SAWCUT JOINT AT MAXIMUM SPACING OF 15' ON CENTER. SAWCUT SHALL BE 2" IN DEPTH.
- TYPICAL POUR CONTROL JOINT POUR CONTROL JOINT SHALL BE PROVIDED WITH 1-1/4" DIAMETER BY 20" LONG SMOOTH DOWEL PLACED AT 12" O.C. ONE HALF OF THE DOWEL SHALL BE GREASED. GREENSTREAK 9" SPEED DOWEL TUBES SHALL BE USED.
- USED.

  3. HEAVY DUTY CONCRETE (TRUCK TRAFFIC) 6" OF CONCRETE OVER 6" OF 3/4" CRUSHED AGGREGATE. CONCRETE SHALL BE REINFORCED WITH #3 REPARS ON CHAIRS AT 3' O.C. REPAR SHALL BE PLACED IN THE LIPPER 1/3 TO 1/4 OF THE SLAB. CONTRACTION JOINTS
- WITH #3 REBARS ON CHAIRS AT 3' O.C. REBAR SHALL BE PLACED PLACED IN THE UPPER 1/3 TO ½ OF THE SLAB. CONTRACTION JOINTS SHALL BE SAWCUT 1.5" IN DEPTH AND BE SPACED A MAXIMUM OF 15' ON CENTER.

  E. DESIGN MIXES SHALL BE IN ACCORDANCE WITH ASTM C94
- STRENGTH TO BE MINIMUM OF 4,500 PSI AT 28 DAYS FOR EXTERIOR CONCRETE.
- 2. MAXIMUM WATER/CEMENT RATIO SHALL BE 0.45.
- 3. SLUMP SHALL NOT EXCEED 4" FOR EXTERIOR CONCRETE FLAT WORK
  4. SLUMP SHALL BE 2.5" OR LESS FOR SLIP-FORMED CURB AND GUTTER
- SLUMP SHALL BE 2.5 OR LESS FOR SLIP-FORMED CURB AND GUTTER
   SLUMP SHALL BE BETWEEN 1.5" TO 3" FOR NON SLIP-FORMED CURB AND GUTTER
- 6. ALL EXTERIOR CONCRETE SHALL BE AIR ENTRAINED WITH 4% TO 7% AIR CONTENT. NO OTHER ADMIXTURES SHALL BE USED WITHOUT
- APPROVAL OF EXCEL ENGINEERING, INC. CALCIUM CHLORIDE SHALL NOT BE USED.

  7. MAXIMUM AGGREGATE SIZE FOR ALL EXTERIOR CONCRETE SHALL BE 0.75 INCHES.
- F. VERIFY EQUIPMENT CONCRETE PAD SIZES WITH CONTRACTOR REQUIRING PAD. PADS SHALL HAVE FIBERMESH 300 FIBERS AT A RATE OF
- 1.5 LBS/CU. YD. OR 6 X 6-W1.4 X W1.4 WELDED WIRE MESH WITH MINIMUM 1 INCH COVER. EQUIPMENT PADS SHALL BE 5.5 INCHES THICK WITH 1 INCH CHAMFER UNLESS SPECIFIED OTHERWISE. COORDINATE ADDITIONAL PAD REQUIREMENTS WITH RESPECTIVE CONTRACTOR.

  G. ALL CONCRETE FLAT WORK SURFACES AND CONCRETE CURB FLOWLINES SHALL BE CONSTRUCTED TO WITHIN 0.05' OF DESIGN SURFACE AND FLOWLINE GRADES ASSUMING POSITIVE DRAINAGE IS MAINTAINED IN ACCORDANCE WITH THE DESIGN PLANS.
- H. CONCRETE FLAT WORK SHALL HAVE CONSTRUCTION JOINTS OR SAW CUT JOINTS PLACED AS INDICATED ON THE PLANS OR PER THIS SPECIFICATION. SAWCUTS SHALL BE DONE AS SOON AS POSSIBLE, BUT NO LATER THAN 24 HOURS AFTER CONCRETE IS PLACED. CONCRETE CURB AND GUTTER JOINTING SHALL BE PLACED EVERY 10' OR CLOSER (6' MIN.). IF CONCRETE PAVEMENT IS ADJACENT TO CONCRETE CURB, JOINTING IN THE PAVEMENT AND CURB SHALL ALIGN. ALL EXTERIOR CONCRETE SHALL HAVE A BROOM FINISH UNLESS NOTED OTHERWISE. A UNIFORM COAT OF A HIGH SOLIDS CURING COMPOUND MEETING ASTM C309 SHALL BE APPLIED TO ALL EXPOSED

CONCRETE SURFACES. ALL CONCRETE IS TO BE CURED FOR 7 DAYS. EXTERIOR CONCRETE SHALL BE SEPARATED FROM BUILDINGS WITH

- CONTINUOUS 0.5 INCH FIBER EXPANSION JOINT AND/OR 0.25 INCH FIBER EXPANSION JOINT AT DECORATIVE MASONRY UNITS.

  I. ALL REINFORCING BARS SHALL BE ASTM A615 GRADE 60. THICKNESS OF CONCRETE COVER OVER REINFORCEMENT SHALL BE NOT LESS THAN 3" WHERE CONCRETE IS DEPOSITED AGAINST THE GROUND WITHOUT THE USE OF FORMS AND NOT LESS THAN 1.5" FOR UP TO #5 BARS AND 2" FOR #6 TO #10 BARS IN ALL OTHER LOCATIONS. ALL REINFORCING SHALL BE LAPPED 48 DIAMETERS FOR UP TO #6 BARS, 62 DIAMETERS FOR #7 TO #9 BARS, 68 DIAMETERS FOR #10 BARS OR AS NOTED ON THE DRAWINGS AND EXTENDED AROUND CORNERS WITH CORNER BARS. PLACING AND DETAILING OF STEEL REINFORCING AND REINFORCING SUPPORTS SHALL BE IN ACCORDANCE WITH CRSI AND ACI MANUAL AND STANDARD PRACTICES. THE REINFORCEMENT SHALL NOT BE PAINTED AND MUST BE FREE OF GREASE/OIL, DIRT OR DEEP RUST WHEN PLACED IN THE WORK. ALL WELDED WIRE FABRIC SHALL MEET THE REQUIREMENTS OF ASTM A 1064. WELDED
- WIRE FABRIC SHALL BE PLACED 2" FROM TOP OF SLAB, UNLESS INDICATED OTHERWISE.

  J. CONTRACTOR SHALL ENGAGE A QUALIFIED INDEPENDENT TESTING AND INSPECTING AGENCY TO SAMPLE MATERIALS, PERFORM TESTS, AND SUBMIT TEST REPORTS DURING CONCRETE PLACEMENT. TESTS WILL BE PERFORMED ACCORDING TO ACI 301. CAST AND LABORATORY CURE ONE SET OF FOUR STANDARD CYLINDERS FOR EACH COMPOSITE SAMPLE FOR EACH DAY'S POUR OF EACH CONCRETE MIX EXCEEDING 5 CU. YD., BUT LESS THAN 25 CU. YD., PLUS ONE SET FOR EACH ADDITIONAL 50 CU. YD. OR FRACTION THEREOF. PERFORM COMPRESSIVE-STRENGTH TESTS ACCORDING TO ASTM C 39. TEST TWO SPECIMENS AT 7 DAYS AND TWO SPECIMENS AT 28 DAYS. PERFORM SLUMP TESTING ACCORDING TO ASTM C 143. PROVIDE ONE TEST AT POINT OF PLACEMENT FOR EACH COMPOSITE SAMPLE, BUT NOT LESS THAN ONE TEST FOR EACH DAY'S POUR OF EACH CONCRETE MIX. PERFORM ADDITIONAL TESTS WHEN CONCRETE CONSISTENCY
- K. PROTECT FRESHLY PLACED CONCRETE FROM PREMATURE DRYING AND EXCESSIVE COLD OR HOT TEMPERATURES. IN HOT, DRY, AND WINDY WEATHER, APPLY AN EVAPORATION-CONTROL COMPOUND ACCORDING TO MANUFACTURER'S INSTRUCTIONS AFTER SCREEDING AND BULL FLOATING, BUT BEFORE POWER FLOATING AND TROWELLING.
- L. LIMIT MAXIMUM WATER-CEMENTITIOUS RATIO OF CONCRETE EXPOSED TO FREEZING, THAWING AND DEICING SALTS TO 0.45.
- M. TEST RESULTS WILL BE REPORTED IN WRITING TO THE DESIGN ENGINEER, READY-MIX PRODUCER, AND CONTRACTOR WITHIN 24 HOURS AFTER TESTS. REPORTS OF COMPRESSIVE STRENGTH TESTS SHALL CONTAIN THE PROJECT IDENTIFICATION NAME AND NUMBER, DATE OF CONCRETE PLACEMENT, NAME OF CONCRETE TESTING SERVICE, CONCRETE TYPE AND CLASS, LOCATION OF CONCRETE BATCH ON SITE, DESIGN COMPRESSIVE STRENGTH AT 28 DAYS, CONCRETE MIX PROPORTIONS AND MATERIALS, COMPRESSIVE BREAKING STRENGTH, AND TYPE OF BREAK FOR BOTH 7-DAY TESTS AND 28-DAY TESTS.
- N. CONTRACTOR TO PROVIDE 4" WIDE YELLOW PAINTED STRIPING FOR PARKING STALLS, TRAFFIC LANES, AND NO PARKING AREAS. YELLOW PAINT MARKINGS SHALL ALSO BE PROVIDED FOR H.C. ACCESSIBLE SYMBOLS, TRAFFIC ARROWS, AND TRAFFIC MESSAGES.

#### 32 30 00 LANDSCAPING AND SITE STABILIZATION

- A. TOPSOIL: CONTRACTOR TO PROVIDE A MINIMUM OF 6" OF TOPSOIL FOR ALL DISTURBED OPEN AREAS, OTHER THAN A LANDSCAPE ISLANDS SHALL BE PROVIDED WITH A MINIMUM OF 10" OF TOPSOIL. REUSE SURFACE SOIL STOCKPILED ON SITE AND SUPPLEMENT WITH IMPORTED OR MANUFACTURED TOPSOIL FROM OFF SITE SOURCES WHEN QUANTITIES ARE INSUFFICIENT. EXCAVATOR SHALL BE RESPONSIBLE FOR ROUGH PLACEMENT OF TOPSOIL TO WITHIN 1" OF FINAL GRADE PRIOR TO LANDSCAPER FINAL GRADING. LANDSCAPER TO PROVIDE PULVERIZING AND FINAL GRADING OF TOPSOIL. PROVIDE SOIL ANALYSIS BY A QUALIFIED SOIL TESTING LABORATORY AS REQUIRED TO VERIFY THE SUITABILITY OF SOIL TO BE USED AS TOPSOIL AND TO DETERMINE THE NECESSARY SOIL AMENDMENTS. TEST SOIL FOR PRESENCE OF ATRAZINE AND INFORM EXCEL ENGINEERING, INC. IF PRESENT PRIOR TO BIDDING PROJECT. TOPSOIL SHALL HAVE A PH RANGE OF 5.5 TO 8, CONTAIN A MINIMUM OF 5 PERCENT ORGANIC MATERIAL CONTENT, AND SHALL BE FREE OF STONES 1 INCH OR
- A PH RANGE OF 5.5 TO 8, CONTAIN A MINIMUM OF 5 PERCENT ORGANIC MATERIAL CONTENT, AND SHALL BE FREE OF STONES 1 INCH OR LARGER IN DIAMETER. ALL MATERIALS HARMFUL TO PLANT GROWTH SHALL ALSO BE REMOVED.

  TOPSOIL INSTALLATION: LOOSEN SUBGRADE TO A MINIMUM DEPTH OF 6 INCHES AND REMOVE STONES LARGER THAN 1" IN DIAMETER. ALSO REMOVE ANY STICKS, ROOTS, RUBBISH, AND OTHER EXTRANEOUS MATTER AND DISPOSE OF THEM OFF THE PROPERTY. SPREAD TOPSOIL TO A DEPTH OF 6" BUT NOT LESS THAN WHAT IS REQUIRED TO MEET FINISHED GRADES AFTER LIGHT ROLLING AND NATURAL

SETTLEMENT. DO NOT SPREAD TOPSOIL IF SUBGRADE IS FROZEN, MUDDY, OR EXCESSIVELY WET. GRADE PLANTING AREAS TO A SMOOTH,

- UNIFORM SURFACE PLANE WITH LOOSE, UNIFORMLY FINE TEXTURE. GRADE TO WITHIN 0.05 FEET OF FINISHED GRADE ELEVATION.

  B. SEEDED LAWNS:
- 1. PERMANENT LAWN AREAS SHALL BE SEEDED WITH THE FOLLOWING MIXTURE: 65% KENTUCKY BLUEGRASS BLEND (2.0-2.6 LBS./1,000 S.F.), 20% PERENNIAL RYEGRASS (0.6-0.8 LBS./1,000 S.F.), 15% FINE FESCUE (0.4-0.6 LBS/1,000 S.F.). STRAW AND MULCH SHALL BE LAID AT 100LBS/1,000 S.F. FERTILIZE AS PER SOIL TEST OR APPLY 5-10-10 OR EQUIVALENT AT 5-6 LBS/1,000 S.F. SEE EROSION MATTING SPECIFICATIONS AS REQUIRED. ALL SITE DISTURBED AREAS NOT DESIGNATED FOR OTHER LANDSCAPING AND SITE STABILIZATION METHODS SHALL BE SEEDED AS PERMANENT LAWN. NO BARE TOPSOIL SHALL BE LEFT ONSITE. FOLLOW PROCEDURES FOUND IN WDNR TECHNICAL STANDARDS 1058 & 1059.
- 2. ALL PERMANENT AND TEMPORARY STORM WATER CONVEYANCE SWALE BOTTOMS AND SIDE SLOPES SHALL BE SEEDED WITH THE FOLLOWING MIXTURE: 45% KENTUCKY BLUEGRASS (0.60 LBS./1000 S.F.), 40% CREEPING RED FESCUE (0.50 LBS./1,000 S.F.), AND 15% PERENNIAL RYEGRASS (0.20 LBS./1,000 S.F.). FERTILIZE AS PER SOIL TEST OR APPLY 5-10-10 OR EQUIVALENT AT 5-6 LBS./1,000 S.F. SEE
- EROSION MATTING SPECIFICATIONS AS REQUIRED. FOLLOW PROCEDURES FOUND IN WDNR TECHNICAL STANDARDS 1058 & 1059.

  3. ALL TEMPORARY SEEDING SHALL CONSIST OF THE FOLLOWING MIXTURE: 100% RYEGRASS AT 1.9 LBS./1,000 S.F. STRAW AND MULCH SHALL BE LAID AT 100 LBS./1,000 S.F. FERTILIZE AS PER SOIL TEST OR APPLY 5-10-10 OR EQUIVALENT AT 5-6 LBS./1,000 S.F. SEE EROSION MATTING SPECIFICATIONS AS REQUIRED. FOLLOW PROCEDURES FOUND IN WDNR TECHNICAL STANDARDS 1058 & 1059.
- C. SEEDED LAWN MAINTENANCE: CONTRACTOR TO PROVIDE MAINTENANCE OF ALL LANDSCAPING FOR A PERIOD OF 90 DAYS FROM THE DATE OF INSTALLATION. AT THE END OF THE MAINTENANCE PERIOD, A HEALTHY, UNIFORM, CLOSE STAND OF GRASS SHOULD BE ESTABLISHED FREE OF WEEDS AND SURFACE IRREGULARITIES. LAWN COVERAGE SHOULD EXCEED 90% AND BARE SPOTS SHOULD NOT EXCEED 5"X5". CONTRACTOR SHOULD REESTABLISH LAWNS THAT DO NOT COMPLY WITH THESE REQUIREMENTS AND CONTINUE
- EXCEED 5"X5". CONTRACTOR SHOULD REESTABLISH LAWNS THAT DO NOT COMPLY WITH TH MAINTENANCE UNTIL LAWNS ARE SATISFACTORY.

  D. EROSION MATTING:
- CONTRACTOR TO PROVIDE EROSION CONTROL MATTING (NORTH AMERICAN GREEN \$150) OR EQUIVALENT ON ALL SLOPES THAT ARE
  4:1 AND GREATER. LAWN SEED SHALL BE PLACED <u>BELOW</u> MATTING IN ACCORDANCE WITH SEEDING REQUIREMENTS AND
  MANUFACTURER SPECIFICATIONS.
- 2. CONTRACTOR TO PROVIDE EROSION MATTING (NORTH AMERICAN GREEN C125) OR EQUIVALENT IN ALL SWALE BOTTOMS AND SIDE SLOPES AS REQUIRED. LAWN SEED SHALL BE PLACED <u>BELOW</u> MATTING IN ACCORDANCE WITH SEEDING REQUIREMENTS AND MANUFACTURER SPECIFICATIONS
- E. SODDED LAWNS: PROVIDE SOD CONSISTING OF THE FOLLOWING GRASS SPECIES 65% KENTUCKY BLUEGRASS, 20% PERENNIAL RYEGRASS, 15% FINE FESCUE. PROVIDE VIABLE SOD OF UNIFORM DENSITY, COLOR, AND TEXTURE. SOD SHOULD BE STRONGLY ROOTED AND CAPABLE OF VIGOROUS GROWTH AND DEVELOPMENT WHEN PLANTED. LAY SOD WITHIN 24 HOURS OF HARVESTING. DO NOT LAY SOD IF DORMANT OR IF GROUND IS FROZEN OR MUDDY. LAY SOD WITH TIGHTLY FITTED BUTT END AND SIDE JOINTS. DO NOT STRETCH OR OVERLAP. STAGGER SOD STRIPS TO OFFSET JOINTS IN ADJACENT COURSES. TAMP AND ROLL LIGHTLY TO ENSURE CONTACT WITH TOPSOIL. ANCHOR SOD ON SLOPES EXCEEDING 6:1 SLOPE. PROVIDE SLOW RELEASE FERTILIZER AS RECOMMENDED BY SOD SUPPLIER FOR
- PROPER LAWN ESTABLISHMENT. SATURATE WITH FINE WATER SPRAY WITHIN 2 HOURS OF PLANTING.

  F. SODDED LAWN MAINTENANCE: CONTRACTOR TO PROVIDE MAINTENANCE FOR ALL SODDED AREAS FOR A PERIOD OF 90 DAYS FROM THE DATE OF INSTALLATION. AT THE END OF THE MAINTENANCE PERIOD, A HEALTHY, WELL-ROOTED, EVEN-COLORED, VIABLE LAWN SHOULD BE ESTABLISHED. THE LAWN SHOULD BE FREE OF WEEDS, OPEN JOINTS, BARE AREAS, AND SURFACE IRREGULARITIES. REESTABLISH LAWNS THAT DO NOT COMPLY WITH THESE REQUIREMENTS AND CONTINUE MAINTENANCE UNTIL LAWNS ARE SATISFACTORY.
- G. TREES AND SHRUBS: FURNISH NURSERY-GROWN TREES AND SHRUBS WITH HEALTHY ROOT SYSTEMS DEVELOPED BY TRANSPLANTING OR ROOT PRUNING. PROVIDE WELL-SHAPED, FULLY BRANCHED, AND HEALTHY LOOKING STOCK. STOCK SHOULD ALSO BE FREE OF DISEASE, INSECTS, EGGS, LARVAE, AND DEFECTS SUCH AS KNOTS, SUN SCALD, INJURIES, ABRASIONS, AND DISFIGUREMENT. SEE THE LANDSCAPE PLAN FOR SPECIFIC SPECIE TYPE, SIZE, AND LOCATION.
- H. TREE AND SHRUB INSTALLATION: EXCAVATE CIRCULAR PITS WITH SIDES SLOPED INWARD. TRIM BASE LEAVING CENTER AREA RAISED SLIGHTLY TO SUPPORT ROOT BALL. EXCAVATE PIT APPROXIMATELY THREE TIMES AS WIDE AS THE ROOT BALL DIAMETER. SET TREES AND SHRUBS PLUMB AND IN CENTER OF PIT WITH TOP OF BALL 1" ABOVE ADJACENT FINISHED GRADES. PLACE PLANTING SOIL MIX AROUND ROOT BALL IN LAYERS AND TAMP TO SETTLE MIX. WATER ALL PLANTS THOROUGHLY. PROVIDE TEMPORARY STAKING FOR TREES AS REQUIRED.
- TREE AND SHRUB MAINTENANCE/WARRANTY: CONTRACTOR TO PROVIDE MAINTENANCE OF ALL LANDSCAPING FOR A PERIOD OF 90 DAYS FROM THE DATE OF INSTALLATION. MAINTENANCE TO INCLUDE REGULAR WATERING AS REQUIRED FOR SUCCESSFUL PLANT ESTABLISHMENT. CONTRACTOR TO PROVIDE 1 YEAR WARRANTY ON ALL TREES, SHRUBS, AND PERENNIALS.
   J. ORGANIC MULCH: PROVIDE 3" MINIMUM THICK BLANKET OF SHREDDED HARDWOOD MULCH AT ALL PLANTING AREAS INDICATED ON
- THE LANDSCAPE PLAN. INSTALL OVER NON-WOVEN WEED BARRIER FABRIC. COLOR BY OWNER.

  K. MINERAL MULCH: PROVIDE 3" MINIMUM THICK BLANKET OF 1.5" MINIMUM TO 2.5" MAXIMUM CRUSHED DECORATIVE STONE AT ALL
- PLANTING AREAS INDICATED ON THE LANDSCAPE PLAN. INSTALL OVER NON-WOVEN WEED BARRIER FABRIC. COLOR BY OWNER.

  L. PLASTIC EDGING: INSTALL VALLEY VIEW INDUSTRIES BLACK DIAMOND LAWN EDGING TO SEPARATE ALL PLANTING BEDS FROM LAWN AREAS. EDGING TO BE 5.5" TALL WITH METAL STAKES INSTALLED PER MANUFACTURER'S WRITTEN INSTRUCTIONS.
- M. LANDSCAPE AND LAWN IRRIGATION: CONTRACTOR TO PROVIDE DESIGN AND INSTALLATION OF IRRIGATION SYSTEM PIPING, VALVES, VALVE BOXES, SPRINKLERS, EMITTERS, DRIP TUBES, AND CONTROLS IN COMBINATIONS THAT BEST SUIT THE LANDSCAPE PLAN LAYOUT. ALL LAWN AND LANDSCAPING AREAS SHALL BE PROVIDED WITH IRRIGATION AS DELINEATED ON THE PLAN. THE DESIGN SHOULD MINIMIZE THE AMOUNT OF WATER THAT EXTENDS BEYOND THE PROPERTY AND ON PAVED AREAS. THE SYSTEM SHALL BE DESIGNED FOR FULLY AUTOMATIC OPERATION AND PROVIDE ALL NECESSARY CONTROLS, VALVES, AND WIRING TO OPERATE THE SYSTEM. THE CONTROL UNIT SHALL BE INSTALLED IN A MECHANICAL ROOM OR AT A LOCATION AGREED TO WITH THE OWNER. THE CONTROL UNIT SHOULD BE PROVIDED WITH A LOCKING COVER.

#### **DIVISION 33 UTILITIES**

#### 33 10 00 SITE UTILITIES

- A. CONTRACTOR TO FIELD VERIFY ALL EXISTING UNDERGROUND UTILITIES ON SITE. CONTRACTOR TO VERIFY PIPE LOCATIONS, SIZES, AND DEPTHS AT POINT OF PROPOSED CONNECTIONS AND VERIFY PROPOSED UTILITY ROUTES ARE CLEAR (PER CODE) OF ALL EXISTING UTILITIES AND OTHER OBSTRUCTIONS PRIOR TO CONSTRUCTION. COSTS INCURRED FOR FAILURE TO DO SO SHALL BE THE CONTRACTORS
- B. CONTRACTOR TO FIELD TELEVISE ALL EXISTING SANITARY AND STORM LATERALS THAT ARE SCHEDULED TO BE RE-USED AND/OR CONNECTED TO ON SITE. THE TELEVISING SHALL BE COMPLETED TO ENSURE THE EXISTING LATERAL(S) ARE FREE OF OBSTRUCTIONS AND IN SOUND STRUCTURAL CONDITION. TELEVISING OF THESE LATERAL(S) SHOULD BE COMPLETED AT BEGINNING OF CONSTRUCTION AND DESIGN ENGINEER SHALL BE NOTIFIED OF ANY PIPE OBSTRUCTIONS AND/OR STRUCTURAL DEFICIENCIES IMMEDIATELY AFTER COMPLETION OF FIELD TELEVISING
- C. ALL SANITARY PIPE SHALL BE IN ACCORDANCE WITH MATERIALS SPECIFIED IN TABLE A: ALLOWABLE PIPE MATERIAL SCHEDULE. ALL SANITARY PIPE BELOW PROPOSED & FUTURE BUILDINGS SHALL BE IN ACCORDANCE WITH MATERIALS SPECIFIED IN TABLE A: ALLOWABLE PIPE MATERIAL. INSULATION SHALL BE PROVIDED PER STATE PLUMBING CODES AS NECESSARY BASED ON PROPOSED DEPTH PER PLANS.
- D. CLEANOUTS SHALL BE PROVIDED FOR THE SANITARY & STORM SERVICES AT LOCATIONS INDICATED ON THE UTILITY PLAN. THE CLEANOUT SHALL CONSIST OF A COMBINATION WYE FITTING IN LINE WITH THE SANITARY/STORM SERVICE WITH THE CLEANOUT LEG OF THE COMBINATION WYE FACING STRAIGHT UP. THE CLEANOUT SHALL CONSIST OF A (4" OR 6") VERTICAL PVC PIPE WITH A WATER TIGHT REMOVABLE CLEANOUT PLUG. AN 8" PVC FROST SLEEVE SHALL BE PROVIDED. THE BOTTOM OF THE FROST SLEEVE SHALL TERMINATE 12" ABOVE THE TOP OF THE SANITARY LATERAL OR AT LEAST 6" BELOW THE PREDICTED FROST DEPTH, WHICHEVER IS SHALLOWER. THE CLEANOUT SHALL EXTEND JUST ABOVE THE SURFACE GRADE IN LAWN OR LANDSCAPE AREAS WITH THE FROST SLEEVE TERMINATING AT THE GRADE SURFACE. THE CLEANOUT SHALL EXTEND TO 4 INCHES BELOW SURFACE GRADE IN PAVED SURFACES WITH A ZURN (Z-1474-N) HEAVY DUTY CLEANOUT HOUSING PLACED OVER THE TOP OF THE CLEANOUT FLUSH WITH THE SURFACE GRADE. IN PAVED SURFACES, THE FROST SLEEVE SHALL TERMINATE IN A CONCRETE PAD AT LEAST 6" THICK AND EXTENDING AT LEAST 9" FROM THE SLEEVE ON ALL SIDES, SLOPING AWAY FROM THE SLEEVE. THE CLEANOUT HOUSING SHALL BE CONSTRUCTED PER MANUFACTURERS REQUIREMENTS.
- E. ALL PROPOSED WATER PIPE SHALL BE IN ACCORDANCE WITH MATERIALS SPECIFIED IN TABLE A: ALLOWABLE PIPE MATERIAL SCHEDULE. 6' MINIMUM COVER SHALL BE PROVIDED OVER ALL WATER PIPING UNLESS OTHERWISE SPECIFIED.
   F. ALL PROPOSED STORM PIPE SHALL BE IN ACCORDANCE WITH MATERIALS SPECIFIED IN TABLE A: ALLOWABLE PIPE MATERIAL SCHEDULE.
- F. ALL PROPOSED STORM PIPE SHALL BE IN ACCORDANCE WITH MATERIALS SPECIFIED IN TABLE A: ALLOWABLE PIPE MATERIAL SCHEDULE. ALL PROPOSED STORM PIPE BELOW BUILDINGS SHALL BE IN ACCORDANCE WITH MATERIALS SPECIFIED IN TABLE A: ALLOWABLE PIPE MATERIAL SCHEDULE. SEE UTILITY PLANS FOR ALL STORM PIPE MATERIAL TYPES TO BE USED. PIPE SHALL BE PLACED MIN. 8' HORIZONTALLY FROM FOUNDATION WALLS.
- G. SANITARY, STORM, AND WATER UTILITY PIPE INVERTS SHALL BE CONSTRUCTED WITHIN 0.10' OF DESIGN INVERT ELEVATIONS ASSUMING PIPE SLOPE AND SEPARATION IS MAINTAINED PER THE UTILITY DESIGN PLANS AND STATE REQUIREMENTS.
- H. SITE UTILITY CONTRACTOR SHALL RUN SANITARY SERVICE TO A POINT WHICH IS A MAXIMUM OF 5' FROM THE EXTERIOR WALL OF THE FOUNDATION. SITE UTILITY CONTRACTOR SHALL RUN STORM SEWER FOR INTERNALLY DRAINED BUILDINGS TO A POINT WHICH IS A MAXIMUM OF 5' FROM THE EXTERIOR WALL OF THE FOUNDATION. SITE UTILITY CONTRACTOR SHALL RUN DOWNSPOUT LEADS TO BUILDING FOUNDATION AND UP 6" ABOVE SURFACE GRADE FOR CONNECTION TO DOWNSPOUT FOR ALL DOWNSPOUT TO RISER (DSR) CONNECTIONS. DOWNSPOUTS TO GRADE (DSG) SHALL BE PROVIDED WITH SPLASH BLOCKS AT THE DISCHARGE LOCATION. ALL DOWNSPOUT LOCATIONS SHOULD BE VERIFIED WITH ARCHITECTURAL PLANS AND DOWNSPOUT CONTRACTOR/GC PRIOR TO INSTALLATION OF DOWNSPOUT LEADS. DOWNSPOUT LEADS SHALL NOT UNDERMINE BUILDING FOUNDATIONS. SITE UTILITY CONTRACTOR SHALL RUN WATER SERVICE TO A POINT WITHIN THE FOUNDATION SPECIFIED BY THE PLUMBING PLANS. CONTRACTOR TO CUT AND CAP WATER SERVICE 12" ABOVE FINISHED FLOOR ELEVATION.
- I. ALL UTILITIES SHALL BE INSTALLED WITH PLASTIC COATED TRACER WIRE (10 TO 14 GAUGE SOLID COPPER, OR COPPER COATED STEEL WIRE). PLASTIC WIRE MAY BE TAPED TO PLASTIC WATER OR SEWER PIPE. IF ATTACHED, THE TRACER WIRE SHALL BE SECURED EVERY 6 TO 20 FEET AND AT ALL BENDS. TRACER WIRE SHALL HAVE ACCESS POINTS AT LEAST EVERY 300 FEET. TRACER WIRE SHALL TERMINATE IN
- ACCORDANCE WITH MANUFACTURER SPECIFICATIONS AT GRADE OR IN TERMINATION BOX PER LOCAL/STATE REQUIREMENTS.

  J. ALL UTILITIES SHALL BE INSTALLED PER STATE, LOCAL, AND INDUSTRY STANDARDS. WATER, SANITARY, AND STORM SEWER SHALL BE INSTALLED PER "STANDARD SPECIFICATION FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN". THE EXCEL ENGINEERING DESIGN ENGINEER SHALL BE RESPONSIBLE FOR OBTAINING STATE PLUMBING REVIEW APPROVAL (IF REQUIRED). THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL OTHER PERMITS REQUIRED TO INSTALL WATER, SANITARY AND STORM SEWER.

**SHOP DRAWING SUBMITTALS** 

31.10.00 - TELEVISING REPORTS OF EXISTING LATERALS

32.10.00 (A) - AGGREGATE BASE & ASPHALT PAVEMENT

HOT MIX ASPHALT SPECIFICATIONS

32.20.00-CONCRETE AND AGGREGATE BASE

COMPRESSION TEST RESULTS

DETECTABLE WARNING PLATES

SANITARY & STORM MANHOLES

GREASE INTERCEPTOR SHOP DRAWINGS

CIVIL SPECIFICATIONS

WATER FITTINGS & APPURTENANCES

SANITARY PIPING MATERIALS

WATER PIPING MATERIALS

STORM PIPING MATERIALS

**MATERIAL / INFORMATION** 

STORM

SANITARY

AGGREGATE BASE

AGGREGATE BASE

33.10.00 - SITE UTILITIES

• SITE LIGHTING

DESIGN MIX

PAVEMENT MARKINGS

K. SEE PLANS FOR ALL OTHER UTILITY SPECIFICATIONS AND DETAILS.



Always a Better Plan

100 Camelot Drive Fond du Lac, WI 54935 920-926-9800 excelengineer.com

PROJECT INFORMATION

SIFIC BELLS LLC
GTON STREET • TWO RIVERS, WI 542


PROFESSIONAL SEAL


DEC. 20, 2024

**10В NUMBER** 240331100

CO.2

Table A: Allowable Pipe Material Schedule **Fitting Code Joint Code** Comments ASTM B32 AWS A5.8 BCuP Silver | <2", No Joints below Building Type K Copper-Soft ASTM B-88 ASTM B16.22, ASTM B16.29 Water Lateral ≤ 4", DR11 (200 psi), SDR 9 (250 ASTM D2609, ASTM D2683, Heat fusion: ASTM D2657 Water Lateral C901/906 PE AWWA C901/C906 Mechanical push-on and **ASTM D3261** compression joints allowed per DSPS plumbing code. Push On: ASTM D3212 for ASTM D1785, ASTM D2665, ASTM Sanitary Sewer SDR 35 PVC ASTM F1336 '-15", ≤ 20' deep D3034, ASTM F891 Elastomeric Gasket: ASTM F477 Push On: ASTM D3212 for ASTM D1785, ASTM D2665, ASTM **ASTM F1336** 4"-15", ≤ 20' deep Storm Sewer SDR 35 PVC Tightness D3034. ASTM F891 Elastomeric Seal: ASTM F477







NEW BUILDING FOR:

PACIFIC BELLS LLC

1803 WASHINGTON STREET • TWO RIVERS, WI 54241

PRELIMINARY DATES	
DEC. 20, 2024	NOT FOR CONSTRUCTION

240331100

C1.0

#### GENERAL NOTES:

CONTRACTOR TO PROVIDE ENGINEER WITH FINAL JOINTING PLAN PRIOR TO CONSTRUCTION.

PROPERTY AREA: 27,152 S.F. (0.63 ACRES).

#### SITE INFORMATION:

EXISTING ZONING: B-1 BUSINESS

PROPOSED ZONING: B-1 BUSINESS

PROPOSED USE: RESTAURANT WITH DRIVE-THRU

AREA OF SITE DISTURBANCE: 19,946 S.F. (0.45 ACRES)

SETBACKS: BUILDING: FRONT (WEST) = 0' SIDE (NORTH) = 0' REAR (EAST) = 20'

> **BUFFER YARD:** STREET FRONTAGE (S/W) = 5' INTERIOR LOT LINE (N/E) = 5'

STREET (SOUTH) = 0'

(MAX. HEIGHT ALLOWED: 75')

PARKING REQUIRED: 1 SPACE PER EACH VEHICLE CONNECTED WITH THE BUSINESS, 1 SPACE FOR OWNER OR MANAGER, 1 SPACE FOR EACH 2 EMPLOYEES ON DUTY WHEN FULLY STAFFED (5 SPACES FOR EMPLOYEES/MANAGER PLUS 13 FOR CUSTOMERS=18 REQ.)

PARKING PROVIDED: 18 SPACES (1 H.C. ACCESSIBLE)

HANDICAP STALLS REQUIRED: 1, HANDICAP STALLS PROVIDED: 1


KEYNOT	<u>ES</u>
1	CONCRETE STOOP (SEE STRUCTURAL PLANS FOR DETAILS)
2	RAISED WALK (SEE DETAIL)
6	ADA CURB RAMP (SEE DETAIL)
7	18" CURB & GUTTER (SEE DETAIL)
(11)	CONCRETE TRANSFORMER PAD BY UTILITY SUPPLIER (CONTRACTOR TO VERIFY FINAL LOCATION & DESIGN PRIOR TO CONSTRUCTION)
12	HANDICAP SIGN PER STATE CODE (SEE DETAIL)
13	HANDICAP STALL & STRIPING PER STATE CODES
15	REBRAND EXISITNG MONUMENT SIGN (DETAILS, FINAL LOCATION, & APPROVAL BY SIGN VENDOR)
16	DUMPSTER ENCLOSURE (SEE ARCH PLANS FOR DETAILS)
21	DETECTABLE WARNING PLATE PER STATE CODE
22	TRAFFIC FLOW ARROWS (TYP). COLOR TO MATCH PARKING STALL STRIPING
24	MENU BOARD AND CANOPY. DETAIL BY SUPPLIER.
26	12'X 30' LOADING ZONE

	- Area (AC)	AREA (SF)	RATIC
BUILDING FLOOR AREA	0.14	5,972	22.0%
PAVEMENT (ASP. & CONC.)	0.45	19,486	71.8%
TOTAL IMPERVIOUS	0.58	25,458	93.8%
LANDSCAPE/ OPEN SPACE	0.04	1,694	6.2%
PROJECT SITE	0.62	27,152	100.0%
PROPOSED SITE DA	<u>TA</u>		
PROPOSED SITE DA	TA  AREA (AC)	AREA (SF)	RATIC
PROPOSED SITE DA		AREA (SF) 2,239	RATIC 8.2%
	AREA (AC)	, ,	
BUILDING FLOOR AREA	AREA (AC) 0.05	2,239	8.2%
BUILDING FLOOR AREA PAVEMENT (ASP. & CONC.)	AREA (AC) 0.05 0.40	2,239 17,306	8.2% 63.7%

SCALE: 1"= 20'

PAVEMENT SECTION
STANDARD ASPHALT
HEAVY DUTY ASPHALT
SIDEWALK CONCRETE
HEAVY DUTY CONCRETE
DUMPSTER PAD CONCRETE

CIVIL SITE PLAN




240331100

PROFESSIONAL SEAL

PRELIMINARY DATES


DEC. 9, 2024 DEC. 20, 2024

SHEET NUMBER










#### GENERAL NOTES:

- HANDICAP STALL AND ACCESS AISLES SHALL NOT EXCEED A SLOPE OF 1.50% IN ANY DIRECTION. HANDICAP STALL & ACCESS AISLES SHALL CONFORM TO ADA REQUIREMENTS (CURRENT EDITION)
- ALL SIDEWALKS SHALL NOT EXCEED A MAXIMUM CROSS SLOPE OF 1.50% AND RUNNING SLOPE OF 4.50% UNLESS OTHERWISE SPECIFIED
- CONTRACTOR SHALL PROVIDE STABILIZED CONSTRUCTION ENTRANCE AT CONSTRUCTION ENTRANCE FOR PROPOSED IMPROVEMENTS AS REQUIRED PER CODE.
- CONTRACTOR SHALL PROVIDE CONCRETE WASHOUT AS REQUIRED PER CODE. FINAL LOCATION TBD BY CONTRACTOR.
- CONTRACTOR SHALL PROVIDE TEMPORARY INLET PROTECTION FOR ALL CURB INLETS & CATCH BASINS ONSITE & OFFSITE IMMEDIATELY DOWNSTREAM OF THE PROJECT SITE PER LOCAL CODE.








PRELIMINARY DATES	
DEC. 20, 2024	NOT FOR CONSTRUCTION

ов NUMBER 240331100



SCALE: 1"= 20'





PROJECT INFORMATION

NEW BUILDING FOR:

PACIFIC BELLS LLC

1803 WASHINGTON STREET • TWO RIVERS, WI 54241


PROFESSIONAL SEAL

240331100

SCALE: 1"= 20'

CIVIL UTILITY PLAN

C1.3





			I	DIANITED	
SYMBOL	COMMON NAME	BOTANICAL NAME	QUANTITY	PLANTED SIZE	RC
		DECIDUOUS TREES			
$\otimes$	Lancelot Crabapple	Malux 'Lanzam'	1	5 GAL.	CC
		EXISTING SHRUBS			
0	Existing Vegetation to Remain		45		
		DECIDUOUS SHRUBS			
	Goldmound Spirea	Spiraea x bumalda 'Goldmound'	8	18" HT.	С
		<u>PERENNIALS</u>			
	Happy Returns Daylily	Hemerocallis 'Happy Returns'	14	1 GAL.	
**		Salvia officinalis	11	1 GAL.	
<b>O</b>	Garden Sage	Salvia Officinalis			

	LANDSCAPING CAL	CULATIONS
ZONE	REQ. PLANTS	PLANTS PROVIDED
	8,808 SF OF PARKING AREA / 18 TOTAL SPACES - INTERIOR LANDSCAPING SHALL BE AT LEAST 4% OF THE TOTAL SURFACE PARKING AREA - 1 TREE PER 10 PARKING SPACES	DDO/ADED, FOO SE EVISTING / E4 SE DDODOSED . C41 SE
NTERIOR LANDSCAPING		PROVIDED: 590 SF EXISTING / 51 SF PROPOSED = 641 SF 1 EXISTING / 1 PROPOSED TREE = 2 TREES

### GENERAL NOTES:

- PROTECT ALL EXISTING VEGETATION TO REMAIN SHOWN ON PLAN AND REPLACE IN KIND IF DAMAGED OR REMOVED.
- AREAS OF SOD SHOWN ALONG OUTER DRIVE AISLE ARE <u>ESTIMATED</u>
   BASED ON PROPOSED DEMOLITION AREAS. REPLACE DISTURBED
   LAWN AREA WITH SOD AS NEEDED.





EXCEL

Always a Better Plan

100 Camelot Drive
Fond du Lac, WI 54935
920-926-9800
excelengineer.com

PROJECT INFORMATION

NEW BUILDING FOR:

PACIFIC BELLS LLC
1803 WASHINGTON STREET • TWO RIVERS, WI 5424

PROFESSIONAL SEAL


PRELIMINARY DATES

OL SON CONSTRUCTION


**10В NUMBER** 240331100

SHEET NUMBER

C1.4



## RAISED WALK DETAIL NOT TO SCALE




NOTE:


- USE 4% GUTTER CROSS SLOPE UNLESS OTHERWISE NOTED IN THE PLANS.
   THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MIN. GUTTER THICKNESS IS
- MAINTAINED.

  3. SEE SITE PLAN & GRADING PLAN FOR INVERTED & SHEDDING CURB LOCATIONS


## 18" CONCRETE CURB & GUTTER DETAIL NOT TO SCALE



## **CURB CUT DETAIL**



HANDICAP SIGNAGE WITHOUT CONCRETE BASE DETAIL NOT TO SCALE



ADA SIDEWALK RAMP DETAIL

NOT TO SCALE

CIVIL DETAILS



PROJECT INFORMATION


1803 WASHINGTON STREET


PROFESSIONAL SEAL

PRELIMINARY DATES DEC. 20, 2024 JOB NUMBER

SHEET NUMBER


240331100





### DITCH CHECK, MATERIAL STAKES, PER ENTRENCH PRODUCTS 2 INCHES IN DISTURBED FROM WISDOT EROSION MANUFACTURER'S GROUND. NO ENTRENCHMENT REQUIRED ON VEGETATED OR FROZEN GROUND. PROVIDE THE INSTALLED DITCH CHECK HEIGHT. **ROCK BAG DITCH CHECK** PLACE ROCK BAGS TIGHTLY STAGGER JOINTS BETWEEN AGAINST EACH OTHER TO ADJACENT ROWS OF BAGS FILL BAGS WITH AGGREGATE CONFORMING PROVIDE BAGS MADE OF TO THE FOLLOWING GRADATION (WISDO NO. 1 COARSE AGGREGATE) BAGS SHALL HAVE A MINIMUM PERCENT PASSING IN-PLACE FILLED SIZE OF 18 INCHES LONG BY 12 INCHES BY WEIGHT WIDE BY 6 INCHES HIGH


NOTE: ADDITIONAL POST DEPTH OR TIE BACKS



Vertical spacing along slope varies between 8 and 20 feet, or for every 2 (two) vertical feet of drop in elevation of

slope.

## STORM CURB INLET W/ ROUND STRUCTURE DETAIL



NOT TO SCALE




FIGURE 1. INLET PROTECTION TYPES A, B AND C - TYPE FF GEOTEXTILE FABRIC (EXTEND FABRIC A MINIMUM OF 6" AROUND GRATE PERIMETER FOR MAINTENANCE OR REMOVAL) - WOOD 2" x 4" EXTENDS 8" BEYOND FABRIC WIDTH ON BOTH SIDES, SECURE TO GRATE w/ PLASTIC OR WIRE TIES - INLET WITH OR WITHOUT GRATE **INLET PROTECTION** TYPE A FLAP POCKET PLAN VIEW INLET PROTECTION TYPE C WITH CURB BOX TYPE C WITH CURB BOX MAINTENANCE NOTES: FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2" x 4".
THE REBAR, STEEL PIPE, OR WOOD SHALL BE INSTALLED IN THE REAR . WHEN REMOVING OR MAINTAINING INLET PROTECTION, CARE SHALL BE TAKEN SO THAT THE SEDIMENT TRAPPED IN THE FABRIC DOES NOT

FALL INTO THE STRUCTURE. MATERIAL THAT HAS FALLEN INTO THE

INLET SHALL BE IMMEDIATELY REMOVED.

TYPICAL FIBER ROLL INSTALLATION

N.T.S.

INLET PROTECTION DETAIL

**SHEET NUMBER** TECHNICAL STANDARD No. 12/2021 REVISION DATE NOT TO SCALE CIVIL DETAILS

Always a Better Plan

100 Camelot Drive Fond du Lac, WI 54935

920-926-9800

excelengineer.com

1803

PROFESSIONAL SEAL

PRELIMINARY DATES

DEC. 20, 2024

**JOB NUMBER** 

240331100

PROJECT INFORMATION

Install fiber roll

along a level contour.

Install a fiber roll near

slope where it transitions into a steeper slope


DITCH CHECK DETAIL

LOG-TYPE DITCH CHECK

INSTALL IN ACCORDANCE WITH

WDNR TECHNICAL STANDARD 1056

FLAP AND SHALL NOT BLOCK THE TOP HALF OF THE CURB FACE



Installation

A single fastener secures the hinged door,

underneath the housing and provides

Included terminal block accepts up to 12 ga.

 Utilizes LSI's traditional 3" drill pattern B3 for easy fastening of LSI products. (See

LSI LED Fixtures carry a 5-year warranty.

Listed to UL 1598 and UL 8750.
Meets Buy American Act requirements.

• IP66 rated Luminaire per IEC 60598.

Title 24 Compliant; see local ordinance for

• 3G rated for ANSI C136.31 high vibration

product. Not all versions of this product may be DLC qualified. Please check the DLC

• DesignLights Consortium\* (DLC) qualified

Qualified Products List at www.designlights. org/QPL to confirm which versions are

qualified.

• Patented Silicone Optics (US Patent NO.

IK08 rated luminiare per IEC 66262

Specifications and dimensions subject to

Page 1/9 Rev. 09/08/21 SPEC.1045.A.0620

mechanical impact code

• IDA compliant; with 3000K color

temperature selection.

qualification information.

Suitable for wet Locations.

applications are qualified.

10,816,165 B2)


escription Symbol Avg Max Min Max/Min Avg/Mi Calc Zone #2 + 0.8 fc 4.0 fc 0.0 fc N/A N/A


quick & easy access to the electrical

drawing on page 9)

poles.










PROJECT INFORMATION S. **NEW BUILDING** Ш 8 PA WASHI PROFESSIONAL SEAL

> PRELIMINARY DATES DEC. 20, 2024

JOB NUMBER 240331100

SHEET NUMBER





Fond du Lac, WI 54935 920-926-9800 excelengineer.com

**PROJECT INFORMATION** 

PROFESSIONAL SEAL

PRELIMINARY DATES

DEC. 20, 2024

## EQUIPMENT AND SEATING PLAN 1/4" = 1'-0"

229 ELECTRICAL PANELS. 240 FUTURE I-LINE FLEX.

251 HOOD FIRE SUPPRESSION SYSTEM (ANSUL R-102 OR EQUAL). MAINTAIN 36" MIN. CLEAR ACCESSIBLE AISLE EGRESS PATHS TO EXIT

DOORS, 32" AT DOORWAYS AND CASED OPENINGS. (42" AISLE REQUIRED

WHEN AISLE SERVES MORE THAN 50 SEATS).

255 ALERT LIGHT BOX FOR 3-COMP POWER SOAK.

256 PULL STATION @ 3'-8" A.F.F. COORDINATE LOCATION OF HORIZONTAL PVC SYRUP CHASE THRU WALL TO

6" HIGH WATER HEATER PLATFORM. ROOF LADDER WITH BILCO LADDER UP SAFETY POST.

SPLASH GUARD. AUTOMATIC HAND SOAP AND SANITIZER DISPENSERS PROVIDED BY ECOLAB.

GAS METER. FOR DUAL-FLEX LINE AND I-FLEX LINE SUB-EQUIPMENT SEE SHEET A8.3.

ELECTRICAL EQUIPMENT. SEE ELECTRICAL DRAWINGS. WALL MOUNTED 32" MANAGER MONITOR. PROVIDE POWER AND DATA.

**SHEET NUMBER** 

**JOB NUMBER** 

240331100

TAG	QTY	ITEM DESCRIPTION
D-688	1	COUNTER MOUNT MOBILE SHELVING
D-690	1	SERVICE COUNTER
D-700	11	28.5" H CORE DRILL TABLE BASE
T-201e	6	BARREL BARSTOOL - 29 PURPLE WOOD SEAT
T-302be	2	BENCH BACK REST - 48"
T-302e	2	BENCH SEAT - 48"
T-303be	1	BENCH BACK REST - 60"
T-303e	1	BENCH SEAT - 60"
T-401e	1	HUB TABLE - 72" - HIGH TOP
T-402e	1	HUB TABLE - 48" - ADA
T-405e	4	LAMINATE TABLE - 24 X 20 X 30 - 2 TOP
T-408e	3	LAMINATE TABLE ADA - 24 X 48 X 30 - 4 TOP
T-411e	2	SS TABLE - 24 DIA X 30 - 2 TOP
T-505e	1	COUNTER TOP - 48" X 20" X 30"
T-506e	1	COUNTER TOP - 60" X 20" X 30"
		+

1 CONDIMENT COUNTER - RECTANGLE

TAG	QTY	ITEM DESCRIPTION
T-706e	1	WASTE ENCLOSURE - SINGLE
T-708e	1	WASTE ENCLOSURE - 3 STREAM
T-801e	1	KIOSK 1/2 TOWER
T-901e	27	CHAIR - LAMINATE SEAT
T-905	1	POWER POLE

FURNITURE PACKAGE - BY FURNITURE VENDOR U.O.N.


	$\overline{}$	QTY.	NAME	FAMILY	FRAME OR MURAL	SIZE	LOCATION
	(G308)	1	CONCRETE GRAFFITI	С	M01	H6'-4" x W17'-6 1/2"	SEE A8.0
	(G266)	2	TACO TYPE	С	F01	28x40	SEE A8.0
	(G267)	1	TACO TYPE	С	F01	28x40	SEE A8.0
	G258	1	ANSWER IS TACOS	С	F01	28x40	SEE A8.0
	(G513)	2	CHALK BOARD GRAFFITI	С	M02	48x96	SEE A4.0 & A4.1
	(G514)	1	CHALK BOARD GRAFFITI	С	M02	48x96	SEE A4.0
	(G515)	1	CHALK BOARD GRAFFITI	С	M02	48x96	SEE A4.1

ARTWORK SCHEDULE (XXX)

	GENERAL NO	TES	C1
STORAGE TYPE		LINEA	AR FT.
DRY STORAGE		46	
COLD STORAGE		26	
FROZEN STORAGE		12	
SHI	ELVING QUANTI	TIES	C2

1. REFER TO SC SHEETS FOR SCOPE OF WORK RESPONSIBILITY

2. (HC)- SYMBOL DENOTES A HANDICAP ACCESSIBLE TABLE.



A. SEE SHEET A1.1 "WINDOW TYPES" FOR WINDOW ELEVATIONS.

C. APPLY NEOPRENE GASKET (CONT.) BETWEEN BUILDING AND CANOPY.

A. REQUIRED CLEAR OPENING WIDTH TO ENSURE COORDINATION WITH STANDARD SIGNAGE/BUILDING ELEMENTS DIMENSIONS.

A. SEALANT AT ALL WALL AND ROOF PENETRATIONS.
B. SEALANT AT ALL WINDOW AND DOOR FRAMES AND JAMB. DO NOT SEAL SILL @ WINDOWS.

NOTE: NO EXTERIOR SIGNS ARE WITHIN THE SCOPE OF WORK COVERED BY THE BUILDING PERMIT

DIMENSIONS, ELECTRICAL AND MUST PROVIDE ACCESS TO SITE AND BUILDING FOR FRANCHISEE'S

**GENERAL NOTES** 


C

APPLICATION. THE FRANCHISEE WILL COORDINATE THE SIGN INSTALLATION. THE GENERAL

CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING REQUIRED BLOCKING, PROPER

SEALERS (REFER TO SPECS)

SIGN INSTALLER.



**WALK UP ELEVATION** 1/4" = 1'-0"

APPLICATOR MUST DO THEIR DUE DILIGENCE WITH PREPARATION. PRIMER: 1 COAT SW A24W8300 FINISH: 2 COATS SW A82-100 SERIES, MATCH COLORS FROM MATERIAL SCHEDULE. A-100 EXTERIOR LATEX SATIN.

D

**PAINT NOTES** 

*MUST SELECT ONE COMPLE	TE OPTION FOR #1	THROUGH #4 AND II	NCLUDE LETTER IN S	YMROL TAG IF C	CHOOSING 'A' OR 'B

TYPE MARK

TOWER

V-04.42

SIDE ENTR'

V-200.EN

V-102.DT

V-202.EN

V-203.EN

V-201.EN

EYEBROW AWNINGS

DRIVE THRU

V-04.42

— CARLING TYPE EXTERNAL

DISCONNECT SWITCH

TRANSFORMER BOX TO

HOUSE POWER SUPPLY

∠ 1/2" X 6' LONG FLEXIBLE

POWER SUPPLY

LIQUID TITLE CONDUIT WHIP TO OWNER PROVIDED

**LED WALL WASHER DETAIL** 

V-09.14W

		*MUST SELECT ONE COMPLI	ETE OPTION FOR #1 THROUGH #4 AND INCLUD	E LETTER IN SYMBOL TAG IF CHOOSING 'A' OR	? 'B'				
SYMBOL	ITEM/MATERIAL	MANUFACTURER	MATERIAL SPEC	ALT. MANUFACTURER SPEC 'A'	ALT. MATERIAL SPEC 'A'	ALT. MANUFACTURER SPEC 'B'	ALT. MATERIAL SPEC 'B'	COLOR	CONTACT INFO
1	SIDING - HORIZONTAL APPLICATION	JAMES HARDIE	ARTISAN V-GROOVE 144"L X 8.25"W; 7" EXPOSURE COMES PRIMED FOR PAINT	WESTLAKE ROYAL BUILDING PRODUCTS	TruExterior V-RUSTIC 192"L x 7.5"W; 7" EXPOSURE; PRIMED FOR PAINT	NICHIHA	TruExterior V-RUSTIC 192"L x 7.5"W; 7" EXPOSURE; PRIMED FOR PAINT	WORLDLY GRAY (SW7043), SEMI-GLOSS	
2	BUILDING TRIM	JAMES HARDIE	HARDIE TRIM 5/4 SMOOTH; 1"x5.5" PRIMED FOR PAINT	WESTLAKE ROYAL BUILDING PRODUCTS	TruExterior TRIM 5/4 x 6; 1" x 5.5" PRIMED FOR PAINT	NICHIHA	TruExterior TRIM 5/4 x 6; 1" x 5.5" PRIMED FOR PAINT	CYBERSPACE (SW7076), SEMI-GLOSS	REFER TO EXTERIOR
3	REVEAL PANEL  **CONSULTANT TO REVISE REVEAL BREAKS FOR USING NICHIHA ILLUMINATION PANEL	JAMES HARDIE	HARDIE PANEL VERTICAL SIDING W/ ALUM TRIM FROM FRY REGLET AND/OR TAMLYN	N/A	USE HARDIE PANEL	NICHIHA	USE HARDIE PANEL	CYBERSPACE (SW7076), SEMI-GLOSS	FINISH VENDOR CONTACTS ON A7.2 FOR TACO BELL
4	REVEAL PANEL  **CONSULTANT TO REVISE REVEAL BREAKS FOR USING NICHIHA ILLUMINATION PANEL	JAMES HARDIE	HARDIE PANEL VERTICAL SIDING W/ ALUM TRIM FROM FRY REGLET AND/OR TAMLYN	N/A	USE HARDIE PANEL	NICHIHA	USE HARDIE PANEL	SW PURPLE (TB2603C), SEMI-GLOSS	NATIONAL ACCOUNT REPRESENTATIVES (DO NOT CALL
5	DRIVE THRU CORNER TOWER & ENTRY PORTAL RECESS	WESTERN STATES	T-GROOVE 24GA PAINTED 18" PANEL					WEATHERED RUSTIC	MANUFACTURER 1-800 OR GENERAL CONTACT
6	METAL PARAPET CAP		24GA GALVANIZED					CYBERSPACE (SW7076) KYNAR 500 COATING	NUMBERS AS YOU WILL NOT RECEIVE
7	HOLLOW METAL DOOR							SW PURPLE (TB2603C), SEMI-GLOSS	CORRECT INFORMATION TO BRAND SPECIFIED
8	NOT USED								PRODUCTS.
9	AWNINGS	BRAND APPROVED SIGNAGE VENDOR						BLACK (BY THE SIGNAGE VENDOR)	

ITEM DESCRIPTION

14" WHITE CHANNEL LETTERS VERTICAL

42" SWINGING BELL PURPLE LOGO FACE LIT

42" SWINGING BELL PURPLE LOGO FACE LIT

SIDE ENTRY AWNING 6' 2" X 3' 0" BLACK

DT AWNING (OVER DT) 9' 6" X 4' 0" BLACK

DT AWNING (OVER DT) 6' 0" X 4' 0" BLACK

FRONT EYEBROW (WINDOW) 12'-10" X 6" H X 1' 4" D BLACK

SIDE ENTRY EYEBROW (WINDOW) 8'-8" L 6" H X 1' 4" D BLACK A4.0

**SIGNAGE** 

DT EYEBROW (WINDOW) 7'-9" L X 6" H X 1' 4" D BLACK

A4.1

A4.1

A4.0

E

ALUMINUM TRIM PROFILES [ALTERNATE SOURCE]					
DESCRIPTION	ITEM ID - MANUFACTURER				
SURROUND J CHANNEL TRIM	T2 - FRY REGLET JMS - TAMLYN				
SURROUND VERTICAL TRIM	V2 - FRY REGLET W516RV - TAMLYN				
VENT SCREEN	VST38 - TAMLYN				
SURROUND HORIZONTAL TRIM	W2 - TAMLYN				
SURROUND DRAINAGE FLASHING	XWF - TAMLYN				
SURROUND OUTSIDE CORNER TRIM	OC9 - FRY REGLET XOCR516 - TAMLYN				
SURROUND INSIDE CORNER TRIM	IC1 or IC21 - FRY REGLET XIC516 - TAMLYN				

**EXTERIOR FINISH SCHEDULE** 

- 329 MECHANICAL UNIT, SEE ROOF PLAN.
- 401 BUILDING SIGN BY VENDOR. REQUIRES ELECTRICAL, SEE ELECTRICAL
- 407 METAL CANOPIES BY VENDOR. REQUIRES ELECTRICAL, SEE ELECTRICAL PLANS.
- 408 CO2 FILLER VALVE & COVER.
- 416 HOSE BIB BOX AT 18" A.F.F.
- 419 EXTERIOR LIGHT FIXTURE. SEE ELECTRICAL DRAWINGS. 422 PURPLE LIGHT WALL WASHER, PROVIDED BY SIGNAGE VENDOR.
- 424 LINE OF ROOF BEYOND.
- 425 SWITCH GEAR. WALL SHALL BE FINISHED PRIOR TO INSTALLATION.
- 426 OIL RECLAMATION PORT.

RELIMINARY DATES	
DEC. 20, 2024	$\overline{\sim}$
	_ 9
	<u> 5</u>
	- <b>3</b>
	CONSTRUCTIO
	$\mathcal{E}$
	OR
	7
	- 6
	- >

PROFESSIONAL SEAL

100 Camelot Drive

920-926-9800 excelengineer.com

**BE** 

PACIFIC F 1803 WASHINGTON STREE

**JOB NUMBER** 240331100

ET NUMBER

		SHE
KEY NOTES XXX	В	
EXTERIOR ELEVATIO	NS	

EXISTING WALL -

HORIZONTAL TRIM

#8 S.S.P.H. WOOD

SCREW @ 24" O.C.

.063" BRAKE FORMED

ALUM. LIGHT TRAY -

AGILIGHT ULTRA 650

PURPLE LED - (5) PER


WALL BUSTER FOR LED

WIRE PASS THRU -

2" 3/16 SPACER W/ 14"

AS REQUIRED -

DIAMETER HARDWARE



**FRONT ELEVATION** 1/4" = 1'-0" 2

SEE SHEET A4.0 FOR FINISH, ARTWORK AND SIGNAGE SCHEDULE

- MECHANICAL UNIT, SEE ROOF PLAN.
- BUILDING SIGN BY VENDOR. REQUIRES ELECTRICAL, SEE ELECTRICAL
- 402 DRIVE THRU WINDOW. SEE SHEET A1.0 AND A1.1.
- METAL CANOPIES BY VENDOR. REQUIRES ELECTRICAL, SEE
- ASSUME D/T LANE SURFACE IS 6" BELOW THE FINISH FLOOR. REFER TO GRADING & SITE PLAN.
- CONCRETE CURB.
- HOSE BIB BOX AT 18" A.F.F.
- EXTERIOR LIGHT FIXTURE. SEE ELECTRICAL DRAWINGS.
- 422 PURPLE LIGHT WALL WASHER, PROVIDED BY SIGNAGE VENDOR.
  - LINE OF ROOF BEYOND.
- ROOF OVERFLOW TO BE STUBBED INSIDE WALL DOWN TO 24" ABOVE DRIVE THRU LANE GRADE AND FINISHED WITH COWS TONGUE CAULKED TO EXTERIOR WALL SURFACE. SEE PLUMBING DRAWINGS.

Always a Better Plan

PROJECT INFORMATION

100 Camelot Drive Fond du Lac, WI 54935

920-926-9800

excelengineer.com


PROFESSIONAL SEAL


PRELIMINARY DATES DEC. 20, 2024

JOB NUMBER 240331100

SHEET NUMBER **A4.1** 


**EXTERIOR ELEVATIONS** 







**REAR ELEVATION** 1/4" = 1'-0" 3

**KEY NOTES** 







Always a Better Plan 100 Camelot Drive Fond du Lac, WI 54935

920-926-9800

excelengineer.com

PROJECT INFORMATION

803

PROFESSIONAL SEAL

**PRELIMINARY DATES** DEC. 20, 2024

**JOB NUMBER** 240331100

SHEET NUMBER

DUMPSTER ENCLOSURE LAYOUT 3/8" = 1'-0" A