

Latitude™ with ClimateFlex Technology™
Exterior Acrylic Latex — *Deliver stunning results while keeping projects on track all season long thanks to high-quality performance and weather-adaptive features.*



**Deliver
Stunning Results**

Durable finish protects against peeling, cracking and dirt pickup in extreme climates — to keep the finish looking fresh.



**Get a Premium Finish
in Fewer Coats**

Outstanding hide, coverage and block resistance make it easy to achieve a nearly flawless finish.



Avoid Weather Delays

Develops early moisture resistance in as little as 30 minutes — so you can paint with confidence even when rain or heavy dew is forecasted.



**Extend the
Painting Season**

Applies smoothly even when air, surface and material temperatures are as low as 35°F or as high as 120°F.

Latitude™

Exterior Acrylic Gloss

K64-650 Series



**SHERWIN
WILLIAMS.**

CHARACTERISTICS

Latitude™ Exterior Acrylic Gloss gives painters more flexibility in their schedules and extends the painting season. **Latitude** is formulated with ClimateFlex Technology™, providing exceptional early moisture resistance and smooth application and appearance at extreme temperatures (application at 35°F-120°F (1.7°C - 48.8°C) air, surface and material temperatures) and is resistant to early dirt pick up.

Latitude provides outstanding performance on properly prepared aluminum and vinyl siding, wood siding, clapboard, shakes, shingles, plywood, masonry, and metal.

Key Attributes and Benefits:

ClimateFlex Technology™
Excellent application, flow and leveling
Great dirt pick up resistance

VinylSafe™ paint colors allow you the freedom to choose from 100 color options, including a limited selection of darker colors formulated to resist warping and buckling when applied to a sound, stable vinyl substrate.

Color: Most Colors
Coverage: 350-400 sq. ft. per gallon
@ 4 mils wet, 1.4 mils dry

Drying Time, @ 50% RH:

	@35-45°F	@45°F+
Touch:	2 Hours	2 Hours
Recoat:	24-48 hours	4 Hours

Drying and recoat times are temperature, humidity, and film thickness dependent.

Finish: 35-45 units @ 60°

Tinting with CCE only:

Base:	oz. per gallon	Strength
Extra White*	0-7	SherColor
Super White	NO NOT TINT	
Deep Base	4-12	SherColor
Ultra Deep Base	10-12	SherColor
Vivid Yellow	0-10	SherColor
Real Red*	0-10	SherColor

*Extra White and Real Red bases may be used without the addition of CCR tint.

Extra White K64W00651
(may vary by color)

V.O.C.(less exempt solvents):

Less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids:	34 ±2%
Weight Solids:	46 ±2%
Weight per Gallon:	9.96 lbs
Flash Point:	N.A.
Vehicle Type:	100% Acrylic
Shelf Life:	36 months, unopened
WVP Perms (US)	34.91 grains/(hr ft ² in Hg)

Mildew Resistant

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

COMPLIANCE

As of 09/22/2022, Complies with :

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	N/A
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	No
MIR-Manufacturer Inventory	No
MPI®	Yes

APPLICATION

When the air temperature is at 35°F (1.7°C), substrates may be colder; prior to painting, check to be sure the air, surface, and material temperature are above 35°F (1.7°C) and at least 5°F above the dew point. Avoid using if rain or snow is expected within 30 minutes.

Do not apply at air or surface temperatures below 35°F (1.7°C) or when air or surface temperatures may drop below 35°F (1.7°C) within 48 hours.

No reduction needed.

Brush:

Use a nylon-polyester brush.

Roller:

Use a high quality 3/8-3/4 inch nap synthetic roller cover.

For specific brushes and rollers, please refer to our Brush and Roller Guide on sherwin-williams.com

Spray - Airless:

Pressure2000 p.s.i.
Tip0 15-.019 inch

APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

Thoroughly follow the recommended surface preparations. Most coating failures are due to inadequate surface preparation or application. Thorough surface preparation will help provide long term protection with **Latitude** coating.

SPECIFICATIONS

Latitude can be self-priming when used directly over existing coatings, or exterior bare drywall, plaster and masonry (with a cured pH of less than 9). The first coat acts like a coat of primer and the second coat provides the final appearance and performance. Please note that some specific surfaces require specialized treatment.

Use on these properly prepared surfaces:

Aluminum & Aluminum Siding¹, Galvanized Steel¹:
2 coats Latitude Exterior Acrylic

Concrete Block, CMU, Split face Block:
1 coat Loxon Acrylic Block Surfacers
2 coats Latitude Exterior Acrylic

Brick, Stucco, Cement, Concrete:

1 coat Loxon Concrete & Masonry Primer (if needed)
or
Loxon Conditioner (if needed)
2 coats Latitude Exterior Acrylic

Cement Composition Siding/Panels:

1 coat Loxon Concrete & Masonry Primer (if needed)
or
Loxon Conditioner (if needed)
2 coats Latitude Exterior Acrylic

Plywood:

1 coat Exterior Latex Primer
2 coats Latitude Exterior Acrylic

*Vinyl Siding:

2 coats Latitude Exterior Acrylic

Wood (Cedar, Redwood):

1 coat Exterior Oil-Based Wood Primer
2 coats Latitude Exterior Acrylic

Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of Exterior Oil-Based Wood Primer.

Wood Composition Board - Hardboard:

Because of the potential for wax bleeding out of the substrate, apply 1 coat of Exterior Oil-Based Wood Primer and then topcoat.

¹ On large expanses of metal siding, the air, surface, and material temperatures must be 50°F (10°) or higher. Standard latex primers cannot be used below 50°F (10°C) or above 100°F (37.7°C). See specific primer label for that product's application limitations.

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

Latitude™

Exterior Acrylic Gloss

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Aluminum and Galvanized Steel:

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method. On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.

Cement Composition Siding-Panels:

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 9, prime with Loxon Concrete & Masonry Primer. After power washing, previously painted masonry may still have a powdery surface that should be sealed with Loxon Conditioner.

Caulking:

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

Masonry, Concrete, Cement, Block:

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant. Concrete masonry units (CMU) - Surface should be thoroughly clean and dry. Air, material and surface temperatures must be at least 50°F (10°C) before filling. Use Loxon Acrylic Block Surfacer. The filler must be thoroughly dry before topcoating.

Previously Painted Surfaces:

Spot prime bare areas, wait 4 hours, and paint the entire surface. Some specific surfaces require specialized treatment.

SURFACE PREPARATION

Mildew:

Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised. Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts clean water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with clean water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

Wood:

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.

Steel:

Rust and mill scale must be removed using sandpaper, wire brush, or other abrading method. Bare steel must be primed the same day as cleaned.

Stucco:

Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

***Vinyl or other PVC Building Products:**

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, if needed prime with appropriate white primer. Do not paint vinyl with any color darker than the original color or having a Light Reflective Value (LRV) of less than 56 unless VinylSafe® Colors are used. If VinylSafe colors are not used the vinyl may warp. Follow all painting guidelines of the vinyl manufacturer when painting. Only paint properly installed vinyl siding. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.

CAUTIONS

For exterior use only.
Protect from freezing.
Non-Photochemically reactive.

Before using, carefully read **CAUTIONS on label**.

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 05/23/2022 K64W00651 04 31
FRC, SP

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm clean water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.