

Ε	FLOOR PLAN NOTES D	
		16 NOTE THIS IS A SHEAR WALL - TAKE INTO ACCOUNT PLYWOOD SUBSTRATE ALONG WITH FRAMING FOR FINISH WIDTH OF 6'-1" IN ALCOVE.
		15 CONCRETE CURB. SEE STRUCTURAL & CIVIL/SITE DRAWINGS.
	 D. SEE A7.1 FOR CEILING FINISHES. <u>GENERAL:</u> A. PROVIDE THREE FIRE EXTINGUISHERS - (2) 10 lb. BC and (1) 10 lb. ABC - TO COMPLY WITH LOCAL FIRE CODE. LOCATE PER DIRECTION OF FIRE MARSHALL OR LOCAL AUTHORIZING AGENT. B. DRAWINGS ARE BASED UPON WOOD FRAMING. UTILIZATION OF METAL STUDS ON NON-BEARING INTERIOR PARTITIONS, BULKHEADS AND SOFFITS IS ACCEPTABLE. 	14 CORNER GUARD TILE SCHLUTER. REFER TO DETAIL 15 & 17/A6.3.
		13 STAINLESS STEEL SPLASH GUARD. REFER TO DETAIL 9/A6.3
		12 LOW WALL BY G.C. COORDINATE REFER TO DETAIL 15/A6.5.
		11) FUR OUT WALL AS INDICATED WTH 2X4 WOOD STUDS AT 16" O.C.
	 B. SEE A7.0 FOR FLOOR FINISHES. C. SEE A8.0 - A8.3 FOR WALL FINISHES. 	10 NOT USED.
	DECOR: A. SEE A2.0 FOR SEATING PLAN AND DETAILS.	9 DOUBLE STUD WALL. SEE PARTITION TYPES FOR STUD SIZES.
	 B. ALL JOINTS, GAPS OR SPACES LEADING TO ALL HOLLOW OR INACCESSIBLE SPACES SHALL BE SEALED WITH "NSF INTERNATIONAL" APPROVED SEALANTS. C. ALL BACK OF HOUSE AND OFFICE WALLS SHALL HAVE 1/2" CDX PLYWOOD SUBSTRATE, U.O.N. 	8 ROOF LADDER SEE 4/A6.0 & 6/A8.3
		7 14"x14" HORIZONTAL OPENING FOR SYRUP TUBES. COORDINATE WALL PENETRATION WI INSTALLER. SEAL CHASE TO COUNTER. SEE 8/A6.4.
	A. PROVIDE 1/2" THICK CEMENTITIOUS BD. FROM FLOOR SLAB TO 12" A.F.F. MIN. IN LIEU OF GYP. BD. AT ALL WALLS EXCEPT SHEARWALL SURFACES. U.O.N.	
M. F	FINISH SUBSTRATES:	KITCHEN SIDE OF THE SERVICE COUNTER. SEE DETAIL 14/A6.3.
IEL	A. SEE SHT. A1.1 FOR WINDOW TYPES AND DOOR SCHEDULE. B. ALL DOOR AND WINDOW OPENING DIMENSIONS ARE TO ROUGH OPENING.	5 S.S. CORNER GUARD / WALL CAP [TM-2], TYP. ALL CORNERS IN BACK-OF-HOUSE FROM F
	WALL FRAMING. WINDOWS / DOORS:	(4) KEEP CLEAR FOR UTILITIES & SYRUP LINES. SEE DETAIL 7, 10 & 11/A6.4 FOR STUD LAYOU
	DIMENSIONS NOTED AS "CLEAR" OR "HOLD" ARE MIN. REQ'D. NET CLEARANCE FROM FACE OF WALL / WAINSCOT FINISH. VERIFY FINAL EQUIPMENT SIZES W/ VENDOR PRIOR TO INT. WALL FRAMING.	3 HOOD WALL, SEE WALL LEGEND.
	 ALL DIMENSIONS ARE TO FACE OF STOD 0.0.N. REFER TO FOUNDATION PLAN FOR FACE OF CONC. DIMENSIONS. B. DIMENSIONS NOTED AS "CLEAR" OR "HOLD" ARE MIN. REQ'D. NET CLEARANCE FROM FACE 	2 PIPE BOLLARD. SEE DETAIL CIVIL DWGS.
1	DIMENSIONS: A. ALL DIMENSIONS ARE TO FACE OF STUD U.O.N. REFER TO FOUNDATION PLAN FOR FACE	1 NO FRP BEHIND (W-059) WALK-IN COOLER/FREEZER.