



SEE GENERAL FOUNDATION NOTE #7 ON S1  
FOR TYPICAL WALL REINFORCING, #11 FOR  
TYPICAL FOOTING REINFORCEMENT, AND #15  
FOR ANCHOR BOLT SIZE AND SPACING (NOTE:  
5/8" Ø ANCHOR BOLTS REQUIRED DUE TO 10'  
FOUNDATION WALL HEIGHT).

FOUNDATION WALLS 8" THICK (UNO).



FOUNDATION PLAN  
1/4"SCALE

Kara Carlson  
KaraCarchitect@gmail.com 913-908-8398



**NOTICE DUTY OF COOPERATION**  
Release of these plans requires further cooperation among the owner, the contractor, and the designer. Design and construction are complex. Although the designer and their consultants have performed their services with due care and diligence, they can not guarantee perfection. Communication is imperfect and every contingency cannot be anticipated. Any ambiguity or discrepancy discovered by the use of these plans shall be reported immediately to the designer. A failure to cooperate by a simple notice to the designer shall relieve the designer from responsibility for all consequences. Changes made from the plan without the consent of the designer are unauthorized, and shall relieve the designer of responsibility for all consequences arising out of such changes. Contractor shall check and verify all dimensions.

NEW HOME  
KEI & KRISTIN KAMARA  
4810 BELINDER CT  
WESTWOOD, KS

REVISIONS		
DATE	DESCRIPTION	
2-10-25	BEDROOM 1, BATHROOM 1, CLOSET 1, LAUNDRY, EAVES, ROOF, SECOND FLOOR BATHS	

DATE: December 23, 2024  
Foundation Plan

A2