



Utility Tractors & Mowers - 062117  
 CE and AG - 040319  
 Utility Vehicles 122220  
 NIPA Arkansas 4600041718  
 NIPA Delaware GSS-17673  
 Nebraska 14777 (OC)  
 Mississippi (CE Only) 820036654  
 Mississippi 8200055841

SSV65PHFC WEB QUOTE #2031000  
 Date: 5/20/2021 7:03:07 AM  
 - Customer Information -  
 SHANNON, TODD  
 CITY OF WILLOWICK  
 TSHANNON@CITYOFWILLOWICK.COM  
 4405850963

Quote Provided By  
 Middlefield Farm and Garden  
 Ryan Ivans  
 15980 Georgia Road  
 Middlefield, OH 44062  
 email: mryan@mfgkubota.com  
 phone: 4408624515

- Standard Features -

- Custom Options -



S Series SSV65PHFC  
 \*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**FEATURES**

Vertical Lift Path Loader Frame  
 Standard Front Quick Coupler,  
 Float Standard  
 Hydraulic Quick Coupler Option  
 One Way Self-Leveling  
 with Kubota Shock-less Ride  
 (KSR) Option  
 Loader Boom Lock  
 Loader Arm Drop Valve  
 Open ROPS & Air Conditioned  
 ROPS/FOPS Cab Models  
 Adjustable, Vinyl, Suspension  
 Seat  
 2" Retractable Seat Belt and 2-  
 Piece Seat Bar  
 12V Electric Outlet  
 18 gpm Auxiliary Hydraulics,  
 28 gpm High Flow Hydraulics  
 Option  
 Direct To Tank Return Line  
 10x16.5, 8PR Heavy-Duty Tires  
 Two Speed Travel System  
 Spring Applied Hydraulically  
 Released (SAHR) Brakes  
 Gear Drive Pumps & Variable  
 Loader  
 and High Flow Pumps (if  
 equipped)  
 Mechanical Hand & Foot  
 Controls  
 Electronic Dial Throttle  
 Automatic Glow Plugs  
 Key Switch Stop/Start System  
 Self-Bleed Fuel System  
 2 Front and 2 Rear Working  
 Lights  
 2 Front Corner Lights & 2 Rear  
 Red Tail Lights  
 Hour Meter, Engine  
 Temperature and Fuel  
 Gauges and Warning Lights  
 Horn and Backup Alarm  
 Lockable Fuel Cap Door  
 Bolt On Grab Handles to enter  
 machine

**ISO-PILOT CONTROL BASIC**

UNIT  
 SSV65PHFC, AC Enclosed Cab,  
 High Flow Hydraulics  
 Hydraulic Quick Coupler  
 OPERATIONAL  
 DIMENSIONS  
 Operating Weight\*, SSV65P\*,  
 Open ROPS/FOPS Cab,  
 Mechanical Quick Coupler 6,790  
 lbs.  
 Tipping Load 3,900 lbs.  
 Auxiliary Hydraulics Flow 18.0 /  
 28.0 gpm  
 Travel Speed (Low / High) 6.0 /  
 11.1 mph  
 Reach @ Maximum Height 32.7"  
 Height to Hinge Pin 121.5"  
 Ground Clearance 7.6"  
 Traction Force 9,678 lbf.

\* Includes operator's weight, 175 lbs.

**ENGINE**

V2607 Kubota CR-TE4, Tier 4  
 Diesel Engine  
 4-Cylinder, 4 Cycle, Turbo Charged  
 64 Gross HP @ 2700 rpm  
 2.6 L Displacement  
 166 lbf-ft Peak Torque

**DIMENSIONS**

Cab Height 79.9"  
 Width over wheels 66.5"  
 Width with 68" standard bucket  
 69.0"  
 Length without bucket 106.3"  
 Length with standard bucket 135.4"

SSV65PHFC Base Price: \$50,228.00

(1) 74" HEAVY DUTY LOW PROFILE LONG  
 FLOOR BUCKET (19.2 CU-FT) W/CUTTING EDGE \$1,745.00  
 AP-HD74LLC-74" HEAVY DUTY LOW PROFILE LONG FLOOR  
 BUCKET (19.2 CU-FT) W/CUTTING EDGE

Configured Price: \$51,973.00

Sourcewell Discount: (\$12,473.52)

SUBTOTAL: \$39,499.48

Dealer Assembly: \$0.00

Freight Cost: \$665.00

PDI: \$250.00

1845C CASE SKID STEER TRADE (\$10,000.00)

Total Unit Price: \$30,414.48  
 Quantity Ordered: 1  
 Final Sales Price: \$30,414.48

**Purchase Order Must Reflect  
 the Final Sales Price**

To order, place your Purchase Order directly with the quoting dealer

\*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.