





- REMOVE EXISTING SPEAKER POST. USE EXISTING ELECTRICAL/
 COMMUNICATIONS CONNECTIONS FOR NEW SPEAKER POST/ CANOPY,
 SEE CIOI, ELECTRICAL DRAWINGS, AND SIGN VENDOR DRAWINGS.
 COORDINATE ANY NEW WORK WITH SIGNAGE, VENDOR DRAWINGS
 (DIFFERENT PERMIT)
- 2 CLEAN EXISTING DUMPSTER ENCLOSURE AND PREPARE FOR NEW PAINT.
- REMOVE EXISTING CONCRETE AND ASPHALT AS REQUIRED FOR NEW WORK.
- 4 PREPARE PARKING LOT FOR RE-STRIPING.
- 5 EXISTING LANDSCAPE AREA TO REMAIN. PROTECT VEGETATION FROD DAMAGE THROUGHOUT ALL PHASES OF DEMOLITION CONSTRUCTION.
- 6 EXISTING MONUMENT SIGN TO REMAIN. COORDINATE SCOPE OF SIGNAGE WITH SIGN VENDOR (SEPARATE PERMIT).
- $\boxed{7}$ Existing Lot Lighting to Remain. No Work.
- $\langle \delta
 angle$ existing directional sign to remain.
- $\langle 9 \rangle$ Existing accessible parking signage to be removed.


	SEA)	.0		1	Te
₹.		/*	FRE	مرير DEF GOG	CICK,	V	
	REGISTRATION	REG\2	. N	0.	9602		C C
	Щ В		5,	·····	AR	CZ	
EM		DEDIO	all a		MA		- T (10
		IRATIC	Ŋ.,	GUGI		1/25	
ROM DN.				မ		7/2	24/24
		\leq		6314	.co		
		7		ST. LOUIS, MO 63146	www.arcv.com		
		\sim		SNO.	\$		
				ST.L	0		
					5-230		
)		4 4		
		X	<u> </u>	8	FAX (314) 415-2300		
		$\frac{2}{8}$	TECT, NCARB, RDI	AIG ROAD, SUITE 300	芷		
			iŞ		0		
			5	. Š	415-2400		
		Щ		RAIG	4		
			ARCH.	1950 CR	PH. (314)		
			- ∢	<u>\$</u>	<u> </u>		
					2		
					J	2-	
						h	7
		6			7		
		回			2		
		Q			14 09		32
				, .	٦ , ۲		$\overset{\circ}{\infty}$
		ARBY'S REMODE		EST	WILLOWICK OH, 44095		## []
		B		Ž Ž	™		別別
		AB		31215			STORE # 1832
	NAME						
	≱						-
	Ţ						
	DESCRIPTION						
「							
							NOITE DEVICE THOSE
	ш						[
	DATE						
QUIRED	REV						
		30698	—	MQ		74	
		NO: 2,	S ∐≾	BY: JI		;` <u>`</u>	<u>}</u>
		PROJECT NO: 230698	DRAWN BY: ST	CHECKED BY: JDW		07/19/24	
₹E	otag	PR	띪	핑	٤		י ע
				4			`

GENERAL NOTES

- COORDINATE SCOPE OF REFACING/REFURBINSHMENT OF EXISTING DIRECTIONAL SIGNS WITH SIGNAGE VENDOR/DRAWINGS.
- B. ALL SIGNAGE DRAWINGS ARE SUBMITTED SEPARATELY AND FOR SEPARATE PERMIT BY SIGNAGE VENDOR.
- ALL ADDRESS IDENTIFYING FEATURES SHALL BE REMOVED AS REQU DUE TO NEW WORK. COORDINATE WITH OWNER AND LOCAL FIRE DEPARTMENT/ZONING AUTHORITY FOR RE-MOUNTING POSITIONS.

<u>LEGEND</u>








- INSTALL NEW SPEAKER POST AND DRIVE THRU CANOPY.
 COORDINATE WITH CANOPY VENDOR UNDER SEPARATE PERMIT
- $\langle 2 \rangle$ Existing Menu Board, coordinate scope of Work With SIGNAGE/BRANDING VENDOR, SEPARATE PERMIT
- RE-STRIPE AND SEAL SITE TO EXTENTS UNDER ARBY'S RESPONSIBILITY (MATCH EXISTING, EXCEPT AS NOTED). COORDINATE ANY REPAIR WITH FACILITIES.
- 4 RE-PAINT INTERNATIONAL SYMBOL OF ACCESSIBILITY. 5 NEW ACCESSIBLE PARKING SIGNAGE. SEE 2/CIO2
- 6 MONUMENT SIGN TO REMAIN. COORDINATE ANY NEW WORK WITH SIGNAGE VENDOR.
- $\langle 7 \rangle$ EXISTING BOLLARD.
- $\langle \delta \rangle$ POWER WASH EXISTING SIDEWALK/ CONCRETE.
- \langle 9 \rangle REFRESH LANDSCAPING. COORDINATE ANY NEW PLANTINGS WITH
- EXISTING DUMPSTER ENCLOSURE. CLEAN AND PAINT "ROOKWOOD BROWN". SEE A400 FOR SPECIFICATION.
- VERIFY SIDEWALK AT EXIT DOORS AND AT TOPS OF RAMPS TO BE ADA COMPLIANT- MAX 2% SLOPES IN ALL DIRECTIONS. IF SLOPES EXCEED THESE, NOTIFY ARCHITECT
- (12) EXISTING DIRECTION SIGN, SEE SIGNAGE/BRANDING VENDOR FOR SCOPE (SEPARATE PERMIT).
- (13) FLUSH TRANSITION AT PAVEMENT.
- (14) EXISTING FLAG POLE
- NEW CONCRETE AT ADA PATHWAY MAX 2% SLOPES IN ALL DIRECTIONS. ALTERNATE, RESURFACE ASPHALT TO ACHIEVE SLOPE REQUIREMENT. SEE DETAIL 2/CIO2.

GENERAL NOTES

<u>LEGEND</u>

AREA OF NEW CONCRETE

AREA OF REFRESHED LANDSCAPING-COORDINATE WITH FACILITIES




C101


GOGLIA

FREDERICK J. GOGLIA, LICENSE #9602

7/24/24

EXPIRATION DATE: 12/31/25







- REMOVE ALL DINING AREA SEATS, TABLES, TRASH ENCLOSURES, DIVIDER WALLS, AND CONDIMENT COUNTER.
- REMOVE ALL EXISTING TILE FLOORING AND COVE BASE IN DINING AREA, VESTIBULES, CUSTOMER AREA, CORRIDOR, WOMEN'S RESTROOM & MEN'S
- RESTROOM.
- REMOVE EXISTING DOOR AND FRAME. PREPARE OPENING TO RECEIVE NEW CASING. SEE DECOR
- REMOVE EXISTING SELF SERVE BEVERAGE COUNTER. THE EXISTING SODA DISPENSER WILL BE REMOVED BY OWNER FOR RE-INSTALLATION. SEE AIOI FOR NEW LOCATION.
- REMOVE ALL EXISTING WALLCOVERING THROUGHOUT DINING AREA.
 COORDINATE WITH OWNER REMOVAL OF CHAIR RAIL (OR PAINT EXISTING).
- EXISTING POS STATIONS TO BE RELOCATED BY OWNER VENDOR. SEE SHEET AIOO FOR THEIR RE-INSTALL LOCATIONS.
- 7 REMOVE PORTION OF EXISTING INTERIOR FULL HEIGHT WALL TO EXTENTS
- (8) REMOVE EXISTING SERVICE COUNTER AND KNEE WALL.

INDICATED. SEE Aloo FOR BALANCE OF EXTENTS.

- (9) REMOVE PRODUCTION TABLE/SYSTEM.
- REMOVE EXISTING RESTROOM PLUMBING FIXTURES, TOWEL DISPENSER, CHANGING STATION, PARTITIONS. SALVAGE CHANGING STATION FOR RELOCATION, SEE 20/AIO2.
- (II) REMOVE DOOR, FRAME TO REMAIN.
- (12) EXISTING HAND SINK TO REMAIN.
- RELOCATE EXISTING SAFE. SEE SHEET AIOI FOR NEW LOCATION.
- (14) EXISTING MOP SINK TO REMAIN.
- $\langle 15 \rangle$ EXISTING 3-COMPARTMENT SINK AND WAREWASHER TO REMAIN.
- REMOVE DRIVE-THRU WINDOW. PREPARE OPENING TO RECEIVE NEW WINDOW. SEI
- (17) EXISTING DRIVE-THRU BEVERAGE STATION EQUIPMENT TO REMAIN.
- (18) RELOCATE EXISTING MEAT SLICER. SEE AIOI.
- (19) RELOCATE COOK-N-HOLD.
- 20 RELOCATE BREAD CART.
- (21) EXISTING PREP SINK
- (22) EXISTING STOREFRONT WINDOW TO REMAIN. CLEAN, REPAIR TO "AS NEW"
- (23) RELOCATE FIRE EXTINGUISHER
- REMOVE FULL HEIGHT WALL (VERIFY ANY STRUCTURAL COMPONENTS AND II FOUND TO NOTIFY ARCHITECT IMMEDIATELY).

REA GOGLIA NO. 9602 FREDERICK J. GOGLIA, LICENSE #960 EXPIRATION DATE: 12/31/25 REA GODA SEE AIOI FREDERICK J. GOGLIA, LICENSE #960 EXPIRATION DATE: 12/31/25 REA GOODA SEE SHEET FINE SHEET FIN

DEMOLITION PLAN GENERAL NOTES

EXAMINATION OF PREMISES: THE CONTRACTOR, BEFORE SUBMITTING A PROPOSAL FOR THIS WORK, SHALL EXAMINE THE PREMISES AND ALL CONDITIONS THEREON AND/OR THEREIN. THE PROPOSAL SHALL TAKE INTO CONSIDERATION ALL SUCH CONDITIONS AS MAY AFFECT THE WORK UNDER THIS CONTRACT. SUBMISSION OF A BID BY THE CONTRACTOR SHALL BE CONSIDERED AS ACKNOWLEDGMENT BY HIM THAT ALL SUCH CONDITIONS ARE FULLY KNOWN TO HIM. ARRANGEMENT FOR SITE VISITS SHALL BE MADE THROUGH LANDLORD.

- 2. GENERAL CONTRACTOR SHALL PAY FOR ALL REQUIRED DEMOLITION PERMIT FEES AND OBTAIN ALL APPLICABLE DEMOLITION PERMITS.
- 3. GENERAL CONTRACTOR IS TO PROVIDE ALL NECESSARY DUST & TRAFFIC BARRIERS & TEMPORARY PARTITIONS AS REQUIRED TO MAINTAIN A SAFE AND CLEAN ENVIRONMENT FOR THE PUBLIC AND EMPLOYEES THROUGHOUT THE PROJECT.
- 4. GENERAL CONTRACTOR SHALL REMOVE ALL DEBRIS & EQUIPMENT DAILY DURING THE DEMOLITION WORK.
- NO OVER-CUTTING WILL BE ALLOWED BEYOND THE NOTED HOLE SIZES FOR ANY NEW OPENINGS IN STRUCTURAL CONCRETE SLAB OR THE EXISTING ROOF, UNLESS OTHERWISE APPROVED BY THE ARCHITECT'S REPRESENTATIVE.
- GENERAL CONTRACTOR IS TO PATCH AND REPAIR ALL DAMAGED SURFACES TO MATCH ADJACENT SURFACES. ALL EXISTING DRYWALL OR PLASTER THAT IS TO REMAIN AND TO RECEIVE A NEW SCHEDULED PAINT OR WALL COVERING SHALL HAVE ALL DEFECTS, (CRACKS, PAINT CHIPPING, HOLES, ETC.) FILLED, PLASTERED OR SPACKLED, SANDED SMOOTH AND CLEANED PRIOR TO THE SCHEDULED FINISH. REPAIR ALL WALLS THAT ARE TO REMAIN TO MATCH EXISTING. WHEREVER A WALL OR FIXTURE HAS BEEN REMOVED OR ANY DAMAGE HAS OCCURRED AS A RESULT OF DEMOLITION OR CONSTRUCTION.

PLAI	N L	.EG	END	


- EXISTING WALLS TO REMAIN

- WALLS TO BE REMOVED

- NO WORK IN THIS AREA


D100

ARBY






- REMOVE CEILING TILE AND GRID COMPLETELY THROUGHOUT DINING ROOM, HALL, VESTIBULE, AND CUSTOMER QUEUING AREA AS NOTED.
- \langle $_2$ angle existing diffuser and grilles to remain in dining areas, and VESTIBULES, AS INDICATED. REINSTALL IN NEW GRID WHERE APPLICABLE.
- REMOVE EXISTING LIGHT FIXTURES (PENDANTS, 2X2's \$ 2X4's) THROUGHOUT DINING ROOM AND VESTIBULES.
- EXISTING MENU BOARD, TAKE DOWN TO ALLOW NEW FINISHE(S) TO BE APPLIED, RE-INSTALL AT SAME LOCATION.
- (5) REMOVE EXISTING SPEAKERS.
- 6 EXISTING SOFFIT/GYPSUM CEILING TO REMAIN.
 -PATCH AND REPAIR AS NECESSARY.
 -PREP FOR NEW FINISHES, SEE A200, DECOR
- \langle 7 \rangle REMOVE EXISTING EXIT SIGN.
- $\langle s \rangle$ REMOVE EXISTING LIGHTING. SEE A200 FOR REPLACEMENT WITH LED.
- REMOVE EXISTING AWNING AND BACK LIGHTING. REPAIR ALL EIFS AND PREPARE TO RECEIVE NEW FINISHES. SEE A400.
- (10) EXISTING HOOD, PROTECT DURING ALL PHASES OF WORK.
- ANY LIGHTS AFFECTED BY CEILING WORK ARE TO BE SALVAGED FOR RELOCATION, SEE A200.
- REMOVE EXISTING HARD CEILING/SOFFIT AND FRAMING TO EXTENTS SHOWN. SEE A200 FOR BALANCE OF EXTENTS
- (13) REMOVE CEILING TILE TO EXTENTS REQUIRED FOR NEW WORK



GENERAL NOTES

- EXAMINATION OF PREMISES: THE CONTRACTOR, BEFORE SUBMITTING A PROPOSAL FOR THIS WORK, SHALL EXAMINE THE PREMISES AND ALL CONDITIONS THEREON AND/OR THEREIN. THE PROPOSAL SHALL TAKE INTO CONSIDERATION ALL SUCH CONDITIONS AS MAY AFFECT THE WORK UNDER THIS CONTRACT. SUBMISSION OF A BID BY THE CONTRACTOR SHALL BE CONSIDERED AS ACKNOWLEDGMENT BY HIM THAT ALL SUCH CONDITIONS AR FULLY KNOWN TO HIM. ARRANGEMENT FOR SITE VISITS SHALL BE MADE THROUGH LANDLORD.
- GENERAL CONTRACTOR SHALL PAY FOR ALL REQUIRED DEMOLITION PERMIT FEES AND OBTAIN ALL APPLICABLE DEMOLITION PERMITS.
- AT LEAST ONE RESTROOM MUST BE AVAILABLE DURING ALL PERIODS OF
- ALL REMODELING WORK MUST BE INITIATED IN A MANNER TO ELIMINATE THE POSSIBILITY OF DUST, DEBRIS OR CONTAMINANTS GETTING INTO THE ACTIVE PART OF THE FACILITY.
- GENERAL CONTRACTOR IS TO PROVIDE ALL NECESSARY DUST & TRAFFIC BARRIERS & TEMPORARY PARTITIONS AS REQUIRED TO MAINTAIN A SAFE AND CLEAN ENVIRONMENT FOR THE PUBLIC AND EMPLOYEES THROUGHOUT THE
- GENERAL CONTRACTOR SHALL REMOVE ALL DEBRIS & EQUIPMENT DAILY DURING THE DEMOLITION WORK.
- NO OVER-CUTTING WILL BE ALLOWED BEYOND THE NOTED HOLE SIZES FOR ANY NEW OPENINGS IN STRUCTURAL CONCRETE SLAB OR THE EXISTING ROOF, UNLESS OTHERWISE APPROVED BY THE ARCHITECT'S REPRESENTATIVE.
- GENERAL CONTRACTOR IS TO PATCH AND REPAIR ALL DAMAGED SURFACES TO MATCH ADJACENT SURFACES. ALL EXISTING GYPSUM BOARD OR PLASTER THAT IS TO REMAIN AND TO RECEIVE A NEW SCHEDULED PAINT OR WALL COVERING SHALL HAVE ALL DEFECTS, (CRACKS, PAINT CHIPPING, HOLES, ETC.) FILLED, PLASTERED OR SPACKLED, SANDED SMOOTH AND CLEANED PRIOR TO THE SCHEDULED FINISH. REPAIR ALL WALLS THAT ARE TO REMAIN TO MATCH EXISTING. WHEREVER A WALL OR FIXTURE HAS BEEN REMOVED OR ANY DAMAGE HAS OCCURRED AS A RESULT OF DEMOLITION OR CONSTRUCTION.
- GENERAL CONTRACTOR TO VERIFY ALL EXISTING ELEVATIONS AND BUILDIN CONDITIONS IN FIELD PRIOR TO START OF DEMOLITION.
- G.C. SHALL IMMEDIATELY NOTIFY ARCHITECT OF ANY DISCREPANCIES IN EXISTING STRUCTURAL COMPONENTS OF BUILDING.
- ALL SECURITY EQUIPMENT (CAMERAS, SENSORS, KEYPADS) THAT REQUIRES REMOVAL SHALL BE REINSTALLED IN SAME LOCATION.


PLAN LEGEND - EXISTING 2'x2' CEILING GRID AND TILE TO BE REMOVED.









SE HAS OCCURRED AS A RESULT OF DEMOLITION								
O VERIFY ALL EXISTING ELEVATIONS AND BUILDING OR TO START OF DEMOLITION.								
NOTIFY ARCHITECT OF ANY DISCREPANCIES IN MPONENTS OF BUILDING.		0			44095		1832	
(CAMERAS, SENSORS, KEYPADS) THAT REQUIRES STALLED IN SAME LOCATION.		H		ST.			#=	
		လ်			<u></u>		Щ	
N LEGEND		ARBY'S REMODE		31219 VINE ST.	WILLOWICK OH		STORE	
				כיז	<u> </u>		<u> </u>	
- EXISTING 2'x2' CEILING GRID AND TILE TO BE REMOVED.	NAME							
- EXISTING 2'x4' CEILING GRID AND TILE TO BE REMOVED. SEE KEYED AND PLAN NOTES FOR REQUIREMENTS.	DESCRIPTION						NV Id	ובאו
WALLS/ ELEMENTS TO BE	ш							בור בורי
REMOVED	DATE						"	5
	REV						\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	5
NO WORK IN THIS AREA		PROJECT NO: 230698	DRAWN BY: ST	CHECKED BY: JDW	ISSUE DATE:	07/19/24	NA IQ ONI IION CEII ING PI AN	
- CEILING MOUNTED ITEMS TO BE REMOVED - SEE KEY NOTES AND SHEET A200			D	1	0	1		















			DO	OR SC	CHE	DUL	E					
00R	DOOR					FRAM	E					
NO.	SIZE M × H	MTL.	FIN.	TYPE	MTL.	ELEV.	TYPE	THR.	CLOSER	U.L. LABEL	HDW. SET	REMARKS
-	FIT TO EXISTING DOOR FRAME	MOOD	P. LAM EACH SIDE	B	HM		EXIST	NEM	YES	-	4	1, 2, 3, 4
2	FIT TO EXISTING DOOR FRAME	MOOD	P. LAM EACH SIDE	В	HM		EXIST	NEM	YES	-	4	1, 2, 3

HARDWARE SCHEDULE DOOR **REMARKS** HARDWARE SET 4 (SINGLE OCCUPANT RESTROOM):

I I/2 PR. HAGER HINGES ECBB IIOO 26D I HAGER 5100 GRADE I HEAVY DUTY SURFACE CLOSER I SCHLAGE ND405-RH0-626 2 HAGER 1905 KICK PLATES 32D 8" X 34" 3 SILENCERS PER DOOR I SIGN- MENS / WOMEN'S I HAGER 243F LIGHT DUTY DOME STOP HIGH 26D

PLASTIC LAMINATE COLOR BY OWNER REFER TO DECOR DRAWINGS. VERIFY SIGNAGE FOR RESTROOM DOORS AND "EMPLOYEES ONLY" DOORS IS MOUNTED (REMOUNT TO REFINISHED WALLS) ON WALL AT 60" A.F.F. TO THE CENTER OF THE SIGN. SIGNS SHALL BE MOUNTED ON THE WALL ADJACENT TO THE DOOR, ON THE LATCH SIDE. ALL SIGNS SHALL HAVE TACTILE CHARACTERS AND RESTROOM SIGNAGE SHALL HAVE PICTOGRAMS. ALL SIGNAGE TO COMPLY WITH ADA

ADJUST DOOR OPENING PRESSURES. 5LBS MAX. FOR INTERIOR DOORS & 8.5LBS MAX. FOR EXTERIOR DOORS.

4. NO FLOOR STOP. ADJUST DOOR CLOSER TO STOP AT 45°

KEYED NOTES

- NEW PRODUCTION TABLE (OUTLINE OF), PROVIDED BY OWNER, INSTALLED BY KES. G.C. TO PROVIDE ALL CONNECTIONS. SEE AIOI, ELECTRICAL, PLUMBING
- NEW CORIAN COUNTER TOP ON KNEE WALL. TOP OF COUNTER TO BE SET AT 34" A.F.F. BUTT COUNTER TO EXISTING DOOR FRAME. SEE 3/A601.

NO. 9602

FREDERICK J. GOGLIA, LICENSE #960 EXPIRATION DATE: 12/31/25


7/24/24

- (3) NEW PLUMBING FIXTURES, FINISHES, AND ACCESSORIES IN RESTROOMS. RELOCATED CHANGING STATIONS.
- 4 Existing hand sink
- $\langle 5 \rangle$ EXISTING THREE-COMPARTMENT SINK AND WAREWASHER.
- $\langle 6 \rangle$ EXISTING MOP SINK
- 7 EXISTING PREP SINK
- δ NEW BEVERAGE COUNTER (OUTLINE OF) AND EQUIPMENT BY OWNER, INSTALLED BY G.C. TOP OF COUNTER TO BE SET AT 34" A.F.F. MAX. G.C. TO TRENCH SLAB AS REQUIRED FOR NEW FLOOR SINK. SODA VENDOR TO RUN SODA LINES.
- $\langle \mathsf{q} \rangle$ NEW INTERIOR DOOR, FIT TO EXISTING FRAME.
- (10) NEW LOW WALL, SEE DECOR FOR FINISHES.
- $| | | \rangle$ NEW FULL-HEIGHT WALL, SEE WALL TYPE.
- \langle I2 angle NEW FLOOR TILE, WALL FINISHES-SEE DECOR DRAWINGS. (13) RESTROOM SIGN, SEE 17/AIO2
- (14) EXIT SIGN, SEE 17/AIO2
- (15) ELECTRICAL OUTLET-SEE ELECTRICAL DRAWINGS FOR TYPE, ETC.
- REPLACE ALL DAMAGED FRP AND CLEAN, INSTALL NEW AT LOCATIONS AFFECTED BY NEW WORK, TO +6" ABOVE CEILING.
- NEW WALL TILE-SEE DECOR. EXTEND INTO OPENING AT REMOVED DOOR. COVE BASE TO MATCH EXISTING EXCEPT AS
- (18) TERMINATE TILE AT CORNER WITH FINISHED EDGE.
- REPAIR WALL AT REMOVED FRAMING AND FINISH. ALIGN ALL NEW SUBSTRATES WITH ADJACENT, SEE DECOR FOR FINISHES
- (20) NEW DRIVE-THRU WINDOW, SEE WINDOW TYPES, AND AIOI.
- EXISTING OPENING, SEE DECOR FOR TILE CASING EXTENTS AND SCHLUTER TRIM.
- (22) EXTEND HALL TILE INTO OPENING TO MEET (REPAIRED/EXISTING) QUARRY TILE AT SERVICE AREA. SEE DECOR.
- ALIGN SALES COUNTER EDGE WITH FACE OF FINISHED WALL.
- (24) NEW HAND SINK.
- (25) ALIGN WITH SOFFIT ABOVE.
- (26) EXISTING FRYER (OUTLINE)

GENERAL NOTES

- AT LEAST ONE RESTROOM MUST BE AVAILABLE DURING ALL PERIODS OF OPERATION.
- ALL REMODELING WORK MUST BE INITIATED IN A MANNER TO ELIMINATE THE POSSIBILITY OF DUST, DEBRIS OR CONTAMINANTS GETTING INTO THE ACTIVE PART OF THE FACILITY.
- G.C. TO VERIFY DINING LAYOUT WITH LATEST DECOR PLANS PRIOR TO INSTALLATION.
- ALL EQUIP. REMOVED FROM PREP/DRIVE THRU AREA TO BE RE-MOUNTED TO ORIG. POSITIONS ONCE FLOOR TILE INSTALL IS
- GENERAL CONTRACTOR TO REFER TO SITE PLAN DRAWINGS FOR ALL RELEVANT SITE WORK INCLUDING, BUT NOT LIMITED TO, SIDEMALKS, CURBS, DRIVEMAYS, PARKING AREAS, ETC. GENERAL CONTRACTOR TO VERIFY ALL EXISTING ELEVATIONS AND BUILDING CONDITIONS IN FIELD PRIOR TO START OF CONSTRUCTION.
- GC SHALL STORE ALL EXISTING FIRE EXTINGUISHERS FOR REINSTALLATION.
- REINSTALL EXISTING FIRE EXTINGUISHERS. POSITION SO THAT THEY ARE WITHIN 75' OF EVERY POINT WITHIN THE BUILDING.
- REINSTALL OR PROVIDE NEW CLASS 'K' FIRE EXTINGUISHER WITHIN 30' OF COMMERCIAL COOKING EQUIPMENT.
- COORDINATE ALL FINAL FIRE EXTINGUISHER LOCATIONS WITH THE LOCAL FIRE DEPARTMENT.

NOTE: ALL DIMENSIONS ARE FROM FINISHED FACE OF SURFACE TO FINISHED FACE OF SURFACE, EXCEPT



-KEYED NOTE

-WINDOW TYPE


REM

ARBY

A100

			EQUIPMENT SCHEDULE	
No	0774	Ť	SEN III CUSTOM FAB: WHEN ORDERING FROM KES, VERIFY LATEST APPROVED SHOP	
NO	QTY.	ITEM	MANUF. AND MODEL NO.	REMARKS
3	l	SELF SERVE BEVERAGE COUNTER	KES / DECOR	7'-II" L × 42"D × 34"H
5	l	WALL MOUNTED HAND SINK	KROWNE H52	
I7A	I	OVEN STAND	KES	28M × 41 1/2H MOBILE STAND TO HOLD (2) #17
26		BEEF PORTION SCALE	SMALLWARE ITEM	SEE SMALLWARES LIST
26A	I	BEEF PORTION SCALE DISPLAY-INTEGRAL TO #26	SEE PLAN FOR LOCATION	
47		TURNOVER DISPLAY CASE	HOWARD (II PANEL) PLATINUM MODULAR LED MENU BOARD SUYSTEM	24"L × 17"D × 24"H
46	_	UNIVERSAL PRODUCTION TABLE- 171"	KES, CUSTOM FAB ITEM	
46A	-	60" ROLL-IN COLD WELL UNIT	BEVERAGE AIR, SPE 24-60M	
46C	-	UNDERCOUNTER REFRIGERATED DRAWERS	BEVERAGE-AIR MODEL UCRD2TA-23ARB	INTEGRATED INTO #46 SLICER COUNTER
46D	I	TO-GO BAG HOLDER		INTEGRATED INTO #46 SLICER COUNTER
46F	I	BEEF DRAWER	KES, CUSTOM FAB ITEM	INTEGRATED INTO #46 SLICER COUNTER
46H		BACKLINE TIMER	A.J. ANTUNES SOLAR TIMER MODEL #TTS-8 PT	INTEGRATED INTO #46 SLICER COUNTER
48	ı	SANDWICH SLIDE / ORGANIZER STAND	KES, CUSTOM FAB ITEM	
52A	I	SLICER HEAT LAMP	MARSHAL AIR THERMO GLO BM4B-I	24.875 X 28 X 24.75 STAINLESS STEEL CONSTRUCTION
54	1	HORIZONTAL TOASTER	MARSHALL AIR, AUTOTOAST, 18" MODEL HT18, ARBY'S SPEC MM2B-ARB, HIGH SPEED HORIZONTAL CONTACT TOASTER	II.50"H x 27.00"W x 23.375"D
56	1	DUAL CHEESE PUMP	STAR MFGR. #SPDE-2ARB	10.75"W X 21.38"D X 32.25"H
56A	I	WIRE SOUFFLE CUP HOLDER	QUADRATEC, DISPWAR 0001	COLOR: BLACK
57	1	HEAT-N-HOLD 3 SHELF CABINET	MERCOECO, MHD32SSTIT	20.8"MX22.5"DXI2.8"H
57A	1	HEAT-N-HOLD 4 SHELF CABINET	MERCOECO, MHD4255LIT	I6.2"WX22.5"DX23.8"H
62	I	HEATED HOLDING	MARSHALL AIR, 3 TIER, 3x2 HOLDING UNIT	19.75"H X 15.375"W X 15.625"D
65	I	CASHIER / ORDER TAKING COUNTER	KES, CUSTOM FAB ITEM	
75	ı	AUTOMATIC DRIVE THRU WINDOW	QUIKSERV #55-4035E	FIELD VERIFY OPENING. BRONZE FINISH

77	I	AU JUS SERVER	SERVER, MODEL SY I.O ARBY'S #85503, I GAL AU JUS SERVER	
78	Ι	PAPER TOWEL DISPENSER	BY OWNER	
79	l	LIQUID SOAP DISPENSER	BY OWNER	
89	LOT	FRONT COUNTER SHELVING, BRIGHT ZINC FINISH	METRO (2) 42" × 24" × (3) TIER, (I) 24" × 24" × (3) TIER	SEE PLAN FOR SHELF LOCATION
90	2	UNDERCOUNTER CUP DISPENSER CABINET	KES, CUSTOM FAB ITEM	28"H X 7 7/8"W X 32 1/2"D INCLUDES JAMAR CUP DISPENSER
93	_	STRAM & LID HOLDER	KES, CUSTOM FAB ITEM	
98	2	HIGH CHAIR / BOOSTER SEATS	BY OWNER	
102	LOT	TRASH CAN		
103	2	SINGLE TRASH CAN		
107	I	HEAVY DUTY PAN RACK	WIN-HOLT	
		<u></u>		







- PELOCATED POS UNIT
- (3) RELOCATED SAFE
- \langle 4 \rangle RELOCATED SUPPLY/BREAD RACK
- (5) EXISTING SHAKE MACHINE AND STAND
- RELOCATED SELF-SERVE BEVERAGE DISPENSER AND (RELOCATED) TOP-MOUNT ICE MACHINE.
- NEW PLUMBING FIXTURES, FINISHES, CHANGING STATIONS AND ACCESSORIES (EXCEPT AS NOTED) IN RESTROOMS.
- (8) RELOCATED COOK N HOLDS (4) AND RACK
- (9) RELOCATED LEMONADE EQUIPMENT.
- (10) ALIGN.
- \langle II \rangle Existing hand sink
- \langle 12angle existing three-comp sink and warewasher. (13) EXISTING MOP SINK
- (14) RELOCATED MICROMAVES ON PREP-LINE.
- $\langle 15 \rangle$ NEW HAND SINK.
- EXISTING DRIVE THRU COUNTER AND BEVERAGE MACHINE TO REMAIN (17) EXISTING PREP-SINK.
- NEW DECOR FURNISHINGS AND FINISHES IN FRONT OF HOUSE, VESTIBULES, HALL BY DECOR. SEE DECOR DRAWINGS.
- $\langle {\sf IP} \rangle$ RELOCATED CADCO CONVECTION OVENS(2).
- (20) NEW DRIVE THRU WINDOW.
- 21) NEW SALES COUNTER ON NEW LOW WALL.
- (22) RELOCATED FIRE EXTINGUISHER

GENERAL NOTES

- COORDINATE WITH OWNER PLACEMENT OF RELOCATED ITEMS.
 DUE TO HIGHER DEMAND, IT MIGHT BE PREFERRED THAT THE
 NEW EQUIPMENT OF MULTIPLES SHOULD BE IN THE MORE
 FREQUENTLY ATTENDED POSITIONS.
- COORDINATE ANY UNLISTED ITEMS REMOVED WITH OWNER FOR RELOCATION OR RE-USE. ANYTHING THAT REQUIRES ADDITIONAL POWER WILL NEED TO BE BROUGHT TO THE ATTENTION OF THE ARCHITECT OF RECORD SO CIRCUIT LOADING CAN BE CONFIRMED.



(###)

- EXISTING WALLS TO REMAIN - NEW WALLS TO BE CONSTRUCTED - NEW LOW WALL TO BE CONSTRUCTED

> - NO WORK IN THIS AREA - KEYED NOTE

- EQUIPMENT TAG


A101


ARBY'S REM

31219 VINE ST. WILLOWICK OH, 4

FREDERICK J. GOGLIA, LICENSE #960 EXPIRATION DATE: 12/31/25

7/24/24





1 REFLECTED CEILING PLAN
SCALE: 1/4" - 1'-0"



FIXT	TURE LEGEND
SYMBOL	DESCRIPTION
	HVAC SUPPLY DIFFUSERS TO BE PAINTED, NEW DIFFUSERS TO BE WHITE
	HVAC RETURN DIFFUSERS TO BE PAINTED, NEW DIFFUSERS TO BE WHITE
	RESTROOM HVAC DIFFUSERS TO BE PAINTED, NEW DIFFUSERS TO BE WHITE
(SP)	NEM SPEAKER
4_4	EXISTING/NEW EMERGENCY LIGHT FIXTURE: SEE ELECTRICAL
⊗	NEW EXIT LIGHT FIXTURE
0	NEW RECESSED CAN LIGHT FIXTURE: SEE ELECTRICAL
•	NEW BRONZE PENDANT LIGHT, SEE DECOR DRAWINGS AND ELECTRICAL
P	2x4 GRID LAMP
0	2x2 GRID LAMP
Į.	NEW EXTERIOR WALL PACK. SERVICE DOOR
	NEW EXTERIOR WALL PACK. SEE ELECTRICAL DRAWINGS
Ð	NEW EXTERIOR SCONCE FIXTURE. SEE ELECTRICAL DRAWINGS.
	NEW TRACK LIGHTING AND TRACK. SEE ELECTRICAL

KEYED NOTES

- PAINT CEILING GRID (WHITE), REPLACE TILES WITH NEW. SEE DECOR.
- 2 NEW PRE-MANUFACTURED CANOPY BY SIGN VENDOR. G.C. TO INSTALL BLOCKING FOR CANOPY SUPPORT.
- (3) NEW TRACK LIGHTING. SEE ELECTRICAL DRAWINGS.
- 4 NEW EMERGENCY LIGHT. SEE ELECTRICAL DRAWINGS.
- 5 INSTALL NEW SPEAKERS.
- EXISTING SUPPLY/RETURN AIR DEVICES IN THE RESTROOMS AREA TO REMAIN.
 GRILLES TO BE RE-PAINTED. FIELD VERIFY THAT THE DEVICES ARE IN PROPER
 WORKING CONDITION AND EXACT LOCATION.
- $\langle 1 \rangle$ re-lamp light if required, paint trim ring to match adjacent finish
- NEW 8" RECESSED CAN LIGHTS THROUGHOUT DINING ROOM, VESTIBULES, AND AS
- (9) INSTALL NEW EXIT SIGN.
- (IO) EXISTING MENU BOARD, REINSTALL AFTER NEW FINISH IS APPLIED.
- $\langle \parallel
 angle$ GYP CEILING TO REMAIN. REPAIR AS NEEDED, SEE DECOR FOR NEW (PAINT) FINISH.
- (12) NEW SIGNAGE BY SIGN VENDOR, SEPARATE PERMIT.
- (13) EXISTING HOOD TO REMAIN.
- $\langle 14 \rangle$ REPAIR EXISTING GRID AS REQUIRED DUE TO NEW WORK. MATCH ADJACENT.
- (15) NEW 8" RECESSED CAN LIGHTS ABOVE SERVICE COUNTER, INSTALL WHERE PREVIOUS LIGHTS ARE REMOVED.
- (16) NEW PENDANT LIGHTS. ALIGN WITH/CENTER ON TABLE BELOW. COORDINATE WITH
- NEW INTERIOR WALL SCONCES, CENTER ON WALL. SEE DECOR FOR HEIGHT.
- (19) NEW EXTERIOR WALL PACKS. SEE A400 FOR MOUNTING LOCATION.
- (20) EXISTING GRID/CEILING AND LIGHTING TO REMAIN.
- (21) REPLACE/EXTEND EXISTING GRID TO EXTENTS INDICATED/AS REQUIRED DUE TO NEW WORK
- REPAIR CEILING AT REMOVED LIGHT (TYPICAL, ALL INSTANCES). MATCH ADJACENT, SEE DECOR FOR FINISH.
- 23) PAINT EXISTING EXTERIOR SOFFIT PURE WHITE. SEE A400 FOR SPECS.

GENERAL NOTES

- INSTALLATION SHALL CONFORM TO THE ENERGY CONSERVATION DESIGN MANUAL STANDARDS FOR NEW NON-RESIDENTIAL BUILDINGS.
- B. ALL WORK AND MATERIALS SHALL COMPLY WITH GOVERNING CODES, SAFETY ORDERS
 AND REGULATIONS. CONTRACTOR SHALL OBTAIN AND PAY FOR ALL NECESSARY
 PERMITS, FEES, AND INSPECTIONS REQUIRED BY GOVERNING AUTHORITIES.
- C. CONTRACTOR PROVIDES CONDUIT FOR LINE AND LOW VOLTAGE WIRING, LINE VOLTAGE WIRING SWITCHES, DISCONNECTS, CIRCUIT BREAKERS, FINAL CONNECTIONS, AND ITEMS INDICATED.
- D. ANY EQUIPMENT THAT IS SUBSTITUTED SHALL FIT IN THE SPACE PROVIDED, WITH ADEQUATE ROOM FOR SERVICING, INCLUDING SUBSTITUTE EQUIPMENT NAMED IN THE SPECIFICATIONS. CONTRACTOR SHALL SUBMIT A 1/4" SCALE DRAWING OF ALL EQUIPMENT SUBSTITUTED FOR APPROVAL PRIOR TO INSTALLATION.
- E. ALL BRANCH DUCTS FEEDING INDIVIDUAL DIFFUSERS/GRILLES TO HAVE ACCESSIBLE
- DAMPERS AT TAKE-OFFS FOR AIR BALANCING.

 THE CONTRACTOR IS RESPONSIBLE TO MAINTAIN SERVICE ACCESS SPACE IN ACCORDANCE TO MANUFACTURES, LOCAL CODE & AUTHORITY REQUIREMENTS.
- THE MECHANICAL CONTRACTOR IS RESPONSIBLE FOR ALL THE HVAC SYSTEM CONTROLS INCLUDING LOW VOLTAGE WIRING.
- H. CONTRACTOR SHALL COORDINATE INSTALLATION OF MECHANICAL WORK WITH ALL OTHER TRADES SO AS TO AVOID UNNECESSARY DELAY OR INTERFERENCES.
 CONTRACTOR TO REVIEW ARCHITECTURAL AND EQUIPMENT SHEETS.
- I. AT LEAST ONE RESTROOM MUST BE AVAILABLE DURING ALL PERIODS OF OPERATION.
- J. ALL REMODELING WORK MUST BE INITIATED IN A MANNER TO ELIMINATE THE POSSIBILITY OF DUST, DEBRIS OR CONTAMINANTS GETTING INTO THE ACTIVE PART OF THE FACILITY.
- K. G.C. TO VERIFY DINING LAYOUT WITH LATEST DECOR PLANS PRIOR TO CEILING FEATURE/LIGHTING INSTALLATION.
- G.C. TO VERIFY EQUIPMENT LOCATION WITH PROJECT MANAGER PRIOR TO AFFECTED CEILING FEATURE/LIGHTING INSTALLATION.
- M. REFER TO DECOR DRAWINGS FOR CEILING TILES IN DINING ROOM -ALL NEW/ REPAIR SUSPENDED GRID SHALL MATCH ADJACENT-ANY REPLACED CEILING TILES IN SERVICE AREA AND KITCHEN AREA SHALL MATCH ADJACENT.
- N. ALL (CEILING) TILES IN VESTIBULES TO BE CLIPPED DOWN.
- O. ALL HVAC THERMOSTATS TO BE PROTECTED DURING CONSTRUCTION. DO NOT REMOVE.

CEILING	<u>PLAN</u>	LEGEND	

- 2'x2' CEILING GRID AND TILE. SEE KEYED NOTES AND PLAN NOTES FOR REQUIREMENTS.
- 2'x4' CEILING GRID AND TILE. SEE KEYED NOTES AND PLAN NOTES FOR REQUIREMENTS.
- NEW GYPSUM, SEE KEYNOTES
- NO WORK IN THIS AREA

- KEYED NOTE

FREDERICK J. GOGLIA, LICENSE #960

7/24/24

EXPIRATION DATE: 12/31/25

