



RCP GENERAL NOTES

1. REF. KEYNOTES ON FLOOR PLAN FOR CEILING HEIGHTS. MAINTAIN EXISTING SPRINKLER HEAD LAY OUT IN ACCORDANCE WITH SPRINKLER DESIGNER'S FINAL FIRE PROTECTION PLAN IN AREAS WHERE NEW CEILING ARE MATCHING EXISTING ACT GRID PATTERNS AND HEIGHT.
2. REF. ELEC. DWGS. FOR EMERGENCY AND EXIT LIGHTING LOCATIONS.
3. PAINT EXISTING EXPOSED ROOF DECK IN ROOMS: CORRIDOR 14, RECEIVING 14, AND STORAGE 05 TO MATCH BASE BE-1.
4. MOUNT FLUORESCENT STRIP LIGHT FIXTURES TO THE BOTTOM OF BAR JOISTS IN ROOMS: CORRIDOR 14, RECEIVING 14, AND STORAGE 05.
5. ALL CEILING MATERIALS SHALL BE CLASS 'A' TYPE.
6. PROVIDE ACCESS PANELS IN GYPSUM BD. CEILINGS AS REQUIRED BY MEP DWGS.
7. REFER TO ELECTRICAL SHEETS FOR ADDITIONAL INFORMATION.
8. ACCESS PANELS IN CEILING MUST BE LOCATED TO PROVIDE ACCESS TO MECHANICAL EQUIPMENT, VALVES, DAMPERS, CONTROLS, CLEANOUTS, J-BOXES, ETC. VERIFY AND COORDINATE WITH BUILDING OPERATIONS MANAGER PRIOR TO CONSTRUCTION. PANELS SHALL BE 24" x 24".
9. ALL PLUMBING SHUT OFF VALVES ARE TO BE LOCATED IN ACCESSIBLE CEILING. REFER TO PLUMBING DWGS. (TYP.)
10. FIRE PROTECTION PLANS (SPRINKLER DRAWINGS) MUST BE ENGINEERED. G. C. SHALL COORDINATE THE SUBMITTAL TO THE LANDLORD AND CITY FOR APPROVAL.

CEILING LEGEND

- SUSPENDED CEILING SYSTEM TYPE "A":
24"x48" ACOUSTICAL CEILING PANEL, ARMSTRONG OPTIMA #1462 WITH 1/4" GRID 'PRELUDE' SERIES, COLOR WHITE OR ARCH. APPROVED EQ.
- 5/8" GYPSUM BOARD CEILING / SOFFIT, PAINTED WHITE U.N.O.
- 2"x4" RECESSED LED FIXTURE, CEILING GRID AND GYPSUM BOARD MOUNTED.
- 2"x2" LED FIXTURE
- RECESSED DOWN LIGHTS
- COVE LIGHT
- 4" LED FIXTURE, REF. ELEC. DWGS FOR MOUNTING TYPE.
- 8" LED FIXTURE, REF. ELEC. DWGS FOR MOUNTING TYPE.

