



PLANNING COMMISSION

WEDNESDAY, MARCH 8, 2023

WORK SESSION

3. Frog Pond East and South Implementation-Development Code (Pauly)
(60 minutes)



PLANNING COMMISSION MEETING STAFF REPORT

Meeting Date: March 8, 2023		Subject: Frog Pond East and South Master Plan Development Code	
		Staff Member: Daniel Pauly, Planning Manager	
		Department: Community Development	
Action Required		Advisory Board/Commission Recommendation	
<input type="checkbox"/> Motion <input type="checkbox"/> Public Hearing Date: <input type="checkbox"/> Ordinance 1 st Reading Date: <input type="checkbox"/> Ordinance 2 nd Reading Date: <input type="checkbox"/> Resolution <input checked="" type="checkbox"/> Information or Direction <input type="checkbox"/> Information Only <input type="checkbox"/> Council Direction <input type="checkbox"/> Consent Agenda		<input type="checkbox"/> Approval <input type="checkbox"/> Denial <input type="checkbox"/> None Forwarded <input checked="" type="checkbox"/> Not Applicable	
		Comments:	
Staff Recommendation: Provide requested input on draft Development Code amendments for Frog Pond East and South Implementation.			
Recommended Language for Motion: N/A			
Project / Issue Relates To:			
<input checked="" type="checkbox"/> Council Goals/Priorities: Expand home ownership	<input checked="" type="checkbox"/> Adopted Master Plan(s): Frog Pond East and South Master Plan	<input type="checkbox"/> Not Applicable	

ISSUE BEFORE COMMISSION

An important next step in realizing the vision of the Frog Pond East and South Master Plan is to write implementing Development Code amendments. This work session is the third in a series of work sessions for the Commission to work through the details of these Development Code amendments.

EXECUTIVE SUMMARY:

In late 2022, the City Council, on recommendation from the Planning Commission, adopted the Frog Pond East and South Master Plan. The Master Plan identifies the types and locations of the homes, commercial development, parks, open spaces, streets, trails, and infrastructure to be built over the next 10-20 years in an area on the east side of Wilsonville added to the Metro Urban Growth Boundary in 2018. The Master Plan focuses on providing for the community's future housing needs, including providing diverse housing opportunities.

The Master Plan provides clear policy direction and guidance for future development in Frog Pond East and South. However, an important implementation step is to develop a detailed set of Development Code standards consistent with the Master Plan. These standards will be relied on by developers to plan and design development. These standards will also be relied on by City reviewers to ensure development meets City expectations.

This work session is the third in the series of work sessions for the Planning Commission to review and guide the drafting of these Development Code amendments. The first four work sessions will focus on specific portions or sets of the draft amendments with subsequent work sessions providing an opportunity to review the draft amendments all together. This work session will focus on different design standards.

Attachment 1 includes, for easy reference, excerpts from the Frog Pond East and South Master Plan that give specific direction for implementing Development Code. This directive language can be summarized and grouped as follows:

- Ensuring a variety of housing and encouraging specific housing types to be built;
- Creating design standards to implement the Type 1, Type 2, and Type 3 Urban Design Types mapped in the Master Plan and otherwise guide quality, cohesive development;
- Setting the design standards for sub-districts within the neighborhoods; and
- Establishing standards for the Brisband Main Street.

Attachment 2 contains the design-focused Development Code amendments, arranged by topic. For each draft code amendment, the document also contains the following supporting information:

- **Intent:** A description of what the draft code amendment is trying to accomplish, including any reference to related Master Plan implementation language.
- **Explanation:** An explanation of how the draft code amendment was developed. As applicable, this includes reference to background and reference information in the packet.
- **Code Reference:** This includes where the draft code amendment would go in the Development Code. It specifies if it is a new Section or Subsection or amendment to an existing section.

For the Planning Commission's reference, Attachment 3 is a copy of the current Wilsonville Code Section 4.127, Residential Neighborhood Zone, where a majority of the code amendments

are proposed. Also included, as Attachment 4, are excerpts from Section 4.113 Residential Development in Any Zone.

The project team invites the Planning Commission to review the draft code amendments and supporting information, ask any clarifying questions, and provide feedback. At the work session the project team requests the Planning Commission provide one of the following for each presented draft code amendment.

1. Confirmation that the draft code amendment is ready for finalization before being brought forward for a public hearing; or
2. Direction on next steps to further develop or refine the presented draft code amendment.

EXPECTED RESULTS:

Feedback from the meeting will guide completion of a package of Development Code amendments for adoption in the coming months.

TIMELINE:

Five work sessions are currently planned for the Planning Commission to draft Wilsonville Development Code amendments to implement the Frog Pond East & South Master Plan. A public hearing will follow this summer. City Council action on the Planning Commission’s recommendation is planned for summer or early fall.

CURRENT YEAR BUDGET IMPACTS:

The Development Code implementation work is funded by remaining funds from the \$350,000 Metro grant for the Frog Pond East and South Master Plan and matching City funds in the form of staff time. \$311,000 total is budgeted in FY 22/23 including the adoption of the Master Plan and follow up implementation, including this Development Code work and the infrastructure funding implementation work.

COMMUNITY INVOLVEMENT PROCESS:

During this implementation phase the primary focus is on honoring past input. However, the project team will engage key stakeholders for input on draft Development Code amendments.

POTENTIAL IMPACTS OR BENEFIT TO THE COMMUNITY:

Realization of the policy objectives set out in the Frog Pond East and South Master Plan to create Wilsonville’s next great neighborhoods. This includes furthering of the City’s Equitable Housing Strategic Plan and Council’s goal of affordable home ownership.

ALTERNATIVES:

The project team prepared draft amendments to help implement the Frog Pond East and South Master Plan. A number of alternative amendments can be considered to meet the same intent.

ATTACHMENTS:

1. Excerpts from Frog Pond East and South Master Plan related to Development Code Implementation
2. Draft Development Code Amendments with Supporting Information (March 2023)
3. Wilsonville Development Code Section 4.127 Residential Neighborhood Zone
4. Excerpts of Wilsonville Development Code Section 4.113 Residential Development in Any Zone

FROG POND EAST & SOUTH MASTER PLAN



A VISION AND IMPLEMENTATION PLAN FOR TWO NEW
NEIGHBORHOODS IN EAST WILSONVILLE



ADOPTED BY WILSONVILLE CITY COUNCIL
ORDINANCE NO. 870

DECEMBER 19 2022




COMMUNITY DESIGN CONCEPTS

SUBDISTRICTS

Figure 14 shows the concept of “subdistricts” within Frog Pond East and South. The subdistricts are intended as “neighborhoods within neighborhoods” – areas with cohesive building form, public realm features, and other characteristics that give them identity. There are ten subdistricts planned for Frog Pond East and South. Each will have a “green focal point” that is central in the subdistrict and/or aligned with a key feature such as a tree grove. The focal points, together with the neighborhood destinations, will provide many community gathering places in Frog Pond East and South.



Figure 14. Diagram of Conceptual Sub-Districts Frog Pond East and South Implementation-Development Code East & South Master Plan





COMMUNITY DESIGN CONCEPTS

IMPLEMENTING THE DESIGN CONCEPTS


The design concepts discussed above are the foundation of the Master Plan's intent to create a strong sense of place and identity in Frog Pond East and South. The Master Plan's Land Use and Urban Form Plan is shown on Figure 15. The following section summarizes how the Master Plan's key features and intended outcomes implement the design concepts. Additional descriptions are provided in the Land Use and Public Realm chapters of this report.

NEIGHBORHOOD DESTINATIONS WITHIN FROG POND EAST AND SOUTH

- Park/gathering space at the Frog Pond Grange
- A Future Frog Pond East Neighborhood Park
- The SW Brisband Main Street as a neighborhood-scale commercial and mixed-use center
- The Frog Pond South Community Park
- Meridian Creek Middle School
- "Green focal points" within each subdistrict
- Meridian Creek and Newland Creek natural areas
- Significant tree groves



Figure 15. Land Use and Urban Form Plan





COMMUNITY DESIGN CONCEPTS

FORM BASED DESIGN AND TRANSECT

- More compact housing is in “Type 1” urban form areas (see Chapter 6 for more description of the urban form types)
- Adjacent areas are less compact and result in a transect or transition to even less compact housing form
- The East Neighborhood has its Type 1 housing in the central area adjacent to the Brisband Main Street, future Frog Pond East Neighborhood Park and BPA Easement
- The South Neighborhood has a small node of Type 1 housing located south of the Meridian Middle School property.
- In both neighborhoods, Type 2 and 3 housing form “feathers out” from the Type 1 areas.

A WIDE VARIETY OF HOUSING CHOICES

- Opportunities for a wide spectrum of housing choices: townhomes, quadplexes, tri-plexes, duplexes, cottage clusters, cottage developments, small-lot detached homes, medium and larger lot detached homes, accessory dwelling units, apartments/condos, tiny homes and co-housing
- Requirements for a mix of housing choices in each subdistrict
- Housing capacity for an estimated minimum of 1587 dwellings (See Chapter 6 for housing and land use metrics)





LAND USE

RESIDENTIAL LAND USE AND URBAN FORM

KEY OUTCOMES

The Land Use and Urban Form Plan includes residential areas intended to create three key outcomes:

- **A variety of housing choices** throughout the East and South Neighborhoods
- **Opportunities for affordable housing choices** integrated into the neighborhoods
- A planned **“transect”** of housing form in order to create a cohesive neighborhood that maximizes the amenities available to residents while creating an urban form sensitive to the local context.

VARIETY THROUGHOUT

The Master Plan creates opportunities for a wide variety of housing choices in each neighborhood and subdistrict. This concept focuses on mixing and integrating different housing choices throughout each subdistrict and block rather than having separate areas for separate types of housing units.

The plan defines and maps three types of urban form for housing – Types 1, 2, and 3 – that define the look and feel of the different subdistricts within the neighborhoods. The focus of this typology is urban form: the bulk, height and spacing of buildings. Each urban form type allows for a full array of housing choices.

For example, a detached home may exist in any of the urban form types, but for Type 1 it would have a smaller footprint and, be closer to adjoining homes, and for Type 3 it would have a larger footprint and be farther apart from adjoining homes. Building height will also tend to be taller where Type 1 is designated with height trending down in areas with Type 2 and Type 3 building form. A multi-family building also may exist in any of the urban forms, but for Type 1 the building would be taller and wider with more units per building and closer to adjoining buildings. For Type 3, a multi-family building would be shorter and smaller (similar to the size of a larger single-family home) with fewer units per building, and buildings would be further apart, likely interspersed with single-family homes.



LAND USE

TYPE 1 RESIDENTIAL URBAN FORM

Type 1 residential urban form is the most compact and urban of the three forms:

- Buildings 2-4 stories tall close to the street
- Buildings are closely spaced from each other
- Townhouse, condo/apartment buildings, and similar are not limited in width allowing larger buildings that may even occupy an entire block face
- Lot area per building for detached homes will be small with less yard space than in Type 2 and Type 3
- Townhouses, closely spaced detached homes, and multi-family buildings are expected to be common housing choices provided; cottages or similar small-unit housing is also likely to be built





LAND USE

TYPE 2 RESIDENTIAL URBAN FORM

Type 2 residential urban form is less compact than Type 1 but more compact than Type 3:

- Buildings are intended to be 2 stories, with 3 stories allowed under applicable State law for certain housing categories
- Moderate setbacks from the street
- Building separation is generally 10 feet,
- Building width is moderately limited, to maintain a building bulk consistent among multi-family, middle housing, and single-family detached housing choices
- Detached home lot size is approximately double that of Type 1 allowing for larger home footprints and larger yards than Type 1
- Small to medium sized single-family detached homes and townhouses are expected to be common housing choices, with duplexes, triplexes, quadplexes, cottage clusters, and smaller multi-family buildings also likely to be built.





LAND USE

TYPE 3 RESIDENTIAL URBAN FORM

Type 3 is the least compact residential urban form, characteristics include:

- Buildings primarily 1-2 stories in height, with 3 stories allowed for certain housing categories consistent with applicable State law
- Buildings are set back from the street
- Width of buildings is limited to create smaller buildings, which limits the number of units in multifamily or middle housing structures
- Building separation generally more than 10 feet
- Lot size for detached single-family homes generally 1.5 times that of Type 2 and 3 times that of Type 1, allowing for larger homes and yards
- Medium to large single-family detached homes along with smaller townhouse and duplex buildings are expected to be common housing choices, cottage clusters would be well-suited to this Type, and triplexes, quadplexes, and small multi-family buildings may also be built





PUBLIC REALM

GREEN FOCAL POINTS

In addition to the planned Community Park in Frog Pond South and the Neighborhood Park in Frog Pond East, several “green focal points” are identified in central locations within each walkable subdistrict of the planning area. These are flexible in location and size but are intended to serve as central neighborhood destinations or gathering places that contribute to neighborhood character and identity. In addition to being centrally located, these focal points will be integrated into the neighborhood with front doors facing them, where possible, and provide clear and inviting access for public use.

Many different kinds of uses and activities are envisioned for the green focal points. Examples include community garden plots, small playgrounds or splash pads, nature play areas, pocket parks or plazas, and central green courtyards within housing developments. These smaller open spaces also provide opportunities to preserve mature and significant trees and provide visible stormwater treatment.





IMPLEMENTATION

IMPLEMENTATION MEASURE 4.1.7.D

Implementation of the Frog Pond East & South Master Plan will include the following:

1. Designation and mapping of subdistricts. Subdistricts are smaller geographic areas within each neighborhood where specific regulations may be applied to implement the Master Plan.
2. Clear and objective Development Code standards that:
 - a. Set minimum number of units at the subdistrict or tax lot level.
 - b. Establish height, setback and other development standards for the Type 1, Type 2, and Type 3 Urban Forms described and mapped in the Frog Pond East & South Master Plan.
 - c. Require a variety of housing and include minimum and maximum amounts of specific housing types at the subdistrict or tax lot level.
 - d. Require middle housing.
3. Zoning provisions that provide an alternative path of discretionary review to provide flexibility for development while still achieving the intent of the Master Plan and Development Code.
 - a. The alternative path will include criteria to guide flexibility from the clear and objective height, setback, and other similar development standards for buildings in specific urban design contexts.
4. Define categories of housing for use in implementing housing variety standards.
5. Coordination with the owners of the Frog Pond Grange to coordinate and support continued use and development of the Grange as a community destination. Any future public ownership or use of the Grange building is dependent on future funding not yet identified.
6. Coordination with the Bonneville Power Administration (BPA) on land use and development within their easement in the East Neighborhood.
7. A future study of design options for the creek crossings shown on the Park and Open Space plan in this Master Plan. This work will address potential structured crossings.
8. The City may initiate a Main Street study to evaluate specific designs and implementation for the SW Brisband Main Street.
9. Special provisions will be in place for design of both the public realm and private development along the east side of SW Stafford Road and SW Advance Road and surrounding the East Neighborhood Park.



IMPLEMENTATION

- a. On the east side of SW Stafford Road provisions will combine blending the brick wall design used in Frog Pond West and the desire to have structures have a presence fronting SW Stafford Road with access to the protected sidewalk and bicycle path. These provisions will include:
 - i. Requiring structures, besides those fronting the SW Brisband Main Street, to have pedestrian access and entrances facing SW Stafford Road;
 - ii. Requiring courtyard-style brick fences matching the materials used along the edges of Frog Pond West, except being approximately half the height, with buildings setback to create usable courtyard areas;
 - iii. Requiring three-story structures, or two-story equivalent to three story-height, along Stafford Road between SW Advance Road and the SW Brisband Main Street and for one block north of the SW Brisband Main Street. This will ensure structures have a visual presence on SW Stafford Road while not dominating the streetscape and provide a gradual design transition from the four-story structures on SW Brisband.
 - b. SW Advance Road provisions will be added to require residential structure orientation, including main entrance, to SW Advance Road. This provision intends to ensure SW Advance is integrated into the design of the development like other collectors in the area such as SW Willow Creek Drive in Frog Pond West. The provisions also ensure homes on the north side of SW Advance across from the community park face the community park.
 - c. Provisions will require development around the East Neighborhood Park to orient as to have an active side of the development facing the park.
- 10.** The Master Plan shows the entire area between streams just below where SW Kahle Road forks as SROZ based on existing tree canopy. According to the property owner a portion of this area may have been planted as agricultural trees and may not meet criteria to be SROZ. The City will coordinate with the property owner to further evaluate if a portion of this area is developable or if it should remain in the SROZ. If it is found to be developable, code provisions will allow it to be developed consistent with Type 3 Urban Design standards.
- 11.** Standards that ensure private yard spaces, particularly for closely spaced detached homes, are of a size and design that are usable, accessible, and practical to maintain.



IMPLEMENTATION

ZONING IMPLEMENTATION

ZONING MAP AMENDMENTS AND IMPLEMENTATION

Table 7 lists the zone districts that will implement each of the Comprehensive Plan designations identified within the planning area.

Table 7. Implementing Zoning Designations

COMPREHENSIVE PLAN DESIGNATION	IMPLEMENTING ZONE
Residential Neighborhood	Residential Neighborhood (RN)
Commercial	Planned Development Commercial (PDC)
Public	Public Facilities (PF)
All, where applicable	Significant Resource Overlay Zone (SROZ)

Zoning will be applied concurrent with the annexation and development review process for individual properties.

CODING FOR VARIETY AND PRIORITY HOUSING TYPES

Providing a variety of housing types, and particular housing types, throughout the East and South neighborhoods are important intended outcomes for the Master Plan. There are many examples of how variety and specific housing is designed and delivered in master planned communities such as Northwest Crossing in Bend and like Villebois here in Wilsonville. In those communities, a master developer defines and maps the planned housing types at a very site-specific level such as individual lots or blocks. Master planned communities can also implement specific and strategic phasing of infrastructure and housing types.

The Frog Pond East & South Master Plan aspires to have the detailed variety of a master planned community like Villebois even though it does not have the oversight of a single master developer. There is an opportunity to require and encourage housing that is a priority for the City. Examples include: home ownership opportunities for households of modest income (80-120% of AMI), middle housing units, dwellings that provide for ground floor living (full kitchen, bath and master bedroom on the main floor), and dwellings that provide for ADA³ accessibility.

The standards for Frog Pond’s housing variety will also recognize and accommodate several development realities:

3 Americans with Disabilities Act (1990).



IMPLEMENTATION

- The neighborhoods will develop incrementally. There may be several larger projects where a developer prepares a coordinated plan for relatively large areas (e.g. 20+ acres). However, there will also be many smaller developments that will occur by different developers, on varied parcel sizes, and at different points of time. The code’s variety standards must work for the likely range of differently scaled projects.
- Flexibility will be needed for evolving market and housing needs over time, including to reflect the City’s future Housing Needs Analyses and Housing Production Strategies..
- All standards that address housing must be clear and objective. A discretionary review path can be provided as an alternative to provide additional flexibility.

Below is a list of potential strategies for requiring variety throughout Frog Pond East and South. These show the intent of the implementing standards and are subject to refinement or change as the development code is prepared.

Strategy 1: Permit a wide variety of housing types.

Amend the RN Zone to allow the following types in Frog Pond East and South:

- Single-Family Dwelling Units⁴
- Townhouses
- Duplex, Triplex, and Quadplex
- Cluster Housing
- Multiple-Family Dwelling Units
- Cohousing
- Manufactured Dwellings⁵
- Accessory Dwelling Units

Strategy 2: Define “categories” of housing units to be used for implementing variety standards.

Each category would provide a range of housing units to choose from when meeting the variety standards. The categories will be based on the policy objectives of the Council for equitable housing opportunities. They will also include specific housing types desired by the City (e.g. accessory dwelling units). The categories will be defined as part of the development code.

4 Tiny homes are included in this use type
5 Manufactured dwellings are subject to the definitions and requirements of ORS 443.



IMPLEMENTATION

Strategy 3: Establish minimum dwelling unit requirements

Establish the minimum number of dwelling units required in each subdistrict (or on each pre-existing tax lot). The minimum number of required dwellings will help ensure the provision of attached housing forms.

Minimum number of dwelling unit requirements helps ensure variety by preventing a lower production of units than anticipated by the Master Plan. The unit count anticipated in the Master Plan assumes a variety of housing and meeting the minimum is not anticipated to be met without provision of a variety of housing.

Note: The housing capacity estimates prepared for the Master Plan could be used as the basis for the minimums.

Strategy 4: Create development standards for lots and structures that regulate built form according to the mapped Type 1, Type 2, and Type 3 urban form typologies.

This strategy uses form-based standards to create the transect of most compact urban form in Type 1 areas to least compact urban form in Type 3 areas. For each of the Urban form types, define standards for:

- Minimum lot size
- Minimum lot width/street frontage
- Maximum height setbacks for front, side, and rear yards, and garages
- Minimum building spacing
- Maximum lot coverage
- Maximum building width

Strategy 5: Establish minimum housing variety standards by subdistrict and development area.

For each subdistrict (or existing tax lots within subdistricts), define:

- The minimum number of categories required. This standard ensures variety at the subdistrict or tax lot level.
- The maximum percent of net development area for a category. This standard ensures no single category dominates a subdistrict.
- The minimum percent of net development area for categories that represent more affordable and/or accessible housing choices not traditionally provided by the private market and meeting City housing objectives..

Strategy 6: Encourage variety at the block level



IMPLEMENTATION

Housing variety on the block level prevents segregation of housing types that often subsequently segregates populations by economic status. Code provisions, likely incentives but potentially requirements, related to the percent of net area of blocks by housing category will help ensure a fine grained variety of housing type and integration of lower cost housing.

CODING FOR MAIN STREET

The Brisband Main Street received very strong support in open houses, focus groups, tabling events and surveys for the Master Plan. Community members were excited that Main Street could become a walkable and attractive destination with restaurants, shops and services.

Wilsonville has existing and future models of the type of pedestrian-oriented commercial center envisioned for the Frog Pond's Main Street. The village center in Villebois is an anchor point for that community with its well-designed public realm, higher density housing, mixed-use, and strong connections to the adjacent neighborhoods. Wilsonville's Town Center Main Street is a central element of the Town Center Plan and will include attractive streetscapes, mixed-use buildings, and three-to-four story building form.

To achieve the vision for the Brisband Main Street, the following design and development strategies for the Brisband Main Street will be implemented:

- Permit neighborhood-scale retail, services, mixed-use, multi-family residential
- Prohibit drive-through uses and facilities
- Adopt development standards such as:
 - › Shallow setbacks to bring buildings close to Main Street's sidewalks
 - › Up to 4-story building height

"The overall vision for the neighborhood commercial center is that it is a place that provides local goods and services within easy access of the local neighborhoods, has a high quality and pedestrian-oriented design, and serves as a gathering place for the community. Due to its small scale and local orientation, it will not compete with other commercial areas in Wilsonville."

— Frog Pond Area Plan



IMPLEMENTATION

- › Tall ground floors to emphasize storefront character
- › Building frontages that occupy a high percentage of the block faces along Main Street
- Adopt design standards such as:
 - › Primary entrances oriented to Brisband or its intersections
 - › Front setback areas designed for pedestrian use
 - › Parking to the sides or rears of buildings
 - › Small plazas designed as an accessible amenity
 - › Weather protection (awnings and/or canopies) along sidewalks
 - › Building articulation, fenestration, and materials that make Main Street an attractive place and contribute to the vitality of the street environment

The City may initiate a design study for Main Street to evaluate detailed public realm improvements and coordinate them with private development.



Frog Pond East and South Implementation

Draft Development Code Amendments for March 2023 Work Session

1. Design criteria for Brisband Main Street

- **Intent:** Provide detailed standards for the Main Street
- **Explanation:** Incorporate appropriate standards from TC zone
- **Code Reference:** Subsection 4.127 (.03) *Residential Neighborhood Zone-Permitted and Prohibited Uses* and new Subsection 4.127 (.24) *Residential Neighborhood Zone-Commercial Main Street Development Standards*
- **Draft Code Amendment:**

(.03) *Permitted and prohibited uses in the Frog Pond East and South Neighborhoods:*

[...]

C. *Uses permitted in the Commercial Main Street Area:*

1. Retail sales and service of retail products, under a footprint of 30,000 square feet per use.
2. Office, including medical facilities.
3. Personal and professional services.
4. Child and/or day care.
5. Food service (e.g., restaurants, food carts, food cart pods).
6. Beverage service (e.g., cafes, brewpubs, bars).
7. Community services and community centers.
8. Residential dwellings, except that no more than XX% of the ground floor of any building may be residential dwellings.

D. *Uses prohibited in the Commercial Main Street Area:*

1. Uses with drive-through facilities (e.g., fast food, banks, car wash) are prohibited.

(.XX) *Development Standards.* The following development standards apply to all development within the Commercial Main Street area of Frog Pond East.

Table XX. Commercial Main Street Development Standards	
STANDARD	
Front setback	
Minimum	0 ft.
Maximum	20 ft.
Side facing street on corner	
Minimum	0 ft.
Maximum	10 ft.

Side yard	
Minimum	0 ft.
Maximum	10 ft.
Rear setback	
Minimum	0 ft.
Building height (stories) ^A	
Minimum	two
Maximum	four
Ground floor height minimum	12 ft.
Building site coverage maximum	90%
Minimum landscaping	10%
Minimum building frontage ^B	
On SW Brisband Street	70%
On SW Stafford Road	50%
On other streets	None

^A Second stories or higher in buildings must be useable. No false front buildings are permitted.

^B To meet the minimum building frontage requirement, the ground level street-facing façade must meet the maximum setback standard for a minimum of 70% of the lot length on SW Brisband Street and a minimum of 50% of the lot length on SW Stafford Road.

(.20) *Design Standards for the Commercial Main Street Designation in Frog Pond East and South:*

- A. *Purpose and Intent.* The purpose of the design standards is to provide high quality design within the Commercial Main Street area that creates a place of distinct character. The design of buildings and other site features shall functionally relate to adjacent streets and open spaces; shall include architectural diversity and variety in their built form; shall contribute to the vitality of the street environment through incorporation of storefronts, windows, and entrances facing the sidewalk; and shall minimize the visual impact of off-street parking from streets.
- B. *Building and Entry Placement.* Buildings shall meet the following standards:
 1. Development shall meet the minimum building frontage standards in Table XX.
 2. At least one entrance door is required for each business, including live-work units, with a ground floor frontage.
 3. All primary ground-floor common entrances shall be oriented to the street or a public space directly facing the street, or placed at an angle up to 45 degrees from an adjacent street. Primary ground-

floor common entrances shall not be oriented to the interior or to a parking lot.

4. If a parcel has frontage on more than one street, the primary building entrance is encouraged to orient to the street intersection. If the parcel has frontage on Brisband Street, the primary entrance shall orient to Brisband Street or to the intersection.
 5. Courtyards, plazas and similar entrance features may be utilized to satisfy the building entrance requirement when these features are designed to connect the adjacent street edge to the primary building entrance. A direct pedestrian walkway not exceeding 20 feet in length shall be provided between the building entrance and the street property line.
 6. Each entrance shall be covered, recessed, or treated with a permanent architectural feature in such a way that weather protection is provided.
- C. *Building Setbacks.* Development shall meet the minimum and maximum setback standards in subsection 4.127(.XX). No off-street vehicle parking or loading is permitted within the setback. Bicycle parking is permitted within the setback.
- D. *Front Yard Setback Design.* If front yard setbacks are provided, they shall be designed to encourage pedestrian activity and active ground floor uses. Landscaping, water quality treatment, seating areas, an arcade, or a hard-surfaced expansion of the pedestrian path must be provided between a structure and a public street or accessway. If a building abuts more than one street, the required improvements shall be provided on all streets. Hard-surfaced areas shall be constructed with scored concrete or modular paving materials. Benches and other street furnishings are encouraged.
- E. *Walkway Connection to Building Entrances.* A walkway connection is required between a building's primary entrance and a public street or accessway. This walkway must be at least six feet wide and be paved with concrete or modular paving materials.
- F. *Parking Location and Landscape Design:*
1. Parking for buildings adjacent to public street rights-of-way must be located to the side or rear of buildings, except for buildings fronting Brisband Street or Stafford Road, where parking must be located behind the building, either surface, tuck under or structured (above or below grade).
 2. For locations where parking may be located to the side of the building, parking is limited to 50 percent of the street frontage (provided minimum building frontage standards are also met), and must be behind a landscaped area per Section 4.176.
 2. Within off-street parking lots, all parking spaces, except for those designated for ADA accessible space or deliveries, shall be shared spaces. Designation for individual uses is not permitted.

3. Within off-street parking lots, time limitations may be placed on parking spaces to encourage parking turnover. This includes time limitations to pick up and drop off of goods from area businesses (e.g. drycleaner, bank ATM etc.).

G. *Building Design Standards:*

1. *General Provisions:*

- a. The first-floor façade of all buildings shall be designed to encourage and complement pedestrian-scale interest and activity through the use of elements such as windows, awnings, and other similar features.
- b. Building entrances shall be clearly marked, provide weather covering, and incorporate architectural features of the building.
- c. Architectural features and treatments shall not be limited to a single façade. All public-facing facades shall display a similar level of quality and architectural interest, with elements such as windows, awnings, murals, a variety of exterior materials, reveals, and other similar features.

2. *Design Standards.* All buildings shall comply with the following design standards:

a. *Windows:*

- i. Building facade windows are required on all facades facing SW Brisband Street or SW Stafford Road (see Figure 1), as follows:

Ground Story facing SW Brisband Street	60% of ground floor wall area
Ground Story facing SW Stafford Road	40% of ground floor wall area
Upper Stories facing SW Brisband Street or SW Stafford Road	20% of facade
Other facades	No minimum

- ii. Window area is the aggregate area of the glass within each window, including any interior grids, mullions, or transoms. Facade area is the aggregate area of each street-facing vertical wall plane.
- iii. Required windows shall be clear glass and not mirrored or frosted, except for bathrooms. Clear glass within doors may be counted toward meeting the window coverage standard.
- iv. *Ground floor windows.* For facades facing SW Brisband Street and SW Stafford Road, elevations within the building setback shall include a minimum percentage of the ground floor wall area with windows, display areas or doorway openings, as required in subsection i. The ground floor wall area shall be measured from two feet above grade to ten feet above grade for the entire width of the street-facing elevation. The ground floor

window requirement shall be met within the ground floor wall area; glass doorway openings to ground level may be counted toward meeting the requirement. Up to 50 percent of the ground floor window requirement may be met on an adjoining elevation within 20 feet of the building corner. (Note: Figure to be added to illustrate this requirement)

b. *Building Facades:*

- i. Public-facing facades shall extend no more than 50 feet without providing at least one of the following features:
 - (a) a variation in building materials;
 - (b) a building off-set of at least one foot;
 - (c) a wall area that is entirely separated from other wall areas by a projection, such as an arcade;
 - or (d) by other design features that reflect the building's structural system (See Figure 2).No building façade shall extend for more than 250 feet without a pedestrian connection between or through the building.

Figure 1. Window Placement and Percentage of Facade





Figure 2. Building Facade Articulation




- c. *Weather Protection*: Building facades facing SW Brisband Street shall provide weather protection as follows:
- i. A projecting facade element (awning, canopy, arcade, or marquee) must be provided along at least 75 percent of the façade.
 - ii. All weather protection must comply with the Oregon Structural Specialty Code in effect at the time of application for projections or encroachments into the public right-of-way.
 - iii. Weather protection shall be maintained and in good condition.
 - iv. Weather protection features shall project at least five feet from the building façade.
 - v. Marquees shall have a minimum ten-foot clearance from the bottom of the marquee to the sidewalk. Canopies and awnings shall have a minimum eight-foot clearance from the bottom of the awning or canopy to the sidewalk. (See Figure 3.)
 - vi. The projecting façade element shall not conflict with street lights. If the projecting façade element blocks light shed from adjacent street lights, exterior lighting shall be located on the building.
 - vii. Awnings shall match the width of storefronts or window openings.
 - viii. Internally lit awnings are not permitted.
 - ix. Awnings shall be made of glass, metal, or a combination of these materials. Fabric awnings are not permitted.
- d. *Building Materials*. Plain concrete block, plain concrete, T-111 or similar sheet materials, corrugated metal, plywood, sheet press board or vinyl siding may not be used as exterior finish materials. Foundation material may be plain concrete or plain concrete block where the foundation material is not revealed for more than two feet. Use of brick and natural materials (wood) is encouraged.

- e. *Roofs and roof lines.* Except in the case of a building entrance feature, roofs shall be designed as an extension of the primary materials used for the building and should respect the building's structural system and architectural style. False fronts and false roofs are not permitted.
- f. *Rooftop features/equipment screening:*
 - i. The following rooftop equipment does not require screening:
 - Solar panels, wind generators, and green roof features;
 - Equipment under two feet in height.
 - ii. Elevator mechanical equipment may extend above the height limit a maximum of 16 feet provided that the mechanical shaft is incorporated into the architecture of the building.
 - iii. Satellite dishes and other communications equipment shall be limited to ten feet in height from the roof, shall be set back a minimum of five feet from the roof edge and screened from public view to the extent possible.
 - iv. All other roof-mounted mechanical equipment shall be limited to ten feet in height, shall be set back a minimum of five feet from the roof edge and screened from public view and from views from adjacent buildings.
 - v. On all structures exceeding 35 feet in height, roofs shall have drainage systems that are architecturally integrated into the building design.
 - vi. Any external stairwells, corridors and circulation components of a building shall be architecturally compatible with the overall structure, through the use of similar materials, colors, and other building elements.
 - vii. Required screening shall not be included in the building's maximum height calculation.
- g. *General Screening.* Utility meters shall be located on the back or side of a building, screened from view from a public street to the greatest extent possible, and shall be painted a color to blend with the building façade.
- h. *Building projections.* Building projections are allowed as follows (see Figure 3):
 - i. Architectural elements such as eaves, cornices and cornices may project up to one foot from the face of the building.
 - ii. Bay windows and balconies may project up to four feet from the face of the building. Balconies that project into the right-of-way shall have a minimum vertical

- clearance of 12 feet from sidewalk grade or be mounted at the floor elevation, whichever is greater.
- iii. See also Subsection 4.127(.20)XX. for standards related to weather protection.

Figure 3. Building Projections



2. *Clear and objective standards for multi-family*

- **Intent:** Provide clear and objective standards for multi-family similar to single-family and middle housing. Note, proposed multi-family buildings/uses that are not part of an approved subdivision or Master Plan, still need to go through the Stage I/Stage II Master Plan development review process. The intent of the proposed standards is to change the review criteria and process that applies to architectural review and basic site planning review such as setback and lot coverage for multi-family buildings where the use has already received a master plan approval.
- **Explanation:** Adapt and modify current standards for townhouses to apply to multi-family.
- **Code Reference:** Subsection 4.113 (.14) *Residential Design Standards*, new subsection for multi-family)
- **Draft Code Amendment:**

(.15) *Design Standards for Multi-Family Housing:*

A. *Purpose and Intent.* The purpose of the multi-family design standards is to create and maintain street frontages that are varied and attractive, create an environment that is conducive to walking, and provide natural surveillance of public spaces. The standards will also promote building details in multi-family development that provide visual interest, contribute to a high-quality living environment for residents, give a sense of quality and permanence, and enhance compatibility with the surrounding community. The design standards also aim to create consistency with design standards for other residential unit types that multi-family housing may be built adjacent to.

B. *Entrance Orientation.*

1. At least one main entrance for each multi-family structure must either meet the standards in subsections a. and b. below, or must meet the alternative standard in subsection B.2.
 - a. The entrance must be within eight feet of the longest street-facing exterior wall of the structure; and
 - b. The entrance must either:
 - i. Face the street;
 - ii. Be at an angle of up to 45 degrees from the street; or
 - iii. Open onto a porch. The porch must:
 - a. Be at least 25 square feet in area; and
 - b. Have at least one entrance facing the street or have a roof.
2. Alternative standard. As an alternative to subsection 1., a main entrance to a multi-family structure may face a courtyard if the courtyard-facing entrance is located within 60 feet of a street and the courtyard meets the following standards:
 - a. The courtyard must be at least 15 feet in width;

- b. The courtyard must abut a street; and
- c. The courtyard must be landscaped or hard-surfaced for use by pedestrians.
- C. *Windows.* A minimum of 15 percent of the area of all public-facing façades must include windows or entrance doors. Façades separated from the street or public space by a dwelling are exempt from meeting this standard. Required windows shall be clear glass and not mirrored or frosted, except for bathrooms.
- D. *Articulation.*
 - 1. *Minimum Articulation.* All public-facing façades shall incorporate the following design elements at a minimum interval of every 30 feet. The minimum number of design elements is determined by dividing the façade length (in feet) by 30 and rounding up to the nearest whole number.
 - a. Varying rooflines.
 - b. Offsets of at least 12 inches.
 - c. Balconies.
 - d. Projections of at least 12 inches and width of at least three feet.
 - e. Porches.
 - f. Entrances that are recessed at least 24 inches or covered.
 - g. Dormers at least three feet wide.
 - 2. *Articulation Element Variety.* Different articulation elements shall be used as provided below, based on the length of the facade. For the purpose of this standard, a "different element" is defined as one of the following: a completely different element from the list in subsection D.1. above; the same type of element but at least 50 percent larger; or for varying rooflines, vertically offset by at least three feet.
 - a. Where two to four elements are required on a façade, at least two different elements shall be used.
 - b. Where more than four elements are required on a façade, at least three different elements shall be used.
- F. *Pedestrian Access and Circulation.* The following standards are intended to ensure safe and efficient circulation for pedestrians within multi-family development.
 - 1. Each multi-family development shall contain an internal pedestrian circulation system that makes connections between individual units and parking areas, green focal points and other common open space areas, children's play areas, and public rights-of-way. All pedestrian connections (walkways) shall meet the following standards:
 - a. Except as required for crosswalks, per subsection 3., where a walkway abuts a vehicle circulation area, it shall be physically separated by a curb that is raised at least six inches or by bollards.

- b. Walkways shall be constructed of concrete, asphalt, brick or masonry pavers, or other hard surface, and not less than five feet wide.
 2. All walkways shall comply with the requirements of the Americans with Disabilities Act.
 3. In order to provide safe crossings of driveways and parking areas, crossings shall be clearly marked with either contrasting paving materials (such as pavers, light-color concrete inlay between asphalt, or similar contrasting material) or reflective striping that emphasizes the crossing under low light and inclement weather conditions.
 4. Pedestrian connections shall be provided between buildings within the development, and between the development and adjacent rights-of-way, transit stops, parks, schools, and commercial developments. At least one connection shall be made to each adjacent street and sidewalk for every 200 linear feet of street frontage. Sites with less than 200 linear feet of street frontage shall provide at least one connection to the street and/or sidewalk.
- F. *Off-Street Parking Location and Design.* The following standards are intended to support a pedestrian-friendly street environment and to minimizing the visual impacts of parking areas and garages.
1. Off-street parking spaces and vehicle maneuvering areas shall not be located between the front building plane and a street property line (except alleys).
 2. Off-street parking areas shall not occupy more than 50% of the total length of each street frontage as measured 20 feet from the street property line. Drive aisles without adjacent parking spaces do not count as parking areas for the purposes of this standard.
 3. Off-street parking spaces shall not be located within ten feet of any property line, except alley property lines. Driveways and drive aisles are permitted within ten feet of property lines.
 4. Landscaping, fencing, or walls at least three feet tall shall separate parking areas from useable open space, green focal points, and public streets (except alleys).
 5. If garages are attached to a street-facing facade, they may not be located closer to the street property line than the building facade.
 6. Driveways associated with attached garages that take direct individual access from a public or private street must meet the townhouse driveway and access standards in Subsection 4.113 (.14) 5. For the purpose of those standards, each individual multi-family garage shall meet the standards applicable to a townhouse or townhouse lot.

3. Process Updates for Multi-family Housing

- **Intent:** Improve language throughout code to clarify and update review process for multi-family housing in residential zones.
- **Explanation:** Review and update language throughout Development Code to make process to review multi-family housing in residential zones substantially similar to the process for single-family and middle housing. Additional section-specific explanations are provided below.
- **Code Reference:** various
- **Draft Code Amendments:**

Modified language (changes ~~struckthrough~~ or **bold underlined**)

Section 4.030 Jurisdiction and Powers of Planning Director and Community Development Director

Explanation: Add clarity for the review process for architecture review of middle housing. Draft reflects Planning Commission discussion in January about DRB not being the appropriate place for review, but larger buildings should still provide public notice. Current draft has smaller apartment buildings (6 or fewer units) follow the same process as middle housing (Class I Review, staff decision with no public notice) and larger buildings being subject to Class II Review (staff decision with public notice and notice to DRB).

(.01) *Authority of Planning Director.* The Planning Director shall have authority over the daily administration and enforcement of the provisions of this Chapter, including dealing with non-discretionary matters, and shall have specific authority as follows:

- A. A Class I application shall be processed as a ministerial action without public hearing, shall not require public notice, and shall not be subject to appeal or call-up, except as noted below. Pursuant to Class I procedures set forth in Section 4.035, and upon finding that a proposal is consistent with the provisions of this Code and any applicable Conditions of Approval, shall approve the following, with or without conditions:
 4. Building permits for **residential structures in residential zones not subject to Site Design Review, except for multi-family structures with seven or more units**, ~~single family dwellings, middle housing, and in the Village zone, row houses or apartments,~~ meeting clear and objective zoning, siting, and design requirements standards and located on lots that have been legally created. The Planning Director's approval of such plans shall apply only to Development Code requirements and shall not alter the authority of the Building Official or City Engineer on these matters.

- B. A Class II application shall be processed as an administrative action, with or without a public hearing, shall require public notice, and shall be subject to appeal or call-up, as noted below. Pursuant to Class II procedures set forth in Section 4.035, the Director shall approve, approve with conditions, deny, or refer the application to the Development Review Board for a hearing:
12. **Architectural and site plans, including modifications and remodels, for multi-family residential structures in residential zones with seven or more units not subject to Site Design Review and meeting clear and objective zoning, siting, and design standards and located on lots that have been legally created. This does not include review of Stage I and Stage II Planned Development Master Plans and Site Design Review of open space and other common improvements, which is subject to review by the Development Review Board.**

Subsection 4.176 (.04) Buffering and Screening

Explanation: Remove requirement for screening and buffering between single-family and multi-family as new standards and allow and encourage them to be integrated.

- B. Activity areas on commercial and industrial sites shall be buffered and screened from adjacent residential areas. ~~Multi-family developments shall be screened and buffered from single-family areas.~~

Section 4.113 (.01) Residential Open Space Standards

Explanation: Clarify that a multi-family development does not need to provide additional open space when it is part of a larger development. Makes the requirement consistent with those for single-family and middle housing.

- B. *Applicability.*
1. The open space standards of this subsection shall apply to the following:
 - a. Subdivisions.
 - b. Planned Developments.
 - c. Multi-family Development, **except as noted in 2. c. below.**
 2. These standards do not apply to the following:
 - a. Partitions for non-Multi-family development. However, serial or adjacent partitions shall not be used to avoid the requirements.
 - b. Middle Housing Land Divisions.
 - c. **Development of a multi-family building(s) on a lot within a subdivision where the open space requirements are**

otherwise met in the subdivision, as acknowledged in a prior land use approval.

4. Discretionary alternative path standards

- **Intent:** Provide guidance to both applicants and decision-makers for waivers that are sought through the discretionary review process.
- **Explanation:** Provide factors for DRB to consider during discretionary review.
- **Code Reference:** Subsection 4.118 (.03) A List of Development Standards Typically Subject to Waivers. Add new subsection 4.127 (.23).
- **Draft Code Amendment:**

Modified language (changes ~~struckthrough~~ or **bold underlined**)

4.118 Standards Applying to all Planned Development Zones

- (.03) Notwithstanding the provisions of Section 4.140 to the contrary, the Development Review Board, in order to implement the purposes and objectives of Section 4.140, and based on findings of fact supported by the record may:
- A. Waive the following typical development standards:

...
13. Architectural design standards, **including residential design standards;**

Note: More extensive proposed amendments to Section 4.420 are shown below for context, with the portion specifically related to alternative review process highlighted.

Section 4.420. ~~Jurisdiction and Powers of the Board~~ **Review Authority for Site Design Review**

- (.01) ~~Application of Section. Except for single-family and middle housing dwellings in any residential zoning district, and apartments in the Village zone,~~
- A. **Unless exempt as noted in 1.-2. below,** no building permit shall be issued for a new building or major exterior remodeling of an existing building **unless the building architecture and siting is approved by the Development Review Board (Board) through Site Design Review.**
1. **Residential structures in residential zones are exempt from Site Design Review as long as they meet established clear and objective design and**

- siting standards. This exemption does not apply to mixed-use residential structures. However, an applicant may elect to have residential structures approved by the Board through Site Design Review in association with waivers from specific standards.**
2. **Minor building modifications to non-residential structures are reviewed under the authority of the Planning Director as established in Section 4.030.**
- B. **Unless exempt as noted in 1.-2. below, no building permit within an area covered by a Stage II Planned Development, or PDP in the Village Zone, shall be granted unless landscaping plans are reviewed and approved by the Board through Site Design review, or FDP in the Village Zone.**
1. **Landscaping on residential lots in residential zones is exempt from Site Design Review unless it is part of the open space required under Subsection 4.113 (.01).**
 2. **Minor modifications to landscape plans subject to Site Design Review can be reviewed by the Planning Director as established in Section 4.030.**
- C. No Sign Permit, except as permitted in Sections 4.156.02 and 4.156.05, shall be issued for the erection or construction of a sign relating to such new building or major remodeling, until the plans, drawings, sketches and other documents required for a Sign Permit application have been reviewed and approved by the Board.

The following is proposed new language:

Section 4.127 Residential Neighborhood Zone

- (.23) *Consideration of Waivers in the Frog Pond East and South Neighborhoods.*
- A. Applicants for development in the Frog Pond East and South neighborhoods may request waivers to applicable development and design standards in Section 4.127, provided the criteria in subsection B. are met.
 - B. In addition to the waiver criteria in Sections 4.118 and 4.140 and applicable Site Design Review standards, when reviewing a

waiver for development within the Frog Pond East and South Neighborhoods the Development Review Board's decision shall be based on the following criteria, which reflects guidance in the Frog Pond East and South Master Plan.

1. The development enabled by the waiver is complementary and compatible with development that would typically be built within the subject Urban Form Type as described in Chapter 6 of the Frog Pond East and South Master Plan.
2. The waiver supports a wide variety of housing or at least does not reduce the level of housing variety within a Stage I Master Plan Area.

Section 4.127. Residential Neighborhood (RN) Zone.

(.01) *Purpose.* The Residential Neighborhood (RN) zone applies to lands within Residential Neighborhood Comprehensive Plan Map designation. The RN zone is a Planned Development zone, subject to applicable Planned Development regulations, except as superseded by this section or in legislative master plans. The purposes of the RN Zone are to:

- A. Implement the Residential Neighborhood policies and implementation measures of the Comprehensive Plan.
- B. Implement legislative master plans for areas within the Residential Neighborhood Comprehensive Plan Map designation.
- C. Create attractive and connected neighborhoods in Wilsonville.
- D. Regulate and coordinate development to result in cohesive neighborhoods that include: walkable and active streets; a variety of housing appropriate to each neighborhood; connected paths and open spaces; parks and other non-residential uses that are focal points for the community; and, connections to and integration with the larger Wilsonville community.
- E. Encourage and require quality architectural and community design as defined by the Comprehensive Plan and applicable legislative master plans.
- F. Provide transportation choices, including active transportation options.
- G. Preserve and enhance natural resources so that they are an asset to the neighborhoods, and there is visual and physical access to nature.
- H. Create housing opportunities for a variety of households, including housing types that implement the Wilsonville Equitable Housing Strategic Plan and housing affordability provisions of legislative master plans.

(.02) *Permitted uses:*

- A. Open Space.
- B. Single-Family Dwelling Unit.
- C. Townhouses. During initial development in the Frog Pond West Neighborhood, a maximum of two townhouses may be attached, except on corners, a maximum of three townhouses may be attached.
- D. Duplex.
- E. Triplex and quadplex. During initial development in the Frog Pond West Neighborhood, triplexes are permitted only on corner lots and quadplexes are not permitted.
- F. Cluster housing. During initial development in the Frog Pond West Neighborhood, only two-unit cluster housing is permitted except on corner lots where three-unit cluster housing is permitted.
- G. Multiple-Family Dwelling Units, except when not permitted in a legislative master plan, subject to the density standards of the zone. Multi-family dwelling units are not permitted within the Frog Pond West Master Plan area.
- H. Cohousing.
- I. Cluster Housing (Frog Pond West Master Plan).
- J. Public or private parks, playgrounds, recreational and community buildings and grounds, tennis courts, and similar recreational uses, all of a non-commercial nature, provided that any principal building or public swimming pool shall be located not less than 45 feet from any other lot.

K. Manufactured homes.

(.03) *Permitted accessory uses:*

- A. Accessory uses, buildings and structures customarily incidental to any of the principal permitted uses listed above, and located on the same lot.
- B. Living quarters without kitchen facilities for persons employed on the premises or for guests. Such facilities shall not be rented or otherwise used as a separate dwelling unless approved as an accessory dwelling unit or duplex.
- C. Accessory Dwelling Units, subject to the standards of Section 4.113 (.10).
- D. Home occupations.
- E. A private garage or parking area.
- F. Keeping of not more than two roomers or boarders by a resident household.
- G. Temporary buildings for uses incidental to construction work, which buildings shall be removed upon completion or abandonment of the construction work.
- H. Accessory buildings and uses shall conform to front and side yard setback requirements. If the accessory buildings and uses do not exceed 120 square feet or ten feet in height, and they are detached and located behind the rear-most line of the main buildings, the side and rear yard setbacks may be reduced to three feet.
- I. Livestock and farm animals, subject to the provisions of Section 4.162.

(.04) *Uses permitted subject to Conditional Use Permit requirements:*

- A. Public and semi-public buildings and/or structures essential to the physical and economic welfare of an area, such as fire stations, sub-stations and pump stations.
- B. Commercial Recreation, including public or private clubs, lodges or meeting halls, golf courses, driving ranges, tennis clubs, community centers and similar commercial recreational uses. Commercial Recreation will be permitted upon a finding that it is compatible with the surrounding residential uses and promotes the creation of an attractive, healthful, efficient and stable environment for living, shopping or working. All such uses except golf courses and tennis courts shall conform to the requirements of Section 4.124(.04)(D) (Neighborhood Commercial Centers).
- C. Churches; public, private and parochial schools; public libraries and public museums.
- D. Neighborhood Commercial Centers limited to the provisions of goods and services primarily for the convenience of and supported by local residents. Neighborhood Commercial Centers are only permitted where designated on an approved legislative master plan.

(.05) *Residential Neighborhood Zone Sub-districts:*

- A. RN Zone sub-districts may be established to provide area-specific regulations that implement legislative master plans.
 - 1. For the Frog Pond West Neighborhood, the sub-districts are listed in Table 1 of this Code and mapped on Figure 6 of the Frog Pond West Master Plan. The Frog Pond West Master Plan Sub-District Map serves as the official sub-district map for the Frog Pond West Neighborhood.

(.06) *Minimum and Maximum Residential Lots:*

- A. The minimum and maximum number of residential lots approved shall be consistent with this Code and applicable provisions of an approved legislative master plan.

1. For initial development of the Frog Pond West Neighborhood, Table 1 in this Code and Frog Pond West Master Plan Table 1 establish the minimum and maximum number of residential lots for the sub-districts.
 2. For areas that are a portion of a sub-district, the minimum and maximum number of residential lots are established by determining the proportional gross acreage and applying that proportion to the minimums and maximums listed in Table 1. The maximum density of the area may be increased, up to a maximum of ten percent of what would otherwise be permitted, based on an adjustment to an SROZ boundary that is consistent with 4.139.06.
- B. The City may allow a reduction in the minimum density for a sub-district when it is demonstrated that the reduction is necessary due to topography, protection of trees, wetlands and other natural resources, constraints posed by existing development, infrastructure needs, provision of non-residential uses and similar physical conditions.

Table 1. Minimum and Maximum Residential Lots by Sub-District in the Frog Pond West Neighborhood			
Area Plan Designation	Frog Pond West Sub-district	Minimum Lots in Sub-district ^{a,b}	Maximum Lots in Sub-district ^{a,b}
R-10 Large Lot	3	26	32
	7	24	30
	8	43	53
R-7 Medium Lot	2	20	25
	4	86	107
	5	27	33
	9	10	13
	11	46	58
R-5 Small Lot	1	66	82
	6	74	93
	10	30	38
Civic	12	0	7 ^a
Public Facilities (PF)	13	0	0

- a. Each lot must contain at least one dwelling unit but may contain additional units consistent with the allowance for ADUs and middle housing.
- b. For townhouses, the combined lots of the townhouse project shall be considered a single lot for the purposes of the minimum and maximum of this table. In no case shall the density of a townhouse project exceed 25 dwelling units per net acre.
- c. These metrics apply to infill housing within the Community of Hope Church property, should they choose to develop housing on the site. Housing in the Civic sub-district is subject to the R-7 Medium Lot Single Family regulations.

(.07) Development Standards Generally:

- A. Unless otherwise specified by this the regulations in this Residential Development Zone chapter, all development must comply with Section 4.113, Standards Applying to Residential Development in Any Zone.

(.08) Lot Development Standards:

- A. Lot development shall be consistent with this Code and applicable provisions of an approved legislative master plan.
- B. Lot Standards Generally. For the Frog Pond West Neighborhood, Table 2 establishes the lot development standards unless superseded or supplemented by other provisions of the Development Code.
- C. Lot Standards for Small Lot Sub-districts. The purpose of these standards is to ensure that development in the Small Lot Sub-districts includes varied design that avoids homogenous street frontages, creates active pedestrian street frontages and has open space that is integrated into the development pattern.

Standards. Planned developments in the Small Lot Sub-districts shall include one or more of the following elements on each block:

- 1. Alleys.
- 2. Residential main entries grouped around a common green or entry courtyard (e.g. cluster housing).
- 3. Four or more residential main entries facing a pedestrian connection allowed by an applicable legislative master plan.
- 4. Garages recessed at least four feet from the front façade or six feet from the front of a front porch.

Neighborhood Zone Sub-District	Min. Lot Size (sq. ft.) ^{A,B}	Min. Lot Depth (ft.)	Max. Lot Coverage (%)	Min. Lot Width ^{J, N} (ft.)	Max. Bldg. Height ^H (ft.)	Setbacks ^{K, L, M}				
						Front Min. (ft.)	Rear Min. (ft.)	Side Min. (note)	Garage Min Setback from Alley (ft.)	Garage Min Setback from Street ^{O,P} (ft.)
R-10 Large Lot	8,000	60'	40% ^E	40	35	20 ^F	20	^M	18 ^G	20
R-7 Medium Lot	6,000 ^C	60'	45% ^E	35	35	15 ^F	15	^M	18 ^G	20
R-5 Small Lot	4,000 ^{C,D}	60'	60% ^E	35	35	12 ^F	15	^M	18 ^G	20

Notes:

- A. Minimum lot size may be reduced to 80% of minimum lot size for any of the following three reasons: (1) where necessary to preserve natural resources (e.g. trees, wetlands) and/or provide active open space, (2) lots designated for cluster housing (Frog Pond West Master Plan), (3) to increase the number of lots up to the maximum number allowed so long as for each lot reduced in size a lot meeting the minimum lot size is designated for development of a duplex or triplex.
- B. For townhouses the minimum lot size in all sub-districts is 1,500 square feet.
- C. In R-5 and R-7 sub-districts the minimum lot size for quadplexes and cottage clusters is 7,000 square feet.
- D. In R-5 sub-districts the minimum lot size for triplexes is 5,000 square feet.
- E. On lots where detached accessory buildings are built, maximum lot coverage may be increased by 10%. Cottage clusters are exempt from maximum lot coverage standards.
- F. Front porches may extend 5 feet into the front setback.

- G. The garage setback from alley shall be minimum of 18 feet to a garage door facing the alley in order to provide a parking apron. Otherwise, the rear or side setback shall be between 3 and 5 feet.
 - H. Vertical encroachments are allowed up to ten additional feet, for up to 10% of the building footprint; vertical encroachments shall not be habitable space.
 - I. For townhouses in all sub-districts minimum lot width is 20 feet.
 - J. May be reduced to 24' when the lot fronts a cul-de-sac. No street frontage is required when the lot fronts on an approved, platted private drive or a public pedestrian access in a cluster housing (Frog Pond West Master Plan) development.
 - K. Front Setback is measured as the offset of the front lot line or a vehicular or pedestrian access easement line. On lots with alleys, Rear Setback shall be measured from the rear lot line abutting the alley.
 - L. For cottage clusters all setbacks otherwise greater than 10 feet for other housing types is reduced to 10 feet
 - M. On lots greater than 10,000 SF with frontage 70 ft. or wider, the minimum combined side yard setbacks shall total 20 ft. with a minimum of 10 ft. On other lots, minimum side setback shall be 5 ft. On a corner lot, minimum side setbacks are 10 feet.
 - N. For cluster housing (Frog Pond West Master Plan) with lots arranged on a courtyard, frontage shall be measured at the front door face of the building adjacent to a public right-of-way or a public pedestrian access easement linking the courtyard with the Public Way.
 - O. All lots with front-loaded garages are limited to one shared standard-sized driveway/apron per street regardless of the number of units on the lot.
 - P. The garage shall be setback a minimum of 18 feet from any sidewalk easements that parallels the street.
- D. Lot Standards Specific to the Frog Pond West Neighborhood.
- 1. Lots adjacent to Boeckman Road and Stafford Road shall meet the following standards:
 - a. Rear or side yards adjacent to Boeckman Road and Stafford Road shall provide a wall and landscaping consistent with the standards in Figure 10 of the Frog Pond West Master Plan.
 - 2. Lots adjacent to the collector-designated portions of Willow Creek Drive and Frog Pond Lane shall not have driveways accessing lots from these streets, unless no practical alternative exists for access. Lots in Large Lot Sub-districts are exempt from this standard.

(.09) Open Space:

- A. *Purpose.* The purposes of these standards for the Residential Neighborhood Zone are to:
 - 1. Provide light, air, open space, and useable recreation facilities to occupants of each residential development.
 - 2. Retain and incorporate natural resources and trees as part of developments.
 - 3. Provide access and connections to trails and adjacent open space areas.

For Neighborhood Zones which are subject to adopted legislative master plans, the standards work in combination with, and as a supplement to, the park and open space recommendations of those legislative master plans. These standards supersede the Open Space requirements in WC Section 4.113(.01).
- B. *Within the Frog Pond West Neighborhood, the following standards apply:*
 - 1. Properties within the R-10 Large Lot sub-districts and R-7 Medium Lot sub-districts are exempt from the requirements of this section. If the Development Review Board finds, based upon substantial evidence in the record, that there is a need for open space, they may waive this exemption and require open space proportional to the need.
 - 2. For properties within the R-5 Small Lot sub-districts, Open Space Area shall be provided in the following manner:

- a. Ten percent of the net developable area shall be in open space. Net developable area does not include land for non-residential uses, SROZ-regulated lands, streets and private drives, alleys and pedestrian connections. Open space must include at least 50 percent usable open space as defined by this Code and other like space that the Development Review Board finds will meet the purpose of this section.
- b. Natural resource areas such as tree groves and/or wetlands, and unfenced low impact development storm water management facilities, may be counted toward the ten percent requirement at the discretion of the Development Review Board. Fenced storm water detention facilities do not count toward the open space requirement. Pedestrian connections may also be counted toward the ten percent requirement.
- c. The minimum land area for an individual open space is 2,000 square feet, unless the Development Review Board finds, based on substantial evidence in the record, that a smaller minimum area adequately fulfills the purpose of this Open Space standard.
- d. The Development Review Board may reduce or waive the usable open space requirement in accordance with Section 4.118(.03). The Board shall consider substantial evidence regarding the following factors: the walking distance to usable open space adjacent to the subject property or within 500 feet of it; the amount and type of open space available adjacent or within 500 feet of the subject property, including facilities which support creative play.
- e. The Development Review Board may specify the method of assuring the long-term protection and maintenance of open space and/or recreational areas. Where such protection or maintenance are the responsibility of a private party or homeowners' association, the City Attorney shall review any pertinent bylaws, covenants or agreements prior to recordation.

(.10) *Block, access and connectivity standards:*

- A. *Purpose.* These standards are intended to regulate and guide development to create: a cohesive and connected pattern of streets, pedestrian connections and bicycle routes; safe, direct and convenient routes to schools and other community destinations; and, neighborhoods that support active transportation and Safe Routes to Schools.
- B. *Blocks, access and connectivity shall comply with adopted legislative master plans:*
 1. Within the Frog Pond West Neighborhood, streets shall be consistent with Figure 18, Street Demonstration Plan, in the Frog Pond West Master Plan. The Street Demonstration Plan is intended to be guiding, not binding. Variations from the Street Demonstration Plan may be approved by the Development Review Board, upon finding that one or more of the following justify the variation: barriers such as existing buildings and topography; designated Significant Resource Overlay Zone areas; tree groves, wetlands or other natural resources; existing or planned parks and other active open space that will serve as pedestrian connections for the public; alignment with property lines and ownerships that result in efficient use of land while providing substantially equivalent connectivity for the public; and/or site design that provides substantially equivalent connectivity for the public.
 2. If a legislative master plan does not provide sufficient guidance for a specific development or situation, the Development Review Board shall use the block and access standards in Section 4.124(.06) as the applicable standards.

(.11) *Signs.* Per the requirements of Sections 4.156.01 through 4.156.11 and applicable provisions from adopted legislative master plans.

(.12) *Parking*. Per the requirements of Section 4.155 and applicable provisions from adopted legislative master plans.

(.13) *Corner Vision Clearance*. Per the requirements of Section 4.177.


(.14) *Main Entrance Standards*:


A. *Purpose*. These standards:

1. Support a physical and visual connection between the living area of the residence and the street;
2. Enhance public safety for residents and visitors and provide opportunities for community interaction;
3. Ensure that the pedestrian entrance is visible or clearly identifiable from the street by its orientation or articulation; and
4. Ensure a connection to the public realm for development on lots fronting both private and public streets by making the pedestrian entrance visible or clearly identifiable from the public street.

B. *Location*. At least one main entrance for each structure must:

1. Be within 12 feet of the longest street-facing front wall of the dwelling unit; and
2. Either;
 - a. Face the street;
 - b. Be at an angle of up to 45 degrees from the street; or
 - c. Open onto a porch. The porch must:
 - (i) Be at least six feet deep;
 - (ii) Have at least one entrance facing the street; and
 - (iii) Be covered with a roof or trellis.





- C. *Distance from grade.* Main entrances meeting the standards in subsection B., above, must be within four feet of grade. For the purposes of this Subsection, grade is the average grade measured along the foundation of the longest street-facing wall of the dwelling unit.

(.15) *Garage Standards:*


A. *Purpose.* These standards:

1. Ensure that there is a physical and visual connection between the living area of the residences and the street;
2. Ensure that the location and amount of the living area of the residence, as seen from the street, is more prominent than garages;
3. Prevent garages from obscuring the main entrance from the street and ensure that the main entrance for pedestrians, rather than automobiles, is the prominent entrance;
4. Provide for a pleasant pedestrian environment by preventing garages and vehicle areas from dominating the views of the neighborhood from the sidewalk; and
5. Enhance public safety by preventing garages from blocking views of the street from inside the residence.

B. *Street-Facing Garage Walls:*

1. Where these regulations apply. Unless exempted, the regulations of this subsection apply to garages accessory to residential units.
2. *Exemptions:*
 - a. Garages on flag lots.
 - b. Development on lots which slope up or down from the street with an average slope of 20 percent or more.
3. *Standards:*

- a. The length of the garage wall facing the street may be up to 50 percent of the length of the street-facing building façade. For middle housing, this standard applies to the total length of the street-facing façades. For detached single-family and accessory structures, the standards apply to the street-facing façade of each unit. For corner lots, this standard applies to only one street side of the lot. For lots less than 50 feet wide at the front lot line, the standard in (b) below applies.
- b. For lots less than 50 wide at the front lot line, the following standards apply:
 - (i) The width of the garage door may be up to 50 percent of the length of the street-facing façade.
 - (ii) The garage door must be recessed at least four feet from the front façade or six feet from the front of a front porch.
 - (iii) The maximum driveway width is 18 feet.
- c. Where a dwelling abuts a rear or side alley or a shared driveway, the garage shall orient to the alley or shared drive.
- d. Where three or more contiguous garage parking bays are proposed facing the same street, the garage opening closest to a side property line shall be recessed at least two feet behind the adjacent opening(s) to break up the street facing elevation and diminish the appearance of the garage from the street. Side-loaded garages, i.e., where the garage openings are turned away from the street, are exempt from this requirement.
- e. A garage entry that faces a street may be no closer to the street than the longest street facing wall of the dwelling unit. There must be at least 20 feet between the garage door and the sidewalk. This standard does not apply to garage entries that do not face the street.



(.16) *Residential Design Standards:*

- A. *Purpose.* These standards:

1. Support consistent quality standards so that each home contributes to the quality and cohesion of the larger neighborhood and community.
 2. Support the creation of architecturally varied structures, blocks and neighborhoods, whether a neighborhood develops all at once or one lot at a time, avoiding homogeneous street frontages that detract from the community's appearance.
- B. *Applicability.* These standards apply to all façades facing streets, pedestrian connections, parks, open space tracts, the Boeckman Trail, or elsewhere as required by this Code or the Development Review Board. Exemptions from these standards include: (1) Additions or alterations adding less than 50 percent to the existing floor area of the structure; and, (2) Additions or alterations not facing a street, pedestrian connection, park, or open space tract.
- C. *Windows.* The standards for minimum percentage of façade surface area in windows are below. These standards apply only to facades facing streets, pedestrian connections, parks, and open space tracts.
1. For two-story structures:
 - a. 15 percent front facades.
 - b. 12.5 percent—front facades if a minimum of six design elements are provided per Section 4.127(0.15)E., Design Menu.
 - c. Ten percent—front facades facing streets if a minimum of seven design elements are provided per Section 4.127(0.15)E., Design Menu.
 2. For one-story structures:
 - a. 12.5 percent—front facades.
 - b. Ten percent—front facades if a minimum of six design elements are provided per Section 4.127(0.15)E., Design Menu.
 3. For all structures: Five percent for street-side facades.
 4. Windows used to meet this standard must provide views from the building to the street. Glass block does not meet this standard. Windows in garage doors and other doors count toward this standard.
 5. Street-facing facades along Boeckman Road and Stafford Road must meet the standards for front facades.
- D. *Articulation.* Plans for residential buildings shall incorporate design features such as varying rooflines, offsets, balconies, projections (e.g., overhangs, porches, or similar features), recessed or covered entrances, window reveals, or similar elements that break up otherwise long, uninterrupted elevations. Such elements shall occur at a minimum interval of 30 feet on façades facing streets, pedestrian connections, parks, open space tracts, or elsewhere as required by this Code or the Development Review Board. Where a façade governed by this standard is less than 30 feet in length, at least one of the above-cited features shall be provided.
- E. *Residential Design Menu.* Residential structures shall provide a minimum of five of the design elements listed below for front façades and façades facing Boeckman Road and Stafford Road, unless otherwise specified by the code. For side façades facing streets, pedestrian connections, parks, open space tracts, a minimum of three of the design elements must be provided. Where a design feature includes more than one element, it is counted as only one of the five required elements.
1. Dormers at least three feet wide.

2. Covered porch entry—minimum 48 square foot covered front porch, minimum six feet deep and minimum of a six foot deep cover. A covered front stoop with minimum 24 square foot area, four foot depth and hand rails meets this standard.
 3. Front porch railing around at least two sides of the porch.
 4. Front facing second story balcony - projecting from the wall of the building a minimum of four feet and enclosed by a railing or parapet wall.
 5. Roof overhang of 16 inches or greater.
 6. Columns, pillars or posts at least four inches wide and containing larger base materials.
 7. Decorative gables - cross or diagonal bracing, shingles, trim, corbels, exposed rafter ends or brackets (does not include a garage gable if garage projects beyond dwelling unit portion of street façade).
 8. Decorative molding above windows and doors.
 9. Decorative pilaster or chimneys.
 10. Shakes, shingles, brick, stone or other similar decorative materials occupying at least 60 square feet of the street façade.
 11. Bay or bow windows - extending a minimum of 12 inches outward from the main wall of a building and forming a bay or alcove in a room within the building.
 12. Sidelight and/or transom windows associated with the front door or windows in the front door.
 13. Window grids on all façade windows (excluding any windows in the garage door or front door).
 14. Maximum nine foot wide garage doors or a garage door designed to resemble two smaller garage doors and/or windows in the garage door (only applicable to street facing garages).
 15. Decorative base materials such as natural stone, cultured stone or brick extending at least 36 inches above adjacent finished grade occupying a minimum of ten percent of the overall primary street facing façade.
 16. Entry courtyards which are visible from, and connected directly to, the street. Courtyards shall have a minimum depth of ten feet and minimum width of 80 percent of the non-garage/driveway building width to be counted as a design element.
- F. *House Plan Variety.* No two directly adjacent or opposite residential structures may possess the same front or street-facing elevation. A structure containing multiple middle housing units shall be considered a single residential structure for the purpose of house plan variety. This standard is met when front or street-facing elevations differ from one another due to different materials, articulation, roof type, inclusion of a porch, fenestration, and/or number of stories. Where façades repeat on the same block face, they must have at least three intervening residential structures between them that meet the above standard. Small Lot developments over ten acres shall include duplexes and/or two-unit townhouses comprising ten percent of the homes—corner locations are preferred.
- G. *Prohibited Building Materials.* The following construction materials may not be used as an exterior finish:
1. Vinyl siding.
 2. Wood fiber hardboard siding.
 3. Oriented strand board siding.
 4. Corrugated or ribbed metal.

5. Fiberglass panels.

(.17) *Fences:*

- A. Within Frog Pond West, fences shall comply with standards in 4.113 (.07) except as follows:
 1. Columns for the brick wall along Boeckman Road and Stafford Road shall be placed at lot corners where possible.
 2. A solid fence taller than four feet in height is not permitted within eight feet of the brick wall along Boeckman Road and Stafford Road, except for fences placed on the side lot line that are perpendicular to the brick wall and end at a column of the brick wall.
 3. Height transitions for fences shall occur at fence posts.

(.18) *Residential Structures Adjacent to Schools, Parks and Public Open Spaces.*

- A. *Purpose.* The purpose of these standards is to ensure that development adjacent to schools and parks is designed to enhance those public spaces with quality design that emphasizes active and safe use by people and is not dominated by driveways, fences, garages, and parking.
- B. *Applicability.* These standards apply to development that is adjacent to or faces schools and parks. As used here, the term adjacent includes development that is across a street or pedestrian connection from a school or park.
- C. *Development must utilize one or more of the following design elements:*
 1. Alley loaded garage access.
 2. On corner lots, placement of the garage and driveway on the side street that does not face the school, park, or public open space.
 3. Recess of the garage a minimum of four feet from the front façade of the home. A second story above the garage, with windows, is encouraged for this option.
- D. Development must be oriented so that the fronts or sides of residential structures face adjacent schools or parks. Rear yards and rear fences may generally not face the schools or parks, unless approved through the waiver process of 4.118 upon a finding that there is no practicable alternative due to the size, shape or other physical constraint of the subject property.

(Ord. No. 806, 7-17-2017)

Section 4.113. Standards Applying to Residential Developments in any Zone.

(.01) Open Space:

- A. *Purpose.* The purposes of the following standards for open space are to provide adequate light, air, open space and usable recreational facilities to occupants of each residential development.
- B. *Applicability.*
 - 1. The open space standards of this subsection shall apply to the following:
 - a. Subdivisions.
 - b. Planned Developments.
 - c. Multi-family Development.
 - 2. These standards do not apply to the following:
 - a. Partitions for non-Multi-family development. However, serial or adjacent partitions shall not be used to avoid the requirements.
 - b. Middle Housing Land Divisions.
- C. *Area Required.* The minimum open space area required in a development is an area equal to 25 percent of the size of the Gross Development Area except if reduced for shared parking pursuant to Subsection 4.155(.03)S.
- D. *Required Open Space Characteristics:*
 - 1. *Size of Individual Open Spaces.* For developments with ten or more lots buildable with dwelling units (or ten or more multi-family units) an open space area must be at least 2,000 square feet to be counted towards the 25 percent open space requirement. For developments with less than ten lots buildable with dwelling units (or less than ten multi-family units) an open space area must be at least 1,000 square feet to be counted towards the 25 percent open space requirement.
 - 2. *Types of Open Space and Ownership.* The following types of areas count towards the minimum open space requirement if they are or will be owned by the City, a homeowners' association or similar joint ownership entity, or the property owner for Multi-family Development.
 - a. Preserved wetlands and their buffers, natural and/or treed areas, including those within the SROZ
 - b. New natural/wildlife habitat areas
 - c. Non-fenced vegetated stormwater features
 - d. Play areas and play structures
 - e. Open grass area for recreational play
 - f. Swimming and wading areas
 - g. Other areas similar to a. through f. that are [publicly] accessible
 - h. Walking paths besides required sidewalks in the public right-of-way or along a private drive.
 - 3. *Usable open space requirements.* Half of the minimum open space area, an area equal to 12.5 percent of the size of the Gross Development Area, shall be located outside the SROZ and be

usable open space programmed for active recreational use. Any open space considered usable open space programmed for active recreation use shall meet the following requirements.

- a. Be designed by a registered professional landscape architect with experience designing residential park areas. An affidavit of such professional's credentials shall be included in the development application material.
 - b. Be designed and programmed for a variety of age groups or other user groups.
4. *Enhancing Existing Wildlife Habitat through Design of Open Space:*
- a. Open space designed, as wildlife habitat shall be placed adjacent to and connect to existing, preserved wildlife habitat to the extent feasible.
 - b. To the extent feasible, open space shall create or enhance connections between existing wildlife habitat.
- E. Any dedication of land as public park land must meet City parks standards. The square footage of any open space land outside the SROZ and BPA easements, whether dedicated to the public or not, shall be considered part of the Gross Development Area.
- F. Approval of open space must ensure the long-term protection and maintenance of open space and/or recreational areas. Where such protection or maintenance are the responsibility of a private party or homeowners' association, the City Attorney shall review any pertinent bylaws, covenants, or agreements prior to recordation.
- G. The open space requirements of this subsection are subject to adjustments in PDR zones pursuant to Subsection 4.124(.08).

(.14) Design Standards for Detached Single-family and Middle Housing.

- A. The standards in this subsection apply in all zones, except as indicated in 1.—2. below:
 1. The Façade Variety standards in Subsection C.1. do not apply in the Village Zone or Residential Neighborhood Zones, as these zones have their own variety standards, except that the standards do apply within middle housing development with multiple detached units on a single lot which the standards of these zones do not address;
 2. The entry orientation and window standards for triplexes, quadplexes, and townhouses in Subsections D.1-2. and E. 2-3. do not apply in the Village Zone or Residential Neighborhood Zone as these zones have their own related standards applicable to all single-family and middle housing.
- B. For the purpose of this subsection the term "residential structure" is inclusive of a series of structures that are attached to one another such as a grouping of townhouses.
- C. Standards applicable to all residential structures except as noted in I. below.
 1. *Façade Variety:*
 - a. Each public-facing façade of a residential structure shall differ from the public-facing façades of directly adjacent residential structures in at least one of the three ways listed in Subsection d. below.
 - b. Where public-facing façades repeat on the same block, at least two residential structures with different public-facing façades shall intervene between residential structures with the same public-facing façades, with sameness defined by not differing in at least one of the three ways listed in Subsection d. below.

- c. For façades of residential structures facing a public street, the façade of any residential structures directly across the street shall differ in at least one of the three ways listed in Subsection d. below. Directly across means any residential structure façade intersected by imaginary lines extending the shortest distance across the street from the mid-point of a façade and from the edges of a façade. See Figure 1 below.
- d. A façade shall be considered different if it differs from another façade in at least one of the following ways:
- i. Variation in type, placement, or width of architectural projections (such as porches, dormers, or gables) or other features that are used to meet the Articulation standards in Subsection (.14)C.2.b or Subsection (.14)E.4. If adjacent or opposite façades feature the same projection type, the projections on adjacent/opposite façades must differ in at least one of the following ways:
 - At least 20 percent difference in width; or
 - Horizontally offset by at least five feet. For the purposes of this standard, "offset" means a measurable difference of at least five feet from the left edge of the projection to the left edge of the front façade or at least five feet from the right edge of the projection to the right edge of the front façade.
 - ii. At least 20 percent of the façade (excluding glazing) is covered by different exterior finish materials. The use of the same material in different types of siding (e.g., cedar shingles vs. cedar lap siding) shall be considered different materials for the purpose of this standard.
 - iii. Variation in primary paint color as determined by a LRVR (Light Reflectance Value) difference of at least 15 percent.




Figure 1. Determining If A Residential Structure is Directly Across the Street from Another

2. *Architectural Consistency and Interest.*
 - a. Architectural styles shall not be mixed within the same residential structure (a series of attached structures is one structure for the purpose of these standards). Architectural style consistency is defined by adherence to all of the following:
 - i. Use of the same primary and supporting façade materials throughout the structure.
 - ii. Use of no more than two roof pitch angles.
 - iii. Use of the same door size for each primary entrance in the structure.
 - b. Articulation. All public-facing façades of residential structures, other than townhouses, shall incorporate the following design elements at a minimum interval of every 30 feet, except as noted in 2.c. below. The minimum number of design elements is determined by dividing the façade length by 30 and rounding up to the nearest whole number. For townhouse articulation standards, see subsection (.14)E.4.
 - i. varying rooflines.
 - ii. offsets of at least 12 inches.
 - iii. balconies.
 - iv. projections of at least 12 inches and width of at least three feet.
 - v. porches.
 - vi. entrances that are recessed at least 24 inches or covered.
 - vii. dormers at least three feet wide.
 - c. For structures with two or more dwelling units, a single design element that spans at least 50 percent of the façade of two adjacent units can count as two articulation elements to meet the standard in subsection b. and can meet the standard for 60 feet of façade width (two adjacent 30 foot intervals). Such elements may overlap horizontally with other required design elements on the façade.
 - d. Articulation Element Variety: Different articulation elements shall be used as provided below. For the purpose of this standard, a "different element" is defined as one of the following: a completely different element from the list in subsection 2.b above; the same type of element but at least 50 percent larger; or for varying rooflines, vertically offset by at least three feet.
 - i. Where two to four elements are required on a façade, at least two different elements shall be used.
 - ii. Where more than four elements are required on a façade, at least three different elements shall be used.
 - e. Reductions to required windows percentage: The required percent of façade of a residential structure in the public-facing façade covered by windows or entry doors for single-family or middle housing in any zone may be reduced to the percentages that follows:
 - i. For of 1.5 or 2-story façades facing the front or rear lot line:

- 12.5 percent if six of the design features in Subsection e.v. below are used.
- Ten percent if seven or more of the design features in Subsection e.v. below are used.
- ii. For 1-story façades facing the front or rear lot line;
 - 12.5 percent if less than six design features in Subsection e.v. are used
 - ten percent if six or more design features in Subsection e.v. are used
- iii. For façades facing a side lot line:
 - Five percent regardless of the number of design features
- iv. Glass block does not count towards meeting window and entry percentage
- v. Window reduction design features:
 - Dormers at least three feet wide.
 - Covered porch entry—minimum 48 square foot covered front porch, minimum six feet deep and minimum of a six foot deep cover. A covered front stoop with minimum 24 square foot area, four foot depth and hand rails meets this standard.
 - Front porch railing around at least two sides of the porch.
 - Second story balcony—projecting from the wall of the building a minimum of four feet and enclosed by a railing or parapet wall.
 - Roof overhang of eight inches or greater.
 - Columns, pillars or posts at least four inches wide and containing larger base materials.
 - Decorative gables—cross or diagonal bracing, shingles, trim, corbels, exposed rafter ends or brackets (does not include a garage gable if garage projects beyond dwelling unit portion of street façade).
 - Decorative molding above windows and doors.
 - Decorative pilaster or chimneys.
 - Bay or bow windows—extending a minimum of 12 inches outward from the main wall of a building and forming a bay or alcove in a room within the building.
 - Sidelight and/or transom windows associated with the front door or windows in the front door.
 - Window grids on all façade windows visible from behind fences (excluding any windows in the garage door or front door).
 - Maximum nine foot wide garage doors or a garage door designed to resemble two smaller garage doors and/or windows in the garage door (only applicable to street facing garages).
 - Decorative base materials such as natural stone, cultured stone or brick extending at least 36 inches above adjacent finished grade occupying a

minimum of ten percent of the overall primary street facing façade. This design element does not count if behind a site-obscuring fence.

- Entry courtyards which are visible from, and connected directly to, the street. Courtyards shall have a minimum depth of ten feet and minimum width of 80 percent of the non-garage/driveway building width to be counted as a design element.

D. Standards applicable to Triplexes and Quadplexes except as noted in I. below.

1. *Entry Orientation.*

- a. At least one main entrance for each triplex or quadplex must meet the standards in subsections b. and c. below.
- b. The entrance must be within eight feet of the longest street-facing exterior wall of the dwelling unit or if no exterior wall faces a street the front of the dwelling unit facing a common drive or open space as designated by the applicant; and
- c. The entrance must either:
 - i. Face the street (see Figure 2. Main Entrance Facing the Street);
 - ii. Be at an angle of up to 45 degrees from the street (see Figure 3. Main Entrance at 45 degree angle from the street); or
 - iii. Open onto a porch (see Figure 4. Main Entrance Opening onto a Porch). The porch must:
 - Be at least 25 square feet in area; and
 - Have at least one entrance facing the street or have a roof.




Figure 2. Main Entrance Facing the Street




Figure 3. Main Entrance at 45° Angle from the Street





Figure 4. Main Entrance Opening onto a Porch

2. *Windows.* A minimum of 15 percent of the area of all street-facing façades must include windows or entrance doors. Façades separated from the street property line by a dwelling are exempt from meeting this standard. See Figure 5. Window Coverage.



Figure 5. Window Coverage

3. *Garages and Off-Street Parking Areas.* The combined width of all garages and outdoor on-site parking and maneuvering areas shall not exceed a total of 50 percent of any street frontage (other than an alley) (see Figure 6. Width of Garages and Parking Areas).




- (A) Garage and on-site parking and maneuvering areas
- (B) Total street frontage

$$\frac{A^1 + A^2 + A^3}{B} \leq 50\%$$

Figure 6. Width of Garages and Parking Areas

4. *Driveway Approach.* Driveway approaches must comply with all of the following:
 - a. The total width of all driveway approaches must not exceed 32 feet per frontage, as measured at the property line (see Figure 7. Driveway Approach Width and Separation on Local Street). For lots or parcels with more than one frontage, see subsection c.
 - b. Driveway approaches may be separated when located on a local street.
 - c. In addition, lots or parcels with more than one frontage must comply with the following:
 - i. Lots or parcels must access the street with the lowest transportation classification for vehicle traffic. For lots or parcels abutting an alley that is improved with a paved surface, access must be taken from the alley (see Figure 8. Alley Access).
 - ii. Lots or parcels with frontages only on collectors and/or arterial streets must meet the access standards in the Wilsonville Public Works Standards.

- iii. Lots or parcels with frontages only on local streets may have either:
- Two driveway approaches not exceeding 32 feet in total width on one frontage; or
 - One maximum 16-foot-wide driveway approach per frontage (see Figure 9. Driveway Approach Options for Multiple Local Street Frontages).



- (A) $X^1 + X^2 + X^3 + X^4$ must not exceed 32 feet per frontage.
- (B) Driveway approaches may be separated when located on a local street

Figure 7. Driveway Approach Width and Separation on Local Street





Figure 8. Alley Access



Options for site with more than one frontage on local streets:

- (A)** Two driveway approaches not exceeding 32 feet in total width on one frontage (as measured $X1 + X2$); or
- (B)** One maximum 16-foot-wide driveway approach per frontage.

(Note: Both options are depicted here for illustrative purposes only. The standards do not allow both Options A and B on the same site.)

Figure 9. Driveway Approach Options for Multiple Local Street Frontages


E. Standards applicable to Townhouses.

1. *Number of Attached Dwelling Units.*

- a. Minimum. A townhouse project must contain at least two attached units.
- b. Maximum. The maximum number of townhouse units that may be attached together to form a group is specified below.
 - R, OTR, PDR-1—PDR-3 Zones: maximum four attached units per group
 - RN, V, PDR-4—PDR-7 Zones: maximum eight attached units per group, except for initial development in Frog Pond West per Section 4.124.

2. *Entry Orientation.* The main entrance of each townhouse unit must:

- a. Be within eight feet of the longest wall of the dwelling unit facing a street or private drive;
and
 - b. Either:
 - i. Face the street or private drive (see Figure 2. Main Entrance Facing the Street);
 - ii. Be at an angle of up to 45 degrees from the street or private drive (see Figure 3. Main Entrance at 45° Angle from the Street);
 - iii. Face a common open space or private access or driveway that is abutted by dwellings on at least two sides; or
 - iv. Open onto a porch (see Figure 4. Main Entrance Opening onto a Porch). The porch must:
 - A. Be at least 25 square feet in area; and
 - B. Have at least one entrance facing the street or private drive or have a roof.
3. *Windows.* A minimum of 15 percent of the area of all public-facing façades on each individual unit must include windows or entrance doors. Half of the window area in the door of an attached garage may count toward meeting this standard. See Figure 5. Window Coverage.
4. *Unit definition.* Each townhouse unit must include at least one of the items listed in a. through g. below on at least one public-facing façade (see Figure 10. Townhouse Unit Definition). Alternatively, if a single item from the list below spans across at least 50 percent of two adjacent townhouse units, it can meet the standard for two units.
- a. A roof dormer a minimum of four feet in width, or
 - b. A balcony a minimum of two feet in depth and four feet in width and accessible from an interior room, or
 - c. A bay window that extends from the façade a minimum of two feet, or
 - d. An offset of the façade of a minimum of two feet in depth, either from the neighboring townhouse or within the façade of a single townhouse, or
 - e. An entryway that is recessed a minimum of three feet, or
 - f. A covered entryway with a minimum depth of four feet, or
 - g. A porch meeting the standards of subsection (.14)E.2.b.iv.
- Balconies and bay windows may encroach into a required setback area, pursuant to Section 4.180.



- (A) Roof dormer, minimum of 4 feet wide
- (B) Balcony, minimum 2 feet deep and 4 feet wide. Accessible from interior room.
- (C) Bay window extending minimum of 2 feet from facade
- (D) Facade offset, minimum of 2 feet deep
- (E) Recessed entryway, minimum 3 feet deep
- (F) Covered entryway, minimum of 4 feet deep
- (G) Porch, meets standards of subsection (1)(b)(iv) of section (C)

Figure 10. Townhouse Unit Definition

5. *Driveway Access and Parking.* Townhouses with frontage on a street or private drive shall meet the following standards:
 - a. *Alley Access.* Townhouse project sites abutting an alley that is improved with pavement shall take access to the rear of townhouse units from the alley rather than the public street.
 - b. *Front Access.* Garages on the front façade of a townhouse, off-street parking areas in the front yard, and driveways in front of a townhouse are allowed if they meet the following standards (see Figure 11. Townhouses with Parking in Front Yard).
 - i. Each townhouse lot has a street frontage of at least 20 feet on a local street.
 - ii. A maximum of one driveway approach is allowed for every townhouse. Driveway approaches and/or driveways may be shared.
 - iii. Outdoor on-site parking and maneuvering areas do not exceed 12 feet wide on any lot.

- iv. The garage width does not exceed 12 feet, as measured from the inside of the garage door frame.




Figure 11. Townhouses with Parking in Front Yard

- c. *Shared Access.* The following standards apply to driveways and parking areas for townhouse projects that do not meet all of the standards in subsections a. or b.
 - i. Off-street parking areas shall be accessed on the back façade or located in the rear yard. No off-street parking shall be allowed in the front yard or side yard of a townhouse.
 - ii. A townhouse project that includes a corner lot shall take access from a single driveway approach on the side of the corner lot. See Figure 12. Townhouses on Corner Lot with Shared Access.




Figure 12. Townhouses on Corner Lot with Shared Access

- iii. Townhouse projects that do not include a corner lot shall consolidate access for all lots into a single driveway. The driveway and approach are not allowed in the area directly between the front façade and front lot line of any of the townhouses. See Figure 13. Townhouses with Consolidated Access.





Figure 13. Townhouses with Consolidated Access

- iv. A townhouse project that includes consolidated access or shared driveways shall grant access easements to allow normal vehicular access and emergency access.
- F. Standards applicable to Cottage Clusters.
- 1. *Courtyard Required.* All cottages within a single cottage cluster must share a common courtyard. A cottage cluster project may include more than one cluster and more than one common courtyard.
 - 2. *Number of Dwellings.*
 - a. A single cottage cluster shall contain a minimum of four and a maximum of eight cottages.
 - 3. *Setbacks.*
 - a. *Building Separation.* Cottages shall be separated by a minimum distance of six feet. The minimum distance between all other structures, including accessory structures, shall be in accordance with building code requirements.
 - b. All other setbacks are provided in section (.02) or in the applicable base zone.
 - 4. *Building Height.* The maximum building height for all structures is 25 feet.

5. *Footprint.* The maximum building footprint for each cottage is 900 square feet. Individual attached garages up to 200 square feet shall be exempted from the calculation of maximum building footprint.
6. *Maximum Habitable Floor Area.* The maximum habitable floor area of each cottage is 1,400 square feet.
7. *Cottage Orientation.* Cottages must be clustered around a common courtyard and must meet the following standards (see Figure 14. Cottage Cluster Orientation and Common Courtyard Standards):
 - a. Each cottage within a cluster must either abut the common courtyard or must be directly connected to it by a pedestrian path.
 - b. A minimum of 50 percent of cottages within a cluster must be oriented to the common courtyard and must:
 - i. Have a main entrance facing the common courtyard;
 - ii. Be within ten feet from the common courtyard, measured from the façade of the cottage to the nearest edge of the common courtyard; and
 - iii. Be connected to the common courtyard by a pedestrian path.
 - c. Cottages within 20 feet of a street property line may have their entrances facing the street.
 - d. Cottages not facing the common courtyard or the street must have their main entrances facing a pedestrian path that is directly connected to the common courtyard.
8. *Common Courtyard Design Standards.* Each cottage cluster must share a common courtyard in order to provide a sense of openness and community of residents. Common courtyards must meet the following standards (see Figure 14. Cottage Cluster Orientation and Common Courtyard Standards):
 - a. The common courtyard must be a single, contiguous piece.
 - b. Cottages must abut the common courtyard on at least two sides of the courtyard.
 - c. The common courtyard must contain a minimum of 150 square feet per cottage within the associated cluster.
 - d. The common courtyard must be a minimum of 15 feet wide at its narrowest dimension.
 - e. The common courtyard shall be developed with a mix of landscaping, lawn area, pedestrian paths, and/or paved courtyard area, and may also include recreational amenities. Impervious elements of the common courtyard shall not exceed 75 percent of the total common courtyard area.
 - f. Pedestrian paths must be included in a common courtyard. Paths that are contiguous to a courtyard shall count toward the courtyard's minimum dimension and area. Parking areas, required setbacks, and driveways do not qualify as part of a common courtyard.



- (A) A minimum of 50% of cottages must be oriented to the common courtyard.
- (B) Cottages oriented to the common courtyard must be within 10 feet of the courtyard.
- (C) Cottages must be connected to the common courtyard by a pedestrian path.
- (D) Cottages must abut the courtyard on at least two sides of the courtyard.
- (E) The common courtyard must be at least 15 feet wide at its narrowest width.


Figure 14. Cottage Cluster Orientation and Common Courtyard Standards

9. *Community Buildings.* Cottage cluster projects may include community buildings for the shared use of residents that provide space for accessory uses such as community meeting rooms, guest housing, exercise rooms, day care, or community eating areas. Community buildings must meet the following standards:
 - a. Each cottage cluster is permitted one community building.
 - b. The community building shall have a maximum floor area of 1,400 sf.
 - c. A community building that meets the definition of a dwelling unit must meet the maximum 900 square foot footprint limitation that applies to cottages (pursuant to subsection (.14)(F.5.)), unless a covenant is recorded against the property stating that the structure is not a legal dwelling unit and will not be used as a primary dwelling.
10. *Pedestrian Access.*

- a. An accessible pedestrian path must be provided that connects the main entrance of each cottage to the following:
 - i. The common courtyard;
 - ii. Shared parking areas;
 - iii. Community buildings; and
 - iv. Sidewalks in public rights-of-way abutting the site or rights-of-way if there are no sidewalks.
 - b. The pedestrian path must be hard-surfaced and a minimum of four feet wide.
11. *Windows.* Cottages within 20 feet of a street property line must meet any window coverage requirements of the applicable base zone.
12. *Parking Design (see Figure 15. Cottage Cluster Parking Design Standards).*
- a. *Clustered parking.* Off-street parking may be arranged in clusters, subject to the following standards:
 - i. A parking cluster must not exceed five contiguous spaces.
 - ii. Parking clusters must be separated from other spaces by at least four feet of landscaping.
 - iii. Clustered parking areas may be covered.
 - iv. Parking areas must also meet the standards in Subsections 4.155(.02)—(.03), except where they conflict with these standards.
 - b. *Parking location and access.*
 - i. Off-street parking spaces and vehicle maneuvering areas shall not be located between a street property line and the front façade of cottages located closest to the street property line. This standard does not apply to alleys.
 - ii. Off-street parking spaces shall not be located within ten feet of any property line, except alley property lines.
 - iii. Driveways and drive aisles are permitted within ten feet of property lines.
 - c. *Screening.* Landscaping, fencing, or walls at least three feet tall shall separate clustered parking areas and parking structures from common courtyards and public streets.
 - d. *Garages and carports.*
 - i. Garages and carports (whether shared or individual) must not abut common courtyards.
 - ii. Individual attached garages up to 200 square feet shall be exempted from the calculation of maximum building footprint for cottages.
 - iii. Individual detached garages must not exceed 400 square feet in floor area.
 - iv. Garage doors for attached and detached individual garages must not exceed 20 feet in width.
13. *Accessory Buildings.* Accessory buildings must not exceed 400 square feet in floor area.
14. *Existing Structures.* On a lot or parcel to be used for a cottage cluster project, an existing detached single-family detached dwelling on the same lot at the time of proposed development

of the cottage cluster may remain within the cottage cluster project area under the following conditions:

- a. The existing dwelling may be nonconforming with respect to the requirements of this subsection (.14)F.
- b. The existing dwelling may be expanded up to a maximum height of 25 feet or a maximum building footprint of 900 square feet; however, existing dwellings that exceed these maximum height and/or footprint standards may not be expanded.
- c. The existing dwelling shall be excluded from the calculation of orientation toward the common courtyard, per subsection (.14)F.7.b.



- (A)** Parking allowed in clusters of up to 5 spaces. Clusters separated by minimum 4 feet of landscaping.
- (B)** No parking or vehicle area within 20 feet from street property line (except alley).
- (C)** No parking within 10 feet from other property lines (except alley). Driveways and drive aisles permitted within 10 feet.
- (D)** Screening required between clustered parking areas or parking structures and public streets or common courtyards.
- (E)** Garages and carports must not abut common courtyards. Garage doors for individual garages must not exceed 20 feet in width.

Figure 15. Cottage Cluster Parking Design Standards

- G. Standards applicable to Cluster Housing besides Cottage Clusters.

1. *Architectural Consistency.* Architecture shall be consistent within the same two-unit, three-unit, or four-unit cluster. However, facade variety standards in Subsection (.14)C.1. shall continue to apply. Architectural consistency is defined by adherence to all of the following:
 - a. Use of the same primary and supporting façade materials throughout the cluster.
 - b. Use of no more than two roof pitch angles.
 - c. Use of the same door size for each primary entrance in the structures.
2. *Entry Orientation.*
 - a. The entry orientation standards apply as follows:
 - i. At least one main entrance for each cluster home must meet the standards in subsections b and c below.
 - b. The entrance must be within eight feet of the longest street-facing exterior wall of the dwelling unit or if no exterior wall faces a street the front of the dwelling unit, facing a common drive or open space as designated by the applicant; and
 - c. The entrance must either:
 - i. Face the street (see Figure 2. Main Entrance Facing the Street);
 - ii. Be at an angle of up to 45 degrees from the street (see Figure 3. Main Entrance at 45° Angle from the Street); or
 - iii. Open onto a porch (see Figure 4. Main Entrance Opening onto a Porch). The porch must:
 - Be at least 25 square feet in area; and
 - Have at least one entrance facing the street or have a roof.
3. *Windows.* A minimum of 15 percent of the area of all street-facing facades must include windows or entrance doors. Facades separated from the street property line by a dwelling are exempt from meeting this standard. See Figure 5. Window Coverage.
4. *Garages and Off-Street Parking Areas.* The combined width of all garages and outdoor on-site parking and maneuvering areas shall not exceed a total of 50 percent of any street frontage (other than an alley). Garages and off-street parking areas that are separated from the street property line by a dwelling are not subject to this standard. (See Figure 6. Width of Garages and Parking Areas).
5. *Driveway Approach.* Driveway approaches must comply with all of the following:
 - a. The total width of all driveway approaches must not exceed 32 feet per frontage, as measured at the property line (see Figure 7. Driveway Approach Width and Separation on Local Street). For lots or parcels with more than one frontage, see subsection c.
 - b. Driveway approaches may be separated when located on a local street.
 - c. In addition, lots or parcels with more than one frontage must comply with the following:
 - i. Lots or parcels must access the street with the lowest transportation classification for vehicle traffic. For lots or parcels abutting an alley that is improved with pavement access must be taken from the alley (see Figure 8. Alley Access).

- ii. Lots or parcels with frontages only on collectors and/or arterial streets must meet the access standards in the Wilsonville Public Works Standards.
 - iii. Lots or parcels with frontages only on local streets may have either:
 - Two driveway approaches not exceeding 32 feet in total width on one frontage; or
 - One maximum 16-foot-wide driveway approach per frontage (see Figure 9. Driveway Approach Options for Multiple Local Street Frontages).
6. *Setbacks.*
- a. **Building Separation.** Cluster housing structures shall be separated by a minimum distance of six feet. The minimum distance between all other structures, including accessory structures, shall be in accordance with building code requirements.
 - b. All other setbacks are provided in the applicable base zone.
7. *Pedestrian Access.*
- a. An accessible pedestrian path must be provided that connects the main entrance of each unit to the following:
 - i. Shared open space;
 - ii. Shared parking areas; and
 - iv. Sidewalks in public rights-of-way abutting the site or rights-of-way if there are no sidewalks.
 - b. The pedestrian path must be hard-surfaced and a minimum of four feet wide.
- H. **Combining Unit Types in One Development.**
- 1. If a project proposes a mix of middle housing types which creates a conflict with various standards, the more restrictive standards shall apply.
- I. **Existing Structures and Conversions:**
- 1. Where a residential structure is converted from one type of dwelling unit to another without any additions, the design standards in C.—H. do not apply.
 - 2. Where a residential structure is added on to, the design standards in C.—H. only apply if the footprint is expanded by 25 percent or more.
- J. **Alternative Discretionary Review:** As an alternative to meeting one or more design standards of this subsection an applicant may request Site Design Review by the Development Review Board of a proposed design. In addition to the Site Design Review Standards, affirmative findings shall be made that the following standards are met:
- 1. The request is compatible with existing surrounding development in terms of placement of buildings, scale of buildings, and architectural design;
 - 2. The request is due to special conditions or circumstances that make it difficult to comply with the applicable Design Standards, or the request would achieve a design that is superior to the design that could be achieved by complying with the applicable Design Standards; and
 - 3. The request continues to comply with and be consistent with State statute and rules related to Middle Housing, including being consistent with State definitions of different Middle Housing types.

(Ord. No. 677, 3-1-2010; Ord. No. 682, 9-9-2010; Ord. No. 704, 6-18-2012; Ord. No. 806, 7-17-2017; Ord. No. 825, 10-15-2018; Ord. No. 841, eff. 6-4-2020)