

ORDINANCE NO 2026-XXX

AN ORDINANCE AMENDING ARTICLE 3.09 “FLOOD DAMAGE PREVENTION” OF THE CODE OF ORDINANCES OF THE CITY OF WOLFFORTH, TEXAS ,AS AMENDED BY ADOPTING UPDATED REGULATIONS TO COMPLY WITH GUIDELINES ESTABLISHED BY THE FEDERAL EMERGENCY MANAGEMENT AGENCY; PROVIDING THAT THIS ORDINANCE SHALL BE CUMULATIVE OF ALL ORDINANCES; PROVIDING A SEVERABILITY CLAUSE; PROVIDING A SAVINGS CLAUSE; AND PROVIDING AN EFFECTIVE DATE.

WHEREAS, the City of Wolfforth is a home rule city acting under its charter adopted by the electorate pursuant to Article XI, Section 5 of the Texas Constitution and Chapter 9 of the Local Government Code; and

WHEREAS, in order to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions the City has adopted flood damage prevention ordinances; and

WHEREAS, the Federal Emergency Management Agency (FEMA) has issued a revised model ordinance related to flood damage prevention; and

WHEREAS, the City of Wolfforth desires to amend its ordinance to reflect the revised model ordinance provided by FEMA; and

WHEREAS, the Texas State Legislature had delegated the responsibility of local governmental units to adopt regulations that minimize flood losses by enacting the Flood Control Insurance Act set forth in Section 16.315 of the Texas Water Code; and

WHEREAS, after careful consideration, the City Council has determined that it is in the best interests of the citizens of the City of Wolfforth to adopt this ordinance.

NOW, THEREFORE, BE IT ORDAINED BY THE CITY COUNCIL OF THE CITY OF WOLFFORTH, TEXAS:

SECTION 1. § 3.09.018 through § 3.09.021 of Article 3.09 “Flood Damage Prevention” of Chapter 3 “Building Regulations” of the Wolfforth City Code are amended to read as follows and § 3.09.21 Penalties for noncompliance is renumbered as § 3.09.22:

§ 3.09.018 Specific standards for flood hazard reduction.

In all areas of special flood hazards where base flood elevation data has been provided as set forth in section 3.09.007, section 3.09.014(8), or section 3.09.019(c), the following provisions are required:

(1) Residential construction. New construction and substantial improvement of any residential structure shall have the lowest floor (including basement), elevated to two (2) feet above the base flood elevation. A registered professional engineer, architect, or land surveyor shall submit a certification to the floodplain administrator that the standard of this subsection as proposed in section 3.09.015(a), is satisfied.

(2) Nonresidential construction. New construction and substantial improvements of any commercial, industrial or other nonresidential structure shall either have the lowest floor (including basement) elevated to two (2) feet above the base flood level or together with attendant utility and sanitary facilities, be designed so that below the base flood level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy. A registered professional engineer or architect shall develop and/or review structural design, specifications, and plans for the construction, and shall certify that the design and methods of construction are in accordance with accepted standards of practice as outlined in this subsection. A record of such certification which includes the specific elevation (in relation to mean sea level) to which such structures are floodproofed shall be maintained by the floodplain administrator.

(3) Enclosures. New construction and substantial improvements, with fully enclosed areas below the lowest floor that are usable solely for parking of vehicles, building access or storage in an area other than a basement and which are subject to flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a registered professional engineer or architect or meet or exceed the following minimum criteria:

(A) A minimum of two openings on separate walls having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding shall be provided.

(B) The bottom of all openings shall be no higher than 1 foot above grade.

(C) Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.

(4) Manufactured homes.

(A) Require that all manufactured homes to be placed within zone A on a community's FHBM or FIRM shall be installed using methods and practices which minimize flood damage. For the purposes of this requirement, manufactured homes must be elevated and anchored to resist flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-

the-top or frame ties to ground anchors. This requirement is in addition to applicable state and local anchoring requirements for resisting wind forces.

(B) Require that manufactured homes that are placed or substantially improved within zones A1-30, AH, and AE on the community's FIRM on sites:

(i) Outside of a manufactured home park or subdivision;

(ii) In a new manufactured home park or subdivision;

(iii) In an expansion to an existing manufactured home park or subdivision;
or

(iv) In an existing manufactured home park or subdivision on which a manufactured home has incurred "substantial damage" as a result of a flood, be elevated on a permanent foundation such that the lowest floor of the manufactured home is elevated to two (2) feet above the base flood elevation and be securely anchored to an adequately anchored foundation system to resist flotation, collapse, and lateral movement.

(C) Require that manufactured homes be placed or substantially improved on sites in an existing manufactured home park or subdivision with zones A1-30, AH and AE on the community's FIRM that are not subject to the provisions of subsection (4) of this section be elevated so that either:

(i) The lowest floor of the manufactured home is at two (2) feet above the base flood elevation; or

(ii) The manufactured home chassis is supported by reinforced piers or other foundation elements of at least equivalent strength that are no less than 36 inches in height above grade and be securely anchored to an adequately anchored foundation system to resist flotation, collapse, and lateral movement.

(5) Recreational vehicles. Require that recreational vehicles placed on sites within zones A1-30, AH, and AE on the community's FIRM either:

(A) Be on the site for fewer than 180 consecutive days;

(B) Be fully licensed and ready for highway use; or

(C) Meet the permit requirements of section 3.09.015(a), and the elevation and anchoring requirements for "manufactured homes" in subsection (4) of this section. A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached additions.

3.09.019 Standards for subdivision proposals.

- (a) All subdivision proposals including the placement of manufactured home parks and subdivisions shall be consistent with sections 3.09.002, 3.09.003, and 3.09.004 of this article.
- (b) All proposals for the development of subdivisions including the placement of manufactured home parks and subdivisions shall meet floodplain development permit requirements of section 3.09.008; section 3.09.015; and the provisions of sections 3.09.017 through 3.09.021 of this article.
- (c) Base flood elevation data shall be generated for subdivision proposals and other proposed development including the placement of manufactured home parks and subdivisions which is greater than 50 lots or 5 acres, whichever is lesser, if not otherwise provided pursuant to section 3.09.007 or section 3.09.014(8) of this article.
- (d) Base flood elevation data shall be generated by a detailed engineering study for all Zone A areas, within 100 feet of the contour lines of Zone A areas, and other streams not mapped by FEMA, as indicated on the community's FIRM.
- (e) All subdivision proposals including the placement of manufactured home parks and subdivisions shall have adequate drainage provided to reduce exposure to flood hazards.
- (f) All subdivision proposals including the placement of manufactured home parks and subdivisions shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize or eliminate flood damage.

3.09.020 Standards for areas of shallow flooding (AO/AH zones).

Located within the areas of special flood hazard established in section 3.09.007, are areas designated as shallow flooding. These areas have special flood hazards associated with flood depths of 1 to 3 feet where a clearly defined channel does not exist, where the path of flooding is unpredictable, and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow; therefore, the following provisions apply:

- (1) All new construction and substantial improvements of residential structures have the lowest floor (including basement) elevated two (2) feet above the base flood elevation or the highest adjacent grade at least as high as the depth number specified in feet on the community's FIRM (at least 2 feet if no depth number is specified); or
- (2) All new construction and substantial improvements of nonresidential structures:
 - (A) Have the lowest floor (including basement) elevated two (2) feet above the base flood elevation or the highest adjacent grade at least as high as the depth number specified in feet on the community's FIRM (at least two feet if no depth number is specified); or

(B) Together with attendant utility and sanitary facilities be designed so that below the base specified flood depth in an AO zone, or below the base flood elevation in an AH zone, level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads of effects of buoyancy.

(3) A registered professional engineer or architect shall submit a certification to the floodplain administrator that the standards of this section, as proposed in section 3.09.015, are satisfied.

(4) Require within zones AH or AO adequate drainage paths around structures on slopes, to guide floodwaters around and away from proposed structures.

3.09.021 Floodways

Floodways located within areas of special flood hazard established in 3.09.007, are areas designated as floodways. Since the floodway is an extremely hazardous area due to the velocity of flood waters which carry debris, potential projectiles and erosion potential, the following provisions shall apply:

(1) Encroachments are prohibited, including fill, new construction, substantial improvements and other development within the adopted regulatory floodway unless it has been demonstrated through hydrologic and hydraulic analyses performed in accordance with standard engineering practice that the proposed encroachment would not result in any increase in flood levels within the community during the occurrence of the base flood discharge.

(2) If 3.09.021(1) above is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of this article.

(3) Under the provisions of 44 CFR Chapter 1, Section 65.12, of the National Flood Insurance Program Regulations, a community may permit encroachments within the adopted regulatory floodway that would result in an increase in base flood elevations, provided that the community first completes all of the provisions required by Section 65.12.

3.09.022 Penalties for noncompliance.

No structure or land shall hereafter be constructed, located, extended, converted, or altered without full compliance with the terms of this court order and other applicable regulations. Violation of the provisions of this court order by failure to comply with any of its requirements (including violations of conditions and safeguards established in connection with conditions) shall constitute a misdemeanor. Any person who violates this court order or fails to comply with any of its requirements shall upon conviction thereof be fined not more than \$500.00 for each violation, and in addition shall pay all costs and

expenses involved in the case. Nothing herein contained shall prevent the city from taking such other lawful action as is necessary to prevent or remedy any violation.

SECTION 2. This Ordinance shall be cumulative of all provisions of the Code of Ordinances of the City of Wolfforth, and other applicable City ordinances, except where the provisions of this Ordinance are in direct conflict with the provisions of such ordinances, in which event the applicability of the conflicting provisions of such ordinances are hereby repealed as they relate to flood damage prevention.

SECTION 3. It is hereby declared to be the intention of the City Council that the phrases, clauses, sentences, paragraphs, and sections of this ordinance are severable, and if any phrase, clause, sentence, paragraph or section of this ordinance shall be declared unconstitutional by the valid judgment or decree of any court of competent jurisdiction, such unconstitutionality shall not affect any of the remaining phrases, clauses, sentences, paragraphs or sections of this ordinance, since the same would have been enacted by the City Council without the incorporation in this ordinance of any such unconstitutional phrase, clause, sentence, paragraph or section.

SECTION 4. All rights and remedies of the City of Wolfforth are expressly saved as to any of all violations of ordinances affecting the floodplain which have accrued at the time of the effective date of this ordinance; and, as to such accrued violations and all pending litigation, both civil and criminal, whether pending in court or not, under such ordinances, same shall not be affected by this ordinance but may be prosecuted until final disposition by the courts.

SECTION 5.

This Ordinance shall be in full force and effect from and after its passage a, and it is so ordained.

PASSED AND APPROVED on this 15th day of June, 2026.

Charles Addington, II, Mayor
City of Wolfforth, TX

ATTEST:

Terri Robinette, City Secretary