
VICINITY MAP




verizon^v

PROJECT NEW TELECOMMUNICATION CELL SITE

SITE NAME **PILOT GROVE**

SITE ADDRESS **5085 BENNETT ROAD** WYLIE, TX. 75098 **COLLIN COUNTY** 33.015568°, -96.490606°

ENLARGED MAP



LEGAL DESCRIPTION

BEING A LEASE AREA CONTAINING 0.055 ACRES (2,400 SQ.FT.) LOCATED IN THE F DEL PINA SURVEY, ABSTRACT NO. 688, COLLIN COUNTY, TEXAS, AND BEING OUT OF AND PART OF LOT 1, BLOCK A OF THE WYLIE EAST HIGH SCHOOL ADDITION AS RECORDED IN PLAT BOOK 2008, PAGE 138, PLAT RECORDS OF COLLIN COUNTY, TX, SAID 63.5-ACRE TRACT BEING MORE PARTICULARLY DESCRIBED BY METES AND BOUNDS

AS FOLLOWS WITH ALL CONTROL REFERRED TO THE TEXAS STATE PLANE COORDINATE SYSTEM, NORTH CENTRAL ZONE (4202), NORTH AMERICAN DATUM OF 1983:

SCOPE OF WORK: NEW CELLULAR COMMUNICATIONS SITE WITH 100' HIGH MONOPOLE TOWER

- NEW CELL SITE COMPOUND
- NEW CMU BRICK WALL NEW ELECTRIC & FIBER SERVICE TO SITE - NEW COMMUNITY RACK FOR POWER/FIBER DEMARCS
- NEW 25' CONCRETE ACCESS ROAD NEW RETAINING WALL

☐ APPROVED ☐ DENIED STAFF P&Z Date Initials NEIGHBORHOOD

See the Staff Approval Letter or P&Z Result Memo for an

ACTION

PROJECT SUMMARY

SITE INFORMATION

JURISDICTION: COLLIN COUNTY OCCUPANCY: UNMANNED ZONE: AG/30 CONSTRUCTION TYPE: NEW CELL SITE MONOPOLE TOWER COORDINATES: 33.015568*, -96.490606* ELEVATION: 437.40' A.M.S.L.

PROPERTY OWNER

WYLIE ISD OWNER CONTACT: SCOTT RODERICK 951 S. Ballard Ave. WYLIE, TX 75098 PHONE: 972-429-3027

APPLICANT

VERIZON WIRELESS 6696 TRI COUNTY PARKWAY STE. 100 SCHERTZ, TX. 78154

SURVEYOR

H&S SURVEYING, INC. 201 N. BICKFORD, EL RENO, OK 73036 PHONE: (405) 262-0249 FAX: (405) 262-5107 HSSURVEYING1@AOL.COM

ENGINEER CONSULTANT

ALLPRO CONSULTING GROUP, INC. 9221 LYNDON B. JOHNSON FWY, SUITE 204 DALLAS, TEXAS 75243 OFFICE: (972) 231-8893 FAX: (866) 364-8375 CONTACT: CHIYU ZHANG, P.E.

SHEET INDEX

T-1 COVER PAGE

WYLIE EAST FINAL PLAT (BY OTHERS)

SV-1 SURVEY (BY OTHERS)

EXHIBIT A-2

OVERALL SITE PLAN

ENLARGED & COMPOUND/LANDSCAPE PLAN Z-2 Z-3 ELEVATION / ANTENNA LAYOUT PLAN

SITE DETAILS

Z-4SITE DETAILS

EROSION CONTROL DETAILS



TEXAS ONE CALL

CONTRACTOR TO CALL 48 HOURS BEFORE DIGGING! PHONE: (800) 545-6005 INDEPENDENT LOCATORS TO BE LISED ON ALL SITES

THESE DRAWINGS ARE SCALED FOR 24"X36" SHEET

verizon

ACGI# 23-1664

DRAWN BY: MG

CHECKED BY: CZ

ISSUE FOR ZONING REVIEW



02/01/24 REVIEW ONLY

PILOT GROVE


LEGAL DESCRIPTION WYLIE EAST HIGH SCHOOL ADDITION 63.5 ACRE TRACT BLOCK A, LOT1 VOLUME 2018 PAGE 349 PLAT RECORDS OF COLIN COUNTY, TX


> WYI IF. TX. 75098 COLLIN COUNTY


DATE: 08/31/23


SHEET TITLE TITLE PAGE

T-1










PLANTING SCHEDULE COMMON NAME QUANTI: CALIPER HEIGHT SPREAD 10 ILEX OPACA 8' MIN. FULL, DENSE. PLANT AS SHOWN AMERICAN HOLLY MC MYRICA CERIFERA SOUTHERN WAX MYRTLE 24"-36" 24"-36" 30 FULL, DENSE. PLANT AS SHOWN

*TREE CONTAINER TO BE MIN. 25 GAL OR EQUIVALENT BALL AND BURLAP.



GENERAL PLANTING NOTES:

1. ALL PLANT MATERIALS SHALL BE SPECIFIED TO BE EQUAL TO OR BETTER THAN THE STANDARDS FOR NURSERY STOCK,

1. ALL PLANT MATERIALS SHALL BE SPECIFIED TO BE EQUAL TO OR BETTER THAN THE STANDARDS FOR NURSERY STOCK, BY THE AMERICAN NURSERY AND LANDSCAPERA SSOCIATION (ANLA).
2. PLANTING SEASON RESTRICTIONS: ALL BALLED AND BURLAPPED PLANTS SHALL BE INSTALLED BETWEEN OCTOBER 1 AND NOVEMBER 15 UNLESS OTHERWISE AUTHORIZED BY THE LANDSCAPE ARCHITECT. ALL CONTAINER GROWN PLANTS SHALL BE INSTALLED BETWEEN SEPTEMBER 15 AND MAY 15 UNLESS OTHERWISE AUTHORIZED BY THE LANDSCAPE ARCHITECT.
3. FINISHED GRADES ON GRADING PLANS THAT OCCUR IN SHALLB BEDS SPECIFY TOP OF FINISHED MULCH GRADES.
LANDSCAPE CONTRACTOR SHALL NOT EXCEED THESE GRADES WHEN BEDS ARE COMPLETE.

4. TOP OF MULCH SHALL FINISH 1" BELOW ADJACENT PAVEMENT.

5. VERIFICATION OF TOTAL QUANTITIES AS SHOWN IN THE "PLANT SCHEDULE" SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR, UPON DISCREPANCIES, THE PLANTING PLAN SYMBOLS SHALL GOVERN.

CONTINUATION. OF THE PLANTING PLANS THROUGH SHALL GUYERN.


6. NEW PLANTING SHALL BE LOCATED AS SHOWN ON PLANS. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING THE LOCATION OF ALL SITE ELEMENTS AND UTILITIES. IF DISCREPANCIES OCCUR, OR IF OBSTRUCTIONS BELOW GROUND OVERHEAD ARE ENCOUNTERED, THE CONTRACTOR SHALL NOTIFY THE LANDSCAPE ARCHITECT. NECESSARY ADJUSTMENTS SHALL BE MADE ONLY UPON APPROVAL OF THE LANDSCAPE ARCHITECT. NECESSARY ADJUSTMENTS SHALL BE MADE ONLY UPON APPROVAL OF THE LANDSCAPE ARCHITECT.

-2"-3" ORGANIC MULCH (WIPE DOWN AT STEM) REMOVE BURLAP FROM TOP AND SIDES OF BALL (LEAVE IN PLACE) 4"-6" HT. MULCH SAUCER -FINISHED CRADE _2'-3' WIDTHS_ OF ROOTBALL -UNDISTURBED SOIL

SHRUB PLANTING DETAIL

THE PROPOSED VEGETATION HAS HAD OPPORTUNITY TO BECOME ESTABLISHED.

LANDSCAPING (OR) 1/8" = 1'-0" (11x17)



2. GENERAL CONTRACTOR TO VERIFY ALL GATE DIMENSION PRIOR TO CONSTRUCTING GATE.

MASONRY

- HOLLOW CONCRETE MASONRY UNITS: GRADE N, LIGHTWEIGHT WITH A COMPRESSIVE STRENGTH OF $F=1500\,$ PSI ON THE NET AREA.
- B. GROUT: 2000 PSI, MINIMUM 28 DAY COMPRESSIVE STRENGTH. VIBRATE GROUT IMMEDIATELY AFTER POURING AND AGAIN AFTER 5 MINUTES. GROUT SHALL CONFORM TO TO ASTM C476 AND UBC 2103. MIX GROUT FOR AT LEAST FIVE MINUTES AND UNTIL MIX HAS BEEN ATTAINED. GROUT SHALL HAVE SUFFICIENT WATER ADDED TO PRODUCE A CONSISTENCY FOR POURING WITHOUT SEGREGATION USE GROUT WITHIN 1.5 HOURS OF
- C. MORTAR: CEMENT-LIME TYPES, 1800 PSI MINIMUM 28 DAY COMPRESSIVE STRENGTH. CONFORM TO UBC 2103.
- D. 2,500 PSI STRENGTH CONCRETE AT 28 DAY 3" TO 5" SLUMP.
- 2. LAY UNITS IN RUNNING BOND. CORNERS SHALL HAVE A STANDARD BOND BY OVER-LAPPING UNITS.
- 3. MAXIMUM GROUT LIFT WITHOUT CLEAN-OUTS SHALL BE 4'-0"
- 4. TIE VERTICAL REINFORCING AT EACH END OF BAR AND AT 4'-0" MAXIMUM VERTICAL SPACING USING SINGLE WIRE LOOP TYPE TIES AS MANUFACTURED BY A.A. WIRE PRODUCTS COMPANY OR APPROVED ALTERNATE.
- 5. SEE ARCHITECTURAL DRAWINGS FOR LOCATIONS OF EXPANSION AND CONTROL JOINTS.
- GROUT SOLID ALL WALLS IN CONTACT WITH EARTH, RETAINING WALLS, STEM WALLS, AND AS NOTED ON DRAWINGS.
- 7. GROUTED MASONRY SHALL BE CONSTRUCTED IN SUCH A MANNER THAT ALL ELEMENTS OF THE MASONRY ACT TOGETHER AS A STRUCTURAL ELEMENT.
- 8. KNOX PADLOCK KEYED TO WYLIE FIRE DEPARTMENT WILL BE REQUIRED ON GATE FOR FD ACCESS TO SITE IN EMERGENCIES. GATE LOCKING MECHANISM MUST SUPPORT MULTIPLE LOCK ACCESS. CONTRACTOR MUST SUPPLY KNOX PADLOCK FOR FD INSTALLATION.



ACGI# 23-1664

DRAWN BY: MG

CHECKED BY: CZ

ISSUE FOR ZONING REVIEW ISSUE FOR ZONING REVIEW 02/01/24 ISSUE FOR ZONING REVIEW



02/01/24



PILOT GROVE

OWNER WYLIE I.S.D.

LEGAL DESCRIPTION WYLIE EAST HIGH SCHOOL

ADDITION 63.5 ACRE TRACT BLOCK A, LOT1 VOLUME 2018 PAGE 349 PLAT RECORDS OF COLIN COUNTY, TX


> WYI IF. TX. 75098 COLLIN COUNTY

> > DATE: 08/31/23

SHEET TITLE SITE DETAILS

Z-4

SCALE: 1 1/2" = 1'-0" (24x3 (OR) 3/4" = 1'-0" (11v17)



- ALL VEGETATIVE AND STRUCTURAL EROSION CONTROL PRACTICES SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE MINIMUM STANDARDS AND SPECIFICATIONS OF THE APPLICABLE STATE ADOPTED "PROCEDURES AND STANDARDS FOR URBAN SOIL EROSION AND SEDIMENTATION CONTROL" AND THE "STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL" OF THE STATE ENVIRONMENTAL PROTECTION
- A SOIL EROSION CONTROL FENCE SHALL BE INSTALLED BEFORE DISTURBING THE GROUND AND SHALL BE PROVIDED AS SHOWN ON THE PLAN. THE CONDITION OF THE FENCE SHALL BE INSPECTED REGULARLY AND AFTER EVERY RAINSTORM THAT MIGHT PRODUCE RUNOFF. DAMAGED OR DETERIORATED ITEMS SHALL BE REPLACED AND MAINTAINED IN AN EFFECTIVE CONDITION.
- SOIL EROSION CONTROL MEASURES SHALL BE INCLUDED IN CONTRACTOR BID AND PRICING.
- THE ENTIRE SITE SHALL BE GRADED SO THAT NO STORM WATER RUNOFF AND LIKEWISE SOIL SEDIMENT CAN FLOW
- ALL INLETS, STRUCTURES, PIPES, SWALES, AND ROADS SHALL BE KEPT CLEAN AND FREE OF DIRT AND SILT.
- MAINTAIN SOIL EROSION CONTROL MEASURES THROUGH THE DURATION OF THIS PROJECT.
- SEDIMENT DEPOSITS SHALL BE REMOVED WHEN REACHING ONE HALF THE HEIGHT OF THE BARRIER.
- ALL SOIL EROSION CONTROL MEASURES SHALL REMAIN IN PLACE UNTIL ALL DISTURBED EARTH HAS BEEN PAVED
- ANY EXCESS TOPSOIL THAT IS TO BE STOCKPILED FOR A PERIOD LONGER THAN 2 WEEKS SHALL BE PROTECTED BY EXCAVATING A TRENCH COMPLETELY AROUND THE STOCKPILE TO PREVENT THE ESCAPE OF SOIL MATERIAL THROUGH STORM WATER RUNOFF. STOCKPILES THAT ARE TO REMAIN LONGER THAN 14 DAYS SHALL BE SEEDED WITH AN APPROPRIATE GROUND COVER.
- TO PREVENT SOIL FROM LEAVING THE SITE ON CONSTRUCTION VEHICLE WHEELS, TEMPORARY GRAVEL ROADS AT WORK ENTRANCES SHALL BE CONSTRUCTED AND SHALL EXTEND INTO JOB SITE. THE EXISTING PAVEMENT SURFACES SHALL BE INSPECTED DAILY FOR SOIL DEBRIS AND SHALL BE CLEANED WHEN NECESSARY.
- 11. REPLACE SOIL EROSION CONTROL MEASURES WITH SEED, SOD AND TOPSOIL AT THE COMPLETION OF THE PROJECT.
- SOIL EROSION CONTROL MEASURES SHALL BE REMOVED AND PROPERLY DISPOSED OF WHEN PROJECT IS

	_
	DF
	Cł
	0
	2
	=

ACGI# 23-1664

DRAWN BY: MG

CHECKED BY: CZ

09/27/23 ISSUE FOR ZONING REVIEW 11/01/23 ISSUE FOR ZONING REVIEW



02/01/24



PILOT GROVE

OWNER WYLIE I.S.D.

LEGAL DESCRIPTION WYLIE EAST HIGH SCHOOL ADDITION 63.5 ACRE TRACT

BLOCK A, LOT1 VOLUME 2018 PAGE 349

PLAT RECORDS OF

COLIN COUNTY, TX

SOIL EROSION AND SEDIMENT CONTROL NOTES

4

NOT USED

3

NOT USED

2



1. EXCAVATE THE TRENCH.



3. WEDGE LOOSE STRAW BETWEEN BALES.

4. BACKFILL AND COMPACT THE

2. PLACE AND STAKE STRAW BALES.




1. THE CONTRACTOR SHALL REWORK (DRY, SCARIFY, ETC...) ALL MATERIAL NOT SUITABLE FOR SUB GRADE IN ITS PRESENT STATE. IF THE MATERIAL, AFTER REWORKING, REMAINS UNSUITABLE THEN THE CONTRACTOR SHALL UNDERCUT THIS MATERIAL AND REPLACE WITH APPROVED MATERIAL AT HIS EXPENSE. ALL SUB GRADES SHALL BE PROOF ROLLED WITH A FULLY LOADED TANDEM AXLE DUMP TRUCK PRIOR TO PAVING. ANY SOFT MATERIAL SHALL BE REWORKED OR REPLACED.


2. THE CONTRACTOR IS REQUIRED TO MAINTAIN ALL DITCHES, PIPES, AND OTHER DRAINAGE STRUCTURES FREE FROM OBSTRUCTION UNTIL WORK IS ACCEPTABLE BY THE OWNER. THE CONTRACTOR IS RESPONSIBLE FOR ANY DAMAGES CAUSED BY FAILURE TO MAINTAIN DRAINAGE STRUCTURES IN OPERABLE CONDITION.

3. ALL MATERIALS AND WORKMANSHIP SHALL BE WARRANTED FOR ONE (1) YEAR FROM DATE OF ACCEPTANCE.

4. ALL DIMENSIONS SHALL BE VERIFIED WITH THE PLANS (LATEST REVISION) PRIOR TO COMMENCING CONSTRUCTION. NOTIFY THE OWNER IMMEDIATELY IF DISCREPANCIES ARE DISCOVERED. THE CONTRACTOR SHALL HAVE A SET OF APPROVED PLANS AVAILABLE AT THE SITE AT ALL TIMES WHEN WORK IS BEING PRE FORMED. A DESIGNATED RESPONSIBLE EMPLOYEE SHALL BE AVAILABLE FOR CONTACT BY GOVERNING AGENCY INSPECTORS.




1. SET POSTS AND EXCAVATE A 4"X4" TRENCH UPSLOPE ALONG POSTS.



3. ATTACH THE FILTER FABRIC TO THE WRE FENCE AND EXTEND IT INTO THE TRENCH.



2. STAPLE WIRE FENCING TO THE LINE OF



4. EXTENSION OF FABRIC AND WIRE INTO

SILT FENCE

ADDRESS 5085 BENNETT ROAD WYI IF. TX. 75098 COLLIN COUNTY

DATE: 08/31/23

EROSION CONTROL DETAILS

Z-6

STRAW BALE BARRIER

EROSION CONTROL DETAIL NITS