



ECS Southwest, LLP

Geotechnical Engineering Report

Stone Road Improvements

WA Allen Boulevard to Bennett Road
Wylie, Texas

ECS Project Number 19:8613

March 16, 2022





March 16, 2022

Mr. Tim Porter, P.E., CFM
Director of Public Works
City of Wylie
949 Hensley Lane, Suite 300
Wylie, Texas 75098

ECS Project No. 19:8613

Reference: Geotechnical Engineering Report
Stone Road Improvements
From WA Allen Boulevard to Bennett Road
Wylie, Texas

Dear Mr. Porter:

ECS Southwest, LLP (ECS) has completed the subsurface exploration, laboratory testing, and geotechnical engineering analyses for the above-referenced project. Our services were performed in general accordance with our agreed to scope of work. This report presents our understanding of the geotechnical aspects of the project along with the results of the field exploration and laboratory testing conducted, and our recommendations.

It has been our pleasure to be of service to you for the project. We would appreciate the opportunity to remain involved during the continuation of the design phase, and we would like to provide our services during construction phase operations as well to verify subsurface conditions assumed for this report. Should you have any questions concerning the information contained in this report, or if we can be of further assistance to you, please contact us.

Respectfully submitted,

ECS Southwest, LLP

Che-Hung (Chris) Tsai, Ph.D., P.E.
Geotechnical Senior Project Manager
ctsai@ecslimited.com



Michael Batuna, P.E.
Principal Engineer
mbatuna@ecslimited.com

The electronic seal on this document was authorized by Michael P. Batuna No. 92147, on March 16, 2022

TABLE OF CONTENTS

EXECUTIVE SUMMARY	1
1.0 INTRODUCTION	2
2.0 PROJECT INFORMATION	3
2.1 Project Location/current site use.....	3
2.2 Proposed Construction.....	3
3.0 FIELD EXPLORATION	4
3.1 Subsurface characterization.....	4
3.3 Groundwater Observations.....	5
3.4 Laboratory testing	6
4.0 DESIGN RECOMMENDATIONS	7
4.1 Potential Vertical Movements	7
4.2 Soluble Sulfate.....	7
4.3 Pavement Section.....	7
4.3.1 Pavement Materials.....	10
4.3.2 Pavement Maintenance.....	10
5.0 SITE CONSTRUCTION RECOMMENDATIONS	12
5.1 Subgrade Preparation	12
5.1.1 Proofrolling	12
5.2 Earthwork Operations	13
5.3 Material Specifications.....	13
6.0 CLOSING	15

APPENDICES

Appendix A – Figures

- Site Location Diagram
- Boring Location Diagram
- Generalized Subsurface Soil Profile
- Regional Geology
- General Recommendations for Quality Assurance (QA) Testing

Appendix B – Field Operations

- Reference Notes for Boring Logs
- Subsurface Exploration Procedure
- Boring Logs

Appendix C – Laboratory Testing

- Laboratory Testing Summary
- Lime/pH Series Summary

Appendix D – WinPAS Pavement Design Outputs

EXECUTIVE SUMMARY

The following summarizes the main findings of the exploration, particularly those that may have a cost impact on the planned roadway improvements. Further, our pavement and subgrade improvement recommendations are summarized. Information gleaned from the executive summary should not be utilized in lieu of reading the entire geotechnical report.

- Based on our interpretation of the borings drilled for this study, the existing pavements generally consist of 2 to 4 inches of asphalt concrete (AC). Sand and gravel fill (3 to 10 inches) was encountered below the asphalt concrete in all the borings. Below the pavement and gravel fill, soil fill, lean clay and fat clay were encountered in the borings.
- Groundwater seepage was not observed in borings during drilling and at the completion of drilling operations.
- Design values for the proposed pavement, subgrade preparation and stabilization, as well as materials specifications are provided in the report. Based on the anticipated traffic, the pavement section for the planned reconstruction may consist of 9 inches of Asphalt Concrete (AC) pavement and 8 inches of Portland Cement Concrete (PCC) for a 25-year design life. For a 40 year design life, the proposed pavement may consist of 9 inches of Portland Cement Concrete (PCC). The AC and PCC pavements can be supported on lime stabilized subgrade, flexible base with geogrid, or cement treated Reclaimed Asphalt Pavement (RAP) base.
- The potential vertical movement (PVM) of the site is estimated to be about 3 to 5 inches under a dry soil condition. These potential movements reflect moisture changes in the soil that can occur over the life of the structure and after construction is complete.
- It is recommended that ECS conduct a geotechnical review of the project plans (prior to issuance for construction) to check to see that ECS' geotechnical recommendations have been properly interpreted and implemented.
- To prevent misinterpretation of ECS recommendations, ECS should be retained to perform quality control testing and documentation during construction of the earthwork and foundations for the project.

1.0 INTRODUCTION

The purpose of this study was to provide geotechnical information for the design and reconstruction of the street pavements in Wylie, Texas. The recommendations developed for this report are based on project information provided by the client. This report contains the results of our subsurface explorations and geotechnical laboratory testing programs, site characterization, engineering analyses, and recommendations for the design and construction of the planned pavement improvements.

Our services were performed in general accordance with ECS Proposal No. 19:11708-GP, dated November 22, 2021. The project was authorized by client on January 3, 2022. The terms of this agreement will be according to the Contract for Professional Engineering Services between the City of Wylie and ECS Southwest, LLP.

This report contains the procedures and results of our subsurface exploration with soil borings and laboratory testing programs, review of existing site conditions, engineering analyses, and recommendations for the design and construction of the project.

The report includes the following items.

- A brief review and description of our field and laboratory test procedures and the results of testing conducted.
- A review of site conditions.
- A review of area and site geologic conditions.
- A review of subsurface soil stratigraphy with pertinent available physical properties.
- A final copy of our soil test borings.
- Recommendations for pavement design.
- Recommendations for site preparation and construction of compacted fills, including an evaluation of on-site soils for use as compacted fills.

2.0 PROJECT INFORMATION

2.1 PROJECT LOCATION/CURRENT SITE USE

The proposed project consists of the pavement improvements of the Stone Road which include a 2-lane undivided roadway from WA Allen Boulevard to Bennett Road in Wylie, Texas. The project location is depicted in the attached Site Location Diagram in Appendix A and below.




Figure 2.1.1 Site Location Diagram

2.2 PROPOSED CONSTRUCTION

The following information was provided by the City of Wylie and explains our understanding of the planned development of the street section.

Table 2.2.1 A Summary of Design Information

SUBJECT	DESIGN INFORMATION / ASSUMPTIONS
Street Classification	A local residential street and will be upgraded to future roadway as a Secondary Thoroughfare with 4-lane divided concrete with 100-foot right-of-way.
Existing Street Pavement	21 feet wide Asphalt Concrete (AC) pavement with drainage ditches.
Type of the Proposed Streets	Asphalt Concrete (AC) or Portland Cement Concrete (PCC) pavement.
Design Life	25 years (AC and PCC) and 40 years (PCC)
Growth Factor	1.5 %
Total Linear Foot	About 11,500 feet.

If ECS' understanding of the project is not correct, please contact ECS so that we may review these changes and revise our recommendations, as appropriate.

3.0 FIELD EXPLORATION

Our scope of work included drilling a total of 23 soil borings to a depth of 10 feet below the existing grades. These borings were located with a handheld GPS unit and their approximate locations are shown on the Boring Location Diagram in Appendix A.

3.1 SUBSURFACE CHARACTERIZATION

The subsurface conditions encountered were generally consistent with published geological mapping. The following sections provide generalized characterizations of the soil and rock strata. Please refer to the boring logs in Appendix B. Based on a review of available published geological maps, the project area is located within the Ozan formation (Ko). The location of the site on the geologic map are depicted in the attached Regional Geology in Appendix A.

Ozan formation (Ko): The Ozan formation typically consists of relatively uniform, massive, calcareous shale (commonly referred to as marl). Because marl weathers easily, this rock typically cannot be seen in creek beds or outcrops, and soil is found instead. Upper portions of the “limy” shale can weather into softer, clayey shale.

Through chemical and mechanical weathering, this formation produces highly plastic clay soils. Soil above the marl is typically tan and gray, having a blocky structure. Shallower soils typically have a dark brown to black appearance. These clays can be calcareous with silt and sand content increasing incrementally toward the surface. Glauconitic, phosphate pellets, and hematite and pyrite nodules may appear within the soil matrix.

Based on the soil boings, the existing pavements generally consist of 2 to 4 inches of asphalt concrete (AC) underlain by the sand and gravel fill. A summary of the thickness of the existing pavement section with gravel and sand fill encountered in the borings is shown in the following table.

Table 3.1.1 Existing Pavement Section at Boring locations

Boring Location	Asphalt Concrete (in.)	Sand and Gravel Fill (in.)
B-01	3	7
B-02	3	5
B-03	3	5
B-04	2	6
B-05	3	6
B-06	2	5
B-07	3	7
B-08	2	5
B-09	4	5
B-10	3	6
B-11	4	4
B-12	3	7
B-13	3	8
B-14	4	6

B-15	3	8
B-16	4	8
B-17	4	7
B-18	4	6
B-19	4	4
B-20	2	10
B-21	2	8
B-22	3	4
B-23	3	3

A summary of subsurface stratigraphy encountered in the borings is shown in Table 3.1.2 below.

Table 3.1.2 Subsurface Stratigraphy

Approximate Depth to Bottom of Strata (feet)	Elevation of Bottom of Strata ¹ (ft)	Stratum No.	Material Description	Consistency
2 to 8	464 to 510	I	FILL, LEAN and FAT CLAYS, brown, light brown, dark brown	Firm to Hard
6 to 10 ²	456 to 509	II	FAT CLAY (CH), dark brown, brown, light brown	Stiff to Hard
10 ²	476 to 496	III	LEAN CLAY (CL), light brown, brown, light brownish yellow, brownish yellow	Very Stiff to Hard

Note:

¹Please note that the ground surface elevations were not surveyed by a licensed surveyor; these elevations are approximate based on dfwmaps.com. Elevation ranges are approximate +/- several feet.

²Boring termination depths

Please refer to the attached boring logs and laboratory data summary for a more detailed description of the subsurface conditions encountered as the stratification descriptions above are generalized for presentation purposes. A graphical presentation of the subsurface conditions is shown on the Generalized Subsurface Soil Profile included in Appendix A.

3.3 GROUNDWATER OBSERVATIONS

Groundwater level observations were made in the borings during drilling operations. In auger drilling operations, water is not introduced into the borehole and the groundwater level can often be determined by observing water flowing into the excavation. Furthermore, visual observation of soil samples retrieved can often be used in evaluating the groundwater conditions.

Groundwater seepage was not observed in borings during drilling and at the completion of drilling operations.

The highest groundwater observations are normally encountered in the late winter and early spring. Fluctuation in the location of the long-term water table may occur as a result of changes in precipitation, evaporation, surface water runoff and other factors not immediately apparent at the

time of this investigation. The groundwater conditions at this site are expected to be significantly influenced by surface water runoff and rainfall.

3.4 LABORATORY TESTING

The laboratory testing consisted of selected tests performed on samples obtained during our field exploration operations. Classification and index property tests were performed on representative soil samples. The soil samples were tested for moisture content, Atterberg limits, soluble sulfate, lime/pH series, and percent passing No. 200 sieve.

Each sample was visually classified on the basis of texture and plasticity in accordance with ASTM D2488 Standard Practice for Description and Identification of Soils (Visual-Manual Procedures) and including USCS classification symbols. After classification, the samples were grouped in the major zones noted on the boring logs in Appendix B. The group symbols for each soil type are indicated in parentheses along with the soil descriptions. The stratification lines between strata on the logs are approximate; in situ, the transitions may be gradual.

The soil samples will be retained in our laboratory for a period of 60 days, after which, they will be discarded unless other instructions are received as to their disposition.

4.0 DESIGN RECOMMENDATIONS

The following recommendations have been developed on the basis of the previously described project characteristics and subsurface conditions. If there are any changes to the project characteristics or if different subsurface conditions are encountered during construction, ECS should be consulted so that the recommendations of this report can be reviewed.

4.1 POTENTIAL VERTICAL MOVEMENTS

The soils encountered at this site are moderate to highly expansive. These soils are susceptible to shrink swell tendencies, occurring seasonally, throughout the life of the pavement with the changes in moisture content. Based on test method TEX-124-E in the Texas Department of Transportation (TxDOT) Manual of Testing Procedures, and our experience with similar soils, we estimate potential vertical soil movements (PVM) under a dry soil moisture condition will be about 3 to 5 inches. The actual movements could be greater if poor drainage, ponded water, and/or other unusual sources of moisture are allowed to saturate the soils beneath the pavement after construction.

In order to minimize the impact of moisture changes within the subgrade soils and reduce potential for movements, the exposed subgrade during construction should be kept moist by adding moisture and covering the subgrade. Positive drainage should be conducted during all phases of construction. Regular pavement maintenance should be performed by routinely sealing all cracks and joints in the pavement. Subgrade treatment should be considered to reduce future movement potential. In addition, root barriers to about 5 feet below the existing grade along the edge of the pavement may be considered to reduce root penetration below the pavement that may affect long term pavement performance.

4.2 SOLUBLE SULFATE

Soluble sulfate tests were performed on selected samples to evaluate the potential for sulfate induced heave. The laboratory test results indicated that soluble sulfate concentrations were generally less than 3,000 ppm in the subgrade soils except for one sample with 3,066 ppm from Boring B-23. This sulfate level is considered to have a moderate to high risk for sulfate induced heave upon lime stabilization.

In general, soil with soluble sulfate concentrations of 3,000 ppm or less, are not considered to require special treatment considerations when lime stabilized in accordance with TxDOT "Guidelines for Modification and Stabilization of Soils and Base for Use in Pavement Structures" (2005). We recommend that sulfate contents be confirmed by additional laboratory tests during the construction phase after final grading.

Double lime stabilization should be used on the subgrade with high sulfate contents (3,000 to 8,000 ppm). As an alternative, flexible base material may be used in lieu of lime stabilized subgrade.

4.3 PAVEMENT SECTION

The proposed street section is classified as a local residential street and will be upgraded to future roadway as a Secondary Thoroughfare with 4-lane divided concrete with 100-foot right-of-way, according to the Thoroughfare Plan by the City of Wylie, dated December 2018.

A Preliminary Engineering Report, prepared by Brinkley & Barfield Consulting Engineer for Collin County, "E. Stone Road Improvements Study" – From W.A. Allen Boulevard to Bennett Road, dated November 2021, was provided by the City of Wylie for the use of this geotechnical study. The proposed road will have a long-term growth factor of 1.5 percent. Traffic volumes were observed at four locations for 48 hours along the corridor on August 24 to 26, 2021. Combined two-way traffic on the east-west segment between WA Allen Boulevard and Beaver Creek Road, average daily traffic ranged from 2,127 to 5,167 vpd. Combined two-way traffic on the north-south segment between Bennet Road and Shore Drive, average daily traffic ranged from 2,172 to 2,791 vpd. The highest average daily traffic (ADT) of 5,167 vpd was used in the traffic study.

Based on the information obtain from the preliminary engineering report for the Stone Road Improvements provided by the City of Wylie and our past experience, we use the design parameters summarized on the following Table 4.3.1 for the pavement design analysis with 25-year design life (AC/PCC pavements) and 40-year design life (PCC pavement).

Table 4.3.1: Design Parameters for Stone Road Improvements

Design Parameters	Design Values	
	Flexible (AC)	Rigid (PCC)
Pavement Type		
Average Daily Traffic (ADT)	5,167	
Growth Factor (%)	1.5	
Percent Heavy Trucks (%) (assumed)	5.0	
ESAL Truck Factor (assumed)	1.7	
Total ESALs (25-Year Design Life) - AC/PCC	2,411,300	
Total ESALs (40-Year Design Life) - PCC	4,352,720	
Subgrade Soil Type	Clay Soils	
Unified Soil Classification System (USCS)	CH or CL	
Reliability (percentage)	90	
Overall Standard Deviation	0.45	0.39
Initial Pavement Serviceability	4.2	4.5
Terminal Pavement Serviceability	2.5	
Concrete Modulus of Rupture (psi) -28 Days	620	
Concrete Modulus of Elasticity (psi) -28 days	4,000,000	
Drainage Coefficient	1.0	
Load Transfer Coefficient – Rigid	3.0	
Layer Coefficient of Asphalt Surface Course	0.44	
Layer Coefficient of Asphalt Base Course	0.41	

Layer Coefficient (Asphalt Pavement)	0.12 (Lime Stabilized Subgrade) 0.14 (Flexible Base with Geogrid) 0.15 (Cement Treated RAP)
Modulus of Subgrade Reaction (psi/in) – k (PCC Pavement)	200 (Lime Stabilized Subgrade) 240 (Flexible Base with Geogrid) 240 (Cement Treated Base/RAP)

Pavement sections provided in this report were designed in general accordance with the AASHTO Guide for Design of Pavement Structures (1993). Based on our analysis and the calculations with the design parameters on the Table 4.3.2, the pavement reconstruction may be designed as asphalt concrete pavement section supported on either lime stabilized subgrade, flexible base with geogrid (Tensar BX1100 or similar), or cement treated Reclaimed Asphalt Pavement (RAP) subgrade. The proposed asphalt concrete pavement sections are summarized in the following table.

Table 4.3.2: Asphalt Concrete (AC) Pavement Section

Design Life (year)	Asphalt Surface Course (inches)	Asphalt Base Course (inches)	Cement Treated RAP (inches)	Flexible Base with Geogrid (inches)	Lime Stabilized Subgrade (inches)
25	2	7	N/A	N/A	8
25	2	7	N/A	8	N/A
25	2	7	8	N/A	N/A

Table 4.3.3: Portland Cement Concrete (PCC) Pavement Section

Design Life (year)	Concrete Pavement Thickness (inches)	Cement Treated RAP (inches)	Flexible Base with Geogrid (inches)	Lime Stabilized Subgrade (inches)
25	8	N/A	N/A	8
25	8	N/A	8	N/A
25	8	8	N/A	N/A
40	9	N/A	N/A	8
40	9	N/A	8	N/A
40	9	8	N/A	N/A

We recommend the existing HMAC and fill material (consisted of sand and gravel) be removed from below the footprint of the proposed new pavement area before using lime to stabilize the clay fill and native soil if lime stabilized subgrade will be used for the project.

For the design and construction of pavement, the subgrade should be prepared in accordance with the recommendations in the “Earthwork Operations” section of this report. An important consideration with the design and construction of pavements is surface and subsurface drainage. Where standing water develops, either on the pavement surface or within the base course layer, softening of the subgrade and other problems related to the deterioration of the pavement can be expected. Furthermore, good drainage should reduce the possibility of the subgrade materials becoming saturated during the normal service period of the pavement.

Please note, the recommended pavement sections provided above are considered the minimum necessary to provide satisfactory performance based on the provided traffic loading. In some cases, jurisdictional minimum standards for pavement section construction may exceed those provided above.

4.3.1 Pavement Materials

We recommend that pavement be specified, constructed and tested to meet the following requirements:

1. Hot Mix Asphaltic Concrete: Item 340 of the TxDOT Standard Specifications, Type B Base Course (binder), Type D Surface Course.
2. Portland Cement Concrete: A minimum compressive strength of 4,000 psi at 28 days.
3. Reinforcing Steel: #4 bars at 18” centers both ways.
4. Concrete Pavement Joints:
 - a. Transverse Joints shall be sawed on 15’ centers. Use 18” #8 or #10 dowels (smooth bars) at 12” spacing per TxDOT concrete Pavement Details Contraction Design (CPCD-14)
 - b. Longitudinal Joints shall be sawed based on the following:
25’ Width Saw Joint 3” from the center; 27’ & 31’ Width Saw Joint along the center
 - c. Expansion Joints to be constructed a maximum of 500’ to 700’ apart on straight paving, and on all radii, PC, PT and CR or otherwise specified. Use at least 18” (#10) dowels for paving 8” thick or greater.
5. Lime Stabilized Subgrade: 8% Lime by dry weight of soil (about 48 lbs/sy for 8 inches)
6. Flexible Base Subgrade (TxDOT Item 247)
7. Cement Treated Subgrade (Public Works Construction Standards, NCTCOG, 4th Edition, Item 301.1 and 301.3) or TxDOT Item 275 (Cement Treatment – Road Mixed)

4.3.2 Pavement Maintenance

Routine maintenance, such as sealing and repair of cracks, is necessary to achieve the long-term life of a pavement system. We recommend a preventive maintenance program be developed and followed for all pavement systems so the design life can be realized. Choosing to defer maintenance usually results in accelerated deterioration leading to higher future maintenance costs, and/or repair.

The life and serviceability of the pavement system is dependent upon a well-planned pavement maintenance program. Pavement maintenance guidelines are provided in the following tables. We also recommend a Pavement Information Management System to be instituted and a strict maintenance schedule to be implemented.

Table 4.3.2.1: General Rigid (PCC) Pavement Maintenance Program

Year	Program
7	Joint Seal and Crack Seal
14	Joint Seal and Crack Seal Patch and Slab Replacement
20	Diamond Grind ½ inch and Reseal Joints or Cracks
27	Joint Seal and Crack Seal
35	Joint Seal and Crack Seal Patch and Slab Replacement
40	Overlay with 3-inch AC Pavement Maintenance to Follow AC Pavement Recommendations in Table 4.3.2.2

Table 4.3.2.2: Flexible (AC) Pavement Maintenance Program

Year	Program
7	Crack Seal and 2-inch Stone Matrix Asphalt (SMA) Overlay
10	Crack Seal
15	2 inches Mill and 2-inch SMA Inlay
18	Crack Seal
22	Crack Seal and 2-inch SMA Inlay
25	Crack Seal or Reconstruct the Asphalt section Layer

5.0 SITE CONSTRUCTION RECOMMENDATIONS

5.1 SUBGRADE PREPARATION

In a dry and undisturbed state, the upper 1-foot of the majority of the soil at the site will provide good subgrade support for fill placement and construction operations. However, these soils contain fines which are considered moderately erodible and are moisture and disturbance sensitive. Therefore, good site drainage should be maintained during earthwork operations, which would help maintain the integrity of the soil.

We recommend that an attempt be made to enhance the natural drainage without interrupting its pattern. All erosion and sedimentation should be controlled in accordance with sound engineering practice and current jurisdictional requirements.

The site should be stripped. After stripping, cutting to the proposed grade, and prior to the placement of any structural fill, the exposed subgrade should be examined by the Geotechnical Engineer or authorized representative. The exposed subgrade should be thoroughly proofrolled with previously approved construction equipment having a minimum axle load of 20 tons (e.g. fully loaded tandem-axle dump truck). The areas subject to proofrolling should be traversed by the equipment in two perpendicular (orthogonal) directions with overlapping passes of the vehicle under the observation of the Geotechnical Engineer or authorized representative. This procedure is intended to assist in identifying any localized yielding materials.

In the event that unstable or “pumping” subgrade is identified by the proofrolling, those areas should be marked for repair prior to the placement of any subsequent structural fill or other construction materials. Methods of repair of unstable subgrade, such as undercutting or moisture conditioning or chemical stabilization, should be discussed with the Geotechnical Engineer to determine the appropriate procedure with regard to the existing conditions causing the instability.

5.1.1 Proofrolling

Prior to fill placement or other construction on subgrades, the subgrades should be evaluated by an ECS field technician. The exposed subgrade outside moisture conditioned soil zone should be thoroughly proofrolled with construction equipment having a minimum axle load of 10 tons [e.g. fully loaded tandem-axle dump truck]. Proofrolling should be traversed in two perpendicular directions with overlapping passes of the vehicle under the observation of an ECS technician. This procedure is intended to assist in identifying any localized yielding materials.

Where proofrolling identifies areas that are unstable or “pumping” subgrade those areas should be repaired prior to the placement of any subsequent Structural Fill or other construction materials. Methods of stabilization include undercutting, moisture conditioning, or chemical stabilization. The situation should be discussed with ECS to determine the appropriate procedure. Test pits may be excavated to explore the shallow subsurface materials to help in determining the cause of the observed unstable materials, and to assist in the evaluation of appropriate remedial actions to stabilize the subgrade.

5.2 EARTHWORK OPERATIONS

Prior to placement of any new fill, all subgrades should be scarified to a minimum depth of 6 inches, compacted to at least 95% of Maximum Dry Density as obtained by the Standard Proctor Method (ASTM D-698) and moisture conditioned at +3% or above the optimum value. All fills should be benched into the existing soils.

Soil moisture levels should be preserved (by various methods that can include covering with plastic, watering, etc.) until new fill, or pavements are placed. All fill soils should be placed in 8 inch loose lifts for mass grading operations and 4 inches for trench type excavations where walk behind or “jumping jack” compaction equipment is used.

Upon completion of the filling operations, care should be taken to maintain the soil moisture content prior to construction of floor slabs and pavements. Soil moisture levels can be preserved by various methods that can include covering with plastic, watering, etc. If the soil becomes desiccated, the affected material should be removed and replaced, or these materials should be scarified, moisture conditioned and recompacted.

Utility cuts should not be left open for extended periods of time and should be properly backfilled. Backfilling should be accomplished with properly compacted on-site soils, rather than granular materials. A utility trench cut-off is recommended to help prevent water from migrating through the utility trench backfill to beneath the proposed structure.

Field density and moisture tests should be performed on each lift as necessary to verify that adequate compaction is achieved. As a guide, one test per 2,500 square feet per lift is recommended in the paving areas (two tests minimum per lift). Utility trench backfill should be tested at a rate of one test per lift per each 150 linear feet of trench (two tests minimum per lift). Certain jurisdictional requirements may require testing in addition to that noted previously. Therefore, these specifications should be reviewed and the more stringent specifications should be followed.

5.3 MATERIAL SPECIFICATIONS

This section is intended to outline the material requirements of those recommendations.

Lime stabilized subgrade: Lime stabilized on site clay should be used below the pavement. Lime application rate of 8% hydrated lime (about 48 lbs/sy for 8 inches) by dry weight of clay (TxDOT Item 260) can be used for budgeting purposes. The actual amount of lime required should be confirmed by additional laboratory tests (lime series) during the construction phase.

The lime stabilized clay should be thoroughly mixed and appropriately mellowed for at least 48 hours (TxDOT Item 260) and tested for gradation and lime solubility (pH) prior to final placement and compaction. Once appropriately mixed and mellowed, this material may then be placed and compacted at workable moisture contents within of at least +3 percent of optimum moisture content and compacted to at least 95% of the Maximum Dry Density as obtain using the Standard Proctor Method (ASTM D-698).

Please refer to the “General Recommendations for Quality Assurance (QA) Testing” table provided in the Appendix A of this report for specific requirements.

Flexible base material: The material may be used beneath pavements. Flexible base should meet the requirements of TxDOT Item 247, Type D, Grade 1-2, or NCTCOG Item 301.5. Recycled concrete meeting the gradation requirements of flexible base is also acceptable for use. The flexible base and recycled concrete should be compacted to at least 95% of maximum dry density at or above the optimum moisture content as obtained using the Standard Proctor Method (ASTM D-698).

Please refer to the “General Recommendations for Quality Assurance (QA) Testing” table provided in the Appendix A of this report for specific requirements.

Cement Treated Reclaimed Asphalt Pavement (RAP): The existing asphalt pavement sections may be considered for the project. The existing pavement sections should be milled/crushed down or pulverized to fragments by using a pulverizing/mixing rototiller or similar equipment. Asphalt concrete, gravelly fill materials, and subgrade soils should be mixed together. The particle size distribution of the pulverized material should be such that 100 percent passing the 1-3/4-in. sieve, 85 percent passing the 3/4-in. sieve, and at least 60 percent passing the No. 4 sieve.

The resulting mix should be cement stabilized (TxDOT Item 275) to the minimum depth of 8 inches and compacted to at least 95 percent of its maximum standard Proctor dry density (ASTM D 698) at a moisture content above the optimum moisture. We recommend 3 to 5 percent cement (TxDOT Item 275), by dry weight, for the treatment. The cement should be thoroughly mixed and blended with the pulverized mixture. The resulting mix should have a minimum unconfined compressive strength of 240 psi, as determined by TxDOT method Tex-120-E.

6.0 CLOSING

ECS has prepared this report to guide the geotechnical-related design and construction aspects of the project. We performed these services in accordance with the standard of care expected of professionals in the industry performing similar services on projects of like size and complexity at this time in the region. No other representation, expressed or implied, and no warranty or guarantee is included or intended in this report.

The description of the proposed project is based on information provided to ECS by Client. If any of this information is inaccurate or changes, either because of our interpretation of the documents provided or site or design changes that may occur later, ECS should be contacted so we can review our recommendations and provide additional or alternate recommendations that reflect the proposed construction.

All construction activities should be conducted in accordance with the most recent City's Design Standards, as well as the latest edition of North Central Texas Council of Governments (NCTCOG) Standard Specifications for Public Works Construction and TxDOT specifications.

We recommend that ECS review the project plans and specifications so we can confirm that those plans/specifications are in accordance with the recommendations of this geotechnical report.

Field observations, and quality assurance testing during earthwork and foundation installation are an extension of, and integral to, the geotechnical design. We recommend that ECS be retained to apply our expertise throughout the geotechnical phases of construction, and to provide consultation and recommendation should issues arise.

ECS is not responsible for the conclusions, opinions, or recommendations of others based on the data in this report.

APPENDIX A – Figures


Site Location Diagram

Boring Location Diagram

Generalized Subsurface Soil Profile (From West to East)

Regional Geology

General Recommendations for Quality Assurance (QA) Testing




SITE LOCATION DIAGRAM STONE ROAD IMPROVEMENTS


FROM WA ALLEN BOULEVARD TO BENNETT ROAD, WYLIE, TEXAS
CITY OF WYLIE, TX



ENGINEER MPB1
SCALE AS NOTED
PROJECT NO. 19:8613
SHEET 1 OF 1
DATE 2/22/2022



Legend Key



Notes:

- 1- EOB: END OF BORING AR: AUGER REFUSAL SR: SAMPLER REFUSAL.
- 2- THE NUMBER BELOW THE STRIPS IS THE DISTANCE ALONG THE BASELINE.
- 3- SEE INDIVIDUAL BORING LOG AND GEOTECHNICAL INFORMATION.
- 4- STANDARD PENETRATION TEST RESISTANCE (LEFT OF BORING) IN BLOWS PER FOOT (ASTM D1586).

Plastic Limit	Water Content	Liquid Limit
X	●	△
[FINES CONTENT %]		
BOTTOM OF CASING		
LOSS OF CIRCULATION		

WL (First Encountered)
WL (Completion)
WL (Seasonal High Water)
WL (Stabilized)

Fill
Possible Fill
Probable Fill
Rock




GENERALIZED SUBSURFACE SOIL PROFILE Section line A-A'

Stone Road Improvements

City of Wylie, TX

WA Allen Boulevard to Bennett Road, Wylie, Texas 75098

Project No: 19-8513 Date: 03/10/2022



Notes:

1- EOB: END OF BORING AR: AUGER REFUSAL SR: SAMPLER REFUSAL.
 2- THE NUMBER BELOW THE STRIPS IS THE DISTANCE ALONG THE BASELINE.
 3- SEE INDIVIDUAL BORING LOG AND GEOTECHNICAL INFORMATION.
 4- STANDARD PENETRATION TEST RESISTANCE (LEFT OF BORING) IN BLOWS PER FOOT (ASTM D1586).

Plastic Limit Water Content Liquid Limit

X ———●—————△

[FINES CONTENT %]

■ BOTTOM OF CASING

⏏ LOSS OF CIRCULATION

▽ WL (First Encountered)

▽ WL (Completion)

▽ WL (Seasonal High Water)

▽ WL (Stabilized)

■ Fill

■ Possible Fill

■ Probable Fill

■ Rock



GENERALIZED SUBSURFACE SOIL PROFILE Section line B-B'

Stone Road Improvements

City of Wylie, TX


WA Allen Boulevard to Bennett Road, Wylie, Texas 75098

Project No:

19-8513

Date:

03/10/2022



Notes:

1- EOB: END OF BORING AR: AUGER REFUSAL SR: SAMPLER REFUSAL.
 2- THE NUMBER BELOW THE STRIPS IS THE DISTANCE ALONG THE BASELINE.
 3- SEE INDIVIDUAL BORING LOG AND GEOTECHNICAL INFORMATION.
 4- STANDARD PENETRATION TEST RESISTANCE (LEFT OF BORING) IN BLOWS PER FOOT (ASTM D1586).

Plastic Limit	Water Content	Liquid Limit
X	●	△
[FINES CONTENT %]		
BOTTOM OF CASING		
LOSS OF CIRCULATION		

▽	WL (First Encountered)
▼	WL (Completion)
▽	WL (Seasonal High Water)
▽	WL (Stabilized)

Fill
Possible Fill
Probable Fill
Rock



GENERALIZED SUBSURFACE SOIL PROFILE Section line C-C'

Stone Road Improvements

City of Wylie, TX

WA Allen Boulevard to Bennett Road, Wylie, Texas 75098

Project No: 19-8513 Date: 03/10/2022



REGIONAL GEOLOGY STONE ROAD IMPROVEMENTS

FROM WA ALLEN BOULEVARD TO BENNETT ROAD, WYLIE, TEXAS
CITY OF WYLIE, TX



ENGINEER MPB1
SCALE AS NOTED
PROJECT NO. 19:8613
SHEET 1 OF 1
DATE 2/22/2022

General Recommendations for Quality Assurance (QA) Testing*

Item	Parameter	Test Method ASTM unless noted otherwise	Test Frequency or Observations	Requirements
General Earth Fill Below Paving & Structures	Standard Proctor Curve	D698	1 per soil type	--
	Atterberg Limits	D4318	1 per soil type	--
	-200 Mesh Sieve	D1140	1 per soil type	--
	In Situ Density/Moisture Nuclear Gauge	D2922 D3017	1 per each 200 ft. of lane direction per 6 inch lift (2 tests minimum per lift per section)	Density \geq 95% Moisture: PI < 20 (-2 to +5) PI > 20 (0 to +5)
Select Fill	Standard Proctor Curve	D698	1 per soil type	Lean Sandy Clay (CL) or Clayey Sand (SC)
	Atterberg Limits	D4318	1 per soil type	LL \leq 35 6 \leq PI \leq 15
	-200 Mesh Sieve (P 200)	D1140	1 per soil type	P200 \leq 50
	In Situ Density/Moisture Nuclear Gauge	D2922 D3017	1 per each 200 ft. of lane direction per 6 inch lift (2 tests minimum per lift per section)	Density \geq 95% Moisture: (-2 to +5)
Stabilized Subgrade	Standard Proctor Curve	D698	1 per soil type	--
	Atterberg Limits	D4318	1 per soil type	PI \leq 15
	In Situ Density/Moisture Nuclear Gauge	D2922 D3017	1 per each 200 ft. of lane direction (2 tests minimum)	Density \geq 95% Moisture: +3%
	Gradation	D422	1 per 2 Density/Moisture tests	100% Passing 1-3/4" Sieve 60 % passing #4 Sieve
	Depth Check	Survey, drive probe or hand auger	1 per 2 Density/Moisture tests	Min. Specified

*Performed by the Construction Materials Engineering and Testing Company hired by owner.

Item	Parameter	Test Method ASTM unless noted otherwise	Test Frequency or Observations	Requirements
Trench Backfill Below Streets & Structures	Standard Proctor Curve	D698	1 per soil type	--
	Atterberg Limits	D4318	1 per soil type	--
	-200 Mesh Sieve	D1140	1 per soil type	--
	In Situ Density/Moisture Nuclear Gauge	D2922 D3017	1 per each 250 ft. of lane direction per 12 inch lift (2 tests minimum per lift per section)	Density \geq 95% Moisture: -1 to +4
Wall Backfill	Standard Proctor Curve	D698	1 per soil type	--
	Atterberg Limits	D4318	1 per soil type	LL \leq 35 6 \leq PI \leq 15
	-200 Mesh Sieve (P 200)	D1140	1 per soil type	P200 \leq 50
	In Situ Density/Moisture Nuclear Gauge	D2922 D3017	1 per each 200 ft. of lane direction per 8 inch lift 6 inch lifts if hand-operated tampers are used (2 tests minimum per lift per section)	Density \geq 95% Moisture: (-1 to +4)
Crushed Limestone Flexible Base (TxDOT Item 247)	Modified Proctor Curve	D1557	1 per material type	Type A, Grade 1 or better
	Atterberg Limits	D4318	1 per material type	LL \leq 40 PI \leq 12
	Sieve Analysis	D422	1 per material type	0-10 % Passing 1-3/4 inch 45-75 % Passing No. 4 60-85 % Passing No. 40
	Wet Ball Mill	TxDOT	1 per material type	Max. 45
	In Situ Density/Moisture Nuclear Gauge	D2922 D3017	1 per each 200 ft. of lane direction (Streets/Roads)	Density \geq 95% (Modified) Moisture: -2 to +4%

Notes: 1. Table 1 is a guide for sampling and testing. Each of these items may not apply to the specified project.

2. Material changes, suspect areas, or other field conditions may require the engineer to increase testing and sampling frequencies.

3. Minimum of two tests per lift.

4. The moisture content ranges specified are to be considered as maximum allowable ranges. The contractor may have to maintain a more narrow range (within the maximum allowable) in order to consistently achieve the specified density for some soils or under some conditions.

APPENDIX B – Field Operations

Reference Notes for Boring Logs
Subsurface Exploration Procedure
Boring Logs



REFERENCE NOTES FOR BORING LOGS

MATERIAL^{1,2}

	ASPHALT
	CONCRETE
	GRAVEL
	TOPSOIL
	VOID
	BRICK
	AGGREGATE BASE COURSE
	GW WELL-GRADED GRAVEL gravel-sand mixtures, little or no fines
	GP POORLY-GRADED GRAVEL gravel-sand mixtures, little or no fines
	GM SILTY GRAVEL gravel-sand-silt mixtures
	GC CLAYEY GRAVEL gravel-sand-clay mixtures
	SW WELL-GRADED SAND gravelly sand, little or no fines
	SP POORLY-GRADED SAND gravelly sand, little or no fines
	SM SILTY SAND sand-silt mixtures
	SC CLAYEY SAND sand-clay mixtures
	ML SILT non-plastic to medium plasticity
	MH ELASTIC SILT high plasticity
	CL LEAN CLAY low to medium plasticity
	CH FAT CLAY high plasticity
	OL ORGANIC SILT or CLAY non-plastic to low plasticity
	OH ORGANIC SILT or CLAY high plasticity
	PT PEAT highly organic soils

DRILLING SAMPLING SYMBOLS & ABBREVIATIONS

SS	Split Spoon Sampler	PM	Pressuremeter Test
ST	Shelby Tube Sampler	RD	Rock Bit Drilling
WS	Wash Sample	RC	Rock Core, NX, BX, AX
BS	Bulk Sample of Cuttings	REC	Rock Sample Recovery %
PA	Power Auger (no sample)	RQD	Rock Quality Designation %
HSA	Hollow Stem Auger		

PARTICLE SIZE IDENTIFICATION

DESIGNATION	PARTICLE SIZES
Boulders	12 inches (300 mm) or larger
Cobbles	3 inches to 12 inches (75 mm to 300 mm)
Gravel: Coarse	¾ inch to 3 inches (19 mm to 75 mm)
Fine	4.75 mm to 19 mm (No. 4 sieve to ¾ inch)
Sand: Coarse	2.00 mm to 4.75 mm (No. 10 to No. 4 sieve)
Medium	0.425 mm to 2.00 mm (No. 40 to No. 10 sieve)
Fine	0.074 mm to 0.425 mm (No. 200 to No. 40 sieve)
Silt & Clay ("Fines")	<0.074 mm (smaller than a No. 200 sieve)

COHESIVE SILTS & CLAYS

UNCONFINED COMPRESSIVE STRENGTH, QP ⁴	SPT ⁵ (BPF)	CONSISTENCY ⁷ (COHESIVE)
<0.25	<2	Very Soft
0.25 - <0.50	2 - 4	Soft
0.50 - <1.00	5 - 8	Firm
1.00 - <2.00	9 - 15	Stiff
2.00 - <4.00	16 - 30	Very Stiff
4.00 - 8.00	31 - 50	Hard
>8.00	>50	Very Hard

RELATIVE AMOUNT ⁷	COARSE GRAINED (%) ⁸	FINE GRAINED (%) ⁸
Trace	≤5	≤5
With	10 - 20	10 - 25
Adjective (ex: "Silty")	25 - 45	30 - 45

GRAVELS, SANDS & NON-COHESIVE SILTS

SPT ⁵	DENSITY
<5	Very Loose
5 - 10	Loose
11 - 30	Medium Dense
31 - 50	Dense
>50	Very Dense

WATER LEVELS⁶

	WL (First Encountered)
	WL (Completion)
	WL (Seasonal High Water)
	WL (Stabilized)

FILL AND ROCK

FILL	POSSIBLE FILL	PROBABLE FILL	ROCK

¹Classifications and symbols per ASTM D 2488-17 (Visual-Manual Procedure) unless noted otherwise.

²To be consistent with general practice, "POORLY GRADED" has been removed from GP, GP-GM, GP-GC, SP, SP-SM, SP-SC soil types on the boring logs.

³Non-ASTM designations are included in soil descriptions and symbols along with ASTM symbol [Ex: (SM-FILL)].

⁴Typically estimated via pocket penetrometer or Torvane shear test and expressed in tons per square foot (tsf).

⁵Standard Penetration Test (SPT) refers to the number of hammer blows (blow count) of a 140 lb. hammer falling 30 inches on a 2 inch OD split spoon sampler required to drive the sampler 12 inches (ASTM D 1586). "N-value" is another term for "blow count" and is expressed in blows per foot (bpf). SPT correlations per 7.4.2 Method B and need to be corrected if using an auto hammer.

⁶The water levels are those levels actually measured in the borehole at the times indicated by the symbol. The measurements are relatively reliable when augering, without adding fluids, in granular soils. In clay and cohesive silts, the determination of water levels may require several days for the water level to stabilize. In such cases, additional methods of measurement are generally employed.

⁷Minor deviation from ASTM D 2488-17 Note 14.

⁸Percentages are estimated to the nearest 5% per ASTM D 2488-17.






SUBSURFACE EXPLORATION PROCEDURES





The field exploration was planned with the objective of characterizing the project site in general geotechnical and geological terms and to evaluate subsequent field and laboratory data to assist in the determination of geotechnical recommendations.






The subsurface conditions were explored by drilling and sampling 23 borings to a depth of approximately 10 feet below the existing site grades. A truck-mounted drill rig with continuous flight augers was utilized to drill the borings. The boring locations were determined by and identified in the field by ECS personnel using the supplied diagram. The approximate as-drilled boring locations are shown on the Boring Location Diagram in Appendix A. The ground surface elevations noted on the boring logs were obtained from NCTCOG (www.dfwmaps.com), which provided elevation contours in 2-foot intervals.





Representative soil samples were obtained by means of Shelby tube sampling procedures in accordance with ASTM Specification D-1587. In the Shelby tube sampling procedure, a thin walled, steel, seamless tube with sharp cutting edges is pushed hydraulically into the soil, and a relatively undisturbed sample is obtained.







Field logs of the soils encountered in the borings were maintained by the drilling crew. After recovery, each sample was removed from the sampler and visually classified. Representative portions of each soil sample were then wrapped in plastic and transported to our laboratory for further visual examination and laboratory testing. After completion of the drilling operations, the boreholes were backfilled with auger cuttings and patched on the surface.




CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-01		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7058095.9			EASTING: 2582679.1			STATION:		SURFACE ELEVATION: 519.00		BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— △		
									⊗ STANDARD PENETRATION BLOWS/FT		
									ROCK QUALITY DESIGNATION & RECOVERY		
									— RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	14	14	Asphalt [3"]		514		○ 2.25		
	S-2	ST	24	24	FILL, sand and gravel, brown [7"]				○ 2.75		
	S-3	ST	24	24	(CH) FAT CLAY, brown and dark brown, moist, very stiff to hard				○ 3.50		
	S-4	ST	24	24					○ 3.50		
	S-5	ST	24	24					○ 4.25		
	END OF BORING AT 10.0 FT									509	
10											
15											
20											
25											
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)				Dry		BORING STARTED: Feb 10 2022			CAVE IN DEPTH:		
▼ WL (Completion)				Dry		BORING COMPLETED: Feb 10 2022			HAMMER TYPE: Auto		
☒ WL (Seasonal High Water)				N/A		EQUIPMENT: Truck			LOGGED BY: StrataBore		
☒ WL (Stabilized)				N/A					DRILLING METHOD: CFA		
GEOTECHNICAL BOREHOLE LOG											














CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-02		SHEET: 1 of 1						
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC										
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 				
NORTHING: 7057605.1			EASTING: 2582663.0		STATION:		SURFACE ELEVATION: 518.00			BOTTOM OF CASING 				
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— △					
									⊗ STANDARD PENETRATION BLOWS/FT					
									ROCK QUALITY DESIGNATION & RECOVERY					
									— RQD — REC					
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %					
5	S-1	ST	16	16	Asphalt [3"]		513			○ 3.50				
	S-2	ST	24	24	FILL, sand and gravel, brown [5"]						(CH) FAT CLAY, brown and dark brown, moist, very stiff to hard			○ 3.50
	S-3	ST	24	24										
	S-4	ST	24	24										
	S-5	ST	24	24										
	10	END OF BORING AT 10.0 FT												
15						503			○ 4.00					
						498			○ 4.25					
25						493								
30						488								
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL														
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022				CAVE IN DEPTH:						
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022				HAMMER TYPE: Auto						
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA						
☒ WL (Stabilized)		N/A												
GEOTECHNICAL BOREHOLE LOG														





CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-03		SHEET: 1 of 1						
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC										
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 				
NORTHING: 7057123.5			EASTING: 2582653.8		STATION:		SURFACE ELEVATION: 516.00			BOTTOM OF CASING 				
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● Δ					
									⊗ STANDARD PENETRATION BLOWS/FT					
									ROCK QUALITY DESIGNATION & RECOVERY					
									— RQD — REC					
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %					
5	S-1	ST	16	16	Asphalt [3"]		511			○ 2.75				
	S-2	ST	24	24	FILL, sand and gravel, brown [5"]									○ 2.75
	S-3	ST	24	24	FILL, LEAN/FAT CLAYS, brown and light brown, moist, very stiff									
	S-4	ST	24	24	(CH) FAT CLAY, brown and dark brown, moist, very stiff									
	10	S-5	ST	24	24									
END OF BORING AT 10.0 FT														
								○ 3.00						
15							501							
20							496							
25							491							
30							486							
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL														
☒ WL (First Encountered)				Dry	BORING STARTED: Feb 10 2022				CAVE IN DEPTH:					
▼ WL (Completion)				Dry	BORING COMPLETED: Feb 10 2022				HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)				N/A	EQUIPMENT: Truck				LOGGED BY: StrataBore					
☒ WL (Stabilized)				N/A	DRILLING METHOD: CFA									
GEOTECHNICAL BOREHOLE LOG														






CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-04		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7056647.6			EASTING: 2582638.7		STATION:		SURFACE ELEVATION: 507.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● — △		
									⊗ STANDARD PENETRATION BLOWS/FT		
									— RQD		
									○ CALIBRATED PENETROMETER TON/SF		
									[FINES CONTENT] %		
5	S-1	ST	16	16	Asphalt [2"]		502		○ 2.75		
	S-2	ST	24	24	FILL, sand and gravel, brown and yellowish brown [6"]						
	S-3	ST	24	24	FILL, FAT/LEAN CLAYS, brown and light brown, moist, very stiff						
	S-4	ST	24	24	(CH) FAT CLAY, dark brown, moist, hard						
	S-5	ST	24	24	(CH) FAT CLAY, light brown, moist, very stiff						
10	END OF BORING AT 10.0 FT						497		○ 3.25		
15							492		○ 3.25		
20							487		○ 3.25		
25							482		○ 4.25		
30							477		○ 3.75		
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											







CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-05		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7056168.1			EASTING: 2582642.0		STATION:		SURFACE ELEVATION: 510.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● — △		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	15	15	Asphalt [3"]		505				
	S-2	ST	24	24	FILL, sand and gravel, dark brown [6"] (CH) FAT CLAY, dark brown, moist, very stiff						
	S-3	ST	24	24							
	S-4	ST	24	24	(CH) FAT CLAY, brown and light brown, moist, hard						
	S-5	ST	24	24							
10	END OF BORING AT 10.0 FT						500				
15							495				
20							490				
25							485				
30							480				
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)				Dry	BORING STARTED: Feb 10 2022			CAVE IN DEPTH:			
▼ WL (Completion)				Dry	BORING COMPLETED: Feb 10 2022			HAMMER TYPE: Auto			
☒ WL (Seasonal High Water)				N/A	EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA		
☒ WL (Stabilized)				N/A							
GEOTECHNICAL BOREHOLE LOG											






CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-06		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7055673.7			EASTING: 2582631.5		STATION:		SURFACE ELEVATION: 496.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— △		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	17	17	Asphalt [2"]						
	S-2	ST	24	24	FILL, sand and gravel, brown [5"]						
	S-3	ST	24	24	FILL, LEAN/FAT CLAYS, light brown and dark brown, moist, very stiff to hard						
	S-4	ST	24	24							
10	S-5	ST	24	24	(CH) FAT CLAY, light brown and brown, moist, very stiff						
END OF BORING AT 10.0 FT											
15											
20											
25											
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022				CAVE IN DEPTH:			
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022				HAMMER TYPE: Auto			
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											





CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-07		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7055145.4			EASTING: 2582613.0		STATION:		SURFACE ELEVATION: 487.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	14	14	Asphalt [3"]						
					FILL, sand and gravel, brown, brownish yellow [7"]						
	S-2	ST	24	24	(CL) LEAN CLAY, light brownish yellow, moist, very stiff						
	S-3	ST	24	24	(CL) LEAN CLAY, brown and light brown, moist, very stiff to hard		482				3.00
	S-4	ST	24	24							3.00
10	S-5	ST	24	24							3.50
											4.25
											4.50
											
											
					END OF BORING AT 10.0 FT		477				
15											
20											
25											
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022				CAVE IN DEPTH:			
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022				HAMMER TYPE: Auto			
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											






CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-08		SHEET: 1 of 1								
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC												
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 						
NORTHING: 7054643.8			EASTING: 2582601.5		STATION:		SURFACE ELEVATION: 471.00			BOTTOM OF CASING 						
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● Δ							
									⊗ STANDARD PENETRATION BLOWS/FT							
									ROCK QUALITY DESIGNATION & RECOVERY							
									— RQD — REC							
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %							
5	S-1	ST	17	17	Asphalt [2"]		466		○ 2.25	○ 3.00	○ 3.00					
	S-2	ST	24	24	FILL, sand and gravel, brown [5"]							461				
	S-3	ST	24	24	(CH) FAT CLAY, brown and light brown, moist, very stiff											
													S-4	ST	24	24
													S-5	ST	24	24
10	END OF BORING AT 10.0 FT						461									
15							456									
							451									
							446									
20							441									
25																
30																
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL																
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022		CAVE IN DEPTH:										
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022		HAMMER TYPE: Auto										
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA								
☒ WL (Stabilized)		N/A														
GEOTECHNICAL BOREHOLE LOG																









CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-09		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054468.9			EASTING: 2582459.5		STATION:		SURFACE ELEVATION: 469.00		BOTTOM OF CASING 		
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	15	15	Asphalt [4"]		464				
	S-2	ST	24	24	FILL, sand and gravel, brown [5"]						
	S-3	ST	24	24	(CH) FAT CLAY, dark brown and light brown, moist, very stiff						
	S-4	ST	24	24							
	S-5	ST	24	24							
	10	END OF BORING AT 10.0 FT									
15						459					
20						454					
25						449					
30						444					
						439					
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)				Dry	BORING STARTED: Feb 10 2022			CAVE IN DEPTH:			
▼ WL (Completion)				Dry	BORING COMPLETED: Feb 10 2022			HAMMER TYPE: Auto			
☒ WL (Seasonal High Water)				N/A	EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA		
☒ WL (Stabilized)				N/A							
GEOTECHNICAL BOREHOLE LOG											




CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-10		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054496.5			EASTING: 2581997.8		STATION:		SURFACE ELEVATION: 490.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— △		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	15	15	Asphalt [3"]						○ 4.50
					FILL, sand and gravel, brown [6"]						○ 4.50
	S-2	ST	24	24	(CH) FAT CLAY, dark brown, moist, hard						
					(CH) FAT CLAY, light brown and brown, moist, hard						○ 4.50
	S-3	ST	24	24							○ 4.50
10	S-4	ST	24	24							○ 4.50
	S-5	ST	24	24							○ 4.50
	END OF BORING AT 10.0 FT										
15											
20											
25											
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											












CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-11		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054507.4			EASTING: 2581576.3		STATION:		SURFACE ELEVATION: 509.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	16	16	Asphalt [4"]						○ 4.50
					FILL, sand and gravel, brown [4"]						○ 4.50
	S-2	ST	24	24	(CH) FAT CLAY, dark brown, moist, hard						○ 4.50
					(CH) FAT CLAY, light brown, moist, hard						○ 4.50
	S-3	ST	24	24							○ 4.50
S-4	ST	24	24							○ 4.50	
10	S-5	ST	24	24							○ 4.50
	END OF BORING AT 10.0 FT										
15											
20											
25											
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 10 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 10 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											




CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-12		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054506.4			EASTING: 2581026.9		STATION:		SURFACE ELEVATION: 487.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● — △		
									⊗ STANDARD PENETRATION BLOWS/FT		
									ROCK QUALITY DESIGNATION & RECOVERY		
									— RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	14	14	Asphalt [3"]		482			○ 4.50	
	S-2	ST	24	24	FILL, sand and gravel, brown [7"]						○ 4.50
	S-3	ST	24	24	FILL, FAT/LEAN CLAYS, brown, moist, hard						○ 4.50
	S-4	ST	24	24	(CH) FAT CLAY, light brown and brown, moist, hard						○ 4.50
	S-5	ST	24	24							○ 4.50
10	END OF BORING AT 10.0 FT						477				
15							472				
20							467				
25							462				
30							457				
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											







CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-13		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054510.2			EASTING: 2580515.1			STATION:		SURFACE ELEVATION: 486.00		BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	13	13	Asphalt [3"]						
					FILL, sand and gravel, brown [8"]						
	S-2	ST	24	24	(CL) LEAN CLAY, light brown and brown, moist, very stiff to hard						
	S-3	ST	24	24							
	S-4	ST	24	24							
	S-5	ST	24	24							
10					END OF BORING AT 10.0 FT		476				
15							471				
20							466				
25							461				
30							456				
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											





CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-14		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054519.9			EASTING: 2579996.2		STATION:		SURFACE ELEVATION: 504.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● — △		
									⊗ STANDARD PENETRATION BLOWS/FT		
									ROCK QUALITY DESIGNATION & RECOVERY		
									— RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	14	14	Asphalt [4"]				○ 3.00		
	S-2	ST	24	24	FILL, sand and gravel, brown [6"]				○ 3.50		
	S-3	ST	24	24	(CH) FAT CLAY, dark brown and brown, moist, very stiff		499		○ 3.75		
	S-4	ST	24	24	(CH) FAT CLAY, light brown and brown, moist, very stiff				○ 2.75		
10	S-5	ST	24	24			494		○ 3.00		
END OF BORING AT 10.0 FT											
15							489				
20							484				
25							479				
30							474				
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											






CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-15		SHEET: 1 of 1		
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC						
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										
NORTHING: 7054530.4		EASTING: 2579510.3		STATION:		SURFACE ELEVATION: 511.00		LOSS OF CIRCULATION 		
								BOTTOM OF CASING 		
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● — △	
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC	
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %	
5	S-1	ST	13	13	Asphalt [3"]					
	S-2	ST	24	24	FILL, sand and gravel, brown [8"]					
	S-3	ST	24	24	FILL, LEAN/FAT CLAYS, brown, moist, very stiff					
	S-4	ST	24	24	(CH) FAT CLAY, dark brown, moist, very stiff		506			3.50
	S-5	ST	24	24	(CH) FAT CLAY, light brown and dark brown, moist, very stiff to hard					2.75
10					END OF BORING AT 10.0 FT		501			2.50
15							496			3.75
20							491			4.50
25							486			
30							481			
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL										
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:				
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto				
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA		
☒ WL (Stabilized)		N/A								
GEOTECHNICAL BOREHOLE LOG										






CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-16		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054534.6			EASTING: 2579024.9		STATION:		SURFACE ELEVATION: 515.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	12	12	Asphalt [4"]		510			2.25	
	S-2	ST	24	24	FILL, sand and gravel, brown [8"] (CH) FAT CLAY, dark brown, moist, very stiff						
	S-3	ST	24	24							
	S-4	ST	24	24							
	10	S-5	ST	24	24	(CH) FAT CLAY, brown, moist, hard					
END OF BORING AT 10.0 FT											
15							500				
20							495				
25							490				
30							485				
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
 WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
 WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
 WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
 WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											







CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-17		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054545.9			EASTING: 2578566.0		STATION:		SURFACE ELEVATION: 518.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● — △		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	13	13	Asphalt [4"]						
	S-2	ST	24	24	FILL, sand and gravel, brown [7"]						
	S-3	ST	24	24	(CH) FAT CLAY, dark brown and brown, moist, very stiff to hard						
	S-4	ST	24	24							
	S-5	ST	24	24							
10	END OF BORING AT 10.0 FT										
15											
20											
25											
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											

CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-18		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054534.4			EASTING: 2577937.4		STATION:		SURFACE ELEVATION: 506.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	14	14	Asphalt [4"]						
	S-2	ST	24	24	FILL, sand and gravel, dark brown [6"] (CH) FAT CLAY, brown and light brown, moist, very stiff to hard						3.50
	S-3	ST	24	24			501				4.00
	S-4	ST	24	24	(CL) LEAN CLAY, light brown and brownish yellow, moist, very stiff to hard						3.50
10	S-5	ST	24	24							4.25
					END OF BORING AT 10.0 FT		496				3.75
15							491				
20							486				
25							481				
30							476				
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											

CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-19		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054522.3			EASTING: 2577377.1		STATION:		SURFACE ELEVATION: 490.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● Δ		
									⊗ STANDARD PENETRATION BLOWS/FT		
									ROCK QUALITY DESIGNATION & RECOVERY		
									— RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	16	16	Asphalt [4"]		485			○ 4.50	
	S-2	ST	24	24	FILL, sand and gravel, brown [4"]						○ 4.50
	S-3	ST	24	24	(CH) FAT CLAY, brown and light brown, moist, hard						○ 4.50
	S-4	ST	24	24							○ 4.50
	S-5	ST	24	24							○ 4.50
	10	END OF BORING AT 10.0 FT									
15						475					
						470					
						465					
						460					
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											

CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-20		SHEET: 1 of 1						
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC										
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 				
NORTHING: 7054522.6			EASTING: 2576774.3			STATION:		SURFACE ELEVATION: 478.00		BOTTOM OF CASING 				
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— △					
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC					
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %					
5	S-1	ST	12	12	Asphalt [2"]		473			○ 4.50				
	S-2	ST	24	24	FILL, sand and gravel, brown [10"]							468		○ 4.50
	S-3	ST	24	24	FILL, LEAN/FAT CLAYS, light brown and brown, moist, hard									
	S-4	ST	24	24	(CH) FAT CLAY, dark brown, moist, stiff									
	S-5	ST	24	24										
10	END OF BORING AT 10.0 FT						468			○ 2.00				
15							463			○ 1.50				
							458							
							453							
20							448							
25														
30														
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL														
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:								
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto								
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA						
☒ WL (Stabilized)		N/A												
GEOTECHNICAL BOREHOLE LOG														

CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-21		SHEET: 1 of 1						
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC										
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 				
NORTHING: 7054529.9			EASTING: 2576274.8		STATION:		SURFACE ELEVATION: 483.00			BOTTOM OF CASING 				
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ————— ● ————— △					
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC					
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %					
5	S-1	ST	14	14	Asphalt [2"]		478			○ 4.50				
	S-2	ST	24	24	FILL, sand and gravel, brown [8"]							473		○ 4.50
	S-3	ST	24	24	FILL, LEAN/FAT CLAYS, light brown and brown, moist, hard									
	S-4	ST	24	24	(CH) FAT CLAY, dark brown, moist, hard									
	10	S-5	ST	24	24									
					END OF BORING AT 10.0 FT									
15														
20														
25														
30														
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL														
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022				CAVE IN DEPTH:						
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022				HAMMER TYPE: Auto						
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA						
☒ WL (Stabilized)		N/A												
GEOTECHNICAL BOREHOLE LOG														

CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-22		SHEET: 1 of 1			
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC							
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										LOSS OF CIRCULATION 	
NORTHING: 7054536.4			EASTING: 2575652.5		STATION:		SURFACE ELEVATION: 504.00			BOTTOM OF CASING 	
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● ———— Δ		
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC		
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %		
5	S-1	ST	19	19	Asphalt [3"]						
					FILL, sand and gravel, brown [4"]						○ 2.50
	S-2	ST	24	24	FILL, LEAN/FAT CLAYS, light brown and brown, moist, very stiff						○ 3.00
					(CH) FAT CLAY, dark brown, moist, very stiff						○ 2.50
	S-3	ST	24	24							○ 2.25
10	S-4	ST	24	24	(CH) FAT CLAY, light brown and brown, moist, very stiff		499				
	S-5	ST	24	24							○ 2.25
	END OF BORING AT 10.0 FT						494				
15							489				
							484				
							479				
25							474				
30											
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL											
☒ WL (First Encountered)		Dry		BORING STARTED: Feb 09 2022		CAVE IN DEPTH:					
▼ WL (Completion)		Dry		BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto					
☒ WL (Seasonal High Water)		N/A		EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA			
☒ WL (Stabilized)		N/A									
GEOTECHNICAL BOREHOLE LOG											

CLIENT: City of Wylie, TX				PROJECT NO.: 19:8613		BORING NO.: B-23		SHEET: 1 of 1		
PROJECT NAME: Stone Road Improvements				DRILLER/CONTRACTOR: StrataBore, LLC						
SITE LOCATION: WA Allen Boulevard to Bennett Road, Wylie, Texas 75098										
NORTHING: 7054549.5		EASTING: 2575075.3		STATION:		SURFACE ELEVATION: 512.00		LOSS OF CIRCULATION 		
								BOTTOM OF CASING 		
DEPTH (FT)	SAMPLE NUMBER	SAMPLE TYPE	SAMPLE DIST. (IN)	RECOVERY (IN)	DESCRIPTION OF MATERIAL	WATER LEVELS	ELEVATION (FT)	BLOWS/6"	Plastic Limit Water Content Liquid Limit X ● ———— Δ	
									⊗ STANDARD PENETRATION BLOWS/FT ROCK QUALITY DESIGNATION & RECOVERY — RQD — REC	
									○ CALIBRATED PENETROMETER TON/SF [FINES CONTENT] %	
5	S-1	ST	18	18	Asphalt [3"]					○ 0.75
	S-2	ST	24	24	FILL, sand and gravel, brown [3"]					○ 1.25
	S-3	ST	24	24	FILL, LEAN/FAT CLAYS, brown and light brown, moist, firm to stiff					○ 1.25
	S-4	ST	24	24	(CH) FAT CLAY, dark brown, moist, stiff					○ 2.00
10	S-5	ST	24	24						○ 1.75
					END OF BORING AT 10.0 FT					
15										
20										
25										
30										
THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY LINES BETWEEN SOIL TYPES. IN-SITU THE TRANSITION MAY BE GRADUAL										
☒ WL (First Encountered) Dry					BORING STARTED: Feb 09 2022		CAVE IN DEPTH:			
▼ WL (Completion) Dry					BORING COMPLETED: Feb 09 2022		HAMMER TYPE: Auto			
☒ WL (Seasonal High Water) N/A					EQUIPMENT: Truck		LOGGED BY: StrataBore		DRILLING METHOD: CFA	
☒ WL (Stabilized) N/A										
GEOTECHNICAL BOREHOLE LOG										

APPENDIX C – Laboratory Testing

Laboratory Testing Summary

Lime/pH Series Results



ECS Southwest, LLP
Carrollton, Texas
Laboratory Testing Summary

Date: 3/2/2022

Project Number: 19:8613

Project Name: Stone Road Improvements (Wylie, TX)

Project Engineer: CT

Principal Engineer: MPB

Summary By: CT

Boring Number	Sample Number	Depth (feet)	MC ¹ (%)	Soil Type ²	Atterberg Limits ³			Percent Passing No. 200 Sieve ⁴	Dry Unit Weight ⁵ (pcf)	Compressive Strength (tsf)	One-Dimensional Swell ⁶			Soluble Sulfate ⁷ (ppm)
					LL	PL	PI				Final Moisture (%)	Surcharge (psf)	Swell (%)	
B-01	S-2	2-4	29.8	CH	70	25	45	98.3						< 3,000
	S-4	6-8	26.9											
B-02	S-1	1-2	10.1											< 3,000
	S-3	4-6	25.7	CH	74	25	49							
B-03	S-1	1-2	10.0											< 3,000
	S-3	4-6	23.4	CH	42	18	24	89.5						
B-04	S-1	1-2	20.4											< 3,000
	S-3	4-6	13.7	CH	54	21	33							
B-05	S-1	1-2	15.2											< 3,000
	S-4	6-8	22.5	CH	66	24	42							
B-06	S-1	1-2	7.9											< 3,000
	S-4	6-8	5.4	FILL	31	16	15							
B-07	S-1	1-2	17.7	CL	45	19	26							< 3,000
	S-4	6-8	17.9	CL	49	20	29							
B-08	S-1	1-2	11.7											< 3,000
	S-3	4-6	30.2	CH	73	25	48							
B-09	S-1	1-2	17.4											< 3,000
	S-3	4-6	29.1	CH	69	24	45	95.0						
B-10	S-1	1-2	17.6											< 3,000
	S-3	4-6	16.3	CH	54	21	33							

Notes: 1. ASTM D 2216, 2. ASTM D 2487, 3. ASTM D 4318, 4. ASTM D 422, 5. ASTM D 2937, 6. ASTM D4546, 7 TEX 145E, 8 ASTM D 2166

Definitions: MC: Moisture Content, Soil Type: USCS (Unified Soil Classification System), LL: Liquid Limit, PL: Plastic Limit, PI: Plasticity Index, NP: Non Plastic



Carrollton, Texas
Laboratory Testing Summary

Date: 3/2/2022

Project Number: 19:8613

Project Name: Stone Road Improvements (Wylie, TX)

Project Engineer: CT

Principal Engineer: MPB

Summary By: CT

Boring Number	Sample Number	Depth (feet)	MC ¹ (%)	Soil Type ²	Atterberg Limits ³			Percent Passing No. 200 Sieve ⁴	Dry Unit Weight ⁵ (pcf)	Compressive Strength (tsf)	One-Dimensional Swell ⁶			Soluble Sulfate ⁷ (ppm)
					LL	PL	PI				Final Moisture (%)	Surcharge (psf)	Swell (%)	
B-11	S-1	1-2	19.5	CH										< 3,000
	S-4	6-8	16.6		58	22	36							
B-12	S-1	1-2	22.3	CH										< 3,000
	S-4	6-8	20.0		58	22	36							
B-13	S-1	1-2	17.1	CL										< 3,000
	S-4	6-8	18.1		41	18	23	98.7						
B-14	S-1	1-2	40.6	CH										< 3,000
	S-3	4-6	24.8		64	23	41	96.2						
B-15	S-2	2-4	26.5	CH										< 3,000
	S-4	6-8	23.1		59	22	37							
B-16	S-1	1-2	26.1	CH										< 3,000
	S-3	4-6	25.6		67	24	43	98.7						
B-17	S-1	1-2	18.6	CH										< 3,000
	S-4	6-8	18.2		68	24	44	85.7						
B-18	S-1	1-2	19.1	CL										< 3,000
	S-3	4-6	20.7											
	S-5	8-10	22.1		47	19	28							
B-19	S-1	1-2	15.0	CH										< 3,000
	S-4	6-8	19.5		52	21	31							
B-20	S-1	1-2	18.9	FILL										< 3,000
	S-3	4-6	8.6		27	14	13	42.6						

Notes: 1. ASTM D 2216, 2. ASTM D 2487, 3. ASTM D 4318, 4. ASTM D 422, 5. ASTM D 2937, 6. ASTM D4546, 7 TEX 145E

Definitions: MC: Moisture Content, Soil Type: USCS (Unified Soil Classification System), LL: Liquid Limit, PL: Plastic Limit, PI: Plasticity Index, NP: Non Plastic

Notes: 1. ASTM D 2216, 2. ASTM D 2487, 3. ASTM D 4318, 4. ASTM D 422, 5. ASTM D 2937, 6. ASTM D4546, 7. TEX 145E

Definitions: MC: Moisture Content, Soil Type: USCS (Unified Soil Classification System), LL: Liquid Limit, PL: Plastic Limit, PI: Plasticity Index, NP: Non Plastic



ECS Southwest, LLP
Dallas, TX

Project No: 19:8613

Date : 02/17/22

Project : Stone Road Improvements (Wylie, TX)


Tested By : KM

Source : B - 1 at 1' - 2'

Sample Information: Fat Clay, dark brown (CH)

Lime pH Series Test

% of Hydrated Lime	Corrected pH	Remarks
0%	8.3	
2%	12.0	
3%	12.0	
4%	12.2	
5%	12.3	
6%	12.3	
7%	12.4	
8%	12.4	
10%	12.4	



APPENDIX D – Winpas Pavement Design Outputs

WinPAS

Pavement Thickness Design According to
1993 AASHTO Guide for Design of Pavements Structures
American Concrete Pavement Association

Rigid Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen Blvd. to Bennett Road

Rigid Pavement Design/Evaluation

PCC Thickness	7.89 inches	Load Transfer, J	3.00
Design ESALs	2,411,295	Mod. Subgrade Reaction, k	200 psi/in
Reliability	90.00 percent	Drainage Coefficient, Cd	1.00
Overall Deviation	0.39	Initial Serviceability	4.50
Modulus of Rupture	620 psi	Terminal Serviceability	2.50
Modulus of Elasticity	4,000,000 psi		

Modulus of Subgrade Reaction (k-value) Determination

Resilient Modulus of the Subgrade	0.0 psi
Resilient Modulus of the Subbase	0.0 psi
Subbase Thickness	0.00 inches
Depth to Rigid Foundation	0.00 feet
Loss of Support Value (0,1,2,3)	0.0

Modulus of Subgrade Reaction	200.00 psi/in
------------------------------	---------------

WinPAS

Pavement Thickness Design According to
1993 AASHTO Guide for Design of Pavements Structures
American Concrete Pavement Association

Rigid Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen Blvd. to Bennett Road

Rigid Pavement Design/Evaluation

PCC Thickness	7.78 inches	Load Transfer, J	3.00
Design ESALs	2,411,295	Mod. Subgrade Reaction, k	240 psi/in
Reliability	90.00 percent	Drainage Coefficient, Cd	1.00
Overall Deviation	0.39	Initial Serviceability	4.50
Modulus of Rupture	620 psi	Terminal Serviceability	2.50
Modulus of Elasticity	4,000,000 psi		

Modulus of Subgrade Reaction (k-value) Determination

Resilient Modulus of the Subgrade	0.0 psi
Resilient Modulus of the Subbase	0.0 psi
Subbase Thickness	0.00 inches
Depth to Rigid Foundation	0.00 feet
Loss of Support Value (0,1,2,3)	0.0

Modulus of Subgrade Reaction	240.00 psi/in
------------------------------	---------------

WinPAS

Pavement Thickness Design According to

1993 AASHTO Guide for Design of Pavements Structures

American Concrete Pavement Association

Flexible Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen to Bennett Road

Flexible Pavement Design/Evaluation

Structural Number	4.62	Soil Resilient Modulus	5,000.00 psi
Design ESALs	2,411,295	Initial Serviceability	4.20
Reliability	90.00 percent	Terminal Serviceability	2.50
Overall Deviation	0.45		

Layer Pavement Design/Evaluation

Layer Material	Layer Coefficient	Drainage Coefficient	Layer Thickness	Layer SN
Asphalt Cement Concrete	0.44	1.00	2.00	0.88
Asphalt Treated Agg. Base	0.41	1.00	7.00	2.87
Bitum. Treated Agg. Base	0.12	1.00	8.00	0.96
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
Σ SN				4.71

WinPAS

Pavement Thickness Design According to

1993 AASHTO Guide for Design of Pavements Structures

American Concrete Pavement Association

Flexible Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen to Bennett Road

Flexible Pavement Design/Evaluation

Structural Number	4.62	Soil Resilient Modulus	5,000.00 psi
Design ESALs	2,411,295	Initial Serviceability	4.20
Reliability	90.00 percent	Terminal Serviceability	2.50
Overall Deviation	0.45		

Layer Pavement Design/Evaluation

Layer Material	Layer Coefficient	Drainage Coefficient	Layer Thickness	Layer SN
Asphalt Cement Concrete	0.44	1.00	2.00	0.88
Asphalt Treated Agg. Base	0.41	1.00	7.00	2.87
Bitum. Treated Agg. Base	0.14	1.00	8.00	1.12
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
Σ SN				4.87

WinPAS

Pavement Thickness Design According to

1993 AASHTO Guide for Design of Pavements Structures

American Concrete Pavement Association

Flexible Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen to Bennett Road

Flexible Pavement Design/Evaluation

Structural Number	4.62	Soil Resilient Modulus	5,000.00 psi
Design ESALs	2,411,295	Initial Serviceability	4.20
Reliability	90.00 percent	Terminal Serviceability	2.50
Overall Deviation	0.45		

Layer Pavement Design/Evaluation

Layer Material	Layer Coefficient	Drainage Coefficient	Layer Thickness	Layer SN
Asphalt Cement Concrete	0.44	1.00	2.00	0.88
Asphalt Treated Agg. Base	0.41	1.00	7.00	2.87
Bitum. Treated Agg. Base	0.15	1.00	8.00	1.20
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
Σ SN				4.95

WinPAS

Pavement Thickness Design According to
1993 AASHTO Guide for Design of Pavements Structures
American Concrete Pavement Association

Rigid Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen Blvd. to Bennett Road

Rigid Pavement Design/Evaluation

PCC Thickness	8.72 inches	Load Transfer, J	3.00
Design ESALs	4,352,719	Mod. Subgrade Reaction, k	200 psi/in
Reliability	90.00 percent	Drainage Coefficient, Cd	1.00
Overall Deviation	0.39	Initial Serviceability	4.50
Modulus of Rupture	620 psi	Terminal Serviceability	2.50
Modulus of Elasticity	4,000,000 psi		

Modulus of Subgrade Reaction (k-value) Determination

Resilient Modulus of the Subgrade	0.0 psi
Resilient Modulus of the Subbase	0.0 psi
Subbase Thickness	0.00 inches
Depth to Rigid Foundation	0.00 feet
Loss of Support Value (0,1,2,3)	0.0

Modulus of Subgrade Reaction	200.00 psi/in
------------------------------	---------------

WinPAS

Pavement Thickness Design According to
1993 AASHTO Guide for Design of Pavements Structures
American Concrete Pavement Association

Rigid Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen Blvd. to Bennett Road

Rigid Pavement Design/Evaluation

PCC Thickness	8.62 inches	Load Transfer, J	3.00
Design ESALs	4,352,719	Mod. Subgrade Reaction, k	240 psi/in
Reliability	90.00 percent	Drainage Coefficient, Cd	1.00
Overall Deviation	0.39	Initial Serviceability	4.50
Modulus of Rupture	620 psi	Terminal Serviceability	2.50
Modulus of Elasticity	4,000,000 psi		

Modulus of Subgrade Reaction (k-value) Determination

Resilient Modulus of the Subgrade	0.0 psi
Resilient Modulus of the Subbase	0.0 psi
Subbase Thickness	0.00 inches
Depth to Rigid Foundation	0.00 feet
Loss of Support Value (0,1,2,3)	0.0

Modulus of Subgrade Reaction	240.00 psi/in
------------------------------	---------------

WinPAS

Pavement Thickness Design According to

1993 AASHTO Guide for Design of Pavements Structures

American Concrete Pavement Association

Flexible Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen to Bennett Road

Flexible Pavement Design/Evaluation

Structural Number	5.04	Soil Resilient Modulus	5,000.00 psi
Design ESALs	4,352,719	Initial Serviceability	4.20
Reliability	90.00 percent	Terminal Serviceability	2.50
Overall Deviation	0.45		

Layer Pavement Design/Evaluation

Layer Material	Layer Coefficient	Drainage Coefficient	Layer Thickness	Layer SN
Asphalt Cement Concrete	0.44	1.00	2.00	0.88
Asphalt Treated Agg. Base	0.41	1.00	8.00	3.28
Bitum. Treated Agg. Base	0.12	1.00	8.00	0.96
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
			Σ SN	5.12

WinPAS

Pavement Thickness Design According to

1993 AASHTO Guide for Design of Pavements Structures

American Concrete Pavement Association

Flexible Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen to Bennett Road

Flexible Pavement Design/Evaluation

Structural Number	5.04	Soil Resilient Modulus	5,000.00 psi
Design ESALs	4,352,719	Initial Serviceability	4.20
Reliability	90.00 percent	Terminal Serviceability	2.50
Overall Deviation	0.45		

Layer Pavement Design/Evaluation

Layer Material	Layer Coefficient	Drainage Coefficient	Layer Thickness	Layer SN
Asphalt Cement Concrete	0.44	1.00	2.00	0.88
Asphalt Treated Agg. Base	0.41	1.00	8.00	3.28
Bitum. Treated Agg. Base	0.14	1.00	8.00	1.12
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
Σ SN				5.28

WinPAS

Pavement Thickness Design According to

1993 AASHTO Guide for Design of Pavements Structures

American Concrete Pavement Association

Flexible Design Inputs

Agency: City of Wylie
Company: ECS
Contractor:
Project Description: Stone Road Improvements
Location: From WA Allen to Bennett Road

Flexible Pavement Design/Evaluation

Structural Number	5.04	Soil Resilient Modulus	5,000.00 psi
Design ESALs	4,352,719	Initial Serviceability	4.20
Reliability	90.00 percent	Terminal Serviceability	2.50
Overall Deviation	0.45		

Layer Pavement Design/Evaluation

Layer Material	Layer Coefficient	Drainage Coefficient	Layer Thickness	Layer SN
Asphalt Cement Concrete	0.44	1.00	2.00	0.88
Asphalt Treated Agg. Base	0.41	1.00	8.00	3.28
Bitum. Treated Agg. Base	0.15	1.00	8.00	1.20
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
	0.00	0.00	0.00	0.00
Σ SN				5.36